


Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control


Slide 1




Slide 2



Slide 3



Slide 4



Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 5



Slide 6



Slide 7



Slide 8

**Construction Site Runoff:
Impacts to STPs**

- Filling-in of permanent stormwater ponds
- Clogging of infiltration devices
- Smothering of swales and buffers

Copyright Center for Watershed Protection, 2001

Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control


Slide 9



Slide 10



Slide 11



Slide 12

ESC Reality

- Recent surveys reveal:
 - 16% of ESC practices prescribed in plans are never installed
 - 16% not installed correctly and fail to perform
 - 18% of practices fail due to lack of maintenance
 - Only 50% of ESC installation budget actually spent
 - Local governments spend 3 to 6 times more effort on plan review than inspection

Sources: Paterson, 1994 and Paterson et al., 1993

Copyright Center for Watershed Protection, 2001

Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 13

Practice	Installed	Installed Properly	Adequately Maintained
Silt Fence	67%	58%	34%
Sediment Trap	86%	86%	58%
Anti-Tracking Pad	89%	89%	67%

Source: Paterson, 1994
Copyright Center for Watershed Protection, 2001

Slide 14




Slide 15

- ### 10 Elements of an Effective ESC Plan
- Plan to minimize area to be disturbed, eliminate unnecessary clearing and grading.
 - Protect waterways and stabilize drainageways.
 - Phase construction to limit duration of soil exposure.
 - Stabilize exposed soils immediately.
 - Avoid grading on steep slopes and cuts, protect them if avoidance impossible.
- Copyright Center for Watershed Protection, 2001


Slide 16

- ### 10 Elements of an Effective ESC Plan
- Install perimeter controls to filter sediments including Silt Fences, Stabilized Construction Entrances, flow diversions, etc.
 - Employ advance sediment settling devices including Sediment Traps and Basins.
 - Certify contractors on ESC plan implementation.
 - Adjust ESC plan at construction site to adapt to field conditions.
 - Assess ESC practices routinely and after storms.
- Copyright Center for Watershed Protection, 2001

Slide 17



Slide 18



Slide 19

1. Minimize Clearing

- Objectives:
 - Prevent erosion by never clearing/grading portions of the work site
 - Protect sensitive areas from grading
 - Preserve natural vegetation/forest
- Techniques:
 - Site fingerprinting
 - Restrict clearing to minimum needed
 - Use of "tree-save"

Copyright Center for Watershed Protection, 2001

Slide 20

Clearing Restrictions

Areas never cleared or activities sharply restricted:

- Stream buffers
- Forest conservation areas
- Wetlands, springs and seeps
- Steep slopes, highly erodible soils
- Stormwater infiltration areas

Copyright Center for Watershed Protection, 2001

Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 21



Slide 22




Slide 23

Site Fingerprinting

- Use alternative grading practices
- Reduce grading to building pad, roadway, utilities and septic areas
- Can reduce grading and ESC costs by as much as \$5,000/acre


Copyright Center for Watershed Protection, 2001

Slide 24



Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control


Slide 25



Slide 26



Slide 27



Slide 28

Minimizing Clearing Quick Facts

<u>Approximate Costs</u>	<ul style="list-style-type: none">No Additional Construction Costs
<u>Effectiveness</u>	<ul style="list-style-type: none">Erosion/ Sediment Control HighLong-term Pollutant Reduction . . . HighHabitat/ Stream Protection High
<u>Ease of Application</u>	<ul style="list-style-type: none">Installation AverageMaintenance Easy
<u>Limitations</u>	<ul style="list-style-type: none">Where zoning prevents alternative site designsSites with excessively steep slopesSmall sites for some techniques

Copyright Center for Watershed Protection, 2001

Slide 29



Slide 30

2a. Protect Waterways

Objective:

- Protect streams and waterways from sedimentation during construction

Techniques:

- Restrict clearing within 25 feet of waterway (Integrate with existing buffer regulations).
- Special crossings required if work is planned across the waterway
- Permit needed to work in stream

Copyright Center for Watershed Protection, 2001

Slide 31



Slide 32

Protecting Waterways: Vegetated Buffers
Quick Facts

Approximate Costs

- No Additional Construction Costs

Effectiveness

- Erosion/ Sediment ControlModerate
- Long-term Pollutant ReductionModerate
- Habitat/ Stream ProtectionHigh

Ease of Application

- InstallationAverage
- MaintenanceEasy

Limitations

- Steep slopes or slopes w/ rills limit filtering capacity
- Sites with limited space

Copyright Center for Watershed Protection, 2001

Slide 33



Slide 34

2b. Stabilize Drainageways

Objectives:

- Prevent erosion in vulnerable drainageways
- Promote infiltration

Techniques:

- Checkdams
- Sod
- Erosion control blankets or mats
- Rip rap (use sparingly)

Copyright Center for Watershed Protection, 2001

Slide 35

Check Dams

- Reduce flow velocities in channels
- Provide limited sediment trapping
- Require spacing so that the bottom of each dam lines up with the top of the next one
- Ineffective on slopes > 10%

Copyright Center for Watershed Protection, 2001

Slide 36



Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 37



Slide 38

Swales

- Often used in conjunction with earth dikes.
- Can be used to divert clean water around a site or convey runoff to ESC device.
- Keeps flow velocity non-erosive if designed carefully.

Copyright Center for Watershed Protection, 2001

Slide 39



Slide 40



Slide 41

Stabilizing Drainageways
Quick Facts

Approximate Costs • \$5 to \$6 / lf (depending on depth of cut)

Effectiveness

- Erosion/ Sediment ControlHigh
- Long-term Pollutant Reduction ...Low
- Habitat/ Stream ProtectionLow

Ease of Application


- Installation Moderate
- Maintenance Difficult

Limitations

- Very small sites

Copyright Center for Watershed Protection, 2001

Slide 42



Slide 43

3. Phase Construction

Objective:

- Reduce soil erosion by minimizing the amount of time and area of exposed soil
- Grade only portion of site where construction is active ("just-in-time" grading)
- Should not be confused with construction sequence

Copyright Center for Watershed Protection, 2001

Slide 44

3. Phase Construction

- Can reduce erosion by 40% over traditional mass grading
- Requires careful planning
 - "Cut" soil matches "fill" requirement
 - Provisions for temporary stockpiling and construction access
 - Phases should correspond to existing and future drainage boundaries where possible

Copyright Center for Watershed Protection, 2001

Slide 45

Phase Construction
Quick Facts

Approximate Costs

- No Additional Construction Costs

Effectiveness

- Erosion/ Sediment Control High
- Long-term Pollutant Reduction Low
- Habitat/ Stream Protection Low

Ease of Application


- Installation Difficult
- Maintenance Easy

Limitations

- Where it is impossible to balance earthwork by phase
- Where alternative access is not feasible for both construction equipment and occupants
- Small sites

Copyright Center for Watershed Protection, 2001

Slide 46



Slide 47

4. Rapid Soil Stabilization

Objective:

- Reduce soil erosion by minimizing the amount of time soil is exposed

Techniques:

- Hydroseeding
- Mulching
- Erosion control blankets/mats

Copyright Center for Watershed Protection, 2001


Slide 48

4. Rapid Soil Stabilization

- Establish grass or mulch cover within two weeks of soil exposure
- Permanently stabilize disturbed soils at conclusion of each phase of construction
- Contingency line item for replacing cover that does not take
- Require heavy mulching after the growing season

Copyright Center for Watershed Protection, 2001

Slide 49



Slide 50

Seeding

- Cost: \$0.10/ square yard
- Nearly 100% effective for established grass, 80% for sparse cover
- Best in combination with a mulch or erosion control blanket cover
- Restricted outside the growing season

Copyright Center for Watershed Protection, 2001

Slide 51



Slide 52

Straw Mulch

- Cost: \$0.35 per square yard
- Can be up to 95% effective
- Must be anchored to the soil surface
- Best if used in combination with seeding
- Best for slopes flatter than 3:1
- Thick mulch (4 tons/acre) can be used as a winter cover

Copyright Center for Watershed Protection, 2001

Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 53



Slide 54



Slide 55

Fiber Mulch

- Cost: \$0.25 per square yard
- Can be up to 90% effective
- Typically used in combination with hydroseeding
- Can apply with seeding in one step
- Not appropriate for steep slopes or long time periods

Copyright Center for Watershed Protection, 2001

Slide 56



Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 57

Blankets

- Cost: \$1.50 per square yard.
- Up to 90% effective.
- Best when used with seeding.
- Effective for steep slopes or channels.
- Two Types: Temporary and Permanent
 - Temporary erosion control blankets
 - Permanent turf reinforcement matting

Copyright Center for Watershed Protection, 2001

Slide 58

Plastic Sheeting

- Cost: \$0.10 per square yard
- Only effective on areas less than ½ acre
- Good for short term cover
- Plastic edges should be weighed down to prevent displacement by wind
- Example use: stockpiles

Copyright Center for Watershed Protection, 2001

Slide 59

Comparison of Erosion Control Materials

Material Types	Cost (\$/sq yard)	Uses	Limitations and Disadvantages
Seeding	0.10	As a permanent or temporary erosion control, established grass is the most effective control	Climate (dry or cold weather), infertile soils (needs fertilizer, lime, etc), needs some other surficial cover on most slopes
Straw mulch	0.20 – 0.35	As a protection for seeds, alone as a temporary erosion control	Slopes steeper than 20% for straw mulch, can interfere with grading operations, straw or hay mulch needs to be secured to the soil surface

Copyright Center for Watershed Protection, 2001

Slide 60


Comparison of Erosion Control Materials

Material Types	Cost (\$/sq yd)	Uses	Limitations and Disadvantages
Blankets	1.00 – 2.00	Useful on steeper slopes than mulches, protects seed and prevents erosion	Installation is more complicated and time-consuming than for mulches
Plastic Sheeting	0.05 – 0.15	Temporary control for very small areas	Does not allow infiltration, edges must be weighed down, unsuitable for areas greater than 2,000 sq feet
Sodding	1.80	Use of sod to provide vegetative cover, can be used in low-flow channels	Drought or poor soils can impede growth, most expensive

Copyright Center for Watershed Protection, 2001

Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 61



Slide 62

5. Protect Steep Slopes

Objective:

- Reduce erosion from steep (>3:1) slopes

Techniques:

- Limit clearing of steep slopes
- Divert upland flow using earthen dike, temporary swale or pipe slope drain
- Use upslope line of silt fence
- Erosion control blankets with seed
- Sodding

Copyright Center for Watershed Protection, 2001

Slide 63



Slide 64

Pipe Slope Drain

- Cost: \$5-6 per linear foot
- Used to convey runoff past steep slopes.
- Limited to <3 acres for each 24" pipe.
- Effective in combination with a sediment trap or basin.
- Requires stable outlet.

Copyright Center for Watershed Protection, 2001

Slide 65




Slide 66

Protecting Steep Slopes
Quick Facts

<u>Approximate Costs</u>	• \$5-6 / lf
<u>Effectiveness</u>	• Erosion/ Sediment ControlMod • Long-term Pollutant ReductionLow • Habitat/ Stream ProtectionLow
<u>Ease of Application</u>	• Installation Average • Maintenance Average
<u>Limitations</u>	• Very small sites • Sites with no room for basin or trap below disturbed slope

Copyright Center for Watershed Protection, 2001

Slide 67



Slide 68

6. Perimeter Controls

Objective:

- Retain or filter runoff before it leaves the site.

Techniques:

- Earth dikes or diversions.
- Silt fences.
- Stabilized construction entrances.

Copyright Center for Watershed Protection, 2001

Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 69

Silt Fences

- Popular practice due to low cost: \$3.50 per linear foot.
- Between 65% and 85% TSS removal in field studies.
- Real life performance (recent North Carolina field study).
 - Only 67% of silt fences on the ESC plan were installed.
 - Only 58% were installed correctly.
 - Only 34% were adequately maintained.
- Ongoing maintenance is typically required that can cost as much as original installation over project life.
- Challenges include proper placement and construction.

Copyright Center for Watershed Protection, 2001

Slide 70

Improving Silt Fences

- Improvements to silt fences
 - Strengthen geotextiles
 - Use longer, thicker poles for support
 - Include a 10 foot grass buffer
 - Practice effective erosion control to reduce sediment buildup

Copyright Center for Watershed Protection, 2001

Slide 71

Super Silt Fence


The diagram illustrates a Super Silt Fence with a cross-section of 30" high and 30" wide. It features a 2" diameter galvanized steel pipe for support. The fence is made of 2" x 2" geotextile fabric. A 10' x 10' layer of filter cloth is attached to the bottom. The diagram also shows a chain-link fence and a 2" x 2" geotextile fabric. The flow direction is indicated by an arrow labeled 'FLOW'.

Copyright Center for Watershed Protection, 2001

Slide 72



Slide 73




Slide 74

Perimeter Control: Silt Fence Quick Facts

<u>Approximate Costs</u>	<ul style="list-style-type: none"> • \$2.50 - \$3.50 / lf
<u>Effectiveness</u>	<ul style="list-style-type: none"> • Erosion/ Sediment Control Moderate • Long-term Pollutant Reduction Low • Habitat/ Stream Protection Low
<u>Ease of Application</u>	<ul style="list-style-type: none"> • Installation Difficult • Maintenance Difficult
<u>Limitations</u>	<ul style="list-style-type: none"> • Steep slopes or channels • Construction traffic

Copyright Center for Watershed Protection, 2001

Slide 75



Slide 76

7. Employ Advance Settling Devices

<u>Objective:</u>	<ul style="list-style-type: none"> • Trap sediment in runoff before it leaves the site
<u>Techniques:</u>	<ul style="list-style-type: none"> • Sediment traps • Sediment basins

Copyright Center for Watershed Protection, 2001

Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 77

Settling Devices

- TSS removal varies between 50% to 90%
- Trapping limited by
 - Difficulty in settling fine-grained soils
 - Simplistic design of existing basins

Copyright Center for Watershed Protection, 2001

Slide 78




Slide 79

Ways to Improve Trapping

- Increase storage volume / residence time.
- Perforated risers.
- Use of baffles, skimmers, other devices.
- Multiple cell construction.
- Gentler side slopes and inflow protection.

Copyright Center for Watershed Protection, 2001

Slide 80




Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control


Slide 81



Slide 82



Slide 83



Slide 84



Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 85



Slide 86

Employing Advanced Settling Devices Quick Facts

<u>Approximate Costs</u>	<ul style="list-style-type: none">• \$15/ cy (for earthwork)
<u>Effectiveness</u>	<ul style="list-style-type: none">• Erosion/ Sediment Control Moderate• Long-term Pollutant Reduction . . . High• Habitat/ Stream Protection Moderate
<u>Ease of Application</u>	<ul style="list-style-type: none">• Installation Average• Maintenance Average
<u>Limitations</u>	<ul style="list-style-type: none">• Small sites especially for basins• Extreme weather conditions• Fine Soils

Copyright Center for Watershed Protection, 2001

Slide 87



Slide 88

8. Certified Contractors Implement Plan

Objectives:

- Improve performance of ESC through proper installation and maintenance.
- Involve contractors in the ESC process.

Techniques:

- State mandated and sponsored ESC training.
- Applies to contractors responsible for installation and maintenance of ESC devices.
- Pre-construction meetings.

Copyright Center for Watershed Protection, 2001

Slide 89



Slide 90

Maintenance of ESC Practices

- Cost of ESC maintenance and repair should be included in construction plan
- Designate on-site contractor for maintenance
- Set minimum maintenance and periodic self inspection schedule


Copyright Center for Watershed Protection, 2001

Slide 91

**Maintenance Costs
(% of Installation Costs)**

Practice	Annual maintenance as % of installation
Seeding	20%
Mulching	2%
Silt Fence	100%
Sediment Trap	20%
Sediment Basin	25%
Inlet Protection	60%

Slide 92



Keeping Soil in Its Place: A Presentation on Erosion and Sediment Control

Slide 93

9. Adjust ESC Plan for Field Conditions

Objectives:

- Keep plans up to date with changing field conditions
- Modify poorly-designed plans

Stage	Basis of Plan Change
Pre-construction meeting	Plan impractical from contractors' standpoint, site visit confirms plan unsuitability
After clearing/grading and sediment controls installed	"As built" grading or sediment controls different from original plan

Copyright Center for Watershed Protection, 2001

Slide 94



Slide 95



Slide 96



Slide 97

10. Assess ESC Practices After Storms

Objectives:

- Repair the damage of storm events
- Prepare ESC practices for the next storm

Techniques:

- Modify ESC plans
- Reinforce or cleanout existing practices

Copyright Center for Watershed Protection, 2001

Slide 98



Slide 99

ESC Planning at the Local Level

- Most ESC programs are mandated by State laws or are in place to conform with Federal permits.
- 90% are implemented by local agencies.
- Minimal funding is available.

Copyright Center for Watershed Protection, 2001

Slide 100

Management Tips for Better Local ESC Planning

- Have a committed local leadership
- Re-deploy existing staff from office to field or training room
- Cross train local development review and inspection staff
- Submit erosion prevention elements for early planning review
- Prioritize inspection based on erosion risk
- Require designer to certify initial installation of ESC practices
- Invest in contractor certification and private inspector programs

Copyright Center for Watershed Protection, 2001

Slide 101

**Management Tips for Better
Local ESC Planning**

- Use public-sector construction projects to demonstrate effective ESC controls
- Enlist the talents of developers and engineering consultants
- "Reinvent" the local ESC manual

Copyright Center for Watershed Protection, 2007

Slide 102