

IV. Storage of Highly Volatile Organic Compounds**IV.A. Highly volatile organic compounds shall be stored:**

IV.A.1. In a pressure tank which is at all times capable of maintaining working pressures sufficient to prevent vapor loss to the ambient air; or

IV.A.2. With methods and/or equipment approved by the Division in writing pursuant to the request of the person owning or operating the storage facility.

IV.B. Vapor loss shall be determined visually, by presence of frost or condensation at the point of leakage, or using a portable hydrocarbon analyzer. When an analyzer is used, vapor loss means a VOC concentration exceeding 10,000 ppm and testing and monitoring procedures shall be conducted as in Section VIII.C.3.

V. Disposal of Volatile Organic Compounds

V.A. No person shall dispose of volatile organic compounds by evaporation or spillage unless RACT is utilized.

V.B. No owner or operator of a bulk gasoline terminal, bulk gasoline plant, or gasoline dispensing facility as defined in Section VI.C.2., VI.C.3. and XV.A.3., shall permit gasoline to be intentionally spilled, discarded in sewers, stored in open containers, or disposed of in any other manner that would result in evaporation.

VI. Storage and Transfer of Petroleum Liquid**VI.A. General Requirements**

VI.A.1. No person shall build, install, or permit the building or installation of any rotating pump or compressor handling any type of petroleum liquid unless said pump or compressor is equipped with mechanical seals or other equipment of equal efficiency. If reciprocating-type pumps and compressors are used, they shall be equipped with packing glands properly installed, in good working order, and properly maintained so that no detectable emissions occur from the drain recovery systems.

VI.A.2. Definitions

For the purpose of this section, the following definitions apply:

VI.A.2.a. Repealed.

VI.A.2.b. "Crude Oil" means a naturally occurring mixture which consists of hydrocarbons, sulfur, nitrogen or oxygen derivatives of hydrocarbons, and which is a liquid at standard conditions.

VI.A.2.c. "Custody Transfer" means the transfer of produced crude oil and/or condensate, after processing and/or treating in the producing operations, from storage tanks or automatic transfer facilities to pipelines or any other forms of transportation.

VI.A.2.d. "EFR Tank" means a storage vessel having an external floating roof.

VI.A.2.e. "External Floating Roof" means a storage vessel cover in an open top tank consisting of a double deck or pontoon single deck which rests upon