

**R307. Environmental Quality, Air Quality.**

**R307-301. Utah and Weber Counties: Oxygenated Gasoline Program.**

**R307-301-3. Average Oxygen Content Standard.**

(1) All gasoline sold or dispensed during the control period, for use in each control area, by each CAR or blender CAR as defined in R307-301-1, shall be blended for each averaging period to contain an average oxygen content of not less than 2.7% oxygen by weight.

(2) The averaging period over which all gasoline sold or dispensed in the control area is to be averaged shall be equal to the control period.

(3) All gasoline, both leaded and unleaded, shall be blended in compliance with 40 CFR Part 79 (1991) - Registration of Fuels and Fuel Additives and 40 CFR Part 80 (1991) - Regulation of Fuels and Fuel Additives.

(4) Any gasoline blended under 42 U.S.C. 7545(f)(1) dealing with substantially similar fuels must be blended in compliance with the criteria specified in the substantially similar ruling. Any extra volume of oxygenate or oxygenates added to gasoline blended under a substantially similar ruling as provided for under 42 U.S.C. 7545(f)(1) in excess of the criteria specified in 42 U.S.C. 7545(f)(1) may not be included in the compliance calculations specified in R307-301-5(2) and (3).

(5) Any gasoline blended under a waiver granted by the Environmental Protection Agency under the provisions of 42 U.S.C. 7545(f)(4) must be blended in compliance with the criteria specified in the appropriate waiver. Gasoline blends waived to oxygen content above 2.7% oxygen by weight are not permitted a blending allowance for blending tolerance purposes. Any extra volume of oxygenate in excess of the criteria specified in the appropriate waiver may not be included in the compliance calculations specified in R307-301-5(2) or (3).

(6) Oxygen content shall be determined in accordance with R307-301-4.

**KEY: air pollution control, motor vehicles, gasoline, petroleum**

September 10, 2001

19-2-101

Notice of Continuation June 9, 1997

19-2-104