



South Coast Air Quality Management District

21865 Copley Drive, Diamond Bar, CA 91765-4178
(909) 396-2000 • www.aqmd.gov

June 6, 2008

Gerardo Rios
Chief – Permits Office
U.S. EPA — Region IX — Air-3
75 Hawthorne Street
San Francisco, CA 94105

**Subject: Title V Permit to Operate Revision
Disneyland – ID#800189**

Dear Mr. Rios:

Please find the attached revised version of the Disneyland (ID#800189, SIC 7900) Facility Permit. This revision was previously sent to EPA for your review on April 16, 2008. The revised Facility Permit reflects the inclusion of the following equipment approved for Permit to Operate:

<u>Application No.</u>	<u>Equipment</u>	<u>Device No.</u>	<u>Process/System</u>
478405	Emergency, ICE	D259	1, 1
478418	Pressure Washer	D255	2
478419	Pressure Washer	D256	2
478420	Pressure Washer	D257	2
478421	Pressure Washer	D258	2
478422	Emergency, ICE	D1	1, 1
478423	Emergency, ICE	D2	1, 1
478424	Emergency, ICE	D4	1, 1
478425	Emergency, ICE	D7	1, 1
478426	Emergency, ICE	D8	1, 1
478427	Emergency, ICE	D153	1, 1
478428	Emergency, ICE	D160	1, 1
478429	Emergency, ICE	D168	1, 1
478430	Emergency, ICE	D12	1, 1
478431	Emergency, ICE	D15	1, 1
478432	Emergency, ICE	D95	1, 1
478433	Emergency, ICE	D99	1, 1

Cleaning the air that we breathe...

The following equipment has been issued a Permit to Construct:

<u>Application No.</u>	<u>Equipment</u>	<u>Device No.</u>	<u>Process/System</u>
478416	Heater	D260	2
478417	Heater	D261	2

Insert the enclosed Sections D, K and H into the Facility Permit and discard the earlier versions. Questions concerning changes to your permit should be directed to Mr. Roy Olivares at (909)396-2208.

Sincerely,

Michael D. Mills

Michael D. Mills, P.E.
Senior Manager
General Commercial and Energy Team
Engineering and Compliance

Attachments



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	0	08/03/2007
B	RECLAIM Annual Emission Allocation	1	01/01/2008
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	2	06/06/2008
E	Administrative Conditions	0	08/03/2007
F	RECLAIM Monitoring and Source Testing Requirements	0	08/03/2007
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	0	08/03/2007
H	Permit To Construct and Temporary Permit to Operate	1	06/06/2008
I	Compliance Plans & Schedules	0	08/03/2007
J	Air Toxics	0	08/03/2007
K	Title V Administration	1	06/06/2008
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	0	08/03/2007
B	Rule Emission Limits	1	06/06/2008



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
System 1 : EMERGENCY					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 133DN, WITH TURBOCHARGER, 210 HP A/N: 478422	D1		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.11, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 64DT, WITH TURBOCHARGER, 137 HP A/N: 478423	D2		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.11, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 133DN, 210 HP A/N: 180124	D3		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, D12.1, E71.7, H23.6
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 133DT, WITH TURBOCHARGER, 290 HP A/N: 478424	D4		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.11, D12.1, E71.4, E71.7, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, FORD, MODEL 4DEF4XR1601B, 52 HP A/N: 180129	D5		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, D12.1, E71.7, H23.6
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 64DT, WITH TURBOCHARGER, 137 HP A/N: 478425	D7		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.11, C177.1, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16

* (1)(1A)(1B) Denotes RECLAIM emission factor	(2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit	(4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit	(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit	(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits	(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 64DTA, WITH AFTERCOOLER, TURBOCHARGER, 163 HP A/N: 478426	D8		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.11, C177.1, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 133DTA, WITH AFTERCOOLER, TURBOCHARGER, 368 HP A/N: 195818	D10		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.2, C177.1, D12.1, E71.7, H23.6
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 6.4DTA, WITH AFTERCOOLER, TURBOCHARGER, 160 HP A/N: 478430	D12		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.11, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL 3208TA, WITH AFTERCOOLER, TURBOCHARGER, 299 HP A/N: 478431	D15		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.20, C177.1, D12.1, E71.6, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, DETROIT DIESEL, MODEL 40-8.7LT, WITH TURBOCHARGER, 205 BHP A/N: 478432	D95		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.11, C177.1, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL 3508 DITA, WITH AFTERCOOLER, TURBOCHARGER, 1337 BHP A/N: 303611	D98		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.3, C177.1, D12.1, E71.6, H23.6
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, JOHN DEERE, MODEL 6059T, WITH A TURBOCHARGER, 166 BHP A/N: 478433	D99		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.20, C177.1, D12.1, E71.6, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, GENERAC 7.4GN, MODEL CG070, WITH CATALYTIC REDUCTION, 116 HP A/N: 334912	D101		NOX: PROCESS UNIT**	NOX: 37.9 LBS/MMSCF NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-5-2003 RULE 2012,5-6-2005] ; PM: (9) [RULE 404,2-7-1986]	C1.1, D12.1, H23.12
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344925	D115		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995]	C1.1, D12.1, H23.12, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				<p><i>RULE 2012, 4-9-1999</i> ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]</p> <p>ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]</p>	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344926	D116		NOX: PROCESS UNIT**	<p>CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 12-7-1995</p> <p><i>RULE 2012, 4-9-1999</i> ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]</p> <p>ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999]</p>	C1.1, D12.1, H23.12, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344927	D117		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, D12.1, H23.12
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344928	D118		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, D12.1, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344929	D119		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999] ; PM: (9) (RULE 404,2- 7-1986) ROG: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999]	C1.1, D12.1, H23.12, K67.4
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3306SITA, NATURAL GAS, RICH BURN, WITH TURBOCHARGER AND AFTERCOOLER, WITH CATALYTIC REDUCTION, 194 BHP A/N: 344913	D120		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995	C1.1, D12.1, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				RULE 2012, 4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005, 10-15-1993; RULE 2005, 4-9- 1999] ; PM: (9) [RULE 404, 2- 7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3304SINA, NATURAL GAS, WITH CATALYTIC REDUCTION, 95 BHP A/N: 344914	D121		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 12-7-1995 RULE 2012, 4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005, 10-15-1993; RULE 2005, 4-9- 1999] ; PM: (9) [RULE 404, 2- 7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996]	C1.1, D12.1, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor	(2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit	(4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit	(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit	(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits	(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3516SITA, NATURAL GAS, LEAN BURN, WITH TURBOCHARGER AND AFTERCOOLER, 1482 BHP A/N: 344899	D122		NOX: PROCESS UNIT**	CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, D12.1, H23.12
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344933	D123		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, D12.1, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor
(2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344934	D124		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999] ; PM: (9) [RULE 404,2- 7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, D12.1, H23.12, K67.4
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344935	D125		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995	C1.1, D12.1, H23.12, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				<p><i>RULE 2012, 4-9-1999</i> ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005, 10-15-1993; RULE 2005, 4-9-1999] ; PM: (9) [RULE 404, 2-7-1986]</p> <p>ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996]</p>	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344936	D126		NOX: PROCESS UNIT**	<p>CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 12-7-1995</p> <p><i>RULE 2012, 4-9-1999</i> ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005, 10-15-1993; RULE 2005, 4-9-1999] ; PM: (9) [RULE 404, 2-7-1986]</p> <p>ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996]</p>	C1.1, D12.1, H23.12, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344937	D127		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 405,2-7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, D12.1, H23.12, K67.4
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344938	D128		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]	C1.1, D12.1, H23.12, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS,etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device:



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344939	D129		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999] ; PM: (9) [RULE 404,2- 7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, D12.1, H23.12, K67.4
INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, GASOLINE, FORD, MODEL LSG-875R-6003-C, WITH CATALYTIC REDUCTION, 193 HP A/N: 359091	D131		NOX: PROCESS UNIT**	CO: 0.6 GRAM/BHP-HR GASOLINE (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 102 LBS/1000 GAL GASOLINE (1) [RULE 2012,12- 7-1995;RULE 2012,4-9-1999]	C1.1, D12.1, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				NOX: 0.15 GRAM/BHP-HR GASOLINE (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ; ROG: 0.15 GRAM/BHP-HR GASOLINE (4) [RULE 1303(a)(1)-BACT,5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 7.5 DTA, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 184 BHP A/N: 362182	D133		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 264 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, D12.1, E71.6, E202.2, H23.6, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5)(5A)(5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2)(2A)(2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
 (10) See Section J for NESHAP/MACT requirements
 ** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CUMMINS, MODEL 800 GTA 500 G3, NATURAL GAS, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 1334 BHP A/N: 360419	D134		NOX: PROCESS UNIT**	CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, D12.1, E202.3, H23.12, K67.4
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 7.5 DTA, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 184 BHP A/N: 367064	D146		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 264 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, D12.1, E71.6, E202.2, H23.6, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor
(2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL 3303 ATACC, WITH AFTERCOOLER, TURBOCHARGER, 377 BHP A/N: 378803	D149		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] ; NOX: 302 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] ; PM: (9) [RULE 404,2-7-1986] PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] ; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996 RULE 1303(a)(1)-BACT,10-20-2000]	C1.1, C1.11, D12.1, E71.1, E71.4, H23.6, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, PARADISE PIER HOTEL, DIESEL FUEL, CUMMINS, MODEL N-855-F, 6 CYLINDERS, FOUR CYCLE, NATURALLY ASPIRATED, SERIAL NO. 1815303, 240 HP A/N: 311603	D152		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.22, D12.1, H23.6
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, PARADISE PIER HOTEL, DIESEL FUEL, CATERPILLAR, MODEL 3508DI.8 CYLINDERS, INTERCOOLED, SERIAL NO. 28Z00641, WITH TURBOCHARGER, 712 HP A/N: 478427	D153		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.20, C177.1, D12.1, E71.6, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, CUMMINS, MODEL 4BT3.9-G4, 4 CYLINDERS, SERIAL NO. 45901859, WITH TURBOCHARGER, 102 HP A/N: 363159	D159		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.8, D12.1, E71.6, H23.6, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, CUMMINS, MODEL 6CT8.3G, 6 CYLINDERS, FOUR CYCLE, WITH TURBOCHARGER, 207 HP A/N: 478428	D160		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7- 1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.11, C177.1, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, CUMMINS, MODEL 6CT8.3G, 6 CYLINDERS, FOUR CYCLE, WITH TURBOCHARGER, 207 HP A/N: 241137	D162		NOX: PROCESS UNIT**	NOX: 2.9 LBS/HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10- 1996] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16- 2001] PM: (9) [RULE 404,2-7-1986] ; ROG: 0.11 LBS/HR DIESEL (4) [RULE 1303(a)(1)-BACT,5- 10-1996]	C177.1, D12.1, E71.6, H23.6, K67.4
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, CUMMINS, MODEL 6CT8.3G, 6 CYLINDERS, FOUR CYCLE, WITH TURBOCHARGER, 207 HP A/N: 241138	D163		NOX: PROCESS UNIT**	NOX: 2.9 LBS/HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10- 1996] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16- 2001]	C177.1, D12.1, E71.6, H23.6, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				PM: (9) [RULE 404,2-7-1986] ; ROG: 0.11 LBS/HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, DISNEYLAND HOTEL, DIESEL FUEL, CLARKE GM DIESEL INC, MODEL MD-4-1226, 4 CYLINDERS, SERIAL NO. 47463, 73 HP A/N: 241139	D164		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7- 1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986]	C1.8, C1.22, D12.1, H23.6, K67.4
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, ALLIS- CHALMERS, MODEL 649, 6 CYLINDERS, FOUR CYCLE, SERIAL NO. K820640605, 73 HP A/N: 478429	D168		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7- 1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986]	C1.1, C1.20, D12.1, E71.6, E116.1, H23.6, H23.11, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, JOHN DEERE, MODEL 6081A, WITH AFTERCOOLER, TURBOCHARGER, 250 BHP A/N: 397419	D169		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996] ; NOX: 304 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001]	C1.1, C1.11, D12.1, E71.1, E71.4, H23.6, K67.4

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-9-1999;RULE 2005,4-20-2001] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, DIESEL FUEL, CUMMINS, MODEL 6BTA5.9F1, PARADISE PIER HOTEL, WITH AFTERCOOLER, TURBOCHARGER, 182 BHP A/N: 408907	D172		NOX: PROCESS UNIT**	CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-9-1999;RULE 2005,4-20-2001] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; SOX: 15 PPM DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, C1.22, D12.1, H23.6, K67.4, K67.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, CATERPILLAR, MODEL G3412STIA/450KW, SERIAL NO. 7DM, JOHNSON MATTHEY-MODEL QXC-30-08-NSCR, MODEL EPC-100-CONTROLLER, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 622 BHP A/N: 412302	D173		NOX: PROCESS UNIT**	CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,3-16-2001] ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]	C1.1, C1.11, D12.1, E71.1, E202.3, H23.12, K67.4
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, CUMMINS, MODEL GTA14 GS/GC 280 KW, WITH NSCR-MIRATECH, MODEL MCS-22Y1515-08-C2, CONTROLLER-MODEL MEC-2001-1LP, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 431 BHP A/N: 419597	D174		NOX: PROCESS UNIT**	CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995	C1.1, C1.11, D12.1, E71.3, E202.3, H23.12, K67.13

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				<p><i>RULE 2012, 3-16-2001</i> ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005, 4-9-1999; RULE 2005, 4-20-2001] ; PM: (9) [RULE 404, 2-7-1986]</p> <p>ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]</p>	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, PERKINS, MODEL 1004-40T, WITH TURBOCHARGER, 95.2 BHP A/N: 425385	D175		NOX: PROCESS UNIT**	<p>CO: 3.7 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 12-7-1995 <i>RULE 2012, 3-16-2001</i>] ; NOX + ROG: 5.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 4-20-2001]</p> <p>PM: 0.3 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002] ; PM: (9) [RULE 404, 2-7-1986]</p>	C1.1, C1.11, D12.1, E71.4, H23.6, K67.14

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, CATERPILLAR, MODEL G3406SITA (250 KW), WITH NSCR, JOHNSON MATTHEY, QXC20, A/F, WOODWARD, MODEL GECCO, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 367 BHP A/N: 431660	D176		NOX: PROCESS UNIT**	CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-5-2003 RULE 2012,5-6-2005] ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996]	C1.1, C1.11, D12.1, E71.5, E202.3, H23.12, K67.14
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, FORD, MODEL WSG-1068, WITH NSCR, MINE-X, MODEL DC47, NEUTRONIC, MARK V, A/F CONTROLLER, WITH CATALYTIC REDUCTION, TURBOCHARGER, 176 BHP A/N: 436095	D178		NOX: PROCESS UNIT**	CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995]	C1.1, D12.1, E202.3, H23.12, K67.14

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,4-20-2001] ; PM: (9) [RULE 404,2-7-1986] ; ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)- BACT,5-10-1996]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL G3456 DITA AA, WITH AFTERCOOLER, TURBOCHARGER, 685 BHP A/N: 445773	D179		NOX: PROCESS UNIT**	CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] ; NOX: 221 LBS/1000 GAL DIESEL (1) [RULE 2012,12-5- 2003 RULE 2012,1-7-2005] ; NOX + ROG: 4.8 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-20- 2001] ; PM: 0.15 GRAM/BHP- HR DIESEL (5) [RULE 1470,6- 1-2007] PM: (9) [RULE 404,2-7-1986] ; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)- BACT,5-10-1996;RULE 1303(a),12-6-2002]	C1.1, D12.1, E71.4, E116.1, H23.6, K67.16

* (1)(1A)(1B) Denotes RECLAIM emission factor
(2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL G3456 DITA AA, WITH AFTERCOOLER, TURBOCHARGER, 685 BHP A/N: 445774	D180		NOX: PROCESS UNIT**	CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 221 LBS/1000 GAL DIESEL (1) [RULE 2012,12-5-2003 RULE 2012,1-7-2005] ; NOX + ROG: 4.8 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-20-2001] ; PM: 0.15 GRAM/BHP-HR DIESEL (5) [RULE 1470,6-1-2007] PM: (9) [RULE 404,2-7-1986] ; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002]	C1.1, D12.1, E71.4, E116.1, H23.6, K67.16
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL G3456 DITA AA, WITH AFTERCOOLER, TURBOCHARGER, 685 BHP A/N: 445775	D181		NOX: PROCESS UNIT**	CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] ; NOX: 221 LBS/1000 GAL DIESEL (1) [RULE 2012,12-5-2003 RULE 2012,1-7-2005] ; NOX + ROG: 4.8 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-20-2001] ; PM: 0.15 GRAM/BHP-HR DIESEL (5) [RULE 1470,6-1-2007]	C1.1, D12.1, E71.4, E116.1, H23.6, K67.16

* (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				PM: (9) [RULE 404,2-7-1986] ; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, FORD, MODEL ESG-642, WITH NSCR, MODEL L102, WITH AIR FUEL RATIO CONTROLLER, WITH CATALYTIC REDUCTION, 67 BHP A/N: 444735	D182		NOX: PROCESS UNIT**	CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 437 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,3-16-2001] ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002]	C1.1, D12.1, E71.4, E71.5, H23.12, K67.14
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL 3306ATACC, WITH AFTERCOOLER, TURBOCHARGER, 377 BHP A/N: 445546	D183		NOX: PROCESS UNIT**	CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] ; NOX: 209 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7- 1995	C1.1, D12.1, E71.4, E116.1, H23.6, K67.16

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				RULE 2012,3-16-2001] ; NOX + ROG: 4.8 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002;RULE 2005,4-20-2001 RULE 2005,5-6-2005] ; PM: 0.15 GRAM/BHP-HR DIESEL (5) [RULE 1470,6-1-2007] ; PM: (9) [RULE 404,2-7-1986] PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL C-9 DITA, LOCATED AT NEMO SITE, WITH AFTERCOOLER, TURBOCHARGER, 398 BHP A/N: 459428	D223		NOX: PROCESS UNIT**	CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 136 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] NOX + ROG: 3 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002;RULE 2005,5-6-2005] ; PM: 0.15 GRAM/BHP-HR DIESEL (5) [RULE 1470,6-1-2007]	C1.1, C1.11, D12.1, E71.4, E116.1, H23.6, K67.16

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				PM: (9) [RULE 404,2-7-1986] ; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)- BACT,5-10-1996;RULE 1303(a),12-6-2002]	
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, CATERPILLAR, MODEL G3046 SITA, WITH NSCR,JOHNSON MATTHEY, MODEL QXE 10-8, A/F, GILL MODEL 120, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 367 BHP A/N: 478405	D259		NOX: PROCESS UNIT**	CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 413 LBS/MMSCF NATURAL GAS (1) [RULE 2012,5-6-2005] NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,5-6-2005] ; PM: (9) [RULE 404,2-7-1986] ; ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)- BACT,5-10-1996 RULE 1303(a),12-6-2002]	C1.1, C1.11, D12.1, E71.5, E116.1, E202.3, H23.12, K67.14
System 2 : NON - EMERGENCY					
INTERNAL COMBUSTION ENGINE, NON-EMERGENCY, DIESEL FUEL, JOHN DEERE, MODEL 4045TF275, ON-SITE PORTABLE DRIVING A WOOD CHIPPER, WITH TURBOCHARGER, 115 BHP A/N: 432411	D177		NOX: PROCESS UNIT**	CO: 3.7 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)- BACT,5-10-1996] ; NOX: 188 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995]	C1.12, D12.1, D323.1, K67.15

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : INTERNAL COMBUSTION, INDUSTRIAL					
				NOX + ROG: 4.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 2005,4-20-2001] ; PM: 0.22 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)- BACT,5-10-1996] PM: (9) [RULE 404,2-7-1986]	
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, EAST UNIT # 2, NATURAL GAS, SUPERIOR, MODEL LND145P, WITH FLUE GAS RECIRCULATION, OXYGEN CONTENT CONTROL, 12.57 MMBTU/HR WITH A/N: 370698 BURNER, INDUSTRIAL COMBUSTION, MODEL LNDG105, WITH LOW NOX BURNER	D16		NOX: LARGE SOURCE**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 30 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	D12.3, D12.4, H23.4, H23.12
BOILER, WEST UNIT # 2, NATURAL GAS, SUPERIOR, MODEL LND145S, WITH FLUE GAS RECIRCULATION, OXYGEN CONTENT CONTROL, 9.95 MMBTU/HR WITH A/N: 405301	D17		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 47.75 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995	D12.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, INDUSTRIAL COMBUSTION, MODEL LNDG105, WITH LOW NOX BURNER				RULE 2012,4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	
BOILER, EAST UNIT # 1, NATURAL GAS, SUPERIOR, MODEL LND145P, WITH FLUE GAS RECIRCULATION, OXYGEN CONTENT CONTROL, 12.57 MMBTU/HR WITH A/N: 370699	D18		NOX: LARGE SOURCE**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 30 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995] RULE 2012,4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	D12.3, D12.4, H23.4, H23.12
BURNER, INDUSTRIAL COMBUSTION, MODEL LNDG105, WITH LOW NOX BURNER					
BOILER, WEST UNIT # 1, NATURAL GAS, SUPERIOR, MODEL LND145S, WITH FLUE GAS RECIRCULATION, OXYGEN CONTENT CONTROL, 9.95 MMBTU/HR WITH A/N: 405302	D19		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 47.75 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995] RULE 2012,4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	D12.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, INDUSTRIAL COMBUSTION, MODEL LNDG105, WITH LOW NOX BURNER					
BOILER, B1, NATURAL GAS, CLEAVER BROOKS, MODEL FLX, WITH LOW NOX BURNER, 8.5 MMBTU/HR WITH A/N: 360389	D135		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	E202.4, H23.4, H23.12
BURNER, NATURAL GAS, ALZETA, MODEL CSB84					
BOILER, B2, NATURAL GAS, CLEAVER BROOKS, MODEL FLX, WITH LOW NOX BURNER, 8.5 MMBTU/HR WITH A/N: 360386	D137		NOX: PROCESS UNIT**	CO: 400 PPMV NATURAL GAS (5A) [RULE 1146,11-17-2000] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002]	E202.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, NATURAL GAS, ALZETA, MODEL CSB84				CO: 2000 PPMV NATURAL GAS (5) [RULE 407,4-2-1982] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981]	
BOILER, B3, NATURAL GAS, CLEAVER BROOKS, MODEL FLX, WITH LOW NOX BURNER, 8.5 MMBTU/HR WITH A/N: 360387	D138		NOX: PROCESS UNIT**	CO: 400 PPMV NATURAL GAS (5A) [RULE 1146,11-17-2000] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] CO: 2000 PPMV NATURAL GAS (5) [RULE 407,4-2-1982] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995;RULE 2012,3-16-2001]	E202.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, NATURAL GAS, ALZETA, MODEL CSB84				NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981]	
BOILER, B4, NATURAL GAS, CLEAVER BROOKS, MODEL FLX, WITH LOW NOX BURNER, 8.5 MMBTU/HR WITH A/N: 360388	D139		NOX: PROCESS UNIT**	CO: 400 PPMV NATURAL GAS (5A) [RULE 1146,11-17-2000] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] CO: 2000 PPMV NATURAL GAS (5) [RULE 407,4-2-1982] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981]	E202.4, H23.4, H23.12
BURNER, NATURAL GAS, ALZETA, MODEL CSB84					

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
HEATER, CPI, NO. 1, NATURAL GAS, INTERNATIONAL BOILER WORKS, MODEL TH-3, WITH LOW NOX BURNER, 3.8 MMBTU/HR A/N: 457328	D200		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 400 PPMV (5) [RULE 1146.1,5-13-1994] ; NOX: 49.18 LBS/MMSCF NATURAL GAS (1) [RULE 2012,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] ; PM: (9) [RULE 404,2-7-1986]	D332.1, E17.1, H23.8, H23.12
HEATER, CPI, NO. 2, NATURAL GAS, INTERNATIONAL BOILER WORKS, MODEL TH-3, WITH LOW NOX BURNER, FLUE GAS RECIRCULATION, 3.4 MMBTU/HR WITH A/N: 457329 BURNER, NATURAL GAS, GORDON-PAITT, MODEL LNR10-C20, WITH LOW NOX BURNER, 3.4 MMBTU/HR	D202		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 400 PPMV (5) [RULE 1146,11-17-2000; RULE 1146.1,5-13-1994] ; NOX: 30 PPMV NATURAL GAS (4) [RULE 2005,2-14-1997] NOX: 49.18 LBS/MMSCF NATURAL GAS (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] ; PM: (9) [RULE 404,2-7-1986]	D332.1, E17.1, H23.8, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, PARADISE PIER HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 1, 5 MMBTU/HR WITH A/N: 459430 BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000	D206		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	D12.4, H23.4, H23.12
BOILER, PARADISE PIER HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 2, 5 MMBTU/HR WITH A/N: 459431	D207		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002]	D12.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000				CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	
BOILER, PARADISE PIER HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 3, 5 MMBTU/HR WITH A/N: 459432	D209		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	D12.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000					
BOILER, PARADISE PIER HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 4, 5 MMBTU/HR WITH A/N: 459433 BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000	D211		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	D12.4, H23.4, H23.12
BOILER, DISNEYLAND HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 1, 5 MMBTU/HR WITH A/N: 473755	D214		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002]	C1.13, D12.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor
(2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000				CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	
BOILER, DISNEYLAND HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 2, 5 MMBTU/HR WITH A/N: 473757	D215		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) (RULE 407,4-2-1982) ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	C1.13, D12.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000					
BOILER, DISNEYLAND HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 3, 5 MMBTU/HR WITH A/N: 473758	D217		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	C1.13, D12.4, H23.4, H23.12
BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000					
BOILER, DISNEYLAND HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 4, 5 MMBTU/HR WITH A/N: 473761	D219		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002]	C1.13, D12.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000				CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	
BOILER, DISNEYLAND HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 5, 5 MMBTU/HR WITH A/N: 473762	D221		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	C1.13, D12.4, H23.4, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000					
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, LANDA, MODEL VHW 3-700, 0.21 MMBTU/HR A/N: 471806	D224		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, STEAM X, MODEL DELCO, 0.28 MMBTU/HR A/N: 471807	D225		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, STEAM X, MODEL VANGUARD, 0.28 MMBTU/HR A/N: 471808	D226		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 407,4-2-1982]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, A&M EQUIPMENT SERVICE, MODEL AMHGD-2003, NO. 1, 0.21 MMBTU/HR A/N: 471809	D227		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, A&M EQUIPMENT SERVICE, MODEL AMHGD-2003, NO. 2, 0.21 MMBTU/HR A/N: 471810	D228		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 7205, NO. 1, 0.3 MMBTU/HR A/N: 471811	D229		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 7205, NO. 2, 0.3 MMBTU/HR A/N: 471812	D230		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.16, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 1, 0.3 MMBTU/HR A/N: 471813	D231		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18

* (1)(1A)(1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5)(5A)(5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2)(2A)(2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
 (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 2, 0.3 MMBTU/HR A/N: 471814	D232		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 3, 0.3 MMBTU/HR A/N: 471816	D233		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 4, 0.3 MMBTU/HR A/N: 471817	D234		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 5, 0.3 MMBTU/HR A/N: 471818	D235		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 6, 0.3 MMBTU/HR A/N: 471820	D236		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 7, 0.3 MMBTU/HR A/N: 471821	D237		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 8, 0.3 MMBTU/HR A/N: 471822	D238		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 9, 0.3 MMBTU/HR A/N: 471823	D239		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 10, 0.3 MMBTU/HR A/N: 471824	D240		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.16, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 1, 0.56 MMBTU/HR A/N: 471825	D241		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 2, 0.56 MMBTU/HR A/N: 471826	D242		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 3, 0.56 MMBTU/HR A/N: 471827	D243		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.17, D12.8, K67.18

* (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 4, 0.56 MMBTU/HR A/N: 471829	D244		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.17, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 5, 0.56 MMBTU/HR A/N: 471830	D245		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 6, 0.56 MMBTU/HR A/N: 471831	D246		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 7, 0.56 MMBTU/HR A/N: 471833	D247		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 8, 0.56 MMBTU/HR A/N: 471834	D248		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.17, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 9, 0.56 MMBTU/HR A/N: 471835	D249		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 247, NO. 1, 0.56 MMBTU/HR A/N: 471836	D250		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 247, NO. 2, 0.56 MMBTU/HR A/N: 471838	D251		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.17, D12.8, K67.18

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 247, NO. 3, 0.56 MMBTU/HR A/N: 471839	D252		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, C1.17, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 247, NO. 4, 0.56 MMBTU/HR A/N: 471840	D253		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 247, NO. 5, 0.56 MMBTU/HR A/N: 471841	D254		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.14, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 11, 0.3 MMBTU/HR A/N: 478418	D255		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.16, C1.18, D12.8, K67.18

* (1)(1A)(1B) Denotes RECLAIM emission factor
 (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 12, 0.3 MMBTU/HR A/N: 478419	D256		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.16, C1.18, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 13, 0.3 MMBTU/HR A/N: 478420	D257		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.16, C1.18, D12.8, K67.18
BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO.14, 0.3 MMBTU/HR A/N: 478421	D258		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.2, C1.16, C1.18, D12.8, K67.18
Process 3 : ORGANIC SOLVENT SURFACE COATING					
SPRAY COATING OPERATION, WATER WASH TYPE, WITH SPRAY BOOTH A/N: 12162X	D20			PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9-2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1171,11-7-2003 RULE 1171,2-1-2008]	D322.2, H23.2, K67.3

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 3 : ORGANIC SOLVENT SURFACE COATING					
SPRAY COATING OPERATION, FLOOR TYPE, WITH 24 EXHAUST FILTERS, EACH 20" X 25" X 2", WITH SPRAY BOOTH A/N: 214087	D21			PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9-2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1171,11-7-2003 RULE 1171,2-1-2008]	A63.1, B27.4, C6.1, D12.2, D322.1, E175.1, H23.2, K67.2
SPRAY COATING OPERATION, FLOOR TYPE, WITH 21 EXHAUST FILTERS, EACH 20" X 25" X 2", WITH SPRAY BOOTH A/N: 214086	D22			PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9-2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1171,11-7-2003 RULE 1171,2-1-2008]	A63.1, B27.4, C6.1, D12.2, D322.1, E175.1, H23.2, K67.2
SPRAY COATING OPERATION, AUTOMOTIVE TYPE, WITH 22 EXHAUST FILTERS, EACH 20" X 25" X 2", WITH SPRAY BOOTH A/N: 19482X	D24			PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9-2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1171,11-7-2003 RULE 1171,2-1-2008]	C6.1, D12.2, D322.1, E175.1, H23.2, K67.2
SPRAY COATING OPERATION, SOLVENT, DISNEYLAND HOTEL, AUTOMOTIVE TYPE, WITH 44 EXHAUST FILTERS, EACH 20" X 25" X 1.5", WITH SPRAY BOOTH A/N: 241140	D165			PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9-2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1145,2-14-1997 RULE 1145,12-3-2004;RULE 1171,11-7-2003;RULE 1171,2-1-2008]	B27.4, C1.9, C1.10, C6.1, D12.2, D322.1, E175.2, H23.2, K67.2, K67.8

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4 : PETROLEUM MARKETING, CONSUMER FLEET FUELING					
System 1 : FUEL STORAGE AND DISPENSING SYSTEMS					
STORAGE TANK, UNDERGROUND, GASOLINE, NOT METHANOL COMPATIBLE, WITH OPW (VR-102-E), 10000 GALS A/N: 437542	D36				D330.1, J109.1, J373.1
STORAGE TANK, UNDERGROUND, GASOLINE, NOT METHANOL COMPATIBLE, WITH OPW (VR-102-E), 10000 GALS A/N: 437542	D40				D330.1, J109.1, J373.1
FUEL DISPENSING NOZZLE, BALANCE TYPE PHASE II CONTROL, GASOLINE, WITH BALANCE RETRACTOR (G-70-52-AM), WITH PHASE II VAPOR RECOVERY SYSTEM A/N: 437542	D88				D330.1, J110.1, J373.1
FUEL DISPENSING NOZZLE, BALANCE TYPE PHASE II CONTROL, GASOLINE, WITH BALANCE RETRACTOR (G-70-52-AM), WITH PHASE II VAPOR RECOVERY SYSTEM A/N: 437542	D89				D330.1, J110.1, J373.1
FUEL DISPENSING NOZZLE, BALANCE TYPE PHASE II CONTROL, GASOLINE, WITH BALANCE RETRACTOR, (G-70-52-AM), WITH PHASE II VAPOR RECOVERY SYSTEM A/N: 437542	D90				D330.1, J110.1, J373.1

* (1)(1A)(1B) Denotes RECLAIM emission factor
(2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 4 : PETROLEUM MARKETING, CONSUMER FLEET FUELING					
DISPENSE MOBILE FUELER, GASOLINE, FRANZEN-HILL (G-70-193), WITH TWO HEALY 100 JET PUMPS, 400 GALS; WIDTH: 3 FT 8 IN; HEIGHT: 3 FT 10 IN; LENGTH: 7 FT 1 IN A/N: 367066	D147				C1.6, C1.7, E71.2, J109.1, J110.1, J397.1, K67.6
FUEL DISPENSING NOZZLE, GASOLINE, EQUIPPED WITH PHASE II VAPOR RECOVERY, HEALY, MODEL 400 ORVR A/N: 367066	D148				
Process 5 : FABRICATED METALS					
System 1 :					
ABRASIVE BLASTING, OPEN, SAND WITH A/N: 193050 ABRASIVE BLASTING NOZZLE, DIAMETER: 0.375 IN	D44			PM: (9) [RULE 1140,2-1-1980;RULE 1140,8-2-1985;RULE 405,2-7-1986]	D323.1, K67.5
ABRASIVE BLASTING, ROOM, SAND, BAGHOUSE SERVICES, WITH 3000 LB POT, WIDTH: 15 FT 8 IN; HEIGHT: 15 FT 11 IN; LENGTH: 28 FT WITH A/N: 385807 ABRASIVE BLASTING NOZZLE, 2, MAXIMUM WORKING PRESSURE OF 120 PSI, DIAMETER: 0.625 IN	D156	C158		PM: (9) [RULE 404,2-7-1986]	B27.2, K67.11

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5 : FABRICATED METALS					
BAGHOUSE, UNITED AIR SPECIALIST, MODEL SBD24-3, PULSE JET CLEANING, SERIAL NO. 60042645, 7440 SQ.FT.; 24 CARTRIDGE A/N: 385808	C158	D156		PM: (9) [RULE 404,2-7-1986]	C6.2, D12.2, D322.3, D381.1, E102.1, K67.10
ABRASIVE BLASTING, CARBON DIOXIDE (DRY ICE), COLDJET, MODEL 2000, WITH 40 POUND CAPACITY HOPPER WITH A/N: 404957 ABRASIVE BLASTING NOZZLE, 1, WITH A MAX. THROAT AREA OF 0.068 IN2, 140 PSIA	D170			PM: (9) [RULE 1140,2-1-1980;RULE 1140,8-2-1985;RULE 405,2-7-1986]	B59.1, D381.1, H23.5, K67.11
Process 7 : FABRICATED METALS, MACHINING OPERATIONS					
System 1 :					
PLASMA ARC CUTTER, DUAL CARRIAGE TYPE, WITH A FOUR TORCH CAPACITY A/N: 243063	D48	C49		PM: (9) [RULE 405,2-7-1986]	D323.1
ELECTROSTATIC PRECIPITATOR, TEPCO TRION, MODEL T5200, WITH A 3 H.P. BLOWER A/N: 249015	C49	D48		PM: (9) [RULE 404,2-7-1986]	D323.1, E202.1
Process 8 : SMOKE EFFECTS					
System 1 :					
FILTER, HEPA, FARR A/N: 288923	C96			PM: (9) [RULE 404,2-7-1986]	D322.1, D323.1, K67.2

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9 : R-219 EXEMPT EQUIPMENT SUBJECT TO SOURCE SPECIFIC RULES					
System 1 :					
RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS, COMFORT A/C	E102				H23.3
RULE 219 EXEMPT EQUIPMENT, PRINTING EQUIPMENT, WITH RELATED COATING, LAMINATING AND DRYING EQUIPMENT	E104			ROG: (9) [RULE 1130.1,12-13-1996;RULE 1171,11-7-2003;RULE 1171,2-1-2008]	
RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL, UNHEATED, NON-CONVEYORIZED	E105			ROG: (9) [RULE 1171,11-7-2003;RULE 1171,2-1-2008]	H23.1
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS	E107			ROG: (9) [RULE 1113,11-8-1996;RULE 1113,7-13-2007;RULE 1171,11-7-2003;RULE 1171,2-1-2008]	K67.1
RULE 219 EXEMPT EQUIPMENT, HAND LAY, BRUSH AND ROLL UP RESIN OPERATIONS	E108			ROG: (9) [RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7-2003;RULE 1171,2-1-2008]	
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS	E111			ROG: (9) [RULE 1106.1,2-12-1999;RULE 1171,11-7-2003;RULE 1171,2-1-2008]	

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 9 : R-219 EXEMPT EQUIPMENT SUBJECT TO SOURCE SPECIFIC RULES					
RULE 219 EXEMPT EQUIPMENT, LAMINATING EQUIPMENT, LOW USE OR EMISSIONS	E112			ROG: (9) [RULE 1168,10-3-2003;RULE 1168,1-7-2005;RULE 1171,11-7-2003;RULE 1171,2-1-2008]	
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS	E113			ROG: (5) [RULE 1128,3-8-1996;RULE 1171,11-7-2003;RULE 1171,2-1-2008]	

* (1)(1A)(1B) Denotes RECLAIM emission factor	(2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit	(4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit	(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit	(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits	(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: DEVICE ID INDEX

Device Index For Section D				
Device ID	Section D Page No.	Process		System
D1	1	1		1
D2	1	1		1
D3	1	1		1
D4	1	1		1
D5	1	1		1
D7	1	1		1
D8	2	1		1
D10	2	1		1
D12	2	1		1
D15	2	1		1
D16	28	2		0
D17	28	2		0
D18	29	2		0
D19	29	2		0
D20	48	3		0
D21	49	3		0
D22	49	3		0
D24	49	3		0
D36	50	4		1
D40	50	4		1
D44	51	5		1
D48	52	7		1
C49	52	7		1
D88	50	4		1
D89	50	4		1
D90	50	4		1
D95	2	1		1
C96	52	8		1
D98	3	1		1
D99	3	1		1
D101	3	1		1
E102	53	9		1
E104	53	9		1
E105	53	9		1
E107	53	9		1
E108	53	9		1



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: DEVICE ID INDEX

Device Index For Section D				
Device ID	Section D Page No.	Process		System
E111	53	9		1
E112	54	9		1
E113	54	9		1
D115	3	1		1
D116	4	1		1
D117	5	1		1
D118	5	1		1
D119	6	1		1
D120	6	1		1
D121	7	1		1
D122	8	1		1
D123	8	1		1
D124	9	1		1
D125	9	1		1
D126	10	1		1
D127	11	1		1
D128	11	1		1
D129	12	1		1
D131	12	1		1
D133	13	1		1
D134	14	1		1
D135	30	2		0
D137	30	2		0
D138	31	2		0
D139	32	2		0
D146	14	1		1
D147	51	4		1
D148	51	4		1
D149	15	1		1
D152	16	1		1
D153	16	1		1
D156	51	5		1
C158	52	5		1
D159	16	1		1
D160	17	1		1
D162	17	1		1



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D163	17	1	1
D164	18	1	1
D165	49	3	0
D168	18	1	1
D169	18	1	1
D170	52	5	1
D172	19	1	1
D173	20	1	1
D174	20	1	1
D175	21	1	1
D176	22	1	1
D177	27	1	2
D178	22	1	1
D179	23	1	1
D180	24	1	1
D181	24	1	1
D182	25	1	1
D183	25	1	1
D200	33	2	0
D202	33	2	0
D206	34	2	0
D207	34	2	0
D209	35	2	0
D211	36	2	0
D214	36	2	0
D215	37	2	0
D217	38	2	0
D219	38	2	0
D221	39	2	0
D223	26	1	1
D224	40	2	0
D225	40	2	0
D226	40	2	0
D227	40	2	0
D228	41	2	0
D229	41	2	0



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: DEVICE ID INDEX

Device Index For Section D				
Device ID	Section D Page No.	Process		System
D230	41	2		0
D231	41	2		0
D232	42	2		0
D233	42	2		0
D234	42	2		0
D235	42	2		0
D236	43	2		0
D237	43	2		0
D238	43	2		0
D239	43	2		0
D240	44	2		0
D241	44	2		0
D242	44	2		0
D243	44	2		0
D244	45	2		0
D245	45	2		0
D246	45	2		0
D247	45	2		0
D248	46	2		0
D249	46	2		0
D250	46	2		0
D251	46	2		0
D252	47	2		0
D253	47	2		0
D254	47	2		0
D255	47	2		0
D256	48	2		0
D257	48	2		0
D258	48	2		0
D259	27	1		1



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F1.1 The operator shall limit the material processed to no more than 2000 lb(s) in any one year.

For the purpose of this condition, material processed shall be defined as 1,1,1 trichloroethane.

[H&S 44300, 7-1-1988]

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 9-11-1998]

F14.2 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F48.1 The operator shall not operate at this facility non chain driven, uncontrolled charbroiler exceeding the opacity limits specified in Rule 401.

[RULE 401, 3-2-1984; RULE 401, 9-11-1998]

DEVICE CONDITIONS

A. Emission Limits



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A63.1 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than or equal to 10 LBS IN ANY ONE DAY

The operator shall calculate the emission limit(s) SUGGESTED CHAR CONDITION PARAMETER NOT SET UP

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D21, D22]

B. Material/Fuel Type Limits

B27.2 The operator shall not use abrasive material (except for abrasive containing nickel) containing any carcinogenic compounds identified in the SCAQMD Rule 1401, as amended 18-aug-2000.

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D156]

B27.4 The operator shall not use materials containing any compounds identified in the SCAQMD Rule 1401, as amended 12/07/1990.

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D21, D22, D165]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

B59.1 The operator shall only use the following material(s) in this device :

Diesel fuel

[RULE 1140, 8-2-1985]

[Devices subject to this condition : D170]

B59.2 The operator shall only use the following material(s) in this device :

diesel fuel or bio-diesel

[**RULE 1303(b)(2)-Offset, 5-10-1996**; **RULE 1303(b)(2)-Offset, 12-6-2002**; **RULE 1401, 3-4-2005**]

[Devices subject to this condition : D224, D225, D226, D227, D228, D229, D230, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D241, D242, D243, D244, D245, D246, D247, D248, D249, D250, D251, D252, D253, D254, D255, D256, D257, D258]

C. Throughput or Operating Parameter Limits

C1.1 The operator shall limit the operating time to no more than 200 hour(s) in any one year.

[**RULE 1110.2, 6-3-2005**; **RULE 1303(a)(1)-BACT, 5-10-1996**; **RULE 1303(b)(1)-Modeling, 5-10-1996**; **RULE 1303(b)(2)-Offset, 5-10-1996**; **RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996**; **RULE 2005, 10-15-1993**; **RULE 2005, 4-9-1999**; **RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995**; **RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : D1, D2, D3, D4, D5, D7, D8, D12, D15, D95, D99, D101, D115, D116, D117, D118, D119, D120, D121, D122, D123, D124, D125, D126, D127, D128, D129, D131, D133, D134, D146, D149, D152, D153, D160, D168, D169, D172, D173, D174, D175, D176, D178, D179, D180, D181, D182, D183, D223, D259]



AQMD
AIR QUALITY MANAGEMENT DISTRICT

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.2 The operator shall limit the operating time to no more than 125 hour(s) in any one year.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]

[Devices subject to this condition : D10]

C1.3 The operator shall limit the operating time to no more than 100 hour(s) in any one year.

[RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]

[Devices subject to this condition : D98]

C1.6 The operator shall limit the gasoline dispensed to no more than 240000 gallon(s) per year.

[RULE 1401, 8-18-2000]

[Devices subject to this condition : D147]

C1.7 The operator shall limit the gasoline dispensed to no more than 20000 gallon(s) in any one calendar month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 10-20-2000]

[Devices subject to this condition : D147]

C1.8 The operator shall limit the operating time to no more than 199 hour(s) in any one year.

[RULE 1110.2, 6-3-2005; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]

[Devices subject to this condition : D159, D164]

C1.9 The operator shall limit the coating and solvent usage to no more than 4 gallon(s) per day.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D165]



AQMD

**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.10 The operator shall limit the coating and solvent usage to no more than 88 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D165]

C1.11 The operator shall limit the maintenance testing to no more than 50 hour(s) in any one year.

[RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000; RULE 1470, 6-1-2007]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D95, D149, D160, D169, D173, D174, D175, D176, D223, D259]

C1.12 The operator shall limit the operating time to no more than 1092 in any one calendar year.

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D177]

C1.13 The operator shall limit the natural gas fuel usage to no more than 15.569 MM cubic feet in any one calendar month.

The fuel usage limit of 15.569 mmcf/month is the total fuel to be used in the five boilers.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D214, D215, D217, D219, D221]

C1.14 The operator shall limit the operating time to no more than 300 hour(s) in any one month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005; RULE 2012, 5-6-2005]

[Devices subject to this condition : D224, D225, D226, D227, D228, D229, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D241, D242, D243, D244, D245, D246, D247, D248, D249, D250, D251, D252, D253, D254]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.16 The operator shall limit the operating time to no more than 22 hour(s) in any one day.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 5-6-2005**]

[Devices subject to this condition : D229, D230, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D255, D256, D257, D258]

C1.17 The operator shall limit the operating time to no more than 12 hour(s) in any one day.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 5-6-2005**]

[Devices subject to this condition : D243, D244, D248, D251, D252]

C1.18 The operator shall limit the operating time to no more than 330 hour(s) in any one month.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005**]

[Devices subject to this condition : D255, D256, D257, D258]

C1.20 The operator shall limit the maintenance testing to no more than 30 hour(s) in any one year.

[**RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000; RULE 1470, 6-1-2007**]

[Devices subject to this condition : D15, D99, D153, D168]

C1.22 The operator shall limit the maintenance testing to no more than 34 hour(s) in any one year.

[**RULE 1470, 6-1-2007**]

[Devices subject to this condition : D152, D164, D172]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- C6.1 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 0.25 inches water column.

The operator shall to comply with this condition, monitor the differential pressure as specified in condition D12.2..

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D21, D22, D24, D165]

- C6.2 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 5 inches water column.

The operator shall to comply with this condition, monitor the differential pressure as specified in condition D12.2..

[RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C158]

- C177.1 The operator shall set and maintain the fuel injection timing of the engine at 4 degrees retarded relative to standard timing.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000]

[Devices subject to this condition : D7, D8, D10, D15, D95, D98, D99, D153, D160, D162, D163]

D. Monitoring/Testing Requirements



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D12.1 The operator shall install and maintain a(n) timer to accurately indicate the elapsed operating time of the engine.

[RULE 1110.2, 6-3-2005; **RULE 1303(b)(1)-Modeling, 5-10-1996**; RULE 1303(b)(1), 10-20-2000; **RULE 1303(b)(2)-Offset, 5-10-1996**; **RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996**; **RULE 2005, 10-15-1993**; **RULE 2005, 4-9-1999**; **RULE 2012, 12-7-1995**; RULE 2012, 4-9-1999; **RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995**; **RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : D1, D2, D3, D4, D5, D7, D8, D10, D12, D15, D95, D98, D99, D101, D115, D116, D117, D118, D119, D120, D121, D122, D123, D124, D125, D126, D127, D128, D129, D131, D133, D134, D146, D149, D152, D153, D159, D160, D162, D163, D164, D168, D169, D172, D173, D174, D175, D176, D177, D178, D179, D180, D181, D182, D183, D223, D259]

D12.2 The operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the filter.

[RULE 1303, 10-20-2000; **RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : D21, D22, D24, C158, D165]

D12.3 The operator shall install and maintain a(n) flow meter to accurately indicate the flue gas flow in the flue gas recirculation system.

For the purpose of this condition a flue gas flow regulator that indicates the percent open setting in the FGR system may be used instead of a flow meter.

[**RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : D16, D18]

D12.4 The operator shall install and maintain a(n) non-resettable totalizing fuel flow meter to accurately indicate the fuel usage of the equipment.

[**RULE 2012, 12-7-1995**; RULE 2012, 4-9-1999]

[Devices subject to this condition : D16, D17, D18, D19, D206, D207, D209, D211, D214, D215, D217, D219, D221]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D12.8 The operator shall install and maintain a(n) timer to accurately indicate the elapsed operating time from the pressure washer.

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005; RULE 2012, 5-6-2005**]

[Devices subject to this condition : D224, D225, D226, D227, D228, D229, D230, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D241, D242, D243, D244, D245, D246, D247, D248, D249, D250, D251, D252, D253, D254, D255, D256, D257, D258]

D322.1 The operator shall perform a weekly inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : D21, D22, D24, C96, D165]

D322.2 The operator shall perform a weekly inspection to check for the water wash integrity.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : D20]

D322.3 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : C158]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D44, D48, C49, C96, D177]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D330.1 The operator shall have a person that has been trained in accordance with Rule 461(d)(5) conduct a semi-annual inspection of the gasoline transfer and dispensing equipment. The first inspection shall be in accordance with Rule 461, Attachment B, the second inspection shall be in accordance with Rule 461, Attachment C, and the subsequent inspections shall alternate protocols. The operator shall keep records of the inspection and the repairs in accordance to Rule 461 and Section K of this Permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D36, D40, D88, D89, D90]

D332.1 The operator shall determine compliance with the CO emission limit(s) by conducting a test at least every five years using a portable analyzer and AQMD-approved test method or, if not available, a non-AQMD approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with Rule 1146.1 concentration limit. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D200, D202]

D381.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C158, D170]

E. Equipment Operation/Construction Requirements



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E17.1 The operator shall not use more than 1 of the following items simultaneously:

Device ID: D200 [Heater]

Device ID: D202 [Heater]

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D200, D202]

E71.1 The operator shall only operate this equipment during emergencies resulting in an interruption of service of the primary power supply or during stage II or III electrical emergency declared by the California Independent system operator (in addition to maintenance and testing of this engine)..

[RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000]

[Devices subject to this condition : D149, D169, D173]

E71.2 The operator shall only operate this equipment using the manufacturers recommendation for the installation, operation and maintenance of the phase one and phase two vapor recovery equipment. The manufacturers manuals shall be readily accessible on site and made available to District representatives upon request.

[RULE 461, 6-3-2005]

[Devices subject to this condition : D147]

E71.3 The operator shall only operate this equipment during operation beyond 50 hours per year for maintenance and testing is allowed only in the event of loss of grid power or up to 30 minutes prior to a rotating outage provided that: 1) the electrical grid operator or electric utility has ordered rotating outages in the control area where the engine is located or has indicated that it expects to issue such an order at a certain time; and 2) the engine is located in a utility service block that is subject to the rotating outage.

[RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000]

[Devices subject to this condition : D174]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- E71.4 The operator shall only operate this equipment during operation beyond 50 hours per year for maintenance and testing is allowed only in the event of loss of grid power or up to 30 minutes prior to a rotating outage provided that: 1) the electrical grid operator or electric utility has ordered rotating outages in the control area where the engine is located or has indicated that it expects to issue such an order at a certain time; and 2) the engine is located in a utility service block that is subject to the rotating outage.

Engine operation shall be terminated immediately after the utility distribution company advises that a rotating outage is no longer imminent or in effect.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1470, 6-1-2007]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D95, D149, D160, D169, D175, D179, D180, D181, D182, D183, D223]

- E71.5 The operator shall only operate this equipment during operation beyond 50 hours per year, this engine shall only operate during emergencies resulting in an interruption of service of the primary power supply or during stage II or III electrical emergency declared by the electrical grid operator. Operators may use this engine as part of interruptible electrical service program.

An interruptible electric service program is a program in which the facility receives payment or reduced rate in return for a requirement to reduce its electric load on the grid when requested to do so by the utility, the grid operator, or other organization.

[RULE 1303(a)-BACT, 5-10-1996]

[Devices subject to this condition : D176, D182, D259]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- E71.6 The operator shall only operate this equipment during operation beyond 30 hours per year for maintenance and testing is allowed only in the event of loss of grid power or up to 30 minutes prior to a rotating outage provided that: 1) the electrical grid operator or electric utility has ordered rotating outages in the control area where the engine is located or has indicated that it expects to issue such an order at a certain time; and 2) the engine is located in a utility service block that is subject to the rotating outage.

Engine operation shall be terminated immediately after the utility distribution company advises that a rotating outage is no longer imminent or in effect.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1470, 6-1-2007]

[Devices subject to this condition : D15, D98, D99, D133, D146, D153, D159, D162, D163, D168]

- E71.7 The operator shall only operate this equipment during operation beyond 20 hours per year for maintenance and testing is allowed only in the event of loss of grid power or up to 30 minutes prior to a rotating outage provided that: 1) the electrical grid operator or electric utility has ordered rotating outages in the control area where the engine is located or has indicated that it expects to issue such an order at a certain time; and 2) the engine is located in a utility service block that is subject to the rotating outage.

Engine operation shall be terminated immediately after the utility distribution company advises that a rotating outage is no longer imminent or in effect.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1470, 6-1-2007]

[Devices subject to this condition : D3, D4, D5, D10]

- E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C158]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E116.1. This engine shall not be used as part of a demand response program using interruptible service contract in which a facility receives a payment or reduced rates in return for reducing its electric load on the grid when requested to do so by the utility or the grid operator.

[**RULE 1303(a)-BACT, 5-10-1996; RULE 1303(a), 12-6-2002; RULE 1470, 6-1-2007**]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D15, D95, D99, D153, D160, D168, D179, D180, D181, D183, D223, D259]

E175.1 The operator shall not use this equipment unless all exhaust air passes through the following:

filter media at least 2 inches thick

[**RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : D21, D22, D24]

E175.2 The operator shall not use this equipment unless all exhaust air passes through the following:

filter media at least 1.5 inches thick

[**RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : D165]

E202.1 The operator shall clean and maintain this equipment according to the following specifications:

Thoroughly clean the ionizers and collector cells quarterly

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : C49]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E202.2 The operator shall clean and maintain this equipment according to the following specifications:

the diesel catalyst shall be inspected once every calendar year and cleaned, if necessary. If cleaning is necessary, all loose soot deposits shall be removed and the catalyst shall be washed according to manufacturers specifications

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D133, D146]

E202.3 The operator shall clean and maintain this equipment according to the following specifications:

the engine shall not be operated without the use of an automatic air to fuel ratio controller which shall be maintained and kept in proper operating conditions at all times as specified by the manufacturer

the catalytic converter temperature and exhaust oxygen concentration shall be maintained within the effective operating range of the catalytic converter as specified by the manufacturer

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 2005, 10-15-1993; RULE 2005, 4-9-1999]

[Devices subject to this condition : D134, D173, D174, D176, D178, D259]

E202.4 The operator shall clean and maintain this equipment according to the following specifications:

Records shall be maintained of inspections and maintenance of the burners

The operator shall follow the procedures specified by the manufacturer to tune-up and maintain the combustion system (including but not limited to the burner and air/fuel control device) of this heater

Manufacturers maintenance procedures shall be kept by the operator and made available at the request of AQMD

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000; RULE 2005, 4-9-1999]

[Devices subject to this condition : D135, D137, D138, D139]

H. Applicable Rules



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	1122

[RULE 1122, 10-1-2004]

[Devices subject to this condition : E105]

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	109
PM	District Rule	481

[RULE 109, 5-2-2003; RULE 481, 1-11-2002]

[Devices subject to this condition : D20, D21, D22, D24, D165]

H23.3 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Refrigerants	District Rule	1415
Refrigerants	40CFR82, SUBPART	F

[RULE 1415, 10-14-1994; 40CFR 82 Subpart F, 5-14-1993]

[Devices subject to this condition : E102]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.4 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
CO	District Rule	1146

This CO emissions (concentration) shall be tested at least once per year per Rule 1146 (d)(6).

[RULE 1146, 11-17-2000]

[Devices subject to this condition : D16, D17, D18, D19, D135, D137, D138, D139, D206, D207, D209, D211, D214, D215, D217, D219, D221]

H23.5 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
PM	District Rule	1140

[RULE 1140, 2-1-1980; RULE 1140, 8-2-1985]

[Devices subject to this condition : D170]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.6 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
PM	District Rule	1470

[RULE 1470, 6-1-2007]

[Devices subject to this condition : D1, D2, D3, D4, D5, D7, D8, D10, D12, D15, D95, D98, D99, D133, D146, D149, D152, D153, D159, D160, D162, D163, D164, D168, D169, D172, D175, D179, D180, D181, D183, D223]

H23.8 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
CO	District Rule	1146.1

[RULE 1146.1, 5-13-1994]

[Devices subject to this condition : D200, D202]

H23.11 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
PM	District Rule	1472

[RULE 1472, 3-7-2008]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D15, D95, D99, D153, D160, D168]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.12 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
SOX	District Rule	431.1

[RULE 431.1, 6-12-1998]

[Devices subject to this condition : D16, D17, D18, D19, D101, D115, D116, D117, D118, D119, D120, D121, D122, D123, D124, D125, D126, D127, D128, D129, D134, D135, D137, D138, D139, D173, D174, D176, D178, D182, D200, D202, D206, D207, D209, D211, D214, D215, D217, D219, D221, D259]

J. Rule 461

J109.1 The operator shall use, except for diesel transfer, the phase I vapor recovery system in full operation whenever this equipment is in use. This system shall be installed, operated and maintained to meet all CARB certification requirements.

[RULE 461, 3-7-2008]

[Devices subject to this condition : D36, D40, D147]

J110.1 The operator shall use, except for diesel transfer, the phase II vapor recovery system in full operation whenever gasoline from this equipment is dispensed to motor vehicles as defined in Rule 461. This system shall be installed, operated and maintained to meet all CARB certification requirements.

[RULE 461, 3-7-2008]

[Devices subject to this condition : D88, D89, D90, D147]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

J373.1 The operator shall comply with the following gasoline transfer and dispensing requirements:

a). At least seventy-two (72) hours prior to back-filling any underground storage tank or piping, the SCAQMD shall be notified by e-mail at r461backfill@aqmd.gov or by facsimile at telephone number (909) 396-3606. Such notification shall include the name of the owner or operator; the name of the contractors; the location of the facility; and the scheduled start and completion dates of the back-filling procedure. The backfilling procedure shall not commence until inspected by a District representative.

b). As required by AQMD Rule 461 or CARB Executive Order, a static pressure leak decay test shall be conducted to demonstrate that the storage tanks, the remote and/or nozzle vapor recovery check valves, associated vapor return piping and fittings are free from vapor leaks. The test shall be conducted in accordance with CARB Test Procedure Method TP-201.3. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at R461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractors; the location of the facility; and the scheduled start and completion dates of the static pressure leak decay test.

c). Depending on the system configuration, a pressure integrity test of the drop tube/drain valve assembly shall be conducted to quantify the pressure integrity of both the drop tube and drain valve seal or a pressure integrity test of the drop tube overflow prevention device and spill container drain and the pressure integrity of the spill container drain valve. Either test shall be conducted as a reverification test and the test shall be conducted in accordance with test procedure method TP-201.1C or TP-201.1D, respectively. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at (909) 396-2606 at least 72 hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the of the pressure integrity test of drop tube/drain valve assembly or pressure integrity test of the drop tube overflow prevention device and spill container drain valve.

d). A leak rate and cracking pressure test of pressure/vacuum relief vent valves shall be conducted within thirty (30) days after the start of operation of the (add type) Phase I EVR equipment and at least once every three (3) years thereafter to determine the pressure and vacuum at which the pressure/vacuum vent valve actuates, and to determine the volumetric leak rate at a given pressure. The test shall be conducted in accordance with the test procedure method TP-201.1E. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of test. This test result shall be kept on site for three (3) years and made available to district representatives upon request.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at (909) 396-2606 at least 72 hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the leak rate and cracking pressure of pressure/vacuum relief vent valves test.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

e). A static torque test of rotatable Phase I adaptors shall be conducted as a reverification test to quantify the amount of static torque required to start the rotation of the rotatable Phase I adaptors. The test shall be conducted in accordance with the test procedure method outlined in TP-201-1B.. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at (909) 396-2606 at least 72 hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the static torque test of rotatable Phase I adaptors.

f). The Phase II vapor recovery systems shall be installed, operated, and maintained such that the maximum allowable pressure through the system including nozzle, vapor hose, swivels, and underground piping does not exceed the dynamic back pressures described by the California Air Resources Board (CARB) Executive Order by which the system was certified:

Nitrogen Flowrates (CFH)	Dynamic Back Pressure (Inches of Water)
60	0.35
80	0.62

As required by AQMD Rule 461 or CARB Executive Order, dynamic back pressure tests shall be conducted to determine the Phase II system vapor recovery back pressures. The tests shall be conducted in accordance with CARB Test Procedure Method TP-201.4. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at R461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractors; the location of the facility; and the scheduled start and completion dates of the dynamic back pressure test.

The test shall be conducted as frequently as that required by the most recent amendment to Rule 461 or CARB Executive Order requirements, whichever is more stringent.

g). If the CARB Executive Order requires the installation of a liquid removal device, a liquid removal rate test shall be conducted to demonstrate the removal of gasoline from the vapor passage of the coaxial hose. The test shall be conducted within thirty days of initial installation and in accordance with CARB test procedure Method TP-201.6. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractors; the location of the facility; and the scheduled start and completion dates of the liquid removal rate test.

The testing frequency for the above mentioned tests shall be conducted in accordance with the most recent AQMD Rule 461 amendment or CARB Executive Order requirements, whichever is more stringent.



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All records and test results that are required to be maintained by Rule 461 shall be kept on site and made available to AQMD representatives upon request.

[RULE 461, 3-7-2008]

[Devices subject to this condition : D36, D40, D88, D89, D90]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

J397.1 The operator shall comply with the following CARB Executive Order G-70-193:

1. The owner or operator of this equipment shall conduct a physical inspection of the equipment and manually monitor the system gauge levels during gasoline dispensing on a daily operating basis per site. The equipment shall operate within the following gauge levels:

- | | |
|------------------------------|--------------------|
| a) Vapor return line vacuum: | 35" to 65" wc |
| b) Gasoline supply pressure: | 27 psig to 35 psig |
| c) Cargo tank pressure: | less than 18" wc |

All physical inspections and gauge observations shall be recorded in a systems log and be kept on board the mobile fueler at all times.

2. If a violation of the gauge ranges specified in conditions 1a, 1b, or 1c occurs, the owner or operator of this equipment shall:

- Record the date, time period, and fuel totalizing meter reading when the system first began to fail to operate within the specified range.
- Record the date and time that contact was made with an authorized representative to have the system inspected and repaired.
- Record the date and time that the authorized representative inspected the system, provide a written description of the repairs performed, and record the fuel totalizing meter reading.

3. This equipment shall cease all gasoline dispensing operations when any one of the following conditions occur:

- One of the jet pumps is disabled;
- Failing to achieve the minimum operating vacuum of 35" wc within five seconds after the system has been activated for three consecutive dispensing episodes;
- A vacuum level below 15" wc for more than three seconds after the system has reached 35" wc;
- A vacuum level above 85" wc during a dispensing episode to non-ORVR vehicles;
- Except during testing operations, a closed valve at the vapor return line connection to each jet pump;
- A pressure in the cargo tank headspace exceeding 18" wc for more than five minutes (accumulated) during any sixty minute gasoline dispensing period;
- Except during repair operations, an open drain valve in the liquid drop out pot;
- Except during testing operations, a closed drain valve at the liquid drop out pot in the liquid removal



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

line;

i) Any observation of breaks, cracks, or holes in the tank insulation, which affects the insulating properties or durability of the insulation;

j) The accumulated length of all tears of the nozzle boot (including rips, slits, cracks, etc.) exceeds 0.5" in length; or

k) The faceplate and fill pipe interface cannot achieve a seal of at least 25 percent of the accumulated circumference of the faceplate.

4. Within thirty (30) days of initial operation and at least once every twelve months from the previous test, a vapor return line vacuum integrity test shall be conducted and pass in accordance with Exhibit 3 of CARB Executive Order G-70-193. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within forty-eight (48) hours of test.

The AQMD shall be notified at telephone number (909) 396-3886 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator of this equipment; the name of the testing contractor; the location of the mobile fueler; and the scheduled start and completion dates of the vapor return line vacuum integrity test.

5. Within thirty (30) days of initial operation and at least once every twelve months from the previous test, a fill pipe pressure regulation fueling test shall be conducted and pass in accordance with Exhibit 4 of CARB Executive Order G-70-193. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within forty-eight (48) hours of test.

The AQMD shall be notified at telephone number (909) 396-3886 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator of this equipment; the name of the testing contractor; the location of the mobile fueler; and the scheduled start and completion dates of the fill pipe pressure regulation fueling test.

6. Within thirty (30) days of initial operation and at least once every twelve months from the previous test, a ten gallon per minute flowrate limitation test shall be conducted and pass in accordance with Exhibit 5 of CARB Executive Order G-70-193. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within forty-eight (48) hours of test.

The AQMD shall be notified at telephone number (909) 396-3886 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator of this equipment; the name of the testing contractor; the location of the mobile fueler; and the scheduled start and completion dates of the ten gallon per minute limitation test.

7. The individual and company performing any maintenance on any part of the vapor recovery system shall provide at a minimum for the owner or operator of the mobile fueler, a chronological record consisting of the following information for the mobile fueler's maintenance log. The date of service, name of maintenance technician, a contact phone number, a description of and location of any equipment replaced including appropriate test results, and a description of the system problems repaired.



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

9. Except for necessary inspections due to equipment failures, and for scheduled maintenance and repairs; the mobile fueler dome hatch shall remain closed and latched at all times. Furthermore, the mobile fueler dome hatch shall remain closed and latched until the head space pressure is less than 2" wc.
8. A current CARB certification decal shall be displayed on the mobile fueler in a manner approved by the executive officer.
10. All physical inspection and gauge observation records; all test results; and all maintenance records as required by this CARB Executive Order shall be prepared, shall be retained for two years, and shall be kept within the mobile fueler and made available to district representatives upon request.

[RULE 461, 3-7-2008]

[Devices subject to this condition : D147]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : E107]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the filter

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D21, D22, D24, C96, D165]

K67.3 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the water wash

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D20]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

date of operation, elapsed time in hours, and reason for operation

[RULE 1110.2, 6-3-2005; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 2005, 10-15-1993; RULE 2005, 4-9-1999]

[Devices subject to this condition : D115, D116, D119, D124, D125, D126, D127, D128, D129, D131, D133, D134, D146, D149, D159, D162, D163, D164, D169, D172, D173]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.5 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Purchase records of abrasive used or daily records of abrasives used and evidence of ARB certification

If abrasives are re-used, records to demonstrate that such abrasives are tested with CARB Method 371-A

Daily records of the description of items blasted to demonstrate compliance

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D44]

K67.6 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

All maintenance, monthly and annual gasoline dispensed records, shall be prepared, shall be retained for five years, and shall be kept within the mobile fueler and made available to District representatives upon request.

All daily inspection records shall be completed immediately after the daily inspection.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 10-20-2000; RULE 461, 3-7-2008]

[Devices subject to this condition : D147]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.8 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

The operator shall keep records in accordance with the requirements of rule 109 (record keeping for volatile organic compound emissions). Such records shall be retained for a period of three years and shall be made available to any district representative upon request.

Within 14 calendar days after the end of each month, the operator shall total and record VOC emissions for the month from all permitted equipment covered by the monthly limit. The record shall include any procedures used to account for control device efficiencies and/or waste disposal. It shall be signed and certified for accuracy by the highest ranking individual responsible for operation of equipment subject to the permit.

The operator shall maintain a single list which includes only the name and address of each person from whom the facility acquired VOC-containing material regulated by the district that was used or stored at the facility during the preceding 12 months.

The operator shall retain all purchase invoices for all VOC-containing material used or stored at the facility, and all waste manifest for all waste VOC containing material removed from the facility, for 36 months.

[RULE 109, 5-2-2003; RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D165]

K67.10 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the baghouse

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C158]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.11 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

copy of MSDS shall be kept for the abrasive material used in this equipment

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D156, D170]

K67.12 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

MSDS for the diesel fuel used in this equipment

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D172]

K67.13 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

The log shall list the date of operation, the timer reading in hours at the beginning and end of operation, and the reason for operation. The total hours of operation (include hours for manual and automatic operation) shall be recorded sometime during the first 15 days of January of each year.

[RULE 1110.2, 6-3-2005; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 2005, 10-15-1993; RULE 2005, 4-9-1999]

[Devices subject to this condition : D174]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.14 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

An engine operating log shall be kept and maintained on file to record when this engine is started manually. The log shall list the date of operation, the timer reading in hours at the beginning and end of operation, and the reason for operation for a minimum of five calendar years prior to the current year and made available to District personnel upon request. The total hours of operation (include hours for manual and automatic operation) shall be recorded sometime during the first 15 days of January

[RULE 1110.2, 6-3-2005; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 2005, 4-20-2001]

[Devices subject to this condition : D175, D176, D178, D182, D259]

K67.15 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

The hours of operation per year.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1401, 12-7-1990]

[Devices subject to this condition : D177]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.16 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

An engine operating log shall be maintained which on a monthly basis shall include manual and automatic operation and shall list all engine operations in each of the following areas:

EMERGENCY USE HOURS OF OPERATION.

MAINTENANCE AND TESTING HOURS.

OTHER OPERATING HOURS (DESCRIBE THE REASON FOR OPERATION).

In addition, each time the engine is started manually, the log shall include the date of operation and the timer reading in hours at the beginning and end of operation. The log shall be kept for a minimum of three calendar years prior to the current year and made available to District personnel upon request. The total hours of operation for the previous calendar year shall be recorded sometime during the first 15 days of January of each year.

[RULE 1110.2, 6-3-2005; **RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002; **RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996**; RULE 1470, 6-1-2007; **RULE 2005, 4-20-2001**]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D15, D95, D99, D153, D160, D168, D179, D180, D181, D183, D223]

K67.18 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Operating time records as required per conditions C1.14, C1.16, C1.17 and C1.18.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002; **RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005]

[Devices subject to this condition : D224, D225, D226, D227, D228, D229, D230, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D241, D242, D243, D244, D245, D246, D247, D248, D249, D250, D251, D252, D253, D254, D255, D256, D257, D258]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL					
HEATER, CPI, NO. 1, NATURAL GAS, FULTON, MODEL FT0400-C, WITH LOW NOX BURNER, 5.128 MMBTU/HR A/N: 478416 Permit to Construct Issued: 06/03/08	D260		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 24.57 LBS/MMSCF NATURAL GAS (1) [RULE 2012,5-6-2005] ; NOX: 20 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] ; PM: (9) [RULE 404,2-7-1986]	C1.19, C1.21, D12.4, D29.1, D29.2, E202.4, H23.9, H23.12
HEATER, CPI, NO. 2, NATURAL GAS, FULTON, MODEL FT0400-C, WITH LOW NOX BURNER, 5.128 MMBTU/HR A/N: 478417 Permit to Construct Issued: 06/03/08	D261		NOX: PROCESS UNIT**	CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 24.57 LBS/MMSCF NATURAL GAS (1) [RULE 2012,5-6-2005] ; NOX: 20 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] ; PM: (9) [RULE 404,2-7-1986]	C1.19, C1.21, D12.4, D29.1, D29.2, E202.4, H23.9, H23.12

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION H: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION H: DEVICE ID INDEX

Device Index For Section H			
Device ID	Section H Page No.	Process	System
D260	1	2	0
D261	1	2	0



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F1.1 The operator shall limit the material processed to no more than 2000 lb(s) in any one year.

For the purpose of this condition, material processed shall be defined as 1,1,1 trichloroethane.

[H&S 44300, 7-1-1988]

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 9-11-1998]

F14.2 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F48.1 The operator shall not operate at this facility non chain driven, uncontrolled charbroiler exceeding the opacity limits specified in Rule 401.

[RULE 401, 3-2-1984; RULE 401, 9-11-1998]

DEVICE CONDITIONS

C. Throughput or Operating Parameter Limits



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

C1.19 The operator shall limit the fuel usage to no more than 6.156 MM cubic feet in any one calendar month.

This limit shall be based on the total combined limit for equipment D260 and D261.

This equipment shall only use natural gas as a fuel.

The operator shall identify the primary and secondary heater fuel usage..

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D260, D261]

C1.21 The operator shall limit the fuel usage to no more than 2.637 MM cubic feet in any one calendar month.

This equipment shall only use natural gas as a fuel.

The operator shall identify the primary and secondary heater.

This condition only applies to the secondary heater.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D260, D261]

D. Monitoring/Testing Requirements

D12.4 The operator shall install and maintain a(n) non-resettable totalizing fuel flow meter to accurately indicate the fuel usage of the equipment.

[RULE 2012, 12-7-1995; RULE 2012, 4-9-1999]

[Devices subject to this condition : D260, D261]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D29.1 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
NOX emissions	District method 100.1	District-approved averaging time	Outlet
CO emissions	District method 100.1	District-approved averaging time	Outlet

A. SOURCE TESTING SHALL BE CONDUCTED WITHIN 30 DAYS AFTER ACHIEVING MAXIMUM PRODUCTION RATE AT WHICH THE EQUIPMENT WILL BE OPERATED, BUT NO LATER THAN 90 DAYS AFTER INITIAL START-UP

B. THE SOURCE TEST SHALL BE DONE TO VERIFY EMISSIONS LIMITS FOR NOX AND CO CO, 20 PPMV AND 50 PPMV RESPECTIVELY

C. THE TEST SHALL BE CONDUCTED FOR 15 MINUTES EACH WHILE OPERATING AT NORMAL LOAD, HIGH, LOW AND AVERAGE FIRING RATES

D. TWO COMPLETE COPIES OF SOURCE TEST REPORTS (INCLUDE THE APPLICATION NUMBER AND A COPY OF THE PERMIT IN THE REPORT) SHALL BE SUBMITTED TO THE DISTRICT (ADDRESSED TO SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, ATTN: ROY OLIVARES, P.O. BOX 4941, DIAMOND BAR, CA 91765). THE RESULTS IN WRITING SHALL BE SUBMITTED WITHIN 45 DAYS AFTER THE SOURCE TEST IS COMPLETED. IT SHALL INCLUDE, BUT NOT LIMITED TO EMISSIONS RATE IN POUNDS PER HOUR AND CONCENTRATION IN PPMV AT THE OUTLET OF THE HEATER

E. TESTING LABORATORY CERTIFIED BY THE CALIFORNIA AIR RESOURCES BOARD IN THE REQUIRED TEST METHODS FOR CRITERIA POLLUTANT TO BE MEASURED, AND IN COMPLIANCE WITH DISTRICT RULE 304 (NO CONFLICT OF INTEREST) SHALL CONDUCT THE TEST

F. SAMPLING FACILITIES SHALL COMPLY WITH THE ATTACHED AQMD "GUIDELINES FOR CONSTRUCTION OF SAMPLING AND TESTING FACILITIES", PURSUANT TO RULE 217.

[RULE 1146, 11-17-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 5-6-2005]

[Devices subject to this condition : D260, D261]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D29.2 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
CO emissions	District method 100.1	District-approved averaging time	Outlet

In lieu of the using the above test method for CO, the operator may choose to use a portable monitor as allowed per Rule 1146 (d)(4)

This test should be done at least once per year as per Rule 1146 (d)

[RULE 1146, 11-17-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 5-6-2005]

[Devices subject to this condition : D260, D261]

E. Equipment Operation/Construction Requirements

E202.4 The operator shall clean and maintain this equipment according to the following specifications:

Records shall be maintained of inspections and maintenance of the burners

The operator shall follow the procedures specified by the manufacturer to tune-up and maintain the combustion system (including but not limited to the burner and air/fuel control device) of this heater

Manufacturers maintenance procedures shall be kept by the operator and made available at the request of AQMD

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000; RULE 2005, 4-9-1999]

[Devices subject to this condition : D260, D261]

H. Applicable Rules



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

H23.9 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
CO	District Rule	1146

[RULE 1146, 11-17-2000]

[Devices subject to this condition : D260, D261]

H23.12 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
SOX	District Rule	431.1

[RULE 431.1, 6-12-1998]

[Devices subject to this condition : D260, D261]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under Section 129(e) of the Clean Air Act, this permit shall expire five years from the date that the initial Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:

(A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION K: TITLE V Administration

- (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
- (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

- 8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
 - (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

- 9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]
- 10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION K: TITLE V Administration

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]
12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]
13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]
14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION K: TITLE V Administration

commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION K: TITLE V Administration

EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for non-compliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 - Breakdown Provisions, or subdivision (i) of Rule 2004 - Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION K: TITLE V Administration

RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 - Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.
 - (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION K: TITLE V Administration

- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;
- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105
[3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000).
[3004(a)(12)]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION K: TITLE V Administration

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the Title V application file. [3004(a)(4)]



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations:

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1106.1	2-12-1999	Federally enforceable
RULE 1107	1-6-2006	Non federally enforceable
RULE 1107	11-9-2001	Federally enforceable
RULE 1110.2	6-3-2005	Non federally enforceable
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	7-13-2007	Non federally enforceable
RULE 1122	10-1-2004	Federally enforceable
RULE 1128	3-8-1996	Federally enforceable
RULE 1130.1	12-13-1996	Federally enforceable
RULE 1136	6-14-1996	Federally enforceable
RULE 1140	2-1-1980	Federally enforceable
RULE 1140	8-2-1985	Non federally enforceable
RULE 1145	12-3-2004	Non federally enforceable
RULE 1145	2-14-1997	Federally enforceable
RULE 1146	11-17-2000	Federally enforceable
RULE 1146.1	5-13-1994	Federally enforceable
RULE 1162	11-17-2000	Federally enforceable
RULE 1162	7-8-2005	Non federally enforceable
RULE 1168	1-7-2005	Non federally enforceable
RULE 1168	10-3-2003	Federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	2-1-2008	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(a)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(1)	10-20-2000	Non federally enforceable



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 1303(b)(1)-Modeling	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1304(a)-Modeling and Offset Exemption	6-14-1996	Federally enforceable
RULE 1401	12-7-1990	Non federally enforceable
RULE 1401	3-4-2005	Non federally enforceable
RULE 1401	8-18-2000	Non federally enforceable
RULE 1415	10-14-1994	Non federally enforceable
RULE 1470	6-1-2007	Non federally enforceable
RULE 1472	3-7-2008	Non federally enforceable
RULE 2005	10-15-1993	Federally enforceable
RULE 2005	2-14-1997	Federally enforceable
RULE 2005	4-20-2001	Federally enforceable
RULE 2005	4-9-1999	Federally enforceable
RULE 2005	5-6-2005	Federally enforceable
RULE 2012	1-7-2005	Federally enforceable
RULE 2012	12-5-2003	Federally enforceable
RULE 2012	5-6-2005	Federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	6-1-2007	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 2202	11-8-1996	Non federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	1-14-1982	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 431.1	6-12-1998	Federally enforceable
RULE 431.2	5-4-1990	Federally enforceable
RULE 431.2	9-15-2000	Non federally enforceable
H&S 44300	7-1-1988	Non federally enforceable
RULE 461	3-7-2008	Federally enforceable
RULE 461	6-3-2005	Federally enforceable
RULE 481	1-11-2002	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 82 Subpart F	5-14-1993	Federally enforceable



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1106.1 2-12-1999]

Except as otherwise provided in Rule 1106.1

- (1) Within the District, the operator shall not sell, offer for sale, solicit, apply, or require any other person to use in the District any pleasure craft coating with a VOC content in excess of the following limits, expressed as grams of VOC per liter of coating applied, less water and exempt solvents:

COATING	VOC LIMIT		
	On or After 7/1/94	On or After 2/12/99	On or After 1/1/2001
Topcoats			
Extreme High Gloss	490	650	490
High Gloss	420	420	420
Pretreatment Wash Primers	780	780	780
Finish Primer/Surfacer	420	600	420
High Build Primer Surfacer	340	340	340
Teak Primer	775	775	775
Antifoulant Coatings			
Aluminum Substrate	560	560	560
Other Substrates	150	400	330
Clear Wood Finishes			
Sealers	550	550	550
Varnishes	490	490	490
Others	420	420	420

In the case of any coating sold, offered for sale, or solicited for use, this prohibition shall only apply where it is designated anywhere on the container by any sticker or label affixed thereto, or where it is



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1106.1 2-12-1999]

indicated in any sales or advertising literature, that the coating may be used as, or is suitable for use as, a pleasure craft coating.

- (2) A person shall not apply pleasure craft coatings subject to the requirements of this rule with a coating containing carbon tetrachloride or any of the Group II exempt compounds as defined in paragraph (b)(4) of Rule 1106.1 except for: methylene chloride; perchloroethylene; cyclic, branched, or linear, completely methylated siloxanes (VMS); or parachlorobenzotrifluoride (PCBTF).



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 1-6-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 1-6-2006]

VOC LIMITS								
Less Water and Less Exempt Compounds								
Effective Dates, cont.								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.



FACILITY PERMIT TO OPERATE

DISNEYLAND RESORT

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-9-2001]**

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

<u>Coating</u>	LIMITS			
	Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds			
	<u>Air Dried</u>	<u>(lb/gal)</u>	<u>Baked</u>	<u>(lb/gal)</u>
General				
One-Component	275	(2.3)	275	(2.3)
Multi-Component	340	(2.8)	275	(2.3)
Military Specification	340	(2.8)	275	(2.3)
Etching Filler	420	(3.5)	420	(3.5)
Solar-Absorbent	420	(3.5)	360	(3.0)
Heat-Resistant	420	(3.5)	360	(3.0)
Extreme High-Gloss	420	(3.5)	360	(3.0)
Metallic	420	(3.5)	420	(3.5)
Extreme Performance	420	(3.5)	360	(3.0)
Prefabricated Architectural Component	420	(3.5)	275	(2.3)
Touch Up	420	(3.5)	360	(3.0)
Repair	420	(3.5)	360	(3.0)
Silicone Release	420	(3.5)	420	(3.5)
High Performance Architectural	420	(3.5)	420	(3.5)
Camouflage	420	(3.5)	420	(3.5)
Vacuum-Metalizing	420	(3.5)	420	(3.5)
Mold-Seal	420	(3.5)	420	(3.5)
High-Temperature	420	(3.5)	420	(3.5)
Electric-Insulating Varnish	420	(3.5)	420	(3.5)
Pan Backing	420	(3.5)	420	(3.5)
Pretreatment Coatings	420	(3.5)	420	(3.5)



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-9-2001]

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-8-1996]

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

**Grams of VOC Per Liter of Coating,
Less Water And Less Exempt Compounds**

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers	350						
Clear Wood Finishes							
Varnish	350						
Sanding Sealers	350						
Lacquer	680		550			275	
Concrete-Curing Compounds	350						
Dry-Fog Coatings	400						
Fire-proofing Exterior Coatings	350	450		350			
Fire-Retardant Coatings							
Clear	650						
Pigmented	350						
Flats	250				100		50
Graphic Arts (Sign) Coatings	500						
Industrial Maintenance							



AQMD

FACILITY PERMIT TO OPERATE

DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

Primers and Topcoats						
Alkyds	420					
Catalyzed Epoxy	420					
Bituminous Coatings	420					
Materials						
Inorganic Polymers	420					
Vinyl Chloride Polymers	420					
Chlorinated Rubber	420					
Acrylic Polymers	420					
Urethane Polymers	420					
Silicones	420					
Unique Vehicles	420					
Japans/Faux Finishing	350	700		350		
Coatings						
Magnesite Cement Coatings	600			450		
Mastic Coatings	300					
Metallic Pigmented Coatings	500					
Multi-Color Coatings	420		250			
Pigmented Lacquer	680		550		275	
Pre-Treatment Wash Primers	780					
Primers, Sealers, and	350					
Undercoaters						
Quick-Dry Enamels	400					
Roof Coatings	300					
Shellac						
Clear	730					
Pigmented	550					
Stains	350					
Swimming Pool Coatings						
Repair	650					
Other	340					
Traffic Coatings	250		150			
Waterproofing Sealers	400					
Wood Preservatives						
Below-Ground	350					
Other	350					

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-8-1996]**

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 7-13-2007]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 7-13-2007]

TABLE OF STANDARDS
VOC LIMITS
Grams of VOC Per Liter of Coating,
Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Bond Breakers	350							
Clear Wood Finishes	350					275		
Varnish	350					275		
Sanding Sealers	350					275		
Lacquer	680	550			275			
Clear Brushing Lacquer	680				275			
Concrete-Curing Compounds	350						100	
Concrete-Curing Compounds For Roadways and Bridges**	350							
Dry-Fog Coatings	400						150	
Fire-Proofing Exterior Coatings	450	350						
Fire-Retardant Coatings***								
Clear	650							
Pigmented	350							
Flats	250	100						50
Floor Coatings	420		100			50		
Graphic Arts (Sign) Coatings	500							
Industrial Maintenance (IM) Coatings	420			250		100		
High Temperature IM Coatings			420					
Zinc-Rich IM Primers	420		340			100		
Japans/Faux Finishing Coatings	700	350						
Magnesite Cement Coatings	600	450						
Mastic Coatings	300							
Metallic Pigmented Coatings	500							
Multi-Color Coatings	420	250						
Nonflat Coatings	250		150			50		
Nonflat High Gloss	250		150				50	



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 7-13-2007]**

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Pigmented Lacquer	680	550			275			
Pre-Treatment Wash Primers	780		420					
Primers, Sealers, and Undercoaters	350		200			100		
Quick-Dry Enamels	400		250			150	50	
Quick-Dry Primers, Sealers, and Undercoaters	350		200			100		
Recycled Coatings			250					
Roof Coatings	300		250		50			
Roof Coatings, Aluminum	500				100			
Roof Primers, Bituminous	350		350					
Rust Preventative Coatings	420		400			100		
Shellac								
Clear	730							
Pigmented	550							
Specialty Primers	350					250	100	
Stains	350		250				100	
Stains, Interior	250							
Swimming Pool Coatings								
Repair	650		340					
Other	340							
Traffic Coatings	250	150					100	
Waterproofing Sealers	400		250			100		
Waterproofing	400					100		
Concrete/Masonry Sealers								
Wood Preservatives								
Below-Ground	350							
Other	350							

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

** Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

*** The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 7-13-2007]

TABLE OF STANDARDS (cont.)
VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1130.1 12-13-1996]

Except as otherwise provided in Rule 1130.1

(1) VOC Content of Screen Printing Materials

The operator shall not apply to any substrate any screen printing material, excluding extreme performance screen printing materials, which contains, as applied, a total amount of VOC in excess of the limits specified in subparagraphs (1)(A), (1)(B), or (1)(C). The applicable VOC limit for a screen printing operation shall be determined by first looking for the product in subparagraph (1)(A). If the product is not listed in subparagraph (1)(A), look for the product's substrate in subparagraph (1)(B). If the substrate is not listed in subparagraph (1)(B), look for the applicable limit in subparagraph (1)(C).

In lieu of meeting the requirements in subparagraph (1)(C), the operator may comply with the requirements in paragraph (2) if the screen printing material qualifies for an extreme performance classification under subdivision (e) of Rule 1130.1.

(A) For screen printing coatings and inks used in the production of the following products:

<u>PRODUCT</u>	<u>VOC LIMIT</u>	
	grams per Liter of Coating (or Ink), Less water and Less Exempt Compounds	
	On and After December 13, 1996	
	<u>g/L</u>	<u>lbs/gal</u>
Chlorine Indicator	500	4.2
Containers	800	6.7
Electronic Circuit	850	7.1
Mechanically-Formed Products	800	6.7
Overlays	800	6.7
Polyethylene Products	800	6.7
Stained Glass Overlay	800	6.7
Sterilization Indicator	600	5.0
Sub-Printed Products	800	6.7
Water Slide Decals:		



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1130.1 12-13-1996]**

<u>PRODUCT</u>	VOC LIMIT	
	grams per Liter of Coating (or Ink), Less water and Less Exempt Compounds	
Opaque Inks	800	6.7
Clear Inks	800	6.7
Ceramic Decal Inks	800	6.7

- (B) For screen printing coatings and inks not regulated by subparagraph (1)(A) and which are applied to the following specified substrates:

<u>SUBSTRATE</u>	VOC LIMIT	
	grams per Liter of Coating (or Ink), Less water and Less Exempt Compounds	
	On and After December 13, 1996	
	<u>g/L</u>	<u>lbs/gal</u>
Ceramic	800	6.7
Fiberglass	600	5.0
Glass or Metal	600	5.0
Man-Made Textile	800	6.7
Unsealed Aluminum	800	6.7

If a substrate is regulated under more than one substrate category listed in subparagraph (1)(B), the category with the highest VOC limit shall apply.

- (C) For screen printing materials not regulated by the provisions in subparagraph (1)(A) or (1)(B), which have the following material classifications:

<u>SCREEN PRINTING MATERIAL</u>	VOC LIMIT
	grams per Liter of Coating (or Ink or Adhesive), Less water and Less Exempt Compounds



**FACILITY PERMIT TO OPERATE
 DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1130.1 12-13-1996]**

	<u>On and After December 13, 1996</u>	
	<u>g/L</u>	<u>lbs/gal</u>
Adhesive	400	3.3
Coating	400	3.3
Fine Detail Loose-leaf Binder Ink	745	6.2
Fluorescent Ink	540	4.5
High-VOC Serigraph Ink	800	6.7
Loose-leaf Binder Metallic Ink	745	6.2
Metallic Ink	400	3.3
Printing Ink	400	3.3
Resists	600	5.0
Scratch-Off Ink	800	6.7
Water-Slide Decal Adhesive	800	6.7

If a screen printing material is regulated under more than one screen printing material category listed in subparagraph (1)(C), the category with the highest VOC limit shall apply.

(2) VOC Content of Extreme Performance Screen Printing Materials.

The operator shall not apply any extreme performance screen printing material in excess of the limits specified below:

	VOC LIMIT Grams of VOC per Liter of Extreme Performance Screen Printing Material, Less Water and <u>Less</u> <u>Exempt Compounds</u>	
	<u>g/L</u>	<u>lbs/gal</u>
On and after July 9, 1993	800	6.7
On and after January 1, 2003	400	3.3

(3) Usage of High-VOC Serigraph Inks

The total usage of high-VOC serigraph inks, as defined in paragraph (b)(23) of Rule 1130.1, shall not exceed 10 percent, (by volume), of the total usage of screen



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1130.1 12-13-1996]

printing materials applied on all serigraphs at a facility, on a monthly basis, unless an approved emission control system is used to reduce emissions from high-VOC serigraph inks by an equivalent or greater level to that which would have been achieved by the use of an ink containing 3.3 pounds per gallon VOC (less water and exempt compounds). The required overall control efficiency of the emission control system shall be determined by the equation in paragraph (d)(1) of Rule 1130.1.



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1136 6-14-1996]

Except as otherwise provided in Rule 1136

- (a) The operator shall not apply any coating to a wood product which has a VOC content, including any VOC-containing material added to the original coating supplied by the manufacturer, which exceeds the applicable limit specified below:

<u>COATING</u>	<u>VOC LIMITS</u>			<u>On and After</u> <u>7/1/2005</u>
	Grams Per Liter (lb/gal) of Coating, [lbs VOC/lb of solids], Less Water and Less Exempt Compounds			
	<u>Current Limit</u>			
	<u>I</u>	<u>or</u>	<u>II</u>	
Clear Sealers	550 (4.6) [1.39]		680 (5.7) [3.36]	275 (2.3) [0.36]
Clear Topcoat	550 (4.6) [1.37]		275 (2.3) [0.35]	275 (2.3) [0.35]
Pigmented Primers, Sealers & Undercoats	550 (4.6) [1.06]		600 (5.0) [1.08]	275 (2.3) [0.21]
Pigmented Topcoats	550 (4.6) [1.10]		275 (2.3) [0.25]	275 (2.3) [0.25]

The operator shall use coatings on a wood product that comply with either all VOC limits in column I or all VOC limits in column II. The operator that applies a primer, sealer or undercoat, but not a topcoat, to a wood product, shall be subject to column I for that wood product.

- (2) Notwithstanding the requirements of clause (a)(1), an operator that applies a topcoat and a primer, sealer or undercoat to a shutter may, until July 1, 2005, choose to comply with the VOC limits specified below for that shutter:

<u>COATING</u>	<u>VOC LIMITS</u>
	Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids], Less Water and Less Exempt Compounds
Clear Sealers	275 (2.3) [0.36]
Clear Topcoat	680 (5.7) [2.99]
Pigmented Primers, Sealers & Undercoats	275 (2.3) [0.33]
Pigmented Topcoats	600 (5.0) [1.38]



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1136 6-14-1996]

(3)

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

<u>COATING</u>	<u>Current Limit</u>	<u>On and After</u>
		<u>7/1/2005</u>
Barrier Coat - Plastic Components	760 (6.3) [3.9]	275 (2.3) [0.28]
Composite Wood Edge Filler	550 (4.6) [1.15]	275 (2.3) [0.31]
Extreme Performance Coatings	420 (3.5) [0.51]	275 (2.3) [0.33]
Fillers	500 (4.2) [0.66]	275 (2.3) [0.18]
High-Solid Stains	550 (4.6) [1.23]	350 (2.9) [0.42]
Inks	500 (4.2) [0.96]	500 (4.2) [0.96]
Mold-Seal Coatings	750 (6.3) [4.2]	750 (6.3) [4.2]
Multi-Colored Coatings	685 (5.7) [2.6]	275 (2.3) [0.33]

VOC LIMITS

Grams Per Liter (lb/gal) of Material

<u>COATING</u>	<u>Current Limit</u>	<u>On and After</u>
		<u>7/1/2005</u>
Low-Solids Barrier Coat - Plastic Components	760 (6.3)	120 (1.0)
Low-Solid Stains, Toners, and Washcoats	480 (4.0)	120 (1.0)

Any coating subject to this rule that meets any of the three VOC limit formats (grams per liter, lb/gal, or lbs VOC/lb of solids) is in compliance with this subparagraph.

- (4) The VOC limit for japan coatings is 700 grams per liter of coatings, less water and exempt compounds, as applied.
- (b) A person shall not use a stripper on wood products unless:
- (1) it contains less than 350 grams of VOC per liter of material; or
 - (2) the VOC composite vapor pressure is 2 mm Hg (0.04 psia) or less at 20°C (68°F).



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1140 2-1-1980]**

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1140 8-2-1985]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1145 2-14-1997]

Except as otherwise provided in Rule 1145, the operator shall not apply on plastics, glass, or rubber any coatings which are applied with a VOC content in excess of the limits specified below:

COATING

VOC LIMITS
Less Water and Less Exempt
Compounds

	Current		On and After 1-1-98	
	g/L	lbs/gal	g/L	lbs/gal
General Coatings				
One-component	275	2.3	275	2.3
Two-component	420	3.5	420	3.5
Military Spec. Coating				
One-component	340	2.8	340	2.8
Two-component	420	3.5	420	3.5
Multi-Colored Coatings	685	5.7	685	5.7
Mold Seal Coatings	750	6.3	750	6.3
Vacuum Metalizing Coatings	800	6.7	800	6.7
Mirror Backing				
Curtain Coated	500	4.2	500	4.2
Roll Coated	430	3.6	430	3.6
Optical Coatings	800	6.7	800	6.7
Electric Dissipating Coatings and Shock-Free Coatings	800	6.7	360	3.0
Metallic Coatings	420	3.5	420	3.5



FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS [RULE 1162 11-17-2000]

The operator shall not use a polyester resin material in a polyester resin operation which has a monomer content in excess of the limits specified in the Table below.

Polyester Resin Materials	Monomer Content in Polyester Resin Materials as Applied (By Weight Percent)
General Purpose Polyester Resin	35
Corrosion-Resistant	48
Fire Retardant	42
High Strength	48
Clear Gel Coat	50
Pigmented Gel Coat	45



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1162 7-8-2005]

The operator shall not use polyester resin material in an open molding system, which has a monomer content in excess of the limits specified in the following Table.

Polyester Resin Materials	Monomer Percentage by Weight as Applied	
	Prior to 11-09-2001	Current Limits
Clear Gel Coat	50	-
For Marble Resins	-	40
For Other Resins	-	44
Pigmented Gel Coat	45	-
White and Off White	-	30
Non-White	-	37
Primer	-	28
Specialty Gel Coats	-	48
General Purpose Resin	35	-
Marble Resins	-	10 or (32 % as supplied, no fillers)
Solid Surface Resins	-	17
Tub/Shower Resins	-	24 or (35 % as supplied, no fillers)
Lamination Resins	-	31 or (35 % as supplied, no fillers)
Others	-	35
Fire Retardant Resin	42	38
Corrosion Resistant Resin	48	48
High Strength Resin	48	40



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 1-7-2005]**

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

Architectural Applications	Current VOC Limit*
Indoor Carpet Adhesives	50
Carpet Pad Adhesives	50
Outdoor Carpet Adhesives	150
Wood Flooring Adhesive	100
Rubber Floor Adhesives	60
Subfloor Adhesives	50
Ceramic Tile Adhesives	65
VCT and Asphalt Tile Adhesives	50
Dry Wall and Panel Adhesives	50
Cove Base Adhesives	50
Multipurpose Construction Adhesives	70
Structural Glazing Adhesives	100
Single Ply Roof Membrane Adhesives	250



AQMD

FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 1-7-2005]

Specialty Applications	VOC Limits and Effective Dates**			
	Current VOC Limit*	1-1-05	7-1-05	1-1-07
PVC Welding	510			
CPVC Welding	490			
ABS Welding	400		325	
Plastic Cement Welding	350	250		
Adhesive Primer for Plastic	650		550	
Computer Diskette Manufacturing	350			
Contact Adhesive	80			
Special Purpose Contact Adhesive	250			
Tire Retread	100			
Adhesive Primer for Traffic Marking Tape	150			
Structural Wood Member Adhesive	140			
Sheet Applied Rubber Lining Operations	850			
Top and Trim Adhesive	540			250

** The specified limits remain in effect unless revised limits are listed in subsequent columns.



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 1-7-2005]**

For adhesives, adhesive bonding primers, or any other primer not regulated by the above two tables and applied to the following substrates, the following limits shall apply:

Substrate Specific Applications	Current VOC Limit*
Metal to Metal	30
Plastic Foams	50
Porous Material (except wood)	50
Wood	30
Fiberglass	80

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

Sealants	Current VOC Limit*
Architectural	250
Marine Deck	760
Nonmembrane Roof	300
Roadway	250
Single-Ply Roof Membrane	450
Other	420



AQMD

FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 1-7-2005]

Sealant Primers	Current VOC Limit*
Architectural	
Non Porous	250
Porous	775
Modified Bituminous	500
Marine Deck	760
Other	750

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 10-3-2003]**

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

Architectural Applications	Current VOC Limit
Indoor Carpet Adhesives	50
Carpet Pad Adhesives	50
Outdoor Carpet Adhesives	150
Wood Flooring Adhesive	100
Rubber Floor Adhesives	60
Subfloor Adhesives	50
Ceramic Tile Adhesives	65
VCT and Asphalt Tile Adhesives	50
Dry Wall and Panel Adhesives	50
Cove Base Adhesives	50
Multipurpose Construction Adhesives	70
Structural Glazing Adhesives	100
Single Ply Roof Membrane Adhesives	250

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 10-3-2003]**

Specialty Applications	VOC Limits and Effective Dates**			
	Current VOC Limit	6-7-02	1-1-03	1-1-05
PVC Welding	510			285
CPVC Welding	490			270
ABS Welding	400			
Plastic Cement Welding	350			250
Adhesive Primer for Plastic	650			250
Computer Diskette Manufacturing	350			
Contact Adhesive	250		80	
Special Purpose Contact Adhesive	250			
Tire Retread	100			
Adhesive Primer for Traffic Marking Tape	150			
Structural Wood Member Adhesive	140			
Sheet Applied Rubber Lining Operations	850			
Top and Trim Adhesive	250	540		250

** The specified limits remain in effect unless revised limits are listed in subsequent columns.

Substrate Specific Applications	Current VOC Limit
Metal to Metal	30
Plastic Foams	50
Porous Material (except wood)	50



AQMD

FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 10-3-2003]

Substrate Specific Applications	Current VOC Limit
Wood	30
Fiberglass	80

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

Sealants	Current VOC Limit
Architectural	250
Marine Deck	760
Nonmembrane Roof	300
Roadway	250
Single-Ply Roof Membrane	450
Other	420

Sealant Primers	Current VOC Limit
Architectural	
Non Porous	250
Porous	775
Modified Bituminous	500
Marine Deck	760
Other	750



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-7-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-7-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)



AQMD

FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-7-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 2-1-2008]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 2-1-2008]

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	800 (6.7)		
(B) General Work Surfaces	600 (5.0)		
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)		
(D) Cleaning of Ink Application Equipment			
(i) General	25 (0.21)		
(ii) Flexographic Printing	25 (0.21)		
(iii) Gravure Printing			
(A) Publication	100 (0.83)		
(B) Packaging	25 (0.21)		
(iv) Lithographic (Offset) or Letter Press Printing			
(A) Roller Wash, Blanket Wash, & On-Press Components			
(I) Newsprint	100 (0.83)		



**FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 2-1-2008]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(II) Other Substrates	500 (4.2)	100 (0.83)	
(B) Removable Press Components	25 (0.21)		
(v) Screen Printing	500 (4.2)	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)		
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)		

* The specified limits remain in effect unless revised limits are listed in subsequent columns.



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 2-7-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 2-7-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 405 2-7-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process)		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process)	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9



FACILITY PERMIT TO OPERATE
DISNEYLAND RESORT

APPENDIX B: RULE EMISSION LIMITS
[RULE 405 2-7-1986]

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process)		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process)	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0