

FACILITY PERMIT TO OPERATE

**DELUXE LABORATORIES
1377 N SERRANO AVE
HOLLYWOOD, CA 90027**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By _____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

TABLE OF CONTENTS

| Section | Description | Revision # | Date Issued |
|----------|--|-----------------|-------------|
| A | Facility Information | DRAFT | 08/07/2012 |
| B | RECLAIM Annual Emission Allocation | DRAFT | 08/07/2012 |
| C | Facility Plot Plan | TO BE DEVELOPED | |
| D | Facility Description and Equipment Specific Conditions | DRAFT | 08/07/2012 |
| E | Administrative Conditions | DRAFT | 08/07/2012 |
| F | RECLAIM Monitoring and Source Testing Requirements | DRAFT | 08/07/2012 |
| G | Recordkeeping and Reporting Requirements for RECLAIM Sources | DRAFT | 08/07/2012 |
| H | Permit To Construct and Temporary Permit to Operate | DRAFT | 08/07/2012 |
| I | Compliance Plans & Schedules | DRAFT | 08/07/2012 |
| J | Air Toxics | DRAFT | 08/07/2012 |
| K | Title V Administration | DRAFT | 08/07/2012 |
| Appendix | | | |
| A | NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219 | DRAFT | 08/07/2012 |
| B | Rule Emission Limits | DRAFT | 08/07/2012 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR: DELUXE LABORATORIES

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION: 1377 N SERRANO AVE
 HOLLYWOOD, CA 90027-5623

MAILING ADDRESS: 9668 N SERRANO AVE
 HOLLYWOOD, CA 90027-5623

RESPONSIBLE OFFICIAL: MICHAEL GEORGE

TITLE: EVP & GENERAL MANAGER

TELEPHONE NUMBER: (323) 960-8401

CONTACT PERSON: RICK BROWN

TITLE: VICE PRESIDENT EH&S

TELEPHONE NUMBER: (323) 462-6171

TITLE V PERMIT ISSUED: October 01, 2006

TITLE V PERMIT EXPIRATION DATE: September 30, 2011

| TITLE V | RECLAIM |
|---------|---|
| YES | NOx: NO SOx: NO CYCLE: 0 ZONE: COASTAL |

**FACILITY PERMIT TO OPERATE
DELUXE LABORATORIES**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

NOT APPLICABLE

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

| Application number | Permit to Operate number | Equipment description |
|--------------------|--------------------------|-----------------------------------|
| A55606 | P35446 | FILM CLEANING MACHINE |
| A81276 | P58096 | FILM CLEANING MACHINE |
| C00859 | P66226 | FILM CLEANING MACHINE |
| C00860 | P66227 | FILM CLEANING MACHINE |
| C00861 | P66228 | FILM CLEANING MACHINE |
| 126382 | M42077 | MISC MATERIALS BLENDING |
| 126383 | M42078 | MISC MATERIALS BLENDING |
| 126384 | M42079 | MISC MATERIALS BLENDING |
| 126385 | M42080 | MISC MATERIALS BLENDING |
| 406439 | F56679 | WET-GATE FILM-PRINTING MACHINE |
| 406442 | F56678 | WET-GATE FILM-PRINTING MACHINE |
| 493510 | G14129 | ACTIVATED CARBON ADSORBER / REGEN |
| 516869 | | ICE |
| 535945 | | WET-GATE FILM-PRINTING MACHINE |
| 535947 | | WET-GATE FILM-PRINTING MACHINE |
| 535948 | | FILM CLEANING MACHINE |
| 535950 | | ACTIVATED CARBON ADSORBER / REGEN |
| 535952 | | FILM CLEANING MACHINE |
| 535953 | | FILM CLEANING MACHINE |
| 535954 | | FILM CLEANING MACHINE |
| 535955 | | FILM CLEANING MACHINE |

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.
[RULE 401]
2. THE OPERATOR SHALL NOT USE FUEL OIL CONTAINING SULFUR COMPOUNDS IN EXCESS OF 0.05 PERCENT BY WEIGHT.
[RULE 431.2]
3. AFTER JUNE 1, 2004, THE OPERATOR SHALL NOT PURCHASE ANY DIESEL FUEL UNLESS THE FUEL IS LOW SULFUR DIESEL FOR WHICH THE SULFUR CONTENT SHALL NOT EXCEED 15 PPM BY WEIGHT AS SUPPLIED BY THE SUPPLIER.
[RULE 431.2]
4. ALL FILM CLEANING MACHINES AT THIS FACILITY SHALL NOT BE OPERATED WITH PERCHLOROETHYLENE UNLESS THEY ARE VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1425]
5. THE TOTAL QUANTITY OF PERCHLOROETHYLENE EMISSIONS AT THIS FACILITY SHALL NOT EXCEED 6548 POUNDS IN ANY CALENDAR YEAR.
[AB-2588, CALIFORNIA H & S 44300]
6. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND EMISSIONS FROM THIS FACILITY EXCLUDING THE LIPSNER SMITH ULTRASONIC FILM CLEANING MACHINES UNDER A/Ns A55606, A81276, C00859, C00860 & C00861 SHALL NOT EXCEED 1944 POUNDS IN ANY CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
7. THE TOTAL QUANTITY OF VOC EMISSIONS FROM THE USE OF ALL VOC-CONTAINING MATERIALS IN EQUIPMENT OR PROCESSES SUBJECT TO RULE 442 AT THIS FACILITY SHALL NOT EXCEED 833 POUNDS IN ANY ONE CALENDAR MONTH. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH CALENDAR MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE CALENDAR MONTH FROM ALL EQUIPMENT AND OPERATIONS SUBJECT TO RULE 442 AT THE FACILITY.
[RULE 442]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

8. THE OPERATOR SHALL KEEP RECORDS IN ACCORDANCE WITH THE REQUIREMENTS OF RULE 109 (RECORDKEEPING FOR VOLATILE ORGANIC COMPOUND EMISSIONS) AND TO VERIFY COMPLIANCE WITH FACILITY WIDE CONDITION NOS. 5, 6 AND 7. SUCH RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED FOR A PERIOD OF FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
9. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC AND PERCHLOROETHYLENE EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS COVERED BY A LIMIT. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING MANAGEMENT OFFICIAL WITH RESPONSIBILITY FOR OPERATION OF EQUIPMENT SUBJECT TO THE PERMIT.
[RULE 1303(b)(2)-OFFSET]
10. THE OPERATOR SHALL RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL AND PERCHLOROETHYLENE USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL AND PERCHLOROETHYLENE REMOVED FROM THE FACILITY.
[RULE 1303(b)(2)-OFFSET]
11. THE OPERATOR SHALL MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL AND PERCHLOROETHYLENE REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

**Permit No. P35446
A/N A55606**

Equipment Description:

FILM CLEANING MACHINE, LIPSNER-SMITH, ULTRASONIC, SERIAL NO. 65-6021.

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 442
VOC: RULE 109

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No. P58096
A/N A81276

Equipment Description:

FILM CLEANING MACHINE, LIPSNER-SMITH, ULTRASONIC, SERIAL NO. 61-29.

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 442
VOC: RULE 109

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

**Permit No. P66226
A/N C00859**

Equipment Description:

FILM CLEANING MACHINE, LIPSNER-SMITH, ULTRASONIC TYPE, SERIAL NO. 7047, 5 GALLON SOLVENT CAPACITY.

Conditions:

1. PHOTOCHEMICALLY REACTIVE SOLVENT SHALL NOT BE USED IN THIS EQUIPMENT.
[RULE 442]

Emissions and Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 442
VOC: RULE 109

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

**Permit No. P66227
A/N C00860**

Equipment Description:

FILM CLEANING MACHINE, LIPSNER-SMITH, ULTRASONIC TYPE, SERIAL NO. 7047, 5 GALLON SOLVENT CAPACITY.

Conditions:

1. PHOTOCHEMICALLY REACTIVE SOLVENT SHALL NOT BE USED IN THIS EQUIPMENT.
[RULE 442]

Emissions and Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 442
VOC: RULE 109

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

**Permit No. P66228
A/N C00861**

Equipment Description:

FILM CLEANING MACHINE, LIPSNER-SMITH, ULTRASONIC, SERIAL NO. 7054, 5 GALLON SOLVENT CAPACITY.

Conditions:

1. PHOTOCHEMICALLY REACTIVE SOLVENT SHALL NOT BE USED IN THIS EQUIPMENT.
[RULE 442]

Emissions and Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 442
VOC: RULE 109

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No. M42077
A/N 126382

Equipment Description:

MIXING TANK, 5'-3" DIA. X 7'-4" H., 1000 GALLON CAPACITY, WITH A 1 1/2 HP AGITATOR.

Conditions:

1. MIXING TANK SHALL BE COVERED AT ALL TIMES EXCEPT WHEN ADDING INGREDIENTS AND TAKING SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

2. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST; AND EITHER:
 - A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION.
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS.
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

Emissions and Requirements:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No. M42078
A/N 126383

Equipment Description:

MIXING TANK, 5'-3" DIA. X 7'-4" H., 1,000 GALLON CAPACITY, WITH A 1 ½ HP AGITATOR.

Conditions:

1. MIXING TANK SHALL BE COVERED AT ALL TIMES EXCEPT WHEN ADDING INGREDIENTS AND TAKING SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

2. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST; AND EITHER:
 - A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

Emissions and Requirements:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No. M42079
A/N 126384

Equipment Description:

MIXING TANK, 3'-9" DIA. X 4'-5" H., 300 GALLON CAPACITY, WITH A 1 1/3 HP AGITATOR.

Conditions:

1. MIXING TANK SHALL BE COVERED AT ALL TIMES EXCEPT WHEN ADDING INGREDIENTS AND TAKING SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

2. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST; AND EITHER:
 - A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

Emissions and Requirements:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No. M42080
A/N 126385

Equipment Description:

MIXING TANK, 3'-9" DIA X 3'-4" H, 200 GALLON CAPACITY, WITH A 1/3 HP AGITATOR.

Conditions:

1. MIXING TANK SHALL BE COVERED AT ALL TIMES EXCEPT WHEN ADDING INGREDIENTS AND TAKING SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

2. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST; AND EITHER:
 - A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

Emissions and Requirements:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No. F56679
A/N 406439

Equipment Description:

WET-GATE FILM-PRINTING MACHINE NO. 13, OPTICAL TYPE, CUSTOM MADE, 1'-6" W. X 8'-6" L. X 8'-6" H., WITH ONE ELECTRICAL AIR HEATER, TWO 1/3 HP EXHAUST BLOWERS, AND ONE 1/3 HP SOLVENT PUMP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT EMIT TOXIC AIR CONTAMINANTS LISTED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF MAY 3, 2002 OR EARLIER EXCEPT FOR BENZENE, TOLUENE AND XYLENE.
[RULE 1401]
4. THE MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN 0.01% OF BENZENE.
[RULE 1401]
5. TOTAL QUANTITY OF COMBINED SOLVENT USAGE (LOSS) FOR THE WET GATE FILM-PRINTING EQUIPMENT UNDER APPLICATIONS 406439, AND 406442 SHALL NOT EXCEED 18 GALLONS PER CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
6. TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMITTED TO THE ATMOSPHERE FROM THIS PRINTING MACHINE SHALL BE LESS THAN 1 POUND PER DAY.
[RULE 1303(b)(2)-OFFSET]
7. THE OPERATOR SHALL MAINTAIN A LOG OF ALL SOLVENT ADDITIONS OR REMOVALS FROM THIS EQUIPMENT. THE LOG SHALL BE RETAINED FOR PERIOD OF FIVE YEARS AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 442

VOC: RULE 109

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

**Permit No. F56678
A/N 406442**

Equipment Description:

WET-GATE FILM-PRINTING MACHINE NO. 14, OPTICAL TYPE, CUSTOM MADE, 1'-6" W. X 8'-6" L. X 8'-6" H., WITH ONE ELECTRICAL AIR HEATER, TWO 1/3 HP EXHAUST BLOWERS, AND ONE 1/3 HP SOLVENT PUMP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL NOT EMIT TOXIC AIR CONTAMINANTS LISTED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF MAY 3, 2002 OR EARLIER EXCEPT FOR BENZENE, TOLUENE AND XYLENE.
[RULE 1401]
4. THE MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN 0.01% OF BENZENE.
[RULE 1401]
5. TOTAL QUANTITY OF COMBINED SOLVENT USAGE (LOSS) FOR THE WET GATE FILM-PRINTING EQUIPMENT UNDER APPLICATIONS 406439, AND 406442 SHALL NOT EXCEED 18 GALLONS PER CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
6. TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMITTED TO THE ATMOSPHERE FROM THIS PRINTING MACHINE SHALL BE LESS THAN 1 POUND PER DAY.
[RULE 1303(b)(2)-OFFSET]
7. THE OPERATOR SHALL MAINTAIN A LOG OF ALL SOLVENT ADDITIONS OR REMOVALS FROM THIS EQUIPMENT. THE LOG SHALL BE RETAINED FOR PERIOD OF FIVE YEARS AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 442
VOC: RULE 109

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

**Permit No. G14129
A/N 493510**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. CARBON ADSORBER, CROFTSHAW, REGENERATIVE ADSORBER TYPE, WITH FOUR CARBON CANISTERS IN PARALLEL, EACH 2'-10" DIA. X 4'-1" H. (INSIDE DIMENSIONS), EACH WITH 350 POUNDS OF CARBON, AND AN AUTOMATIC STEAM DESORPTION SYSTEM.
2. RECLAIMED SOLVENT TANK, DUAL COMPARTMENT, EACH WITH A 250-GALLON CAPACITY, AND ONE 3/4-HP TRANSFER PUMP.
3. EXHAUST SYSTEM WITH ONE 5-HP BOOSTER-AXIFLOW BLOWER, FOUR 3-HP EXHAUST BLOWERS AND ONE 7.5 H.P. STROBIC BOOSTER BLOWER VENTING TWELVE (IN ANY COMBINATION) FILM-CLEANING AND WET-GATE FILM-PRINTING MACHINES.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. WHENEVER THIS EQUIPMENT IS IN OPERATION AT LEAST THREE OF THE FOUR CARBON BEDS SHALL BE IN THE ADSORBING MODE, AND THE LOADING TIME SHALL NOT EXCEED EIGHTEEN HOURS.
[RULE 1303(a)(1)-BACT]
4. ONLY TWELVE OF ANY COMBINATION OF FILM-CLEANING AND FILM-PRINTING MACHINES SHALL BE VENTED TO THIS EQUIPMENT AT ANY ONE TIME.
[RULE 1303(a)(1)-BACT]
5. THIS EQUIPMENT SHALL BE MAINTAINED AND OPERATED AT A MINIMUM OVERALL CONTROL EFFICIENCY (COLLECTION AND REMOVAL) OF 90% WHEN THE BASIC EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(b)(2)-OFFSET, 1425]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

Periodic Monitoring:

6. THE OPERATOR SHALL MONITOR THE PERCHLOROETHYLENE CONCENTRATION AT THE INLET AND OUTLET OF THE CARBON ADSORBER ON A DAILY BASIS ACCORDING TO THE FOLLOWING SPECIFICATIONS:
- A. THE OPERATOR SHALL MONITOR THE INLET AND OUTLET OF THE CARBON ADSORBER SEQUENTIALLY IN THE SAME GENERAL TIME PERIOD.
 - B. THE OPERATOR SHALL MONITOR WHEN THE FILM CLEANING MACHINES AND/OR THE WET GATE PRINTERS ARE BEING VENTED TO THE CARBON ADSORBER.
 - C. THE OPERATOR SHALL USE A DISTRICT APPROVED VAPOR ANALYZER TO MONITOR THE PARAMETER.
 - D. THE MONITORING SHALL BE CONDUCTED TO DEMONSTRATE COMPLIANCE WITH RULE 1425 APPLICABLE LIMIT(S).
[RULE 3004(a)(4)]
7. THE OPERATOR SHALL CONDUCT SOURCE TEST(S) IN ACCORDANCE WITH THE FOLLOWING SPECIFICATIONS:
- A. THE TEST SHALL BE CONDUCTED AT LEAST ONCE DURING THE LIFE OF THE PERMIT.
 - B. THE TEST SHALL BE CONDUCTED NO LATER THAN JUNE 1, 2011 UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
 - C. THE TEST SHALL BE CONDUCTED TO DETERMINE THE VOC AND OR PERCHLOROETHYLENE EMISSIONS USING AN APPROVED DISTRICT METHOD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE PERMIT CONDITION(S), RULES AND REGULATIONS.
 - D. THE OPERATOR SHALL COMPLY WITH ADMINISTRATIVE CONDITIONS NOs. 8, 9, AND 10 OF SECTION E OF THIS FACILITY PERMIT.
 - E. THE OPERATOR SHALL SUBMIT TWO COMPLETE COPIES OF THE SOURCE TEST REPORT SPECIFIED IN CONDITION NO. 9 OF SECTION E OF THIS FACILITY PERMIT TO THE DISTRICT ENGINEERING AND COMPLIANCE DIVISION. THE ENGINEERING COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, COATING, PRINTING, PLATING, MILITARY & ENTERTAINMENT OPERATIONS, ATTN: AIR QUALITY AND COMPLIANCE SUPERVISOR, 21865 COPLEY DRIVE, DIAMOND BAR, CA 91765. THE COMPLIANCE COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, P.O. BOX 4941, DIAMOND BAR, CA 91765
[RULE 3004(a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- | | |
|--------------------|---|
| HAP: | RULE 40CFR63, SUBPART T, SEE SECTION J FOR REQUIREMENTS |
| PERCHLOROETHYLENE: | RULE 1425 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No.
A/N 516869

Equipment Description:

INTERNAL COMBUSTION ENGINE, MTU DETROIT DIESEL, DIESEL-FUELED, EMERGENCY ELECTRICAL GENERATOR, MODEL NO. 12V2000G85, TURBOCHARGED, 12 CYLINDERS, 1193 BHP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. A NON-RESETTABLE TOTALIZING TIMER SHALL BE INSTALLED AND MAINTAINED TO INDICATE THE ENGINE ELAPSED OPERATING TIME.
[RULE 1110.2, 1304(a)(4), 1470, 40CFR63 SUBPART ZZZZ]
4. THIS ENGINE SHALL NOT BE OPERATED MORE THAN 200 HOURS IN ANY ONE YEAR, WHICH INCLUDES NO MORE THAN 50 HOURS IN ANY ONE YEAR FOR MAINTENANCE.
[RULE 1110.2, 1304(a)(4), 1470, 40CFR60 SUBPART III]
5. OPERATING BEYOND THE 50 HOURS PER YEAR ALLOTTED FOR MAINTENANCE AND TESTING PURPOSES SHALL BE ALLOWED ONLY IN THE EVENT OF A LOSS OF GRID POWER OR UP TO 30 MINUTES PRIOR TO A ROTATING OUTAGE, PROVIDED THAT THE UTILITY DISTRIBUTION COMPANY HAS ORDERED ROTATING OUTAGES IN THE CONTROL AREA WHERE THE ENGINE IS LOCATED OR HAS INDICATED THAT IT EXPECTS TO ISSUE SUCH AN ORDER AT A CERTAIN TIME, AND THE ENGINE IS LOCATED IN A UTILITY SERVICE BLOCK THAT IS SUBJECT TO THE ROTATING OUTAGE. ENGINE OPERATION SHALL BE TERMINATED IMMEDIATELY AFTER THE UTILITY DISTRIBUTION COMPANY ADVISES THAT A ROTATING OUTAGE IS NO LONGER IMMINENT OR IN EFFECT.
[RULE 13404(a), 1470]
6. AN ENGINE OPERATING LOG SHALL BE KEPT AND, DOCUMENTING THE TOTAL TIME THE ENGINE IS OPERATED EACH MONTH AND SPECIFIC REASON FOR OPERATION AS:
 - A. EMERGENCY USE.
 - B. MAINTENANCE AND TESTING.
 - C. OTHER (DESCRIBE THE REASON FOR OPERATING).[RULE 1110.2, 1304(a)(4), 1470, 40CFR60 SUBPART III]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

7. IN ADDITION, EACH TIME THE ENGINE IS MANUALLY STARTED, THE LOG SHALL INCLUDE THE DATE OF OPERATION, THE SPECIFIC REASON FOR OPERATION, AND THE TOTALIZING HOUR METER READING (IN HOURS AND TENTHS OF HOURS) AT THE BEGINNING AND END OF OPERATION.
[RULE 1110.2, 1304(a)(4), 1470]
8. ON OR BEFORE JANUARY 15th OF EACH YEAR, THE OPERATOR SHALL RECORD IN THE ENGINE OPERATING LOG THE FOLLOWING:
 - A. THE TOTAL HOURS OF OPERATION FOR THE PREVIOUS CALENDAR YEAR, AND
 - B. THE TOTAL HOURS OF ENGINE OPERATION FOR MAINTENANCE AND TESTING FOR THE PREVIOUS CALENDAR YEAR.

THE ENGINE OPERATING LOG SHALL BE RETAINED ON SITE FOR A MINIMUM OF FIVE CALENDAR YEARS AND SHALL BE MADE AVAILABLE TO THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE UPON REQUEST.

[RULE 1303(b)(2)-OFFSET, 1110.2, 1470, 40CFR60 SUBPART III]

9. THE OPERATOR SHALL NOT USE ANY DIESEL FUEL UNLESS THE FUEL IS LOW SULFUR DIESEL FOR WHICH THE SULFUR CONTENT SHALL NOT EXCEED 15 PPM BY WEIGHT AS SUPPLIED BY THE SUPPLIER.
[RULE 431.2, 40CFR60 SUBPART III]
10. THIS ENGINE SHALL NOT BE USED AS PART OF A DEMAND RESPONSE PROGRAM USING INTERRUPTIBLE SERVICE CONTRACT IN WHICH A FACILITY RECEIVES A PAYMENT OR REDUCED RATES IN RETURN FOR REDUCING ITS ELECTRIC LOAD ON THE GRID WHEN REQUESTED TO SO BY THE UTILITY OR THE GRID OPERATOR.
[RULE 1470, 40CFR63 SUBPART ZZZZ]

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

| | |
|------------------------|--|
| NO _x + VOC: | 4.8 GRAMS/BHP-HR, RULE 1303(a)(1)-BACT, 40CFR60 SUBPART III |
| CO: | 2.6 GRAMS/BHP-HR, RULE 1303(a)(1)-BACT, 40CFR60 SUBPART III |
| PM: | 0.15 GRAMS/BHP-HR, RULE 1303(a)(1)-BACT, 1470, 40CFR60 SUBPART III |
| PM: | RULE 404, SEE APPENDIX B FOR EMISSION LIMITS |
| PM: | RULE 1472 |
| HAPS: | 40CFR63 SUBPART ZZZZ, SEE SECTION J FOR REQUIREMENTS |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No.
A/N 535945

Equipment Description:

WET-GATE FILM-PRINTING MACHINE NO. 4, CONTACT TYPE, CUSTOM MADE, 3'-0" W. X 8'-0" L. X 7'-0" H., WITH ONE ELECTRICAL AIR HEATER, ONE 1/3 HP EXHAUST BLOWER, AND ONE 2 HP HEATER BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL NOT USE ANY MATERIALS OTHER THAN PERCHLOROETHYLENE IN THIS EQUIPMENT.
[RULE 1401]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL ONLY OPERATE THIS EQUIPMENT USING THE PERMANENT TOTAL ENCLOSURE (PTE) WHICH IS MAINTAINED IN ACCORDANCE WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
6. THE OPERATOR SHALL MAINTAIN A LOG OF ALL SOLVENT ADDITIONS OR REMOVALS FROM THIS EQUIPMENT. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PERCHLOROETHYLENE: RULE 1425

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No.
A/N 535947

Equipment Description:

WET-GATE FILM-PRINTING MACHINE NO. 1, CONTACT TYPE, CUSTOM MADE, 3'-0" W. X 8'-0" L. X 7'-0" H., WITH ONE ELECTRICAL AIR HEATER, ONE 1/3 HP EXHAUST BLOWER, AND ONE 2 HP HEATER BLOWER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL NOT USE ANY MATERIALS OTHER THAN PERCHLOROETHYLENE IN THIS EQUIPMENT.
[RULE 1401]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL ONLY OPERATE THIS EQUIPMENT USING THE PERMANENT TOTAL ENCLOSURE (PTE) WHICH IS MAINTAINED IN ACCORDANCE WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
6. THE OPERATOR SHALL MAINTAIN A LOG OF ALL SOLVENT ADDITIONS OR REMOVALS FROM THIS EQUIPMENT. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PERCHLOROETHYLENE: RULE 1425

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO OPERATE

Permit No.
A/N 535948

Equipment Description:

FILM-CLEANING MACHINE, LIPSNER SMITH, ULTRASONIC-TYPE, MODEL CF3000- MK VI, WITH AN ELECTRIC AIR HEATER, REFRIGERATED CONDENSER COILS, AND A COMMON THREE STAGE SOLVENT PURIFICATION SYSTEM AND SOLVENT RECLAIMING TANK.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL NOT USE ANY MATERIALS OTHER THAN PERCHLOROETHYLENE IN THIS EQUIPMENT.
[RULE 1401]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL ONLY OPERATE THIS EQUIPMENT USING THE PERMANENT TOTAL ENCLOSURE (PTE) WHICH IS MAINTAINED IN ACCORDANCE WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
6. THE OPERATOR SHALL MAINTAIN A LOG OF ALL SOLVENT ADDITIONS OR REMOVALS FROM THIS EQUIPMENT. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

| | |
|--------------------|---|
| HAP: | RULE 40CFR63, SUBPART T, SEE SECTION J FOR REQUIREMENTS |
| PERCHLOROETHYLENE: | RULE 1425 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO CONSTRUCT

Permit No.
A/N 535950

Equipment Description:

MODIFICATION TO AIR POLLUTION CONTROL SYSTEM OPERATING UNDER PERMIT TO OPERATE NO. G14129 (A/N 511419) CONSISTING OF:

1. CARBON ADSORBER, CROFTSHAW, REGENERATIVE ADSORBER TYPE, FOUR CARBON CANISTERS, EACH 2'-10" DIA. X 4'-1" H. (INSIDE DIMENSIONS), EACH WITH 350 POUNDS OF CARBON, AND AN AUTOMATIC STEAM DESORPTION SYSTEM.
2. RECLAIMED SOLVENT TANK, DUAL COMPARTMENT, EACH WITH A 250-GALLON CAPACITY, AND ONE 3/4-HP TRANSFER PUMP.
3. EXHAUST SYSTEM WITH ONE 5-HP BOOSTER-AXIFLOW BLOWER, FOUR 3-HP EXHAUST BLOWERS AND ONE 7.5 H.P. STROBIC BOOSTER BLOWER VENTING TWELVE (IN ANY COMBINATION) FILM-CLEANING AND WET-GATE PRINTING MACHINES.

BY THE REMOVAL THE VENTING OF SEVEN FILM CLEANING MACHINES AND NINE WET-GATE FILM PRINTING MACHINES.

AND THE TOTAL VENTING OF FIVE FILM CLEANING MACHINES AND TWO WET-GATE PRINTING MACHINES.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL ONLY OPERATE THIS EQUIPMENT USING THE PERMANENT TOTAL ENCLOSURES (PTE) WHICH IS MAINTAINED IN COMPLIANCE WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
4. THE COMBINED PROCESS STREAM VENTED TO THIS AIR POLLUTION CONTROL SYSTEM SHALL BE LIMITED TO LESS THAN 700 CFM AT ANY ONE TIME.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

5. THE OPERATOR SHALL KEEP RECORDS TO DEMONSTRATE COMPLIANCE WITH CONDITION NO. 4 IN A FORMAT ACCEPTABLE TO THE DISTRICT. THE OPERATOR SHALL USE THE FOLLOWING FLOW RATES IN COMPUTING THE COMBINED PROCESS STREAM VENTED TO THE AIR POLLUTION CONTROL SYSTEM:

70 CFM FOR EACH FILM CLEANING MACHINE.

300 CFM FOR EACH WETGATE FILM PRINTING MACHINE.

[RULE 1303(a)(1)-BACT]

6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO SHOW COMPLIANCE WITH CONDITION NO. 5. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.

[RULE 1303(a)(1)-BACT]

7. THIS EQUIPMENT SHALL BE MAINTAINED AND OPERATED AT A MINIMUM OVERALL CONTROL EFFICIENCY (COLLECTION AND REMOVAL) OF 95% WHEN THE BASIC EQUIPMENT IT SERVES IS IN OPERATION.

[RULE 1303(b)(2)-OFFSET]

8. THE OPERATOR SHALL OPERATE AND MAINTAIN THIS EQUIPMENT ACCORDING TO THE FOLLOWING REQUIREMENTS:

THE OPERATOR SHALL OPERATE AND MAINTAIN A MONITORING SYSTEM CONSISTING OF A FLAME IONIZATION DETECTOR AND A DATA ACQUISITION SYSTEM TO CONTINUOUSLY MEASURE AND RECORD THE 30 MINUTE ROLLING AVERAGE CONCENTRATION OF PERCCHLOROETHYLENE (PERC) IN PPMV AT THE CARBON BED INLET AND OUTLET. THE OUTLET CONCENTRATION SHALL NOT EXCEED 5% OF THE INLET CONCENTRATION. SUCH A SYSTEM SHALL BE INSPECTED, MAINTAINED, AND CALIBRATED IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

FOR THE PURPOSE OF THIS CONDITION, A DEVIATION SHALL BE DEFINED AS WHEN THE 30 MINUTE ROLLING AVERAGE CONCENTRATION OF PERC AT THE CARBON BED OUTLET EXCEEDS 5% OF THE INLET CONCENTRATION DURING THE NORMAL OPERATION OF THE EQUIPMENT IT SERVES. THE OPERATOR SHALL REVIEW THE RECORDS OF THE CONCENTRATIONS ON A DAILY BASIS TO DETERMINE IF A DEVIATION OCCURS OR SHALL INSTALL AN ALARM SYSTEM TO ALERT THE OPERATOR WHEN A DEVIATION OCCURS.

WHENEVER A DEVIATION OCCURS, THE OPERATOR SHALL INSPECT THIS EQUIPMENT TO IDENTIFY THE CAUSE OF SUCH A DEVIATION, TAKE IMMEDIATE CORRECTIVE ACTION TO MAINTAIN THE OUTLET PERC CONCENTRATION AT OR BELOW 5% OF THE INLET CONCENTRATION, AND KEEP RECORDS OF THE DURATION AND CAUSE (INCLUDING UNKNOWN CAUSE, IF APPLICABLE) OF THE DEVIATION AND THE CORRECTIVE ACTION TAKEN.

ALL DEVIATIONS SHALL BE REPORTED TO THE AQMD PURSUANT TO THE REQUIREMENTS SPECIFIED IN 40 CFR PART 64.9 AND CONDITION NOS. 22 AND 23 IN SECTION K OF THIS PERMIT. THE MONITORING REPORT SHALL INCLUDE THE TOTAL OPERATING TIME OF THIS EQUIPMENT AND THE TOTAL ACCUMULATED DURATION OF ALL DEVIATIONS FOR EACH SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

THE OPERATOR SHALL SUBMIT AN APPLICATION WITH A QUALITY IMPROVEMENT PLAN (QIP) IN ACCORDANCE WITH 40 CFR PART 64.8 TO THE AQMD IF AN ACCUMULATION OF DEVIATIONS EXCEEDS 5 PERCENT DURATION OF THIS EQUIPMENT'S TOTAL OPERATING TIME FOR ANY SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT. THE REQUIRED QIP SHALL BE SUBMITTED TO THE AQMD WITHIN 90 CALENDAR DAYS AFTER THE DUE DATE FOR THE SEMI-ANNUAL MONITORING REPORT.

THE OPERATOR SHALL INSPECT AND MAINTAIN ALL COMPONENTS OF THIS EQUIPMENT ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

THE OPERATOR SHALL KEEP ADEQUATE RECORDS IN A FORMAT THAT IS ACCEPTABLE TO THE AQMD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE REQUIREMENTS SPECIFIED IN THIS CONDITION AND 40 CFR PART 64.9 FOR A MINIMUM OF FIVE YEARS.

[RULE 1303(A)(1)-BACT, 3004(A)(4)-PERIODIC MONITORING, 40CFR PART 64]

9. THE OPERATOR SHALL MAINTAIN RECORDS OF DATES OF CARBON REGENERATION AND REPLACEMENT, RETAIN SUCH RECORDS ON FILE FOR FIVE YEARS, AND MAKE THESE RECORDS AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT]
10. THE OPERATOR SHALL MAINTAIN RECORDS OF SOLVENT (CONTAINING PERCHLOROETHYLENE) USAGE IN ALL FILM PRINTING AND CLEANING OPERATIONS AT THIS FACILITY AS PER THE REQUIREMENTS OF RULE 1425 AND 109. THESE RECORDS SHALL BE RETAINED ON FILE AT THE FACILITY FOR A MINIMUM OF FIVE YEARS AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2) -OFFSET]
11. THE OWNER/OPERATOR OF THIS EQUIPMENT SHALL CONDUCT A SOURCE TEST(S) UNDER THE FOLLOWING CONDITIONS:
 - A. THE TEST SHALL BE CONDUCTED WITHIN 60 DAYS OF INITIAL START-UP OF THE NEW FILM CLEANERS BUT NOT LATER THAN 180 DAYS AFTER INITIAL START-UP, UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
 - B. A SOURCE TEST PROTOCOL SHALL BE SUBMITTED TO THE DISTRICT NO LATER THAN 30 DAYS AFTER THE INITIAL START-UP OF THIS EQUIPMENT UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT. THE TEST PROTOCOL SHALL BE APPROVED IN WRITING BY THE DISTRICT BEFORE THE TEST COMMENCES. THE TEST PROTOCOL SHALL INCLUDE THE COMPLETED DISTRICT FORMS ST-1 AND ST-2 SPECIFYING THE PROPOSED OPERATING CONDITIONS OF THE EQUIPMENT DURING THE TEST, THE IDENTITY OF THE TESTING LABORATORY, A STATEMENT FROM THE TESTING LABORATORY CERTIFYING IT MEETS THE CRITERIA IN DISTRICT RULE 304(K), AND A DESCRIPTION OF THE SAMPLING AND ANALYTICAL PROCEDURES TO BE USED.
 - C. THE TESTS SHALL CONSIST OF BUT NOT LIMITED TO, TESTING AT THE INLET AND THE EXHAUST OF THE CARBON ADSORPTION SYSTEM FOR:
 1. PERCHLOROETHYLENE EMISSIONS IN PPMV AND POUNDS PER HOUR.
 2. SYSTEM COLLECTION EFFICIENCY.
 3. ACTIVATED CARBON REMOVAL EFFICIENCY.
 4. FLOW RATES.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

5. USAGE OF ALL PERC-CONTAINING MATERIALS DURING THE TEST.
 6. OXYGEN CONTENT.
 7. MOISTURE CONTENT.
 8. FLOW RATE FROM EACH MACHINE.
 9. OUTLET FLOW RATES.
 10. TEMPERATURE.
 11. DEMONSTRATE THAT THE PTES MEET THE CRITERIA FOR PTE PURSUANT TO EPA METHOD 204.
- D. THE DISTRICT ENGINEER IDENTIFIED BELOW SHALL BE NOTIFIED OF THE DATE AND TIME OF THE TEST AT LEAST 10 DAYS PRIOR TO THE TEST, OR WITHIN A TIME PERIOD AGREED UPON BY THE DISTRICT ENGINEER.
- E. THE CONTINUOUS MONITORING SYSTEM READINGS SPECIFIED IN CONDITION NO.8 DURING THE TEST SHALL BE PROVIDED WITH THE SOURCE TEST RESULTS.
- F. THE SOURCE TEST SHALL BE CONDUCTED BY A TESTING LABORATORY CERTIFIED BY THE CALIFORNIA AIR RESOURCES BOARD IN THE REQUIRED TEST METHODS FOR EACH CRITERIA POLLUTANT TO BE MEASURED AND IN COMPLIANCE WITH DISTRICT RULE 304 (NO CONFLICT OF INTEREST).
- G. THE OPERATOR OF THIS EQUIPMENT SHALL SUBMIT THE RESULTS OF ALL PRELIMINARY TESTS THAT ARE CONDUCTED ON THIS EQUIPMENT FOR INFORMATIONAL PURPOSES TO THE DISTRICT WITHIN 45 DAYS AFTER THE TESTING DATE.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

12. THE OPERATOR SHALL CONDUCT SOURCE TEST(S) IN ACCORDANCE WITH THE FOLLOWING SPECIFICATIONS:
 - A. THE TEST SHALL BE CONDUCTED AT LEAST ONCE DURING THE LIFE OF THE PERMIT (EVERY FIVE YEARS).
 - B. THE TEST SHALL BE CONDUCTED NO LATER THAN NOVEMBER 1, 2016.
 - C. THE TEST SHALL BE CONDUCTED TO DETERMINE THE PERCHLOROETHYLENE EMISSIONS USING AN APPROVED DISTRICT METHOD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE PERMIT CONDITION(S), RULES AND REGULATIONS.
 - D. THE OPERATOR SHALL COMPLY WITH ADMINISTRATIVE CONDITIONS NOs. 8, 9, AND 10 OF SECTION E OF THIS FACILITY PERMIT.
 - E. THE OPERATOR SHALL SUBMIT TWO COMPLETE COPIES OF THE SOURCE TEST REPORT SPECIFIED IN CONDITION NO. 9 OF SECTION E OF THIS FACILITY PERMIT TO THE DISTRICT ENGINEERING AND COMPLIANCE DIVISION. THE ENGINEERING COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, COATING, PRINTING, PLATING, MILITARY & ENTERTAINMENT OPERATIONS, ATTN: AIR QUALITY AND COMPLIANCE SUPERVISOR, 21865 COPLEY DRIVE, DIAMOND BAR, CA 91765. THE COMPLIANCE COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, P.O. BOX 4941, DIAMOND BAR, CA 91765

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

[RULE 3004(a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

| | |
|--------------------|---|
| HAP: | RULE 40CFR63, SUBPART T, SEE SECTION J FOR REQUIREMENTS |
| PERCHLOROETHYLENE: | RULE 1425 |
| PM: | RULE 404, SEE APPENDIX B FOR EMISSION LIMITS |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO CONSTRUCT

Permit No.
A/N 535952

Equipment Description:

FILM-CLEANING MACHINE, LIPSNER SMITH, ULTRASONIC-TYPE, MODEL CF-7200, 3'-8" W. X 2'-9" D. X 6'-5" H., WITH AN ELECTRIC AIR HEATER, ONE 3.5-GALLONS CAPACITY CLEANING TANK, REFRIGERATED CONDENSER COILS, AND A COMMON THREE STAGE SOLVENT PURIFICATION SYSTEM AND SOLVENT RECLAIMING TANK.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL NOT USE ANY MATERIALS OTHER THAN PERCHLOROETHYLENE IN THIS EQUIPMENT.
[RULE 1401]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL ONLY OPERATE THIS EQUIPMENT USING THE PERMANENT TOTAL ENCLOSURE (PTE) WHICH IS MAINTAINED IN ACCORDANCE WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
6. THE OPERATOR SHALL MAINTAIN A LOG OF ALL SOLVENT ADDITIONS OR REMOVALS FROM THIS EQUIPMENT. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

**FACILITY PERMIT TO OPERATE
DELUXE LABORATORIES, INC**

PERCHLOROETHYLENE: RULE 1425
HAP: RULE 40CFR63, SUBPART T, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO CONSTRUCT

Permit No.
A/N 535953

Equipment Description:

FILM-CLEANING MACHINE, LIPSNER SMITH, ULTRASONIC-TYPE, MODEL CF-7200, 3'-8" W. X 2'-9" D. X 6'-5" H., WITH AN ELECTRIC AIR HEATER, ONE 3.5-GALLONS CAPACITY CLEANING TANK, REFRIGERATED CONDENSER COILS, AND A COMMON THREE STAGE SOLVENT PURIFICATION SYSTEM AND SOLVENT RECLAIMING TANK.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL NOT USE ANY MATERIALS OTHER THAN PERCHLOROETHYLENE IN THIS EQUIPMENT.
[RULE 1401]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL ONLY OPERATE THIS EQUIPMENT USING THE PERMANENT TOTAL ENCLOSURE (PTE) WHICH IS MAINTAINED IN ACCORDANCE WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
6. THE OPERATOR SHALL MAINTAIN A LOG OF ALL SOLVENT ADDITION OR REMOVAL FROM THIS EQUIPMENT. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

**FACILITY PERMIT TO OPERATE
DELUXE LABORATORIES, INC**

PERCHLOROETHYLENE: RULE 1425
HAP: RULE 40CFR63, SUBPART T, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO CONSTRUCT

Permit No.
A/N 535954

Equipment Description:

FILM-CLEANING MACHINE, LIPSNER SMITH, ULTRASONIC-TYPE, MODEL CF-3000 MK VI, 3'-8" W. X 2'-9" D. X 6'-5" H., WITH AN ELECTRIC AIR HEATER, ONE 3.5-GALLONS CAPACITY CLEANING TANK, REFRIGERATED CONDENSER COILS, AND A COMMON THREE STAGE SOLVENT PURIFICATION SYSTEM AND SOLVENT RECLAIMING TANK.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL NOT USE ANY MATERIALS OTHER THAN PERCHLOROETHYLENE IN THIS EQUIPMENT.
[RULE 1401]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL ONLY OPERATE THIS EQUIPMENT USING THE PERMANENT TOTAL ENCLOSURE (PTE) WHICH IS MAINTAINED IN ACCORDANCE WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
6. THE OWNER/OPERATOR SHALL MAINTAIN A LOG OF ALL SOLVENT ADDITION OR REMOVAL FROM THIS EQUIPMENT. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

**FACILITY PERMIT TO OPERATE
DELUXE LABORATORIES, INC**

PERCHLOROETHYLENE: RULE 1425
HAP: RULE 40CFR63, SUBPART T, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

PERMIT TO CONSTRUCT

Permit No.
A/N 535955

Equipment Description:

FILM-CLEANING MACHINE, LIPSNER SMITH, ULTRASONIC-TYPE, MODEL CF-3000 MK VI, 3'-8" W. X 2'-9" D. X 6' .5" H., WITH AN ELECTRIC AIR HEATER, ONE 3.5-GALLONS CAPACITY CLEANING TANK, REFRIGERATED CONDENSER COILS, AND A COMMON THREE STAGE SOLVENT PURIFICATION SYSTEM AND SOLVENT RECLAIMING TANK.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL NOT USE ANY MATERIALS OTHER THAN PERCHLOROETHYLENE IN THIS EQUIPMENT.
[RULE 1401]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL ONLY OPERATE THIS EQUIPMENT USING THE PERMANENT TOTAL ENCLOSURE (PTE) WHICH IS MAINTAINED IN ACCORDANCE WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
6. THE OPERATOR SHALL MAINTAIN A LOG OF ALL SOLVENT ADDITION OR REMOVAL FROM THIS EQUIPMENT. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

**FACILITY PERMIT TO OPERATE
DELUXE LABORATORIES, INC**

PERCHLOROETHYLENE: RULE 1425
HAP: RULE 40CFR63, SUBPART T, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

[RULE 3004 (a) (4)]

Emissions and Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, ADHESIVE APPLICATION, LOW USE OR EMISSIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 109

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, BOILERS, ≥ 0.4 MMBTU/HR BUT < 2 MMBTU/HR.

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: 0.1 gr/scf, RULE 409
NOx: 30 PPMV, RULE 1146.2
CO: 400 PPMV, RULE 1146.2
CO: 2000 PPMV, RULE 407

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, FIRE EXTINGUISHING EQUIPMENT

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

HALON: RULE 1418

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

REFRIGERANT: RULE 1415
REFRIGERANT: 40CFR 82 SUBART F

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COOLING TOWERS

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

Cr⁺⁶: RULE 1404

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statutes of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]
7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]
 - d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO₂) and be averaged over 15 consecutive minutes; [407]
 - e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO₂) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION E: ADMINISTRATIVE CONDITIONS

- f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O₂) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]
8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
 - a. Brief description of the equipment tested.
 - b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).
9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]
 - a. The results of the source test.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION E: ADMINISTRATIVE CONDITIONS

- b. Brief description of the equipment tested.
 - c. Operating conditions under which the test was performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Field and laboratory data forms, strip charts and analyses.
 - f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]
 11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

**FACILITY PERMIT TO OPERATE
DELUXE LABORATORIES**

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
DELUXE LABORATORIES**

**SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR
RECLAIM SOURCES**

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
DELUXE LABORATORIES, INC**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

See Section D of this permit for any Permit to Construct issued to this facility.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION J: AIR TOXICS [40CFR 63 Subpart T, # 32 12-03-1999]

CONTINUOUS WEB CLEANING SECTION 63.463 g(1) THROUGH (g)(4)

In lieu of meeting the requirements of 63.463 (a)(1) through (7) or (c)(1) or (2) or (d)(1) through (d)(12), the operator shall meet Section 63.463(g).

- (g) Except as provided in Sec. 63.464 and in paragraph (h) of this section for remote reservoir continuous web cleaning machines, each owner or operator of a continuous web cleaning machine shall comply with paragraphs (g)(1) through (4) of this section for each continuous web cleaning machine.
- (1) Except as provided in paragraph (g)(2) of this section, install, maintain, and operate one of the following control combinations on each continuous web cleaning machine.
 - (i) For each existing continuous web cleaning machine, the following control combinations are allowed:
 - (A) Superheated vapor or superheated part technology, and a freeboard ratio of 1.0 or greater.
 - (B) Freeboard refrigeration device and a freeboard ratio of 1.0 or greater.
 - (C) Carbon adsorption system meeting the requirements of paragraph(e)(2)(vii) of this section.
 - (ii) For each new continuous web cleaning machine, the following control combinations are allowed:
 - (A) Superheated vapor or superheated part technology, and a freeboard refrigeration device.
 - (B) A freeboard refrigeration device and a carbon adsorber meeting the requirements of paragraph (e)(2)(vii) of this section.
 - (C) Superheated vapor or superheated part technology, and a carbon adsorber meeting the requirements of paragraph (e)(2)(vii) of this section.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION J: AIR TOXICS [40CFR 63 Subpart T, # 32 12-03-1999]

- (2) If a carbon adsorber system can be demonstrated to the Administrator's satisfaction to have an overall solvent control efficiency (i.e., capture efficiency removal efficiency) of 70 percent or greater, this system is equivalent to the options in paragraph (g) of this section.
- (3) In lieu of complying with the provisions of paragraph (a) of this section, the owner or operator of a continuous web cleaning machine shall comply with the following provisions:
- (i) Each cleaning machine shall meet one of the following control equipment or technique requirements:
 - (A) An idling and downtime mode cover, as described in paragraph (d)(1)(i) of this section, that may be readily opened or closed; that completely covers the cleaning machine openings when in place; and is free of cracks, holes, and other defects. A continuous web part that completely occupies an entry or exit port when the machine is idle is considered to meet this requirement.
 - (B) A reduced room draft as described in paragraph (e)(2)(ii) of this section.
 - (C) Gasketed or leakproof doors that separate both the continuous web part feed reel and take-up reel from the room atmosphere if the doors are checked according to the requirements of paragraph (e)(2)(iii) of this section.
 - (D) A cleaning machine that is demonstrated to the Administrator's satisfaction to be under negative pressure during idling and downtime and is vented to a carbon adsorption system that meets the requirements of either paragraph (e)(2)(vii) of this section or paragraph (g)(2) of this section.
 - (ii) Each continuous web cleaning machine shall have a freeboard ratio of 0.75 or greater unless that cleaning machine is a remote reservoir continuous web cleaning machine.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION J: AIR TOXICS [40CFR 63 Subpart T, # 32 12-03-1999]

- (iii) Each cleaning machine shall have an automated parts handling system capable of moving parts or parts baskets at a speed of 3.4 meters per minute (11 feet per minute) or less from the initial loading of parts through removal of cleaned parts, unless the cleaning machine is a continuous web cleaning machine that has a squeegee system or air knife system installed, maintained, and operated on the continuous web cleaning machine meeting the requirements of paragraph (e) of this section.
 - (iv) Each vapor cleaning machine shall be equipped with a device that shuts off the sump heat if the sump liquid solvent level drops to the sump heater coils.
 - (v) Each vapor cleaning machine shall be equipped with a vapor level control device that shuts off sump heat if the vapor level in the vapor cleaning machine rises above the height of the primary condenser.
 - (vi) Each vapor cleaning machine shall have a primary condenser.
 - (vii) Each cleaning machine that uses an exhaust shall be designed and operated to route all collected solvent vapors through a properly operated and maintained carbon adsorber that meets the requirements of paragraph (e)(2)(ii) of this section.
- (4) In lieu of complying with the provisions of paragraph (d) of this section, the owner or operator of a continuous web cleaning machine shall comply with the following provisions:
- (i) Control air disturbances across the cleaning machine opening(s) by incorporating one of the following control equipment or techniques:
 - (A) Cover(s) to each solvent cleaning machine shall be in place during the idling mode and during the downtime mode unless either the solvent has been removed from the machine or maintenance or monitoring is being performed that requires the cover(s) in place. A continuous web part that completely occupies an entry or exit port when the machine is idle is considered to meet this requirement.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION J: AIR TOXICS [40CFR 63 Subpart T, # 32 12-03-1999]

- (B) A reduced room draft as described in paragraph (e)(2)(ii) of this section.
- (C) Gasketed or leak proof doors or covers that separate both the continuous web part feed reel and take-up reel from the room atmosphere if the doors are checked according to the requirements of paragraph (e)(2)(iii) of this section.
- (D) A cleaning machine that is demonstrated to the Administrator's satisfaction to be under negative pressure during idling and downtime and is vented to a carbon adsorption system that meets either the requirements of paragraph (e)(2)(vii) of this section or paragraph (g)(2) of this section.
 - (ii) Any spraying operations shall be conducted in a section of the solvent cleaning machine that is not directly exposed to the ambient air (i.e., a baffled or enclosed area of the solvent cleaning machine) or within a machine having a door or cover that meets the requirements of paragraph (g)(4)(i)(C) of this section.
 - (iii) During startup of each vapor cleaning machine, the primary condenser shall be turned on before the sump heater.
 - (iv) During shutdown of each vapor cleaning machine, the sump heater shall be turned off and the solvent vapor layer [[Page 67801]] allowed to collapse before the primary condenser is turned off.
 - (v) When solvent is added or drained from any solvent cleaning machine, the solvent shall be transferred using threaded or other leak proof couplings, and the end of the pipe in the solvent sump shall be located beneath the liquid solvent surface.
 - (vi) Each solvent cleaning machine and associated controls shall be maintained as recommended by the manufacturers of the equipment or using alternative maintenance practices that have been demonstrated to the Administrator's satisfaction to achieve the same or better results as those recommended by the manufacturer.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION J: AIR TOXICS [40CFR 63 Subpart T, # 32 12-03-1999]

- (vii) Waste solvent, still bottoms, sump bottoms, and waste absorbent materials used in the cleaning process for continuous web cleaning machines shall be collected and stored in waste containers. The closed containers may contain a device that would allow pressure relief, but would not allow liquid solvent to drain from the container.
- (viii) Except as provided in paragraph (g)(4)(ix) of this section, sponges, fabric, wood, and paper products shall not be cleaned.
- (ix) The prohibition in paragraph (g)(4)(viii) of this section does not apply to absorbent materials that are used as part of the cleaning process of continuous web cleaning machines, including rollers and roller covers.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION J: AIR TOXICS [40CFR 63 Subpart ZZZZ 01-18-2008]

NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS: STATIONARY RECIPROCATING INTERNAL COMBUSTION ENGINES

The owner/operator of stationary Reciprocating Internal Combustion Engines (RICE) located at major or area sources of hazardous air pollutant (HAP) emissions shall comply with the applicable requirements of 40 CFR 63 Subpart ZZZZ including but not limited to the following:

1. The owner/operator of existing, new or reconstructed stationary RICE shall comply with emission and operating limitation requirements as specified in §63.6600 and §63.6601 at all times except during periods of startups, shutdowns, and malfunctions. The owner/operator shall also comply with requirements of the General Provisions (40 CFR 63 Subpart A) as specified in §63.6665.
2. The owner/operator shall operate and maintain a stationary RICE, including air pollution control and monitoring equipment in a manner consistent with good air pollution control practices for minimizing emissions at all times, including during startup, shutdown and malfunction pursuant to §63.6605.
3. The owner/operator shall demonstrate initial compliance as specified in §63.6610 and §63.6611, and subsequent performance tests and other procedures as specified in §63.6615 and §63.6620.
4. The owner/operator shall comply with monitoring, installation, operation, and maintenance requirements as specified in §63.6625 and §63.660.
5. The owner/operator shall monitor and collect data to demonstrate continuous compliance with emission and operating limitations as specified in §63.6635 and §63.6640.
6. The owner/operator shall sent notifications and reports as specified in §63.6645 and §63.6650. Also, the owner/operator shall keep records as specified in §63.6655.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]

15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]

16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

| RULE SOURCE | Adopted/Amended Date | FEDERAL Enforceability |
|------------------------|-----------------------------|-------------------------------|
| RULE 109 | 5-2-2003 | Federally enforceable |
| RULE 1110.2 | 7-9-2010 | Non federally enforceable |
| RULE 1113 | 11-8-1996 | Federally enforceable |
| RULE 1113 | 6-3-2011 | Non federally enforceable |
| RULE 1146.2 | 5-5-2006 | Federally enforceable |
| RULE 1168 | 1-7-2005 | Non federally enforceable |
| RULE 1168 | 10-3-2003 | Federally enforceable |
| RULE 1171 | 11-7-2003 | Federally enforceable |
| RULE 1171 | 5-1-2009 | Non federally enforceable |
| RULE 118 | 12-7-1995 | Non federally enforceable |
| RULE 1303(a)(1)-BACT | 5-10-1996 | Federally enforceable |
| RULE 1303(b)(2)-Offset | 5-10-1996 | Federally enforceable |
| RULE 1401 | 12-7-1990 | Non federally enforceable |
| RULE 1401 | 5-2-2003 | Non federally enforceable |
| RULE 1401 | 9-10-2010 | Non federally enforceable |
| RULE 1404 | 4-6-1990 | Non federally enforceable |
| RULE 1415 | 12-3-2010 | Non federally enforceable |
| RULE 1418 | 9-10-1999 | Non federally enforceable |
| RULE 1425 | 3-16-2001 | Non federally enforceable |
| RULE 1470 | 5-4-2012 | Non federally enforceable |
| RULE 204 | 10-8-1993 | Federally enforceable |
| RULE 217 | 1-5-1990 | Federally enforceable |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration

| RULE SOURCE | Adopted/Amended Date | FEDERAL Enforceability |
|-------------------------------------|-----------------------------|-------------------------------|
| RULE 219 | 6-1-2007 | Non federally enforceable |
| RULE 219 | 9-4-1981 | Federally enforceable |
| RULE 2202 | 11-8-1996 | Non federally enforceable |
| RULE 3002 | 11-14-1997 | Federally enforceable |
| RULE 3002 | 11-5-2010 | Non federally enforceable |
| RULE 3003 | 11-14-1997 | Federally enforceable |
| RULE 3003 | 11-5-2010 | Non federally enforceable |
| RULE 3004 | 12-12-1997 | Federally enforceable |
| RULE 3004(a)(4)-Periodic Monitoring | 12-12-1997 | Federally enforceable |
| RULE 3005 | 11-14-1997 | Federally enforceable |
| RULE 3005 | 11-5-2010 | Non federally enforceable |
| RULE 3007 | 10-8-1993 | Federally enforceable |
| RULE 304 | 5-6-2011 | Non federally enforceable |
| RULE 401 | 11-9-2001 | Non federally enforceable |
| RULE 401 | 3-2-1984 | Federally enforceable |
| RULE 402 | 5-7-1976 | Non federally enforceable |
| RULE 404 | 2-7-1986 | Federally enforceable |
| RULE 405 | 2-7-1986 | Federally enforceable |
| RULE 407 | 4-2-1982 | Federally enforceable |
| RULE 408 | 5-7-1976 | Federally enforceable |
| RULE 409 | 8-7-1981 | Federally enforceable |
| RULE 430 | 7-12-1996 | Non federally enforceable |
| RULE 431.2 | 5-4-1990 | Federally enforceable |
| RULE 431.2 | 9-15-2000 | Non federally enforceable |
| RULE 442 | 12-15-2000 | Federally enforceable |
| RULE 63 Subpart T | 5-3-2007 | Federally enforceable |
| RULE 701 | 6-13-1997 | Federally enforceable |
| H&S 44300 | 7-1-1988 | Non federally enforceable |
| 40CFR 60SubpartIII | 6-28-2011 | Federally enforceable |
| 40CFR 63 Subpart T, # 32 | 12-3-1999 | Federally enforceable |
| 40CFR 63 Subpart ZZZZ | 1-18-2008 | Federally enforceable |
| 40CFR 82 Subpart F | 5-14-1993 | Federally enforceable |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

SECTION K: TITLE V Administration

| RULE SOURCE | Adopted/Amended Date | FEDERAL Enforceability |
|--------------------|-----------------------------|-------------------------------|
| 40CFR Part 64 | 10-22-1997 | Federally enforceable |

**FACILITY PERMIT TO OPERATE
DELUXE LABORATORIES**

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN
PERMIT PURSUANT TO RULE 219

NONE

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-08-1996]

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

| COATING | Limit* | Effective Date of Adoption | Effective 1/1/1998 | Effective 1/1/1999 | Effective 7/1/2001 | Effective 1/1/2005 | Effective 7/1/2008 |
|------------------------------------|--------|----------------------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Bond Breakers | 350 | | | | | | |
| Clear Wood Finishes | | | | | | | |
| Varnish | 350 | | | | | | |
| Sanding Sealers | 350 | | | | | | |
| Lacquer | 680 | | 550 | | | 275 | |
| Concrete-Curing Compounds | 350 | | | | | | |
| Dry-Fog Coatings | 400 | | | | | | |
| Fire-proofing Exterior Coatings | 350 | 450 | | 350 | | | |
| Fire-Retardant Coatings | | | | | | | |
| Clear | 650 | | | | | | |
| Pigmented | 350 | | | | | | |
| Flats | 250 | | | | 100 | | 50 |
| Graphic Arts (Sign) Coatings | 500 | | | | | | |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-08-1996]

| | | | | | | |
|-----------------------------|-----|-----|-----|-----|-----|--|
| Industrial Maintenance | | | | | | |
| Primers and Topcoats | | | | | | |
| Alkyds | 420 | | | | | |
| Catalyzed Epoxy | 420 | | | | | |
| Bituminous Coatings | 420 | | | | | |
| Materials | | | | | | |
| Inorganic Polymers | 420 | | | | | |
| Vinyl Chloride Polymers | 420 | | | | | |
| Chlorinated Rubber | 420 | | | | | |
| Acrylic Polymers | 420 | | | | | |
| Urethane Polymers | 420 | | | | | |
| Silicones | 420 | | | | | |
| Unique Vehicles | 420 | | | | | |
| Japans/Faux Finishing | 350 | 700 | | 350 | | |
| Coatings | | | | | | |
| Magnesite Cement Coatings | 600 | | | 450 | | |
| Mastic Coatings | 300 | | | | | |
| Metallic Pigmented Coatings | 500 | | | | | |
| Multi-Color Coatings | 420 | | 250 | | | |
| Pigmented Lacquer | 680 | | 550 | | 275 | |
| Pre-Treatment Wash Primers | 780 | | | | | |
| Primers, Sealers, and | 350 | | | | | |
| Undercoaters | | | | | | |
| Quick-Dry Enamels | 400 | | | | | |
| Roof Coatings | 300 | | | | | |
| Shellac | | | | | | |
| Clear | 730 | | | | | |
| Pigmented | 550 | | | | | |
| Stains | 350 | | | | | |
| Swimming Pool Coatings | | | | | | |
| Repair | 650 | | | | | |
| Other | 340 | | | | | |
| Traffic Coatings | 250 | | 150 | | | |
| Waterproofing Sealers | 400 | | | | | |
| Wood Preservatives | | | | | | |
| Below-Ground | 350 | | | | | |
| Other | 350 | | | | | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

| COATING | Limit |
|--------------------|-------|
| Low-Solids Coating | 120 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:
 - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
 - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

TABLE OF STANDARDS 1 VOC LIMITS

**Grams of VOC Per Liter of Coating,
 Less Water and Less Exempt Compounds**

| COATING CATEGORY | Ceiling Limit ¹ | Current Limit ² | Effective Date | | |
|--|----------------------------|----------------------------|----------------|--------|--------|
| | | | 7/1/08 | 1/1/12 | 1/1/14 |
| Bond Breakers | | 350 | | | |
| Clear Wood Finishes | | 275 | | | |
| Varnish | 350 | 275 | | | |
| Sanding Sealers | 350 | 275 | | | |
| Lacquer | | 275 | | | |
| Concrete-Curing Compounds | | 100 | | | |
| Concrete-Curing Compounds For Roadways and Bridges ³ | | 350 | | | |
| Concrete Surface Retarder | | 250 | | | 50 |
| Driveway Sealer | | 100 | | 50 | |
| Dry-Fog Coatings | | 150 | | | 50 |
| Faux Finishing Coatings | | | | | |
| Clear Topcoat | | 350 | | 200 | |
| Decorative Coatings | | 350 | | | 100 |
| Glazes | | 350 | | | |
| Japan | | 350 | | | |
| Trowel Applied Coatings | | 350 | | 150 | 50 |
| Fire-Proofing Coatings | | 350 | | | 150 |
| Flats | 250 | 50 | 50 | | |
| Floor Coatings | 100 | 50 | | | |
| Form Release Compound | | 250 | | | 100 |
| Graphic Arts (Sign) Coatings | | 500 | | | 150 |
| Industrial Maintenance (IM) Coatings | 420 | 100 | | | |
| High Temperature IM Coatings | | 420 | | | |
| Non-Sacrificial Anti-Graffiti Coatings | | 100 | | | |
| Zinc-Rich IM Primers | 340 | 100 | | | |
| Magnesite Cement Coatings | | 450 | | | |
| Mastic Coatings | | 300 | | | 100 |
| Metallic Pigmented Coatings | 500 | 500 | | | 150 |
| Multi-Color Coatings | | 250 | | | |
| Nonflat Coatings | 150 | 50 | | | |
| Pre-Treatment Wash Primers | | 420 | | | |
| Primers, Sealers, and Undercoaters | 200 | 100 | | | |
| Reactive Penetrating Sealers | | 350 | | | |
| Recycled Coatings | | 250 | | | |
| Roof Coatings | 250 | 50 | | | |
| Roof Coatings, Aluminum | | 100 | | | |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

| | | | | |
|------------------------------------|-----|-----|--|----|
| Roof Primers, Bituminous | 350 | 350 | | |
| Rust Preventative Coatings | 400 | 100 | | |
| Stone Consolidant | | 450 | | |
| Sacrificial Anti-Graffiti Coatings | | 100 | | 50 |
| Shellac | | | | |
| Clear | | 730 | | |
| Pigmented | | 550 | | |
| Specialty Primers | 350 | 100 | | |
| Stains | | 100 | | |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

| COATING CATEGORY | Ceiling Limit ¹ | Current Limit ² | Effective Date | | |
|--|----------------------------|----------------------------|----------------|--------|--------|
| | | | 7/1/08 | 1/1/12 | 1/1/14 |
| Stains, Interior | 250 | 250 | | | |
| Swimming Pool Coatings | | | | | |
| Repair | | 340 | | | |
| Other | | 340 | | | |
| Traffic Coatings | | 100 | | | |
| Waterproofing Sealers | 250 | 100 | | | |
| Waterproofing Concrete/Masonry Sealers | 400 | 100 | | | |
| Wood Preservatives | | 350 | | | |

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

TABLE OF STANDARDS 1 (cont.) VOC LIMITS

Grams of VOC Per Liter of Material

| COATING | Limit |
|--------------------|-------|
| Low-Solids Coating | 120 |

TABLE OF STANDARDS 2 VOC LIMITS FOR COLORANTS

Grams of VOC Per Liter of Colorant Less Water and Less Exempt Compounds

| COLORANT | Limit ⁴ |
|---|--------------------|
| Architectural Coatings, excluding IM Coatings | 50 |
| Solvent-Based IM | 600 |
| Waterborne IM | 50 |

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

| Architectural Applications | Current VOC Limit* |
|-------------------------------------|--------------------|
| Indoor Carpet Adhesives | 50 |
| Carpet Pad Adhesives | 50 |
| Outdoor Carpet Adhesives | 150 |
| Wood Flooring Adhesive | 100 |
| Rubber Floor Adhesives | 60 |
| Subfloor Adhesives | 50 |
| Ceramic Tile Adhesives | 65 |
| VCT and Asphalt Tile Adhesives | 50 |
| Dry Wall and Panel Adhesives | 50 |
| Cove Base Adhesives | 50 |
| Multipurpose Construction Adhesives | 70 |
| Structural Glazing Adhesives | 100 |
| Single Ply Roof Membrane Adhesives | 250 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

| Specialty Applications | VOC Limits and Effective Dates** | | | |
|--|----------------------------------|--------|--------|--------|
| | Current VOC Limit* | 1-1-05 | 7-1-05 | 1-1-07 |
| PVC Welding | 510 | | | |
| CPVC Welding | 490 | | | |
| ABS Welding | 400 | | 325 | |
| Plastic Cement Welding | 350 | 250 | | |
| Adhesive Primer for Plastic | 650 | | 550 | |
| Computer Diskette Manufacturing | 350 | | | |
| Contact Adhesive | 80 | | | |
| Special Purpose Contact Adhesive | 250 | | | |
| Tire Retread | 100 | | | |
| Adhesive Primer for Traffic Marking Tape | 150 | | | |
| Structural Wood Member Adhesive | 140 | | | |
| Sheet Applied Rubber Lining Operations | 850 | | | |
| Top and Trim Adhesive | 540 | | | 250 |

** The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

For adhesives, adhesive bonding primers, or any other primer not regulated by the above two tables and applied to the following substrates, the following limits shall apply:

| Substrate Specific Applications | Current VOC Limit* |
|---------------------------------|--------------------|
| Metal to Metal | 30 |
| Plastic Foams | 50 |
| Porous Material (except wood) | 50 |
| Wood | 30 |
| Fiberglass | 80 |

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

| Sealants | Current VOC Limit* |
|--------------------------|--------------------|
| Architectural | 250 |
| Marine Deck | 760 |
| Nonmembrane Roof | 300 |
| Roadway | 250 |
| Single-Ply Roof Membrane | 450 |
| Other | 420 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

| Sealant Primers | Current VOC Limit* |
|---------------------|-----------------------|
| Architectural | |
| Non Porous | 250 |
| Porous | 775 |
| Modified Bituminous | 500 |
| Marine Deck | 760 |
| Other | 750 |

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 10-03-2003]

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

| Architectural Applications | Current VOC Limit |
|-------------------------------------|-------------------|
| Indoor Carpet Adhesives | 50 |
| Carpet Pad Adhesives | 50 |
| Outdoor Carpet Adhesives | 150 |
| Wood Flooring Adhesive | 100 |
| Rubber Floor Adhesives | 60 |
| Subfloor Adhesives | 50 |
| Ceramic Tile Adhesives | 65 |
| VCT and Asphalt Tile Adhesives | 50 |
| Dry Wall and Panel Adhesives | 50 |
| Cove Base Adhesives | 50 |
| Multipurpose Construction Adhesives | 70 |
| Structural Glazing Adhesives | 100 |
| Single Ply Roof Membrane Adhesives | 250 |

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 10-03-2003]

| .Specialty Applications | VOC Limits and Effective Dates** | | | |
|--|----------------------------------|--------|--------|--------|
| | Current VOC Limit | 6-7-02 | 1-1-03 | 1-1-05 |
| PVC Welding | 510 | | | 285 |
| CPVC Welding | 490 | | | 270 |
| ABS Welding | 400 | | | |
| Plastic Cement Welding | 350 | | | 250 |
| Adhesive Primer for Plastic | 650 | | | 250 |
| Computer Diskette Manufacturing | 350 | | | |
| Contact Adhesive | 250 | | 80 | |
| Special Purpose Contact Adhesive | 250 | | | |
| Tire Retread | 100 | | | |
| Adhesive Primer for Traffic Marking Tape | 150 | | | |
| Structural Wood Member Adhesive | 140 | | | |
| Sheet Applied Rubber Lining Operations | 850 | | | |
| Top and Trim Adhesive | 250 | 540 | | 250 |

** The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 10-03-2003]

| Substrate Specific Applications | Current VOC Limit |
|---------------------------------|-------------------|
| Metal to Metal | 30 |
| Plastic Foams | 50 |
| Porous Material (except wood) | 50 |
| Wood | 30 |
| Fiberglass | 80 |

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

| Sealants | Current VOC Limit |
|--------------------------|-------------------|
| Architectural | 250 |
| Marine Deck | 760 |
| Nonmembrane Roof | 300 |
| Roadway | 250 |
| Single-Ply Roof Membrane | 450 |
| Other | 420 |

| Sealant Primers | Current VOC Limit |
|---------------------|-------------------|
| Architectural | |
| Non Porous | 250 |
| Porous | 775 |
| Modified Bituminous | 500 |
| Marine Deck | 760 |
| Other | 750 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| SOLVENT CLEANING ACTIVITY | CURRENT LIMITS |
|--|------------------------|
| | VOC g/l (lb/gal) |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application | |
| (i) General | 25 (0.21) |
| (ii) Electrical Apparatus Components & Electronic Components | 500 (4.2) |
| (iii) Medical Devices & Pharmaceuticals | 800 (6.7) |
| (B) Repair and Maintenance Cleaning | |
| (i) General | 25 (0.21) |
| (ii) Electrical Apparatus Components & Electronic Components | 900 (7.5) |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

| SOLVENT CLEANING ACTIVITY | CURRENT LIMITS |
|---|------------------------|
| | VOC g/l (lb/gal) |
| (iii) Medical Devices & Pharmaceuticals | |
| (A) Tools, Equipment, & Machinery | 800 (6.7) |
| (B) General Work Surfaces | 600 (5.0) |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 550 (4.6) |
| (D) Cleaning of Ink Application Equipment | |
| (i) General | 25 (0.21) |
| (ii) Flexographic Printing | 25 (0.21) |
| (iii) Gravure Printing | |
| (A) Publication | 750 (6.3) |
| (B) Packaging | 25 (0.21) |
| (iv) Lithographic or Letter Press Printing | |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

| SOLVENT CLEANING ACTIVITY | CURRENT LIMITS |
|---|------------------------|
| | VOC g/l (lb/gal) |
| (A) Roller Wash – Step 1 | 600 (5.0) |
| (B) Roller Wash-Step 2, Blanket Wash, & On-Press Components | 800 (6.7) |
| (C) Removable Press Components | 25 (0.21) |
| (v) Screen Printing | 750 (6.3) |
| (vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing) | 800 (6.7) |
| (vii) Specialty Flexographic Printing | 600 (5.0) |
| (E) Cleaning of Polyester Resin Application Equipment | 25 (0.21) |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| | CURRENT LIMITS* | EFFECTIVE 1/1/2010 |
|--|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application | | |
| (i) General | 25 (0.21) | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | |
| (iii) Medical Devices & Pharmaceuticals | 800 (6.7) | |
| (B) Repair and Maintenance Cleaning | | |
| (i) General | 25 (0.21) | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2010 |
|---|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY (cont.) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (iii) Medical Devices & Pharmaceuticals | | |
| (A) Tools, Equipment, & Machinery | 800 (6.7) | |
| (B) General Work Surfaces | 600 (5.0) | |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 25 (0.21) | |
| (D) Cleaning of Ink Application Equipment | | |
| (i) General | 25 (0.21) | |
| (ii) Flexographic Printing | 25 (0.21) | |
| (iii) Gravure Printing | | |
| (A) Publication | 100 (0.83) | |
| (B) Packaging | 25 (0.21) | |
| (iv) Lithographic (Offset) or Letter Press Printing | | |
| (A) Roller Wash, Blanket Wash, & On-Press Components | 100 (0.83) | |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2010 |
|--|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY (cont.) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (B) Removable Press Components | 25 (0.21) | |
| (v) Screen Printing | 100 (0.83) | |
| (vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing) | 650 (5.4) | 100 (0.83) |
| (vii) Specialty Flexographic Printing | 100 (0.83) | |
| (E) Cleaning of Polyester Resin Application Equipment | 25 (0.21) | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|--|--------------------------------|--|--------------------------|--|--------------------------------|---|-----------------------------|
| | | Milligrams per Cubic Meter | Grains per Cubic Foot | | | Milligrams per Cubic Meter | Grains per Cubic Foot |
| Cubic meters Per Minute | Cubic feet Per Minute | | | Cubic meters Per Minute | Cubic feet Per Minute | | |
| 25 or less | 883 or less | 450 | 0.196 | 900 | 31780 | 118 | 0.0515 |
| 30 | 1059 | 420 | .183 | 1000 | 35310 | 113 | .0493 |
| 35 | 1236 | 397 | .173 | 1100 | 38850 | 109 | .0476 |
| 40 | 1413 | 377 | .165 | 1200 | 42380 | 106 | .0463 |
| 45 | 1589 | 361 | .158 | 1300 | 45910 | 102 | .0445 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|--|--------------------------------|---|--------------------------|--|--------------------------------|---|-----------------------------|
| | | Milligrams per Cubic Meter | Grains per Cubic Foot | | | Milligrams per Cubic Meter | Grains per Cubic Foot |
| Cubic meters Per Minute | Cubic feet Per Minute | | | Cubic meters Per Minute | Cubic feet Per Minute | | |
| 50 | 1766 | 347 | .152 | 1400 | 49440 | 100 | .0437 |
| 60 | 2119 | 324 | .141 | 1500 | 52970 | 97 | .0424 |
| 70 | 2472 | 306 | .134 | 1750 | 61800 | 92 | .0402 |
| 80 | 2825 | 291 | .127 | 2000 | 70630 | 87 | .0380 |
| 90 | 3178 | 279 | .122 | 2250 | 79460 | 83 | .0362 |
| 100 | 3531 | 267 | .117 | 2500 | 88290 | 80 | .0349 |
| 125 | 4414 | 246 | .107 | 3000 | 105900 | 75 | .0327 |
| 150 | 5297 | 230 | .100 | 4000 | 141300 | 67 | .0293 |
| 175 | 6180 | 217 | .0947 | 5000 | 176600 | 62 | .0271 |
| 200 | 7063 | 206 | .0900 | 6000 | 211900 | 58 | .0253 |
| 250 | 8829 | 190 | .0830 | 8000 | 282500 | 52 | .0227 |
| 300 | 10590 | 177 | .0773 | 10000 | 353100 | 48 | .0210 |
| 350 | 12360 | 167 | .0730 | 15000 | 529700 | 41 | .0179 |
| 400 | 14130 | 159 | .0694 | 20000 | 706300 | 37 | .0162 |
| 450 | 15890 | 152 | .0664 | 25000 | 882900 | 34 | .0148 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|--|--------------------------------|---|--------------------------|--|--------------------------------|---|-----------------------------|
| | | Milligrams per Cubic Meter | Grains per Cubic Foot | | | Milligrams per Cubic Meter | Grains per Cubic Foot |
| Cubic meters Per Minute | Cubic feet Per Minute | | | Cubic meters Per Minute | Cubic feet Per Minute | | |
| 500 | 17660 | 146 | .0637 | 30000 | 1059000 | 32 | .0140 |
| 600 | 21190 | 137 | .0598 | 40000 | 1413000 | 28 | .0122 |
| 700 | 24720 | 129 | .0563 | 50000 | 1766000 | 26 | .0114 |
| 800 | 28250 | 123 | .0537 | 70000 or more | 2472000 or more | 23 | .0100 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

| Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process | | Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process | |
|----------------------------|----------------|---|--------------------|----------------------------|-------|---|--------------------|
| | | Kilograms Per Hour | Pounds Per Hour | | | Kilograms Per Hour | Pounds Per Hour |
| 100 or less | 220 or less | 0.450 | 0.99 | 9000 | 19840 | 5.308 | 11.7 |
| 150 | 331 | 0.585 | 1.29 | 10000 | 22050 | 5.440 | 12.0 |
| 200 | 441 | 0.703 | 1.55 | 12500 | 27560 | 5.732 | 12.6 |
| 250 | 551 | 0.804 | 1.77 | 15000 | 33070 | 5.982 | 13.2 |
| 300 | 661 | 0.897 | 1.98 | 17500 | 38580 | 6.202 | 13.7 |
| 350 | 772 | 0.983 | 2.17 | 20000 | 44090 | 6.399 | 14.1 |
| 400 | 882 | 1.063 | 2.34 | 25000 | 55120 | 6.743 | 14.9 |
| 450 | 992 | 1.138 | 2.51 | 30000 | 66140 | 7.037 | 15.5 |
| 500 | 1102 | 1.209 | 2.67 | 35000 | 77160 | 7.296 | 16.1 |
| 600 | 1323 | 1.340 | 2.95 | 40000 | 88180 | 7.527 | 16.6 |

FACILITY PERMIT TO OPERATE DELUXE LABORATORIES

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

| Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process | | Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process | |
|----------------------------|-------|---|--------------------|----------------------------|--------------------|---|--------------------|
| | | Kilograms Per Hour | Pounds Per Hour | | | Kilograms Per Hour | Pounds Per Hour |
| 700 | 1543 | 1.461 | 3.22 | 45000 | 99210 | 7.738 | 17.1 |
| 800 | 1764 | 1.573 | 3.47 | 50000 | 110200 | 7.931 | 17.5 |
| 900 | 1984 | 1.678 | 3.70 | 60000 | 132300 | 8.277 | 18.2 |
| 1000 | 2205 | 1.777 | 3.92 | 70000 | 154300 | 8.582 | 18.9 |
| 1250 | 2756 | 2.003 | 4.42 | 80000 | 176400 | 8.854 | 19.5 |
| 1500 | 3307 | 2.206 | 4.86 | 90000 | 198400 | 9.102 | 20.1 |
| 1750 | 3858 | 2.392 | 5.27 | 100000 | 220500 | 9.329 | 20.6 |
| 2000 | 4409 | 2.563 | 5.65 | 125000 | 275600 | 9.830 | 21.7 |
| 2250 | 4960 | 2.723 | 6.00 | 150000 | 330700 | 10.26 | 22.6 |
| 2500 | 5512 | 2.874 | 6.34 | 175000 | 385800 | 10.64 | 23.5 |
| 2750 | 6063 | 3.016 | 6.65 | 200000 | 440900 | 10.97 | 24.2 |
| 3000 | 6614 | 3.151 | 6.95 | 225000 | 496000 | 11.28 | 24.9 |
| 3250 | 7165 | 3.280 | 7.23 | 250000 | 551200 | 11.56 | 25.5 |
| 3600 | 7716 | 3.404 | 7.50 | 275000 | 606300 | 11.82 | 26.1 |
| 4000 | 8818 | 3.637 | 8.02 | 300000 | 661400 | 12.07 | 26.6 |
| 4500 | 9921 | 3.855 | 8.50 | 325000 | 716500 | 12.30 | 27.1 |
| 5000 | 11020 | 4.059 | 8.95 | 350000 | 771600 | 12.51 | 27.6 |
| 6000 | 13230 | 4.434 | 9.78 | 400000 | 881800 | 12.91 | 28.5 |
| 7000 | 15430 | 4.775 | 10.5 | 450000 | 992100 | 13.27 | 29.3 |
| 8000 | 17640 | 5.089 | 11.2 | 500000 or more | 1102000 or more | 13.60 | 30.0 |