



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT  
21865 Copley Drive, Diamond Bar, CA 91765

|              |                    |
|--------------|--------------------|
| Title Page   |                    |
| Facility ID. | 136148             |
| Revision #   | 3                  |
| Date         | September 02, 2011 |

## FACILITY PERMIT TO OPERATE


**E/M COATING SERVICES  
6940 FARMDALE AVE  
NORTH HOLLYWOOD, CA 91605**

### NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.  
EXECUTIVE OFFICER

By   
Mohsen Nazemi, P.E.  
Deputy Executive Officer  
Engineering & Compliance



## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### TABLE OF CONTENTS

| Section  | Description  | Revision #      | Date Issued |
|----------|--|-----------------|-------------|
| A        | Facility Information   | 2               | 09/02/2011  |
| B        | RECLAIM Annual Emission Allocation   | 2               | 09/02/2011  |
| C        | Facility Plot Plan   | TO BE DEVELOPED |             |
| D        | Facility Description and Equipment<br>Specific Conditions                            | 3               | 09/02/2011  |
| E        | Administrative Conditions  | 2               | 09/02/2011  |
| F        | RECLAIM Monitoring and Source Testing<br>Requirements                                | 2               | 09/02/2011  |
| G        | Recordkeeping and Reporting<br>Requirements for RECLAIM Sources                      | 2               | 09/02/2011  |
| H        | Permit To Construct and Temporary<br>Permit to Operate                               | 2               | 09/02/2011  |
| I        | Compliance Plans & Schedules   | 2               | 09/02/2011  |
| J        | Air Toxics   | 2               | 09/02/2011  |
| K        | Title V Administration   | 2               | 09/02/2011  |
| Appendix |  |                 |             |
| A        | NOx and SOx Emitting Equipment Exempt<br>From Written Permit Pursuant to Rule<br>219 | 2               | 09/02/2011  |
| B        | Rule Emission Limits   | 2               | 09/02/2011  |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### SECTION A: FACILITY INFORMATION

**LEGAL OWNER &/OR OPERATOR:** E/M COATING SERVICES

**LEGAL OPERATOR (if different than owner):**

**EQUIPMENT LOCATION:** 6940 FARMDALE AVE  
NORTH HOLLYWOOD, CA 91605

**MAILING ADDRESS:** 6940 FARMDALE AVE  
NORTH HOLLYWOOD, CA 91605

**RESPONSIBLE OFFICIAL:** BRENT TAYLOR

**TITLE:** DIVISION MANAGER

**TELEPHONE NUMBER:** (818) 983-1952

**CONTACT PERSON:** ERNIE LUCERO

**TITLE:** EH&S MANAGER

**TELEPHONE NUMBER:** (818) 983-1952

**TITLE V PERMIT ISSUED:** September 02, 2011

**TITLE V PERMIT EXPIRATION DATE:** September 01, 2016

| TITLE V | RECLAIM   |
|---------|---|
| YES     | <b>NOx: NO</b><br><b>SOx: NO</b><br><b>CYCLE: 0</b><br><b>ZONE: COASTAL</b> |

**FACILITY PERMIT TO OPERATE  
E/M COATING SERVICES**

**SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION**

NOT APPLICABLE

# **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

## **SECTION C: FACILITY PLOT PLAN**

(TO BE DEVELOPED)

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **Facility Equipment and Requirements (Section D)**

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

| Application number | Permit to Operate number | Equipment description             |
|--------------------|--------------------------|-----------------------------------|
| 414194             | F60232                   | OVEN, DRYING                      |
| 414193             | F60231                   | OVEN, DRYING                      |
| 414195             | F60233                   | SPRAY BOOTH PAINT AND SOLVENT     |
| 414196             | F60235                   | SPRAY BOOTH PAINT AND SOLVENT     |
| 414197             | F60236                   | SPRAY BOOTH PAINT AND SOLVENT     |
| 414190             | F60228                   | SPRAY BOOTH POWDER COATING SYSTEM |
| 414189             | F60227                   | SPRAY BOOTH POWDER COATING SYSTEM |
| 414187             | F60226                   | SPRAY BOOTH POWDER COATING SYSTEM |
| 414192             | F60230                   | OVEN, DRYING                      |
| 414198             | F60237                   | SPRAY BOOTH PAINT AND SOLVENT     |
| 414199             | F60238                   | SPRAY BOOTH PAINT AND SOLVENT     |
| 414201             | F60239                   | SPRAY BOOTH PAINT AND SOLVENT     |
| 414203             | F60240                   | SPRAY BOOTH PAINT AND SOLVENT     |
| 414204             | F60241                   | SPRAY BOOTH PAINT AND SOLVENT     |
| 414191             | F60229                   | OVEN, DRYING                      |
| 414205             | F60242                   | SPRAY BOOTH PAINT AND SOLVENT     |
| 414207             | F60243                   | SOLV RECLAIM STILL                |
| 414208             | F60244                   | SCRUBBER, OTHER VENTING S.S.      |
| 414210             | F60245                   | DIP TANK, SOLID FILM LUBRICANTS   |
| 414212             | F60246                   | DIP TANK, SOLID FILM LUBRICANTS   |
| 414213             | F60247                   | DIP TANK, SOLID FILM LUBRICANTS   |
| 414214             | F60248                   | SPRAY BOOTH POWDER COATING SYSTEM |
| 425125             | F81484                   | ANODIZING LINE                    |
| 425126             | F81485                   | AQUEOUS PROCESSING LINE           |

**NOTE:** EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### FACILITY WIDE CONDITION(S)

**Condition(s):**

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
  - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
  - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.  
[RULE 401]
  
2. ACCIDENTAL RELEASE PREVENTION REQUIREMENTS OF SECTION 112(r)(7):

THE OPERATOR SHALL COMPLY WITH THE ACCIDENTAL RELEASE PREVENTION REQUIREMENTS PURSUANT TO 40 CFR Part 68 AND SHALL SUBMIT TO THE EXECUTIVE OFFICER, AS PART OF ANNUAL COMPLIANCE CERTIFICATION, A STATEMENT THAT CERTIFIES COMPLIANCE WITH ALL THE REQUIREMENTS OF 40 CFR Part 68, INCLUDING THE REGISTRATION AND SUBMISSION OF A RISK MANAGEMENT PLAN (RMP). THE OPERATOR SHALL SUBMIT ANY ADDITIONAL RELEVANT INFORMATION REQUESTED BY THE EXECUTIVE OFFICER OR DESIGNATED AGENCY.  
[40 CFR68-ACCIDENTAL RELEASE PREVENTION]
  
3. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THE USE OF ALL VOC-CONTAINING MATERIALS IN EQUIPMENT OR PROCESSES SUBJECT TO RULE 442 AT THIS FACILITY SHALL NOT EXCEED 833 POUNDS IN ANY ONE CALENDAR MONTH. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH CALENDAR MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE CALENDAR MONTH FROM ALL EQUIPMENT AND OPERATIONS SUBJECT TO RULE 442 AT THE FACILITY.  
[RULE 442]
  
4. TO ENSURE COMPLIANCE WITH THE EMISSION LIMIT OF CONDITION NO. 3, THE OPERATOR SHALL:
  - A. COMPLY WITH RULE 109 (RECORDKEEPING FOR VOLATILE ORGANIC COMPOUND EMISSIONS).
  - B. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH CALENDAR MONTH, TOTAL AND RECORD VOC EMISSIONS FOR THE CALENDAR MONTH FROM ALL EQUIPMENT AND OPERATIONS THAT ARE REQUIRED TO HAVE WRITTEN PERMITS OR ARE EXEMPT FROM WRITTEN PERMITS PURSUANT TO RULE 219. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
  - C. MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.

- D. RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY.  
[RULE 109, 442]
5. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED AT THE FACILITY FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.  
[RULE 109, 442]
6. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY AND SUBJECT TO DISTRICT RULES SHALL BE KEPT CURRENT AND MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.  
[RULE 109, 1303(b)(2)-OFFSET, 442]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60232**  
**A/N 414194**

#### **Equipment Description:**

OVEN, DISPATCH, BAKING, ELECTRICALLY HEATED 51 K.W., 6'-4" W. X 6'-10" L. X 6'-8" H.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 550 DEGREES FAHRENHEIT.  
[RULE 401]
4. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY THE TEMPERATURE IN THE OVEN. SUCH RECORDS SHALL BE MAINTAINED FOR AT LEAST FIVE YEARS AND SHALL BE AVAILABLE TO THE DISTRICT PERSONNEL UPON REQUEST.  
[RULE 109, 401]
5. A GAUGE SHALL BE INSTALLED AND MAINTAINED TO INDICATE THE TEMPERATURE IN THE OVEN.  
[RULE 401]
6. THIS OVEN SHALL ONLY PROCESS THE PARTS THAT WERE COATED IN SPRAY BOOTH UNDER PERMIT NUMBER F60239.  
[RULE 1303(b)(2)-OFFSET]

#### **Periodic Monitoring:**

7. THE OPERATOR SHALL DETERMINE AND RECORD THE OVEN TEMPERATURE ONCE EVERY DAY.  
[RULE 3004 (a)(4)]

#### **Emissions And Requirements:**

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60231  
A/N 414193**

#### **Equipment Description:**

OVEN, TTX, MODEL, BAKING, NATURAL GAS FIRED, 1,200,000 BTU PER HOUR, 14'-0" W. X 19'-0" L. X 14'-0" H., WITH ONE 20 HP CIRCULATING FAN AND ONE 3/4 HP EXHAUST FAN.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS EQUIPMENT SHALL BE FIRED WITH NATURAL GAS ONLY.  
[RULE 1303(a)(1)-BACT]
4. THE OWNER/OPERATOR SHALL INSTALL AND MAINTAIN A DEVICE TO CONTINUOUSLY INDICATE AND RECORD THE TEMPERATURE IN THE OVEN.  
[RULE 109, 1303(b)(2)-OFFSET]
5. THE EQUIPMENT SHALL NOT BE OPERATED MORE THAN 6 HOURS IN ANY ONE DAY. THE OPERATOR SHALL KEEP A DAILY LOG TO VERIFY COMPLIANCE WITH THIS CONDITION, INCLUDING THE NAME OF THE PERSON WHO MAKES THE ENTRY, DATE OF OPERATION, STARTING TIME, STOPPING TIME, DURATION OF OPERATION, AND OPERATING TEMPERATURE.  
[RULE 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS. ALL RECORDS SHALL BE MAINTAINED FOR AT LEAST FIVE YEARS AND SHALL BE AVAILABLE TO THE DISTRICT PERSONNEL UPON REQUEST.  
[RULE 109, 401]
7. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 550 DEGREES FAHRENHEIT.  
[RULE 401]
8. THIS OVEN SHALL ONLY PROCESS THE PARTS THAT WERE COATED IN SPRAY BOOTHS UNDER PERMITS F60239 & F60237.  
[RULE 1303(b)(2)-OFFSET]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.  
[RULE 1147]

### **Emissions And Requirements:**

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:
- CO: 2000 PPMV, RULE 407
  - PM: 0.1 GR/SCF, RULE 409
  - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
  - NOx: 30 PPMV, RULE 1147

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

Permit No. F60233  
A/N 414195

#### Equipment Description:

SPRAY BOOTH, DEVILBISS, FLOOR TYPE, MODEL DT-6079, 10'-0" W. X 7'-0" H. X 9'-0" D., WITH ONE 1 HP EXHAUST FAN.

#### Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]

#### Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
4. THE OPERATOR SHALL NOT USE THIS EQUIPMENT UNLESS ALL EXHAUST AIR PASSES THROUGH A FILTER MEDIA AT LEAST 2 INCHES THICK.  
[RULE 3004 (a)(4)]
5. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE DIFFERENTIAL PRESSURE ACROSS THE FILTER DOES NOT EXCEED 0.25 INCHES WATER COLUMN. TO COMPLY WITH THIS CONDITION THE OPERATOR SHALL INSTALL AND MAINTAIN A PRESSURE GAUGE TO ACCURATELY INDICATE THE DIFFERENTIAL PRESSURE ACROSS THE FILTER. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **Emissions And Requirements:**

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109  
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS  
PM: RULE 481  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

Permit No. F60235  
A/N 414196

#### Equipment Description:

SPRAY BOOTH, DEVILBISS, FLOOR TYPE, MODEL DTH-506, 6'-0" W. X 7'-0" H. X 7'-0" D., WITH ONE 1 HP EXHAUST FAN.

#### Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]

#### Periodic Monitoring:

3. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
4. THE OPERATOR SHALL NOT USE THIS EQUIPMENT UNLESS ALL EXHAUST AIR PASSES THROUGH A FILTER MEDIA AT LEAST 2 INCHES THICK.  
[RULE 3004 (a)(4)]
5. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE DIFFERENTIAL PRESSURE ACROSS THE FILTER DOES NOT EXCEED 0.25 INCHES WATER COLUMN. TO COMPLY WITH THIS CONDITION THE OPERATOR SHALL INSTALL AND MAINTAIN A PRESSURE GAUGE TO ACCURATELY INDICATE THE DIFFERENTIAL PRESSURE ACROSS THE FILTER. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### **Emissions And Requirements:**

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109  
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS  
PM: RULE 481  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60236**  
**A/N 414197**

#### **Equipment Description:**

SPRAY BOOTH, DEVILBISS, BENCH FILTER TYPE, 3'-0" W. X 3'-0" H. X 3'-0" D., WITH ONE ¼ HP EXHAUST FAN.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THIS EQUIPMENT SHALL NOT EXCEED 6 GALLONS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]
4. THE VOLATILE PORTION OF COATING MATERIALS USED IN THIS EQUIPMENT SHALL BE AT LEAST 80 PERCENT WATER BY VOLUME.  
[RULE 1303(b)(2)-OFFSET]

#### **Periodic Monitoring:**

5. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
6. THE OPERATOR SHALL NOT USE THIS EQUIPMENT UNLESS ALL EXHAUST AIR PASSES THROUGH A FILTER MEDIA AT LEAST 2 INCHES THICK.  
[RULE 3004 (a)(4)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

7. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE DIFFERENTIAL PRESSURE ACROSS THE FILTER DOES NOT EXCEED 0.25 INCHES WATER COLUMN. TO COMPLY WITH THIS CONDITION THE OPERATOR SHALL INSTALL AND MAINTAIN A PRESSURE GAUGE TO ACCURATELY INDICATE THE DIFFERENTIAL PRESSURE ACROSS THE FILTER. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
  - VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
  - HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS
  - PM: RULE 481
  - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60228  
A/N 414190**

#### **Equipment Description:**

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. DUST COLLECTOR, WITH 12 FILTER BAGS, EACH 1'-8" DIA. X 5'-6" H.
2. BOOTH NO. B-3, GRAPHITE IMPREGNATING, 6'-6" W. X 5'-0" H. X 2'-0" D., WITH A 1/2 H.P. GRAPHITE AGITATOR.
3. EXHAUST SYSTEM WITH A 5 HP BLOWER.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]

#### **Periodic Monitoring:**

3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.  
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
  - A. STACK OR EMISSION POINT IDENTIFICATION;
  - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
  - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004 (a)(4)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

4. THE OPERATOR SHALL DISCHARGE DUST COLLECTED IN THIS EQUIPMENT ONLY INTO CLOSED CONTAINERS.  
[RULE 3004 (a)(4)]
  
5. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:  
  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60227  
A/N 414189**

#### **Equipment Description:**

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. DUST COLLECTOR, WITH 12 FILTER BAGS, EACH 1'-8" DIA. X 5'-6" H.
2. BOOTH NO. B-1, GRAPHITE IMPREGNATING, 6'-6" W. X 5'-0" H. X 2'-0" D., WITH A 1/2 H.P. GRAPHITE AGITATOR.
3. EXHAUST SYSTEM WITH A 5 HP BLOWER.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]

#### **Periodic Monitoring:**

3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.  
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
  - A. STACK OR EMISSION POINT IDENTIFICATION;
  - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
  - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004 (a)(4)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

4. THE OPERATOR SHALL DISCHARGE DUST COLLECTED IN THIS EQUIPMENT ONLY INTO CLOSED CONTAINERS.  
[RULE 3004 (a)(4)]
  
5. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:  
  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

Permit No. F60226  
A/N 414187

#### Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. DUST COLLECTOR, WITH 12 FILTER BAGS, EACH 1'-8" DIA. X 5'-6" H.
2. BOOTH NO. B-2, GRAPHITE IMPREGNATING, 6'-6" W. X 5'-0" H. X 2'-0" D., WITH A 1/2 H.P. GRAPHITE AGITATOR.
3. EXHAUST SYSTEM WITH A 5 HP BLOWER.

#### Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]

#### Periodic Monitoring:

3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.  
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
  - A. STACK OR EMISSION POINT IDENTIFICATION;
  - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
  - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004 (a)(4)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

4. THE OPERATOR SHALL DISCHARGE DUST COLLECTED IN THIS EQUIPMENT ONLY INTO CLOSED CONTAINERS.  
[RULE 3004 (a)(4)]
  
5. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:  
  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60230  
A/N 414192**

#### **Equipment Description:**

OVEN, DESPATCH, MODEL NO. V-41HD, 4'-6" W. X 5'-8" L. X 5'-6" H., NATURAL GAS FIRED 300,000 BTU/HR WITH ONE 3 HP CIRCULATING FAN AND ONE 1 HP EXHAUST FAN.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 650 DEGREES F.  
[RULE 401]
4. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THE COATING OF ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 4 GALLONS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]
5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.  
[RULE 1147]

#### **Periodic Monitoring:**

6. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE OVEN TEMPERATURE ONCE EVERY DAY.  
[RULE 3004 (a)(4)]

#### **Emissions And Requirements:**

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

PM: 0.1 GR/SCF, RULE 409  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS  
NOx: 30 PPMV, RULE 1147

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60237  
A/N 414198**

#### **Equipment Description:**

SPRAY BOOTH, DEVILBISS, FLOOR TYPE, MODEL NO. XDF-6038, 16'-0" W. X 12'-0" L. X 8'-0" H., WITH TWENTY-FOUR 20" X 25" EXHAUST FILTERS AND ONE 3 HP EXHAUST FAN.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.  
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.  
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THIS EQUIPMENT SHALL NOT EXCEED 1 1/2 GALLONS IN ANY ONE DAY AND TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 20 POUNDS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]
6. ORGANIC SOLVENTS USED IN THIS EQUIPMENT SHALL BE CLEARLY LABELED AS NON-PHOTOCHEMICALLY REACTIVE BY THE SUPPLIER OR, FOR BULK SHIPMENTS, SHOWN TO BE NON-PHOTOCHEMICALLY REACTIVE ON BILLS OF LADING OR INVOICES.  
[RULE 443]
7. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE. SUCH RECORDS SHALL BE RETAINED FOR A PERIOD OF FIVE YEARS.  
[RULE 109, 1303(b)(2)-OFFSET]

#### **Periodic Monitoring:**

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
- C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.

[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS

PM: RULE 481

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60238**  
**A/N 414199**

#### **Equipment Description:**

SPRAY BOOTH, DEVILBISS, BENCH TYPE, MODEL NO. LXG5011, 4'-0" W. X 5'-0" L. X 4'-0" H., WITH FOUR 36" X 12" EXHAUST FILTERS AND ONE ¼ HP EXHAUST FAN.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.  
[RULE 1303(a)(1)-BACT]
4. ORGANIC SOLVENTS USED IN THIS EQUIPMENT SHALL BE CLEARLY LABELED AS NON-PHOTOCHEMICALLY REACTIVE BY THE SUPPLIER OR, FOR BULK SHIPMENTS, SHOWN TO BE NON-PHOTOCHEMICALLY REACTIVE ON BILLS OF LADING OR INVOICES.  
[RULE 443]
5. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THIS EQUIPMENT SHALL NOT EXCEED 1 GALLON IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]

#### **Periodic Monitoring:**

6. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

7. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE DIFFERENTIAL PRESSURE ACROSS THE FILTER DOES NOT EXCEED 0.25 INCHES WATER COLUMN. TO COMPLY WITH THIS CONDITION THE OPERATOR SHALL INSTALL AND MAINTAIN A PRESSURE GAUGE TO ACCURATELY INDICATE THE DIFFERENTIAL PRESSURE ACROSS THE FILTER. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
  - VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
  - HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS
  - PM: RULE 481
  - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60239**  
**A/N 414201**

#### **Equipment Description:**

SPRAY BOOTH, DEVILBISS, FLOOR FILTER TYPE, 16'-4" W. X 8'-8" H. X 15'-2" D., WITH ONE 3 HP EXHAUST FAN.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.  
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.  
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THIS EQUIPMENT SHALL NOT EXCEED 6 GALLONS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]

#### **Periodic Monitoring:**

6. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

7. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
  - VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
  - HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS
  - PM: RULE 481
  - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60240  
A/N 414203**

#### **Equipment Description:**

SPRAY BOOTH, BINKS, DRY FILTER BENCH TYPE CONVEYORIZED, MODEL 62189, 5'-4" W. X 5'-6" L. X 3'-0" H., WITH ONE 5' X 3' EXHAUST FILTER, ONE 12 KW INFRARED DRYING ENCLOSURE, ONE 1/4 HP CONVEYOR AND ONE 1/4 HP EXHAUST FAN.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.  
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.  
[RULE 1303(a)(1)-BACT]
5. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS AND VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS/HER REPRESENTATIVE.  
[RULE 109, 1303(b)(2)-OFFSET]
6. THE TOTAL COMBINED QUANTITY OF VOC EMISSIONS FROM THE SPRAY BOOTHS UNDER APPLICATION NOS. 414203, 414204 & 414205 SHALL NOT EXCEED 26 POUNDS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]
7. COATINGS, REDUCERS, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN DISTRICT RULE 1401 AS AMENDED ON DECEMBER 7, 1990.  
[RULE 1401]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
  
9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

### Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:  
  
VOC: RULE 109  
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 481  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60241**  
**A/N 414204**

#### **Equipment Description:**

SPRAY BOOTH, BINKS, DRY FILTER BENCH TYPE MODEL PBFA-4T, 4'-0" W. X 6'-0" D. X 7'-0" H., WITH SIX 16" X 20" AND THREE 20" X 20" EXHAUST FILTERS AND A ½ HP EXHAUST FAN.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.  
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.  
[RULE 1303(a)(1)-BACT]
5. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS AND VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS/HER REPRESENTATIVE.  
[RULE 109, 1303(b)(2)-OFFSET]
6. THE TOTAL COMBINED QUANTITY OF VOC EMISSIONS FROM THE SPRAY BOOTHS UNDER APPLICATION NOS. 414203, 414204 & 414205 SHALL NOT EXCEED 26 POUNDS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]
7. COATINGS, REDUCERS, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN DISTRICT RULE 1401 AS AMENDED ON DECEMBER 7, 1990.  
[RULE 1401]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
  
9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

### Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:  
  
VOC: RULE 109  
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 481  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60229  
A/N 414191**

#### **Equipment Description:**

OVEN, DESPATCH, DRYING, MODEL, NO. V-39, 4'-3" W. X 4'-6" D. X 5'-6" H., ELECTRICALLY HEATED, 26 KW.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 425 DEGREES F.  
[RULE 401]
4. THIS OVEN SHALL ONLY BE USED TO PROCESS ARTICLES COATED IN EQUIPMENT WITH A VALID PERMIT FROM THE DISTRICT.  
[RULE 1303(b)(2)-OFFSET]

#### **Periodic Monitoring:**

5. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE OVEN TEMPERATURE ONCE EVERY DAY.  
[RULE 3004 (a)(4)]

#### **Emissions And Requirements:**

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:  
  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

Permit No. F60242  
A/N 414205

#### Equipment Description:

SPRAY BOOTH, BINKS, DRY FILTER BENCH TYPE MODEL PBFA-4T, 4'-0" W. X 6'-0" D. X 7'-0" H., WITH SIX 16" X 20" AND THREE 20" X 20" EXHAUST FILTERS AND A ½ HP EXHAUST FAN.

#### Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.  
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.  
[RULE 1303(a)(1)-BACT]
5. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS AND VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS/HER REPRESENTATIVE.  
[RULE 109, 1303(b)(2)-OFFSET]
6. THE TOTAL COMBINED QUANTITY OF VOC EMISSIONS FROM THE SPRAY BOOTHS UNDER APPLICATION NOS. 414203, 414204 & 414205 SHALL NOT EXCEED 26 POUNDS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]
7. COATINGS, REDUCERS, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN DISTRICT RULE 1401 AS AMENDED ON DECEMBER 7, 1990.  
[RULE 1401]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
  
9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

### Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:  
  
VOC: RULE 109  
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 481  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **PERMIT TO OPERATE**

**Permit No. F60243  
A/N 414207**

#### **Equipment Description:**

SOLVENT RECOVERY STILL, FINISH ENGINEERING CO., MODEL LS-15, SERIAL NO. 1276, 2'-6" W. X 3'-8" L. X 3'-0" H., 15 GALLON CAPACITY WITH A 1.65 KW ELECTRIC HEATER AND A WATER COOLED CONDENSER.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS EQUIPMENT SHALL ONLY BE USED TO RECOVER SPENT ACETONE.  
[RULE 1303(b)(2)-OFFSET]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60244  
A/N 414208**

#### **Equipment Description:**

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. SCRUBBER, TELLKAMP SYSTEM, MODEL VPS-14, WITH A 2 HP RECIRCULATING PUMP.
2. EXHAUST SYSTEM WITH A 20 HP BLOWER VENTING THREE SULFURIC ACID TANKS, ONE CAUSTIC SODA TANK AND TWO DEOXIDIZER TANKS.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. WHENEVER THE TANKS ARE IN OPERATION, AN ADEQUATE WATER SUPPLY SHALL BE MAINTAINED TO THE SCRUBBER.  
[RULE 1303(a)(1)-BACT]

#### **Periodic Monitoring:**

4. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE FLOW RATE OF THE SCRUBBING SOLUTION IS NOT LESS THAN 100 GPM. TO COMPLY WITH THIS CONDITION THE OPERATOR SHALL INSTALL AND MAINTAIN A FLOW METER TO ACCURATELY INDICATE THE FLOW RATE OF THE SCRUBBING SOLUTION. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY DAY.  
[RULE 3004 (a)(4)]
5. THE OPERATOR SHALL USE THIS EQUIPMENT IN SUCH A MANNER THAT THE pH OF THE SCRUBBING SOLUTION IS NOT LESS THAN 6 OF THE pH SCALE. TO COMPLY WITH THIS CONDITION THE OPERATOR SHALL USE A pH METER TO ACCURATELY INDICATE THE pH OF THE SCRUBBING SOLUTION. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY DAY.  
[RULE 3004 (a)(4)]

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **Emissions And Requirements:**

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

Permit No. F60245  
A/N 414210

#### Equipment Description:

DIP COATING MACHINE, DCM-1, PHILIP MACHINE COMPANY, MODEL R-200, WITH A 1'-4" DIA. X 0'-6" D., WORK BASKET.

#### Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS DISCHARGED TO THE ATMOSPHERE FROM USE OF COATINGS AND SOLVENTS IN THIS EQUIPMENT SHALL NOT EXCEED 18 POUNDS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]
4. COATINGS, REDUCERS, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401 TABLE 1 WITH AN EFFECTIVE DATE OF AUGUST 18, 2000 OR EARLIER, EXCEPT ISOPROPYL ALCOHOL, INORGANIC LEAD COMPOUNDS, TOLUENE, METHYL ETHYL KETONE, PHENOL, XYLENE, CHROMIUM COMPOUNDS, AND FORMALDEHYDE.  
[RULE 1401]
5. ONLY SOLID FILM LUBRICANTS CAN BE USED IN THIS EQUIPMENT.  
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY DAILY VOC EMISSIONS IN POUNDS. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE MAINTAINED FOR FIVE YEARS AND SHALL BE AVAILABLE TO THE DISTRICT PERSONNEL UPON REQUEST.  
[RULE 109, 1303(b)(2)-OFFSET]

#### Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

VOC: RULE 109  
VOC: RULE 442, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

Permit No. F60246  
A/N 414212

#### Equipment Description:

DIP COATING MACHINE, DCM-1, PHILIP MACHINE COMPANY, MODEL R-200, WITH A 1'-4" DIA. X 0'-6" D., WORK BASKET.

#### Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS DISCHARGED TO THE ATMOSPHERE FROM USE OF COATINGS AND SOLVENTS IN THIS EQUIPMENT SHALL NOT EXCEED 18 POUNDS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]
4. COATINGS, REDUCERS, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401 TABLE 1 WITH AN EFFECTIVE DATE OF AUGUST 18, 2000 OR EARLIER, EXCEPT ISOPROPYL ALCOHOL, INORGANIC LEAD COMPOUNDS, TOLUENE, METHYL ETHYL KETONE, PHENOL, XYLENE, CHROMIUM COMPOUNDS, AND FORMALDEHYDE.  
[RULE 1401]
5. ONLY SOLID FILM LUBRICANTS CAN BE USED IN THIS EQUIPMENT.  
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY DAILY VOC EMISSIONS IN POUNDS. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE MAINTAINED FOR FIVE YEARS AND SHALL BE AVAILABLE TO THE DISTRICT PERSONNEL UPON REQUEST.  
[RULE 109, 1303(b)(2)-OFFSET]

#### Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

VOC: RULE 109  
VOC: RULE 442, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60247  
A/N 414213**

#### **Equipment Description:**

DIP COATING MACHINE, DCM-1, PHILIP MACHINE COMPANY, MODEL R-200, WITH A 1'-4" DIA. X 0'-6" D., WORK BASKET.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS DISCHARGED TO THE ATMOSPHERE FROM USE OF COATINGS AND SOLVENTS IN THIS EQUIPMENT SHALL NOT EXCEED 18 POUNDS IN ANY ONE DAY.  
[RULE 1303(b)(2)-OFFSET]
4. COATINGS, REDUCERS, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401 TABLE 1 WITH AN EFFECTIVE DATE OF AUGUST 18, 2000 OR EARLIER, EXCEPT ISOPROPYL ALCOHOL, INORGANIC LEAD COMPOUNDS, TOLUENE, METHYL ETHYL KETONE, PHENOL, XYLENE, CHROMIUM COMPOUNDS, AND FORMALDEHYDE.  
[RULE 1401]
5. ONLY SOLID FILM LUBRICANTS CAN BE USED IN THIS EQUIPMENT.  
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY DAILY VOC EMISSIONS IN POUNDS. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE MAINTAINED FOR FIVE YEARS AND SHALL BE AVAILABLE TO THE DISTRICT PERSONNEL UPON REQUEST.  
[RULE 109, 1303(b)(2)-OFFSET]

#### **Emissions And Requirements:**

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

VOC: RULE 109  
VOC: RULE 442, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F60248**  
**A/N 414214**

#### **Equipment Description:**

POWDER COATING SYSTEM, CONSISTING OF:

1. SPRAY BOOTH, BENCH TYPE, 4'-9" W. X 7'-0" L. X 13'-0" H.
2. FOUR CARTRIDGE FILTERS, EACH 3'-0" L. X 1'-0" DIA., WITH AUTOMATIC PULSE SHAKER.
3. TWO HEPA FILTERS, ASTROCEL, MODEL 1 HCX, EACH 2'-0" W. X 1'-0" L. X 2'-0" H.
4. EXHAUST SYSTEM WITH A 5 H.P. BLOWER VENTING THE SPRAY BOOTH.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH DUST COLLECTOR AND HEPA FILTERING SYSTEM.  
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 1 INCH OF WATER ACROSS THE DUST COLLECTOR AND 2 INCHES OF WATER ACROSS EACH HEPA FILTER.  
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN DISTRICT RULE 1401 AS AMENDED ON MAY 3, 2002 OR EARLIER.  
[RULE 1401]
6. CLEAN-UP SOLVENTS SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).  
[RULE 1303(b)(2)-OFFSET]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

7. ONLY POWDER COATINGS SHALL BE APPLIED IN THIS EQUIPMENT. THE POWDER COATING SHALL NOT CONTAIN ANY VOC.  
[RULE 1303(b)(2)-OFFSET]
8. THE TOTAL QUANTITY OF POWDER COATING MATERIALS USED IN THIS EQUIPMENT SHALL NOT EXCEED 30 POUNDS IN ANY ONE CALENDAR MONTH.  
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
9. THE OPERATOR SHALL DISCHARGE DUST COLLECTED IN THIS EQUIPMENT ONLY INTO CLOSED CONTAINERS.  
[RULE 1303(a)(1)-BACT]
10. THE OPERATOR SHALL KEEP ADEQUATE RECORDS IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT TO DEMONSTRATE COMPLIANCE WITH THE USAGE LIMIT FOR POWDER COATING MATERIAL.  
[RULE 1303(b)(2)-OFFSET]

### **Periodic Monitoring:**

11. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.  
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
  - A. STACK OR EMISSION POINT IDENTIFICATION;
  - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
  - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004 (a)(4)]
12. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

13. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTERS ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

14. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109  
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
HAP 40CFR63 SUBPART GG, SEE SECTION J FOR REQUIREMENTS  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 481

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F81484**  
**A/N 425125**

#### **Equipment Description:**

ANODIZING LINE CONSISTING OF:

1. PROCESS TANK NO. 200, STEAM HEATED, SODIUM CHROMATE/SODIUM BORATE, 6'-0" W. X 3'-6" L. X 4'-0" H.
2. PROCESS TANK NO. 202, UNHEATED, SODIUM HYDROXIDE, 3'-0" W. X 3'-6" L. X 4'-0" H., VENTED TO THE AIR POLLUTION CONTROL EQUIPMENT.
3. PROCESS TANK NO. 203, UNHEATED, WATER RINSE, THREE TANKS EACH 3'-0" W. X 3'-0" L. X 4'-0" H., WITH AIR SPARGER.
4. PROCESS TANK NO. 204, UNHEATED, SULFURIC ACID/NITRIC ACID/ALUMINUM DIOXIDE, 6'-0" W. X 3'-6" L. X 4'-0" H., WITH AIR SPARGER, VENTED TO THE AIR POLLUTION CONTROL EQUIPMENT.
5. PROCESS TANK NO. 205, STEAM HEATED, RINSE, THREE TANKS EACH 6'-0" W. X 3'-0" L. X 4'-0" H., WITH AIR SPARGER.
6. PROCESS TANK NO. 206, UNHEATED, NITRIC ACID/PHOSPHORIC ACID/SULFURIC ACID, 2'-11" W. X 3'-6" L. X 4'-0" H., VENTED TO THE AIR POLLUTION CONTROL EQUIPMENT.
7. PROCESS TANK NO. 207, UNHEATED, WATER RINSE, THREE TANKS EACH 3'-0" W. X 3'-0" L. X 4'-0" H., WITH AIR SPARGER.
8. PROCESS TANK NO. 208, UNHEATED, SULFURIC ACID, 6'-0" W. X 3'-6" L. X 4'-0" H., WITH A RECTIFIER AND AIR SPARGER, VENTED TO THE AIR POLLUTION CONTROL EQUIPMENT.
9. PROCESS TANK NO. 209, UNHEATED, WATER RINSE, THREE TANKS EACH 3'-0" W. X 3'-0" L. X 4'-0" H., WITH AIR SPARGER.
10. PROCESS TANK NO. 210, UNHEATED, SULFURIC ACID/OXALIC ACID, 8'-0" W. X 3'-0" L. X 5'-0" H., WITH A RECTIFIER AND AIR SPARGER, VENTED TO THE AIR POLLUTION CONTROL EQUIPMENT.
11. PROCESS TANK NO. 211, UNHEATED, SULFURIC ACID/OXALIC ACID, 8'-0" W. X 3'-6" L. X 5'-0" H., WITH A RECTIFIER AND AIR SPARGER, VENTED TO THE AIR POLLUTION CONTROL EQUIPMENT.
12. PROCESS TANK NO. 212, STEAM HEATED, BLACK DYE, 3'-0" W. X 3'-6" L. X 4'-0" H., WITH AIR SPARGER.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

13. PROCESS TANK NO. 213, UNHEATED, WATER RINSE, 4'-0" W. X 4'-0" L. X 4'-0" H., WITH AIR SPARGER.
14. PROCESS TANK NO. 214, STEAM HEATED, NICKEL ACETATE/ALUSEAL POWDER, 3'-0" W. X 3'-6" L. X 3'-10" H., WITH AIR SPARGER.
15. PROCESS TANK NO. 215, STEAM HEATED, RINSE, THREE TANKS EACH 3'-0" W. X 3'-0" L. X 4'-0" H., WITH AIR SPARGER.
16. PROCESS TANK NO. 216, STEAM HEATED, SODIUM DICHROMATE, 3'-0" W. X 3'-6" L. X 4'-0" H.
17. PROCESS TANK NO. 218, STEAM HEATED, WATER RINSE, 3'-0" W. X 3'-6" L. X 4'-0" H.
18. PROCESS TANK NO. 219, UNHEATED, WATER RINSE, THREE TANKS EACH 3'-0" W. X 3'-6" L. X 4'-0" H., WITH AIR SPARGER.
19. PROCESS TANK NO. 220, UNHEATED, WATER RINSE, 3'-0" W. X 3'-6" L. X 4'-0" H.
20. PROCESS TANK NO. 221, UNHEATED, WATER RINSE, 3'-0" W. X 3'-6" L. X 4'-0" H., WITH AIR SPARGER.
21. PROCESS TANK NO. 222, UNHEATED, CHROMIC ACID/POTASIMUM FLUORIDE/SODIUM FLUORIDE/POTASIMUM FLUOZIRCONATE/POTASIMUM FERRICYANIDE, 3'-0" W. X 3'-6" L. X 4'-0" H., WITH AIR SPARGER.
22. PROCESS TANK NO. 224, UNHEATED, SODIUM CARBONATE/SODIUM SULFATE/SODIUM METASILICATE 3'-0" W. X 3'-0" L. X 3'-0" H., WITH A RECTIFIER.
23. PROCESS TANK NO. 225, UNHEATED, WATER RINSE, THREE TANKS EACH 3'-0" W. X 3'-0" L. X 4'-0" H., WITH AIR SPARGER.
24. PROCESS TANK NO. 226, UNHEATED, FERRIC CHLORIDE, 4'-0" W. X 2'-0" L. X 4'-0" H.
25. PROCESS TANK NO. 227, STEAM HEATED, WATER RINSE, 2'-0" W. X 2'-0" L. X 3'-0" H.
26. PROCESS TANK NO. 228, STEAM HEATED, CHROMIC ACID/SODIUM CHROMATE, 2'-6" W. X 2'-0" L. X 2'-9" H.
27. PROCESS TANK NO. 229, STEAM HEATED, BROWN DYE, 4'-0" W. X 4'-0" L. X 2'-0" H., WITH AIR SPARGER.
28. PROCESS TANK NO. 230, UNHEATED, SULFURIC ACID, 2'-8" W. X 2'-10" L. X 2'-10" H., WITH A RECTIFIER AND AIR SPARGER.

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE USED FOR CHROMIC ACID ANODIZING.  
[RULE 1426, RULE 1469]
4. ALL TANKS THAT CONTAIN CHROMIC ACID SHALL NOT BE AIR-SPARGED WHEN THE ANODIZING LINE IS NOT IN USE.  
[RULE 1401]

### **Emissions And Requirements:**

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:  
  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### PERMIT TO OPERATE

**Permit No. F81485  
A/N 425126**

#### **Equipment Description:**

##### PASSIVATION LINE CONSISTING OF:

1. PROCESS TANK NO. 3, STEAM HEATED, OAKITE 90, 3'-0" W. X 4'-0" L. X 3'-2" H.
2. PROCESS TANK NO. 4, STEAM HEATED, CITRIC ACID, 2'-0" W. X 3'-0" L. X 2'-0" H.
3. PROCESS TANK NO. 5, UNHEATED, WATER RINSE, 2'-0" W. X 2'-0" L. X 2'-0" H.
4. PROCESS TANK NO. 6, UNHEATED, NITRIC/HYDROFLUORIC ACID, 2'-10" W. X 2'-0" L. X 3'-0" H.
5. PROCESS TANK NO. 7, STEAM HEATED, PHOSPHATE ION/POTASSIUM FLUORIDE/HYDROFLUORIC ACID, 2'-10" W. X 2'-0" L. X 3'-0" H.
6. PROCESS TANK NO. 8, STEAM HEATED, SODIUM HYDROXIDE/SODIUM METASILICATE/SODIUM CARBONATE/TETRA SODIUM PYROPHOSPHATE/, 2'-0" W. X 2'-0" L. X 3'-0" H.
7. PROCESS TANK NO. 9, STEAM HEATED, WATER RINSE, 2'-10" W. X 2'-0" L. X 3'-0" H.
8. PROCESS TANK NO. 11, UNHEATED, WATER RINSE, 3'-0" W. X 4'-0" L. X 3'-0" H. WITH AIR SPARGER.
9. PROCESS TANK NO. 12, UNHEATED, WATER RINSE, 2'-0" W. X 2'-0" L. X 3'-0" H.
10. PROCESS TANK NO. 13, STEAM HEATED, CHROMIC ACID/PHOSPHORIC ACID/MANGANESE DIHYDROGEN PHOSPHATE/NITRIC ACID/PHOSPHORIC ACID/NICKEL NITRATE, 3'-0" W. X 4'-0" L. X 3'-0" H.
11. PROCESS TANK NO. 14, STEAM HEATED, PHOSPHORIC ACID/CHROMIC ACID, 3'-0" W. X 4'-0" L. X 3'-2" H.
12. PROCESS TANK NO. 15, UNHEATED, WATER RINSE, 3'-0" W. X 4'-0" L. X 3'-0" H., WITH AIR SPARGER.
13. PROCESS TANK NO. 16, STEAM HEATED, ZINC DIHYDROGEN PHOSPHATE/ZINC PHOSPHATE/NITRIC ACID/PHOSPHORIC ACID/ZINC DIHYDROGEN PHOSPHATE, 3'-0" W. X 4'-0" L. X 3'-2" H.
14. PROCESS TANK NO. 18, UNHEATED, WATER RINSE, 3'-0" W. X 4'-0" L. X 3'-0" H., WITH AIR SPARGING
15. PROCESS TANK NO. 19, STEAM HEATED, SODIUM DICHROMATE, 2'-0" W. X 3'-0" L. X 2'-0" H.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

16. PROCESS TANK NO. 20, STEAM HEATED, NITRIC ACID/SODIUM DICHROMATE, 2'-0" W. X 3'-0" L. X 2'-0" H.
17. PROCESS TANK NO. 21, UNHEATED, NITRIC ACID, 2'-0" W. X 3'-0" L. X 2'-0" H.
18. PROCESS TANK NO. 22, STEAM HEATED, TETRA SODIUM PYROPHOSPHATE/MANGANESE PHOSPHATE, 2'-11" W. X 4'-0" L. X 3'-2" H.
19. PROCESS TANK NO. 23, UNHEATED, WATER RINSE, 3'-0" W. X 4'-0" L. X 3'-0" H., WITH AIR SPARGER.
20. PROCESS TANK NO. 24, STEAM HEATED, ALKALINE, 1'-6" W. X 1'-6" L. X 2'-0" H.
21. PROCESS TANK NO. 1, STEAM HEATED, WATER RINSE, 2'-0" W. X 3'-0" L. X 2'-0" H.
22. PROCESS TANK NO. 2, STEAM HEATED, WATER RINSE, 2'-0" W. X 3'-0" L. X 2'-0" H.

**Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]

**FACILITY PERMIT TO OPERATE  
E/M COATING SERVICES**

**PERMIT TO CONSTRUCT**

**NONE**

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### RULE 219 EQUIPMENT

**Equipment Description:**

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

**Periodic Monitoring:**

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

[RULE 3004 (a) (4)]

**Emissions And Requirements:**

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **RULE 219 EQUIPMENT**

**Equipment Description:**

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

**Emissions And Requirements:**

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:  
  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 109

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **RULE 219 EQUIPMENT**

**Equipment Description:**

RULE 219 EXEMPT EQUIPMENT, BOILER, > 1 MMBTU/HR BUT < 2 MMBTU/HR.

**Emissions And Requirements:**

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: 0.1 gr/scf, RULE 409  
NOx: 30 PPMV, RULE 1146.2  
CO: 400 PPMV, RULE 1146.2  
CO: 2000 PPMV, RULE 407

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **RULE 219 EQUIPMENT**

**Equipment Description:**

RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS

**Emissions And Requirements:**

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

REFRIGERANT:           RULE 1415

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **RULE 219 EQUIPMENT**

**Equipment Description:**

RULE 219 EXEMPT EQUIPMENT, COOLING TOWERS

**Emissions And Requirements:**

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CR<sup>+6</sup>: RULE 1404

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### RULE 219 EQUIPMENT

#### Equipment Description:

RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, GLOVE-BOX, < 53 FT3, WITH DUST FILTER.

#### Periodic Monitoring:

1. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
  - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
  
2. THE OPERATOR SHALL DISCHARGE DUST COLLECTED IN THIS EQUIPMENT ONLY INTO CLOSED CONTAINERS.  
[RULE 3004 (a)(4)]
  
3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.  
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
  - A. STACK OR EMISSION POINT IDENTIFICATION;
  - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
  - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004 (a)(4)]

#### Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

**FACILITY PERMIT TO OPERATE  
E/M COATING SERVICES**

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **RULE 219 EQUIPMENT**

**Equipment Description:**

RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL UNHEATED, NON-CONVEYORIZED

**Emissions And Requirements:**

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 109

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **RULE 219 EQUIPMENT**

**Equipment Description:**

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS

**Emissions And Requirements:**

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
  - VOC: RULE 109
  - VOC: RULE 442, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1124, SEE APPENDIX B FOR EMISSION LIMITS
  - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION E: ADMINISTRATIVE CONDITIONS**

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
  - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
  - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
  - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statues of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION E: ADMINISTRATIVE CONDITIONS**

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]
7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
  - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]
  - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
  - c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]
  - d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO<sub>2</sub>) and be averaged over 15 consecutive minutes; [407]
  - e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO<sub>2</sub>) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION E: ADMINISTRATIVE CONDITIONS**

- f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O<sub>2</sub>) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]
8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
- a. Brief description of the equipment tested.
  - b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.
  - c. Operating conditions under which the test will be performed.
  - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
  - e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
  - f. Description of calibration and quality assurance procedures.
  - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).
9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]
- a. The results of the source test.

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION E: ADMINISTRATIVE CONDITIONS**

- b. Brief description of the equipment tested.
  - c. Operating conditions under which the test was performed.
  - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
  - e. Field and laboratory data forms, strip charts and analyses.
  - f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]
  11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

**FACILITY PERMIT TO OPERATE  
E/M COATING SERVICES**

**SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS**

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE  
E/M COATING SERVICES**

**SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR  
RECLAIM SOURCES**

**NOT APPLICABLE**

**FACILITY PERMIT TO OPERATE  
E/M COATING SERVICES**

**SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE**

See Section D of this permit for any Permit to Construct issued to this facility.

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION I: PLANS AND SCHEDULES**

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### SECTION J: AIR TOXICS [40CFR 63 Subpart GG 12-08-2000]

#### NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR AEROSPACE MANUFACTURING AND REWORK FACILITIES

1. The operator shall comply with all applicable requirements of 40 CFR 63, Subpart GG and of 40 CFR 63, Subpart A - General Provisions by the compliance date(s) specified in these subparts.
2. The operator shall conduct all cleaning operations pursuant to all applicable requirements specified in Section 63.744.
3. The operator shall comply with all applicable requirements of Sections 63.745 and 63.747 for all primer, topcoat, and chemical milling maskant application operations. Primers, topcoats, and chemical milling maskants that are applied to aerospace parts without being vented to a control system shall comply with the following limits.

| Coating Type                     | Organic HAP Limits (g/l)<br>(less water) | VOC Limit (g/l)<br>(less water/exempt solvents) |
|----------------------------------|--|---|
| Primer                           | 350                                      | 350   |
| Topcoats                         | 420                                      | 420   |
| Self-priming Topcoats            | 420                                      | 420   |
| Chemical Milling Maskant Type I  | 622                                      | 622   |
| Chemical Milling Maskant Type II | 160                                      | 160   |

For primer, topcoat, and chemical milling maskant application operations that are vented to a control system, each control system shall reduce the operation's organic HAP and VOC emissions to the atmosphere by 81% or greater, taking into account capture and destruction or removal efficiencies, as determined using the procedures in Section 63.750(g) when a carbon adsorber is used and in Section 63.750(h) when a control device other than a carbon adsorber is used.

4. The operator shall comply with all applicable requirements of Section 63.746 for all depainting operations.
5. The operator shall conduct the handling and transfer of the waste to and from containers, tanks, vats, vessels, and piping systems in such a manner that minimizes spills pursuant to Section 63.748.
6. The operator shall comply with all applicable requirements of this subpart by the compliance dates specified in Section 63.749.

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION J: AIR TOXICS [40CFR 63 Subpart GG 12-08-2000]**

7. The operator of a facility using any HAP-containing chemicals or control equipment venting such chemicals, that are required by this subpart to conduct chemical analyses and/or performance testing, shall submit a protocol to the AQMD for approval of no less than 60 days prior to testing. The tests shall be conducted in accordance with the test methods and procedures specified in Section 63.750.
8. The operator shall comply with all applicable monitoring requirements specified in Section 63.751.
9. The operator shall keep all records pursuant to Section 63.752 of this subpart and Subpart A to demonstrate compliance with all applicable requirements. All records including data, calculations and any supporting documentation shall be prepared in a format which is acceptable to the AQMD.
10. The operator shall submit all reports, notifications, plans, submittals and other communications required by Section 63.753 of this subpart or Subpart A to the AQMD and, unless notified to the contrary by AQMD or US EPA, to US EPA Region IX (See Sections E and K of this permit for addresses).
11. Alternative plans, compliance plans, and the construction and operation of new or modified air pollution control equipment that are required by this subpart shall be approved through the AQMD permit system.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### SECTION K: TITLE V Administration

#### **GENERAL PROVISIONS**

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

#### **Permit Renewal and Expiration**

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]  
  
(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

#### **Duty to Provide Information**

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

#### **Payment of Fees**

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION K: TITLE V Administration**

#### **Reopening for Cause**

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
  - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
  - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

#### **COMPLIANCE PROVISIONS**

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
  - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
  - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
  - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
  - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
  - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]
  
10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]
  
11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]
  
12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]
  
13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION K: TITLE V Administration**

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
- (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
  - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
  - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
  - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
  - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
  - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency<sup>1</sup> constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
    - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
    - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
    - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
    - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
  - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

---

<sup>1</sup> "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS**

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
  - (B) The date(s) analyses were performed;
  - (C) The company or entity that performed the analyses;
  - (D) The analytical techniques or methods used;
  - (E) The results of such analyses; and
  - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

### **REPORTING PROVISIONS**

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **SECTION K: TITLE V Administration**

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:  
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

### **PERIODIC MONITORING**

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### SECTION K: TITLE V Administration

#### *FACILITY RULES*

*This facility is subject to the following rules and regulations*

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

| <b>RULE SOURCE</b>     | <b>Adopted/Amended Date</b> | <b>FEDERAL Enforceability</b> |
|------------------------|-----------------------------|-------------------------------|
| RULE 109               | 5-2-2003                    | Federally enforceable         |
| RULE 1107              | 1-6-2006                    | Non federally enforceable     |
| RULE 1107              | 11-9-2001                   | Federally enforceable         |
| RULE 1113              | 11-8-1996                   | Federally enforceable         |
| RULE 1113              | 6-3-2011                    | Non federally enforceable     |
| RULE 1124              | 9-21-2001                   | Federally enforceable         |
| RULE 1140              | 2-1-1980                    | Federally enforceable         |
| RULE 1140              | 8-2-1985                    | Non federally enforceable     |
| RULE 1145              | 12-4-2009                   | Non federally enforceable     |
| RULE 1145              | 2-14-1997                   | Federally enforceable         |
| RULE 1146.2            | 5-5-2006                    | Federally enforceable         |
| RULE 1147              | 12-5-2008                   | Non federally enforceable     |
| RULE 1171              | 11-7-2003                   | Federally enforceable         |
| RULE 1171              | 5-1-2009                    | Non federally enforceable     |
| RULE 118               | 12-7-1995                   | Non federally enforceable     |
| RULE 1303(a)(1)-BACT   | 5-10-1996                   | Federally enforceable         |
| RULE 1303(b)(2)-Offset | 5-10-1996                   | Federally enforceable         |
| RULE 1401              | 12-7-1990                   | Non federally enforceable     |
| RULE 1401              | 5-3-2002                    | Non federally enforceable     |
| RULE 1401              | 8-18-2000                   | Non federally enforceable     |
| RULE 1404              | 4-6-1990                    | Non federally enforceable     |
| RULE 1415              | 12-3-2010                   | Non federally enforceable     |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### SECTION K: TITLE V Administration

| <b>RULE SOURCE</b>                       | <b>Adopted/Amended Date</b> | <b>FEDERAL Enforceability</b> |
|--|-----------------------------|-------------------------------|
| RULE 204                                 | 10-8-1993                   | Federally enforceable         |
| RULE 217                                 | 1-5-1990                    | Federally enforceable         |
| RULE 219                                 | 6-1-2007                    | Non federally enforceable     |
| RULE 219                                 | 9-4-1981                    | Federally enforceable         |
| RULE 3002                                | 11-14-1997                  | Federally enforceable         |
| RULE 3002                                | 11-5-2010                   | Non federally enforceable     |
| RULE 3003                                | 11-14-1997                  | Federally enforceable         |
| RULE 3003                                | 11-5-2010                   | Non federally enforceable     |
| RULE 3004                                | 12-12-1997                  | Federally enforceable         |
| RULE 3004(a)(4)-Periodic Monitoring      | 12-12-1997                  | Federally enforceable         |
| RULE 3005                                | 11-14-1997                  | Federally enforceable         |
| RULE 3005                                | 11-5-2010                   | Non federally enforceable     |
| RULE 3007                                | 10-8-1993                   | Federally enforceable         |
| RULE 304                                 | 5-6-2011                    | Non federally enforceable     |
| RULE 401                                 | 11-9-2001                   | Non federally enforceable     |
| RULE 401                                 | 3-2-1984                    | Federally enforceable         |
| RULE 402                                 | 5-7-1976                    | Non federally enforceable     |
| RULE 404                                 | 2-7-1986                    | Federally enforceable         |
| RULE 405                                 | 2-7-1986                    | Federally enforceable         |
| RULE 407                                 | 4-2-1982                    | Federally enforceable         |
| RULE 408                                 | 5-7-1976                    | Federally enforceable         |
| RULE 409                                 | 8-7-1981                    | Federally enforceable         |
| RULE 430                                 | 7-12-1996                   | Non federally enforceable     |
| RULE 442                                 | 12-15-2000                  | Federally enforceable         |
| RULE 443                                 | 5-7-1976                    | Federally enforceable         |
| RULE 481                                 | 1-11-2002                   | Federally enforceable         |
| RULE 701                                 | 6-13-1997                   | Federally enforceable         |
| 40CFR 63 Subpart GG                      | 12-8-2000                   | Federally enforceable         |
| 40CFR 68 - Accidental Release Prevention | 5-24-1996                   | Federally enforceable         |

**FACILITY PERMIT TO OPERATE  
E/M COATING SERVICES**

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN  
PERMIT PURSUANT TO RULE 219

NONE

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

| <b>VOC LIMITS</b>                           |                  |               |                |               |                |               |                |               |
|---|------------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|
| <b>Less Water and Less Exempt Compounds</b> |                  |               |                |               |                |               |                |               |
| <b>Effective Dates</b>                      |                  |               |                |               |                |               |                |               |
| <b>Coating</b>                              | <b>Air-Dried</b> |               |                |               | <b>Baked</b>   |               |                |               |
|   | <b>gm/l</b>      |               | <b>lb/gal</b>  |               | <b>gm/l</b>    |               | <b>lb/gal</b>  |               |
|   | <b>Current</b>   | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> |
| General One-Component                       | 275              | 275           | 2.3            | 2.3           | 275            | 275           | 2.3            | 2.3           |
| General Multi-Component                     | 340              | 340           | 2.8            | 2.8           | 275            | 275           | 2.3            | 2.3           |
| Military Specification                      | 340              | 340           | 2.8            | 2.8           | 275            | 275           | 2.3            | 2.3           |
| Etching Filler                              | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Solar-Absorbent                             | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Heat-Resistant                              | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Extreme High-Gloss                          | 420              | 340           | 3.5            | 2.8           | 360            | 360           | 3.0            | 3.0           |
| Metallic                                    | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

| <b>VOC LIMITS</b>                           |                  |               |                |               |                |               |                |               |
|---|------------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|
| <b>Less Water and Less Exempt Compounds</b> |                  |               |                |               |                |               |                |               |
| <b>Effective Dates, cont.</b>               |                  |               |                |               |                |               |                |               |
| <b>Coating</b>                              | <b>Air-Dried</b> |               |                |               | <b>Baked</b>   |               |                |               |
|   | <b>gm/l</b>      |               | <b>lb/gal</b>  |               | <b>gm/l</b>    |               | <b>lb/gal</b>  |               |
|   | <b>Current</b>   | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> |
| Extreme Performance                         | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Prefabricated Architectural One-Component   | 420              | 275           | 3.5            | 2.3           | 275            | 275           | 2.3            | 2.3           |
| Prefabricated Architectural Multi-Component | 420              | 340           | 3.5            | 2.8           | 275            | 275           | 2.3            | 2.3           |
| Touch Up                                    | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Repair                                      | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Silicone Release                            | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| High-Performance Architectural              | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Camouflage                                  | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Vacuum-Metalizing                           | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Mold-Seal                                   | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| High-Temperature                            | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Electric-Insulating Varnish                 | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Pan Backing                                 | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Pretreatment Coatings                       | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]**

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

| <b>VOC LIMITS</b>                           |                  |               |                |               |                |               |                |               |
|---|------------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|
| <b>Less Water and Less Exempt Compounds</b> |                  |               |                |               |                |               |                |               |
| <b>Effective Dates</b>                      |                  |               |                |               |                |               |                |               |
| <b>Coating</b>                              | <b>Air-Dried</b> |               |                |               | <b>Baked</b>   |               |                |               |
|   | <b>gm/l</b>      |               | <b>lb/gal</b>  |               | <b>gm/l</b>    |               | <b>lb/gal</b>  |               |
|   | <b>Current</b>   | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> |
| General One-Component                       | 275              | 275           | 2.3            | 2.3           | 275            | 275           | 2.3            | 2.3           |
| General Multi-Component                     | 340              | 340           | 2.8            | 2.8           | 275            | 275           | 2.3            | 2.3           |
| Military Specification                      | 340              | 340           | 2.8            | 2.8           | 275            | 275           | 2.3            | 2.3           |
| Etching Filler                              | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Solar-Absorbent                             | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Heat-Resistant                              | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Extreme High-Gloss                          | 420              | 340           | 3.5            | 2.8           | 360            | 360           | 3.0            | 3.0           |
| Metallic                                    | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

| <b>VOC LIMITS</b>                           |                  |               |                |               |                |               |                |               |
|---|------------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|
| <b>Less Water and Less Exempt Compounds</b> |                  |               |                |               |                |               |                |               |
| <b>Effective Dates</b>                      |                  |               |                |               |                |               |                |               |
| <b>Coating</b>                              | <b>Air-Dried</b> |               |                |               | <b>Baked</b>   |               |                |               |
|   | <b>gm/l</b>      |               | <b>lb/gal</b>  |               | <b>gm/l</b>    |               | <b>lb/gal</b>  |               |
|   | <b>Current</b>   | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> |
| General One-Component                       | 275              | 275           | 2.3            | 2.3           | 275            | 275           | 2.3            | 2.3           |
| General Multi-Component                     | 340              | 340           | 2.8            | 2.8           | 275            | 275           | 2.3            | 2.3           |
| Military Specification                      | 340              | 340           | 2.8            | 2.8           | 275            | 275           | 2.3            | 2.3           |
| Etching Filler                              | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Solar-Absorbent                             | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Heat-Resistant                              | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Extreme High-Gloss                          | 420              | 340           | 3.5            | 2.8           | 360            | 360           | 3.0            | 3.0           |
| Metallic                                    | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1107 11-09-2001]

| <b>VOC LIMITS</b>                           |                  |               |                |               |                |               |                |               |
|---|------------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|
| <b>Less Water and Less Exempt Compounds</b> |                  |               |                |               |                |               |                |               |
| <b>Effective Dates, cont.</b>               |                  |               |                |               |                |               |                |               |
| <b>Coating</b>                              | <b>Air-Dried</b> |               |                |               | <b>Baked</b>   |               |                |               |
|   | <b>gm/l</b>      |               | <b>lb/gal</b>  |               | <b>gm/l</b>    |               | <b>lb/gal</b>  |               |
|   | <b>Current</b>   | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> | <b>Current</b> | <b>7/1/07</b> |
| Extreme Performance                         | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Prefabricated Architectural One-Component   | 420              | 275           | 3.5            | 2.3           | 275            | 275           | 2.3            | 2.3           |
| Prefabricated Architectural Multi-Component | 420              | 340           | 3.5            | 2.8           | 275            | 275           | 2.3            | 2.3           |
| Touch Up                                    | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Repair                                      | 420              | 420           | 3.5            | 3.5           | 360            | 360           | 3.0            | 3.0           |
| Silicone Release                            | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| High-Performance Architectural              | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Camouflage                                  | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Vacuum-Metalizing                           | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Mold-Seal                                   | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| High-Temperature                            | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Electric-Insulating Varnish                 | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Pan Backing                                 | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |
| Pretreatment Coatings                       | 420              | 420           | 3.5            | 3.5           | 420            | 420           | 3.5            | 3.5           |

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-08-1996]

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

### TABLE OF STANDARDS

#### VOC LIMITS

#### Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

| COATING                            | Limit* | Effective<br>Date of<br>Adoption | Effective<br>1/1/1998 | Effective<br>1/1/1999 | Effective<br>7/1/2001 | Effective<br>1/1/2005 | Effective<br>7/1/2008 |
|------------------------------------|--------|----------------------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Bond Breakers                      | 350    |                                  |                       |                       |                       |                       |                       |
| Clear Wood Finishes                |        |                                  |                       |                       |                       |                       |                       |
| Varnish                            | 350    |                                  |                       |                       |                       |                       |                       |
| Sanding Sealers                    | 350    |                                  |                       |                       |                       |                       |                       |
| Lacquer                            | 680    |                                  | 550                   |                       |                       | 275                   |                       |
| Concrete-Curing Compounds          | 350    |                                  |                       |                       |                       |                       |                       |
| Dry-Fog Coatings                   | 400    |                                  |                       |                       |                       |                       |                       |
| Fire-proofing Exterior<br>Coatings | 350    | 450                              |                       | 350                   |                       |                       |                       |
| Fire-Retardant Coatings            |        |                                  |                       |                       |                       |                       |                       |
| Clear                              | 650    |                                  |                       |                       |                       |                       |                       |
| Pigmented                          | 350    |                                  |                       |                       |                       |                       |                       |
| Flats                              | 250    |                                  |                       |                       | 100                   |                       | 50                    |
| Graphic Arts (Sign) Coatings       | 500    |                                  |                       |                       |                       |                       |                       |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-08-1996]

|                             |     |     |     |     |     |  |
|-----------------------------|-----|-----|-----|-----|-----|--|
| Industrial Maintenance      |     |     |     |     |     |  |
| Primers and Topcoats        |     |     |     |     |     |  |
| Alkyds                      | 420 |     |     |     |     |  |
| Catalyzed Epoxy             | 420 |     |     |     |     |  |
| Bituminous Coatings         | 420 |     |     |     |     |  |
| Materials                   |     |     |     |     |     |  |
| Inorganic Polymers          | 420 |     |     |     |     |  |
| Vinyl Chloride Polymers     | 420 |     |     |     |     |  |
| Chlorinated Rubber          | 420 |     |     |     |     |  |
| Acrylic Polymers            | 420 |     |     |     |     |  |
| Urethane Polymers           | 420 |     |     |     |     |  |
| Silicones                   | 420 |     |     |     |     |  |
| Unique Vehicles             | 420 |     |     |     |     |  |
| Japans/Faux Finishing       | 350 | 700 |     | 350 |     |  |
| Coatings                    |     |     |     |     |     |  |
| Magnesite Cement Coatings   | 600 |     |     | 450 |     |  |
| Mastic Coatings             | 300 |     |     |     |     |  |
| Metallic Pigmented Coatings | 500 |     |     |     |     |  |
| Multi-Color Coatings        | 420 |     | 250 |     |     |  |
| Pigmented Lacquer           | 680 |     | 550 |     | 275 |  |
| Pre-Treatment Wash Primers  | 780 |     |     |     |     |  |
| Primers, Sealers, and       | 350 |     |     |     |     |  |
| Undercoaters                |     |     |     |     |     |  |
| Quick-Dry Enamels           | 400 |     |     |     |     |  |
| Roof Coatings               | 300 |     |     |     |     |  |
| Shellac                     |     |     |     |     |     |  |
| Clear                       | 730 |     |     |     |     |  |
| Pigmented                   | 550 |     |     |     |     |  |
| Stains                      | 350 |     |     |     |     |  |
| Swimming Pool Coatings      |     |     |     |     |     |  |
| Repair                      | 650 |     |     |     |     |  |
| Other                       | 340 |     |     |     |     |  |
| Traffic Coatings            | 250 |     | 150 |     |     |  |
| Waterproofing Sealers       | 400 |     |     |     |     |  |
| Wood Preservatives          |     |     |     |     |     |  |
| Below-Ground                | 350 |     |     |     |     |  |
| Other                       | 350 |     |     |     |     |  |

\* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

### TABLE OF STANDARDS (cont.)

#### VOC LIMITS

#### Grams of VOC Per Liter of Material

| COATING            | Limit |
|--------------------|-------|
| Low-Solids Coating | 120   |

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]**

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:
  - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
  - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

#### TABLE OF STANDARDS 1 VOC LIMITS

**Grams of VOC Per Liter of Coating,  
Less Water and Less Exempt Compounds**

| COATING CATEGORY   | Ceiling Limit <sup>1</sup> | Current Limit <sup>2</sup> | Effective Date |        |        |
|--|----------------------------|----------------------------|----------------|--------|--------|
|  |                            |                            | 7/1/08         | 1/1/12 | 1/1/14 |
| Bond Breakers  |                            | 350                        |                |        |        |
| Clear Wood Finishes  |                            | 275                        |                |        |        |
| Varnish  | 350                        | 275                        |                |        |        |
| Sanding Sealers  | 350                        | 275                        |                |        |        |
| Lacquer  |                            | 275                        |                |        |        |
| Concrete-Curing Compounds  |                            | 100                        |                |        |        |
| Concrete-Curing Compounds<br>For Roadways and Bridges <sup>3</sup> |                            | 350                        |                |        |        |
| Concrete Surface Retarder  |                            | 250                        |                |        | 50     |
| Driveway Sealer  |                            | 100                        |                | 50     |        |
| Dry-Fog Coatings   |                            | 150                        |                |        | 50     |
| Faux Finishing Coatings  |                            |                            |                |        |        |
| Clear Topcoat  |                            | 350                        |                | 200    |        |
| Decorative Coatings  |                            | 350                        |                |        | 100    |
| Glazes   |                            | 350                        |                |        |        |
| Japan  |                            | 350                        |                |        |        |
| Trowel Applied Coatings  |                            | 350                        |                | 150    | 50     |
| Fire-Proofing Coatings   |                            | 350                        |                |        | 150    |
| Flats  | 250                        | 50                         | 50             |        |        |
| Floor Coatings   | 100                        | 50                         |                |        |        |
| Form Release Compound  |                            | 250                        |                |        | 100    |
| Graphic Arts (Sign) Coatings                                       |                            | 500                        |                |        | 150    |
| Industrial Maintenance (IM) Coatings                               | 420                        | 100                        |                |        |        |
| High Temperature IM Coatings                                       |                            | 420                        |                |        |        |
| Non-Sacrificial Anti-Graffiti Coatings                             |                            | 100                        |                |        |        |
| Zinc-Rich IM Primers   | 340                        | 100                        |                |        |        |
| Magnesite Cement Coatings  |                            | 450                        |                |        |        |
| Mastic Coatings  |                            | 300                        |                |        | 100    |
| Metallic Pigmented Coatings  | 500                        | 500                        |                |        | 150    |
| Multi-Color Coatings   |                            | 250                        |                |        |        |
| Nonflat Coatings   | 150                        | 50                         |                |        |        |
| Pre-Treatment Wash Primers   |                            | 420                        |                |        |        |
| Primers, Sealers, and Undercoaters                                 | 200                        | 100                        |                |        |        |
| Reactive Penetrating Sealers                                       |                            | 350                        |                |        |        |
| Recycled Coatings  |                            | 250                        |                |        |        |
| Roof Coatings  | 250                        | 50                         |                |        |        |
| Roof Coatings, Aluminum  |                            | 100                        |                |        |        |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

|                                    |     |     |  |    |  |
|------------------------------------|-----|-----|--|----|--|
| Roof Primers, Bituminous           | 350 | 350 |  |    |  |
| Rust Preventative Coatings         | 400 | 100 |  |    |  |
| Stone Consolidant                  |     | 450 |  |    |  |
| Sacrificial Anti-Graffiti Coatings |     | 100 |  | 50 |  |
| Shellac                            |     |     |  |    |  |
| Clear                              |     | 730 |  |    |  |
| Pigmented                          |     | 550 |  |    |  |
| Specialty Primers                  | 350 | 100 |  |    |  |
| Stains                             |     | 100 |  |    |  |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

| COATING CATEGORY                       | Ceiling Limit <sup>1</sup> | Current Limit <sup>2</sup> | Effective Date |        |        |
|--|----------------------------|----------------------------|----------------|--------|--------|
|  |                            |                            | 7/1/08         | 1/1/12 | 1/1/14 |
| Stains, Interior                       | 250                        | 250                        |                |        |        |
| Swimming Pool Coatings                 |                            |                            |                |        |        |
| Repair                                 |                            | 340                        |                |        |        |
| Other                                  |                            | 340                        |                |        |        |
| Traffic Coatings                       |                            | 100                        |                |        |        |
| Waterproofing Sealers                  | 250                        | 100                        |                |        |        |
| Waterproofing Concrete/Masonry Sealers | 400                        | 100                        |                |        |        |
| Wood Preservatives                     |                            | 350                        |                |        |        |

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

#### TABLE OF STANDARDS 1 (cont.) VOC LIMITS

##### Grams of VOC Per Liter of Material

| COATING            | Limit |
|--------------------|-------|
| Low-Solids Coating | 120   |

#### TABLE OF STANDARDS 2 VOC LIMITS FOR COLORANTS

##### Grams of VOC Per Liter of Colorant Less Water and Less Exempt Compounds

| COLORANT                                      | Limit <sup>4</sup> |
|---|--------------------|
| Architectural Coatings, excluding IM Coatings | 50                 |
| Solvent-Based IM                              | 600                |
| Waterborne IM                                 | 50                 |

4. Effective January 1, 2014.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1124 09-21-2001]

Except as otherwise provided in Rule 1124

- (1) VOC Content of Aerospace Materials
  - (A) A person shall not apply to aerospace components any materials, including any VOC-containing materials added to the original material supplied by the manufacturer, which contain VOC in excess of the limits specified below:

| <b>VOC Limit</b>  |                                  |   |   |
|---|----------------------------------|---|---|
| <b>Grams of VOC per Liter, Less Water and Less Exempt Compounds</b> |                                  |   |   |
| <b>Primers</b>  | <b>Current<br/>VOC<br/>Limit</b> | <b>VOC<br/>Limit<br/>Effective<br/>1-1-03</b> | <b>VOC<br/>Limit<br/>Effective<br/>1-1-05</b> |
| General Primer  | 350                              | 350   | 350   |
| Low-Solids Corrosion Resistant Primer                               | 350                              | 350   | 350   |
| Pretreatment Primer   | 780                              | 780   | 780   |
| Rain Erosion-Resistant Coating<br>Compatible Primer                 | 850                              | 850   | 850   |
| Adhesion Promoter   | 850                              | 850   | 250   |
| <b>Adhesive Bonding Primer</b>                                      |                                  |   |   |
| New Commercial Aircraft   | 805                              | 250   | 250   |
| All Military Aircraft   | 805                              | 805   | 805   |
| Remanufactured Commercial Aircraft<br>Parts                         | 805                              | 805   | 805   |
| Sonic and Acoustic Applications                                     | 805                              | 805   | 805   |
| <b>Adhesive Bonding Primer</b>                                      |                                  |   |   |
| Long Term   | 250                              | 250   | 250   |
| Short Term  | 250                              | 250   | 250   |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1124 09-21-2001]

| Coatings                                    | Current<br>VOC Limit | VOC Limit<br>Effective<br>3-01-02 |
|---|----------------------|-----------------------------------|
| Topcoat                                     | 420                  | 420                               |
| Clear Topcoat                               | 520                  | 520                               |
| Unicoat                                     | 420                  | 420                               |
| Wing Coating                                | 750                  | 750                               |
| Impact Resistant Coating                    | 420                  | 420                               |
| High-Temperature Coating                    | 850                  | 850                               |
| Antichafe Coating                           | 600                  | 420                               |
| Rain Erosion-Resistant Coating              | 800                  | 800                               |
| Conformal Coating                           | 750                  | 750                               |
| Optical Anti-Reflective Coating             | 700                  | 700                               |
| Scale Inhibitor                             | 880                  | 880                               |
| Metallized Epoxy Coating                    | 700                  | 700                               |
| Electric or Radiation Effect Coating        | 800                  | 800                               |
| Temporary Protective Coating                | 250                  | 250                               |
| Fuel Tank Coatings                          | 420                  | 420                               |
| Mold Release Coatings                       | 780                  | 780                               |
| Flight Test Coatings                        |                      |                                   |
| Used on Missiles or Single Use Target Craft | 420                  | 420                               |
| All Other                                   | 840                  | 840                               |
| Fire Resistant Coatings                     |                      |                                   |
| Commercial                                  | 650                  | 650                               |
| Military                                    | 970                  | 800                               |
| Wire Coatings                               |                      |                                   |
| Phosphate Ester Resistant Ink               | 925                  | 925                               |
| Other                                       | 420                  | 420                               |
| Space Vehicle Coatings                      |                      |                                   |
| Electrostatic Discharge Protection Coating  | 800                  | 800                               |
| Other                                       | 1000                 | 1000                              |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1124 09-21-2001]

| <b>Adhesives</b>        | <b>Current VOC Limit</b> |
|-------------------------|--------------------------|
| Non-Structural Adhesive | 250                      |
| Structural Adhesive     |                          |
| Autoclavable            | 50                       |
| Non-Autoclavable        | 850                      |
| Space Vehicle Adhesive  | 800                      |
| Fuel Tank Adhesive      | 620                      |

| <b>Sealants</b>                           | <b>Current VOC Limit</b> | <b>VOC Limit Effective 3-01-02</b> |
|---|--------------------------|------------------------------------|
| Fastener Sealant                          | 675                      | 675                                |
| Extrudable, Rollable or Brushable Sealant | 600                      | 280                                |
| Other                                     | 600                      | 600                                |

| <b>Maskants</b>                | <b>Current VOC Limit</b> |
|--------------------------------|--------------------------|
| For Chemical Processing        | 250                      |
| For Chemical Milling           |                          |
| Type I                         | 250                      |
| Type II                        | 160                      |
| Photolithographic              | 850                      |
| Touch-up, Line Sealer Maskants | 750                      |

| <b>Lubricants</b>   | <b>Current VOC Limit</b> |
|---|--------------------------|
| Fastener Installation                                     |                          |
| Solid-Film Lubricant                                      | 880                      |
| Dry Lubricative Materials                                 | 675                      |
| Fastener-Lubricative Coatings, Fastener Manufacturing     |                          |
| Solid Film Lubricant                                      | 250                      |
| Dry Lubricative Materials                                 | 120                      |
| Barrier Coating   | 420                      |
| Non-Fastener Lubricative Coatings, Fastener Manufacturing |                          |
| Solid Film Lubricant                                      | 880                      |
| Dry Lubricative Materials                                 | 675                      |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1124 09-21-2001]

| <b>VOC LIMIT</b>                          |   |
|---|---|
| <b>Grams of VOC per Liter of Material</b> |   |
| <b>Cleaning Solvents and Strippers</b>    | <b>Current VOC Limit</b>                                  |
| Cleaning Solvents                         | 200 g/L<br>or<br>45 mm Hg VOC Composite Partial Pressure  |
| Strippers                                 | 300 g/L<br>or<br>9.5 mm Hg VOC Composite Partial Pressure |

- (B) Documents shall be provided to the Executive Officer or his designee demonstrating that unicoat is being used in lieu of the application of a primer and topcoat, and the applicant must receive written approval for the use of unicoat specifying the conditions of application from the Executive Officer or his designee.
  - (C) For low-solids adhesives, coatings, primers or sealants, the appropriate limits in subparagraph (c)(1)(A) shall be expressed in grams of VOC per liter of material.
- (2) Solvent Cleaning Operations; Storage and Disposal of VOC-Containing Materials
- (A) Cleaning of material application equipment and storage of solvent laden cloth and paper shall comply with provisions of Rule 1171.
  - (B) A person shall not atomize any solvent into open air.

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **APPENDIX B: RULE EMISSION LIMITS [RULE 1140 02-01-1980]**

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
  - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
  - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
  - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
  - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

## **FACILITY PERMIT TO OPERATE E/M COATING SERVICES**

### **APPENDIX B: RULE EMISSION LIMITS [RULE 1140 08-02-1985]**

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
  - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
  - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
  - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
  - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1145 12-04-2009]

Except as otherwise provided in Rule 1145, no person shall apply on plastics, rubber, leather, or glass any coatings which are applied with a VOC content in excess of the limits listed in the Table of Standards.

### TABLE OF STANDARDS

| <b>VOC LIMITS</b>                              |     |         |
|--|-----|---------|
| <b>LESS WATER AND LESS EXEMPT COMPOUNDS</b>    |     |         |
| COATING CATEGORIES                             | g/L | lbs/gal |
| Electrical dissipating and shock free coatings | 360 | 3.0     |
| Extreme performance two-component coatings     | 420 | 3.5     |
| General one-component coatings                 | 120 | 1.0     |
| General two-component coatings                 | 120 | 1.0     |
| Leather antique coatings                       | 156 | 1.3     |
| Leather color coatings                         | 60  | 0.5     |
| Leather sealer coatings                        | 60  | 0.5     |
| Leather stain coatings                         | 216 | 1.8     |
| Leather top coatings                           | 120 | 1.0     |
| Metallic coatings                              | 420 | 3.5     |
| Military specification one-component coatings  | 340 | 2.8     |
| Military specification two-component coatings  | 420 | 3.5     |
| Mirror backing curtain coated coatings         | 500 | 4.2     |
| Mirror backing rolled coated coatings          | 312 | 2.6     |
| Mold seal coatings                             | 750 | 6.3     |
| Multi-color coatings                           | 680 | 5.7     |
| Refrigerated glass door coatings               | 480 | 4.0     |
| Optical coatings                               | 50  | 0.4     |
| Vacuum metalizing coatings                     | 800 | 6.7     |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1145 02-14-1997]

Except as otherwise provided in Rule 1145, the operator shall not apply on plastics, glass, or rubber any coatings which are applied with a VOC content in excess of the limits specified below:

#### COATING

|  | <b>VOC LIMITS</b>                        |                |                            |                |
|--|--|----------------|----------------------------|----------------|
|  | <b><u>Less Water and Less Exempt</u></b> |                |                            |                |
|  | <b><u>Compounds</u></b>                  |                |                            |                |
|  | <u>Current</u>                           |                | <u>On and After 1-1-98</u> |                |
|  | <u>g/L</u>                               | <u>lbs/gal</u> | <u>g/L</u>                 | <u>lbs/gal</u> |
| General Coatings                         |  |                |                            |                |
| One-component                            | 275                                      | 2.3            | 275                        | 2.3            |
| Two-component                            | 420                                      | 3.5            | 420                        | 3.5            |
| Military Spec. Coating                   |  |                |                            |                |
| One-component                            | 340                                      | 2.8            | 340                        | 2.8            |
| Two-component                            | 420                                      | 3.5            | 420                        | 3.5            |
| Multi-Colored Coatings                   | 685                                      | 5.7            | 685                        | 5.7            |
| Mold Seal Coatings                       | 750                                      | 6.3            | 750                        | 6.3            |
| Vacuum Metalizing Coatings               | 800                                      | 6.7            | 800                        | 6.7            |
| Mirror Backing                           |  |                |                            |                |
| Curtain Coated                           | 500                                      | 4.2            | 500                        | 4.2            |
| Roll Coated                              | 430                                      | 3.6            | 430                        | 3.6            |
| Optical Coatings                         | 800                                      | 6.7            | 800                        | 6.7            |
| Electric Dissipating Coatings and Shock- |  |                |                            |                |
| Free Coatings                            | 800                                      | 6.7            | 360                        | 3.0            |
| Metallic Coatings                        | 420                                      | 3.5            | 420                        | 3.5            |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| SOLVENT CLEANING ACTIVITY  | CURRENT LIMITS         |
|--|------------------------|
|  | VOC<br>g/l<br>(lb/gal) |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application |                        |
| (i) General  | 25<br>(0.21)           |
| (ii) Electrical Apparatus Components & Electronic Components   | 500<br>(4.2)           |
| (iii) Medical Devices & Pharmaceuticals  | 800<br>(6.7)           |
| (B) Repair and Maintenance Cleaning  |                        |
| (i) General  | 25<br>(0.21)           |
| (ii) Electrical Apparatus Components & Electronic Components   | 900<br>(7.5)           |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

| SOLVENT CLEANING ACTIVITY                                   | CURRENT LIMITS         |
|---|------------------------|
|   | VOC<br>g/l<br>(lb/gal) |
| (iii) Medical Devices & Pharmaceuticals                     |                        |
| (A) Tools, Equipment, & Machinery                           | 800<br>(6.7)           |
| (B) General Work Surfaces                                   | 600<br>(5.0)           |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 550<br>(4.6)           |
| (D) Cleaning of Ink Application Equipment                   |                        |
| (i) General   | 25<br>(0.21)           |
| (ii) Flexographic Printing                                  | 25<br>(0.21)           |
| (iii) Gravure Printing                                      |                        |
| (A) Publication   | 750<br>(6.3)           |
| (B) Packaging   | 25<br>(0.21)           |
| (iv) Lithographic or Letter Press Printing                  |                        |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

| SOLVENT CLEANING ACTIVITY   | CURRENT LIMITS         |
|---|------------------------|
|   | VOC<br>g/l<br>(lb/gal) |
| (A) Roller Wash – Step 1  | 600<br>(5.0)           |
| (B) Roller Wash-Step 2,<br>Blanket Wash, & On-Press Components                            | 800<br>(6.7)           |
| (C) Removable Press Components  | 25<br>(0.21)           |
| (v) Screen Printing   | 750<br>(6.3)           |
| (vi) Ultraviolet Ink/ Electron Beam Ink<br>Application Equipment (except screen printing) | 800<br>(6.7)           |
| (vii) Specialty Flexographic Printing   | 600<br>(5.0)           |
| (E) Cleaning of Polyester Resin Application Equipment                                     | 25<br>(0.21)           |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

|  | <b>CURRENT<br/>LIMITS*</b>      | <b>EFFECTIVE<br/>1/1/2010</b>   |
|--|---------------------------------|---------------------------------|
| <b>SOLVENT CLEANING ACTIVITY</b>   | <b>VOC<br/>g/l<br/>(lb/gal)</b> | <b>VOC<br/>g/l<br/>(lb/gal)</b> |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application |                                 |                                 |
| (i) General  | 25<br>(0.21)                    |                                 |
| (ii) Electrical Apparatus Components & Electronic Components   | 100<br>(0.83)                   |                                 |
| (iii) Medical Devices & Pharmaceuticals  | 800<br>(6.7)                    |                                 |
| (B) Repair and Maintenance Cleaning  |                                 |                                 |
| (i) General  | 25<br>(0.21)                    |                                 |
| (ii) Electrical Apparatus Components & Electronic Components   | 100<br>(0.83)                   |                                 |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

|   | <b>CURRENT<br/>LIMITS*</b>      | <b>EFFECTIVE<br/>1/1/2010</b>   |
|---|---------------------------------|---------------------------------|
| <b>SOLVENT CLEANING ACTIVITY<br/>(cont.)</b>                | <b>VOC<br/>g/l<br/>(lb/gal)</b> | <b>VOC<br/>g/l<br/>(lb/gal)</b> |
| (iii) Medical Devices & Pharmaceuticals                     |                                 |                                 |
| (A) Tools, Equipment, & Machinery                           | 800<br>(6.7)                    |                                 |
| (B) General Work Surfaces                                   | 600<br>(5.0)                    |                                 |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 25<br>(0.21)                    |                                 |
| (D) Cleaning of Ink Application Equipment                   |                                 |                                 |
| (i) General   | 25<br>(0.21)                    |                                 |
| (ii) Flexographic Printing                                  | 25<br>(0.21)                    |                                 |
| (iii) Gravure Printing                                      |                                 |                                 |
| (A) Publication   | 100<br>(0.83)                   |                                 |
| (B) Packaging   | 25<br>(0.21)                    |                                 |
| (iv) Lithographic (Offset) or Letter Press Printing         |                                 |                                 |
| (A) Roller Wash, Blanket Wash, & On-Press Components        | 100<br>(0.83)                   |                                 |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

|  | <b>CURRENT<br/>LIMITS*</b>      | <b>EFFECTIVE<br/>1/1/2010</b>   |
|--|---------------------------------|---------------------------------|
| <b>SOLVENT CLEANING ACTIVITY<br/>(cont.)</b>   | <b>VOC<br/>g/l<br/>(lb/gal)</b> | <b>VOC<br/>g/l<br/>(lb/gal)</b> |
| (B) Removable Press Components   | 25<br>(0.21)                    |                                 |
| (v) Screen Printing  | 100<br>(0.83)                   |                                 |
| (vi) Ultraviolet Ink/ Electron Beam Ink<br>Application Equipment (except<br>screen printing) | 650<br>(5.4)                    | 100<br>(0.83)                   |
| (vii) Specialty Flexographic Printing  | 100<br>(0.83)                   |                                 |
| (E) Cleaning of Polyester Resin Application<br>Equipment                                     | 25<br>(0.21)                    |                                 |

\* The specified limits remain in effect unless revised limits are listed in subsequent columns.

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

**TABLE 404(a)**

| Volume Discharged<br>Calculated as Dry<br>Gas<br>At Standard<br>Conditions |                                | Maximum Concentration<br>of Particulate<br>Matter Allowed in<br>Discharged Gas<br>Calculated as Dry<br>Gas at Standard<br>Conditions |                          | Volume Discharged<br>Calculated as Dry Gas<br>At Standard Conditions |                                | Maximum Concentration<br>of Particulate Matter<br>Allowed in Discharged<br>Gas Calculated as Dry Gas<br>at<br>Standard Conditions |                             |
|--|--------------------------------|--|--------------------------|--|--------------------------------|---|-----------------------------|
|  |                                | Milligrams<br>per<br>Cubic<br>Meter  | Grains per<br>Cubic Foot |  |                                | Milligrams<br>per<br>Cubic Meter  | Grains per<br>Cubic<br>Foot |
| Cubic<br>meters<br>Per<br>Minute   | Cubic<br>feet<br>Per<br>Minute |  |                          | Cubic<br>meters<br>Per Minute  | Cubic<br>feet<br>Per<br>Minute |   |                             |
| 25 or<br>less  | 883<br>or<br>less              | 450  | 0.196                    | 900  | 31780                          | 118   | 0.0515                      |
| 30   | 1059                           | 420  | .183                     | 1000   | 35310                          | 113   | .0493                       |
| 35   | 1236                           | 397  | .173                     | 1100   | 38850                          | 109   | .0476                       |
| 40   | 1413                           | 377  | .165                     | 1200   | 42380                          | 106   | .0463                       |
| 45   | 1589                           | 361  | .158                     | 1300   | 45910                          | 102   | .0445                       |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

| Volume Discharged<br>Calculated as Dry<br>Gas<br>At Standard<br>Conditions |                                | Maximum Concentration<br>of Particulate<br>Matter Allowed in<br>Discharged Gas<br>Calculated as Dry<br>Gas at Standard<br>Conditions |                          | Volume Discharged<br>Calculated as Dry Gas<br>At Standard Conditions |                                | Maximum Concentration<br>of Particulate Matter<br>Allowed in Discharged<br>Gas Calculated as Dry Gas<br>at<br>Standard Conditions |                             |
|--|--------------------------------|--|--------------------------|--|--------------------------------|---|-----------------------------|
|  |                                | Milligrams<br>per<br>Cubic<br>Meter  | Grains per<br>Cubic Foot |  |                                | Milligrams<br>per<br>Cubic Meter  | Grains per<br>Cubic<br>Foot |
| Cubic<br>meters<br>Per<br>Minute   | Cubic<br>feet<br>Per<br>Minute |  |                          | Cubic<br>meters<br>Per<br>Minute                                     | Cubic<br>feet<br>Per<br>Minute |   |                             |
| 50   | 1766                           | 347  | .152                     | 1400   | 49440                          | 100   | .0437                       |
| 60   | 2119                           | 324  | .141                     | 1500   | 52970                          | 97  | .0424                       |
| 70   | 2472                           | 306  | .134                     | 1750   | 61800                          | 92  | .0402                       |
| 80   | 2825                           | 291  | .127                     | 2000   | 70630                          | 87  | .0380                       |
| 90   | 3178                           | 279  | .122                     | 2250   | 79460                          | 83  | .0362                       |
| 100  | 3531                           | 267  | .117                     | 2500   | 88290                          | 80  | .0349                       |
| 125  | 4414                           | 246  | .107                     | 3000   | 105900                         | 75  | .0327                       |
| 150  | 5297                           | 230  | .100                     | 4000   | 141300                         | 67  | .0293                       |
| 175  | 6180                           | 217  | .0947                    | 5000   | 176600                         | 62  | .0271                       |
| 200  | 7063                           | 206  | .0900                    | 6000   | 211900                         | 58  | .0253                       |
| 250  | 8829                           | 190  | .0830                    | 8000   | 282500                         | 52  | .0227                       |
| 300  | 10590                          | 177  | .0773                    | 10000  | 353100                         | 48  | .0210                       |
| 350  | 12360                          | 167  | .0730                    | 15000  | 529700                         | 41  | .0179                       |
| 400  | 14130                          | 159  | .0694                    | 20000  | 706300                         | 37  | .0162                       |
| 450  | 15890                          | 152  | .0664                    | 25000  | 882900                         | 34  | .0148                       |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

| Volume Discharged<br>Calculated as Dry<br>Gas<br>At Standard<br>Conditions |                                | Maximum Concentration<br>of Particulate<br>Matter” Allowed in<br>Discharged Gas<br>Calculated as Dry<br>Gas at Standard<br>Conditions |                          | Volume Discharged<br>Calculated as Dry Gas<br>At Standard Conditions |                                | Maximum Concentration<br>of Particulate Matter<br>Allowed in Discharged<br>Gas Calculated as Dry Gas<br>at<br>Standard Conditions |                             |
|--|--------------------------------|---|--------------------------|--|--------------------------------|---|-----------------------------|
|  |                                | Milligrams<br>per<br>Cubic<br>Meter   | Grains per<br>Cubic Foot |  |                                | Milligrams<br>per<br>Cubic Meter  | Grains per<br>Cubic<br>Foot |
| Cubic<br>meters<br>Per<br>Minute   | Cubic<br>feet<br>Per<br>Minute |   |                          | Cubic<br>meters<br>Per Minute  | Cubic<br>feet<br>Per<br>Minute |   |                             |
| 500  | 17660                          | 146   | .0637                    | 30000  | 1059000                        | 32  | .0140                       |
| 600  | 21190                          | 137   | .0598                    | 40000  | 1413000                        | 28  | .0122                       |
| 700  | 24720                          | 129   | .0563                    | 50000  | 1766000                        | 26  | .0114                       |
| 800  | 28250                          | 123   | .0537                    | 70000<br>or more   | 2472000<br>or more             | 23  | .0100                       |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

**TABLE 405(a)**

| Process Weight<br>Per Hour |                | Maximum Discharge<br>Rate<br>Allowed for Solid<br>Particulate Matter<br>(Aggregate<br>Discharged From All<br>Points of<br>Process |                    | Process Weight<br>Per Hour |       | Maximum Discharge Rate<br>Allowed for Solid<br>Particulate Matter<br>(Aggregate Discharged<br>From All points of<br>Process |                    |
|----------------------------|----------------|---|--------------------|----------------------------|-------|---|--------------------|
|                            |                | Kilograms<br>Per Hour   | Pounds<br>Per Hour |                            |       | Kilograms<br>Per Hour   | Pounds<br>Per Hour |
| 100 or<br>less             | 220 or<br>less | 0.450   | 0.99               | 9000                       | 19840 | 5.308   | 11.7               |
| 150                        | 331            | 0.585   | 1.29               | 10000                      | 22050 | 5.440   | 12.0               |
| 200                        | 441            | 0.703   | 1.55               | 12500                      | 27560 | 5.732   | 12.6               |
| 250                        | 551            | 0.804   | 1.77               | 15000                      | 33070 | 5.982   | 13.2               |
| 300                        | 661            | 0.897   | 1.98               | 17500                      | 38580 | 6.202   | 13.7               |
| 350                        | 772            | 0.983   | 2.17               | 20000                      | 44090 | 6.399   | 14.1               |
| 400                        | 882            | 1.063   | 2.34               | 25000                      | 55120 | 6.743   | 14.9               |
| 450                        | 992            | 1.138   | 2.51               | 30000                      | 66140 | 7.037   | 15.5               |
| 500                        | 1102           | 1.209   | 2.67               | 35000                      | 77160 | 7.296   | 16.1               |
| 600                        | 1323           | 1.340   | 2.95               | 40000                      | 88180 | 7.527   | 16.6               |

## FACILITY PERMIT TO OPERATE E/M COATING SERVICES

### APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

| Process Weight<br>Per Hour |       | Maximum Discharge<br>Rate<br>Allowed for Solid<br>Particulate Matter<br>(Aggregate<br>Discharged From All<br>Points of<br>Process |                    | Process Weight<br>Per Hour |                    | Maximum Discharge Rate<br>Allowed for Solid<br>Particulate Matter<br>(Aggregate Discharged<br>From All points of<br>Process |                    |
|----------------------------|-------|---|--------------------|----------------------------|--------------------|---|--------------------|
|                            |       | Kilograms<br>Per Hour   | Pounds<br>Per Hour |                            |                    | Kilograms<br>Per Hour   | Pounds<br>Per Hour |
| 700                        | 1543  | 1.461   | 3.22               | 45000                      | 99210              | 7.738   | 17.1               |
| 800                        | 1764  | 1.573   | 3.47               | 50000                      | 110200             | 7.931   | 17.5               |
| 900                        | 1984  | 1.678   | 3.70               | 60000                      | 132300             | 8.277   | 18.2               |
| 1000                       | 2205  | 1.777   | 3.92               | 70000                      | 154300             | 8.582   | 18.9               |
| 1250                       | 2756  | 2.003   | 4.42               | 80000                      | 176400             | 8.854   | 19.5               |
| 1500                       | 3307  | 2.206   | 4.86               | 90000                      | 198400             | 9.102   | 20.1               |
| 1750                       | 3858  | 2.392   | 5.27               | 100000                     | 220500             | 9.329   | 20.6               |
| 2000                       | 4409  | 2.563   | 5.65               | 125000                     | 275600             | 9.830   | 21.7               |
| 2250                       | 4960  | 2.723   | 6.00               | 150000                     | 330700             | 10.26   | 22.6               |
| 2500                       | 5512  | 2.874   | 6.34               | 175000                     | 385800             | 10.64   | 23.5               |
| 2750                       | 6063  | 3.016   | 6.65               | 200000                     | 440900             | 10.97   | 24.2               |
| 3000                       | 6614  | 3.151   | 6.95               | 225000                     | 496000             | 11.28   | 24.9               |
| 3250                       | 7165  | 3.280   | 7.23               | 250000                     | 551200             | 11.56   | 25.5               |
| 3600                       | 7716  | 3.404   | 7.50               | 275000                     | 606300             | 11.82   | 26.1               |
| 4000                       | 8818  | 3.637   | 8.02               | 300000                     | 661400             | 12.07   | 26.6               |
| 4500                       | 9921  | 3.855   | 8.50               | 325000                     | 716500             | 12.30   | 27.1               |
| 5000                       | 11020 | 4.059   | 8.95               | 350000                     | 771600             | 12.51   | 27.6               |
| 6000                       | 13230 | 4.434   | 9.78               | 400000                     | 881800             | 12.91   | 28.5               |
| 7000                       | 15430 | 4.775   | 10.5               | 450000                     | 992100             | 13.27   | 29.3               |
| 8000                       | 17640 | 5.089   | 11.2               | 500000<br>or more          | 1102000<br>or more | 13.60   | 30.0               |