



FACILITY PERMIT TO OPERATE

**ROHR, INC.
8200 ARLINGTON AVE
RIVERSIDE, CA 92503**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By 
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance



FACILITY PERMIT TO OPERATE ROHR, INC.

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	7	07/06/2010
B	RECLAIM Annual Emission Allocation	20	07/01/2012
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	29	12/20/2011
E	Administrative Conditions	8	07/06/2010
F	RECLAIM Monitoring and Source Testing Requirements	6	07/06/2010
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	6	07/06/2010
H	Permit To Construct and Temporary Permit to Operate	17	05/21/2013
I	Compliance Plans & Schedules	4	07/06/2010
J	Air Toxics	2	07/06/2010
K	Title V Administration	7	05/21/2013
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	6	07/06/2010
B	Rule Emission Limits	5	05/21/2013

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 1: OVENS					P2.1
HEATER, MAKEUP AIR, CURING ROOM, NATURAL GAS, 20 FT. W. X 60 FT. L. X 10 FT. H, WITH LOW NOX BURNER, 0.887 MMBTU/HR A/N: 498846 Permit to Construct Issued: 08/06/09	D252		NOX: PROCESS UNIT**	CO: 50 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 30 PPMV (4) [RULE 2005, 6-3-2011]; NOX: 130 LBS/MMSCF (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	E193.2
Process 4: SURFACE COATING					P2.1
SPRAY COATING OPERATION, SOLVENT, G81, 18 FT. W. X 18 FT. L. X 8 FT. H., WITH FORTY 20 X 20 1 ST STAGE FILTERS, FORTY 20 X 20 2 ND STAGE EXHAUST FILTERS, AND 3 H.P. EXHAUST FAN, WITH SPRAY BOOTH WITH A/N: 498845 Permit to Construct Issued: 08/06/09	D250			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.20, B27.11, C1.21, C6.20, D322.1, E71.1, E175.3, E193.2, H23.5, K67.1, K67.2, K67.6
HEATER, MAKEUP AIR, NATURAL GAS, MODEL WINNOX WX400 LOW NOX BURNER, WITH LOW NOX BURNER, 0.887 MMBTU/HR	D251		NOX: PROCESS UNIT**	CO: 50 PPMV (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 30 PPMV (4) [RULE 2005, 6-3-2011]; NOX: 130 LBS/MMSCF (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	
System 1: PRODUCTION SPRAY BOOTHS					

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 4: SURFACE COATING					P2.1
SPRAY COATING OPERATION, G-10, 18 FT W. X 18 FT L. X 9 FT H., 1-BLANKET, 36SQFT, 15-24"X24" PANEL, 15-24"X24"X15" POCKET, 15-24"X24"X11.5" HEPA FILTERS, 2-20.96HP EXHAUST FANS, WITH SPRAY BOOTH A/N: 527006 Permit to Construct Issued: 12/20/11	D28			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.14, C6.10, D182.2, D322.1, E71.1, E71.4, E175.9, H23.11, K67.1, K67.2, K67.6
SPRAY COATING OPERATION, METALIZING, SOLVENT, G-2A, 16 FT W. X 20 FT L. X 12 FT H., 1-BLANKET, 36SQFT, 15-24"X24" PANEL, 15-24"X24"X15" POCKET, 15-24"X24"X11.5" HEPA FILTERS, 1-44.36HP EXHAUST FAN, WITH SPRAY BOOTH A/N: 527007 Permit to Construct Issued: 12/20/11	D41			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.14, B59.11, C1.4, C6.10, D182.2, D322.1, E71.1, E71.4, E175.9, H23.11, K67.1, K67.2, K67.6
SPRAY COATING OPERATION, G-31, 26FT W. X 36FT L. X 12FT H., 1-BLANKET, 36SQFT, 15-24"X24" PANEL, 15-24"X24"X15" POCKET, 15-24"X24"X11.5" HEPA FILTERS, 1-48.42HP EXHAUST FAN, WITH SPRAY BOOTH A/N: 527005 Permit to Construct Issued: 12/20/11	D151			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.23, B59.11, C1.6, C6.10, D182.2, D322.1, E71.1, E71.4, E175.9, H23.11, K67.1, K67.2, K67.6

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 4: SURFACE COATING					P2.1
SPRAY COATING OPERATION, 14 FT W. X 26FT L. X 9 FT H., 1ST BLANKET, 2ND 24- 24 X 24 X 2 IN PANEL, 3RD 24, 24 X 24 X 15 IN POCKET, 26-24 X 24 X 11.5 IN FINAL HEPA FLTRS,1-7.5HP EXH. FAN A/N: 541177 Permit to Construct Issued: 01/02/13	D210			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.7, B27.12, C1.26, C1.27, C6.24, C6.25, D322.1, E71.7, E175.1, E175.10, H23.11, K67.1, K67.2, K67.6
SPRAY COATING OPERATION, G-82, 20 FT W. X 21FT L. X 8 FT-6 IN H., 1-60" X 144" BLANKET, 36-24" X 24" X 4 SECONDARY & 36-24" X 24" X 12" HEPA FILTERS, WITH 2-9 HP FANS A/N: 509673 Permit to Construct Issued: 07/06/10	D258			PM: (9) [RULE 404, 2-7-1986]; VOC: (10) [40CFR 63 Subpart GG, 12-8-2000]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.14, C6.4, D182.2, D322.1, E71.1, E71.4, E175.5, H23.11, K67.1, K67.2, K67.6, L341.2
SPRAY COATING OPERATION, G-83, 20 FT W. X 21FT L. X 8 FT-6 IN H., 1-60" X 144" BLANKET, 36-24" X 24" X 4 SECONDARY & 36-24" X 24" X 12" HEPA FILTERS, WITH 2-9 HP FANS A/N: 509680 Permit to Construct Issued: 07/06/10	D259			PM: (9) [RULE 404, 2-7-1986]; VOC: (10) [40CFR 63 Subpart GG, 12-8-2000]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.14, C6.4, D182.2, D322.1, E71.1, E71.4, E175.5, H23.11, K67.1, K67.2, K67.6, L341.1

* (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 4: SURFACE COATING					P2.1
SPRAY COATING OPERATION, GLOBAL FINISHING SOLUTIONS, AUTOMOTIVE TYPE, 21 FT W X 21FT L X 12 FT-6 IN H, EIGHT 20 X 20 IN. POCKET FILTERS AND ONE 2-HP EXHAUST FAN A/N: 523904 Permit to Construct Issued: 12/20/11	D265	C266		HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1168, 1-7-2005; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.22, B59.4, C1.25, C6.24, D322.1, E175.8, E193.2, H23.17, K67.1, K67.2, K67.6
AFTERBURNER, ADWEST TECHNOLOGIES, MODEL RETOX 3000, WITH 450,000 BTU/HOUR NGL, ONE 3-HP COMBUSTION AIR BLOWER, EXHAUST SYSTEM WITH A 15 HP BLOWER @ 3000 SCFM, WITH LOW NOX BURNER, 0.867 MMBTU/HR WITH A/N: 525293 Permit to Construct Issued: 12/20/11 BURNER, 867,000 BTU/HR, NATURAL GAS, MAXON, MODEL KINEDIZER LE3", WITH LOW NOX BURNER	C266	D265	NOX: PROCESS UNIT**	CO: 2000 NATURAL GAS (5A) [RULE 407, 4-2-1982]; NOX: 30 PPMV NATURAL GAS (4) [RULE 2005, 6-3-2011]; NOX: 130 LBS/MMSCF (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	A72.1, A72.2, C8.1, D28.1, D29.2, E193.2
SPRAY COATING OPERATION, G-86, 18FT W. X 19FT L. X 8FT-10IN H., 1-BLANKET FILTER, 36SQFT, 12-24"X24" PANEL, 12-24"X24"X15" POCKET, 12-24"X24"X11.5" HEPA FILTERS, WITH A 15-HP EXHAUST FAN, WITH SPRAY BOOTH A/N: 527000 Permit to Construct Issued: 12/20/11	D268			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.14, C6.10, D182.2, D322.1, E71.1, E71.4, E175.9, H23.11, K67.1, K67.2, K67.6, L341.4

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 4: SURFACE COATING					P2.1
SPRAY COATING OPERATION, METALIZING, SOLVENT, G-2B, 16 FT W. X 20 FT L. X 12 FT H., 1-BLANKET, 36SQFT, 15-24"X24" PANEL, 15-24"X24"X15" POCKET, 15-24"X24"X11.5" HEPA FILTERS, 1-44.36HP EXHAUST FAN, WITH SPRAY BOOTH A/N: 528002 Permit to Construct Issued: 12/20/11	D270			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.14, B59.11, C1.4, C6.10, D182.2, D322.1, E71.1, E71.4, E175.9, H23.11, K67.1, K67.2, K67.6
SPRAY COATING OPERATION, METALIZING, SOLVENT, G-2C, 16 FT W. X 20 FT L. X 12 FT H., 1-BLANKET, 36SQFT, 15-24"X24" PANEL, 15-24"X24"X15" POCKET, 15-24"X24"X11.5" HEPA FILTERS, 1-44.36HP EXHAUST FAN, WITH SPRAY BOOTH A/N: 528003 Permit to Construct Issued: 12/20/11	D271			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.14, B59.11, C1.4, C6.10, D182.2, D322.1, E71.1, E71.4, E175.9, H23.11, K67.1, K67.2, K67.6
SPRAY COATING OPERATION, METALIZING, SOLVENT, G-2D, 16 FT W. X 20 FT L. X 12 FT H., 1-BLANKET, 36SQFT, 15-24"X24" PANEL, 15-24"X24"X15" POCKET, 15-24"X24"X11.5" HEPA FILTERS, 1-44.36HP EXHAUST FAN, WITH SPRAY BOOTH A/N: 528005 Permit to Construct Issued: 12/20/11	D272			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986; RULE 405, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.14, B59.11, C1.4, C6.10, D182.2, D322.1, E71.1, E71.4, E175.9, H23.11, K67.1, K67.2, K67.6
System 2: SUPPORT OPERATION SPRAY BOOTHS					

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 4: SURFACE COATING					P2.1
SPRAY COATING OPERATION, G-85, 21FT-4IN W. X 24FT-8IN L. X 12FT-2IN H., 1-BLANKET FILTER, 36SQFT, 12-24"X24"PANEL, 12-24"X24"X15"POCKET,4-24"X24"X 11.5"HEPA FILTERS, & A 7.5HP FAN, WITH SPRAY BOOTH A/N: 526999 Permit to Construct Issued: 12/20/11	D267			HAP: (10) [40CFR 63 Subpart GG, 12-8-2000]; PM: (9) [RULE 404, 2-7-1986]; VOC: (9) [RULE 1124, 9-21-2001; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009]	A63.17, C6.10, D182.2, D322.1, E71.4, E71.6, E175.9, H23.11, K67.1, K67.2, K67.6, L341.3
Process 9: ABRASIVE BLASTING					
ABRASIVE BLASTING, ROOM, MAXIMUM AIR SUPPLIED 80 PSI, MAXIMUM 3/4 IN INNER NOZZLE DIA., ALUMINUM OXIDE, WIDTH: 16 FT ; HEIGHT: 12 FT ; LENGTH: 23 FT WITH A/N: 532303 Permit to Construct Issued: 06/27/12 ABRASIVE BLASTING NOZZLE, FOUR HOPPER, PROGRESSIVE SURFACES, AUTO MEDIA ADDED , VOULUME 40 1/2 CUBIC FEET, AIR OPERATED VALVE CYCLONE, PROGRESSIVE SURFACES, WITH RAT TRAP FILTER, HEIGHT: 7 FT 9 IN; DIAMETER: 4 FT	D67	C70 C274		PM: (9) [RULE 1140, 2-1-1980; RULE 1140, 8-2-1985; RULE 405, 2-7-1986]	D323.1, E193.2, E448.1, K67.9

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 9: ABRASIVE BLASTING					
BAGHOUSE, WITH PULSE JET CLEANING SYSTEM, FARR, MODEL GS12SQ, EACH CARTRIDGE 15 IN DIA X 39 IN LENGTH, 12 CARTRIDGE A/N: 532304 Permit to Construct Issued: 06/27/12	C274	D67		PM: (9) [RULE 404, 2-7-1986]	A63.21, C6.19, D322.2, E102.1, E193.2, H23.14, K67.1
Process 20: LASER CUTTING					
CUTTER, R & D PROTOTYPE, LASER, MODEL NO. YLP-1/100/20, 220 WATTS MAXIMUM A/N: 534123 Permit to Construct Issued: 06/27/12	D248	C264		PM: (9) [RULE 405, 2-7-1986]	B59.12, C1.20, D323.1, E57.1, E147.1, E193.2, E193.3
CUTTER, R & D, LASER, MODEL NO. ASC-3-SPI-20, 220 WATTS MAXIMUM A/N: 525296 Permit to Construct Issued: 12/20/11	D253	C264		PM: (9) [RULE 405, 2-7-1986]	B59.10, C1.20, D323.1, E57.1, E147.1, E193.2, E193.3
CUTTER, R&D PROTOTYPE, SPI LASER REENERGY NO. 2, MODEL #20/HS, WITH FOUR LASERS, 1000, WATTS MAXIMUM INPUT, INCORPORATED INTO ARGES LASER SCANNING, # TIGERCLAW-4 A/N: 525295 Permit to Construct Issued: 12/20/11	D260	C264		PM: (9) [RULE 405, 2-7-1986]	B59.10, C1.24, D323.1, E57.1, E147.1, E175.6, E193.2, E193.3

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 20: LASER CUTTING					
DUST COLLECTOR, TWO STAGE FILTER CONSISTING: PRE-FILTER, DAYTON, 3AA31, 0.75 HP, FUMEX, FA5, WITH MAX 95 SQ. FT PLEATED FILTER, AND 1 FINAL HEPA FILTER A/N: 534122 Permit to Construct Issued: 06/27/12	C264	D248 D253 D260		PM: (9) [RULE 404, 2-7-1986]	A63.21, C6.19, D29.1, D90.2, D322.4, D381.2, E102.1, E175.6, E193.2, E193.3, H23.14, K67.1
CUTTER, R & D, PROTOTYPE, LASER NO. 1, 220 WATTS MAXIMUM INPUT A/N: 546538 Permit to Construct Issued: 05/21/13	D275	C277		PM: (9) [RULE 404, 2-7-1986]	B59.12, C1.20, D323.1, E57.1, E147.1, E193.2
CUTTER, CUTTER, R&D PROTOTYPE, LASER NO. 2, 1000 WATTS MAXIMUM INPUT A/N: 546543 Permit to Construct Issued: 05/21/13	D276	C277		PM: (9) [RULE 404, 2-7-1986]	B59.12, C1.24, D323.1, E57.1, E147.1, E193.2
DUST COLLECTOR, FSC2, THREE STAGE FILTERS CONSISTING: PRE-FILTER: 220 SQ. FT, SECOND STAGE :, CARBON & ALUMINA, AND ONE 1 SQ. FT HEPA FINAL FILTER, WITH 2 HP, .552 CFM BLOWER A/N: 546537 Permit to Construct Issued: 05/21/13	C277	D275 D276		PM: (9) [RULE 404, 2-7-1986]	A63.21, C6.19, D90.2, D322.4, D381.2, E102.1, E175.6, E193.2, H23.14, K67.1
Process 21: SOIL VAPOR EXTRACTION					

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 21: SOIL VAPOR EXTRACTION					
CARBON ADSORBER, GRANULATED ACTIVATED CARBON, WITH A 50-HP VACUUM BLOWER, 2500 CFM, 10000 LBS WITH A/N: 510198 Permit to Construct Issued: 07/06/10 VAPOR EXTRACTION WELL, 12-AIR SPARGING WELLS, WITH A 20-HP COMPRESSOR., 39 TOTAL	C256				C6.21, C6.22, C6.23, D90.3, D90.4, D90.5, E71.5, E128.1, E153.2, H23.16

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: DEVICE ID INDEX

Device Index For Section H			
Device ID	Section H Page No.	Process	System
D28	2	4	1
D41	2	4	1
D67	6	9	0
D151	2	4	1
D210	3	4	1
D248	7	20	0
D250	1	4	0
D251	1	4	0
D252	1	1	0
D253	7	20	0
C256	9	21	0
D258	3	4	1
D259	3	4	1
D260	7	20	0
C264	8	20	0
D265	4	4	1
C266	4	4	1
D267	6	4	2
D268	4	4	1
D270	5	4	1
D271	5	4	1
D272	5	4	1
C274	7	9	0
D275	8	20	0
D276	8	20	0
C277	8	20	0

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

F14.1 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 9-15-2000]

F14.2 The operator shall not use diesel fuel containing sulfur compounds in excess of 0.05 percent by weight.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

PROCESS CONDITIONS

P2.1 The operator shall limit emissions from this process as follows

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than or equal to 1179 LBS IN ANY ONE DAY

For the purposes of this condition, the emission limit(s) shall be based on the total combined emissions from process 1(Ovens) and 4 (Surface coating).

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Processes subject to this condition : 1, 4]

DEVICE CONDITIONS

A. Emission Limits

A63.7 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than or equal to 10 LBS IN ANY ONE DAY

[**RULE 1132(h)(2) - Exemptions, 3-5-2004**; RULE 1132(h)(2) - Exemptions, 5-7-2004;
RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D210]

A63.14 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than or equal to 25 LBS IN ANY ONE DAY

For the purposes of this condition, and for exemption from Rule 1132 by (h)(2), the VOC emissions from this spray booth shall be defined as the monthly average for each calendar month, calculated by dividing the total emissions from this spray booth for the calendar month by the number of calendar days in that month.

[**RULE 1132(h)(2) - Exemptions, 3-5-2004**; RULE 1132(h)(2) - Exemptions, 5-7-2004]

[Devices subject to this condition : D28, D41, D258, D259, D268, D270, D271, D272]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

A63.17 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than or equal to 12 LBS IN ANY ONE DAY

For the purposes of this condition, and for exemption from Rule 1132 by (h)(2), the VOC emissions from this spray booth shall be defined as the monthly average for each calendar month, calculated by dividing the total emissions from this spray booth for the calendar month by the number of calendar days in that month.

[RULE 1132(h)(2) - Exemptions, 3-5-2004; RULE 1132(h)(2) - Exemptions, 5-7-2004]

[Devices subject to this condition : D267]

A63.20 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than or equal to 13 LBS IN ANY ONE DAY

**[RULE 1132(h)(2) - Exemptions, 3-5-2004; RULE 1132(h)(2) - Exemptions, 5-7-2004;
 RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**

[Devices subject to this condition : D250]

A63.21 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
Visible emissions	Less than or equal to 0 Percent Opacity

[RULE 1155, 12-4-2009]

[Devices subject to this condition : C264, C274, C277]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

A63.22 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than 10 TONS IN ANY 12-MONTH PERIOD

This limit is based on the total of all VOC emissions from the spray booth prior to the venting to the thermal oxidizer

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D265]

A63.23 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
VOC	Less than or equal to 25 LBS IN ANY ONE DAY

**[RULE 1132(h)(2) - Exemptions, 3-5-2004; RULE 1132(h)(2) - Exemptions, 5-7-2004;
 RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]**

[Devices subject to this condition : D151]

A72.1 The operator shall maintain this equipment to achieve a minimum destruction efficiency of 95 percent for ROG during the normal operation of the equipment it vents.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C266]

A72.2 The operator shall maintain this equipment to achieve a minimum overall control efficiency of 95 percent for ROG during the normal operation of the equipment it vents.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C266]

B. Material/Fuel Type Limits

B27.11 The operator shall not use materials, except for methyl ethyl ketone, xylene, toluene, ethyl benzene, and ethylene glycol methyl ether, containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401, as amended 03/07/2008.

[RULE 1401, 3-7-2008]

[Devices subject to this condition : D250]

B27.12 The operator shall not use materials, (except methyl ethyl ketone, xylene, toluene, ethyl benzene, chromium and chromium compounds, and methylene diphenyl diisocyanate) containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401, as amended 09/10/2010.

1. The concentration of hexavalent chromium shall be less than 33% as it used in calcium chromate (CaCrCO_4), and concentration of ethyl benzene shall not exceed 1.5% in coatings.

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D210]

B59.4 The operator shall not use the following material(s) in this device :

materials containing any toxic air contaminants identified in Table 1 of the SCAQMD Rule 1401 with an effective date of September 10, 2010 except Methyl Ethyl Keton (CAS# 78-93-3).

[RULE 1401, 9-10-2010]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D265]

B59.10 The operator shall not use the following material(s) in this device :

Materials containing any toxic air contaminants (TAC) listed in Table 1 of Rule 1401 except methyl ethyl ketone, with an effective date of June 5, 2009, or earlier.

[RULE 1401, 6-5-2009]

[Devices subject to this condition : D253, D260]

B59.11 The operator shall not use the following material(s) in this device :

Materials containing any toxic air contaminants identified in table 1 of the SCAQMD Rule 1401 as amended December 7, 1990 or earlier except hexavalent chrome.

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D41, D151, D270, D271, D272]

B59.12 The operator shall not use the following material(s) in this device :

Materials containing any toxic air contaminants identified in table 1 of the SCAQMD Rule 1401 as amended September 10, 2010, or earlier except methyl ethyl ketone.

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D248, D275, D276]

C. Throughput or Operating Parameter Limits

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

C1.4 The operator shall limit the material processed to no more than 43 lb(s) in any one day.

For the purpose of this condition, material processed shall be defined as metallizing wire.

This limit shall be based on the total combined limit for equipment D41, D270, D271 & D272.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D41, D270, D271, D272]

C1.6 The operator shall limit the coating and solvent usage to no more than 2 gallon(s) per day.

For the purpose of this condition, coating and solvent usage shall be defined as the total quantity of chrome containing materials used in this equipment,.

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D151]

C1.20 The operator shall limit the material processed to no more than 15 lb(s) in any one calendar month.

For the purpose of this condition, material processed shall be defined as the total weight of material being cut by the laser.

For the purpose of this condition, material processed shall be defined as resin impregnated carbon fiber, resin impregnated fiberglass, epoxy film adhesive, and peel ply material.

To comply with this condition, the operator shall maintain records of the type of material used, total length, width, and thickness of the material being cut.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D248, D253, D275]

C1.21 The operator shall limit the material processed to no more than 20 gallon(s) per year.

For the purpose of this condition, material processed shall be defined as the adhesion promotor DC 1200.

[RULE 1124, 9-21-2001]

[Devices subject to this condition : D250]

C1.24 The operator shall limit the material processed to no more than 30 lb(s) in any one calendar month.

For the purpose of this condition, material processed shall be defined as the total weight of material being cut by the laser.

For the purpose of this condition, material processed shall be defined as resin impregnated carbon fiber, resin impregnated fiberglass, epoxy film adhesive, and peel ply material.

To comply with this condition, the operator shall maintain records of the type of material used, total length, width, and thickness of the material being cut.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D260, D276]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

C1.25 The operator shall limit the coating and solvent usage to no more than 1200 gallon(s) in any one calendar month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D265]

C1.26 The operator shall limit the material processed to no more than 1.4 lb(s) in any one month.

For the purpose of this condition, material processed shall be defined as the amount of hexavalent chromium sprayed in this equipment.

To comply with this condition, the operator shall determine the amount of hexavalent chromium as follows: (the amount of coating used) x (density) x (percentage of chromate component) x (the ratio of hexavalent chromium molecular weight to the chromate compound molecular weight).

To comply with this condition, the operator shall maintain records in a manner approved by the district to demonstrate compliance with this condition.

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D210]

C1.27 The operator shall limit the material processed to no more than 1.43 lb(s) in any one year.

For the purpose of this condition, material processed shall be defined as the amount of ethyl benzene sprayed in this equipment.

To comply with this condition, the operator shall determine the amount of ethyl benzene as follows: (the amount of coating used) X (density) X (percentage of ethyl benzene compound).

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D210]

- C6.4 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 1.75 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the three stage filters.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D258, D259]

- C6.10 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 5.5 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the filter media.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D28, D41, D151, D267, D268, D270, D271, D272]

- C6.19 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 6 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the filters.

The operator shall determine and record the parameter being monitored once every 7 days.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C264, C274, C277]

- C6.20 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 0.38 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the two stage filter media.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D250]

- C6.21 The operator shall use this equipment in such a manner that the hydrocarbon concentration being monitored, as indicated below, does not exceed 5 ppm.

The operator shall install and maintain a(n) continuous monitoring system to accurately indicate the hydrocarbon concentration between the primary and secondary carbon vessels.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C256]

- C6.22 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 120 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature of the vapor stream at the inlet to the primary carbon vessel.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C256]

- C6.23 The operator shall use this equipment in such a manner that the flow being monitored, as indicated below, does not exceed 2500 CFM.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The operator shall install and maintain a flow indicator at the inlet to the carbon adsorption system to measure the total air flow rate through the carbon adsorbers in cubic feet per minute (CFM).

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C256]

- C6.24 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 1 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the pocket type filter media.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D210, D265]

- C6.25 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 3 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the HEPA filter media.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D210]

- C8.1 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 1500 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature in the combustion chamber.

The operator shall also install and maintain a device to continuously record the parameter being measured.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002**]

[Devices subject to this condition : C266]

D. Monitoring/Testing Requirements

D28.1 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted at least once every five years.

The test shall be conducted no later than July 5, 2014 unless otherwise approved in writing by the District.

The test shall be conducted to determine the VOC emissions using an approved district method to demonstrate compliance with all applicable permit condition(s), rules and regulations.

The test shall be conducted while the oxidizer is operating at a temperature of not less than the minimum operating temperature specified in this permit. If the operating temperature during the source test is greater than the minimum operating temperature specified in this permit, the minimum operating temperature specified in this permit may be increased to reflect the operating temperature during the source test.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : C266]

D29.1 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
PM10 emissions	Approved District method	District-approved averaging time	Outlet

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

total hydrocarbon emissions	Approved District method	District-approved averaging time	Simultaneous inlet and outlet
Polynuclear Aromatic Hydrocarbons (PAH)	Approved District method	District-approved averaging time	Simultaneous inlet and outlet
Cyanide emissions	Approved District method	District-approved averaging time	Simultaneous inlet and outlet

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The source test shall be conducted with only two of three laser cutters Devices D260 & D 253 or D260 & D248 are operating.

A speciated analysis shall be conducted for organic compounds using GC/MS.

The speciated analysis shall be conducted for the inlet and outlet

The source test shall be conducted no later than 210 days after the initial start-up of this equipment unless otherwise approved in writing by the District.

The test shall be conducted to determine the emissions of any toxic air contaminants and volatile organic compounds resulting from the laser cutting operation, the collection efficiency, and the control efficiency of the control equipment.

Two complete copies of source test protocol shall be submitted to the District engineer no later than 90 days after the initial start-up of this equipment unless otherwise approved in writing by the District. The test protocol shall be approved in writing by the District before the test commences.

The test protocol shall include, but not limited to, the proposed operating conditions of the equipment during the test, the identity of the testing laboratory, a statement from the testing laboratory certifying it meets the criteria in District Rule 304(k), and a description of the sampling and analytical procedures to be used.

A written notice of the source tests shall be submitted to the District engineer at least 14 days prior to source testing date so that an observer from the District may be present.

Two complete copies of source test reports shall be submitted to the District engineer within 45 days after the source testing date.

The source test report shall also include, exhaust flow rate, moisture content, O₂ concentration, the number of panels used during the test, number of holes cut, and diameter and depth of each hole cut

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-7-2008]

[Devices subject to this condition : C264]

D29.2 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
VOC	Approved District method	District-approved averaging time	Simultaneously
NOX emissions	Approved District method	District-approved averaging time	Outlet only
CO emissions	Approved District method	District-approved averaging time	Outlet only

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

A speciated analysis shall be conducted for organic compounds using GC/MS.

The speciated analysis shall be conducted for the inlet and outlet

The source test shall be conducted no later than 180 days after the initial start-up of this equipment unless otherwise approved in writing by the District.

Two complete copies of source test protocol shall be submitted to the District engineer no later than 60 days after the initial start-up of this equipment unless otherwise approved in writing by the District. The test protocol shall be approved in writing by the District before the test commences.

The test protocol shall include, but not limited to, the proposed operating conditions of the equipment during the test, the identity of the testing laboratory, a statement from the testing laboratory certifying it meets the criteria in District Rule 304(k), and a description of the sampling and analytical procedures to be used.

A written notice of the source tests shall be submitted to the District engineer at least 14 days prior to source testing date so that an observer from the District may be present.

Two complete copies of source test reports shall be submitted to the District engineer within 45 days after the source testing date.

The source test shall consist of, but may not be limited to, testing at the inlet and the exhaust of the afterburner for:

1) Volatile organic compound (VOC) in PPMV and lbs/hr

Oxides of Nitrogen in PPMV and lbs/hr at start-up while the start-up burner is in operation (Afterburner exhaust only)

Oxides of Nitrogen in ppmv and lbs/hr during normal operation while the start-up burner being off (Afterburner exhaust only)

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

- 4) Carbon Monoxide in ppmv and lbs/hr at start-up (Afterburner exhaust only)
- 5) Carbon Monoxide in ppmv and lbs/hr during normal operation (Afterburner exhaust only)
- 6) VOC Destruction efficiency
- 7) VOC Collection efficiency
- 8) Usage of all VOC-containing materials (Coatings, adhesives, solvent, etc.) during the test
- 9) Oxygen content
- 10) Moisture content
- 11) Flow rate
- 12) Temperature
- 13) VOC collection efficiency permanent total enclosure (PTE) as specified under USEPA Method 204, capture efficiency.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 9-10-2010]

[Devices subject to this condition : C266]

D90.2 The operator shall periodically monitor the hydrocarbon concentration at the inlet and outlet according to the following specifications:

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The operator shall use a District approved Organic Vapor Analyzer (OVA) to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane.

The operator shall monitor once every month.

The monitoring frequency shall be reduced to at least quarterly, if three consecutive monthly monitoring show no hydrocarbon readings

The monitoring frequency shall be increased to once every month, no later than 30 days after the discovery of any hydrocarbon readings

The operator shall maintain records to demonstrate compliance with this condition

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : C264, C277]

D90.3 The operator shall continuously monitor the hydrocarbon concentration across the primary and secondary carbon vessels according to the following specifications:

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The operator shall use a flame ionization detector (FID) or equivalent instrument to monitor the parameter.

The operator shall calibrate the instrument used to monitor the parameter in ppmv hexane.

The operator shall also install and maintain a device to continuously record the parameter being monitored.

The analyzer shall be maintained and calibrated according to the EPA method 21 requirements.

Vapors shall not be extracted from the soil unless they are vented to the carbon adsorption system as described in the equipment description. The extraction and carbon adsorption system shall be leak free between the outlet of the blower and the outlet of the adsorption system.

Upon completion, the vapor extraction wells and ducts shall be capped to prevent vapors from venting to the atmosphere.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1401, 6-5-2009]

[Devices subject to this condition : C256]

D90.4 The operator shall periodically sample the hydrocarbon concentration across the carbon adsorption system according to the following specifications:

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The operator shall sample once every day after the first 15 days of operation for 10 days.

Sampling and analysis shall be conducted by an independent laboratory per Rule 304.

Sampling shall conform to CARB method 422 or equivalent. Samples with high moisture shall be collected using an appropriate method such as SCAQMD method 25.1/25.3 or other methods approved by the SCAQMD.

Analysis shall be conducted using EPA method TO15 or other method approved by SCAQMD.

The samples collected will check for Total Organic Compounds and Speciated Non-methane Organic Compounds.

Samples shall be collected at the inlet and outlet of the carbon adsorption system.

The operator shall submit to the District in writing the results of the sampling including but not limited to monitoring, lab analysis, flow, and temperature readings to prove compliance with the conditions of this permit. Submittal shall be within 45 days of start-up.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1401, 6-5-2009**]

[Devices subject to this condition : C256]

D90.5 The operator shall periodically monitor the hydrocarbon concentration across the carbon adsorption system according to the following specifications:

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

The operator shall sample once after six months but no later than nine months after start-up of operation

Sampling and analysis shall be conducted by an independent laboratory per Rule 304.

Sampling shall conform to CARB method 422 or equivalent. Samples with high moisture shall be collected using an appropriate method such as SCAQMD method 25.1/25.3 or other methods approved by the SCAQMD.

Analysis shall be conducted using EPA method TO15 or other method approved by SCAQMD.

The samples collected will check for Total Organic Compounds and Speciated Non-methane Organic Compounds.

Samples shall be collected at the inlet and outlet of the carbon adsorbtion system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C256]

D182.2 The operator shall test this equipment in accordance with the following specifications:

the operator shall verify the exhaust flow rate within 60 days of initial operation of the equipment. If the exhaust fan of this spray booth is repaired, modified, or replaced the operator shall conduct tests pursuant to an appropriate AQMD approved test method to determine the exhaust flow rate within 60 days of such repair, modification or replacement.

[RULE 1132(h)(2) - Exemptions, 3-5-2004; RULE 1132(h)(2) - Exemptions, 5-7-2004; RULE 1401, 3-4-2005]

[Devices subject to this condition : D28, D41, D151, D258, D259, D267, D268, D270, D271, D272]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D322.1 The operator shall perform a weekly inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D28, D41, D151, D210, D250, D258, D259, D265, D267, D268, D270, D271, D272]

D322.2 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C274]

D322.4 The operator shall perform a monthly inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C264, C277]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D67, D248, D253, D260, D275, D276]

D381.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C264, C277]

E. Equipment Operation/Construction Requirements

E57.1 The operator shall vent this equipment to an air pollution control device which is in full use and which has been issued a permit to operate by the Executive officer whenever it is in operation.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D248, D253, D260, D275, D276]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

- E71.1 The operator shall only operate this equipment if the exhaust fan of this equipment is operating at 10,000 scfm or greater. If the exhaust fan is repaired, modified or replaced, the operator shall conduct tests to determine the exhaust flow rate.
[**RULE 1132(h)(2) - Exemptions, 3-5-2004**; RULE 1132(h)(2) - Exemptions, 5-7-2004]

[Devices subject to this condition : D28, D41, D151, D250, D258, D259, D268, D270, D271, D272]
- E71.4 The operator shall not turn off the exhaust fan on this equipment until 30 seconds after spray operations have ceased.
[RULE 1469.1, 3-4-2005]

[Devices subject to this condition : D28, D41, D151, D258, D259, D267, D268, D270, D271, D272]
- E71.5 The operator shall only use this equipment if it is equipped with an automatic shut down which will shut down the extraction blower when the exhaust of the primary carbon vessel hydrocarbon concentration exceeds 5 ppmv measured as hexane.
[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C256]
- E71.6 The operator shall only operate this equipment if the exhaust fan of this equipment is operating at less than 10,000 scfm. If the exhaust fan is repaired, modified or replaced, the operator shall conduct tests to determine the exhaust flow rate.
[**RULE 1132(h)(2) - Exemptions, 3-5-2004**; RULE 1132(h)(2) - Exemptions, 5-7-2004]

[Devices subject to this condition : D267]
- E71.7 The operator shall not turn off the exhaust fan on this equipment until 5 minutes after spray operations have ceased when coatings containing hexavalent chromium have been sprayed. The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1469.1, 3-4-2005]

[Devices subject to this condition : D210]

E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C264, C274, C277]

E128.1 The operator shall keep all spent carbon in a tightly covered container which shall remain closed except when it is being transferred into or out of the container.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C256]

E147.1 The operator shall only conduct the processing of resin impregnated carbon fiber, resin impregnated fiberglass, epoxy film adhesive, and peel ply material in this equipment.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D248, D253, D260, D275, D276]

E153.2 The operator shall change over the carbon in the adsorber whenever breakthrough occurs.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

When breakthrough occurs, the system shall be shut down until the spent carbon vessel is replaced or replenished.

For the purpose of this condition, breakthrough shall be defined as an exhaust hydrocarbon concentration from the primary vessel in excess of 5 ppmv measured as hexane.

The activated carbon used in the carbon vessels shall have a butane activity number of not less than 23.5 as measured by ASTM method 5742 or a CTC no. not less than 60% as measured by ASTM method D3467.

To change over the carbon, the operator shall replace the first carbon canister with a fresh carbon canister. After the new carbon canister is installed, it shall become the last carbon canister in series.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C256]

E175.1 The operator shall not use this equipment unless all exhaust air passes through the following:

3-stage dry particulate filters

[40CFR 63 Subpart GG, 12-8-2000]

[Devices subject to this condition : D210]

E175.3 The operator shall not use this equipment unless all exhaust air passes through the following:

two stage particulate dry filters

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D250]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

E175.5 The operator shall not use this equipment unless all exhaust air passes through the following:

3-stage dry particulate filters that has a single stage of HEPA filters individually DOP tested (or equivalent) with 0.3 micron particulates and certified to have a control efficiency of not less than 99.97% as required by AQMD Rule 1469.1

[RULE 1469.1, 3-4-2005]

[Devices subject to this condition : D258, D259]

E175.6 The operator shall not use this equipment unless all exhaust air passes through the following:

A HEPA filter that is individually DOP tested with 0.3 micron particulates and certified to have an efficiency of not less than 99.97%.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D260, C264, C277]

E175.8 The operator shall not use this equipment unless all exhaust air passes through the following:

pocket type particulate dry filters and through the regenerative thermal oxidizer (RTO) which is in full operation.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D265]

E175.9 The operator shall not use this equipment unless all exhaust air passes through the following:

Four stage filters consisting of blanket filters, panel filters, pocket filters and HEPA filters as described in the equipment description. The HEPA filters shall be individually DOP tested (or equivalent) with 0.3 micron particulates and certified to have a control efficiency of not less than 99.97%, as required by AQMD Rule 1469.1

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1469.1, 3-4-2005]

[Devices subject to this condition : D28, D41, D151, D267, D268, D270, D271, D272]

E175.10 The operator shall not use this equipment unless all exhaust air passes through the following:

Twenty-six HEPA filters that are individually DOP tested with 0.3 micron particulates and certified to have an efficiency of not less than 99.97%.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1469.1, 3-4-2005]

[Devices subject to this condition : D210]

E193.2 The operator shall construct this equipment according to the following requirements:

This permit shall expire if the construction of this equipment is not completed within one year from the date of the issuance of this permit unless an extension of time has been approved in writing by a District representative.

The operator shall notify a District representative when construction has been completed.

[**RULE 204, 10-8-1993**]

[Devices subject to this condition : D67, D248, D250, D252, D253, D260, C264, D265, C266, C274, D275, D276, C277]

E193.3 The operator shall construct this equipment according to the following requirements:

Only two out of three laser cutters Devices D248, D253, D260 shall be operated at any one time.

[Devices subject to this condition : D248, D253, D260, C264]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

E448.1 The operator shall comply with the following requirements:

the total quantity of abrasive blasting media discharged through the nozzles shall not exceed 60,000 pounds per day, including recycled abrasive material

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D67]

H. Applicable Rules

H23.5 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	109
PM	District Rule	481

[RULE 109, 5-2-2003; RULE 481, 1-11-2002]

[Devices subject to this condition : D250]

H23.11 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	109
Chromium, Hexavalent	District Rule	1469.1
PM	District Rule	481

[RULE 109, 5-2-2003; RULE 1469.1, 3-4-2005; RULE 481, 1-11-2002]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D28, D41, D151, D210, D258, D259, D267, D268, D270, D271, D272]

H23.14 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
PM	District Rule	1155

[RULE 1155, 12-4-2009]

[Devices subject to this condition : C264, C274, C277]

H23.16 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule/Subpart
VOC District Rule	1166

[**RULE 1166, 7-14-1995**; RULE 1166, 5-11-2001]

[Devices subject to this condition : C256]

H23.17 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	109
PM	District Rule	481
VOC	District Rule	1124
VOC	District Rule	1171
VOC	District Rule	1168
HAPs	40CFR63, SUBPART	GG

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 109, 5-2-2003; RULE 1124, 9-21-2001; RULE 1168, 1-7-2005; RULE 1171, 2-1-2008; RULE 1171, 5-1-2009; RULE 481, 1-11-2002; 40CFR 63 Subpart GG, 4-20-2006]

[Devices subject to this condition : D265]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the filter media

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D28, D41, D151, D210, D250, D258, D259, C264, D265, D267, D268, D270, D271, D272, C274, C277]

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

weekly record of pressure drop across the filter media

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D28, D41, D151, D210, D250, D258, D259, D265, D267, D268, D270, D271, D272]

K67.6 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

daily usage and volatile organic compound emissions in a manner acceptable by the Executive Officer

[**RULE 109, 5-2-2003; RULE 1303(b)(2)-Offset, 5-10-1996;** RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D28, D41, D151, D210, D250, D258, D259, D265, D267, D268, D270, D271, D272]

K67.9 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Daily usage of abrasive blasting media, including recycled abrasive material

[**RULE 1303(b)(2)-Offset, 5-10-1996;** RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D67]

L. Expiration Date

L341.1 Within 7 days after start-up of this equipment, the following device(s) shall be removed from operation:

D31

[**RULE 1303(b)(2)-Offset, 5-10-1996;** RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D259]

L341.2 Within 7 days after start-up of this equipment, the following device(s) shall be removed from operation:

D40

[**RULE 1303(b)(2)-Offset, 5-10-1996;** RULE 1303(b)(2)-Offset, 12-6-2002]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D258]

L341.3 Within 7 days after start-up of this equipment, the following device(s) shall be removed from operation:

D42

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D267]

L341.4 Within 7 days after start-up of this equipment, the following device(s) shall be removed from operation:

D30

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D268]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]

15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]

16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1107	1-6-2006	Federally enforceable
RULE 1110.2	2-1-2008	Federally enforceable
RULE 1110.2	9-7-2012	Non federally enforceable
RULE 1113	6-3-2011	Non federally enforceable
RULE 1113	7-13-2007	Federally enforceable
RULE 1122	10-1-2004	Federally enforceable
RULE 1122	5-1-2009	Non federally enforceable
RULE 1124	9-21-2001	Federally enforceable
RULE 1132	3-5-2004	Federally enforceable
RULE 1132	5-7-2004	Non federally enforceable
RULE 1132(h)(2) - Exemptions	3-5-2004	Federally enforceable
RULE 1132(h)(2) - Exemptions	5-7-2004	Non federally enforceable
RULE 1136	6-14-1996	Federally enforceable
RULE 1140	2-1-1980	Federally enforceable
RULE 1140	8-2-1985	Non federally enforceable
RULE 1146	11-17-2000	Federally enforceable
RULE 1146	9-5-2008	Non federally enforceable
RULE 1155	12-4-2009	Non federally enforceable
RULE 1166	5-11-2001	Non federally enforceable

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 1166	7-14-1995	Federally enforceable
RULE 1168	1-7-2005	Federally enforceable
RULE 1171	2-1-2008	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1304(a)-Modeling and Offset Exemption	6-14-1996	Federally enforceable
RULE 1401	12-7-1990	Non federally enforceable
RULE 1401	3-12-1999	Non federally enforceable
RULE 1401	3-4-2005	Non federally enforceable
RULE 1401	3-7-2008	Non federally enforceable
RULE 1401	5-2-2003	Non federally enforceable
RULE 1401	6-5-2009	Non federally enforceable
RULE 1401	8-13-1999	Non federally enforceable
RULE 1401	9-10-2010	Non federally enforceable
RULE 1404	4-6-1990	Non federally enforceable
RULE 1415	12-3-2010	Non federally enforceable
RULE 1418	9-10-1999	Non federally enforceable
RULE 1469.1	3-4-2005	Non federally enforceable
RULE 1470	5-4-2012	Non federally enforceable
RULE 2005	6-3-2011	Federally enforceable
RULE 2012	5-6-2005	Federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	6-1-2007	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3002	11-5-2010	Non federally enforceable
RULE 3003	11-14-1997	Federally enforceable

FACILITY PERMIT TO OPERATE ROHR, INC.

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 3003	11-5-2010	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	11-5-2010	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-1-2012	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 431.2	5-4-1990	Federally enforceable
RULE 431.2	9-15-2000	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 481	1-11-2002	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 63 Subpart GG	12-8-2000	Federally enforceable
40CFR 63 Subpart GG	4-20-2006	Federally enforceable
40CFR 63 Subpart T, #30	6-5-1995	Federally enforceable
40CFR 82 Subpart F	5-14-1993	Federally enforceable

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS								
Less Water and Less Exempt Compounds								
Effective Dates								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

VOC LIMITS								
Less Water and Less Exempt Compounds								
Effective Dates, cont.								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

**FACILITY PERMIT TO OPERATE
ROHR, INC.**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]**

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:
 - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
 - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

TABLE OF STANDARDS 1 VOC LIMITS

**Grams of VOC Per Liter of Coating,
Less Water and Less Exempt Compounds**

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges ³		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	
Decorative Coatings		350			100
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers	340	100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters	200	100			
Reactive Penetrating Sealers		350			
Recycled Coatings		250			
Roof Coatings	250	50			
Roof Coatings, Aluminum		100			

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

Roof Primers, Bituminous	350	350		
Rust Preventative Coatings	400	100		
Stone Consolidant		450		
Sacrificial Anti-Graffiti Coatings		100		50
Shellac				
Clear		730		
Pigmented		550		
Specialty Primers	350	100		
Stains		100		

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Stains, Interior	250	250			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers	250	100			
Waterproofing Concrete/Masonry Sealers	400	100			
Wood Preservatives		350			

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

TABLE OF STANDARDS 1 (cont.) VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

TABLE OF STANDARDS 2 VOC LIMITS FOR COLORANTS

Grams of VOC Per Liter of Colorant Less Water and Less Exempt Compounds

COLORANT	Limit ⁴
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007] TABLE OF STANDARDS VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Bond Breakers	350							
Clear Wood Finishes	350					275		
Varnish	350					275		
Sanding Sealers	350					275		
Lacquer	680	550			275			
Clear Brushing Lacquer	680				275			
Concrete-Curing Compounds	350						100	
Concrete-Curing Compounds For Roadways and Bridges**	350							
Dry-Fog Coatings	400						150	
Fire-Proofing Exterior Coatings	450	350						
Fire-Retardant Coatings***								
Clear	650							
Pigmented	350							
Flats	250	100						50
Floor Coatings	420		100			50		
Graphic Arts (Sign) Coatings	500							
Industrial Maintenance (IM) Coatings	420			250		100		
High Temperature IM Coatings			420					
Zinc-Rich IM Primers	420		340			100		
Japans/Faux Finishing Coatings	700	350						
Magnesite Cement Coatings	600	450						
Mastic Coatings	300							
Metallic Pigmented Coatings	500							
Multi-Color Coatings	420	250						
Nonflat Coatings	250		150			50		

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Nonflat High Gloss	250		150				50	
Pigmented Lacquer	680	550			275			
Pre-Treatment Wash Primers	780		420					
Primers, Sealers, and Undercoaters	350		200			100		
Quick-Dry Enamels	400		250			150	50	
Quick-Dry Primers, Sealers, and Undercoaters	350		200			100		
Recycled Coatings			250					
Roof Coatings	300		250		50			
Roof Coatings, Aluminum	500				100			
Roof Primers, Bituminous	350		350					
Rust Preventative Coatings	420		400			100		
Shellac								
Clear	730							
Pigmented	550							
Specialty Primers	350					250	100	
Stains	350		250				100	
Stains, Interior	250							
Swimming Pool Coatings								
Repair	650		340					
Other	340							
Traffic Coatings	250	150					100	
Waterproofing Sealers	400		250			100		
Waterproofing	400					100		
Concrete/Masonry Sealers								
Wood Preservatives								
Below-Ground	350							
Other	350							

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

** Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

*** The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

**FACILITY PERMIT TO OPERATE
ROHR, INC.**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 07-13-2007]**

**TABLE OF STANDARDS (cont.)
VOC LIMITS**

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1124 09-21-2001]

Except as otherwise provided in Rule 1124

- (1) VOC Content of Aerospace Materials
 - (A) A person shall not apply to aerospace components any materials, including any VOC-containing materials added to the original material supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC Limit			
Grams of VOC per Liter, Less Water and Less Exempt Compounds			
Primers	Current VOC Limit	VOC Limit Effective 1-1-03	VOC Limit Effective 1-1-05
General Primer	350	350	350
Low-Solids Corrosion Resistant Primer	350	350	350
Pretreatment Primer	780	780	780
Rain Erosion-Resistant Coating Compatible Primer	850	850	850
Adhesion Promoter	850	850	250
Adhesive Bonding Primer			
New Commercial Aircraft	805	250	250
All Military Aircraft	805	805	805
Remanufactured Commercial Aircraft Parts	805	805	805
Sonic and Acoustic Applications	805	805	805
Adhesive Bonding Primer			
Long Term	250	250	250
Short Term	250	250	250

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1124 09-21-2001]

Coatings	Current VOC Limit	VOC Limit Effective 3-01-02
Topcoat	420	420
Clear Topcoat	520	520
Unicoat	420	420
Wing Coating	750	750
Impact Resistant Coating	420	420
High-Temperature Coating	850	850
Antichafe Coating	600	420
Rain Erosion-Resistant Coating	800	800
Conformal Coating	750	750
Optical Anti-Reflective Coating	700	700
Scale Inhibitor	880	880
Metallized Epoxy Coating	700	700
Electric or Radiation Effect Coating	800	800
Temporary Protective Coating	250	250
Fuel Tank Coatings	420	420
Mold Release Coatings	780	780
Flight Test Coatings		
Used on Missiles or Single Use Target Craft	420	420
All Other	840	840
Fire Resistant Coatings		
Commercial	650	650
Military	970	800
Wire Coatings		
Phosphate Ester Resistant Ink	925	925
Other	420	420
Space Vehicle Coatings		
Electrostatic Discharge Protection Coating	800	800
Other	1000	1000

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1124 09-21-2001]

Adhesives	Current VOC Limit
Non-Structural Adhesive	250
Structural Adhesive	
Autoclavable	50
Non-Autoclavable	850
Space Vehicle Adhesive	800
Fuel Tank Adhesive	620

Sealants	Current VOC Limit	VOC Limit Effective 3-01-02
Fastener Sealant	675	675
Extrudable, Rollable or Brushable Sealant	600	280
Other	600	600

Maskants	Current VOC Limit
For Chemical Processing	250
For Chemical Milling	
Type I	250
Type II	160
Photolithographic	850
Touch-up, Line Sealer Maskants	750

Lubricants	Current VOC Limit
Fastener Installation	
Solid-Film Lubricant	880
Dry Lubricative Materials	675
Fastener-Lubricative Coatings, Fastener Manufacturing	
Solid Film Lubricant	250
Dry Lubricative Materials	120
Barrier Coating	420
Non-Fastener Lubricative Coatings, Fastener Manufacturing	
Solid Film Lubricant	880
Dry Lubricative Materials	675

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1124 09-21-2001]

VOC LIMIT	
Grams of VOC per Liter of Material	
Cleaning Solvents and Strippers	Current VOC Limit
Cleaning Solvents	200 g/L or 45 mm Hg VOC Composite Partial Pressure
Strippers	300 g/L or 9.5 mm Hg VOC Composite Partial Pressure

- (B) Documents shall be provided to the Executive Officer or his designee demonstrating that unicoat is being used in lieu of the application of a primer and topcoat, and the applicant must receive written approval for the use of unicoat specifying the conditions of application from the Executive Officer or his designee.
 - (C) For low-solids adhesives, coatings, primers or sealants, the appropriate limits in subparagraph (c)(1)(A) shall be expressed in grams of VOC per liter of material.
- (2) Solvent Cleaning Operations; Storage and Disposal of VOC-Containing Materials
- (A) Cleaning of material application equipment and storage of solvent laden cloth and paper shall comply with provisions of Rule 1171.
 - (B) A person shall not atomize any solvent into open air.

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1136 06-14-1996]

Except as otherwise provided in Rule 1136

- (a) The operator shall not apply any coating to a wood product which has a VOC content, including any VOC-containing material added to the original coating supplied by the manufacturer, which exceeds the applicable limit specified below:

(1)

VOC LIMITS

Grams Per Liter (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

<u>COATING</u>	<u>Current Limit</u>		<u>On and After</u> <u>7/1/2005</u>
	I	or	
	II		
Clear Sealers	550 (4.6) [1.39]	680 (5.7) [3.36]	275 (2.3) [0.36]
Clear Topcoat	550 (4.6) [1.37]	275 (2.3) [0.35]	275 (2.3) [0.35]
Pigmented Primers, Sealers & Undercoats	550 (4.6) [1.06]	600 (5.0) [1.08]	275 (2.3) [0.21]
Pigmented Topcoats	550 (4.6) [1.10]	275 (2.3) [0.25]	275 (2.3) [0.25]

The operator shall use coatings on a wood product that comply with either all VOC limits in column I or all VOC limits in column II. The operator that applies a primer, sealer or undercoat, but not a topcoat, to a wood product, shall be subject to column I for that wood product.

- (2) Notwithstanding the requirements of clause (a)(1), an operator that applies a topcoat and a primer, sealer or undercoat to a shutter may, until July 1, 2005, choose to comply with the VOC limits specified below for that shutter:

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1136 06-14-1996]

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

COATING

Clear Sealers	275 (2.3) [0.36]
Clear Topcoat	680 (5.7) [2.99]
Pigmented Primers, Sealers & Undercoats	275 (2.3) [0.33]
Pigmented Topcoats	600 (5.0) [1.38]

(3)

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

On and After

COATING

	<u>Current Limit</u>	<u>7/1/2005</u>
Barrier Coat - Plastic Components	760 (6.3) [3.9]	275 (2.3) [0.28]
Composite Wood Edge Filler	550 (4.6) [1.15]	275 (2.3) [0.31]
Extreme Performance Coatings	420 (3.5) [0.51]	275 (2.3) [0.33]
Fillers	500 (4.2) [0.66]	275 (2.3) [0.18]
High-Solid Stains	550 (4.6) [1.23]	350 (2.9) [0.42]
Inks	500 (4.2) [0.96]	500 (4.2) [0.96]
Mold-Seal Coatings	750 (6.3) [4.2]	750 (6.3) [4.2]
Multi-Colored Coatings	685 (5.7) [2.6]	275 (2.3) [0.33]

VOC LIMITS

Grams Per Liter (lb/gal) of Material

On and After

COATING

	<u>Current Limit</u>	<u>7/1/2005</u>
Low-Solids Barrier Coat - Plastic Components	760 (6.3)	120 (1.0)
Low-Solid Stains, Toners, and Washcoats	480 (4.0)	120 (1.0)

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1136 06-14-1996]

Any coating subject to this rule that meets any of the three VOC limit formats (grams per liter, lb/gal, or lbs VOC/lb of solids) is in compliance with this subparagraph.

- (4) The VOC limit for japan coatings is 700 grams per liter of coatings, less water and exempt compounds, as applied.
- (b) A person shall not use a stripper on wood products unless:
- (1) it contains less than 350 grams of VOC per liter of material; or
 - (2) the VOC composite vapor pressure is 2 mm Hg (0.04 psia) or less at 20°C (68°F).

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 02-01-1980]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 08-02-1985]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

Architectural Applications	Current VOC Limit*
Indoor Carpet Adhesives	50
Carpet Pad Adhesives	50
Outdoor Carpet Adhesives	150
Wood Flooring Adhesive	100
Rubber Floor Adhesives	60
Subfloor Adhesives	50
Ceramic Tile Adhesives	65
VCT and Asphalt Tile Adhesives	50
Dry Wall and Panel Adhesives	50
Cove Base Adhesives	50
Multipurpose Construction Adhesives	70
Structural Glazing Adhesives	100
Single Ply Roof Membrane Adhesives	250

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

Specialty Applications	VOC Limits and Effective Dates**			
	Current VOC Limit*	1-1-05	7-1-05	1-1-07
PVC Welding	510			
CPVC Welding	490			
ABS Welding	400		325	
Plastic Cement Welding	350	250		
Adhesive Primer for Plastic	650		550	
Computer Diskette Manufacturing	350			
Contact Adhesive	80			
Special Purpose Contact Adhesive	250			
Tire Retread	100			
Adhesive Primer for Traffic Marking Tape	150			
Structural Wood Member Adhesive	140			
Sheet Applied Rubber Lining Operations	850			
Top and Trim Adhesive	540			250

** The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

For adhesives, adhesive bonding primers, or any other primer not regulated by the above two tables and applied to the following substrates, the following limits shall apply:

Substrate Specific Applications	Current VOC Limit*
Metal to Metal	30
Plastic Foams	50
Porous Material (except wood)	50
Wood	30
Fiberglass	80

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

Sealants	Current VOC Limit*
Architectural	250
Marine Deck	760
Nonmembrane Roof	300
Roadway	250
Single-Ply Roof Membrane	450
Other	420

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

Sealant Primers	Current VOC Limit*
Architectural	
Non Porous	250
Porous	775
Modified Bituminous	500
Marine Deck	760
Other	750

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	800 (6.7)		
(B) General Work Surfaces	600 (5.0)		
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)		
(D) Cleaning of Ink Application Equipment			
(i) General	25 (0.21)		
(ii) Flexographic Printing	25 (0.21)		
(iii) Gravure Printing			
(A) Publication	100 (0.83)		
(B) Packaging	25 (0.21)		
(iv) Lithographic (Offset) or Letter Press Printing			
(A) Roller Wash, Blanket Wash, & On-Press Components			
(I) Newsprint	100 (0.83)		

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(II) Other Substrates	500 (4.2)	100 (0.83)	
(B) Removable Press Components	25 (0.21)		
(v) Screen Printing	500 (4.2)	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)		
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)		

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

**FACILITY PERMIT TO OPERATE
 ROHR, INC.**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 02-07-1986]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
		Kilograms Per Hour	Pounds Per Hour			Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6

FACILITY PERMIT TO OPERATE ROHR, INC.

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
		Kilograms Per Hour	Pounds Per Hour			Kilograms Per Hour	Pounds Per Hour
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0