SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765

Title Page	
Facility ID:	165249
Revision #:	0
Date:	November 17, 2010

FACILITY PERMIT TO OPERATE

MVP RV, INC
5300 VIA RICARDO
RIVERSIDE, CA 92509

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By _____ FOR
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE
MVP RV, INC

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	0	11/17/2010
B	RECLAIM Annual Emission Allocation	0	11/17/2010
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	0	11/17/2010
E	Administrative Conditions	0	11/17/2010
F	RECLAIM Monitoring and Source Testing Requirements	0	11/17/2010
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	0	11/17/2010
H	Permit To Construct and Temporary Permit to Operate	0	11/17/2010
I	Compliance Plans & Schedules	0	11/17/2010
J	Air Toxics	0	11/17/2010
K	Title V Administration	0	11/17/2010
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	0	11/17/2010
B	Rule Emission Limits	0	11/17/2010

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR:	MVP RV, INC
LEGAL OPERATOR (if different than owner):	
EQUIPMENT LOCATION:	5300 VIA RICARDO RIVERSIDE, CA 92509-2413
MAILING ADDRESS:	5300 VIA RICARDO RIVERSIDE, CA 92509
RESPONSIBLE OFFICIAL:	PABLO CARMONA
TITLE:	COO - CHIEF OPERATIONAL OFFICIAL
TELEPHONE NUMBER:	(951) 208-7526
CONTACT PERSON:	MAUREEN SCHWITZER
TITLE:	SAFETY & ENVIRONMENTAL ENGINEER
TELEPHONE NUMBER:	(951) 733-6477
TITLE V PERMIT ISSUED:	October 01, 2006
TITLE V PERMIT EXPIRATION DATE:	September 30, 2011

TITLE V	RECLAIM	
YES	NOx:	NO
	SOx:	NO
	CYCLE:	0
	ZONE:	INLAND

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

FACILITY PERMIT TO OPERATE
MVP RV, INC

Facility Equipment and Requirements
(Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
514211	G10683	OVEN, DRYING
514189	G10650	SPRAY BOOTH PAINT AND SOLVENT
514191	G10651	SPRAY BOOTH PAINT AND SOLVENT
514210	G10682	SPRAY BOOTH PAINT AND SOLVENT
514209	G10681	DIP TANK COATING MISC
514208	G10680	SPRAY EQUIPMENT OPEN
514207	G10679	SPRAY EQUIPMENT OPEN
514206	G10678	SPRAY EQUIPMENT OPEN
514205	G10677	SPRAY BOOTH PAINT AND SOLVENT
514204	G10676	SPRAY BOOTH PAINT AND SOLVENT
514202	G10675	OVEN, DRYING
514201	G10674	SPRAY EQUIPMENT OPEN
514200	G10671	SPRAY BOOTH PAINT AND SOLVENT
514199	G10670	SPRAY BOOTH HIGH-WATER PAINT
514198	G10669	SPRAY BOOTH HIGH-WATER PAINT
514197	G10666	SPRAY BOOTH PAINT AND SOLVENT
514196	G10664	OVEN
514195	G10653	OVEN
514193	G10652	AFTERBURNER W/ (7)SPRAY BOOTHS

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE
MVP RV, INC

FACILITY WIDE CONDITION(S)

Conditions:

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:

   A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
   B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION. [RULE 401]

2. EQUIPMENT OR PROCESS SUBJECT TO RULE 442 SHALL NOT EMIT TO THE ATMOSPHERE FROM THIS FACILITY VOC EMISSIONS IN EXCESS OF 833 POUNDS PER MONTH.
   [RULE 442]

3. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY DAILY AND MONTHLY VOC IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED INCLUDING (WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
   [RULE 109, 442, 1303(b)(2)-OFFSET]

4. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE MONTH FROM ALL PERMITTED EQUIPMENT COVERED BY THE MONTHLY LIMIT. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING MANAGEMENT OFFICIAL WITH RESPONSIBILITY FOR OPERATION OF EQUIPMENT SUBJECT TO THE PERMIT.
   [RULE 109, 442, 1303(b)(2)-OFFSET]

5. THE OPERATOR SHALL MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
   [RULE 109, 1303(b)(2)-OFFSET]

6. THE OPERATOR SHALL RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.
   [RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
MVP RV, INC

7. MATERIAL SAFETY DATA SHEETS (MSDS) FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST. THE MSDS SHALL INCLUDE THE VOC CONTENT IN POUNDS VOC PER GALLON, LESS WATER, LESS EXEMPT SOLVENT.
[RULE 1303(b)(2)-OFFSET]

8. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT THAT IS ACCEPTABLE TO THE DISTRICT, RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10683
A/N 514211

Equipment Description:

OVEN, DRYING TYPE, BINKS, MODEL ADE25D, 16' W. X 42' L. X 14' H., WITH 42 LAMPS, EACH 3,000 WATTS, AND ONE ¼ HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Emissions And Requirements:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10650
A/N 514189

Equipment Description:

SPRAY BOOTH, BINKS, MODEL ADE250, AUTOMOTIVE DOWNDRAFT TYPE, 16'-0" W. X 47'-0" L. X 15'-0" H., WITH FOUR 36" X 480" X 2" ATI POLYESTER FILTERS AND TWO 5 HP EXHAUST FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. ALL EXHAUST AIR SHALL PASS THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK DURING SPRAYING OPERATIONS.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 1.5 INCH OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THIS EQUIPMENT SHALL NOT EXCEED 20 GALLONS IN ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 50 POUNDS PER DAY. FOR THE PURPOSE OF THIS CONDITION AND FOR EXEMPTION UNDER RULE 1132(h)(2), THE VOC EMISSIONS FROM THIS EQUIPMENT SHALL BE DEFINED AS A MONTHLY AVERAGE FOR EACH CALENDAR MONTH, CALCULATED BY DIVIDING THE TOTAL EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH BY THE NUMBER OF CALENDAR DAYS IN THAT MONTH. IF THE RECORDS GENERATED AFTER THE END OF ANY CALENDAR MONTH SHOW THAT THE VOC EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT THE APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132. EXCEEDANCE OF THE VOC EMISSION LIMIT OF THIS CONDITION SHALL NOT SUBJECT ANY EQUIPMENT AT THIS FACILITY TO NEW SOURCE REVIEW REQUIREMENTS IF THE OPERATOR COMPLIES WITH ALL OTHER CONDITIONS THAT ARE APPICABLE TO SUCH EQUIPMENT.
[RULE 1132]

FACILITY PERMIT TO OPERATE
MVP RV, INC

7. THE EXHAUST FLOW RATE FROM THIS EQUIPMENT SHALL NOT BE LESS THAN 30,000 SCFM. IF THE EXHAUST FAN OF THIS SPRAY BOOTH IS REPAIRED, MODIFIED, OR REPLACED, THE OPERATOR SHALL CONDUCT TESTS PURSUANT TO AN APPROPRIATE AQMD-APPROVED TEST METHOD TO DETERMINE THE EXHAUST FLOW RATE WITHIN 60 DAYS OF SUCH REPAIR, MODIFICATION, OR REPLACEMENT.
[RULE 1132]

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTRATE COMPLIANCE WITH CONDITION NOS. 5 AND 6.
[RULE 109, RULE 1303(b)(2)-OFFSET

Periodic Monitoring:

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
   [RULE 3004 (a)(4)]

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions And Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
VOC: RULE 442
VOC: RULE 109
VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1132
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10651
A/N 514191

Equipment Description:

SPRAY BOOTH, BINKS, AUTOMOTIVE FILTER TYPE, 14'-0" W. X 47'-0" L. X 12'-0" H., WITH TWO 40" X 106" X 2", AND TWO 16" X 76" X 2" ATI POLYESTER FILTERS AND ONE 3 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

5. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THIS EQUIPMENT SHALL NOT EXCEED 8 GALLONS IN ANY ONE DAY.
(RULE 1303(b)(2)-OFFSET)

6. THE TOTAL QUANTITY OF CLEAN-UP SOLVENT USED IN THIS EQUIPMENT SHALL NOT EXCEED 4 ½ GALLONS IN ANY ONE DAY.
(RULE 1303(b)(2)-OFFSET)

FACILITY PERMIT TO OPERATE
MVP RV, INC

7. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 25 POUNDS PER DAY. FOR THE PURPOSE OF THIS CONDITION AND FOR EXEMPTION UNDER RULE 1132(h)(2), THE VOC EMISSIONS FROM THIS EQUIPMENT SHALL BE DEFINED AS A MONTHLY AVERAGE FOR EACH CALENDAR MONTH, CALCULATED BY DIVIDING THE TOTAL EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH BY THE NUMBER OF CALENDAR DAYS IN THAT MONTH. IF THE RECORDS GENERATED AFTER THE END OF ANY CALENDAR MONTH SHOW THAT THE VOC EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT THE APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132. EXCEEDANCE OF THE VOC EMISSION LIMIT OF THIS CONDITION SHALL NOT SUBJECT ANY EQUIPMENT AT THIS FACILITY TO NEW SOURCE REVIEW REQUIREMENTS IF THE OPERATOR COMPLIES WITH ALL OTHER CONDITIONS THAT ARE APPICABLE TO SUCH EQUIPMENT.
[RULE 1132]

8. THE EXHAUST FLOW RATE FROM THIS EQUIPMENT SHALL NOT BE LESS THAN 10,000 SCFM. IF THE EXHAUST FAN OF THIS SPRAY BOOTH IS REPAIRED, MODIFIED, OR REPLACED, THE OPERATOR SHALL CONDUCT TESTS PURSUANT TO AN APPROPRIATE AQMD-APPROVED TEST METHOD TO DETERMINE THE EXHAUST FLOW RATE WITHIN 60 DAYS OF SUCH REPAIR, MODIFICATION, OR REPLACEMENT.
[RULE 1132]

9. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTRATE COMPLIANCE WITH CONDITION NOS. 5, 6 & 7. [RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

10. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
    [RULE 3004 (a)(4)]

11. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions And Requirements:

FACILITY PERMIT TO OPERATE
MVP RV, INC

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
VOC: RULE 442
VOC: RULE 109
VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1132
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10682
A/N 514210

Equipment Description:

SPRAY BOOTH, BINKS, AUTOMOTIVE FILTER TYPE, 14'-0" W. X 47'-0" L. X 12'-0" H., WITH TWO 40" X 106" X 2", AND TWO 16" X 76" X 2" ATI POLYESTER FILTERS AND ONE 3 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF COATINGS AND SOLVENTS USED IN THIS EQUIPMENT SHALL NOT EXCEED 8 GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

6. THE TOTAL QUANTITY OF CLEAN-UP SOLVENT USED IN THIS EQUIPMENT SHALL NOT EXCEED 4 ½ GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
MVP RV, INC

7. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 25 POUNDS PER DAY. FOR THE PURPOSE OF THIS CONDITION AND FOR EXEMPTION UNDER RULE 1132(h)(2), THE VOC EMISSIONS FROM THIS EQUIPMENT SHALL BE DEFINED AS A MONTHLY AVERAGE FOR EACH CALENDAR MONTH, CALCULATED BY DIVIDING THE TOTAL EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH BY THE NUMBER OF CALENDAR DAYS IN THAT MONTH. IF THE RECORDS GENERATED AFTER THE END OF ANY CALENDAR MONTH SHOW THAT THE VOC EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT THE APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132. EXCEEDANCE OF THE VOC EMISSION LIMIT OF THIS CONDITION SHALL NOT SUBJECT ANY EQUIPMENT AT THIS FACILITY TO NEW SOURCE REVIEW REQUIREMENTS IF THE OPERATOR COMPLIES WITH ALL OTHER CONDITIONS THAT ARE APPICABLE TO SUCH EQUIPMENT.
[RULE 1132]

8. THE EXHAUST FLOW RATE FROM THIS EQUIPMENT SHALL NOT BE LESS THAN 10,000 SCFM. IF THE EXHAUST FAN OF THIS SPRAY BOOTH IS REPAIRED, MODIFIED, OR REPLACED, THE OPERATOR SHALL CONDUCT TESTS PURSUANT TO AN APPROPRIATE AQMD-APPROVED TEST METHOD TO DETERMINE THE EXHAUST FLOW RATE WITHIN 60 DAYS OF SUCH REPAIR, MODIFICATION, OR REPLACEMENT.
[RULE 1132]

9. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTRATE COMPLIANCE WITH CONDITION NOS. 5, 6 & 7. [RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

10. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
    [RULE 3004 (a)(4)]

11. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE
MVP RV, INC

Emissions And Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
VOC: RULE 442
VOC: RULE 109
VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1132
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10681
A/N 514209

Equipment Description:

DIP TANK, 4'-5" W. X 7'-8" L. X 1'-11" D., 486 GALLON CAPACITY.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE TOTAL QUANTITY OF SOLVENT AND SOLVENT CONTAINING MATERIALS USED IN APPLICATION NUMBERS 514207, 514201, 514208, 514205, 514209, & 514204 SHALL NOT EXCEED 35 GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

4. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMITTED FROM THIS EQUIPMENT SHALL NOT EXCEED 20 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

5. THE TOP OF THIS TANK SHALL BE COVERED WITH A LID WHEN THIS EQUIPMENT IS NOT IN OPERATION.
[RULE 1303(a)(1)-BACT]

6. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COPMPOUNDS). RECORDS SHALL ALSO BE KEPT TO VERIFY COMPLIANCE WITH CONDITION NOS. 3 AND 4. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 442
VOC: RULE 1136, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10680
A/N 514208

Equipment Description:

SPRAY GUN, HVLP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE TOTAL QUANTITY OF SOLVENT AND SOLVENT CONTAINING MATERIALS USED IN APPLICATION NUMBERS 514207, 514201, 514208, 514205, 514209, & 514204 SHALL NOT EXCEED 35 GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

4. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMITTED FROM THIS EQUIPMENT SHALL NOT EXCEED 17 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

5. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED(INCLUDING WATER AND EXEMPT COMPOUNDS). RECORDS SHALL ALSO BE KEPT TO VERIFY COMPLIANCE WITH CONDITION NO. 3 AND 4. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 442

FACILITY PERMIT TO OPERATE
MVP RV, INC

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10679
A/N 514207

Equipment Description:

SPRAY GUN, HVLP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE TOTAL QUANTITY OF SOLVENT AND SOLVENT CONTAINING MATERIALS USED IN APPLICATION NUMBERS 514207, 514201, 514208, 514205, 514209, & 514204 SHALL NOT EXCEED 35 GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

4. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMITTED FROM THIS EQUIPMENT SHALL NOT EXCEED 17 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

5. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED(INCLUDING WATER AND EXEMPT COMPOUNDS). RECORDS SHALL ALSO BE KEPT TO VERIFY COMPLIANCE WITH CONDITIONS NO. 3 AND 4. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 442
VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10678
A/N 514206

Equipment Description:

SPRAY GUN, HVLP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THE USE OF COATINGS AND SOLVENTS IN THIS EQUIPMENT SHALL NOT EXCEED 17 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

4. RECORDS OF COATINGS USAGE SHALL BE MAINTAINED PURSUANT TO RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 442
VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10677
A/N 514205

Equipment Description:

ADHESIVE SPRAY BOOTH, OPEN FACE, BINKS NO. 30-690, FLOOR TYPE, 12’-0” W. X 7'-0” H. X 6’-0” D., WITH TWENTY-EIGHT 20" X 20" EXHAUST FILTERS AND ONE 1-1/2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST TWO INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF SOLVENT AND SOLVENT CONTAINING MATERIALS USED IN APPLICATION NUMBERS 514207, 514201, 514208, 514205, 514209, & 514204 SHALL NOT EXCEED 35 GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
MVP RV, INC

6. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 12 POUNDS PER DAY. FOR THE PURPOSE OF THIS CONDITION AND FOR EXEMPTION UNDER RULE 1132(h)(2), THE VOC EMISSIONS FROM THIS EQUIPMENT SHALL BE DEFINED AS A MONTHLY AVERAGE FOR EACH CALENDAR MONTH, CALCULATED BY DIVIDING THE TOTAL EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH BY THE NUMBER OF CALENDAR DAYS IN THAT MONTH. IF THE RECORDS GENERATED AFTER THE END OF ANY CALENDAR MONTH SHOW THAT THE VOC EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT THE APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132. EXCEEDANCE OF THE VOC EMISSION LIMIT OF THIS CONDITION SHALL NOT SUBJECT ANY EQUIPMENT AT THIS FACILITY TO NEW SOURCE REVIEW REQUIREMENTS IF THE OPERATOR COMPLIES WITH ALL OTHER CONDITIONS THAT ARE APPICABLE TO SUCH EQUIPMENT.
[RULE 1132]

7. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTRATE COMPLIANCE WITH CONDITION NOS. 5 AND 6. ALL RECORDS SHALL BE PREPARED IN A FORMAT ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND MADE AVAILABLE UPON REQUEST TO THE EXECUTIVE OFFICIER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER MEDIA ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
   [RULE 3004 (a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481

FACILITY PERMIT TO OPERATE
MVP RV, INC

VOC: RULE 442
VOC: RULE 109
VOC: RULE 1132
VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10676
A/N 514204

Equipment Description:

SPRAY BOOTH, DRIVE THROUGH TYPE, BINKS, MODEL PBFA-5-7-T-LH, 25'-4" W. X 55'-0" L. X 16'-0" H., WITH FOUR 36" X 660" X 2" ATI POLYESTER FILTERS AND FOUR EXHAUST FANS, 7.5 HP EACH, AND TWO NATURAL GAS HEATERS, EACH 4,375,000 BTU/HR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST TWO INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.5 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF SOLVENT AND SOLVENT CONTAINING MATERIALS USED IN APPLICATION NUMBERS 514207, 514201, 514208, 514205, 514209, & 514204 SHALL NOT EXCEED 35 GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
MVP RV, INC

6. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 100 POUNDS PER DAY. FOR THE PURPOSE OF THIS CONDITION AND FOR EXEMPTION UNDER RULE 1132(h)(2), THE VOC EMISSIONS FROM THIS EQUIPMENT SHALL BE DEFINED AS A MONTHLY AVERAGE FOR EACH CALENDAR MONTH, CALCULATED BY DIVIDING THE TOTAL EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH BY THE NUMBER OF CALENDAR DAYS IN THAT MONTH. IF THE RECORDS GENERATED AFTER THE END OF ANY CALENDAR MONTH SHOW THAT THE VOC EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT THE APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132. EXCEEDANCE OF THE VOC EMISSION LIMIT OF THIS CONDITION SHALL NOT SUBJECT ANY EQUIPMENT AT THIS FACILITY TO NEW SOURCE REVIEW REQUIREMENTS IF THE OPERATOR COMPLIES WITH ALL OTHER CONDITIONS THAT ARE APPICABLE TO SUCH EQUIPMENT.
[RULE 1132]

7. THE EXHAUST FLOW RATE FROM THIS EQUIPMENT SHALL NOT BE LESS THAN 60,000 SCFM. IF THE EXHAUST FAN OF THIS SPRAY BOOTH IS REPAIRED, MODIFIED, OR REPLACED, THE OPERATOR SHALL CONDUCT TESTS PURSUANT TO AN APPROPRIATE AQMD-APPROVED TEST METHOD TO DETERMINE THE EXHAUST FLOW RATE WITHIN 60 DAYS OF SUCH REPAIR, MODIFICATION, OR REPLACEMENT.
[RULE 1132]

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTRATE COMPLIANCE WITH CONDITION NOS. 5 AND 6. [RULE 109, 1303(b)(2)-OFFSET

Periodic Monitoring:

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
   [RULE 3004 (a)(4)]

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions And Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

FACILITY PERMIT TO OPERATE
MVP RV, INC

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: 0.1 GR/SCF, RULE 409
PM: RULE 481
VOC: RULE 109
VOC: RULE 442
VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1132
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
CO: 2000 PPMV, RULE 407
NOX: 30 PPMV, RULE 1147
HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10675
A/N 514202

Equipment Description:

OVEN INFRARED TYPE, BINKS, MODEL TCE 6-50-40, 16'-0" W. X 55'-0" L. X 16'-0" H., ELECTRICALLY HEATED, 120 KW.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Emissions And Requirements:

3. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10674
A/N 514201

Equipment Description:

OPEN SPRAY SYSTEM CONSISTING OF:

1. TWO SPRAY GUNS, AIRLESS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE TOTAL QUANTITY OF SOLVENT AND SOLVENT CONTAINING MATERIALS USED IN APPLICATION NUMBERS 514207, 514201, 514208, 514205, 514209, & 514204 SHALL NOT EXCEED 35 GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

4. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMITTED FROM THIS EQUIPMENT SHALL NOT EXCEED 43 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

5. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED(INCLUDING WATER AND EXEMPT COMPOUNDS). RECORDS SHALL ALSO BE KEPT TO VERIFY COMPLIANCE WITH CONDITIONS NO. 3 AND 4. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 442

FACILITY PERMIT TO OPERATE
MVP RV, INC

VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10671
A/N 514200

Equipment Description:

SPRAY BOOTH, BINKS, MODEL PFF-12-7-T-LH, 12'-0" W. X 20'-6" L. X 7'-0" H., WITH TWENTY EIGHT 20" X 20" X 2" EXHAUST FILTERS AND ONE 2 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]

4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST TWO INCHES THICK.
[RULE 1303(a)(1)-BACT]

5. COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN CADMIUM, HEXAVALENT CHROMIUM OR ANY OTHER COMPOUND WHICH CONTAINS CADMIUM OR HEXAVALENT CHROMIUM, OR METHYLENE CHLORIDE.
[RULE 1401]

6. THE EXHAUST FLOW RATE FROM THIS EQUIPMENT SHALL NOT BE LESS THAN 10,000 SCFM. IF THE EXHAUST FAN OF THIS SPRAY BOOTH IS REPAIRED, MODIFIED, OR REPLACED, THE OPERATOR SHALL CONDUCT TESTS PURSUANT TO AN APPROPRIATE AQMD-APPROVED TEST METHOD TO DETERMINE THE EXHAUST FLOW RATE WITHIN 60 DAYS OF SUCH REPAIR, MODIFICATION, OR REPLACEMENT.
[RULE 1132]

FACILITY PERMIT TO OPERATE
MVP RV, INC

7. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 25 POUNDS PER DAY. FOR THE PURPOSE OF THIS CONDITION AND FOR EXEMPTION UNDER RULE 1132(h)(2), THE VOC EMISSIONS FROM THIS EQUIPMENT SHALL BE DEFINED AS A MONTHLY AVERAGE FOR EACH CALENDAR MONTH, CALCULATED BY DIVIDING THE TOTAL EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH BY THE NUMBER OF CALENDAR DAYS IN THAT MONTH. IF THE RECORDS GENERATED AFTER THE END OF ANY CALENDAR MONTH SHOW THAT THE VOC EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT THE APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132. EXCEEDANCE OF THE VOC EMISSION LIMIT OF THIS CONDITION SHALL NOT SUBJECT ANY EQUIPMENT AT THIS FACILITY TO NEW SOURCE REVIEW REQUIREMENTS IF THE OPERATOR COMPLIES WITH ALL OTHER CONDITIONS THAT ARE APPICABLE TO SUCH EQUIPMENT.
[RULE 1132]

8. THE TOTAL QUANTITY OF COATINGS AND REDUCER USED IN THIS EQUIPMENT SHALL NOT EXCEED 180 GALLONS IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]

9. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY AND MONTHLY VOC IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED INCLUDING (WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

10. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE MONTH. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING MANAGEMENT OFFICIAL WITH RESPONSIBILITY FOR OPERATION OF EQUIPMENT SUBJECT TO THE PERMIT.
[RULE 109, 1303(b)(2)-OFFSET]

11. THE OPERATOR SHALL MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
(RULE 109, 1303(b)(2)-OFFSET)

12. THE OPERATOR SHALL RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.
(RULE 109, 1303(b)(2)-OFFSET)

13. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT AND RETAINED AT THE FAICLITY FOR FIVE YEARS, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.

FACILITY PERMIT TO OPERATE
MVP RV, INC

(RULE 109, 1303(b)(2)-OFFSET)

Periodic Monitoring:

14. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
    [RULE 3004 (a)(4)]

15. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
    [RULE 3004(a)(4)]

Emissions And Requirements:

16. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481
    VOC: RULE 109
    VOC: RULE 442
    VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1132
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
    HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10670
A/N 514199

Equipment Description:

SPRAY BOOTH, AUTOMOTIVE TYPE, 24'-0" W. X 33'-0" L. X 18'-0" H., WITH ONE 1 HP EXHAUST FAN AND ONE 20" X 20" EXHAUST FILTER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH A FILTER MEDIA, AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. THE DEVICE OR GAUGE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTER SHALL BE PROPERLY MAINTAINED IN GOOD OPERATING CONDITION. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]

5. NO MATERIAL THAT MAY EMIT VOLATILE ORGANIC COMPOUND (VOC) SHALL BE APPLIED/USED IN THIS EQUIPMENT.
[RULE 1303(b)(2)-OFFSET]

6. THE COATINGS, CLEANUP SOLVENTS OR OTHER MATERIALS APPLIED/USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY OF THE COMPOUNDS IDENTIFIED AS CARCINOGENIC IN SCAQMD RULE 1401 AS AMENDED DECEMBER 7,1990.
[RULE 1401]

7. THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE VOC CONTENT OF EACH MATERIAL AS APPLIED INCLUDING (WATER AND EXEMPT COMPOUNDS) AS REQUIRED BY CONDITION NO. 5. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
MVP RV, INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
   A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
   B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
   C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
   [RULE 3004 (a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
   [RULE 3004(a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
VOC: RULE 109
VOC: RULE 442
VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1132
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10669
A/N 514198

Equipment Description:

SPRAY BOOTH, BINKS, AUTOMOTIVE TYPE, SEMI DOWNDRAFT, 22'-4" W. X 48'-0" L. X 12'-0" H., WITH FOUR 5.0 HP EXHAUST FANS AND EIGHT 3'-0" X 20'-0" EXHAUST FILTERS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH A FILTER MEDIA, AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUND IDENTIFIED IN DISTRICT RULE 1401 WITH A LISTING DATE OF AUGUST 13, 1999 OR EARLIER EXCEPT AMMONIA (CAS# 7664-41-7).
[RULE 1401]

6. THE EXHAUST FLOW RATE FROM THIS EQUIPMENT SHALL NOT BE LESS THAN 60,000 SCFM. IF THE EXHAUST FAN OF THIS SPRAY BOOTH IS REPAIRED, MODIFIED, OR REPLACED, THE OPERATOR SHALL CONDUCT TESTS PURSUANT TO AN APPROPRIATE AQMD-APPROVED TEST METHOD TO DETERMINE THE EXHAUST FLOW RATE WITHIN 60 DAYS OF SUCH REPAIR, MODIFICATION, OR REPLACEMENT.
[RULE 1132]

FACILITY PERMIT TO OPERATE
MVP RV, INC

7. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 100 POUNDS PER DAY. FOR THE PURPOSE OF THIS CONDITION AND FOR EXEMPTION UNDER RULE 1132(h)(2), THE VOC EMISSIONS FROM THIS EQUIPMENT SHALL BE DEFINED AS A MONTHLY AVERAGE FOR EACH CALENDAR MONTH, CALCULATED BY DIVIDING THE TOTAL EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH BY THE NUMBER OF CALENDAR DAYS IN THAT MONTH. IF THE RECORDS GENERATED AFTER THE END OF ANY CALENDAR MONTH SHOW THAT THE VOC EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT THE APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132. EXCEEDANCE OF THE VOC EMISSION LIMIT OF THIS CONDITION SHALL NOT SUBJECT ANY EQUIPMENT AT THIS FACILITY TO NEW SOURCE REVIEW REQUIREMENTS IF THE OPERATOR COMPLIES WITH ALL OTHER CONDITIONS THAT ARE APPICABLE TO SUCH EQUIPMENT.
[RULE 1132]

8. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THE USAGE OF COATINGS, REDUCERS AND CLEAN-UP SOLVENTS IN THIS EQUIPMENT SHALL NOT EXCEED 850 POUNDS VOC PER MONTH.
[RULE 1303(b)(2)-OFFSET]

9. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY AND MONTHLY VOC IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED INCLUDING (WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

10. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE MONTH. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
[RULE 109, 1303(b)(2)-OFFSET]

11. THE OPERATOR SHALL MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
(RULE 109, 1303(b)(2)-OFFSET)

12. THE OPERATOR SHALL RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MAIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.
(RULE 109, 1303(b)(2)-OFFSET)

13. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT AND RETAINED AT THE FAICLITY FOR FIVE YEARS, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.

FACILITY PERMIT TO OPERATE
MVP RV, INC

(RULE 109, 1303(b)(2)-OFFSET)

Periodic Monitoring:

14. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
    [RULE 3004 (a)(4)]

15. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
    [RULE 3004(a)(4)]

Emissions And Requirements:

16. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481
    VOC: RULE 109
    VOC: RULE 442
    VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1132
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
    HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10666
A/N 514197

Equipment Description:

SPRAY BOOTH, BINKS, MODEL RF-654-T-LH, AUTOMOTIVE TYPE, 16'-0" W. X 54'-0" L. X 16'-0" H., WITH THIRTY-SIX 20" X 20" EXHAUST FILTERS AND ONE 7.5-HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH A FILTER MEDIA, AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]

4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]

5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC COMPOUND IDENTIFIED IN DISTRICT RULE 1401, WITH A LISTING DATE OF AUGUST 13, 1999 OR EARLIER EXCEPT FOR TOLUENE (CAS#108-33-3), METHYL ETHYL KETONE(CAS#78-93-3), ETHYLENE GLYCOL BUTYL ETHER(CAS#111-76-2), AND XYLENE(CAS#1330-20-7).
[RULE 1401]

6. THE EXHAUST FLOW RATE FROM THIS EQUIPMENT SHALL NOT BE LESS THAN 10,000 SCFM. IF THE EXHAUST FAN OF THIS SPRAY BOOTH IS REPAIRED, MODIFIED, OR REPLACED, THE OPERATOR SHALL CONDUCT TESTS PURSUANT TO AN APPROPRIATE AQMD-APPROVED TEST METHOD TO DETERMINE THE EXHAUST FLOW RATE WITHIN 60 DAYS OF SUCH REPAIR, MODIFICATION, OR REPLACEMENT.
[RULE 1132]

FACILITY PERMIT TO OPERATE
MVP RV, INC

7. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 25 POUNDS PER DAY. FOR THE PURPOSE OF THIS CONDITION AND FOR EXEMPTION UNDER RULE 1132(h)(2), THE VOC EMISSIONS FROM THIS EQUIPMENT SHALL BE DEFINED AS A MONTHLY AVERAGE FOR EACH CALENDAR MONTH, CALCULATED BY DIVIDING THE TOTAL EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH BY THE NUMBER OF CALENDAR DAYS IN THAT MONTH. IF THE RECORDS GENERATED AFTER THE END OF ANY CALENDAR MONTH SHOW THAT THE VOC EMISSIONS FROM THIS EQUIPMENT FOR THE CALENDAR MONTH EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT THE APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132. EXCEEDANCE OF THE VOC EMISSION LIMIT OF THIS CONDITION SHALL NOT SUBJECT ANY EQUIPMENT AT THIS FACILITY TO NEW SOURCE REVIEW REQUIREMENTS IF THE OPERATOR COMPLIES WITH ALL OTHER CONDITIONS THAT ARE APPICABLE TO SUCH EQUIPMENT.
[RULE 1132]

8. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS USAGE OF COATINGS, REDUCERS AND CLEAN-UP SOLVENTS IN THIS EQUIPMENT SHALL NOT EXCEED 850 POUNDS IN ANY ONE CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]

9. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY AND MONTHLY VOC IN POUNDS AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED INCLUDING (WATER AND EXEMPT COMPOUNDS). ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

10. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE MONTH. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING MANAGEMENT OFFICIAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
[RULE 109, 1303(b)(2)-OFFSET]

11. THE OPERATOR SHALL MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WERE USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
[RULE 109, 1303(b)(2)-OFFSET]

12. THE OPERATOR SHALL RETAIN ALL PURCHASE INVOICES FOR ALL VOC CONTAINING MATERIALS USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIALS REMOVED FROM THE FACILITY FOR FIVE YEARS.
[RULE 109, 1303(b)(2)-OFFSET]

13. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE RETAINED AT THE FACILITY FOR FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE
MVP RV, INC

Periodic Monitoring:

14. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
    [RULE 3004 (a)(4)]

15. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
    [RULE 3004(a)(4)]

Emissions And Requirements:

16. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
    PM: RULE 481
    VOC: RULE 109
    VOC: RULE 442
    VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
    VOC: RULE 1132
    VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
    HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
    HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10664
A/N 514196

Equipment Description:

OVEN NO. 1, TELLKAMP SYSTEMS, SERIAL NO. 3773, 20'-6" W. X 50'-8" L. X 16'-10" H., 1,600,000 BTU PER HOUR, NATURAL GAS FIRED, WITH A CYCLOMAX 1.6 LOW-NOX BURNER, MODEL EB2MRV.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE NITROGEN OXIDES (NOX) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPMV @ 3 PERCENT O2.
[RULE 1303(a)(1)-BACT]

4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND HAS BEEN ISSUED A PERMIT BY DISTRICT.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM EQUIPMENT UNDER APPLICATIONS 514193, 514195 & 514196 AND ASSOCIATED OPERATIONS SHALL NOT EXCEED 1290 POUNDS IN ANY CALENDAR MONTH. ASSOCIATED OPERATIONS INCLUDE, BUT ARE NOT LIMITED TO, SURFACE PREPARATION, EQUIPMENT CLEAN-UP, AND THE APPLICATION OF ANY OTHER MATERIALS TO PARTS THAT ARE PROCESSED IN THE PERMITTED EQUIPMENT. FOR EQUIPMENT THAT IS VENTED TO AIR POLLUTION CONTROL (APC) EQUIPMENT, THE VOC EMISSIONS SHALL BE CALCULATED USING THE REQUIRED OVERALL CONTROL EFFICIENCY SPECIFIED IN THE PERMIT(S) FOR THE APC EQUIPMENT. ANY PROCEDURES USED TO ACCOUNT FOR WASTE DISPOSAL SHALL NOT BE ALLOWED UNLESS SUCH PROCEDURES HAVE BEEN APPROVED IN WRITING BY THE AQMD.
[RULE 1303(b)(2)-OFFSET]

6. TO ENSURE COMPLIANCE WITH THE MONTHLY EMISSION CAP, THE FACILITY OPERATOR SHALL:
   (I) COMPLY WITH RULE 109 (RECORD KEEPING FOR VOLATILE ORGANIC COMPOUND EMISSIONS).

FACILITY PERMIT TO OPERATE
MVP RV, INC

(II) WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS COVERED BY A MONTHLY LIMIT. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.

(III) MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.

(IV) RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.
[RULE 109, 1303(b)(2)-OFFSET]

7. COATING, REDUCERS, THINNER, AND CLEAN-UP SOLVENTS USED ON ARTICLES THAT ARE PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC COMPOUNDS WITH A LISTING DATE OF MAY 3, 2002 OR EARLIER IDENTIFIED IN RULE 1401 EXCEPT TOLUENE, ETHYLBENZENE, XYLENE, METHYL ETHYL KETONE, METHANOL, ETHYLENE GLYCOL MONOBUTYL ETHER.
[RULE 1401]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: 0.1 GR/SCF, RULE 409
CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
NOx: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10653
A/N 514195

Equipment Description:

OVEN NO. 2, TELLKAMP SYSTEMS, SERIAL NO. 3773, 20'-6" W. X 50'-8" L. X 16'-10" H., 1,600,000 BTU PER HOUR, NATURAL GAS FIRED, WITH A CYCLOMAX 1.6 LOW-NOX BURNER, MODEL EB2MRV.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE NITROGEN OXIDES (NOX) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPMV @ 3 PERCENT O2.
[RULE 1303(a)(1)-BACT]

4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND HAS BEEN ISSUED A PERMIT BY DISTRICT.
[RULE 1303(a)(1)-BACT]

5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM EQUIPMENT UNDER APPLICATIONS 514193, 514195 & 514196 AND ASSOCIATED OPERATIONS SHALL NOT EXCEED 1290 POUNDS IN ANY CALENDAR MONTH. ASSOCIATED OPERATIONS INCLUDE, BUT ARE NOT LIMITED TO, SURFACE PREPARATION, EQUIPMENT CLEAN-UP, AND THE APPLICATION OF ANY OTHER MATERIALS TO PARTS THAT ARE PROCESSED IN THE PERMITTED EQUIPMENT. FOR EQUIPMENT THAT IS VENTED TO AIR POLLUTION CONTROL (APC) EQUIPMENT, THE VOC EMISSIONS SHALL BE CALCULATED USING THE REQUIRED OVERALL CONTROL EFFICIENCY SPECIFIED IN THE PERMIT(S) FOR THE APC EQUIPMENT. ANY PROCEDURES USED TO ACCOUNT FOR WASTE DISPOSAL SHALL NOT BE ALLOWED UNLESS SUCH PROCEDURES HAVE BEEN APPROVED IN WRITING BY THE AQMD.
[RULE 1303(b)(2)-OFFSET]

6. TO ENSURE COMPLIANCE WITH THE MONTHLY EMISSION CAP, THE FACILITY OPERATOR SHALL:
   (I) COMPLY WITH RULE 109 (RECORD KEEPING FOR VOLATILE ORGANIC COMPOUND EMISSIONS).

FACILITY PERMIT TO OPERATE
MVP RV, INC

(V) WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS COVERED BY A MONTHLY LIMIT. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.

(VI) MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.

(VII) RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.
[RULE 109, 1303(b)(2)-OFFSET]

7. COATING, REDUCERS, THINNER, AND CLEAN-UP SOLVENTS USED ON ARTICLES THAT ARE PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC COMPOUNDS WITH A LISTING DATE OF MAY 3, 2002 OR EARLIER IDENTIFIED IN RULE 1401 EXCEPT TOLUENE, ETHYLBENZENE, XYLENE, METHYL ETHYL KETONE, METHANOL, ETHYLENE GLYCOL MONOBUTYL ETHER.
[RULE 1401]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: 0.1 GR/SCF, RULE 409
CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
NOx: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO OPERATE

Permit No. G10652
A/N 514193

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. REGENERATIVE THERMAL OXIDIZER NO. 1, TELLKAMP SYSTEMS, MODEL ROXIDIZER-40, 2,700,000 BTU PER HOUR, NATURAL GAS FIRED, WITH A NATURAL GAS INJECTION RATE OF 6,000,000 BTU PER HOUR, TWO CERAMIC SADDLE BEDS, 4'-9" H. X 19'-0" L. X 12'-0" W., EACH.

2. REGENERATIVE THERMAL OXIDIZER NO. 2, TELLKAMP SYSTEMS, MODEL ROXIDIZER-40, 2,700,000 BTU PER HOUR, NATURAL GAS FIRED, WITH A NATURAL GAS INJECTION RATE OF 6,000,000 BTU PER HOUR, TWO CERAMIC SADDLE BEDS, 4'-9" H. X 19'-0" L. X 12'-0" W., EACH.

3. SPRAY BOOTH, BC-1, SPRAY SYSTEMS, AUTOMOTIVE TYPE, MODEL NO. TB522216-DDT, 22'-0" W. X 52'-0" L. X 16'-0" H., WITH A 1,375,000 BTU PER HOUR, NATURAL GAS FIRED HEATER, ONE HUNDRED-EIGHT PANEL FILTERS (STAGE 1) 20" X 25" X 1", ONE HUNDRED-EIGHT PLEATED PANEL FILTERS 20" X 25" X 2", ONE HUNDRED EIGHT 5-BAG POCKET FILTERS 20" X 25" X 12" AND TWO 25 HP EXHAUST FANS.

4. SPRAY BOOTH, GC-1, SPRAY SYSTEMS, AUTOMOTIVE TYPE, MODEL NO. TB522216-DDT, 22'-0" W. X 52'-0" L. X 16'-0" H., WITH A 1,375,000 BTU PER HOUR, NATURAL GAS FIRED HEATER, ONE HUNDRED-EIGHT PANEL FILTERS (STAGE 1) 20" X 25" X 1", ONE HUNDRED-EIGHT PLEATED PANEL FILTERS 20" X 25" X 2", ONE HUNDRED EIGHT 5-BAG POCKET FILTERS 20" X 25" X 12" AND TWO 25 HP EXHAUST FANS.

5. SPRAY BOOTH, BC-2, SPRAY SYSTEMS, AUTOMOTIVE TYPE, MODEL NO. TB522216-DDT, 22'-0" W. X 52'-0" L. X 16'-0" H., WITH A 1,375,000 BTU PER HOUR, NATURAL GAS FIRED HEATER, ONE HUNDRED-EIGHT PANEL FILTERS (STAGE 1) 20" X 25" X 1", ONE HUNDRED-EIGHT PLEATED PANEL FILTERS 20" X 25" X 2", ONE HUNDRED EIGHT 5-BAG POCKET FILTERS 20" X 25" X 12" AND TWO 25 HP EXHAUST FANS.

6. SPRAY BOOTH, GC-2, SPRAY SYSTEMS, AUTOMOTIVE TYPE, MODEL NO. TB522216-DDT, 22'-0" W. X 52'-0" L. X 16'-0" H., WITH A 1,375,000 BTU PER HOUR, NATURAL GAS FIRED HEATER, ONE HUNDRED-EIGHT PANEL FILTERS (STAGE 1) 20" X 25" X 1", ONE HUNDRED-EIGHT PLEATED PANEL FILTERS 20" X 25" X 2", ONE HUNDRED EIGHT 5-BAG POCKET FILTERS 20" X 25" X 12" AND TWO 25 HP EXHAUST FAN.

7. SPRAY BOOTH, CC-1, SPRAY SYSTEMS, AUTOMOTIVE TYPE, MODEL NO. TB522216-DDT, 22'-0" W. X 52'-0" L. X 16'-0" H., WITH A 1,375,000 BTU PER HOUR, NATURAL GAS FIRED HEATER, ONE HUNDRED-EIGHT PANEL FILTERS (STAGE 1) 20" X 25" X 1", ONE HUNDRED-EIGHT PLEATED PANEL FILTERS 20" X 25" X 2", ONE HUNDRED EIGHT 5-BAG POCKET FILTERS 20" X 25" X 12" AND TWO 30 HP EXHAUST FANS.

FACILITY PERMIT TO OPERATE
MVP RV, INC

8. SPRAY BOOTH, CC-2, SPRAY SYSTEMS, AUTOMOTIVE TYPE, MODEL NO. TB522216-DDT, 22'-0" W. X 52'-0" L. X 16'-0" H., WITH A 1,375,000 BTU PER HOUR, NATURAL GAS FIRED HEATER, ONE HUNDRED-EIGHT PANEL FILTERS (STAGE 1) 20" X 25" X 1", ONE HUNDRED-EIGHT PLEATED PANEL FILTERS 20" X 25" X 2", ONE HUNDRED EIGHT 5-BAG POCKET FILTERS 20" X 25" X 12" AND TWO 30 HP EXHAUST FANS.

9. SPRAY BOOTH, TOUCH-UP, SPRAY SYSTEMS, AUTOMOTIVE TYPE, MODEL NO. TB522216-DDT, 22'-0" W. X 52'-0" L. X 16'-0" H., WITH A 1,375,000 BTU PER HOUR, NATURAL GAS FIRED HEATER, ONE HUNDRED-EIGHT PANEL FILTERS (STAGE 1), 20" X 25" X 1", ONE HUNDRED-EIGHT PLEATED PANEL FILTERS 20" X 25" X 2", ONE HUNDRED EIGHT 5-BAG POCKET FILTERS 20" X 25" X 12" AND TWO 30 HP EXHAUST FANS.

10. EXHAUST SYSTEM CONSISTING OF A PERMANENT TOTAL ENCLOSURE (PTE) AND TWO 150 HP BLOWERS (ONE FOR EACH OXIDIZER) VENTING SEVEN SPRAY BOOTHS AND TWO OVENS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]

2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

3. THE OPERATOR SHALL INSTALL AND MAINTAIN IN THE DRY FILTER BOOTHS A MANOMETER TO DETERMINE THE DIFFERENTIAL PRESSURE DROP ACROSS THE THREE-STAGE EXHAUST FILTERS. IN OPERATION, THE DIFFERENTIAL PRESSURE SHALL NOT EXCEED 1.5 INCHES WATER COLUMN.
[RULE 1303(a)(1)-BACT]

4. COATING, REDUCERS, THINNER, AND CLEAN-UP SOLVENTS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC COMPOUNDS WITH A LISTING DATE OF MAY 3, 2002 OR EARLIER IDENTIFIED IN RULE 1401 EXCEPT TOLUENE, ETHYLBENZENE, XYLENE, METHYL ETHYL KETONE, METHANOL, ETHYLENE GLYCOL MONOBUTYL ETHER.
[RULE 1401]

5. THE NITROGEN OXIDES (NOX) EMISSIONS FROM THE SPRAY BOOTH HEATERS SHALL NOT EXCEED 60 PPMV AT 3% O2.
[RULE 1303(a)(1)-BACT]

6. THE REGENERATIVE THERMAL OXIDIZERS SHALL BE IN OPERATION WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT]

7. THE OPERATOR SHALL OPERATE AND MAINTAIN THE THERMAL OXIDIZERS ACCORDING TO THE FOLLOWING REQUIREMENTS:

FACILITY PERMIT TO OPERATE
MVP RV, INC

THE COMBUSTION CHAMBER TEMPERATURE SHALL BE MAINTAINED AT A MINIMUM OF 1,550 DEGREES FAHRENHEIT WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.

THE OPERATOR SHALL OPERATE AND MAINTAIN A TEMPERATURE MEASURING AND RECORDING SYSTEM TO CONTINUOUSLY MEASURE AND RECORD THE COMBUSTION CHAMBER TEMPERATURE PURSUANT TO THE OPERATION AND MAINTENANCE REQUIREMENTS SPECIFIED IN 40 CFR PART 64.7. SUCH A SYSTEM SHALL HAVE AN ACCURACY OF WITHIN 1% OF THE TEMPERATURE BEING MONITORED AND SHALL BE INSPECTED, MAINTAINED, AND CALIBRATED ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

FOR THE PURPOSE OF THIS CONDITION, A DEVIATION SHALL BE DEFINED AS WHEN A COMBUSTION CHAMBER TEMPERATURE OF LESS THAN 1,550 DEGREES FAHRENHEIT OCCURS DURING NORMAL OPERATION OF THE EQUIPMENT IT SERVES. THE OPERATOR SHALL REVIEW THE RECORDS OF THE COMBUSTION CHAMBER TEMPERATURE ON A DAILY BASIS TO DETERMINE IF A DEVIATION OCCURS OR SHALL INSTALL AN ALARM SYSTEM TO ALERT THE OPERATOR WHEN A DEVIATION OCCURS.

WHENEVER A DEVIATION OCCURS, THE OPERATOR SHALL INSPECT THIS EQUIPMENT TO IDENTIFY THE CAUSE OF SUCH A DEVIATION, TAKE IMMEDIATE CORRECTIVE ACTION TO MAINTAIN THE COMBUSTION CHAMBER TEMPERATURE AT OR ABOVE 1,550 DEGREES FAHRENHEIT, AND KEEP RECORDS OF THE DURATION AND CAUSE (INCLUDING UNKNOWN CAUSE, IF APPLICABLE) OF THE DEVIATION AND THE CORRECTIVE ACTION TAKEN.

ALL DEVIATIONS SHALL BE REPORTED TO THE AQMD PURSUANT TO THE REQUIREMENTS SPECIFIED IN 40 CFR PART 64.9 AND CONDITION NOS. 22 AND 23 IN SECTION K OF THIS PERMIT. THE REPORT SHALL INCLUDE THE TOTAL OPERATING TIME OF THIS EQUIPMENT AND THE TOTAL ACCUMULATED DURATION OF ALL DEVIATIONS FOR EACH SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL SUBMIT AN APPLICATION WITH A QUALITY IMPROVEMENT PLAN (QIP) IN ACCORDANCE WITH 40 CFR PART 64.8 TO THE AQMD IF AN ACCUMULATION OF DEVIATIONS EXCEEDS 5 PERCENT DURATION OF THIS EQUIPMENT'S TOTAL OPERATING TIME FOR ANY SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT. THE REQUIRED QIP SHALL BE SUBMITTED TO THE AQMD WITHIN 90 CALENDAR DAYS AFTER THE DUE DATE FOR THE SEMI-ANNUAL MONITORING REPORT.

THE OPERATOR SHALL INSPECT AND MAINTAIN ALL COMPONENTS OF THIS EQUIPMENT ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

THE OPERATOR SHALL KEEP ADEQUATE RECORDS IN A FORMAT THAT IS ACCEPTABLE TO THE AQMD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE REQUIREMENTS SPECIFIED IN THIS CONDITION AND 40 CFR PART 64.9 FOR A MINIMUM OF FIVE YEARS.

[RULE 1303(a)(1)-BACT, 3004(a)(4)-PERIODIC MONITORING, 40CFR PART 64]

8. THE TEMPERATURE INDICATING AND RECORDING SYSTEM SHALL BE IN OPERATION WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE
MVP RV, INC

9. THE OXIDIZER SHALL BE FIRED ON NATURAL GAS ONLY.
[RULE 1303(a)(1)-BACT]

10. THE OPERATOR SHALL MAINTAIN THE PERMANENT TOTAL ENCLOSURE (PTE) TO COMPLY WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]

11. ALL ACCESS DOORS TO THE PERMANENT TOTAL ENCLOSURE AND SPRAY BOOTHS SHALL BE KEPT CLOSED DURING NORMAL OPERATIONS.
[RULE 1303(a)(1)-BACT]

12. THIS EQUIPMENT SHALL BE MAINTAINED AND OPERATED AT A MINIMUM DESTRUCTION EFFICIENCY OF 95% AND AN OVERALL VOC CONTROL EFFICIENCY (COLLECTION AND DESTRUCTION) OF 90% WHEN THE BASIC EQUIPMENT IT SERVES IS IN OPERATION
[RULE 1303(a)(1)-BACT]

13. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM EQUIPMENT UNDER APPLICATIONS 514193, 514195 & 514196 AND ASSOCIATED OPERATIONS SHALL NOT EXCEED 1290 POUNDS IN ANY CALENDAR MONTH. ASSOCIATED OPERATIONS INCLUDE, BUT ARE NOT LIMITED TO, SURFACE PREPARATION, EQUIPMENT CLEAN-UP, AND THE APPLICATION OF ANY OTHER MATERIALS TO PARTS THAT ARE PROCESSED IN THE PERMITTED EQUIPMENT. FOR EQUIPMENT THAT IS VENTED TO AIR POLLUTION CONTROL (APC) EQUIPMENT, THE VOC EMISSIONS SHALL BE CALCULATED USING THE REQUIRED OVERALL CONTROL EFFICIENCY SPECIFIED IN THE PERMIT(S) FOR THE APC EQUIPMENT. ANY PROCEDURES USED TO ACCOUNT FOR WASTE DISPOSAL SHALL NOT BE ALLOWED UNLESS SUCH PROCEDURES HAVE BEEN APPROVED IN WRITING BY THE AQMD.
[RULE 1303(b)(2)-OFFSET]

14. TO ENSURE COMPLIANCE WITH THE MONTHLY EMISSION CAP, THE FACILITY OPERATOR SHALL:
   (I) COMPLY WITH RULE 109 (RECORD KEEPING FOR VOLATILE ORGANIC COMPOUND EMISSIONS).
   (VIII) WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS COVERED BY A MONTHLY LIMIT. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
   (IX) MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
   (X) RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.
   [RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

FACILITY PERMIT TO OPERATE
MVP RV, INC

15. THE OPEATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER MEDIA ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

16. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
    A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
    B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
    C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
    [RULE 3004 (a)(4)]

17. THE OPERATOR SHALL CONDUCT SOURCE TEST(S) IN ACCORDANCE WITH THE FOLLOWING SPECIFICATIONS:
    A. THE TEST SHALL BE CONDUCTED AT LEAST ONCE DURING THE LIFE OF THE PERMIT.
    B. THE TEST SHALL BE CONDUCTED NO LATER THAN OCTOBER 1, 2010 UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
    C. THE TEST SHALL BE CONDUCTED TO DETERMINE THE VOC EMISSIONS USING AN APPROVED DISTRICT METHOD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE PERMIT CONDITION(S), RULES AND REGULATIONS.
    D. THE SOURCE TEST SHALL BE CONDUCTED WHILE THE OXIDIZER IS OPERATING AT A TEMPERATURE OF NOT LESS THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT. IF THE OPERATING TEMPERATURE DURING THE SOURCE TEST IS GREATER THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT, THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT MAY BE INCREASED TO REFLECT THE OPERATING TEMPERATURE DURING THE SOURCE TEST.
    E. THE OPERATOR SHALL COMPLY WITH ADMINISTRATIVE CONDITIONS NOS. 8, 9, AND 10 OF SECTION E OF THIS FACILITY PERMIT.
    F. THE OPERATOR SHALL SUBMIT TWO COMPLETE COPIES OF THE SOURCE TEST REPORT SPECIFIED IN CONDITION NO. 9 OF SECTION E OF THIS FACILITY PERMIT TO THE DISTRICT ENGINEERING AND COMPLIANCE DIVISION. THE ENGINEERING COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, COATING, PRINTING AND AEROSPACE OPERATIONS, ATTN: AIR QAULITY AND COMPLIANCE SUPERVISOR, 21865 COPLEY DRIVE, DIAMOND BAR, CA 91765. THE COMPLIANCE COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, P.O. BOX 4941, DIAMOND BAR, CA 91765

    [RULE 3004(a)(4)]

Emissions And Requirements:

18. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

    CO: 2000 PPMV, RULE 407
    PM: 0.1 GR/SCF, RULE 409
    PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PM: RULE 481
VOC: RULE 442
VOC: RULE 109
VOC: RULE 1115, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1132
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
NOX: 60 PPMV, RULE 1147 (AFTERBURNER)
NOX; 30 PPMV, RULE 1147 (MAKE-UP AIR HEATER)
HAP(S) 40CFR63 SUBPART MMMM, SEE SECTION J FOR REQUIREMENTS
HAP(S) 40CFR63 SUBPART PPPP, SEE SECTION J FOR REQUIREMENTS

FACILITY PERMIT TO OPERATE
MVP RV, INC

PERMIT TO CONSTRUCT

NONE

FACILITY PERMIT TO OPERATE
MVP RV, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

   FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

   FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

   [RULE 3004 (a) (4)]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

   VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE
MVP RV, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 109

FACILITY PERMIT TO OPERATE
MVP RV, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND LAY, BRUSH AND ROLL UP RESIN OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   VOC: RULE 1162, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
   VOC: RULE 109

FACILITY PERMIT TO OPERATE
MVP RV, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   REFRIGERANT: 40CFR 82 SUBART F

FACILITY PERMIT TO OPERATE
MVP RV, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, REFRIGERANT RECOVERY AND/OR RECYCLING UNITS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

   REFRIGERANT: 40CFR 82 SUBPART B

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]

   a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]

   b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]

   c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]

2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]

3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statues of other governmental agencies. [204]

4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]

6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]

7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]

   a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]

   b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]

   c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]

   d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO2) and be averaged over 15 consecutive minutes; [407]

   e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO2) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION E: ADMINISTRATIVE CONDITIONS

f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O2) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]

8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]

a. Brief description of the equipment tested.

b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.

c. Operating conditions under which the test will be performed.

d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).

e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.

f. Description of calibration and quality assurance procedures.

g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).

9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]

a. The results of the source test.

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION E: ADMINISTRATIVE CONDITIONS

b. Brief description of the equipment tested.

c. Operating conditions under which the test was performed.

d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).

e. Field and laboratory data forms, strip charts and analyses.

f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.

10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]

11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR RECLAIM SOURCES

NOT APPLICABLE

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

See Section D of this permit for any Permit to Construct issued to this facility.

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION J: AIR TOXICS
[40CFR 63 Subpart MMMM 01-02-2004]

NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR SURFACE COATING OF MISCELLANEOUS METAL PARTS AND PRODUCTS

1. The operator shall comply with all applicable requirements of 40 CFR 63, Subpart MMMM – National Emission Standards for Surface Coating of Miscellaneous Metal Parts and Products and 40 CFR 63, Subpart A - General Provisions by the compliance dates that are specified in these subparts.

2. The operator shall comply with all applicable requirements of this subpart for each new, reconstructed, or existing affected source as defined in Sections 63.3881 and 63.3882 by the compliance dates that are specified in Section 63.3883.

3. The operator shall comply with all applicable emission limits that are specified in Section 63.3890 by using one of the three options identified in Section 63.3891 for each new, reconstructed, or existing affected source. All surface coatings that are applied in each affected source shall comply with the following limits:

Coating Type	Organic HAP Limit New or Reconstructed (kg/l solids)	[lb/gal solids]	Organic HAP Limit Existing (kg/l solids)	[lb/gal solids]
General Use Coating	(0.23)	[1.90]	(0.31)	[2.60]
High Performance Coating	(3.30)	[27.5]	(3.30)	[27.5]
Magnet Wire Coating	(0.04)	[0.44]	(0.12)	[1.00]
Rubber-to-Metal Coating	(0.81)	[6.80]	(4.50)	[37.7]
Extreme Performance Fluoropolymer Coating	(1.50)	[12.4]	(1.50)	[12.4]

4. For each affected source that achieves compliance with this subpart by using the emission rate with add-on control option in Section 63.3891(c), the operator shall comply with all applicable operating limits pursuant to Section 63.3892. All applicable operating limits shall be established in accordance with the requirements that are specified in Section 63.3967 during the performance tests as required in Section 63.3960.

5. The operator shall comply with all applicable work practice standards specified in Section 63.3893.

6. The operator shall comply with all applicable startup, shutdown, and malfunction procedures and other general compliance requirements pursuant to Sections 63.3900 and 63.3901 of this subpart and 40 CFR 63 Subpart A.

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION J: AIR TOXICS
[40CFR 63 Subpart MMMM 01-02-2004]

7. The operator shall comply with all applicable notification requirements pursuant to Section 63.3910 of this subpart and 40 CFR 63, Subpart A.

8. The operator shall comply with all applicable reporting requirements pursuant to Section 63.3920. All required semi-annual compliance reports, performance test reports, and startup, shutdown, and malfunction reports shall be submitted by the compliance dates specified in Section 63.3920.

9. The operator shall collect and keep records of the data and information pursuant to Sections 63.3930 and 63.3931 of this subpart and 40 CFR 63, Subpart A to demonstrate compliance with all applicable requirements. In addition, all records including data, information, calculations, and any supporting documentation shall be prepared in a format which is acceptable to the AQMD.

10. For each affected source that achieves compliance with this subpart by using the compliant material option in Section 63.3891(a), the operator shall demonstrate the initial compliance and continuous compliance with all applicable emission limitations that are specified in Sections 63.3890, 63.3891, 63.3892, and 63.3893 by the compliance dates pursuant to Sections 63.3940, 63.3941, and 63.3942.

11. For each affected source that achieves compliance with this subpart by using the emission rate without add-on controls option in Section 63.3891(b), the operator shall demonstrate the initial compliance and continuous compliance with all applicable emission limitations that are specified in Sections 63.3890, 63.3891, 63.3892, and 63.3893 by the compliance dates pursuant to Sections 63.3950, 63.3951, and 63.3952.

12. For each affected source that achieves compliance with this subpart by using the emission rate with add-on control option in Section 63.3891(c), the operator shall conduct performance tests and demonstrate initial compliance and continuous compliance with all applicable emission limitations that are specified in Sections 63.3890, 63.3891, 63.3892, and 63.3893 by the compliance dates pursuant to Sections 63.3960, 63.3961, and 63.3963. All performance tests shall be conducted in accordance with the applicable requirements specified in Sections 63.3964, 63.3965, and 63.3966. In addition, the operator shall comply with all applicable requirements for continuous parameter monitoring system installation, operation, and maintenance pursuant to Section 63.3968.

13. Alternative plans, compliance plans, and the construction and operation of new or modified air pollution control equipment that are required by this subpart shall be approved through the AQMD permit system.

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION J: AIR TOXICS
[40CFR 63 Subpart PPPP 04-19-2004]

NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR SURFACE COATING OF PLASTIC PARTS AND PRODUCTS

1. The operator shall comply with all applicable requirements of 40CFR63 Subpart PPPP including those requirements of 40CFR63 Subpart A – General Provisions by the compliance dates that are specified in these subparts.
2. The operator shall comply with the following emission limitations:

   a. New or reconstructed affected source

Affected Source	Section	Emission Limit
New general use	63.4490(a)(1)	0.16 kg organic HAP per kg coating solids used
New automotive lamp coating	63.4490(a)(2)	0.26 kg organic HAP per kg coating solids used
New TPO	63.4490(a)(3)	0.22 kg organic HAP per kg coating solids used
New assembled on-road vehicle coating	63.4490(a)(4)	1.34 kg organic HAP per kg coating solids used

   b. Existing affected source

Affected Source	Section	Emission Limit
Existing general use	63.4490(b)(1)	0.16 kg organic HAP per kg coating solids used
Existing automotive lamp coating	63.4490(b)(2)	0.45 kg organic HAP per kg coating solids used
Existing TPO	63.4490(b)(3)	0.26 kg organic HAP per kg coating solids used
Existing assembled on-road vehicle coating	63.4490(b)(4)	1.34 kg organic HAP per kg coating solids used

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION J: AIR TOXICS
[40CFR 63 Subpart PPPP 04-19-2004]

3. The operator shall comply with all applicable work practice standards requirements pursuant to Section 63.4493.
4. For compliance requirements for the compliant material options, the operator shall comply with all applicable requirements that are specified in Sections 63.4540-63.4542.
5. For compliance requirements for the emission rate without add-on controls option, the operator shall comply with all applicable requirements that are specified in Sections 63.4550-63.4552.
6. For the emission rate compliance requirements with add-on controls option, the operator shall comply with all applicable requirements that are specified in Section 63.4560-63.4561 and 63.4563-63.4568.
7. The operator shall comply with all applicable general requirements pursuant to Section 63.4500.
8. The operator shall comply with all applicable notification requirements that are specified in Section 63.4510.
9. The operator shall comply with all applicable reporting requirements that are specified in Section 63.4520.
10. The operator shall keep all required records pursuant to Section 63.4530 and 63.4531 of this subpart and 40CFR63 Subpart A to demonstrate compliance with all applicable requirements. In addition, all records including data, calculations, and any supporting documentation shall be prepared in a format which is acceptable to the AQMD.
11. Alternative plans, compliance plans, and the construction and operation of new or modified air pollution control equipment that are required by this subpart shall be approved through the AQMD permit system.

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]

2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

   (B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]

4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:

   (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.

   (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.

   (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:

   (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or

   (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

   Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:

   (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;

   (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;

   (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and

   (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]

15. Nothing in this permit or in any permit shield can alter or affect:

    (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;

    (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;

    (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;

    (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;

    (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and

    (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]

16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

EMERGENCY PROVISIONS

17. An emergency[1] constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:

    (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:

        (1) An emergency occurred and the operator can identify the cause(s) of the emergency;

        (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;

        (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,

        (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and

    (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]

18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

---

1 "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:

    (A) The date, place as defined in the Title V permit, and time of sampling or measurements;

    (B) The date(s) analyses were performed;

    (C) The company or entity that performed the analyses;

    (D) The analytical techniques or methods used;

    (E) The results of such analyses; and

    (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]

20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]

21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:

    (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

(B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.

(C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.

(D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]

23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]

24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:

(A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

(B) The compliance status during the reporting period;

(C) Whether compliance was continuous or intermittent;

(D) The method(s) used to determine compliance over the reporting period and currently, and

(E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1107	1-6-2006	Non federally enforceable
RULE 1107	11-9-2001	Federally enforceable
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	7-13-2007	Non federally enforceable
RULE 1115	5-12-1995	Federally enforceable
RULE 1132	3-5-2004	Federally enforceable
RULE 1132	5-7-2004	Non federally enforceable
RULE 1136	6-14-1996	Federally enforceable
RULE 1137	2-1-2002	Federally enforceable
RULE 1147	12-5-2008	Non federally enforceable
RULE 1162	11-17-2000	Federally enforceable
RULE 1162	7-8-2005	Non federally enforceable
RULE 1168	1-7-2005	Federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	12-7-1990	Non federally enforceable

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 1401	5-3-2002	Non federally enforceable
RULE 1401	8-13-1999	Non federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	6-1-2007	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	3-16-2001	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	3-16-2001	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-5-2009	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 480	10-7-1977	Federally enforceable
RULE 481	1-11-2002	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 63 Subpart MMMM	1-2-2004	Federally enforceable
40CFR 63 Subpart MMMM	12-22-2006	Federally enforceable
40CFR 63 Subpart PPPP	12-22-2006	Federally enforceable
40CFR 63 Subpart PPPP	4-19-2004	Federally enforceable
40CFR 82 Subpart B	7-14-1992	Federally enforceable
40CFR 82 Subpart F	5-14-1993	Federally enforceable

FACILITY PERMIT TO OPERATE
MVP RV, INC

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
40CFR Part 64	10-22-1997	Federally enforceable

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN PERMIT PURSUANT TO RULE 219

NONE

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates, cont.								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 01-06-2006]

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1107 11-09-2001]

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates, cont.								
Coating	**Air-Dried**				**Baked**			
	gm/l		**lb/gal**		**gm/l**		**lb/gal**	
	Current	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**	**Current**	**7/1/07**
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-08-1996]

(1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.

(2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers	350						
Clear Wood Finishes							
Varnish	350						
Sanding Sealers	350						
Lacquer	680		550			275	
Concrete-Curing Compounds	350						
Dry-Fog Coatings	400						
Fire-proofing Exterior Coatings	350	450		350			
Fire-Retardant Coatings							
Clear	650						
Pigmented	350						
Flats	250				100		50
Graphic Arts (Sign) Coatings	500						

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-08-1996]

Industrial Maintenance Primers and Topcoats							
Alkyds	420						
Catalyzed Epoxy	420						
Bituminous Coatings	420						
Materials							
Inorganic Polymers	420						
Vinyl Chloride Polymers	420						
Chlorinated Rubber	420						
Acrylic Polymers	420						
Urethane Polymers	420						
Silicones	420						
Unique Vehicles	420						
Japans/Faux Finishing	350	700		350			
Coatings							
Magnesite Cement Coatings	600			450			
Mastic Coatings	300						
Metallic Pigmented Coatings	500						
Multi-Color Coatings	420		250				
Pigmented Lacquer	680		550			275	
Pre-Treatment Wash Primers	780						
Primers, Sealers, and Undercoaters	350						
Quick-Dry Enamels	400						
Roof Coatings	300						
Shellac							
Clear	730						
Pigmented	550						
Stains	350						
Swimming Pool Coatings							
Repair	650						
Other	340						
Traffic Coatings	250		150				
Waterproofing Sealers	400						
Wood Preservatives							
Below-Ground	350						
Other	350						

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 07-13-2007]

(1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.

(2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 07-13-2007]
TABLE OF STANDARDS
VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Bond Breakers	350							
Clear Wood Finishes	350					275		
Varnish	350					275		
Sanding Sealers	350					275		
Lacquer	680	550			275			
Clear Brushing Lacquer	680				275			
Concrete-Curing Compounds	350						100	
Concrete-Curing Compounds For Roadways and Bridges**	350							
Dry-Fog Coatings	400						150	
Fire-Proofing Exterior Coatings	450	350						
Fire-Retardant Coatings***								
Clear	650							
Pigmented	350							
Flats	250	100						50
Floor Coatings	420		100			50		
Graphic Arts (Sign) Coatings	500							
Industrial Maintenance (IM) Coatings	420			250		100		
High Temperature IM Coatings			420					
Zinc-Rich IM Primers	420		340			100		
Japans/Faux Finishing Coatings	700	350						
Magnesite Cement Coatings	600	450						
Mastic Coatings	300							
Metallic Pigmented Coatings	500							
Multi-Color Coatings	420	250						
Nonflat Coatings	250		150			50		

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 07-13-2007]

COATING CATEGORY	Ceiling Limit*	Current Limit	Effective Date					
			1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Nonflat High Gloss	250		150				50	
Pigmented Lacquer	680	550			275			
Pre-Treatment Wash Primers	780		420					
Primers, Sealers, and Undercoaters	350		200			100		
Quick-Dry Enamels	400		250			150	50	
Quick-Dry Primers, Sealers, and Undercoaters	350		200			100		
Recycled Coatings			250					
Roof Coatings	300		250		50			
Roof Coatings, Aluminum	500				100			
Roof Primers, Bituminous	350		350					
Rust Preventative Coatings	420		400			100		
Shellac								
Clear	730							
Pigmented	550							
Specialty Primers	350					250	100	
Stains	350		250				100	
Stains, Interior	250							
Swimming Pool Coatings								
Repair	650		340					
Other	340							
Traffic Coatings	250	150					100	
Waterproofing Sealers	400		250			100		
Waterproofing Concrete/Masonry Sealers	400					100		
Wood Preservatives								
Below-Ground	350							
Other	350							

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

** Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

*** The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 07-13-2007]

TABLE OF STANDARDS (cont.)
VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1115 05-12-1995]

Except as otherwise provided in Rule 1115

(1) The operator shall not apply any electrophoretic primer, in any motor vehicle application line, which has a VOC content in excess of 145 grams per liter (1.2 lb/gal) of coating, less water and less exempt compounds.

(2) The operator shall not apply any final repair coating, in any motor vehicle application line, which has a VOC content in excess of 580 grams per liter (4.8 lb/gal) of coating, less water and less exempt compounds.

(3) The operator shall not apply any spray primer, primer surfacer and/or topcoat in any motor vehicle application line that result in VOC emissions in excess of 1.80 kilograms per liter (15.0 lb/gal) of applied solids.

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1136 06-14-1996]

Except as otherwise provided in Rule 1136

(a) The operator shall not apply any coating to a wood product which has a VOC content, including any VOC-containing material added to the original coating supplied by the manufacturer, which exceeds the applicable limit specified below:

(1)

VOC LIMITS
Grams Per Liter (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

COATING	Current Limit I	Current Limit II	On and After 7/1/2005
Clear Sealers	550 (4.6) [1.39]	680 (5.7) [3.36]	275 (2.3) [0.36]
Clear Topcoat	550 (4.6) [1.37]	275 (2.3) [0.35]	275 (2.3) [0.35]
Pigmented Primers, Sealers & Undercoats	550 (4.6) [1.06]	600 (5.0) [1.08]	275 (2.3) [0.21]
Pigmented Topcoats	550 (4.6) [1.10]	275 (2.3) [0.25]	275 (2.3) [0.25]

The operator shall use coatings on a wood product that comply with either all VOC limits in column I or all VOC limits in column II. The operator that applies a primer, sealer or undercoat, but not a topcoat, to a wood product, shall be subject to column I for that wood product.

(2) Notwithstanding the requirements of clause (a)(1), an operator that applies a topcoat and a primer, sealer or undercoat to a shutter may, until July 1, 2005, choose to comply with the VOC limits specified below for that shutter:

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1136 06-14-1996]

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

COATING	
Clear Sealers	275 (2.3) [0.36]
Clear Topcoat	680 (5.7) [2.99]
Pigmented Primers, Sealers & Undercoats	275 (2.3) [0.33]
Pigmented Topcoats	600 (5.0) [1.38]

(3)

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

COATING	Current Limit	On and After 7/1/2005
Barrier Coat - Plastic Components	760 (6.3) [3.9]	275 (2.3) [0.28]
Composite Wood Edge Filler	550 (4.6) [1.15]	275 (2.3) [0.31]
Extreme Performance Coatings	420 (3.5) [0.51]	275 (2.3) [0.33]
Fillers	500 (4.2) [0.66]	275 (2.3) [0.18]
High-Solid Stains	550 (4.6) [1.23]	350 (2.9) [0.42]
Inks	500 (4.2) [0.96]	500 (4.2) [0.96]
Mold-Seal Coatings	750 (6.3) [4.2]	750 (6.3) [4.2]
Multi-Colored Coatings	685 (5.7) [2.6]	275 (2.3) [0.33]

VOC LIMITS

Grams Per Liter (lb/gal) of Material

COATING	Current Limit	On and After 7/1/2005
Low-Solids Barrier Coat - Plastic Components	760 (6.3)	120 (1.0)
Low-Solid Stains, Toners, and Washcoats	480 (4.0)	120 (1.0)

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1136 06-14-1996]

Any coating subject to this rule that meets any of the three VOC limit formats (grams per liter, lb/gal, or lbs VOC/lb of solids) is in compliance with this subparagraph.

(4) The VOC limit for japan coatings is 700 grams per liter of coatings, less water and exempt compounds, as applied.

(b) A person shall not use a stripper on wood products unless:

(1) it contains less than 350 grams of VOC per liter of material; or

(2) the VOC composite vapor pressure is 2 mm Hg (0.04 psia) or less at 20°C (68°F).

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1162 11-17-2000]

The operator shall not use a polyester resin material in a polyester resin operation which has a monomer content in excess of the limits specified in the Table below.

Polyester Resin Materials	Monomer Content in Polyester Resin Materials as Applied (By Weight Percent)
General Purpose Polyester Resin	35
Corrosion-Resistant	48
Fire Retardant	42
High Strength	48
Clear Gel Coat	50
Pigmented Gel Coat	45

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1162 07-08-2005]

The operator shall not use polyester resin material in an open molding system, which has a monomer content in excess of the limits specified in the following Table.

Polyester Resin Materials	Monomer Percentage by Weight as Applied	
	Prior to 11-09-2001	Current Limits
Clear Gel Coat	50	-
For Marble Resins	-	40
For Other Resins	-	44
Pigmented Gel Coat	45	-
White and Off White	-	30
Non-White	-	37
Primer	-	28
Specialty Gel Coats	-	48
General Purpose Resin	35	-
Marble Resins	-	10 or (32 % as supplied, no fillers)
Solid Surface Resins	-	17
Tub/Shower Resins	-	24 or (35 % as supplied, no fillers)
Lamination Resins	-	31 or (35 % as supplied, no fillers)
Others	-	35
Fire Retardant Resin	42	38
Corrosion Resistant Resin	48	48
High Strength Resin	48	40

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 01-07-2005]

(1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.

(2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

Architectural Applications	Current VOC Limit*
Indoor Carpet Adhesives	50
Carpet Pad Adhesives	50
Outdoor Carpet Adhesives	150
Wood Flooring Adhesive	100
Rubber Floor Adhesives	60
Subfloor Adhesives	50
Ceramic Tile Adhesives	65
VCT and Asphalt Tile Adhesives	50
Dry Wall and Panel Adhesives	50
Cove Base Adhesives	50
Multipurpose Construction Adhesives	70
Structural Glazing Adhesives	100
Single Ply Roof Membrane Adhesives	250

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 01-07-2005]

Specialty Applications	VOC Limits and Effective Dates**			
	Current VOC Limit*	1-1-05	7-1-05	1-1-07
PVC Welding	510			
CPVC Welding	490			
ABS Welding	400		325	
Plastic Cement Welding	350	250		
Adhesive Primer for Plastic	650		550	
Computer Diskette Manufacturing	350			
Contact Adhesive	80			
Special Purpose Contact Adhesive	250			
Tire Retread	100			
Adhesive Primer for Traffic Marking Tape	150			
Structural Wood Member Adhesive	140			
Sheet Applied Rubber Lining Operations	850			
Top and Trim Adhesive	540			250

** The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 01-07-2005]

For adhesives, adhesive bonding primers, or any other primer not regulated by the above two tables and applied to the following substrates, the following limits shall apply:

Substrate Specific Applications	Current VOC Limit*
Metal to Metal	30
Plastic Foams	50
Porous Material (except wood)	50
Wood	30
Fiberglass	80

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

Sealants	Current VOC Limit*
Architectural	250
Marine Deck	760
Nonmembrane Roof	300
Roadway	250
Single-Ply Roof Membrane	450
Other	420

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 01-07-2005]

Sealant Primers	**Current VOC Limit***
Architectural	
Non Porous	250
Porous	775
Modified Bituminous	500
Marine Deck	760
Other	750

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	**VOC g/l (lb/gal)**	**VOC g/l (lb/gal)**
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	**VOC g/l (lb/gal)**	**VOC g/l (lb/gal)**
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	**VOC g/l (lb/gal)**	**VOC g/l (lb/gal)**
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

FACILITY PERMIT TO OPERATE
MVP RV, INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100