9. This tank shall not be required to de-gas before commencing cleaning activities. All other applicable requirements shall be complied with before, during, and after tank cleaning activities. [District Rule 4623] Federally Enforceable Through Title V Permit

10. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

11. Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit

12. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

13. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-148-1 **EXPIRATION DATE:** 08/31/2016

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
147 HP MINNEAPOLIS MOLINE MODEL HD800-6A FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
2. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
4. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
6. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
9. Emissions from the engine shall not exceed any of the following limits: 50 ppmv-NOx @ 15% O2, 2,000 ppmv-CO @ 15% O2 and 250 ppmv-VOC @ 15% O2. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
10. This unit shall be fired only on gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, permittee shall monitor and record, on a monthly basis, the catalyst inlet and outlet temperatures. [District Rule 4702] Federally Enforceable Through Title V Permit
12. The acceptable catalyst temperature differential shall be established by source testing this unit or other representative units as approved by the District. The normal range/level shall be any temperature increase across the catalyst unless compliance with applicable NOx and CO emissions limits have been demonstrated through source testing at a similar temperature drop. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Upon recommencing operation, permittee shall maintain records of the date and time of temperature measurements and the measured temperatures. The records shall also include a description of any corrective action taken to maintain the temperature differential at the acceptable level. [District Rule 4702] Federally Enforceable Through Title V Permit

14. If the catalyst temperature differential is outside of the normal range/level, the permittee shall notify the District and take corrective action (i.e. temperature differential returned to normal range/level) with one (1) hour of detection. If the catalyst temperature differential rate is not immediately corrected, the permittee shall conduct a source test within 60 days, to demonstrate compliance with the applicable emissions limits at the new temperature differential. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

15. The permittee shall update the I & M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I & M plan and must submit an updated I & M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I & M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I & M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

16. Upon recommencing operation the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

17. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

18. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701and 4702] Federally Enforceable Through Title V Permit

20. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

21. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

25. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

26. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

27. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

28. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

29. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701 and 4702] Federally Enforceable Through Title V Permit

30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

32. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rules 4701 and 4702. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-149-1 **EXPIRATION DATE:** 08/31/2016

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
147 HP MINNEAPOLIS MOLINE MODEL HD800-6A FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
2. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
4. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
6. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
9. Emissions from the engine shall not exceed any of the following limits: 50 ppmv-NOx @ 15% O2, 2,000 ppmv-CO @ 15% O2 and 250 ppmv-VOC @ 15% O2. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
10. This unit shall be fired only on gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, permittee shall monitor and record, on a monthly basis, the catalyst inlet and outlet temperatures. [District Rule 4702] Federally Enforceable Through Title V Permit
12. The acceptable catalyst temperature differential shall be established by source testing this unit or other representative units as approved by the District. The normal range/level shall be any temperature increase across the catalyst unless compliance with applicable NOx and CO emissions limits have been demonstrated through source testing at a similar temperature drop. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Upon recommencing operation, permittee shall maintain records of the date and time of temperature measurements and the measured temperatures. The records shall also include a description of any corrective action taken to maintain the temperature differential at the acceptable level. [District Rule 4702] Federally Enforceable Through Title V Permit

14. If the catalyst temperature differential is outside of the normal range/level, the permittee shall notify the District and take corrective action (i.e. temperature differential returned to normal range/level) with one (1) hour of detection. If the catalyst temperature differential rate is not immediately corrected, the permittee shall conduct a source test within 60 days, to demonstrate compliance with the applicable emissions limits at the new temperature differential. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

15. The permittee shall update the I & M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I & M plan and must submit an updated I & M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I & M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I & M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

16. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

17. If the NOX or CO concentrations corrected to 15% $O2_{,}$ as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following I hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

18. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701and 4702] Federally Enforceable Through Title V Permit

20. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

21. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

25. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

26. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

27. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

28. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rules 4701, 6.3.1 and 4702] Federally Enforceable Through Title V Permit

29. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701 and 4702] Federally Enforceable Through Title V Permit

30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

32. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rules 4701 and 4702. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-150-1 **EXPIRATION DATE:** 08/31/2016

SECTION: NE20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
147 HP MINNEAPOLIS MOLINE MODEL HD800-6A FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
2. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
4. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
6. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
9. Emissions from the engine shall not exceed any of the following limits: 50 ppmv-NOx @ 15% O2, 2,000 ppmv-CO @ 15% O2 and 250 ppmv-VOC @ 15% O2. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
10. This unit shall be fired only on natural gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, permittee shall monitor and record, on a monthly basis, the catalyst inlet and outlet temperatures. [District Rule 4702] Federally Enforceable Through Title V Permit
12. The acceptable catalyst temperature differential shall be established by source testing this unit or other representative units as approved by the District. The normal range/level shall be any temperature increase across the catalyst unless compliance with applicable NOx and CO emissions limits have been demonstrated through source testing at a similar temperature drop. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Upon recommencing operation, permittee shall maintain records of the date and time of temperature measurements and the measured temperatures. The records shall also include a description of any corrective action taken to maintain the temperature differential at the acceptable level. [District Rule 4702] Federally Enforceable Through Title V Permit

14. If the catalyst temperature differential is outside of the normal range/level, the permittee shall notify the District and take corrective action (i.e. temperature differential returned to normal range/level) with one (1) hour of detection. If the catalyst temperature differential rate is not immediately corrected, the permittee shall conduct a source test within 60 days, to demonstrate compliance with the applicable emissions limits at the new temperature differential. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

15. The permittee shall update the I & M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I & M plan and must submit an updated I & M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I & M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I & M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

16. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

17. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

18. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701and 4702] Federally Enforceable Through Title V Permit

20. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

21. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

25. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

26. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

27. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

28. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rule 4701, 6.3.1 and 4702] Federally Enforceable Through Title V Permit

29. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701 and 4702] Federally Enforceable Through Title V Permit

30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

32. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rules 4701 and 4702. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-151-1 **EXPIRATION DATE:** 08/31/2016

SECTION: SE20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
135 BHP WAUKESHA MODEL 817 FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
2. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
4. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
6. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
8. Emissions from the engine shall not exceed any of the following limits: 50 ppmv NOx @ 15% O2 (equivalent to 0.7 g/bhp-hr), 2,000 ppmv CO @ 15% O2 (equivalent to 17.0 g/bhp-hr), 250 ppmv VOC @ 15% O2 (equivalent to 1.2 g/bhp-hr), and 0.063 g-PM10/bhp-hr. [District NSR Rule and 4702] Federally Enforceable Through Title V Permit
9. This unit shall be fired only on natural gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
10. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rule 4702] Federally Enforceable Through Title V Permit

12. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rule 4702] Federally Enforceable Through Title V Permit

13. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rule 4702] Federally Enforceable Through Title V Permit

14. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

15. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

19. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

20. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

21. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

22. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

23. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081 and 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

25. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rule 4702] Federally Enforceable Through Title V Permit

26. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

27. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rule 4702. [District Rule 4702] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-152-1 **EXPIRATION DATE:** 08/31/2016

SECTION: SE20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
2000 BBL PRODUCED WATER TANK WITH VAPOR CONTROL SYSTEM UNDER PERMIT S-1216-142 (STEVENS LEASE)

PERMIT UNIT REQUIREMENTS

1. The fixed-roof storage tank shall be vented to vapor control system described in PTO S-1216-142. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be maintained in a leak-free condition and equipped with an APCO approved vapor recovery system consisting of a closed system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in a leak-free condition. The VOC control device shall be one of the following: a condensation or vapor recovery system that connects to a gas processing plant, a field gas pipeline, a pipeline distributing PUC quality gas for sale, an injection well for disposal of vapors, or a VOC control device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to relieve pressure at a pressure level higher than that required to actuate compressor. The P/V valve shall be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
6. The water level in the water seal hatch shall be kept in accordance with the manufacturer's specifications, maintaining a leak-free condition. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Operator shall inspect and replenish the water level in the water seal hatch on a daily basis. Records of the water level shall be maintained. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The tank shall comply with the voluntary inspection and maintenance program requirements of conditions 99 through 107 of the Facility-Wide Permit S-1216-0-1. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit

11. This tank shall be degassed before commencing interior cleaning by following one of the following options: 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit

12. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit

13. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit

14. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

15. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit

16. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

17. Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit

18. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit

19. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit

20. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

21. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

23. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-153-1 **EXPIRATION DATE:** 08/31/2016

EQUIPMENT DESCRIPTION:
2000 BBL PRODUCED WATER TANK WITH VAPOR CONTROL UNDER PERMIT S-1216-142 (STEVENS LEASE)

PERMIT UNIT REQUIREMENTS

1. The fixed-roof storage tank shall be vented to vapor control system described in PTO S-1216-142. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be maintained in a leak-free condition and equipped with an APCO approved vapor recovery system consisting of a closed system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in a leak-free condition. The VOC control device shall be one of the following: a condensation or vapor recovery system that connects to a gas processing plant, a field gas pipeline, a pipeline distributing PUC quality gas for sale, an injection well for disposal of vapors, or a VOC control device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping valves and fittings shall be constructed and maintained in a leak-free condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to relieve pressure at a pressure level higher than that required to actuate compressor. The P/V valve shall be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
6. The water level in the water seal hatch shall be kept in accordance with the manufacturer's specifications, maintaining a leak-free condition. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Operator shall inspect and replenish the water level in the water seal hatch on a daily basis. Records of the water level shall be maintained. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit
9. The tank shall comply with the voluntary inspection and maintenance program requirements of conditions 99 through 107 of the Facility-Wide Permit S-1216-0-1. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit

11. This tank shall be degassed before commencing interior cleaning by following one of the following options: 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit

12. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit

13. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit

14. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

15. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit

16. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

17. Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit

18. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit

19. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit

20. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

21. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

23. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-154-1 **EXPIRATION DATE:** 08/31/2016

EQUIPMENT DESCRIPTION:
1000 BBL PRODUCED WATER TANK #508 WITH VAPOR CONTROL UNDER PERMIT S-1216-142 (STEVENS LEASE)

PERMIT UNIT REQUIREMENTS

1. The fixed-roof storage tank shall be vented to vapor control system described in PTO# S-1216-142. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be maintained in a leak-free condition and equipped with an APCO approved vapor recovery system consisting of a closed system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in a leak-free condition. The VOC control device shall be one of the following: a condensation or vapor recovery system that connects to a gas processing plant, a field gas pipeline, a pipeline distributing PUC quality gas for sale, an injection well for disposal of vapors, or a VOC control device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to relieve pressure at a pressure level higher than that required to actuate compressor. The P/V valve shall be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
6. The water level in the water seal hatch shall be kept in accordance with the manufacturer's specifications, maintaining a leak-free condition. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Operator shall inspect and replenish the water level in the water seal hatch on a daily basis. Records of the water level shall be maintained. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623] Federally Enforceable Through Title V Permit
9. The tank shall comply with the voluntary inspection and maintenance program requirements of conditions 99 through 107 of the Facility-Wide Permit S-1216-0-1. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit

11. This tank shall be degassed before commencing interior cleaning by following one of the following options: 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less, or 2) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit

12. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit

13. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623] Federally Enforceable Through Title V Permit

14. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

15. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid having a TVP of 0.5 psia or greater is placed, held, or stored in this tank. [District Rule 4623] Federally Enforceable Through Title V Permit

16. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit

17. Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit

18. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623] Federally Enforceable Through Title V Permit

19. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623] Federally Enforceable Through Title V Permit

20. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

21. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

23. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-155-1 **EXPIRATION DATE:** 08/31/2016

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
10,000 BBL FIXED ROOF PETROLEUM PRODUCTION TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to the VOC vapor control system listed on S-1216-142. VOC vapors from tank shall vent only to the vapor control system. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
2. Storage tank pressure-vacuum cap(s) shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
3. Storage tank pressure-vacuum cap(s) shall be leak-free (except for inbreathing) during normal operation. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District NSR and District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District NSR and District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
7. VOC fugitive emissions from the components in both gas and liquid service on this tank shall not exceed 0.2 lb-VOC/day [District NSR Rule] Federally Enforceable Through Title V Permit
8. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed [District NSR Rule] Federally Enforceable Through Title V Permit
9. Except as otherwise provided in this permit, the operator shall ensure that the VOC vapor control system is functional and is operating as designed at all times. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Any component found to be leaking is in violation of the District's NSR Rule, even if it is under the voluntary inspection and maintenance program. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The tank shall be maintained in a leak-free condition and equipped with an APCO approved vapor recovery system consisting of a closed system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in a leak-free condition. The VOC control device shall be one of the following: a condensation or vapor recovery system that connects to a gas processing plant, a field gas pipeline, a pipeline distributing PUC quality gas for sale, an injection well for disposal of vapors, or a VOC control device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit

12. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623] Federally Enforceable Through Title V Permit

13. The tank shall comply with the voluntary inspection and maintenance program requirements of conditions 99 through 107 of the Facility-Wide Permit S-1216-0-1. [District Rule 4623] Federally Enforceable Through Title V Permit

14. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

15. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water. or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

16. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

17. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

18. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

19. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623, 5.7] Federally Enforceable Through Title V Permit

25. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-156-1 **EXPIRATION DATE:** 08/31/2016

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF PETROLEUM PRODUCTION TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to the VOC vapor control system listed on S-1216-142. VOC vapors from tank shall vent only to the vapor control system. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
2. Storage tank pressure-vacuum cap(s) shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
3. Storage tank pressure-vacuum cap(s) shall be leak-free (except for inbreathing) during normal operation. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District NSR and District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District NSR and District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
7. VOC fugitive emissions from the components in both gas and liquid service on this tank shall not exceed 0.2 lb-VOC/day [District NSR Rule] Federally Enforceable Through Title V Permit
8. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed [District NSR Rule] Federally Enforceable Through Title V Permit
9. Except as otherwise provided in this permit, the operator shall ensure that the VOC vapor control system is functional and is operating as designed at all times. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Any component found to be leaking is in violation of the District's NSR Rule, even if it is under the voluntary inspection and maintenance program. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The tank shall be maintained in a leak-free condition and equipped with an APCO approved vapor recovery system consisting of a closed system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in a leak-free condition. The VOC control device shall be one of the following: a condensation or vapor recovery system that connects to a gas processing plant, a field gas pipeline, a pipeline distributing PUC quality gas for sale, an injection well for disposal of vapors, or a VOC control device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit

12. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4623] Federally Enforceable Through Title V Permit

13. The tank shall comply with the voluntary inspection and maintenance program requirements of conditions 99 through 107 of the Facility-Wide Permit S-1216-0-1. [District Rule 4623] Federally Enforceable Through Title V Permit

14. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

15. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water. or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

16. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

17. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

18. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

19. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623, 5.7] Federally Enforceable Through Title V Permit

25. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

Attachment A

Detailed Facility Printout

Detailed Facility Report

For Facility=1216 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

OCCIDENTAL OF ELK HILLS INC
LIGHT OIL WESTERN

FAC # **S 1216**
STATUS: **A**
TELEPHONE:

TYPE: **TitleV**
TOXIC ID: **50184**

EXPIRE ON: 08/31/2016
AREA: 81 /
INSP. DATE: 11/12

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1216-1-2	5,250 gallon storage	3020-05 B	1	93.00	93.00	A	125 BBL FIXED ROOF WASH TANK SERVED BY A PRESSURE RELIEF DEVICE (MAYS LEASE)
S-1216-2-2	42,000 gallon storage	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY A PRESSURE RELIEF DEVICE #13382 (MAYS LEASE)
S-1216-3-2	42,000 gallon storage	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY A PRESSURE RELIEF DEVICE #13381 (MAYS LEASE)
S-1216-7-2	21,000 gallon storage	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF WASH TANK SERVED BY A PRESSURE RELIEF DEVICE (TAFT LEASE)
S-1216-8-2	84,000 gallon storage	3020-05 D	1	185.00	185.00	A	2,000 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY A PRESSURE RELIEF DEVICE #10752 (TAFT LEASE)
S-1216-10-2	7,560 gallon storage	3020-05 B	1	93.00	93.00	A	180 BBL FIXED ROOF WASH TANK SERVED BY A PRESSURE RELIEF DEVICE (AIRPORT LEASE)
S-1216-11-2	84,000 gallon storage	3020-05 D	1	185.00	185.00	A	2,000 BBL FIXED ROOF STORAGE TANK SERVED BY A PRESSURE RELIEF DEVICE #13303 (AIRPORT LEASE)
S-1216-20-2	21,000 gallon storage	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF WASH TANK SERVED BY A PRESSURE RELIEF DEVICE (BALBOA LEASE)
S-1216-21-2	21,000 gallon storage	3020-05 C	1	135.00	135.00	A	500 BBL STOCK TANK SERVED BY A PRESSURE RELIEF DEVICE, #5384 (BALBOA LEASE)
S-1216-22-2	20,580 gallon storage	3020-05 C	1	135.00	135.00	A	490 BBL FIXED ROOF WASH TANK SERVED BY A PRESSURE/VACUUM RELIEF VENT VALVE (MAYS LEASE)
S-1216-42-1	21,000 gallon storage	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (#.05GF17) SERVED BY VAPOR CONTROL SYSTEM INCLUDING COMPRESSOR(S) AND PIPING SHARED WITH S-1216-43
S-1216-43-1	21,000 gallon storage	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (#.05GF8) SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-42 (KING LEASE)
S-1216-44-1	84,000 gallon storage	3020-05 D	1	185.00	185.00	A	2,000 BBL FIXED-ROOF PETROLEUM WASH TANK (#08002M06E) SERVED BY A VAPOR RECOVERY SYSTEM (LITTLE SIX LEASE)
S-1216-45-1	21,000 gallon storage	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF PETROLEUM WASH TANK SERVED BY PRESSURE-VACUUM VENTS (SECTION 14 TANK SETTING, BUENA VISTA HILLS)
S-1216-46-1	42,000 gallon storage	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED-ROOF PETROLEUM SHIPPING TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON S-1216-44 (LITTLE SIX LEASE)

Detailed Facility Report

For Facility=1216 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1216-47-1	12,600 gallon storage	3020-05 B	1	93.00	93.00	A	300 BBL FIXED ROOF PETROLEUM WASH TANK SERVED BY A PRESSURE-VACUUM VENT (SECTION 10 TANK SETTING, BUENA VISTA HILLS)
S-1216-48-1	8,820 gallon storage	3020-05 B	1	93.00	93.00	A	210 BBL FIXED ROOF SHIPPING TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-49, S-1216-50, S-1216-59, S-1216-63, AND S-1216-86 (SEC 26 BUENA VISTA LEASE)
S-1216-49-1	8,820 gallon storage	3020-05 B	1	93.00	93.00	A	210 BBL FIXED ROOF SHIPPING TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1216-48 (SEC 26 FEE LEASE)
S-1216-50-1	31,500 gallon storage	3020-05 C	1	135.00	135.00	A	750 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1216-48 (#REW 31, SECTION 8 LEASE)
S-1216-51-1	210,000 gallon storage	3020-05 E	1	246.00	246.00	A	5,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #5GF6 (SECTION 8 LEASE)
S-1216-52-1	31,500 gallon storage	3020-05 C	1	135.00	135.00	A	750 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (SECTION 8 LEASE)
S-1216-53-1	42,000 gallon storage	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #RECYCLE 3 (SECTION 8 LEASE)
S-1216-54-1	21,000 gallon storage	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK SERVED BY A VAPOR RECOVERY SYSTEM (SECTION 8 LEASE)
S-1216-55-1	8,400 gallon storage	3020-05 B	1	93.00	93.00	A	200 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (#02GF1, SECTION 10 TANK SETTING, BUENA VISTA HILLS) SERVED BY A PRESSURE-VACUUM VENT VALVE
S-1216-56-1	21,000 gallons	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (#5GF14, SECTION 14, BUENA VISTA HILLS) SERVED BY A PRESSURE-VACUUM VENT VALVE
S-1216-57-1	42,000 gallon storage	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #1GF34 (SECTION 16A LEASE)
S-1216-58-1	42,000 gallon storage	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #1GF35 (SECTION 16A LEASE)
S-1216-59-1	8,820 gallon storage	3020-05 B	1	93.00	93.00	A	210 BBL FIXED ROOF SHIPPING TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-48 (SECTION 26 BUENA VISTA LEASE)
S-1216-60-1	21,000 gallon storage	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY A VAPOR CONTROL SYSTEM WITH A 25 HP COMPRESSOR SHARED WITH S-1216-61 AND '-62 (B.V. HILLS OILFIELD LEASE)
S-1216-61-1	21,000 gallon storage	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-60 (B.V. HILLS OILFIELD LEASE)

Detailed Facility Report

For Facility=1216 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1216-62-1	42,000 gallon storage	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED ROOF CRUDE OIL WASH TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-60 (B.V. HILLS OILFIELD LEASE)
S-1216-63-1	8,820 gallon storage	3020-05 B	1	93.00	93.00	A	210 BBL FIXED ROOF SHIPPING TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-48 (SEC 26 BUENA VISTA LEASE)
S-1216-64-3	126,000 gallon storage	3020-05 E	1	246.00	246.00	A	3,000 BBL FIXED ROOF WASH TANK SERVED BY A VAPOR CONTROL SYSTEM SHARED WITH S-1216-66, '-72, '-73, '-74 &'-75
S-1216-66-1	126,000 gallon storage	3020-05 E	1	246.00	246.00	A	3,000 BBL WELDED, FIXED ROOF PRODUCED WATER TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1216-64 (ASPHALTO FEE)
S-1216-67-1	225 bhp IC engine	3020-10 C	1	240.00	240.00	A	225 BHP CATERPILLAR MODEL G342NA NATURAL GAS-FIRED IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) AND AIR/FUEL RATIO CONTROLLER POWERING A GAS COMPRESSOR (NON-COMPLIANT DORMANT EMISSIONS UNIT)
S-1216-68-1	0.75 MMBtu/hr burner	3020-02 D	1	314.00	314.00	A	GLYCOL GAS DEHYDRATION OPERATION INCLUDING GLYCOL REBOILER WITH 0.75 MMBTU/HR AFTERBURNER
S-1216-69-1	Flare Rating > 15 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	EMERGENCY GAS PLANT FLARE INCLUDING: AUTOMATIC ELECTRONIC IGNITER AND GAS LIQUID SEPARATOR
S-1216-70-1	325 bhp IC engine	3020-10 C	1	240.00	240.00	A	325 HP CATERPILLAR MODEL 3406 TA NATURAL GAS-FIRED IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION AND AUTOMATIC AIR/FUEL RATIO CONTROLLER POWERING A GAS COMPRESSOR
S-1216-71-1	1478 bhp	3020-10 F	1	749.00	749.00	A	1478 HP WAUKESHA MODEL L7042GSI NATURAL GAS-FIRED IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION AND AUTOMATIC AIR/FUEL RATIO CONTROLLER POWERING A GAS COMPRESSOR
S-1216-72-1	672,000 gallon	3020-05 F	1	301.00	301.00	A	16,000 BBL FIXED ROOF PRODUCTION TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON WITH S-1216-64
S-1216-73-1	63,000 gallon	3020-05 D	1	185.00	185.00	A	1,500 BBL FIXED ROOF PRODUCTION TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON S-1216-64
S-1216-75-1	63,000 gallon	3020-05 D	1	185.00	185.00	A	1,500 BBL FIXED ROOF CRUDE OIL TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON S-1216-64 (REVISED 2/4/08)
S-1216-78-1	42,000 gallon	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED ROOF SLOP OIL TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON S-1216-64
S-1216-85-2	17.5 MMBtu/hr burner	3020-02 H	1	1,030.00	1,030.00	A	17.5 MMBTU/HR PORTABLE LPG-FIRED STEAM GENERATOR WITH NORTH AMERICAN 4211 GLE BURNER AND FLUE GAS RECIRCULATION
S-1216-86-1	4,200 gallons	3020-05 A	1	75.00	75.00	A	100 BBL FIXED ROOF PRODUCTION TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-48

Detailed Facility Report

For Facility=1216 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1216-87-2	44.58 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	44.58 MMBTU/HR WELL SAFETY FLARE AUTHORIZED TO OPERATE AT VARIOUS UNSPECIFIED LOCATIONS WITHIN THE LIGHT OIL WESTERN STATIONARY SOURCE
S-1216-88-1	44.58 MMBtu/hr	3020-02 H	1	1,030.00	1,030.00	A	44.58 MMBTU/HR WELL SAFETY FLARE
S-1216-89-1	0.028 MMBtu/hr	3020-02 A	1	87.00	87.00	A	0.028 MMBTU/HR TANK VAPOR RECOVERY SYSTEM FLARE
S-1216-93-2	42,000 gallons	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED ROOF WASH TANK SERVED BY A VAPOR RECOVERY SYSTEM (SHARED WITH S-1216-94, 108, 109, 110)
S-1216-94-1	138,600 gallon	3020-05 E	1	246.00	246.00	A	3,300 BBL FIXED ROOF WASH TANK SERVED BY A VAPOR RECOVERY SYSTEM
S-1216-95-3	210,000 gallons	3020-05 E	1	246.00	246.00	A	WATERFLOOD PLANT/WATER CLEANING AND INJECTION OPERATION INCLUDING ONE 5,000 BBL WASH TANK (T1) SERVED BY A VAPOR CONTROL SYSTEM
S-1216-96-2	84,000 gallons	3020-05 D	1	185.00	185.00	A	2,000 BBL FIXED ROOF STORAGE/SHIPPING TANK (#3) SERVED BY A VAPOR RECOVERY SYSTEM
S-1216-97-2	42,000 gallon	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED ROOF FILTER FEED TANK (T5) SERVED BY A VAPOR CONTROL SYSTEM
S-1216-98-2	84,000 gallons	3020-05 D	1	185.00	185.00	A	2,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T4) SERVED BY A VAPOR CONTROL SYSTEM
S-1216-100-1	22,344 gallons	3020-05 C	1	135.00	135.00	A	532 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1216-101, '-102, '-103, '-104, AND '-105
S-1216-101-1	82,656 gallon	3020-05 D	1	185.00	185.00	A	1,968 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM AT S-1216-100 SHARED WITH S-1216-100, '-102, '-103, '-104, AND '-105
S-1216-102-1	22,344 gallons	3020-05 C	1	135.00	135.00	A	532 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM AT S-1216-100 SHARED WITH S-1216-100, '-101, '-103, '-104, AND '-105
S-1216-103-1	82,656 gallons	3020-05 D	1	185.00	185.00	A	1,968 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM AT S-1216-100 SHARED WITH S-1216-100, -101, '-102, '-104, AND '-105
S-1216-104-1	82,656 gallons	3020-05 D	1	185.00	185.00	A	1,968 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM AT S-1216-100 SHARED WITH S-1216-100, '-101, '-102, '-103, AND '-105
S-1216-105-1	82,656 gallons	3020-05 D	1	185.00	185.00	A	1,968 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM AT S-1216-100 SHARED WITH S-1216-100, '-101, '-102, '-103, AND '-104
S-1216-106-1	8,022 gallons	3020-05 B	1	93.00	93.00	A	191 BBL FIXED ROOF PETROLEUM STORAGE TANK

Detailed Facility Report

For Facility=1216 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1216-107-2	43,764 gallons	3020-05 C	1	135.00	135.00	A	1,042 BBL FIXED ROOF CRUDE OIL STORAGE TANK
S-1216-108-3	22,344 gallons	3020-05 C	1	135.00	135.00	A	532 BBL FIXED ROOF CRUDE OIL STORAGE TANK
S-1216-109-2	22,344 gallons	3020-05 C	1	135.00	135.00	A	532 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED ON PERMIT S-1216-93
S-1216-110-2	22,344 gallons	3020-05 C	1	135.00	135.00	A	532 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED ON PERMIT S-1216-93
S-1216-111-1	65,982 gallons	3020-05 D	1	185.00	185.00	A	1571 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1216-122
S-1216-122-1	42,000 gallons	3020-05 C	1	135.00	135.00	A	1,000 BBL CRUDE OIL STORAGE TANK SERVED BY A VAPOR RECOVERY SYSTEM SHARED WITH S-1216-111
S-1216-123-1	420,000 gallons	3020-05 E	1	246.00	246.00	A	10,000 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY A VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1216-125 AND '-126
S-1216-124-1	429,282 gallons	3020-05 E	1	246.00	246.00	A	10,221 BBL FIXED ROOF STORAGE TANK SERVED BY A VAPOR RECOVERY SYSTEM
S-1216-125-1	429,282 gallons	3020-05 E	1	246.00	246.00	A	10,221 BBL FIXED ROOF STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM (SHARED WITH S-1216-123 AND '-126)
S-1216-126-1	429,282 gallons	3020-05 E	1	246.00	246.00	A	10,221 BBL FIXED ROOF STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM (SHARED WITH S-1216-123 AND '-125)
S-1216-127-2	10,500 gallons	3020-05 B	1	93.00	93.00	A	250 BBL FIXED ROOF CRUDE OIL DRAIN TANK SERVED BY A P/V RELIEF VALVE
S-1216-128-1	84,000 gallons	3020-05 D	1	185.00	185.00	A	2,000 BBL FIXED ROOF WASH TANK SERVED BY A VAPOR CONTROL SYSTEM
S-1216-129-1	5,880 gallons	3020-05 B	1	93.00	93.00	A	140 BBL FIXED ROOF STORAGE TANK
S-1216-130-1	100,800 gallons	3020-05 E	1	246.00	246.00	A	2400 BBL FIXED-ROOF PETROLEUM WASH TANK SERVED BY A VAPOR RECOVERY SYSTEM (BUENA VISTA)
S-1216-131-1	42,000 gallons	3020-05 C	1	135.00	135.00	A	1,000 BBL FIXED-ROOF PETROLEUM WASH TANK (#IGF52) SERVED BY A VAPOR RECOVERY SYSTEM LISTED ON S-1216-44 (LITTLE SIX LEASE)
S-1216-132-2	60.5 hp electric molors	3020-01 C	1	197.00	197.00	A	WEMCO MODEL 84 OIL/WATER SEPARATOR RATED AT 40,000 BBL/DAY AND SERVED BY VAPOR RECOVERY SYSTEM
S-1216-133-2	21,000 gallons	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T6) SERVED BY VAPOR CONTROL SYSTEM
S-1216-134-2	21,000 gallons	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T7) SERVED BY VAPOR CONTROL SYSTEM

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1216-135-2	420,000 gallons	3020-05 E	1	246.00	246.00	A	10,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T2) SERVED BY VAPOR CONTROL SYSTEM
S-1216-136-2	84,000 gallons	3020-05 D	1	185.00	185.00	A	2000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T8) SERVED BY VAPOR CONTROL SYSTEM
S-1216-137-2	21,000 gallons	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF CRUDE OIL STORAGE TANK T9 SERVED BY VAPOR CONTROL SYSTEM
S-1216-139-1	195 bhp IC engine	3020-10 B	1	117.00	117.00	A	195 BHP WAUKESHA MODEL F-1197 SERIAL #265448 FIELD GAS/PROPANE -FIRED RICH BURN CYCLICALLY LOADED I.C. ENGINE WITH NON SELECTIVE CATALYTIC REDUCTION (NSCR) EMISSIONS CONTROL
S-1216-140-1	135 bhp IC engine	3020-10 B	1	117.00	117.00	A	135 BHP WAUKESHA MODEL F-817 FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR
S-1216-141-1	195 bhp IC engine	3020-10 B	1	117.00	117.00	A	195 BHP WAUKESHA MODEL F-1197 FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED I.C. ENGINE WITH NSCR
S-1216-142-2	84,588 gallons	3020-05 D	1	185.00	185.00	A	2014 BBL FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR CONTROL SYSTEM INCLUDING COMPRESSOR(S) CONNECTED WITH TANKS S-1216-143 THROUGH '-145 AND '-152 THROUGH '-156 (555 STEVENS ZONE UNIT)
S-1216-143-1	105,000 gallons	3020-05 E	1	246.00	246.00	A	2500 BBL FIXED ROOF PETROLEUM STORAGE TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)
S-1216-144-1	84,588 gallons	3020-05 D	1	185.00	185.00	A	2014 BBL FIXED ROOF PETROLEUM STORAGE TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)
S-1216-145-1	84,588 gallons	3020-05 D	1	185.00	185.00	A	2014 BBL FIXED ROOF PETROLEUM STORAGE TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)
S-1216-146-1	8,400 gallons	3020-05 B	1	93.00	93.00	A	200 BBL FIXED ROOF PETROLEUM TEST TANK (555 STEVENS ZONE UNIT)
S-1216-147-1	8,400 gallons	3020-05 B	1	93.00	93.00	A	200 BBL FIXED ROOF PETROLEUM TEST TANK (555 STEVENS ZONE UNIT)
S-1216-148-1	147 bhp IC engine	3020-10 B	1	117.00	117.00	A	147 HP MINNEAPOLIS MOLINE MODEL HD800-6A FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR
S-1216-149-1	147 bhp IC engine	3020-10 B	1	117.00	117.00	A	147 HP MINNEAPOLIS MOLINE MODEL HD800-6A FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR
S-1216-150-1	147 bhp IC engine	3020-10 B	1	117.00	117.00	A	147 HP MINNEAPOLIS MOLINE MODEL HD800-6A FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

Detailed Facility Report

For Facility=1216 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1216-151-1	135 bhp IC engine	3020-10 B	1	117.00	117.00	A	135 BHP WAUKESHA MODEL 817 FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR
S-1216-152-1	84,000 gallons	3020-05 D	1	185.00	185.00	A	2000 BBL PRODUCED WATER TANK WITH VAPOR CONTROL SYSTEM UNDER PERMIT S-1216-142 (STEVENS LEASE)
S-1216-153-1	84,000 gallons	3020-05 D	1	185.00	185.00	A	2000 BBL PRODUCED WATER TANK WITH VAPOR CONTROL UNDER PERMIT S-1216-142 (STEVENS LEASE)
S-1216-154-1	42,000 gallons	3020-05 C	1	135.00	135.00	A	1000 BBL PRODUCED WATER TANK #508 WITH VAPOR CONTROL UNDER PERMIT S-1216-142 (STEVENS LEASE)
S-1216-155-1	420,000 gallons	3020-05 E	1	246.00	246.00	A	10,000 BBL FIXED ROOF PETROLEUM PRODUCTION TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)
S-1216-156-1	21,000 gallons	3020-05 C	1	135.00	135.00	A	500 BBL FIXED ROOF PETROLEUM PRODUCTION TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)

Number of Facilities Reported: 1

Attachment B

Insignificant Activities or Equipment

San Joaquin Valley
Unified Air Pollution Control District
Title V Application - INSIGNIFICANT ACTIVITIES

COMPANY NAME: Occidental of Elk Hills (OEHI) | FACILITY ID: S - 1216

Check the box next to the exemption category from Rule 2020 which describes any insignificant activity or equipment at your facility not requiring a permit.

Exemption Category	Rule 2020 Citation	√	Exemption Category	Rule 2020 Citation	√
Structure or incinerator assoc. with a structure designed as a dwelling for 4 families or less	4.1	√	Containers used to store refined lubricating oils	6.6.8	√
Locomotives, airplanes, and watercraft used to transport passengers or freight	4.4	√	Unvented pressure vessels used exclusively to store liquified gases or assoc with exempt equipment	6.6.9 or 6.13	√
Natural gas or LPG-fired boilers or other indirect heat transfer units of 5 MMBtu/hr or less	6.1.1	√	Portable tanks used exclusively to store produced fluids for ≤ six months	6.6.10	√
Piston-type i.c.engine with maximum continuous rating of 50 braking horsepower (bhp) or less	6.1.2	√	Mobile transport tanks on delivery vehicles of VOCs	6.6.11	√
Gas turbine engines with maximum heat input rating of 3 MMBtu/hr or less	6.1.3	√	Loading racks used for the transfer of less than 4,000 gal/day of unheated organic material with initial boiling point ≥ 302 F or of fuel oil with specific gravity ≥0.8251	6.7.1.1	√
Space heating equipment other than boilers	6.1.4	√	Loading racks used for the transfer of asphalt, crude or residual oil stored in exempt tanks, or crude oil with specific gravity ≥ 0.8762	6.7.1.2	√
Cooling towers with a circulation rate less than 10,000 gal/min, and that are not used for cooling of process water, or water from barometric jets or condensers++	6.2	√	Equipment used exclusively for the transfer of refined lubricating oil	6.7.2	√
...e of less than 2 gal/day of graphic arts materials	6.3	√	Equipment used to apply architectural coatings	6.8.1	√
Equipment at retail establishments used to prepare food for human consumption	6.4.1	√	Unheated, non-conveyorized cleaning equipment with < 10 ft² open area; using solvents with initial boiling point ≥ 248 F; and < 25 gal/yr. evaporative losses	6.9	√
Ovens at bakeries with total daily production less than 1,000 pounds and exempt by sec. 6.1.1	6.4.3	√	Brazing, soldering, or welding equipment	6.10	√
Equipment used exclusively for extruding or compression molding of rubber or plastics, where no plastisizer or blowing agent is used	6.5	√	Equipment used to compress natural gas	6.11	√
Containers used to store clean produced water	6.6.1	√	Fugitive emissions sources assoc. with exempt equipment	6.12	√
Containers ≤100 bbl used to store oil with specific gravity ≥ 0.8762	6.6.2	√	Pits and Ponds as defined in Rule 1020	6.15	√
Containers ≤ 100 bbl installed prior to 6/1/89 used to store oil with specific gravity ≥ 0.8762	6.6.3	√	On-site roadmix manufacturing and the application of roadmix as a road base material	6.17	√
Containers with a capacity ≤ 250 gallons used to store organic material where the actual storage temperature <150 F	6.6.4	√	Emissions less than 2 lb/day from units not included above	6.19	√
Containers used to store unheated organic material with an initial boiling point ≥ 302 F	6.6.5	√	Venting PUC quality natural gas from for sole purpose of pipeline and compressor repair and or maintenance	7.2	√
Containers used to store fuel oils or non-air-blown asphalt with specific gravity ≥0.9042	6.6.6	√	Non-structural repairs & maintenance to permitted equipment	7.3	√
Containers used to store petroleum distillates used as motor fuel with specific gravity ≥ 0.8251	6.6.7	√	Detonation of explosives ≤ 100 lb/day and 1,000 lb/year	7.4	√

☐ No insignificant activities (Check this box if no equipment in the above categories exist at your facility.)

Attachment C

SJVUAPCD Previous Permits

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

Permit to Operate

FACILITY: S-1216 **EXPIRATION DATE:** 08/31/2010

LEGAL OWNER OR OPERATOR: OCCIDENTAL OF ELK HILLS INC
MAILING ADDRESS: 10800 STOCKDALE HIGHWAY
BAKERSFIELD, CA 93311

FACILITY LOCATION: LIGHT OIL WESTERN

FACILITY DESCRIPTION: OIL AND GAS PRODCTION

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

David Warner
Director of Permit Services

Jan 12 2012 9:12AM – SIONGCOJ

San Joaquin Valley
Air Pollution Control District

FACILITY: S-1216-0-0 **EXPIRATION DATE:** 08/31/2010

FACILITY-WIDE REQUIREMENTS

1. Facilities S-1216, S-382, and S-1738 constitute one stationary source. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Operator shall maintain accurate monthly records of Gas-to-oil ratio (GOR) and API gravity of liquids produced showing that facility exclusively processes, stores, or transfers black oil (as defined in 40 CFR 63.761). [40 CFR 63.10(b)]
4. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4409, 5.1.1]
5. For valves, threaded connections, flanges, pipes, pumps, compressors, and other components subject to the requirements of Rule 4409, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 2,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1]
6. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1]
7. For polished rod stuffing boxes (PRSBs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1]
8. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.2]
9. Minor gas leaks from PRSBs detected during any District inspection shall not be counted toward determination of compliance with this rule provided the permittee repairs, replaces, or removes leaking PRSBs from VOC service as soon as practicable but not later than seven calendar days. [District Rule 4409, 5.1.3.1.2]
10. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4409 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4409. [District Rule 4409, 5.1.3.2.1 and 5.1.3.2.2]

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

11. Leaking components at this facility detected during annual operator inspections, as required by Rule 4409 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4409, 5.1.3.2.3]

12. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.4.1]

13. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4409, 5.1.4.2]

14. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4409, 5.1.4.3]

15. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4409, 5.1.4.4]

16. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

17. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

18. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

19. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

20. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

21. When 200 or fewer PRSBs are inspected, a leak is when more than four have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 PRSBs are inspected, a leak is when more than 2.0 % (rounded up to the nearest whole number) of the PRSBs have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

22. When 200 or fewer wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than two or more pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than 1.0 % (rounded up to the nearest whole number) of the pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]
23. When pipes at natural gas processing facilities are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]
24. For manned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4409, 5.2.1]
25. For unmanned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once per calendar week. [District Rule 4409, 5.2.2]
26. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.3]
27. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4409, 5.2.4]
28. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4409, 5.2.5]
29. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4409, 5.2.6]
30. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4409, 5.2.7]
31. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4409, 5.2.8]
32. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.8.1]
33. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4409. [District Rule 4409, 5.2.8.2]
34. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4409, 5.2.9 and 5.2.10]
35. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4409, 5.2.11]

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

36. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4409, 5.2.12]

37. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4409, 5.2.13]

38. District inspections shall not be counted as an operator inspection required by District Rule 4409. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4409, 5.2.14]

39. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4409, 5.3.1]

40. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4409, 5.3.4 and 5.3.5]

41. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4409, 5.3.4 and 5.3.5]

42. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4409, 5.3.5]

43. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4409 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4409, 5.3.6]

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

44. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4409, 5.3.7]

45. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4409, 5.4.1]

46. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4409, 6.1.2]

47. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4409, 6.1.4]

48. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4409, 6.2.1]

49. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4409, 6.2.2]

50. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4409, 6.2.3]

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

51. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4409, 6.2.4]

52. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4409, 6.3.1]

53. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4409, 6.3.2]

54. The percent by volume liquid evaporated at 302 øF (150 øC) shall be determined using ASTM D-86. [District Rule 4409, 6.3.3]

55. The TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D-323, and converting the RVP to TVP at the maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures specified in Appendix A of District Rule 4409. [District Rule 4409, 6.3.4]

56. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM D-287 or ASTM 1298. Sampling for API gravity shall be performed in accordance with ASTM D-4057. [District Rule 4409, 6.3.5]

57. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4409, 6.3.6]

58. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4409, 6.3.7]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-1-1 **EXPIRATION DATE:** 08/31/2010

SECTION: 28 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
125 BBL FIXED ROOF WASH TANK SERVED BY A PRESSURE RELIEF DEVICE (MAYS LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
3. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
4. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-2-1 **EXPIRATION DATE:** 08/31/2010

SECTION: 28 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY A PRESSURE RELIEF DEVICE #13382 (MAYS LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
3. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
4. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-3-1 **EXPIRATION DATE:** 08/31/2010

SECTION: 28 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY A PRESSURE RELIEF DEVICE #13381 (MAYS LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
3. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
4. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-7-1 **EXPIRATION DATE:** 08/31/2010

SECTION: 02 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF WASH TANK SERVED BY A PRESSURE RELIEF DEVICE (TAFT LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
3. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
4. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-8-1 **EXPIRATION DATE:** 08/31/2010

SECTION: 02 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY A PRESSURE RELIEF DEVICE #10752 (TAFT LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
3. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
4. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-10-1 **EXPIRATION DATE:** 08/31/2010

SECTION: 32 **TOWNSHIP:** 31S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
180 BBL FIXED ROOF WASH TANK SERVED BY A PRESSURE RELIEF DEVICE (AIRPORT LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
3. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
4. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-11-1 **EXPIRATION DATE:** 08/31/2010

SECTION: 32 **TOWNSHIP:** 31S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED ROOF STORAGE TANK SERVED BY A PRESSURE RELIEF DEVICE #13303 (AIRPORT LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
3. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
4. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-20-1 **EXPIRATION DATE:** 08/31/2010

SECTION: NE21 **TOWNSHIP:** 31S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
500 BBL WASH TANK SERVED BY A PRESSURE RELIEF DEVICE (BALBOA LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The tank PV valve shall be set to within 10% of the maximum allowable working pressure of the tank. [District Rule 4623]
3. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
4. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
5. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-21-1 **EXPIRATION DATE:** 08/31/2010

SECTION: NE32 **TOWNSHIP:** 31S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
500 BBL STOCK TANK SERVED BY A PRESSURE RELIEF DEVICE (#5384, BALBOA LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The tank PV valve shall be set to within 10% of the maximum allowable working pressure of the tank. [District Rule 4623]
3. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
4. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
5. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-22-1 **EXPIRATION DATE:** 08/31/2010

SECTION: NW28 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
490 BARREL FIXED ROOF WASH TANK SERVED BY A PRESSURE/VACUUM RELIEF VENT VALVE (MAYS LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. True vapor pressure of liquids introduced, placed, stored or held in this tank shall not exceed 1.0 psia. [District Rule 2201]
3. Tank shall be designed and operated as a constant liquid level tank. [District Rule 2201]
4. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623]
5. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 2201]
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 2201]
7. Compliance with vapor pressure limit shall be demonstrated by District witnessed or authorized sample collection and analysis. [District Rule 2201]
8. Permittee shall maintain accurate records of liquids stored, storage temperature, and true vapor pressure of such liquids. [District Rule 2201]
9. Permittee shall maintain monthly records of average daily crude oil throughput and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. [District Rule 4623]
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-42-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW16 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (#.05GF17) SERVED BY VAPOR CONTROL SYSTEM INCLUDING COMPRESSOR(S) AND PIPING TO GAS PIPELINE SHARED WITH S-1216-43

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
5. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
6. Vapor control efficiency shall be maintained at no less than 95%. [District Rule 4623]
7. Formerly S-1641-39.
8. Formerly S-382-773.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-43-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE16 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (#.05GF8) SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-42 (KING LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
5. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
6. Vapor control efficiency shall be maintained at no less than 95%. [District Rule 4623]
7. Formerly S-1641-40.
8. Formerly S-382-774.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-44-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 06 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED-ROOF PETROLEUM WASH TANK (#08002M06E) SERVED BY A VAPOR RECOVERY SYSTEM (LITTLE SIX LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Tank shall vent exclusively to gas gathering line shared between permit units S-1216-44 and S-1216-46. [District Rules 2201 and 4623]
3. Operation shall include make-up gas line with Varec Fig. 181 valve regulator and piping through Varec Fig. 180 valve regulator to gas gathering line shared between permit units S-1216-44 and S-1216-46. [District NSR Rule]
4. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
5. Any tank gauging or sampling device shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
6. All piping, valves, and fittings shall be constructed and maintained in a leak free condition. [District Rules 2201 and 4623]
7. A leak free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A gas leak or a liquid leak is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
8. Tank shall be operated at constant fluid level. [District NSR Rule]
9. Varec Fig. 181 gas regulator shall activate when tank pressure falls below 2 in. H2O allowing make-up gas to enter tank. [District NSR Rule]
10. Varec Fig. 180 gas regulator shall activate when tank pressure rises above 2 in-H20 allowing vapor to be drawn into gas gathering line. [District NSR Rule]
11. The tank PV valve shall be set to within 10% of the maximum allowable working pressure of the tank. [District Rule 4623]
12. Total combined volatile organic compound (VOC) emissions from tanks S-1216-44 and S-1216-46 shall not exceed 0.24 lb per day. [District NSR Rule]
13. The operator shall maintain accurate records of types, storage temperature and true vapor pressure of liquids stored. [District Rule 1070]
14. Formerly S-1130-12-2
15. Formerly S-1641-42.
16. Formerly S-382-775.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-45-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NW14 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF PETROLEUM WASH TANK SERVED BY PRESSURE-VACUUM VENTS (SECTION 14 TANK SETTING, BUENA VISTA HILLS)

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623]
2. This tank shall be in a gas-tight condition. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623. [District Rule 4623]
3. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
4. Wash tank shall be operated at constant level. [District NSR Rule]
5. True vapor pressure of any organic liquid introduced to the tank shall be less than 1.5 psia at liquid temperature. [District Rule 4623]
6. Permittee shall test the True Vapor Pressure (TVP) of organic liquids stored at actual storage temperature at least once every 24 months during summer (July - September) and/or whenever there is a change in the source or type of organic liquid stored. Permittee may use the TVP test results from a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 are met. Permittee shall submit the records of TVP and/or API gravity testing to the APCO within 45 days after the date of testing. The record shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the stored organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
7. If the tank stores crude oil or petroleum distillates, the permittee shall also conduct API gravity testing. [District Rule 4623]
8. TVP of liquids stored shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM 323-94, then converting the RVP to TVP at the maximum storage temperature using the equation in Rule 4623, Appendix B. As an alternative to ASTM D 323-94, the TVP of crude oil with an API gravity range greater than 20 degrees but less than or equal to 30 degrees may be determined by other equivalent test methods approved by APCO, ARB, and EPA. [District Rule 4623]
9. The API gravity of crude oil or petroleum distillate shall be determined by ASTM Method D 287-92 (2000) e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057-95 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products". [District Rule 4623]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Permittee shall keep an accurate record of each organic liquid stored, including its storage temperature, TVP, and API gravity. [District Rule 4623]
11. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]
12. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
13. Formerly S-1130-14-3
14. Formerly S-1641-44.
15. Formerly S-382-776.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-46-2 **EXPIRATION DATE:** 08/31/2010

SECTION: NE 6 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED-ROOF PETROLEUM SHIPPING TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON S-1216-44 (LITTLE SIX LEASE)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
3. The tank PV valve shall be set to within 10% of the maximum allowable working pressure of the tank. [District Rule 4623]
4. Tank shall vent exclusively to gas blanketing/gathering line shared with permit unit S-1216-44. [District Rules 2201 and 4623]
5. Operation shall include make-up gas line with Varec Fig. 181 valve regulator and piping through Varec Fig. 180 valve regulator to gas gathering line shared with permit unit S-1216-44. [District NSR Rule]
6. Any tank gauging or sampling device shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623]
7. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623]
8. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A gas leak or a liquid leak is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
9. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623]
10. Any component found to be leaking on two consecutive annual inspections is in violation of Rule 4623. [District Rule 4623]
11. Fugitive VOC emissions from the components in gas/light liquid service and light crude oil service on tanks S-1216-44 and 46, combined, shall not exceed 0.24 lb/day. [District Rule 2201]
12. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb (1999), Screening Value Range emissions factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623]
14. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 1070 and 4623]
15. Formerly S-1130-24-0
16. Formerly S-1641-46.
17. Formerly S-382-777.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-47-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE10 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
300 BBL FIXED ROOF PETROLEUM WASH TANK SERVED BY A PRESSURE-VACUUM VENT (SECTION 10 TANK SETTING, BUENA VISTA HILLS)

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623]
2. This tank shall be in a gas-tight condition. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623. [District Rule 4623]
3. Wash tank shall be operated at constant level. [District NSR Rule]
4. Permittee shall test the True Vapor Pressure (TVP) of organic liquids stored at actual storage temperature at least once every 24 months during summer (July - September) and/or whenever there is a change in the source or type of organic liquid stored. Permittee may use the TVP test results from a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 are met. Permittee shall submit the records of TVP and/or API gravity testing to the APCO within 45 days after the date of testing. The record shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the stored organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
5. TVP of liquids stored shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM 323-94, then converting the RVP to TVP at the maximum storage temperature using the equation in Rule 4623, Appendix B. As an alternative to ASTM D 323-94, the TVP of crude oil with an API gravity range greater than 20 degrees but less than or equal to 30 degrees may be determined by other equivalent test methods approved by APCO, ARB, and EPA. [District Rule 4623]
6. If the tank stores crude oil or petroleum distillates, the permittee shall also conduct API gravity testing. [District Rule 4623]
7. The API gravity of crude oil or petroleum distillate shall be determined by ASTM Method D 287-92 (2000) e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057-95 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products". [District Rule 4623]
8. Permittee shall keep an accurate record of each organic liquid stored, including its storage temperature, TVP, and API gravity. [District Rule 4623]
9. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
11. Formerly S-1130-92-0
12. Formerly S-1641-48.
13. Formerly S-382-779.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-48-2 **EXPIRATION DATE:** 08/31/2010

SECTION: SW26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
210 BBL FIXED ROOF SHIPPING TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-49, S-1216-50, S-1216-59, S-1216-63, AND S-1216-86 DISCHARGING TO FIELD GAS GATHERING LINE (SEC 26 BUENA VISTA LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [40 CFR 60.112a]
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2]
3. Collected vapors shall be discharged only to field gas gathering line. [District Rule 2201]
4. Fugitive VOC emissions rate shall be, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District NSR Rule]
5. VOC emission rate from the components in gas and light oil service associated with this tank, up to the tie-in with the vapor recovery unit trunk-line, shall not exceed 0.1 lb/day. [District Rule 2201]
6. VOC fugitive emissions from the components in gas and light oil service on the vapor control system shall not exceed 0.4 lb/day. [District Rule 2201]
7. All piping, valves and other fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.3.3]
8. A leak free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
9. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)]
10. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)]
12. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)]
13. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)]
14. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)]
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623]
16. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in EPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 4623, 6.2.4]
17. The efficiency of any VOC destruction device shall be measured by EPA Method 25, 25a, or 25b, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4623, 6.2.5]
18. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rules 2201 and 4623]
19. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance but occurs as a routine maintenance activity. [District Rule 2020]
20. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7]
21. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623, 5.7]
22. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule 2201]
23. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-49-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
210 BBL FIXED ROOF SHIPPING TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1216-48 (SEC 26 FEE LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rules 2201 and 4623]
2. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
3. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
5. Tank roof appurtenances shall be maintained leak free (as defined in Rule 4623). [District Rule 2201]
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
7. API gravity of liquid stored shall not exceed 30 as determined by ASTM D-1298-85 or tanks shall be subject to the requirements of District Rule 4403. [District Rules 2201 and 4403]
8. Contents of tank shall be tested by independent laboratory to determine API gravity, upon startup, using ASTM method D-1298-85. [District Rule 1081]
9. The results of the laboratory test for API gravity shall be submitted to the District within 60 days of testing performed at startup. [District Rule 1081]
10. Permittee shall maintain records of API gravity. Such records shall be retained for a period of at least 2 years, and shall be made readily available for District inspection upon request. [District Rule 2201]
11. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
12. Formerly S-1130-99-3
13. Formerly S-1641-50.
14. Formerly S-382-781.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-50-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
750 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1216-48 (#REW 31, SECTION 8 LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rules 2201 and 4623]
2. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623]
3. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
4. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rules 2201 and 4623]
5. Tank roof appurtenances shall be maintained leak free (as defined in Rule 4623). [District Rule 2201]
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
7. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
8. Formerly S-1130-117
9. Formerly S-1641-54.
10. Formerly S-382-784.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-51-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE08 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
5,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #5GF6 (SECTION 8 LEASE)

PERMIT UNIT REQUIREMENTS

1. True vapor pressure of liquids stored shall not exceed 1.5 psia. [District Rule 4623]
2. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4623. [District Rule 4623]
3. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
4. All liquids shall be removed and the produced crude oil inlet line shall be physically disconnected. [District Rule 2080]
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. Formerly S-1130-118-0
7. Formerly S-1641-55.
8. Formerly S-382-785.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-52-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE08 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
750 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (SECTION 8 LEASE)

PERMIT UNIT REQUIREMENTS

1. True vapor pressure of liquids stored shall not exceed 1.5 psia. [District Rule 4623]
2. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4623. [District Rule 4623]
3. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
4. All liquids shall be removed and the produced crude oil inlet line shall be physically disconnected. [District Rule 2080]
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. Formerly S-1130-120-0
7. Formerly S-1641-57.
8. Formerly S-382-786.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-53-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW08 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #RECYCLE 3 (SECTION 8 LEASE)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623]
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623]
3. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623]
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623]
5. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623]
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623]
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]
9. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
10. Formerly S-1130-121-0
11. Formerly S-1641-58.
12. Formerly S-382-787.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-54-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW08 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK SERVED BY A VAPOR RECOVERY SYSTEM (SECTION 8 LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
4. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
5. Tank shall vent vacuum line serving 1C gas plant. [District Rule 2010]
6. The tank PV valve shall be set to within 10% of the maximum allowable working pressure of the tank. [District Rule 4623]
7. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
8. Formerly S-1130-122-0
9. Formerly S-1641-59.
10. Formerly S-382-788.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-55-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NW10 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
200 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (#02GF1, SECTION 10 TANK SETTING, BUENA VISTA HILLS) SERVED BY A PRESSURE-VACUUM VENT VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623]
2. This tank shall be in a gas-tight condition. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623. [District Rule 4623]
3. Permittee shall test the True Vapor Pressure (TVP) of organic liquids stored at actual storage temperature at least once every 24 months during summer (July - September) and/or whenever there is a change in the source or type of organic liquid stored. Permittee may use the TVP test results from a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 are met. Permittee shall submit the records of TVP and/or API gravity testing to the APCO within 45 days after the date of testing. The record shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the stored organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
4. TVP of liquids stored shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM 323-94, then converting the RVP to TVP at the maximum storage temperature using the equation in Rule 4623, Appendix B. As an alternative to ASTM D 323-94, the TVP of crude oil with an API gravity range greater than 20 degrees but less than or equal to 30 degrees may be determined by other equivalent test methods approved by APCO, ARB, and EPA. [District Rule 4623]
5. If the tank stores crude oil or petroleum distillates, the permittee shall also conduct API gravity testing. [District Rule 4623]
6. The API gravity of crude oil or petroleum distillate shall be determined by ASTM Method D 287-92 (2000) e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057-95 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products". [District Rule 4623]
7. Permittee shall keep an accurate record of each organic liquid stored, including its storage temperature, TVP, and API gravity. [District Rule 4623]
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]
9. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Formerly S-1130-123-0
11. Formerly S-1641-60.
12. Formerly S-382-789.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-56-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE14 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (#5GF14, SECTION 14, BUENA VISTA HILLS) SERVED BY A PRESSURE-VACUUM VENT VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623]
2. This tank shall be in a gas-tight condition. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623. [District Rule 4623]
3. True vapor pressure of any organic liquid introduced to the tank shall be less than 1.5 psia at liquid temperature. [District Rule 4623]
4. Permittee shall test the True Vapor Pressure (TVP) of organic liquids stored at actual storage temperature at least once every 24 months during summer (July - September) and/or whenever there is a change in the source or type of organic liquid stored. Permittee may use the TVP test results from a representative tank provided the requirements of Sections 6.2.1.1.1 through 6.2.1.1.5 are met. Permittee shall submit the records of TVP and/or API gravity testing to the APCO within 45 days after the date of testing. The record shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the stored organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
5. TVP of liquids stored shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM 323-94, then converting the RVP to TVP at the maximum storage temperature using the equation in Rule 4623, Appendix B. As an alternative to ASTM D 323-94, the TVP of crude oil with an API gravity range greater than 20 degrees but less than or equal to 30 degrees may be determined by other equivalent test methods approved by APCO, ARB, and EPA. [District Rule 4623]
6. If the tank stores crude oil or petroleum distillates, the permittee shall also conduct API gravity testing. [District Rule 4623]
7. The API gravity of crude oil or petroleum distillate shall be determined by ASTM Method D 287-92 (2000) e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057-95 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products". [District Rule 4623]
8. Permittee shall keep an accurate record of each organic liquid stored, including its storage temperature, TVP, and API gravity. [District Rule 4623]
9. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
11. Formerly S-1130-124-0
12. Formerly S-1641-61.
13. Formerly S-382-790.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-57-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE16 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #1GF34 (SECTION 16A LEASE)

PERMIT UNIT REQUIREMENTS

1. True vapor pressure of liquids stored shall not exceed 1.5 psia. [District Rule 4623]
2. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4623. [District Rule 4623]
3. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
4. All liquids shall be removed and the produced crude oil inlet line shall be physically disconnected. [District Rule 2080]
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. Formerly S-1130-125-0
7. Formerly S-1641-62.
8. Formerly S-382-791.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-58-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE16 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK, #1GF35 (SECTION 16A LEASE)

PERMIT UNIT REQUIREMENTS

1. True vapor pressure of liquids stored shall not exceed 1.5 psia. [District Rule 4623]
2. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4623. [District Rule 4623]
3. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
4. All liquids shall be removed and the produced crude oil inlet line shall be physically disconnected. [District Rule 2080]
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. Formerly S-1130-127-0
7. Formerly S-1641-63.
8. Formerly S-382-792.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-59-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
210 BBL FIXED ROOF SHIPPING TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-48 (SECTION 26 BUENA VISTA LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
4. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
5. Tank roof appurtenances shall be maintained leak free (as defined in Rule 4623). [District Rule 2201]
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
7. API gravity of liquid stored shall not exceed 30 as determined by ASTM D-1298-85 or tanks shall be subject to the requirements of District Rule 4403. [District Rules 2201 and 4403]
8. Average daily throughput of oil (on annual basis) shall not exceed 420 bbl per day. [District Rule 2201]
9. Permittee shall maintain records of API gravity and average daily throughput, records shall be retained for a minimum of 2 years, and shall be made available for District inspection upon request. [District Rule 2201]
10. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
11. Formerly S-1130-133-0
12. Formerly S-1641-64.
13. Formerly S-382-793.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-60-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY A VAPOR CONTROL SYSTEM WITH A 25 HP COMPRESSOR SHARED WITH S-1216-61 AND '-62 (B.V. HILLS OILFIELD LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
3. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
4. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
5. True vapor pressure shall not exceed 4.7 psia. [District Rule 2201]
6. The permittee shall maintain accurate records of true vapor pressure, storage temperature and types of liquids stored. Such records shall be retained for a period of at least two years, and shall be made readily available for District inspection upon request. [District Rule 1070]
7. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
8. Formerly S-1130-134-3
9. Formerly S-1641-65.
10. Formerly S-382-794.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-61-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-60 (B.V. HILLS OILFIELD LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
3. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
4. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
5. True vapor pressure shall not exceed 4.7 psia. [District Rule 2201]
6. The permittee shall maintain accurate records of true vapor pressure, storage temperature and types of liquids stored. Such records shall be retained for a period of at least two years, and shall be made readily available for District inspection upon request. [District Rule 1070]
7. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
8. Formerly S-1130-135-2
9. Formerly S-1641-66.
10. Formerly S-382-795.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-62-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF CRUDE OIL WASH TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-60 (B.V. HILLS OILFIELD LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
3. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
4. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
5. True vapor pressure shall not exceed 4.7 psia. [District Rule 2201]
6. The permittee shall maintain accurate records of true vapor pressure, storage temperature and types of liquids stored. Such records shall be retained for a period of at least two years, and shall be made readily available for District inspection upon request. [District Rule 1070]
7. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
8. Formerly S-1130-136-2
9. Formerly S-1641-67.
10. Formerly S-382-796.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-63-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
210 BBL FIXED ROOF SHIPPING TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-48 (SEC 26 BUENA VISTA LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
4. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
5. Tank roof appurtenances shall be maintained leak free (as defined in Rule 4623). [District Rule 2201]
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
7. True vapor pressure (TVP) of liquid stored in this permit unit shall not exceed 2.71 psia at storage temperature. [District Rule 2201]
8. Average daily throughput of oil (on annual basis) shall not exceed 50 bbl per day. [District Rule 2201]
9. API gravity of liquid stored shall not exceed 30 degrees as determined by ASTM D-1298-85 or liquid handling components shall be subject to the requirements of District Rule 4403. [District Rules 2201 and 4403]
10. Permittee shall maintain records of API gravity, TVP and average daily throughput. Such records shall be retained for a period of at least 2 years, and shall be made readily available for District inspection upon request. [District Rule 2201]
11. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
12. Formerly S-1130-158-0
13. Formerly S-1641-68.
14. Formerly S-382-797.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-64-2 **EXPIRATION DATE:** 08/31/2010

SECTION: NE 23 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
3,000 BBL FIXED ROOF WASH TANK SERVED BY A VAPOR CONTROL SYSTEM SHARED WITH S-1216-66, '-72, '-73, '-74 &'-75

PERMIT UNIT REQUIREMENTS

1. Authority to Construct (ATC) S-1216-64-1 shall be implemented concurrently, or prior to the modification and startup of the equipment authorized by this Authority to Construct. [District Rule 2201]
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
3. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
5. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
6. Tank roof appurtenances shall be maintained leak free. [District Rule 4623]
7. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)]
9. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)]
10. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) eliminate or minimize the leak within 8 hours after detection, (b) if the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices and eliminate the leak within 48 hours after detection. In no event shall the total time to minimize and eliminate the leak exceed 56 hours after detection. [District Rule 4623, 5.7 9 (Table 3)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)]
12. Operator shall maintain an inspection log containing the following 1) type of component leaking; 2) date and time of leak detection, and method of detection; 3) date and time of leak repair, and emission level of recheck after leak is repaired; 4) method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 1070]
13. The efficiency of any VOC destruction device shall be measured by EPA Method 25, 25a, or 25b. [District Rule 4623, 6.4.7]
14. Except as otherwise provided in this permit, operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rules 4623 and 2201]
15. VOC emission rate from vapor, light liquid, and light crude oil components associated with vapor recovery piping shall not exceed 0.3 lb/day. [District Rule 2201]
16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance but occurs as a routine maintenance activity. [District Rule 2020]
17. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7]
18. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623, 5.7]
19. Permittee shall maintain accurate records of fugitive emissions and such records shall be made readily available for District inspection upon request for a period of five years. [District Rule 2201]
20. All records shall be maintained for a period of at least five years and made available for District inspection upon request. [District Rule 1070]
21. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
22. Formerly S-3506-1-0.
23. Formerly S-1641-69.
24. Formerly S-382-798.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-66-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE 23 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
3,000 BBL WELDED, FIXED ROOF PRODUCED WATER TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1216-64 (ASPHALTO FEE)

PERMIT UNIT REQUIREMENTS

1. VOC emission rate from vapor, light liquid, and light crude oil service components associated with tank, up to the tie-in with the vapor control trunk-line, shall not exceed 0.5 lb/day. [District Rule 2201]
2. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623. [District Rules 2201 and 4623, 3.9 and 6.4.8]
3. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions using California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2C: Oil and Gas Production Screening Value Ranges (<10,000 ppmv) Emission Factors with 100% VOC content in components. [District Rule 2201]
4. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
5. Except as otherwise provided in this permit, tank roof appurtenances shall be maintained leak free. [District Rules 2201 and 4623]
6. The tank shall be equipped with a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank to vapor control system S-1216-64 capable of reducing VOC emissions by at least 95%. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. [District Rules 2201 & 4623, 5.6.1]
7. If the source can demonstrate compliance with the provisions of Rule 4623 Section 5.7 any deviations that are addressed under the provisions of Table 3 through 6 shall not be in violation of this permit. [District Rule 4623, 5.7]
8. Except as otherwise provided in this permit, all piping, valves, and fittings shall be constructed and maintained in a gas tight condition. [District Rule 4623, 5.6.3]
9. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. [District Rule 4623, 3.9 and 6.4.8]
10. Any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2]
11. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)]
12. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) eliminate or minimize the leak within 8 hours after detection, (b) if the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices and eliminate the leak within 48 hours after detection. In no event shall the total time to minimize and eliminate the leak exceed 56 hours after detection. [District Rule 4623, 5.7 9 (Table 3)]
14. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)]
15. Operator shall maintain an inspection log containing the following 1) type of component leaking; 2) date and time of leak detection, and method of detection; 3) date and time of leak repair, and emission level of recheck after leak is repaired; 4) method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 1070]
16. Permittee shall comply with all applicable requirements of Rule 4403. [District Rule 4403]
17. The efficiency of any VOC destruction device shall be measured by EPA Method 25, 25a, or 25b. [District Rule 4623, 6.4.7]
18. Except as otherwise provided in this permit, operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rules 4623 and 2201]
19. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance but occurs as a routine maintenance activity. [District Rule 2020]
20. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7]
21. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623, 5.7]
22. Permittee shall maintain accurate records of fugitive emissions and such records shall be made readily available for District inspection upon request for a period of five years. [District Rule 2201]
23. All records shall be maintained for a period of at least five years and made available for District inspection upon request. [District Rule 1070]
24. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
25. Formerly S-1641-75.
26. Formerly S-382-800.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-67-2 **EXPIRATION DATE:** 08/31/2010

SECTION: NW15 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
225 HP CATERPILLAR MODEL G342NA NATURAL GAS-FIRED IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) AND AIR/FUEL RATIO CONTROLLER POWERING A GAS COMPRESSOR

PERMIT UNIT REQUIREMENTS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520]
2. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
3. The fuel supply line shall be physically disconnected from this unit to ensure that this unit is not operated. [District Rule 4702]
4. This equipment shall not be operated for any reason until an Authority to Construct permit is issued approving all necessary retrofits required to comply with the applicable requirements of District Rule 4702 and all other applicable District regulations. [District Rule 4702]
5. Approved locations for this IC engine are NW 1/4 Sec 15, T30S, R22E and NW 1/4 Sec 23, T30S, R22E. [District Rule 2201]
6. The permittee shall notify the District Compliance Division of each location at which the operation is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070]
7. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801)]
8. Particulate emissions shall not exceed at the point of discharge, 0.1 gr/dscf. [District Rule 4201]
9. Engine shall be fired exclusively on natural gas, consisting primarily of methane and ethane, with a sulfur content no greater than 0.75 grains of sulfur compounds (as S) per 100 dry scf of natural gas. [District NSR Rule]
10. If the IC engine is fired on PUC-regulated natural gas, then maintain on file copies of all natural gas bills. [District Rule 1160]
11. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the IC engine shall be determined using ASTM method D 1072, D 3031, D 4084 or D 3246. [District Rule 4801]
12. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 4801]
13. The operator of an internal combustion (IC) engine shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 4701]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. Exhaust shall vent through catalytic converter only. [District NSR Rule]

15. Emissions shall not exceed the following: PM10: 9.8E-5 lb/hp-hr, NOx (as NO2): 7.8E-4 lb/hp-hr (25 ppmv at 15% O2), VOC: 3.26E-4 lb/hp-hr (30 ppmv at 15% O2) and CO: 1.52E-2 lb/hp-hr (800 ppmv at 15% O2). [District NSR Rule]

16. NOx, and CO emissions shall be measured at least once every 24 months with source test conducted by an independent testing laboratory and shall be witnessed or authorized by the District. [District Rule 4701]

17. The permittee shall monitor and record the stack concentration of NOx (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. [In-stack O2 monitors may be allowed if approved by the APCO.] Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rule 4701]

18. If the NOx or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rule 4701]

19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rule 4701]

20. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance test, and a test plan must be submitted for approval 15 days prior to testing. [District Rule 1081]

21. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081]

22. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, and VOC (ppmv) - EPA Method 25 or EPA Method 18 referenced as methane. [District Rules 1081 and 4701]

23. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with rule 4701 for a period of five years and shall make such records readily available for District inspection upon request. [District Rule 4701]

24. An operating log record shall be maintained that includes compliance source test results, monitoring data, make and model of exhaust gas analyzer, exhaust gas analyzer calibration records, and catalyst maintenance and cleaning intervals. [District Rules 4701]

25. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100]

26. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

27. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020. [District Rule 2010, 3.0, 4.0, and 2020]

28. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080]

29. Every application for a permit required under Rule 2010 (Permits Required) shall be filed in a manner and form prescribed by the District. [District Rule 2040]

30. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2080]

31. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2080]

32. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. [District Rule 1100, 7.0]

33. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit . [District Rule 1080]

34. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2080]

35. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 3010]

36. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2080]

37. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2080]

38. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2080]

39. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2080]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

40. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101, by using EPA method 9. If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101]
41. Formerly S-3507-7.
42. Formerly S-382-801.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-68-3 **EXPIRATION DATE:** 08/31/2010

SECTION: SE14 **TOWNSHIP:** 29S **RANGE:** 21E

EQUIPMENT DESCRIPTION:
GLYCOL GAS DEHYDRATION OPERATION INCLUDING GLYCOL REBOILER WITH 0.75 MMBTU/HR AFTERBURNER

PERMIT UNIT REQUIREMENTS

1. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080]
2. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080]
3. While dormant, normal source testing shall not be required. [District Rule 2080]
4. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080]
5. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080]
6. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070]
7. Total dehydrated gas by this permit unit shall not exceed 7.5 MMscf of gas in any one day. [District 2201 Rule]
8. All glycol reboiler vent gas shall be burned in afterburner and none shall vent to atmosphere. [District Rule 2201 and 4408]
9. Only glycol shall be used as the dehydration medium. [District Rule 2201]
10. Condensate handling shall be conducted in closed systems resulting in fugitive component emissions only and no evaporation of VOCs. [District Rule 2201 and 4408]
11. The afterburner shall operate at all times when dehydration is taking place. [District 2201 Rule]
12. Afterburner shall operate in a smokeless manner. [District Rule 4408]
13. Afterburner shall be equipped with electronically controlled ignition system with a malfunction alarm system if the pilot flame fails. [District Rule 4408]
14. Afterburner shall be equipped with liquid knockout system to condense any condensable vapors. [District Rule 4408]
15. Afterburner shall be equipped with a sight glass port if the flame is not visible. [District Rule 4408]
16. All piping, valves and other fittings shall be constructed and maintained in a gas-tight condition. "Gas-tight" shall be defined as emitting no more than 10,000 ppm of methane measured from the potential source with an instrument calibrated with methane in accordance with EPA Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4408]
17. Glycol reboiler and afterburner shall be fired on PUC quality natural gas. [District 2201 Rule]
18. Afterburner emissions shall not exceed any of the following: NOx - 1.8 lb/day, VOC - 0.5 lb/day, or CO - 1.5 lb/day. [District 2201 Rule]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. The VOC destruction efficiency from the glycol dehydration afterburner shall be maintained at or greater than 99.9%. [District 2201 Rule]

20. The owner or operator shall maintain accurate daily records of gas dehydrated for a period of five years and shall make such records available for District inspection upon request. [District Rule 1070]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-69-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE24 **TOWNSHIP:** 29S **RANGE:** 21E

EQUIPMENT DESCRIPTION:
EMERGENCY GAS PLANT FLARE INCLUDING: AUTOMATIC ELECTRONIC IGNITER AND GAS LIQUID SEPARATOR

PERMIT UNIT REQUIREMENTS

1. Flare shall be equipped with automatic reignition provisions, e.g. electronic spark pilot light. [District Rule 2201]
2. Flare shall operate with visible emissions less than 5% opacity. [District Rule 2201]
3. Flare shall operate only during breakdown conditions pursuant to Rule 1100. [District Rule 2201]
4. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100]
5. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100]
6. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020. [District Rule 2010, 3.0, 4.0, and 2020]
7. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080]
8. Every application for a permit required under Rule 2010 (Permits Required) shall be filed in a manner and form prescribed by the District. [District Rule 2040]
9. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2080]
10. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2080]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. [District Rule 1100, 7.0]
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit . [District Rule 1080]
13. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2080]
14. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 3010]
15. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2080]
16. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2080]
17. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2080]
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2080]
19. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101, by using EPA method 9. If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101]
20. Formerly S-3507-12.
21. Formerly S-1793-2-0.
22. Formerly S-382-803.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-70-2 **EXPIRATION DATE:** 08/31/2010

SECTION: NW15 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
325 HP CATERPILLAR MODEL 3406 TA NATURAL GAS-FIRED IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION AND AUTOMATIC AIR/FUEL RATIO CONTROLLER POWERING A GAS COMPRESSOR

PERMIT UNIT REQUIREMENTS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520]
2. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
3. The fuel supply line shall be physically disconnected from this unit to ensure that this unit is not operated. [District Rule 4702]
4. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 2201 and 4702]
5. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rule 2201]
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
8. Upon recommencing operation the NOx emission concentration shall not exceed 5 ppmvd @ 15% O2. [District Rules 2201 and 4702]
9. Upon recommencing operation the CO emission concentration shall not exceed 56 ppmvd @ 15% O2. [District Rules 2201 and 4702]
10. Upon recommencing operation the VOC emission concentration shall not exceed 25 ppmvd, as methane, @ 15% O2. [District Rules 2201 and 4702]
11. Upon recommencing operation the PM10 emissions shall not exceed 10.0 lbs/MMscf of natural gas used. [District Rule 2201]
12. Upon recommencing operation the SOx emissions shall not exceed 2.85 lbs/MMscf of natural gas used. [District Rule 2201]
13. The VOC emission rate from fugitive emissions components shall not exceed 0.2 lb/day. [District Rule 2201]
14. There shall be no leaks in excess of 10,000 ppmv measured pursuant to EPA Method 21 from fugitive emissions components associated with this permit. [District Rule 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

15. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c , Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999) for <10,000 ppmv (no leaks). [District Rule 2201]
16. Engine shall be equipped with nonresettable fuel and hourly meters. [District Rule 4702]
17. The engine shall be equipped with an automatic air to fuel ratio control system. [District Rule 2201]
18. Upon recommencing operation source testing of the NOx, CO and VOC emission concentrations shall be conducted at least once every 12 months. [District Rule 2201 and 4702]
19. Source testing for NOx emissions shall be conducted utilizing CARB 100 or EPA method 7E. [District Rule 4702]
20. Source testing for CO emissions shall be conducted utilizing CARB 100 or EPA method 10. [District Rule 4702]
21. Source testing for VOC emissions shall be conducted utilizing EPA method 25 or EPA method 18, referenced as methane. [District Rule 4702]
22. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rules 1081 and 4702]
23. The results of each source test must be submitted to the District within 60 days thereafter. [District Rule 1081]
24. Sampling facilities for source testing shall be provided in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081]
25. Upon recommencing operation the permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every calendar quarter (in which a source test is not performed) using a portable emission monitor that meets District specifications. [In-stack O2 monitors may be allowed if approved by the APCO.] Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rule 4702]
26. Upon recommencing operation if either the NOx or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the allowable emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rule 4702]
27. Upon recommencing operation all alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rule 4702]
28. Upon recommencing operation the permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rule 4702]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. All records shall be retained for a minimum of 5 years, and shall be made available for District inspection upon request. [District Rule 1070]

30. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100]

31. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100]

32. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020. [District Rule 2010, 3.0, 4.0, and 2020]

33. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080]

34. Every application for a permit required under Rule 2010 (Permits Required) shall be filed in a manner and form prescribed by the District. [District Rule 2040]

35. Upon recommencing operation the operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2080]

36. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2080]

37. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. [District Rule 1100, 7.0]

38. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit . [District Rule 1080]

39. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2080]

40. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 3010]

41. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2080]

42. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2080]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

43. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2080]

44. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2080]

45. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101, by using EPA method 9. If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101]

46. Formerly S-3507-16.

47. Formerly S-382-804.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-71-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NW25 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1478 BHP WAUKESHA MODEL L7042GSI NATURAL GAS-FIRED IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION AND AUTOMATIC AIR/FUEL RATIO CONTROLLER POWERING A GAS COMPRESSOR

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
3. The NOx emission concentration shall not exceed 5 ppmvd @ 15% O2. [District Rules 2201, 4701, and 4702]
4. The CO emission concentration shall not exceed 56 ppmvd @ 15% O2. [District Rules 2201, 4701, and 4702]
5. The VOC emission concentration shall not exceed 25 ppmvd, as methane, @ 15% O2. [District Rules 2201, 4701, and 4702]
6. The PM10 emissions shall not exceed 0.02 g/bhp-hr. [District Rule 2201]
7. The SOx emissions shall not exceed 2.85 lbs/MMscf of natural gas used. [District Rule 2201]
8. VOC emission rate from fugitive emissions components shall not exceed 0.2 lb/day. [District Rule 2201]
9. There shall be no leaks in excess of 10,000 ppmv measured pursuant to EPA Method 21 from fugitive emissions components associated with this permit. [District Rule 2201]
10. Permittee shall maintain with the permit accurate fugitive component counts and resulting emissions calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c , Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999) for <10,000 ppmv (no leaks). [District Rule 2201]
11. Engine shall be equipped with nonresettable fuel and hourly meters. [District Rule 4702]
12. The engine shall be equipped with an automatic air to fuel ratio control system. [District Rule 2201]
13. Source testing of the NOx, CO and VOC emission concentrations shall be conducted within 60 days of initial startup and at least once every 12 months thereafter. [District Rule 2201, 4701, and 4702]
14. Source testing for NOx emissions shall be conducted utilizing CARB 100 or EPA method 7E. [District Rule 4701]
15. Source testing for CO emissions shall be conducted utilizing CARB 100 or EPA method 10. [District Rule 4701]
16. Source testing for VOC emissions shall be conducted utilizing EPA method 25 or EPA method 18, referenced as methane. [District Rule 4701]
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rules 1081 and 4701]
18. The results of each source test must be submitted to the District within 60 days thereafter. [District Rule 1081]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

19. Sampling facilities for source testing shall be provided in accordance with the provisions of Rule 1081 (Source Sampling). [District Rule 1081]

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every calendar quarter (in which a source test is not performed) using a portable emission monitor that meets District specifications. [In-stack O2 monitors may be allowed if approved by the APCO.] Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702]

21. If either the NOx or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the allowable emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4701 and 4702]

22. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701 and 4702]

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702]

24. All records shall be retained for a minimum of 5 years, and shall be made available for District inspection upon request. [District Rule 1070]

25. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100]

26. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100]

27. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020. [District Rule 2010, 3.0, 4.0, and 2020]

28. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

29. Every application for a permit required under Rule 2010 (Permits Required) shall be filed in a manner and form prescribed by the District. [District Rule 2040]

30. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2080]

31. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2080]

32. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. [District Rule 1100, 7.0]

33. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit . [District Rule 1080]

34. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2080]

35. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 3010]

36. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2080]

37. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2080]

38. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2080]

39. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2080]

40. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101, by using EPA method 9. If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101]

41. Formerly S-3507-17.

42. Formerly S-382-805.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-72-0 **EXPIRATION DATE:** 08/31/2010

EQUIPMENT DESCRIPTION:
16,000 BBL FIXED ROOF PRODUCTION TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON WITH S-1216-64

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
4. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
5. Tank roof appurtenances shall be maintained leak free. [District Rule 4623]
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
7. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)]
8. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)]
9. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) eliminate or minimize the leak within 8 hours after detection, (b) if the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices and eliminate the leak within 48 hours after detection. In no event shall the total time to minimize and eliminate the leak exceed 56 hours after detection. [District Rule 4623, 5.7 9 (Table 3)]
10. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Operator shall maintain an inspection log containing the following 1) type of component leaking; 2) date and time of leak detection, and method of detection; 3) date and time of leak repair, and emission level of recheck after leak is repaired; 4) method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 1070]
12. The efficiency of any VOC destruction device shall be measured by EPA Method 25, 25a, or 25b. [District Rule 4623, 6.4.7]
13. Except as otherwise provided in this permit, operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rules 4623 and 2201]
14. VOC emission rate from vapor, light liquid, and light crude oil components associated with vapor recovery piping shall not exceed 0.1 lb/day. [District Rule 2201]
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance but occurs as a routine maintenance activity. [District Rule 2020]
16. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7]
17. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623, 5.7]
18. Permittee shall maintain accurate records of fugitive emissions and such records shall be made readily available for District inspection upon request for a period of five years. [District Rule 2201]
19. All records shall be maintained for a period of at least five years and made available for District inspection upon request. [District Rule 1070]
20. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-73-0 **EXPIRATION DATE:** 08/31/2010

EQUIPMENT DESCRIPTION:
1,500 BBL FIXED ROOF PRODUCTION TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON S-1216-64

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
4. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
5. Tank roof appurtenances shall be maintained leak free. [District Rule 4623]
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
7. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)]
8. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)]
9. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) eliminate or minimize the leak within 8 hours after detection, (b) if the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices and eliminate the leak within 48 hours after detection. In no event shall the total time to minimize and eliminate the leak exceed 56 hours after detection. [District Rule 4623, 5.7 9 (Table 3)]
10. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Operator shall maintain an inspection log containing the following 1) type of component leaking; 2) date and time of leak detection, and method of detection; 3) date and time of leak repair, and emission level of recheck after leak is repaired; 4) method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 1070]
12. The efficiency of any VOC destruction device shall be measured by EPA Method 25, 25a, or 25b. [District Rule 4623, 6.4.7]
13. Except as otherwise provided in this permit, operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rules 4623 and 2201]
14. VOC emission rate from vapor, light liquid, and light crude oil components associated with vapor recovery piping shall not exceed 0.3 lb/day. [District Rule 2201]
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance but occurs as a routine maintenance activity. [District Rule 2020]
16. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7]
17. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623, 5.7]
18. Permittee shall maintain accurate records of fugitive emissions and such records shall be made readily available for District inspection upon request for a period of five years. [District Rule 2201]
19. All records shall be maintained for a period of at least five years and made available for District inspection upon request. [District Rule 1070]
20. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-75-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE23 **TOWNSHIP:** 30S **RANGE:** 22E

EQUIPMENT DESCRIPTION:
1,500 BBL FIXED ROOF CRUDE OIL TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON S-1216-64 (REVISED 2/4/08)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
4. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
5. Tank roof appurtenances shall be maintained leak free. [District Rule 4623]
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
7. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)]
8. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)]
9. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) eliminate or minimize the leak within 8 hours after detection, (b) if the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices and eliminate the leak within 48 hours after detection. In no event shall the total time to minimize and eliminate the leak exceed 56 hours after detection. [District Rule 4623, 5.7 9 (Table 3)]
10. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Operator shall maintain an inspection log containing the following 1) type of component leaking; 2) date and time of leak detection, and method of detection; 3) date and time of leak repair, and emission level of recheck after leak is repaired; 4) method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 1070]
12. The efficiency of any VOC destruction device shall be measured by EPA Method 25, 25a, or 25b. [District Rule 4623, 6.4.7]
13. Except as otherwise provided in this permit, operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rules 4623 and 2201]
14. VOC emission rate from vapor, light liquid, and light crude oil components associated with vapor recovery piping shall not exceed 0.3 lb/day. [District Rule 2201]
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance but occurs as a routine maintenance activity. [District Rule 2020]
16. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7]
17. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623, 5.7]
18. Permittee shall maintain accurate records of fugitive emissions and such records shall be made readily available for District inspection upon request for a period of five years. [District Rule 2201]
19. All records shall be maintained for a period of at least five years and made available for District inspection upon request. [District Rule 1070]
20. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-78-0 **EXPIRATION DATE:** 08/31/2010

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF SLOP OIL TANK SERVED BY A VAPOR CONTROL SYSTEM LISTED ON S-1216-64

PERMIT UNIT REQUIREMENTS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. This Authority to Construct (ATC) cancels and supersedes ATC S-1216-74-0. [District Rule 2201]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
4. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
5. VOC emission rate associated with this tank, up to the tie-in with the vapor recovery unit trunk-line, shall not exceed 0.1 lb/day. [District Rule 2201]
6. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
7. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
9. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
10. Tank roof appurtenances shall be maintained leak free. [District Rule 4623]
11. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
12. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)]
13. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) eliminate or minimize the leak within 8 hours after detection, (b) if the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices and eliminate the leak within 48 hours after detection. In no event shall the total time to minimize and eliminate the leak exceed 56 hours after detection. [District Rule 4623, 5.7 9 (Table 3)]
15. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)]
16. Operator shall maintain an inspection log containing the following 1) type of component leaking; 2) date and time of leak detection, and method of detection; 3) date and time of leak repair, and emission level of recheck after leak is repaired; 4) method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 1070]
17. The efficiency of any VOC destruction device shall be measured by EPA Method 25, 25a, or 25b. [District Rule 4623, 6.4.7]
18. Except as otherwise provided in this permit, operator shall ensure that the vapor control system is functional and is operating as designed at all times. [District Rules 4623 and 2201]
19. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance but occurs as a routine maintenance activity. [District Rule 2020]
20. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7]
21. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623, 5.7]
22. Permittee shall maintain accurate records of fugitive emissions and such records shall be made readily available for District inspection upon request for a period of five years. [District Rule 2201]
23. All records shall be maintained for a period of at least five years and made available for District inspection upon request. [District Rule 1070]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-85-1 **EXPIRATION DATE:** 08/31/2010

EQUIPMENT DESCRIPTION:
17.5 MMBTU PORTABLE LPG-FIRED STEAM GENERATOR WITH NORTH AMERICAN 4211 GLE BURNER AND FLUE GAS RECIRCULATION

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct (ATC) for such modifications, except for changes specified in the conditions below. [District Rule 4306]
2. The fuel supply line shall be physically disconnected from this unit [District Rule 4306]
3. Operator shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit. [District Rule 4306]
4. When designated as a dormant emissions unit, the permittee shall not be required to perform source testing or monitoring requirements otherwise required by this permit. [District Rule 4306]
5. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 4306]
6. This unit may not be operated after the applicable compliance schedule from Rule 4320, unless a valid ATC is implemented that approves the changes allowing this unit to comply with the applicable requirements of Rule 4320. [District Rule 4320]
7. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
8. The equipment shall not be located within 1,000 feet of any K-12 school. [CH&SC 42301.6]
9. Upon recommencing operation, flue gas recirculation system shall be operational at all times. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Steam generator shall be fired exclusively on LPG and shall have no provisions for firing on fuel oil. [District NSR Rule] Federally Enforceable Through Title V Permit
11. Emission rates shall not exceed any of the following: PM10: 0.006 lb/MMBtu, SOx (as SO2): 0.001 lb/MMBtu, NOx (as NO2): 14 ppmv @ 3% O2, VOC: 0.003 lb/MMBtu or CO: 25 ppmv @ 3% O2. [District NSR Rule] Federally Enforceable Through Title V Permit
12. Upon recommencing operation, tests for SOx emissions shall be conducted at least once every 12 months by fuel gas sulfur content analysis and higher heating value analysis of fuel source. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted under conditions representative of normal operation. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Source tests for NOx and CO emissions shall be conducted at least once every 12 months. If compliance is demonstrated on two consecutive annual tests, frequency for NOx and CO source tests shall be reduced to at least once every 36 months. If permittee fails any compliance demonstration for NOx and/or CO emission limits when testing at least once every 36 months, frequency for NOx and CO source tests shall be increased to at least once every 12 months. [District NSR Rule and District Rule 4305] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

15. Annual test results submitted to the District from unit(s) representing a group of units may be used to measure NOx and CO emissions of this permit for that group, provided the selection of the representative unit(s) is approved by the APCO prior to testing. Should any of the representative units exceed the required NOx emission limits of this permit, each of the units in the group shall demonstrate compliance by emissions testing within 90 days of the failed test. [District Rules 4305, 6.3.2 and 4351, 6.3] Federally Enforceable Through Title V Permit

16. The following conditions must be met for representative unit(s) to be used to test for NOx and CO limits for a group of units: 1) all units are initially source tested and emissions from each unit in group are less than 90% of the permitted value and vary 25% or less from the average of all runs, 2) all units in group are similar in terms of rated heat input (rating not to exceed 100 MMBtu/hr), make and series, operation conditions, and control method, and 3) the group is owned by a single owner and located at a single stationary source. [District Rules 2520, 9.3.2 and 4305,6.3.2] Federally Enforceable Through Title V Permit

17. All units in a group for which representative units are source for NOx and CO emissions shall have received the same maintenance and tune-up procedures as the representative unit(s). These tune-up procedures shall be completed according to District Rule 4304 (Adopted October 19, 1995) and tune-up test results shall show comparable results for each unit in the group. Records shall be maintained for the each unit of the group including all preventative and corrective maintenance work done. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

18. All units in a group for which representative units are source tested to for NOx and CO emissions of this permit shall be fired on the same fuel type during the entire compliance period. If a unit switches for any time to an alternate fuel type (e.g. from natural gas to oil) then that unit shall not be considered part of the group and shall be required to undergo a source test for all fuel types used, within one year of the switch. [District Rules 2520, 9.3.2 and 4305, 6.3.2] Federally Enforceable Through Title V Permit

19. The number of representative units source tested for NOx and CO emissions shall be at least 30% of the total number of units in the group. The units included in the 30% shall be rotated, so that in 3 years, all units in the entire group will have been tested at least once. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Sample collection for source testing shall be District witnessed, or authorized, and be conducted by an ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

21. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

22. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

23. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, and fuel gas sulfur content - ASTM D3246 or double GC for H2S and mercaptans. [District Rules 1081, 4305] Federally Enforceable Through Title V Permit

24. Upon recommencing operation the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every month using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the unit unless monitoring has been performed within the last month. [District Rule 4305] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. If the NOX and/or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rule 4305] Federally Enforceable Through Title V Permit

26. Upon recommencing operation the permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rule 4305] Federally Enforceable Through Title V Permit

27. The permittee shall notify the District Compliance Division of each location at which the operation is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070] Federally Enforceable Through Title V Permit

28. Pursuant to Rule 4320, beginning in 2010 the operator shall pay an annual emission fee to the District for NOx emissions from this unit for the previous calendar year. Payments are due by July 1 of each year. Payments shall continue annually until either the unit is permanently removed from service in the District or the operator demonstrates compliance with the applicable NOx emission limit listed in Rule 4320. [District Rule 4320]

29. Permittee shall maintain records of annual heat input (MMBtu) for this unit on a calendar year basis. Such records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and Rule 4320]

30. On and after July 1, 2012, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contacts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320]

31. Formerly S-382-704-1. [District NSR Rule]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-86-0 **EXPIRATION DATE:** 08/31/2010

EQUIPMENT DESCRIPTION:
100 BBL FIXED FIXED ROOF PRODUCTION TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH-1212-48

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [40 CFR 60.112a]
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2]
3. Collected vapors shall be discharged only to vapor control system listed on S-1216-48. [District Rule 2201]
4. Fugitive VOC emissions rate shall be, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District NSR Rule]
5. VOC emission rate from the components in gas and light oil service associated with this tank, up to the tie-in with the vapor recovery unit trunk-line, shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All piping, valves and other fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.3.3]
7. A leak free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)]
9. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)]
10. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)]
12. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)]
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)]
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623]
15. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in EPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 4623, 6.2.4]
16. The efficiency of any VOC destruction device shall be measured by EPA Method 25, 25a, or 25b, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4623, 6.2.5]
17. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rules 2201 and 4623]
18. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance but occurs as a routine maintenance activity. [District Rule 2020]
19. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7]
20. Permittee shall comply with all applicable Tank Interior Cleaning Program requirements specified in Table 6 of Rule 4623. [District Rule 4623, 5.7]
21. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule 2201]
22. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 4623]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-87-1 **EXPIRATION DATE:** 08/31/2010

SECTION: 29 **TOWNSHIP:** 30S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
44.58 MMBTU/HR WELL SAFETY FLARE AUTHORIZED TO OPERATE AT VARIOUS UNSPECIFIED LOCATIONS WITHIN THE LIGHT OIL WESTERN STATIONARY SOURCE

PERMIT UNIT REQUIREMENTS

1. The permittee shall notify the District Compliance Division of each location at which the operation is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070]
2. The flare shall not operate within 2300 feet of any receptor. [District Rule 4102]
3. Flare shall not be located within 1000 ft of a school. [District Rule CH&SC 42301.6]
4. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)]
5. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)]
6. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0]
7. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020]
8. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031]
9. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040]
10. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1]

12. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4]

13. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3]

14. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F]

15. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B]

16. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8021 and 8011]

17. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8031 and 8011]

18. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8041 and 8011]

19. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8051 and 8011]

20. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8061 and Rule 8011]

21. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8071 and Rule 8011]

22. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M]

23. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

24. When applicable to 40 CFR Part 68, a subject facility shall submit to the proper authority a Risk Management Plan, and comply with all the requirements of Program 1, 2, or 3 when mandated by the regulation. [40 CFR Part 68]

25. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4409, 5.1.1]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

26. For valves, threaded connections, flanges, pipes, pumps, compressors, and other components subject to the requirements of Rule 4409, but not specified in this permit; a major gas leak is a detection of > *10,000* ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 2,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1]

27. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1]

28. For polished rod stuffing boxes (PRSBs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1]

29. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.2]

30. Minor gas leaks from PRSBs detected during any District inspection shall not be counted toward determination of compliance with this rule provided the permittee repairs, replaces, or removes leaking PRSBs from VOC service as soon as practicable but not later than seven calendar days. [District Rule 4409, 5.1.3.1.2]

31. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4409 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4409. [District Rule 4409, 5.1.3.2.1 and 5.1.3.2.2]

32. Leaking components at this facility detected during annual operator inspections, as required by Rule 4409 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4409, 5.1.3.2.3]

33. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.4.1]

34. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4409, 5.1.4.2]

35. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4409, 5.1.4.3]

36. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4409, 5.1.4.4]

37. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

38. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

39. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

40. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

41. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

42. When 200 or fewer PRSBs are inspected, a leak is when more than four have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 PRSBs are inspected, a leak is when more than 2.0 % (rounded up to the nearest whole number) of the PRSBs have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

43. When 200 or fewer wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than two or more pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than 1.0 % (rounded up to the nearest whole number) of the pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

44. When pipes at natural gas processing facilities are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4]

45. For manned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4409, 5.2.1]

46. For unmanned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once per calendar week. [District Rule 4409, 5.2.2]

47. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.3]

48. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4409, 5.2.4]

49. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4409, 5.2.5]

50. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4409, 5.2.6]

51. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4409, 5.2.7]

52. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4409, 5.2.8]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

53. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.8.1]

54. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4409. [District Rule 4409, 5.2.8.2]

55. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4409, 5.2.9 and 5.2.10]

56. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4409, 5.2.11]

57. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4409, 5.2.12]

58. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4409, 5.2.13]

59. District inspections shall not be counted as an operator inspection required by District Rule 4409. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4409, 5.2.14]

60. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4409, 5.3.1]

61. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4409, 5.3.4 and 5.3.5]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

62. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4409, 5.3.4 and 5.3.5]

63. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4409, 5.3.5]

64. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4409 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4409, 5.3.6]

65. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4409, 5.3.7]

66. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4409, 5.4.1]

67. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4409, 6.1.2]

68. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4409, 6.1.4]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

69. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4409, 6.2.1]
70. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4409, 6.2.2]
71. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4409, 6.2.3]
72. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4409, 6.2.4]
73. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4409, 6.3.1]
74. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4409, 6.3.2]
75. The percent by volume liquid evaporated at 302 øF (150 øC) shall be determined using ASTM D-86. [District Rule 4409, 6.3.3]
76. The TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D-323, and converting the RVP to TVP at the maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures specified in Appendix A of District Rule 4409. [District Rule 4409, 6.3.4]
77. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM D-287 or ASTM 1298. Sampling for API gravity shall be performed in accordance with ASTM D-4057. [District Rule 4409, 6.3.5]
78. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4409, 6.3.6]
79. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4409, 6.3.7]
80. Formerly S-382-409-4. [District NSR Rule]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-88-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 29 **TOWNSHIP:** 30S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
44.58 MMBTU/HR EMERGENCY WELL SAFETY FLARE

PERMIT UNIT REQUIREMENTS

1. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period. The operator shall test the sulfur content of the gases being flared and demonstrate the sulfur content does not exceed 3.3% by weight. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
2. To show compliance with sulfur emission limits, the gas being flared shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for the flared gas, then the compliance testing frequency shall be semi-annually. If a semi-annual sulfur content test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
3. The sulfur content of the gas being flared shall be determined using ASTM D 1072-80,D 3031-81, D 4084-82, D 3246-81 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
4. The fuel higher heating value for the gases being flared shall be certified by third party fuel supplier or determined by ASTM D 1826-88 or D 1945-81 in conjunction with ASTM D 3588-89. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
5. The permittee shall maintain accurate records of gas volume flared. These records and all records of required monitoring data and support information shall be maintained and retained for a period of 5 years and made available for inspection at any time. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. If this flare requires a pilot flame, then the flare shall be operated with a flame present at all times, and kept in operation when emissions may be vented to it. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. This flare shall not be used as a leak control device as described in Rule 4403, 5.3.1, nor as a control device for any permit unit subject to NSPS, without modification of permit requirements to address 40 CFR 60.18. [District Rule 2520, 9.4.3] Federally Enforceable Through Title V Permit
8. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

10. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

11. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

12. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

13. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

14. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

15. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

16. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

17. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

18. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

19. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

20. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

22. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

23. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

24. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

25. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

26. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

27. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

28. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

29. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

30. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

31. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

32. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

33. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

34. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

36. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

37. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

38. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

39. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

40. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

41. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

42. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

43. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

44. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

45. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

46. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (9/17/2004); 8031 (9/17/2004); 8041 (9/17/2004); 8051 (9/17/2004); 8061 (9/17/2004); and 8071 (9/17/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

48. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

49. When applicable to 40 CFR Part 68, a subject facility shall submit to the proper authority a Risk Management Plan, and comply with all the requirements of Program 1, 2, or 3 when mandated by the regulation. [40 CFR Part 68] Federally Enforceable Through Title V Permit

50. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

51. For valves, threaded connections, flanges, pipes, pumps, compressors, and other components subject to the requirements of Rule 4409, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 2,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

52. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

53. For polished rod stuffing boxes (PRSBs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

54. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.2] Federally Enforceable Through Title V Permit

55. Minor gas leaks from PRSBs detected during any District inspection shall not be counted toward determination of compliance with this rule provided the permittee repairs, replaces, or removes leaking PRSBs from VOC service as soon as practicable but not later than seven calendar days. [District Rule 4409, 5.1.3.1.2] Federally Enforceable Through Title V Permit

56. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4409 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4409. [District Rule 4409, 5.1.3.2.1 and 5.1.3.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

57. Leaking components at this facility detected during annual operator inspections, as required by Rule 4409 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4409, 5.1.3.2.3] Federally Enforceable Through Title V Permit

58. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.4.1] Federally Enforceable Through Title V Permit

59. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4409, 5.1.4.2] Federally Enforceable Through Title V Permit

60. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4409, 5.1.4.3] Federally Enforceable Through Title V Permit

61. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

62. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

63. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

64. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

65. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

66. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

67. When 200 or fewer PRSBs are inspected, a leak is when more than four have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 PRSBs are inspected, a leak is when more than 2.0 % (rounded up to the nearest whole number) of the PRSBs have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

68. When 200 or fewer wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than two or more pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than 1.0 % (rounded up to the nearest whole number) of the pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

69. When pipes at natural gas processing facilities are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

70. For manned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4409, 5.2.1] Federally Enforceable Through Title V Permit

71. For unmanned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once per calendar week. [District Rule 4409, 5.2.2] Federally Enforceable Through Title V Permit

72. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.3] Federally Enforceable Through Title V Permit

73. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4409, 5.2.4] Federally Enforceable Through Title V Permit

74. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4409, 5.2.5] Federally Enforceable Through Title V Permit

75. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4409, 5.2.6] Federally Enforceable Through Title V Permit

76. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4409, 5.2.7] Federally Enforceable Through Title V Permit

77. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4409, 5.2.8] Federally Enforceable Through Title V Permit

78. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.8.1] Federally Enforceable Through Title V Permit

79. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4409. [District Rule 4409, 5.2.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

80. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4409, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit

81. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4409, 5.2.11] Federally Enforceable Through Title V Permit

82. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4409, 5.2.12] Federally Enforceable Through Title V Permit

83. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4409, 5.2.13] Federally Enforceable Through Title V Permit

84. District inspections shall not be counted as an operator inspection required by District Rule 4409. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4409, 5.2.14] Federally Enforceable Through Title V Permit

85. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4409, 5.3.1] Federally Enforceable Through Title V Permit

86. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit

87. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

88. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4409, 5.3.5] Federally Enforceable Through Title V Permit

89. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4409 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4409, 5.3.6] Federally Enforceable Through Title V Permit

90. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4409, 5.3.7] Federally Enforceable Through Title V Permit

91. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4409, 5.4.1] Federally Enforceable Through Title V Permit

92. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4409, 6.1.2] Federally Enforceable Through Title V Permit

93. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4409, 6.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

94. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4409, 6.2.1] Federally Enforceable Through Title V Permit

95. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4409, 6.2.2] Federally Enforceable Through Title V Permit

96. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4409, 6.2.3] Federally Enforceable Through Title V Permit

97. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4409, 6.2.4] Federally Enforceable Through Title V Permit

98. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4409, 6.3.1] Federally Enforceable Through Title V Permit

99. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4409, 6.3.2] Federally Enforceable Through Title V Permit

100. The percent by volume liquid evaporated at 302 øF (150 øC) shall be determined using ASTM D-86. [District Rule 4409, 6.3.3] Federally Enforceable Through Title V Permit

101. The TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D-323, and converting the RVP to TVP at the maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures specified in Appendix A of District Rule 4409. [District Rule 4409, 6.3.4] Federally Enforceable Through Title V Permit

102. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM D-287 or ASTM 1298. Sampling for API gravity shall be performed in accordance with ASTM D-4057. [District Rule 4409, 6.3.5] Federally Enforceable Through Title V Permit

103. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4409, 6.3.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

104. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4409, 6.3.7] Federally Enforceable Through Title V Permit

105. For vapor recovery systems connected to tanks with pressure relief valves, operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

106. For tanks equipped with pressure relief valves, operator shall inspect pressure relief valves for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

107. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon June 1 of each year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days of the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

108. Formerly S-382-410-3. [District NSR Rule]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-89-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 29 **TOWNSHIP:** 30S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
0.028 MMBTU/HR TANK VAPOR RECOVERY SYSTEM FLARE

PERMIT UNIT REQUIREMENTS

1. The concentration of sulfur compounds in the exhaust from this unit shall not exceed 0.2% by volume as measured on a dry basis over a 15 minute period. The operator shall test the sulfur content of the gases being flared and demonstrate the sulfur content does not exceed 3.3% by weight. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
2. To show compliance with sulfur emission limits, the gas being flared shall be tested weekly for sulfur content and higher heating value. If compliance with the fuel sulfur content limit and sulfur emission limits has been demonstrated for 8 consecutive weeks for the flared gas, then the compliance testing frequency shall be semi-annually. If a semi-annual sulfur content test fails to show compliance, weekly testing shall resume. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
3. The sulfur content of the gas being flared shall be determined using ASTM D 1072-80,D 3031-81, D 4084-82, D 3246-81 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
4. The fuel higher heating value for the gases being flared shall be certified by third party fuel supplier or determined by ASTM D 1826-88 or D 1945-81 in conjunction with ASTM D 3588-89. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
5. The permittee shall maintain accurate records of gas volume flared. These records and all records of required monitoring data and support information shall be maintained and retained for a period of 5 years and made available for inspection at any time. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. If this flare requires a pilot flame, then the flare shall be operated with a flame present at all times, and kept in operation when emissions may be vented to it. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. This flare shall not be used as a leak control device as described in Rule 4403, 5.3.1, nor as a control device for any permit unit subject to NSPS, without modification of permit requirements to address 40 CFR 60.18. [District Rule 2520, 9.4.3] Federally Enforceable Through Title V Permit
8. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

10. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

11. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

12. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

13. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

14. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

15. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

16. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

17. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

18. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

19. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

20. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

22. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

23. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

24. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

25. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

26. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

27. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

28. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

29. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

30. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

31. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

32. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

33. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

34. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

36. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

37. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

38. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

39. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

40. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

41. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/17/2004) or Rule 8011 (9/17/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

42. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

43. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

44. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

45. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

46. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

47. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (9/17/2004); 8031 (9/17/2004); 8041 (9/17/2004); 8051 (9/17/2004); 8061 (9/17/2004); and 8071 (9/17/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

48. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

49. When applicable to 40 CFR Part 68, a subject facility shall submit to the proper authority a Risk Management Plan, and comply with all the requirements of Program 1, 2, or 3 when mandated by the regulation. [40 CFR Part 68] Federally Enforceable Through Title V Permit

50. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

51. For valves, threaded connections, flanges, pipes, pumps, compressors, and other components subject to the requirements of Rule 4409, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 2,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

52. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

53. For polished rod stuffing boxes (PRSBs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

54. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.2] Federally Enforceable Through Title V Permit

55. Minor gas leaks from PRSBs detected during any District inspection shall not be counted toward determination of compliance with this rule provided the permittee repairs, replaces, or removes leaking PRSBs from VOC service as soon as practicable but not later than seven calendar days. [District Rule 4409, 5.1.3.1.2] Federally Enforceable Through Title V Permit

56. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4409 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4409. [District Rule 4409, 5.1.3.2.1 and 5.1.3.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

57. Leaking components at this facility detected during annual operator inspections, as required by Rule 4409 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4409, 5.1.3.2.3] Federally Enforceable Through Title V Permit

58. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.4.1] Federally Enforceable Through Title V Permit

59. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4409, 5.1.4.2] Federally Enforceable Through Title V Permit

60. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4409, 5.1.4.3] Federally Enforceable Through Title V Permit

61. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

62. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

63. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

64. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

65. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

66. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

67. When 200 or fewer PRSBs are inspected, a leak is when more than four have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 PRSBs are inspected, a leak is when more than 2.0 % (rounded up to the nearest whole number) of the PRSBs have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

68. When 200 or fewer wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than two or more pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than 1.0 % (rounded up to the nearest whole number) of the pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

69. When pipes at natural gas processing facilities are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

70. For manned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4409, 5.2.1] Federally Enforceable Through Title V Permit

71. For unmanned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once per calendar week. [District Rule 4409, 5.2.2] Federally Enforceable Through Title V Permit

72. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.3] Federally Enforceable Through Title V Permit

73. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4409, 5.2.4] Federally Enforceable Through Title V Permit

74. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4409, 5.2.5] Federally Enforceable Through Title V Permit

75. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4409, 5.2.6] Federally Enforceable Through Title V Permit

76. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4409, 5.2.7] Federally Enforceable Through Title V Permit

77. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4409, 5.2.8] Federally Enforceable Through Title V Permit

78. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.8.1] Federally Enforceable Through Title V Permit

79. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4409. [District Rule 4409, 5.2.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

80. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4409, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit

81. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4409, 5.2.11] Federally Enforceable Through Title V Permit

82. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4409, 5.2.12] Federally Enforceable Through Title V Permit

83. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4409, 5.2.13] Federally Enforceable Through Title V Permit

84. District inspections shall not be counted as an operator inspection required by District Rule 4409. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4409, 5.2.14] Federally Enforceable Through Title V Permit

85. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4409, 5.3.1] Federally Enforceable Through Title V Permit

86. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit

87. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

88. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4409, 5.3.5] Federally Enforceable Through Title V Permit

89. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4409 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4409, 5.3.6] Federally Enforceable Through Title V Permit

90. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4409, 5.3.7] Federally Enforceable Through Title V Permit

91. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4409, 5.4.1] Federally Enforceable Through Title V Permit

92. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4409, 6.1.2] Federally Enforceable Through Title V Permit

93. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4409, 6.1.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

94. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4409, 6.2.1] Federally Enforceable Through Title V Permit

95. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4409, 6.2.2] Federally Enforceable Through Title V Permit

96. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4409, 6.2.3] Federally Enforceable Through Title V Permit

97. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4409, 6.2.4] Federally Enforceable Through Title V Permit

98. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4409, 6.3.1] Federally Enforceable Through Title V Permit

99. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4409, 6.3.2] Federally Enforceable Through Title V Permit

100. The percent by volume liquid evaporated at 302 øF (150 øC) shall be determined using ASTM D-86. [District Rule 4409, 6.3.3] Federally Enforceable Through Title V Permit

101. The TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D-323, and converting the RVP to TVP at the maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures specified in Appendix A of District Rule 4409. [District Rule 4409, 6.3.4] Federally Enforceable Through Title V Permit

102. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM D-287 or ASTM 1298. Sampling for API gravity shall be performed in accordance with ASTM D-4057. [District Rule 4409, 6.3.5] Federally Enforceable Through Title V Permit

103. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4409, 6.3.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

104. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4409, 6.3.7] Federally Enforceable Through Title V Permit

105. For vapor recovery systems connected to tanks with pressure relief valves, operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

106. For tanks equipped with pressure relief valves, operator shall inspect pressure relief valves for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

107. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon June 1 of each year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days of the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

108. Formerly S-382-411-3. [District NSR Rule]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-93-1 **EXPIRATION DATE:** 08/31/2010

SECTION: 36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
42,000 GALLON FIXED ROOF WASH TANK SERVED BY A VAPOR RECOVERY SYSTEM (SHARED WITH S-1216-94, 108, 109, 110)

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-2-0. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
3. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule]
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623]
5. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623]
7. VOC fugitive emissions from the components in gas service on tank and tank vapor collection system shall not exceed 0.16 lb/day. [District Rule 2201]
8. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201]
9. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201]
10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623]
11. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623]

13. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 1070]

14. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

17. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

18. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

19. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

20. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

21. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

22. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

23. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

24. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

26. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

27. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

28. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

29. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

30. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

31. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

32. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

36. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

37. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

38. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

39. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

40. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

41. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

42. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

43. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

44. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

45. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

46. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

47. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

48. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

49. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

50. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

51. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

52. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

53. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

54. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

55. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

56. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

57. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

58. Facilities S-1216, S-382, and S-1738 constitute one stationary source. [District Rule 2201]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-94-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
3,300 BBL FIXED ROOF WASH TANK SERVED BY A VAPOR RECOVERY SYSTEM

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-7-0. [District NSR Rule]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
5. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

11. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

15. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

16. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

17. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

18. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

19. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

20. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

21. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

22. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

24. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

25. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

26. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

27. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

28. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

29. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

30. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

31. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

35. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

37. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

38. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

39. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

40. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

41. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

42. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

43. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

44. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

45. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

46. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

47. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

48. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

50. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

51. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

52. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

55. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

56. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-95-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
WATERFLOOD PLANT/WATER CLEANING AND INJECTION OPERATION INCLUDING ONE 5,000 BBL WASH TANK (T1) SERVED BY A VAPOR CONTROL SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-17-0. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Crude oil throughput of gauging/cleaning plant shall not exceed 1,800 bbl/day. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The operation shall include up to 6 liquid transfer pumps. [District Rule 2010] Federally Enforceable Through Title V Permit
4. The operation shall include vapor piping from tanks T1 (S-1216-95), T2 (S-1216-135), T3 (S-1216-96), T4 (S-1216-98), T5 (S-1216-97), T6 (S-1216-133), T7 (S-1216-134), T8 (S-1216-136) and Wemco (S-1216-132) to 1 C gas plant (S-48) collection system. [District Rule 2010] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rules 2201 and 4623, 5.3.1] Federally Enforceable Through Title V Permit
6. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
7. VOC content of hydrocarbons in gas shall not exceed 37% by weight. Permittee shall sample and record the VOC content of hydrocarbons at least once every 12 months. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
8. VOC content of gas shall be determined by ASTM D1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Fugitive VOC emissions rate shall be, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC fugitive emissions from the components in gas service on the tank shall not exceed 0.063 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
11. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

13. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

14. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

15. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

16. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

17. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

21. Interior tank cleaning shall be performed in accordance with provisions specified in Table 6 of Rule 4623. [District Rules 2201 & 4623] Federally Enforceable Through Title V Permit

22. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit

24. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

26. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

27. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

28. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

29. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

30. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

31. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

32. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

33. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

34. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

35. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

36. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

38. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

39. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

40. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

41. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

42. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

43. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

44. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

45. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

46. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

47. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

48. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

49. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

50. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

51. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

52. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

53. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

54. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

55. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

56. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

57. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

58. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

59. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

60. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

61. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

62. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

63. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

64. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

65. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

66. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

67. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

68. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-96-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED ROOF STORAGE/SHIPPING TANK (#3) SERVED BY A VAPOR RECOVERY SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-18-0. [District NSR Rule]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
5. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

11. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

15. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

16. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

17. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

18. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

19. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

20. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

21. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

23. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

24. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

25. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

26. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

27. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

28. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

29. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

30. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

31. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

36. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

37. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

38. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

39. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

40. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

41. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

42. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

43. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

44. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

45. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

46. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

47. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

49. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

50. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

51. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

52. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

55. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

56. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-97-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1,000 BBL FIXED ROOF FILTER FEED TANK (T5) SERVED BY A VAPOR CONTROL SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-19-0. [District NSR Rule]
2. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rules 2201 and 4623, 5.3.1] Federally Enforceable Through Title V Permit
3. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
4. VOC content of hydrocarbons in gas shall not exceed 37% by weight. Permittee shall sample and record the VOC content of hydrocarbons at least once every 12 months. [District Rules 1070 and 2201]
5. VOC content of gas shall be determined by ASTM D1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201]
6. Fugitive VOC emissions rate shall be, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
7. VOC fugitive emissions from the components in gas service on the tank shall not exceed 0.026 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
10. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
12. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
14. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
18. Interior tank cleaning shall be performed in accordance with provisions specified in Table 6 of Rule 4623. [District Rules 2201 & 4623] Federally Enforceable Through Title V Permit
19. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
20. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
21. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
22. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit
23. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

25. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

26. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

27. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

28. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

29. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

30. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

31. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

32. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

33. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

34. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

35. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

37. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

38. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

39. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

40. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

41. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

42. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

43. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

44. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

45. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

46. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

47. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

48. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

49. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

50. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

51. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

52. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

53. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

54. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

55. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

56. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

57. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

58. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

59. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

60. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

61. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

62. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

63. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

64. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

65. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-98-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
2,000 BBL FIXED CRUDE OIL PRODUCTION TANK (T4) SERVED BY A VAPOR CONTROL SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-21-0. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rules 2201 and 4623, 5.3.1] Federally Enforceable Through Title V Permit
3. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
4. VOC content of hydrocarbons in gas shall not exceed 37% by weight. Permittee shall sample and record the VOC content of hydrocarbons at least once every 12 months. [District Rules 1070 and 2201]
5. VOC content of gas shall be determined by ASTM D1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201]
6. Fugitive VOC emissions rate shall be, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
7. VOC fugitive emissions from the components in gas service on the tank shall not exceed 0.026 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
10. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

12. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

13. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

14. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

18. Interior tank cleaning shall be performed in accordance with provisions specified in Table 6 of Rule 4623. [District Rules 2201 & 4623] Federally Enforceable Through Title V Permit

19. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit

21. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit

22. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

23. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

25. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

26. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

27. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

28. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

29. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

30. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

31. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

32. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

33. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

34. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

35. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

37. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

38. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

39. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

40. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

41. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

42. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

43. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

44. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

45. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

46. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

47. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

48. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

49. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

50. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

51. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

52. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

53. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

54. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

55. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

56. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

57. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

58. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

59. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

60. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

61. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

62. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

63. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

64. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

65. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-100-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
532 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH TANKS S-1216-101, '-102, '-103, '-104, AND '-105

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-65-1. [District NSR Rule]
2. Tank shall be equipped with temperature indicator. [District Rule 4623, 6.2.1.1.5, 6.2.1.2, 6.3.1, 6.4.5] Federally Enforceable Through Title V Permit
3. Tank vapors shall vent only through collection system and discharge only to gas gathering line. [District NSR Rule] Federally Enforceable Through Title V Permit
4. Tank vapor control system shall include interconnecting piping between tanks, liquid knock out vessel, pressure control valve, emergency relief valves, piping connecting to gas gathering system. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Pressure relief valves setting shall be higher than that required to activate vapor compressor. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
6. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
7. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
8. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
9. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
10. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

12. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

15. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

18. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

19. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

20. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

21. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

23. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

24. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

25. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

26. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

27. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

28. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

29. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

30. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

31. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

32. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

33. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

36. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

37. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

38. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

39. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

40. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

41. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

42. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

43. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

44. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

45. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

46. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

47. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

48. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

50. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

51. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

52. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

53. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

54. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

55. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

56. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

57. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

58. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

59. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-101-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1,968 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM AT S-3079-19 SHARED WITH S-1216-100, '-102, '-103, '-104, AND '-105

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-66-1. [District NSR Rule]
2. Tank shall be equipped with temperature indicator. [District Rule 4623, 6.2.1.1.5, 6.2.1.2, 6.3.1, 6.4.5] Federally Enforceable Through Title V Permit
3. Tank vapors shall vent to control system on permit S-1216-100. [District Rule 4623, 5.1.2 and 5.6.1] Federally Enforceable Through Title V Permit
4. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

11. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

16. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

17. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

18. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

19. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

20. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

21. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

22. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

25. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

26. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

27. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

28. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

29. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

30. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

31. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

37. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

38. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

39. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

40. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

41. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

42. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

43. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

44. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

45. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

46. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

47. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

48. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

50. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

51. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

52. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

55. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

56. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

57. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-102-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
532 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM AT S-1216-100 SHARED WITH S-1216-100, '-101, '-103, '-104, AND '-105

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-67-1. [District NSR Rule]
2. Tank shall be equipped with temperature indicator. [District Rule 4623, 6.2.1.1.5, 6.2.1.2, 6.3.1, 6.4.5] Federally Enforceable Through Title V Permit
3. Tank vapors shall vent to control system on permit S-1216-100. [District Rule 4623, 5.1.2 and 5.6.1] Federally Enforceable Through Title V Permit
4. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

11. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

16. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

17. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

18. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

19. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

20. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

21. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

22. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

25. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

26. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

27. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

28. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

29. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

30. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

31. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

37. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

38. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

39. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

40. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

41. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

42. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

43. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

44. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

45. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

46. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

47. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

48. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

50. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

51. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

52. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

55. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

56. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

57. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-103-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1,968 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-100, -101, '-102, '-104, AND '-105

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-68-1. [District NSR Rule]
2. Tank shall be equipped with temperature indicator. [District Rule 4623, 6.2.1.1.5, 6.2.1.2, 6.3.1, 6.4.5] Federally Enforceable Through Title V Permit
3. Tank vapors shall vent to control system on permit S-1216-100. [District Rule 4623, 5.1.2 and 5.6.1] Federally Enforceable Through Title V Permit
4. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

11. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

16. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

17. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

18. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

19. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

20. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

21. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

22. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

25. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

26. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

27. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

28. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

29. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

30. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

31. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

37. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

38. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

39. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

40. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

41. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

42. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

43. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

44. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

45. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

46. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

47. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

48. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

50. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

51. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

52. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

55. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

56. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

57. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-104-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1,968 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-100, '-101, '-102, '-103, AND '-105

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-69-1. [District NSR Rule]
2. Tank shall be equipped with temperature indicator. [District Rule 4623, 6.2.1.1.5, 6.2.1.2, 6.3.1, 6.4.5] Federally Enforceable Through Title V Permit
3. Tank vapors shall vent to control system on permit S-1216-100. [District Rule 4623, 5.2.1 and 5.6.1] Federally Enforceable Through Title V Permit
4. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

11. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

13. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

15. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

16. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

17. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

18. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

19. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

20. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

21. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

22. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

25. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

26. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

27. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

28. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

29. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

30. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

31. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

37. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

38. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

39. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

40. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

41. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

42. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

43. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

44. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

45. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

46. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

47. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

48. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

50. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

51. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

52. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

55. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

56. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

57. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-105-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1,968 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-100, '-101, '-102, '-103, AND '-104

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-70-1. [District NSR Rule]
2. Tank shall be equipped with temperature indicator. [District Rule 4623, 6.2.1.1.5, 6.2.1.2, 6.3.1, 6.4.5] Federally Enforceable Through Title V Permit
3. Tank vapors shall vent to control system on permit S-1216-100. [District Rule 4623, 5.2.1 and 5.6.1] Federally Enforceable Through Title V Permit
4. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit
13. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
14. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
15. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
16. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
17. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
18. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
19. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
20. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
21. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
22. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

25. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

26. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

27. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

28. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

29. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

30. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

31. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

37. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

38. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

39. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

40. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

41. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

42. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

43. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

44. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

45. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

46. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

47. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

48. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

50. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

51. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

52. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

55. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

56. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

57. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-106-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
191 BBL FIXED ROOF PETROLEUM STORAGE TANK

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-72-0. [District NSR Rule]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
3. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801]
4. This unit is a tank of a small producer with a throughput of 50 barrels of crude oil per day or less and is exempt from District Rule 4623. Operator shall maintain a record of average daily crude oil throughput to determine compliance with section 3.25, and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. The monthly crude oil production records required by the California Division of Oil, Gas, and Geothermal Resources may be used to comply with the above requirement. Operator shall also maintain monthly records of the average daily crude oil throughput of this tank to demonstrate compliance with Section 4.4 and/or 5.1.2 [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
5. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.3] Federally Enforceable Through Title V Permit
6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit
7. The requirements of District Rule 4623 (amended December 20, 2001) do not apply to this source since this tank is exempt under section 4.0 as a small producer tank. A permit shield is granted from this requirement except for sections 6.3.4 and 7.3 for small producer tanks. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

11. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

12. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

13. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

14. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

15. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

16. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

17. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

18. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

19. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

20. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

21. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

23. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

24. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

25. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

26. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

27. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

28. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

29. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

30. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

31. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

32. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

33. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

34. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

35. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

37. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

38. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

39. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

40. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

41. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

42. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

43. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

44. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

45. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

46. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

47. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

49. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

50. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

51. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-107-1 **EXPIRATION DATE:** 08/31/2010

SECTION: SW26 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1,042 BBL FIXED ROOF CRUDE OIL STORAGE TANK

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2201]
2. Operator shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit (DEU), at which time this permit will be administratively modified to remove DEU references. [District Rule 2080]
3. When this tank is not operated (dormant for Rule 4623), all liquids shall be removed and the produced crude oil inlet line shall be physically disconnected. [District Rule 4623]
4. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623]
5. Results of TVP test on material introduced to this tank upon reactivation shall be submitted to the District within 60 days of recommencing operation of this tank. [District Rule 2080]
6. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623]
7. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
8. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801]
9. Upon recommencing operation, permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2]
10. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2]
11. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2]
13. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4]
14. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623]
15. This tank shall be subject to the control requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2]
16. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623]
17. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]
18. Formerly S-2010-74
19. Formerly S-3079-26

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-108-2 **EXPIRATION DATE:** 08/31/2010

SECTION: SE36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
532 BBL FIXED ROOF CRUDE OIL STORAGE TANK

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2010]
2. All liquids shall be removed from this dormant emissions unit and the produced crude oil inlet line shall be physically disconnected. [District Rule 4623]
3. This equipment shall not be operated for any reason until an Authority to Construct permit is issued and implemented for all necessary retrofits to comply with the applicable requirements of District Rule 4623. [District Rule 4623]
4. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
5. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801]
6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 4623, 6.3]
7. Formerly S-2010-82
8. Formerly S-3079-28

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-109-1 **EXPIRATION DATE:** 08/31/2010

SECTION: SE36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
22,344 GALLON FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED ON PERMIT S-1216-93

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-83-0. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
3. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule]
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623]
5. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623]
7. VOC fugitive emissions from the components in gas service on tank shall not exceed 0.1 lb/day. [District Rule 2201]
8. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201]
9. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201]
10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623]
11. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623]

13. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 1070]

14. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801]

15. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

17. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

18. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

19. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

20. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

21. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

22. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

23. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

24. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

26. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

27. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

28. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

29. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

30. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

31. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

32. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

36. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

37. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

38. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

39. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

40. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

41. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

42. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

43. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

44. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

45. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

46. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

47. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

48. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

49. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

50. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

51. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

52. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

53. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

54. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

55. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

56. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

57. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

58. Facilities S-1216, S-382, and S-1738 constitute one stationary source. [District Rule 2201]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-110-1 **EXPIRATION DATE:** 08/31/2010

SECTION: SE36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
22,344 GALLON FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED ON PERMIT S-1216-93

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-84-0. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
3. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule]
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623]
5. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623]
7. VOC fugitive emissions from the components in gas service on tank shall not exceed 0.08 lb/day. [District Rule 2201]
8. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201]
9. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201]
10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623]
11. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623]

13. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 1070]

14. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801]

15. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

17. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

18. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

19. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

20. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

21. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

22. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

23. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

24. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

26. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

27. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

28. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

29. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

30. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

31. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

32. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

36. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

37. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

38. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

39. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

40. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

41. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

42. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

43. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

44. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

45. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

46. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

47. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

48. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

49. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

50. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

51. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

52. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

53. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

54. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

55. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

56. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

57. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

58. Facilities S-1216, S-382, and S-1738 constitute one stationary source. [District Rule 2201]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-111-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE12 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
1571 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED ON S-1216-122

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-87-4. [District NSR Rule]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
4. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

14. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

15. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

16. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

17. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

18. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

19. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

20. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

21. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

22. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

24. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

25. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

26. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

27. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

28. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

29. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

30. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

31. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

34. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

35. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

37. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

38. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

39. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

40. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

41. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

42. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

43. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

44. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

45. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

46. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

47. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

48. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

50. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

51. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

53. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

54. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

55. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-122-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE12 **TOWNSHIP:** 32S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
ONE 42,000 GALLON CRUDE OIL STORAGE TANK SERVED BY A VAPOR RECOVERY SYSTEM AT GAS PLANT S-48 SHARED WITH S-1216-111

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-184-0. [District NSR Rule]
2. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
4. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
5. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

11. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

12. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

14. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

15. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

16. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

17. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

18. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

19. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

20. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

21. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

23. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

24. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

25. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

26. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

27. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

28. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

29. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

30. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

31. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

34. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

36. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

37. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

38. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

39. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

40. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

41. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

42. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

43. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

44. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

45. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

46. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

47. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

49. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

50. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

51. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

52. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

53. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

54. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

55. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-123-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 27 **TOWNSHIP:** 31S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
ONE 420,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK SERVED BY A VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1216-125 AND '-126 AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-185-0. [District NSR Rule]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
5. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

11. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit has a storage capacity of 420,000 gallons but is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

15. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

16. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

17. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

18. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

19. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

20. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

21. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

23. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

24. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

25. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

26. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

27. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

28. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

29. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

30. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

31. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

36. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

37. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

38. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

39. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

40. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

41. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

42. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

43. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

44. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

45. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

46. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

47. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

49. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

50. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

51. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

52. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

55. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

56. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-124-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE27 **TOWNSHIP:** 31S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
ONE 429,282 GALLON FIXED ROOF STORAGE TANK SERVED BY A VAPOR RECOVERY SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-187-0. [District NSR Rule]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
3. This unit is a tank of a small producer with a throughput of 50 barrels of crude oil per day or less, it is exempt from District Rule 4623. Operator shall maintain a record of average daily crude oil throughput to determine compliance with section 3.25, and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. The monthly crude oil production records required by the California Division of Oil, Gas, and Geothermal Resources may be used to comply with the above requirement. Operator shall also maintain monthly records of the average daily crude oil throughput of this tank to demonstrate compliance with Section 4.4 and/or 5.1.2 [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
4. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.3] Federally Enforceable Through Title V Permit
5. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. The requirements of District Rule 4623 (amended December 20, 2001) do not apply to this source since this tank is exempt under section 4.0 as emergency standby, temporary, or a small producer tank. A permit shield is granted from this requirement except for sections 6.3.4 and 7.3 for small producer tanks. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. This unit is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
9. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
11. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
12. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
13. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
14. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
15. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
16. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
17. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
18. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
19. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
20. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
21. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
22. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

24. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

25. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

26. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

27. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

28. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

29. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

30. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

31. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

32. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

33. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

34. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

35. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

37. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

38. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

39. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

40. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

41. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

42. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

43. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

44. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

45. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

46. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

47. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

48. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

49. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

50. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-125-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE27 **TOWNSHIP:** 31S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
ONE 429,282 GALLON FIXED ROOF STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM (SHARED WITH S-1216-123 AND '-126) AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-188-0. [District NSR Rule]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
5. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit
12. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
13. This unit is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
14. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
15. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
16. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
17. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
18. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
19. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
20. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
21. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

23. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

24. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

25. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

26. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

27. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

28. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

29. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

30. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

31. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

36. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

37. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

38. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

39. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

40. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

41. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

42. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

43. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

44. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

45. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

46. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

47. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

49. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

50. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

51. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

52. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

55. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

56. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-126-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE27 **TOWNSHIP:** 31S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
ONE 429,282 GALLON FIXED ROOF STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM (SHARED WITH S-1216-123 AND '-125) AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-189-0. [District NSR Rule]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
4. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
5. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

10. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

11. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, 4623. 6.3] Federally Enforceable Through Title V Permit

12. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

13. This unit is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

14. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

15. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

16. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

17. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

18. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

19. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

20. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

21. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

23. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

24. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

25. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

26. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

27. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

28. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

29. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

30. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

31. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

36. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

37. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

38. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

39. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

40. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

41. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

42. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

43. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

44. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

45. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

46. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

47. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

49. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

50. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

51. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

52. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

55. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

56. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-127-1 **EXPIRATION DATE:** 08/31/2010

SECTION: SW27 **TOWNSHIP:** 31S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
250 BBL FIXED ROOF CRUDE OIL DRAIN TANK SERVED BY A P/V RELIEF VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801]
4. Crude oil throughput shall be less than 50 bbl/day. [District Rule 2080]
5. TVP of material stored in tank shall not exceed 11 psia. [District Rule 4623 5.1.1]
6. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2]
7. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2]
8. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2]
9. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2]
10. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4]
11. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. Permittee shall also maintain monthly records of average daily throughput. [District Rules 4623and 2080]
13. This unit is a tank of a small producer with a throughput of 50 barrels of crude oil per day or less and is exempt from District Rule 4623. Operator shall maintain a record of average daily crude oil throughput to determine compliance with section 3.25, and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. The monthly crude oil production records required by the California Division of Oil, Gas, and Geothermal Resources may be used to comply with the above requirement. Operator shall also maintain monthly records of the average daily crude oil throughput of this tank to demonstrate compliance with Section 4.4 and/or 5.1.2 [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
14. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623]
15. Formerly S-3079-48-0.
16. Formerly S-2010-190-0

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-128-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW21 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
ONE 84,000 GALLON FIXED ROOF WASH TANK SERVED BY A VAPOR CONTROL SYSTEM INCLUDING PIPING TO CHEVRON 1-C GAS PLANT (S-48)

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-193-0. [District NSR Rule]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
3. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801]
4. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. Collected vapors shall be directed to approved control devices having a destruction efficiency of at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623, 5.6.1] Federally Enforceable Through Title V Permit
6. All piping valves and fittings shall be constructed and maintained in a gas tight condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
7. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.9 and 6.4.8] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2, and 4623. 6.3] Federally Enforceable Through Title V Permit
13. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended December 20, 2001). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
14. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
15. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
16. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
17. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
18. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
19. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
20. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
21. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
22. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

24. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

25. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

26. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

27. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

28. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

29. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

30. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

31. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

32. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

33. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

34. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

37. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

38. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

39. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

40. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

41. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

42. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

43. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

44. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

45. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

46. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

47. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

48. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

50. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

51. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

52. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

53. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

54. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

55. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

56. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

57. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-129-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW21 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
ONE 5,880 GALLON FIXED ROOF STORAGE TANK

PERMIT UNIT REQUIREMENTS

1. This permit unit was formerly number S-2010-194-0. [District NSR Rule]
2. Crude oil throughput shall not exceed 50 barrels per day based on a monthly average. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
3. Sulfur compound emissions shall not exceed 2000 ppmv as SO2. [District Rule 4801]
4. This unit is a tank of a small producer with a throughput of 50 barrels of crude oil per day or less and is exempt from District Rule 4623. Operator shall maintain a record of average daily crude oil throughput to determine compliance with section 3.25, and shall submit such information to the APCO 30 days prior to the expiration date indicated in the Permit to Operate. The monthly crude oil production records required by the California Division of Oil, Gas, and Geothermal Resources may be used to comply with the above requirement. Operator shall also maintain monthly records of the average daily crude oil throughput of this tank to demonstrate compliance with Section 4.4 and/or 5.1.2 [District Rule 4623, 6.3.4] Federally Enforceable Through Title V Permit
5. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.3] Federally Enforceable Through Title V Permit
6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit
7. The requirements of District Rule 4623 (amended December 20, 2001) do not apply to this source since this tank is exempt under section 4.0 as a small producer tank. A permit shield is granted from this requirement except for sections 6.3.4 and 7.3 for small producer tanks. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

11. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

12. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

13. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

14. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

15. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

16. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

17. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

18. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

19. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

20. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

21. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

23. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

24. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

25. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

26. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

27. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

28. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

29. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

30. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

31. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

32. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

33. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

34. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

35. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

37. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

38. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

39. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

40. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

41. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

42. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

43. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

44. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

45. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

46. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

47. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

49. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

50. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

51. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-130-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 06 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
ONE 100,800 GALLON FIXED-ROOF PETROLEUM WASH TANK SERVED BY A VAPOR RECOVERY SYSTEM (BUENA VISTA)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
3. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
5. Tank roof appurtenances shall be maintained leak free (less than 10,000 ppmv). [District NSR Rule]
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
7. Tank shall vent exclusively to vapor recovery system. [District NSR Rule]
8. The tank PV valve shall be set to within 10% of the maximum allowable working pressure of the tank. [District Rule 4623]
9. Formerly S-1641-43-0
10. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
11. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

13. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

14. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

15. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

16. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

17. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

18. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

19. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

20. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

21. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

22. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

23. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

24. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

25. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

26. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

27. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

28. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

29. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

30. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

31. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

32. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

33. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

34. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

35. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

36. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

37. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

38. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

39. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

40. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

41. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

42. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

43. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

44. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

45. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

46. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

47. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

48. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

50. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

51. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

52. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-131-0 **EXPIRATION DATE:** 08/31/2010

SECTION: 06 **TOWNSHIP:** 32S **RANGE:** 24E

EQUIPMENT DESCRIPTION:
ONE 42,000 GALLON FIXED-ROOF PETROLEUM WASH TANK (#IGF52) SERVED BY A VAPOR RECOVERY SYSTEM (LITTLE SIX LEASE)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623]
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201]
3. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 4623]
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
5. Tank roof appurtenances shall be maintained leak free (less than 10,000 ppmv). [District NSR Rule]
6. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623]
7. Operation shall include make-up gas line with Varec Fig. 181 valve regulator and piping through Varec Fig. 180 valve regulator to gas gathering line shared between permit units S-1641-42 and S-1641-45. [District NSR Rule]
8. Tank shall vent exclusively to vapor recovery system shared between permit units S-1641-42 and S-1641-45. [District NSR Rule]
9. Tank S-1641-42 shall be operated at constant fluid level. [District NSR Rule]
10. Tank vapor recovery system shall comply with all applicable Rule 4403 requirements. [District Rule 4403]
11. Varec Fig. 181 gas regulator shall activate when tank pressure falls below 2 in. H2O allowing make-up gas to enter tank. [District NSR Rule]
12. Varec Fig. 180 gas regulator shall activate when tank pressure rises above 2 in-H2O allowing vapor to be drawn into gas gathering line. [District NSR Rule]
13. The tank PV valve shall be set to within 10% of the maximum allowable working pressure of the tank. [District Rule 4623]
14. Total combined volatile organic compound (VOC) emissions from tanks S-1641-42 and S-1641-45 shall not exceed 0.24 lb per day. [District NSR Rule]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

15. The operator shall keep accurate records of types, storage temperature and true vapor pressure of liquids stored. [District Rule 1070]

16. Formerly S-1130-23-0

17. Formerly S-1641-45-0

18. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

19. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

20. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

21. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

22. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

23. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

24. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

25. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

26. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

27. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

29. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

30. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

31. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

32. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

33. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

34. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

36. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

37. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

38. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

39. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

40. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

42. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

43. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

44. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

45. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

46. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

47. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

48. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

49. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

50. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

51. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

52. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

53. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

54. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

55. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

56. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

57. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

58. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

59. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

60. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-132-0 **EXPIRATION DATE:** 08/31/2010

EQUIPMENT DESCRIPTION:
WEMCO MODEL 84 OIL/WATER SEPARATOR RATED AT 40,000 BBL/DAY AND SERVED BY GAS PLANT VAPOR RECOVERY SYSTEM AT FACILITY S-48

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
3. All piping, valves, and fittings shall be constructed and maintained in a leak-tight condition. [District NSR Rule] Federally Enforceable Through Title V Permit
4. A leak-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. Fugitive VOC emissions rate for the WEMCO oil/water separator shall be calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components in gas/light liquid service, shall not exceed 0.3 lb-VOC/day or 110 lb-VOC/yr. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. Components subject to District Rule 4409 shall be identified and categorized according to District Rule 4409 component types. [District NSR Rule] Federally Enforceable Through Title V Permit
10. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. For valves, threaded connections, flanges, pipes, pumps, compressors, and other components subject to the requirements of Rule 4409, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 2,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

12. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.2] Federally Enforceable Through Title V Permit

13. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4409 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4409. [District Rule 4409, 5.1.3.2.1 and 5.1.3.2.2] Federally Enforceable Through Title V Permit

14. Leaking components at this facility detected during annual operator inspections, as required by Rule 4409 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4409, 5.1.3.2.3] Federally Enforceable Through Title V Permit

15. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.4.1] Federally Enforceable Through Title V Permit

16. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4409, 5.1.4.2] Federally Enforceable Through Title V Permit

17. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4409, 5.1.4.3] Federally Enforceable Through Title V Permit

18. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

19. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

20. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

22. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

23. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

24. For unmanned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once per calendar week. [District Rule 4409, 5.2.2] Federally Enforceable Through Title V Permit

25. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.3] Federally Enforceable Through Title V Permit

26. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4409, 5.2.4] Federally Enforceable Through Title V Permit

27. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4409, 5.2.5] Federally Enforceable Through Title V Permit

28. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4409, 5.2.6] Federally Enforceable Through Title V Permit

29. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4409, 5.2.7] Federally Enforceable Through Title V Permit

30. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4409, 5.2.8] Federally Enforceable Through Title V Permit

31. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.8.1] Federally Enforceable Through Title V Permit

32. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4409. [District Rule 4409, 5.2.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

33. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4409, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit

34. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4409, 5.2.11] Federally Enforceable Through Title V Permit

35. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4409, 5.2.13] Federally Enforceable Through Title V Permit

36. District inspections shall not be counted as an operator inspection required by District Rule 4409. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4409, 5.2.14] Federally Enforceable Through Title V Permit

37. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4409, 5.3.1] Federally Enforceable Through Title V Permit

38. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit

39. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit

40. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4409, 5.3.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

41. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4409 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4409, 5.3.6] Federally Enforceable Through Title V Permit

42. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4409, 5.3.7] Federally Enforceable Through Title V Permit

43. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4409, 5.4.1] Federally Enforceable Through Title V Permit

44. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4409, 6.1.2] Federally Enforceable Through Title V Permit

45. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4409, 6.1.4] Federally Enforceable Through Title V Permit

46. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4409, 6.2.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

47. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4409, 6.2.2] Federally Enforceable Through Title V Permit

48. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4409, 6.2.3] Federally Enforceable Through Title V Permit

49. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4409, 6.2.4] Federally Enforceable Through Title V Permit

50. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4409, 6.3.1] Federally Enforceable Through Title V Permit

51. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4409, 6.3.2] Federally Enforceable Through Title V Permit

52. The percent by volume liquid evaporated at 302 øF (150 øC) shall be determined using ASTM D-86. [District Rule 4409, 6.3.3] Federally Enforceable Through Title V Permit

53. The TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D-323, and converting the RVP to TVP at the maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures specified in Appendix A of District Rule 4409. [District Rule 4409, 6.3.4] Federally Enforceable Through Title V Permit

54. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM D-287 or ASTM 1298. Sampling for API gravity shall be performed in accordance with ASTM D-4057. [District Rule 4409, 6.3.5] Federally Enforceable Through Title V Permit

55. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4409, 6.3.6] Federally Enforceable Through Title V Permit

56. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4409, 6.3.7] Federally Enforceable Through Title V Permit

57. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

58. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

59. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

60. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

61. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

62. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

63. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

64. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

65. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

66. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

67. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

68. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

69. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

70. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

71. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

72. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

73. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

74. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

75. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

76. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

77. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

78. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

79. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

80. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

81. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

82. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

83. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

84. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

85. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

86. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

87. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

88. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

89. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

90. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

91. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

92. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

93. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

94. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

95. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

96. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

97. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

98. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

99. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-133-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T6) SERVED BY VAPOR CONTROL SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rules 2201 and 4623, 5.3.1] Federally Enforceable Through Title V Permit
3. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
4. VOC content of hydrocarbons in gas shall not exceed 37% by weight. Permittee shall sample and record the VOC content of hydrocarbons at least once every 12 months. [District Rules 1070 and 2201]
5. VOC content of gas shall be determined by ASTM D1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201]
6. Fugitive VOC emissions rate shall be, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
7. VOC fugitive emissions from the components in gas service on the tank shall not exceed 0.008 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
10. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

12. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

13. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

14. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit

17. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

18. Interior tank cleaning shall be performed in accordance with provisions specified in Table 6 of Rule 4623. [District Rules 2201 & 4623] Federally Enforceable Through Title V Permit

19. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

21. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

22. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

24. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

25. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

26. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

27. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

28. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

29. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

30. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

31. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

32. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

33. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

34. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

35. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

36. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

37. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

38. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

39. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

40. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

41. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

42. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

43. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

44. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

45. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

46. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

47. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

48. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

50. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

51. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

52. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

53. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

54. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

55. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

56. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

57. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

58. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

59. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

60. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

61. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

62. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

63. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-134-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T7) SERVED BY VAPOR CONTROL SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rules 2201 and 4623, 5.3.1] Federally Enforceable Through Title V Permit
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
3. VOC content of hydrocarbons in gas shall not exceed 37% by weight. Permittee shall sample and record the VOC content of hydrocarbons at least once every 12 months. [District Rules 1070 and 2201]
4. VOC content of gas shall be determined by ASTM D1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201]
5. Fugitive VOC emissions rate shall be, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC fugitive emissions from the components in gas service on the tank shall not exceed 0.008 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
9. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
11. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
12. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
17. Interior tank cleaning shall be performed in accordance with provisions specified in Table 6 of Rule 4623. [District Rules 2201 & 4623] Federally Enforceable Through Title V Permit
18. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
19. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
20. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
21. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

23. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

24. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

25. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

26. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

27. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

28. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

29. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

30. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

31. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

32. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

33. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

34. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

36. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

37. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

38. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

39. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

40. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

41. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

42. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

43. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

44. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

45. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

46. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

47. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

49. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

50. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

51. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

52. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

53. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

54. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

55. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

56. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

57. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

58. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

59. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

60. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

61. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

62. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-135-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
10,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T2) SERVED BY VAPOR CONTROL SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rules 2201 and 4623, 5.3.1] Federally Enforceable Through Title V Permit
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
3. VOC content of hydrocarbons in gas shall not exceed 37% by weight. Permittee shall sample and record the VOC content of hydrocarbons at least once every 12 months. [District Rules 1070 and 2201]
4. VOC content of gas shall be determined by ASTM D1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201]
5. Fugitive VOC emissions rate shall be, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC fugitive emissions from the components in gas service on the tank shall not exceed 0.008 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
9. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
11. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
12. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit
16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit
17. Interior tank cleaning shall be performed in accordance with provisions specified in Table 6 of Rule 4623. [District Rules 2201 & 4623] Federally Enforceable Through Title V Permit
18. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit
19. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
20. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
21. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

23. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

24. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

25. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

26. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

27. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

28. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

29. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

30. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

31. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

32. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

33. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

34. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

36. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

37. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

38. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

39. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

40. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

41. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

42. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

43. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

44. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

45. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

46. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

47. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

49. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

50. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

51. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

52. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

53. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

54. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

55. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

56. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

57. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

58. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

59. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

60. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

61. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

62. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-136-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
2000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T8) SERVED BY VAPOR CONTROL SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rules 2201 and 4623, 5.3.1] Federally Enforceable Through Title V Permit
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
3. VOC content of hydrocarbons in gas shall not exceed 37% by weight. Permittee shall sample and record the VOC content of hydrocarbons at least once every 12 months. [District Rules 1070 and 2201]
4. VOC content of gas shall be determined by ASTM D1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201]
5. Fugitive VOC emissions rate shall be, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC fugitive emissions from the components in gas service on the tank shall not exceed 0.008 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
9. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

11. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

12. If a component type for a given tank is found to leak during an annual inspection, then conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule NSR] Federally Enforceable Through Title V Permit

16. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

17. Interior tank cleaning shall be performed in accordance with provisions specified in Table 6 of Rule 4623. [District Rules 2201 & 4623] Federally Enforceable Through Title V Permit

18. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

19. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

20. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

21. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

23. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

24. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

25. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

26. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

27. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

28. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

29. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

30. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

31. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

32. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

33. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

34. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

36. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

37. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

38. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

39. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

40. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

41. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

42. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

43. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

44. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

45. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

46. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

47. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

48. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

49. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

50. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

51. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

52. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

53. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

54. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

55. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

56. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

57. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

58. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

59. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

60. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

61. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

62. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-137-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE36 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
500 BBL FIXED ROOF CRUDE OIL STORAGE TANK T9 SERVED BY VAPOR CONTROL SYSTEM AT GAS PLANT S-48

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rules 2201 and 4623, 5.3.1] Federally Enforceable Through Title V Permit
2. All tank gauging or sampling devices on a tank vented to the vapor recovery system shall be equipped with a gas tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.3.2] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions rate shall be calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999), from the total number of components from this tank. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas and light oil service shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
7. If any of the tank components are found to be leaking, operator shall immediately affix a tag and maintain records of gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit
8. Upon detection of any leaking components (having a gas leak >10,000 ppmv, measured in accordance with EPA Method 21 by a portable hydrocarbon detection instrument that is calibrated with methane) operator shall: (a) Eliminate or minimize the leak within 8 hours after detection. (b) If the leak can not be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices; and eliminate the leak within 48 hours after detection. (c) In no event that the total time to minimize and eliminate the leak shall exceed 56 hours after detection. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Leaking tank components affixed to the tank or within five feet of the tank that have been discovered by the operator and that have been immediately tagged and repaired within the specified deadlines, shall not constitute a violation of the District Rule 4623. However, leaking components discovered during inspections by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within specified deadlines, shall constitute a violation of the District Rule 4623. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

10. If a component type for a given tank is found to leak during an annual inspection, then operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If a component type is found to have no leak after four consecutive quarterly inspections, then operator shall revert to annual inspections. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

11. Any component found to be leaking on two consecutive annual inspections is in violation of District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623, 5.7 (Table 3)] Federally Enforceable Through Title V Permit

12. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

13. Permittee shall maintain records of number and type of components installed and calculated fugitive emissions. Permittee shall update such records when new components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit

14. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2020] Federally Enforceable Through Title V Permit

15. Interior tank cleaning shall be performed in accordance with provisions specified in Rule 4623. [District Rules 2201 & 4623] Federally Enforceable Through Title V Permit

16. Permittee shall keep in their facility at all times a copy of the letter sent to the APCO requesting participation in the Rule 4623 Fixed Roof Tank Preventive Inspection and Maintenance Program, and Tank Interior Cleaning Program, and maintain the records of annual tank inspections, maintenance, and cleaning to document the participation in the program. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

17. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

18. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

19. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit

20. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

21. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

23. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

24. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

25. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

26. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

27. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

28. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

29. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

30. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

31. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

32. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

33. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

34. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

35. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

36. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

37. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

38. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

39. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

40. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

41. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

42. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

43. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

44. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

45. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

46. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

47. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

48. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

49. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

50. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

51. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

52. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

53. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

54. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

55. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

56. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

57. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

58. On January 31, 2005, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

59. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

60. To maintain status as a small producer, permittee's crude oil production shall average less than 6000 bbl/day from all operations within Kern County and permittee shall not engage in refining, transporting, or marketing of refined petroleum products. [District Rules 3020, 4623, 3.25 and 4.4] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-139-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NW 20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
195 BHP WAUKESHA MODEL F-1197 SERIAL #265448 FIELD GAS/PROPANE -FIRED RICH BURN CYCLICALLY LOADED I.C. ENGINE WITH NON SELECTIVE CATALYTIC REDUCTION (NSCR) EMISSIONS CONTROL

PERMIT UNIT REQUIREMENTS

1. Unit shall not be located within 1000 feet of any K-12 school. [CH&SC 42301.6]
2. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Permittee shall notify the District Compliance Division of each location at which the unit is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
6. When unit is dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
7. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
8. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
9. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
10. Emissions from the engine shall not exceed any of the following limits: 50 ppmv-NOx @ 15% O2, 2,000 ppmv-CO @ 15% O2 and 250 ppmv-VOC @ 15% O2. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
11. This unit shall be fired only on propane or gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
12. Upon recommencing operation, permittee shall monitor and record, on a monthly basis, the catalyst inlet and outlet temperatures. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. The acceptable catalyst temperature differential shall be established by source testing this unit or other representative units as approved by the District. The normal range/level shall be any temperature increase across the catalyst unless compliance with applicable NOx and CO emissions limits have been demonstrated through source testing at a similar temperature drop. [District Rule 4702] Federally Enforceable Through Title V Permit

14. Upon recommencing operation, permittee shall maintain records of the date and time of temperature measurements and the measured temperatures. The records shall also include a description of any corrective action taken to maintain the temperature differential at the acceptable level. [District Rule 4702] Federally Enforceable Through Title V Permit

15. If the catalyst temperature differential is outside of the normal range/level, the permittee shall notify the District and take corrective action (i.e. temperature differential returned to normal range/level) with one (1) hour of detection. If the catalyst temperature differential rate is not immediately corrected, the permittee shall conduct a source test within 60 days, to demonstrate compliance with the applicable emissions limits at the new temperature differential. [District Rule 4702] Federally Enforceable Through Title V Permit

16. The permittee shall update the I & M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I & M plan and must submit an updated I & M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I & M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I & M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

17. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

18. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

19. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

21. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

22. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

25. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

26. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

27. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

28. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

29. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits for propane combustion shall be conducted at startup. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

30. NOx, CO, and VOC emissions shall be measured (source tested) not less than once every 24 months. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

31. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701 and 4702] Federally Enforceable Through Title V Permit

32. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

33. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

34. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

35. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rules 4701 and 4702. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

36. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-140-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW 20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
135 BHP WAUKESHA MODEL F-817 FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
2. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
4. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
5. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
6. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
7. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
9. Emissions from the engine shall not exceed any of the following limits: 50 ppmv-NOx @ 15% O2, 2,000 ppmv-CO @ 15% O2 and 250 ppmv-VOC @ 15% O2. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
10. This unit shall be fired only on gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, permittee shall monitor and record, on a monthly basis, the catalyst inlet and outlet temperatures. [District Rule 4702] Federally Enforceable Through Title V Permit
12. The acceptable catalyst temperature differential shall be established by source testing this unit or other representative units as approved by the District. The normal range/level shall be any temperature increase across the catalyst unless compliance with applicable NOx and CO emissions limits have been demonstrated through source testing at a similar temperature drop. [District Rule 4702] Federally Enforceable Through Title V Permit
13. Upon recommencing operation, permittee shall maintain records of the date and time of temperature measurements and the measured temperatures. The records shall also include a description of any corrective action taken to maintain the temperature differential at the acceptable level. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. If the catalyst temperature differential is outside of the normal range/level, the permittee shall notify the District and take corrective action (i.e. temperature differential returned to normal range/level) with one (1) hour of detection. If the catalyst temperature differential rate is not immediately corrected, the permittee shall conduct a source test within 60 days, to demonstrate compliance with the applicable emissions limits at the new temperature differential. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

15. The permittee shall update the I & M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I & M plan and must submit an updated I & M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I & M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I & M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

16. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

17. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

18. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701and 4702] Federally Enforceable Through Title V Permit

20. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

21. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

25. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

26. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

27. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

28. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

29. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701 and 4702] Federally Enforceable Through Title V Permit

30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

32. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rules 4701 and 4702. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-141-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NW 29 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
195 BHP WAUKESHA MODEL F-1197 FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED I.C. ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
2. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
4. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
6. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
9. Emissions from the engine shall not exceed any of the following limits: 50 ppmv-NOx @ 15% O2, 2,000 ppmv-CO @ 15% O2 and 250 ppmv-VOC @ 15% O2. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
10. This unit shall be fired only on gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule 2201 and Kern County Rule 407] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, permittee shall monitor and record, on a monthly basis, the catalyst inlet and outlet temperatures. [District Rule 4702] Federally Enforceable Through Title V Permit
12. The acceptable catalyst temperature differential shall be established by source testing this unit or other representative units as approved by the District. The normal range/level shall be any temperature increase across the catalyst unless compliance with applicable NOx and CO emissions limits have been demonstrated through source testing at a similar temperature drop. [District Rule 4702] Federally Enforceable Through Title V Permit
13. Upon recommencing operation, permittee shall maintain records of the date and time of temperature measurements and the measured temperatures. The records shall also include a description of any corrective action taken to maintain the temperature differential at the acceptable level. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

14. If the catalyst temperature differential is outside of the normal range/level, the permittee shall notify the District and take corrective action (i.e. temperature differential returned to normal range/level) with one (1) hour of detection. If the catalyst temperature differential rate is not immediately corrected, the permittee shall conduct a source test within 60 days, to demonstrate compliance with the applicable emissions limits at the new temperature differential. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

15. The permittee shall update the I & M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I & M plan and must submit an updated I & M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I & M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I & M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

16. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

17. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

18. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701and 4702] Federally Enforceable Through Title V Permit

20. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

21. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

23. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

25. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

26. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

27. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

28. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

29. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701 and 4702] Federally Enforceable Through Title V Permit

30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

32. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rules 4701 and 4702. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-142-1 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
84,588 GALLON FIXED ROOF PETROLEUM STORAGE TANK WITH VAPOR CONTROL SYSTEM INCLUDING COMPRESSOR(S) CONNECTED WITH TANKS S-1216-143 THROUGH '-145 AND '-152 THROUGH '-156 (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
2. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
9. Tank shall not be used to store or process liquids if the vapor control system is inoperable. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Vapor recovery system shall vent to gas plant (permit S-39-1) only. [District NSR Rule] Federally Enforceable Through Title V Permit

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

20. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-143-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
105,000 GALLON (2500 BBL) FIXED ROOF PETROLEUM STORAGE TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
4. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Tank shall not be used to store or process liquids if the vapor control system is inoperable. [District NSR Rule] Federally Enforceable Through Title V Permit
10. Tank throughput shall not exceed 1,500 bbl/day. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

18. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

20. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

21. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. Operator shall maintain records of daily tank throughput. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-144-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
84,588 GALLON FIXED ROOF PETROLEUM STORAGE TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
4. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Tank shall not be used to store or process liquids if the vapor control system is inoperable. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

19. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-145-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
84,588 GALLON FIXED ROOF PETROLEUM STORAGE TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. All piping valves and fittings shall be constructed and maintained in a leak-free condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
4. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
7. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
8. The tank shall be equipped with a vapor loss prevention system consisting of vapor and condensate collection systems capable of reducing VOC emissions by at least 99%. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Tank shall not be used to store or process liquids if the vapor control system is inoperable. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

19. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

20. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-146-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
8,400 GALLON FIXED ROOF PETROLEUM TEST TANK (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
3. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
4. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623] Federally Enforceable Through Title V Permit
5. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
7. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

15. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

16. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-147-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
8,400 GALLON FIXED ROOF PETROLEUM TEST TANK (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
3. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
4. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623] Federally Enforceable Through Title V Permit
5. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit
7. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

12. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623 (Table 3)] Federally Enforceable Through Title V Permit

13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit

15. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

16. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-148-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
147 HP MINNEAPOLIS MOLINE MODEL HD800-6A FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
2. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
4. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
6. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
9. Emissions from the engine shall not exceed any of the following limits: 50 ppmv-NOx @ 15% O2, 2,000 ppmv-CO @ 15% O2 and 250 ppmv-VOC @ 15% O2. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
10. This unit shall be fired only on gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, permittee shall monitor and record, on a monthly basis, the catalyst inlet and outlet temperatures. [District Rule 4702] Federally Enforceable Through Title V Permit
12. The acceptable catalyst temperature differential shall be established by source testing this unit or other representative units as approved by the District. The normal range/level shall be any temperature increase across the catalyst unless compliance with applicable NOx and CO emissions limits have been demonstrated through source testing at a similar temperature drop. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Upon recommencing operation, permittee shall maintain records of the date and time of temperature measurements and the measured temperatures. The records shall also include a description of any corrective action taken to maintain the temperature differential at the acceptable level. [District Rule 4702] Federally Enforceable Through Title V Permit

14. If the catalyst temperature differential is outside of the normal range/level, the permittee shall notify the District and take corrective action (i.e. temperature differential returned to normal range/level) with one (1) hour of detection. If the catalyst temperature differential rate is not immediately corrected, the permittee shall conduct a source test within 60 days, to demonstrate compliance with the applicable emissions limits at the new temperature differential. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

15. The permittee shall update the I & M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I & M plan and must submit an updated I & M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I & M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I & M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

16. Upon recommencing operation the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

17. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

18. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701and 4702] Federally Enforceable Through Title V Permit

20. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

21. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly. except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

25. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

26. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

27. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

28. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

29. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701 and 4702] Federally Enforceable Through Title V Permit

30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

32. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rules 4701 and 4702. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-149-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
147 HP MINNEAPOLIS MOLINE MODEL HD800-6A FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
2. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
4. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
6. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
9. Emissions from the engine shall not exceed any of the following limits: 50 ppmv-NOx @ 15% O2, 2,000 ppmv-CO @ 15% O2 and 250 ppmv-VOC @ 15% O2. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
10. This unit shall be fired only on gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, permittee shall monitor and record, on a monthly basis, the catalyst inlet and outlet temperatures. [District Rule 4702] Federally Enforceable Through Title V Permit
12. The acceptable catalyst temperature differential shall be established by source testing this unit or other representative units as approved by the District. The normal range/level shall be any temperature increase across the catalyst unless compliance with applicable NOx and CO emissions limits have been demonstrated through source testing at a similar temperature drop. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Upon recommencing operation, permittee shall maintain records of the date and time of temperature measurements and the measured temperatures. The records shall also include a description of any corrective action taken to maintain the temperature differential at the acceptable level. [District Rule 4702] Federally Enforceable Through Title V Permit

14. If the catalyst temperature differential is outside of the normal range/level, the permittee shall notify the District and take corrective action (i.e. temperature differential returned to normal range/level) with one (1) hour of detection. If the catalyst temperature differential rate is not immediately corrected, the permittee shall conduct a source test within 60 days, to demonstrate compliance with the applicable emissions limits at the new temperature differential. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

15. The permittee shall update the I & M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I & M plan and must submit an updated I & M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I & M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I & M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

16. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

17. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

18. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701and 4702] Federally Enforceable Through Title V Permit

20. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

21. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

25. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

26. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

27. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

28. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rules 4701, 6.3.1 and 4702] Federally Enforceable Through Title V Permit

29. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701 and 4702] Federally Enforceable Through Title V Permit

30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

32. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rules 4701 and 4702. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-150-0 **EXPIRATION DATE:** 08/31/2010

SECTION: NE20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
147 HP MINNEAPOLIS MOLINE MODEL HD800-6A FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
2. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
4. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
6. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
7. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
9. Emissions from the engine shall not exceed any of the following limits: 50 ppmv-NOx @ 15% O2, 2,000 ppmv-CO @ 15% O2 and 250 ppmv-VOC @ 15% O2. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
10. This unit shall be fired only on natural gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, permittee shall monitor and record, on a monthly basis, the catalyst inlet and outlet temperatures. [District Rule 4702] Federally Enforceable Through Title V Permit
12. The acceptable catalyst temperature differential shall be established by source testing this unit or other representative units as approved by the District. The normal range/level shall be any temperature increase across the catalyst unless compliance with applicable NOx and CO emissions limits have been demonstrated through source testing at a similar temperature drop. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Upon recommencing operation, permittee shall maintain records of the date and time of temperature measurements and the measured temperatures. The records shall also include a description of any corrective action taken to maintain the temperature differential at the acceptable level. [District Rule 4702] Federally Enforceable Through Title V Permit

14. If the catalyst temperature differential is outside of the normal range/level, the permittee shall notify the District and take corrective action (i.e. temperature differential returned to normal range/level) with one (1) hour of detection. If the catalyst temperature differential rate is not immediately corrected, the permittee shall conduct a source test within 60 days, to demonstrate compliance with the applicable emissions limits at the new temperature differential. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

15. The permittee shall update the I & M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I & M plan and must submit an updated I & M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I & M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I & M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

16. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

17. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

18. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701and 4702] Federally Enforceable Through Title V Permit

20. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

21. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

22. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

24. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

25. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

26. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

27. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

28. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rule 4701, 6.3.1 and 4702] Federally Enforceable Through Title V Permit

29. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701 and 4702] Federally Enforceable Through Title V Permit

30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

31. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

32. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rules 4701 and 4702. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

34. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-151-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
135 BHP WAUKESHA MODEL 817 FIELD GAS-FIRED RICH-BURN CYCLICALLY LOADED IC ENGINE WITH NSCR

PERMIT UNIT REQUIREMENTS

1. When dormant, the fuel supply line shall be physically disconnected from this unit, or an alternate method approved by the APCO shall be instituted to ensure this unit is not operated. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
2. A source test to demonstrate compliance with the indicated emission limits shall be performed within 60 days of recommencing operation of this unit. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit, at which time this permit will be administratively modified to remove DEU references. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
4. Unit shall only be operated within Occidental of Elk Hills Inc/Vintage Production California, LLC. light oil western stationary source. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Unit shall not be located within 1000 feet of any K-12 school. [District Rule CH&SC 42301.6]
6. Engine shall be maintained according to engine manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
8. Emissions from the engine shall not exceed any of the following limits: 50 ppmv NOx @ 15% O2 (equivalent to 0.7 g/bhp-hr), 2,000 ppmv CO @ 15% O2 (equivalent to 17.0 g/bhp-hr), 250 ppmv VOC @ 15% O2 (equivalent to 1.2 g/bhp-hr), and 0.063 g-PM10/bhp-hr. [District NSR Rule and 4702] Federally Enforceable Through Title V Permit
9. This unit shall be fired only on natural gas with a sulfur content not exceeding 5 grains/100 dscf. [District NSR Rule and Kern County Rule 407] Federally Enforceable Through Title V Permit
10. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOX (as NO2), CO, and O2 at least once every calendar quarter using a portable emission monitor that meets District specifications. Monitoring shall be performed not less than once every month for 12 months if 2 consecutive deviations are observed during quarterly monitoring. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 1 day of restarting the engine unless monitoring has been performed within the last month if on a monthly monitoring schedule, or within the last quarter if on a quarterly monitoring schedule. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. If the NOX or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the permitted emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. [District Rule 4702] Federally Enforceable Through Title V Permit

12. Upon recommencing operation, the permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOX and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records using Protocol 1 gases, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rule 4702] Federally Enforceable Through Title V Permit

13. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rule 4702] Federally Enforceable Through Title V Permit

14. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Kern County Rule 407] Federally Enforceable Through Title V Permit

15. If the engine is fired on PUC-regulated natural gas, then the permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

16. If the engine is not fired on PUC-regulated natural gas, then the sulfur content of the natural gas being fired in the engine shall be determined using ASTM method D1072, D3031, D4084 or D3246. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

17. If the engine is not fired on PUC-regulated natural gas, the sulfur content of each fuel source shall be tested weekly except that if compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks for a fuel source, then the testing frequency shall be quarterly. If a test shows noncompliance with the sulfur content requirement, the source must return to weekly testing until eight consecutive weeks show compliance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

18. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

19. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 407. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

20. Catalyst shall be periodically inspected and cleaned according to manufacturer's recommendations. [District NSR Rule] Federally Enforceable Through Title V Permit

21. Compliance demonstration (source testing) shall be by District witnessed, or authorized, sample collection by ARB certified testing laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

22. Upon recommencing operation, source testing to demonstrate compliance with NOX, CO, and VOC emission limits shall be conducted not less than once every 24 months. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

23. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, VOC (ppmv) - EPA Method 25 or 25B, or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081 and 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

25. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rule 4702] Federally Enforceable Through Title V Permit

26. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

27. Upon recommencing operation, an operating log record shall be maintained that includes, on a monthly basis, the total hours of operation, the type and quantity of fuel used, maintenance or modifications performed, compliance source test results, monitoring data, and any other information necessary to demonstrate compliance with Rule 4702. [District Rule 4702] Federally Enforceable Through Title V Permit

28. Permittee shall maintain records of source test results, monitoring data, and other information deemed necessary by the APCO to demonstrate compliance with District Rules for a period of five years and shall make such records readily available for District inspection upon request. [District Rules 1081 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-152-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SE20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
84,000 GALLON PRODUCED WATER TANK WITH VAPOR CONTROL (STEVENS LEASE)

PERMIT UNIT REQUIREMENTS

1. The fixed-roof storage tank shall be vented to vapor control system described in PTO S-1738-251. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
6. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to relieve pressure at a pressure level higher than that required to actuate compressor. The P/V valve shall be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
7. The water level in the water seal hatch shall be kept in accordance with the manufacturer's specifications, maintaining a leak-free condition. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Operator shall inspect and replenish the water level in the water seal hatch on a daily basis. Records of the water level shall be maintained. [District NSR Rule] Federally Enforceable Through Title V Permit
9. If the unit is a pressure vessel maintaining working pressures sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere, then no monitoring or recordkeeping shall be required. [District Rule 2520, 4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

11. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623]

12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

13. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

18. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-153-0 **EXPIRATION DATE:** 08/31/2010

EQUIPMENT DESCRIPTION:
84,000 GALLON PRODUCED WATER TANK WITH VAPOR CONTROL (STEVENS LEASE)

PERMIT UNIT REQUIREMENTS

1. The fixed-roof storage tank shall be vented to vapor control system described in PTO S-1738-251. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping valves and fittings shall be constructed and maintained in a leak-free condition [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
6. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to relieve pressure at a pressure level higher than that required to actuate compressor. The P/V valve shall be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
7. The water level in the water seal hatch shall be kept in accordance with the manufacturer's specifications, maintaining a leak-free condition. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Operator shall inspect and replenish the water level in the water seal hatch on a daily basis. Records of the water level shall be maintained. [District NSR Rule] Federally Enforceable Through Title V Permit
9. If the unit is a pressure vessel maintaining working pressures sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere, then no monitoring or recordkeeping shall be required. [District Rule 2520, 4.1] Federally Enforceable Through Title V Permit
10. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623]

12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

13. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

18. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-154-0 **EXPIRATION DATE:** 08/31/2010

EQUIPMENT DESCRIPTION:
42,000 GALLON PRODUCED WATER TANK #508 WITH VAPOR CONTROL (STEVENS LEASE)

PERMIT UNIT REQUIREMENTS

1. The fixed-roof storage tank shall be vented to vapor control system described in PTO# S-1738-7. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping valves and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. A reading in excess of 10,000 ppmv above background or the dripping of organic liquid at a rate of more than 3 drops per minute is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623, 3.11, 3.17, 3.18, and 6.4.8] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
6. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to relieve pressure at a pressure level higher than that required to actuate compressor. The P/V valve shall be permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in gas-tight condition except when the operating pressure exceeds the valve's set pressure. [District NSR Rule and Rule 4623] Federally Enforceable Through Title V Permit
7. The water level in the water seal hatch shall be kept in accordance with the manufacturer's specifications, maintaining a leak-free condition. [District NSR Rule] Federally Enforceable Through Title V Permit
8. Operator shall inspect and replenish the water level in the water seal hatch on a daily basis. Records of the water level shall be maintained. [District NSR Rule] Federally Enforceable Through Title V Permit
9. If the unit is a pressure vessel maintaining working pressures sufficient at all times to prevent organic liquid loss or VOC loss to the atmosphere, then no monitoring or recordkeeping shall be required. [District Rule 2520, 4.1] Federally Enforceable Through Title V Permit
10. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Permittee shall record and maintain monthly records of average daily crude oil throughput and shall make such records readily available for District inspection upon request for a period of five years. [District Rule 4623] Federally Enforceable Through Title V Permit

12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

13. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired upon detection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired. Leaks over 10,000 ppmv shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

15. Compliance with permit conditions in the Title V permit shall be deemed compliance with District Rule 4623 (Amended May 19, 2005). A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

16. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

17. The control efficiency of any VOC destruction device, measured and calculated as carbon, shall be determined by US EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case US EPA Method 25a may be used. US EPA Method 18 may be used in lieu of US EPA Method 25 or US EPA Method 25A provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of the known analytes/compounds to ensure that the VOC concentrations are neither under- or over-reported. Analysis of halogenated exempt compounds shall be analyzed by ARB Method 422 "Exempt Halogenated VOCs in Gases September 12, 1990." [District Rule 4623, 6.4.6 and 6.4.7] Federally Enforceable Through Title V Permit

18. Operator shall monitor vapor recovery compressor activation and shut off manometer pressures on quarterly basis to ensure that compressor activation pressure does not exceed pressure relief valve setting. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

19. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-155-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
420,000 GALLON (10,000 BBL) FIXED ROOF PETROLEUM PRODUCTION TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to the VOC vapor control system listed on S-1216-142. VOC vapors from tank shall vent only to the vapor control system. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
2. Storage tank pressure-vacuum cap(s) shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
3. Storage tank pressure-vacuum cap(s) shall be leak-free (except for inbreathing) during normal operation. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
4. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District NSR and District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District NSR and District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. VOC fugitive emissions from the components in both gas and liquid service on this tank shall not exceed 0.2 lb-VOC/day [District NSR Rule] Federally Enforceable Through Title V Permit
9. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed [District NSR Rule] Federally Enforceable Through Title V Permit
10. Except as otherwise provided in this permit, the operator shall ensure that the VOC vapor control system is functional and is operating as designed at all times. [District NSR Rule] Federally Enforceable Through Title V Permit
11. Any component found to be leaking is in violation of the District's NSR Rule, even if it is under the voluntary inspection and maintenance program. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

19. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water. or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623, 5.7] Federally Enforceable Through Title V Permit

29. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

30. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; Kern County Rule 111] Federally Enforceable Through Title V Permit

31. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; Kern County Rule 111] Federally Enforceable Through Title V Permit

32. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

33. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

35. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

36. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

37. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

38. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

39. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

40. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

41. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

42. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

43. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

44. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

45. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

46. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

47. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

48. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

49. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

50. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

51. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (2/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit

52. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

53. All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

54. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

55. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

56. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

57. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

58. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

59. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

60. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

61. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

62. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

63. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/04) or Rule 8011 (8/19/04). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

64. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

65. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

66. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

67. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

68. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

69. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (12/17/09); 8021 (8/19/04); 8031 (8/19/04); 8041 (8/19/04); 8051 (8/19/04); 8061 (8/19/04); and 8071 (9/16/04). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

70. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-1216-156-0 **EXPIRATION DATE:** 08/31/2010

SECTION: SW20 **TOWNSHIP:** 31S **RANGE:** 23E

EQUIPMENT DESCRIPTION:
21,000 GALLON (500 BBL) FIXED ROOF PETROLEUM PRODUCTION TANK WITH PIPING TO VAPOR RECOVERY SYSTEM UNDER PERMIT S-1216-142 (555 STEVENS ZONE UNIT)

PERMIT UNIT REQUIREMENTS

1. Tank shall be connected to the VOC vapor control system listed on S-1216-142. VOC vapors from tank shall vent only to the vapor control system. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
2. Storage tank pressure-vacuum cap(s) shall be set to relieve pressure at a pressure level higher than that required to actuate compressor. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
3. Storage tank pressure-vacuum cap(s) shall be leak-free (except for inbreathing) during normal operation. [District NSR and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
4. Operator shall inspect pressure relief valve for fugitive leaks annually in accordance with EPA Method 21, with the instrument calibrated with methane. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District NSR and District Rule 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. This tank shall be in a leak-free condition. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District NSR Rule and District Rule 4623, 5.1] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District NSR and District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
8. VOC fugitive emissions from the components in both gas and liquid service on this tank shall not exceed 0.2 lb-VOC/day [District NSR Rule] Federally Enforceable Through Title V Permit
9. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed [District NSR Rule] Federally Enforceable Through Title V Permit
10. Except as otherwise provided in this permit, the operator shall ensure that the VOC vapor control system is functional and is operating as designed at all times. [District NSR Rule] Federally Enforceable Through Title V Permit
11. Any component found to be leaking is in violation of the District's NSR Rule, even if it is under the voluntary inspection and maintenance program. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

13. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

14. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

15. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

16. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

19. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water. or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

22. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

23. After a tank has been degassed pursuant to the requirements of this permit, vapor control requirements are not applicable until an organic liquid is placed, held, or stored in this tank. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

24. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

25. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

26. During sludge removal, the operator shall control emissions from the sludge receiving vessel by operating an APCO-approved vapor control device that reduces emissions of organic vapors by at least 95%. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

27. Permittee shall only transport removed sludge in closed, liquid leak-free containers. [District Rule 4623, 5.7] Federally Enforceable Through Title V Permit

28. Permittee shall store removed sludge, until final disposal, in vapor leak-free containers, or in tanks complying with the vapor control requirements of District Rule 4623. Sludge that is to be used to manufacture roadmix, as defined in District Rule 2020, is not required to be stored in this manner. Roadmix manufacturing operations exempt pursuant to District Rule 2020 shall maintain documentation of their compliance with Rule 2020, and shall readily make said documentation available for District inspection upon request. [District Rules 2020 and 4623, 5.7] Federally Enforceable Through Title V Permit

29. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 2520, 9.4.2 and 4623, 6.3] Federally Enforceable Through Title V Permit

30. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; Kern County Rule 111] Federally Enforceable Through Title V Permit

31. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; Kern County Rule 111] Federally Enforceable Through Title V Permit

32. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit

33. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

34. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit

35. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit

36. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit

37. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

38. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

39. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

40. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

41. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

42. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

43. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

44. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

45. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

46. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

47. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

48. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

49. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

50. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

51. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (2/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit

52. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

53. All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

54. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

55. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

56. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

57. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

58. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

59. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

60. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

61. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

62. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

63. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/04) or Rule 8011 (8/19/04). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

64. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

65. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

66. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

67. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

68. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

69. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (12/17/09); 8021 (8/19/04); 8031 (8/19/04); 8041 (8/19/04); 8051 (8/19/04); 8061 (8/19/04); and 8071 (9/16/04). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

70. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

Attachment D

Stringency Analysis of District Rule 4311

Comparison of the Non-SIP amended version (amended June 18, 2009) of District Rule 4311-Flares with the SIP approved version (adopted June 20, 2002)

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
1.0 PURPOSE		
The purpose of this rule is to limit the emissions of volatile organic compounds (VOCs) and oxides of nitrogen (NOx) from the operation of flares.	X	
To limit the emissions of volatile organic compounds (VOC), oxides of nitrogen (NOx), and sulfur oxides (SOx) from the operation of flares.		X
2.0 APPLICABILITY		
This rule is applicable to flares that are owned and operated by major sources.	X	
This rule is applicable to operations involving the use of flares.		X
3.0 DEFINITIONS		
Air-Assisted Flare: a combustion device where forced air is injected to promote turbulence for mixing and to provide combustion air.	X	
Air-Assisted Flare: a combustion device where forced air is injected to promote turbulence for mixing and to provide combustion air.		X
Air Pollution Control Officer (APCO): as defined in Rule 1020 (Definitions).		X
Air Resources Board (ARB): as defined in Rule 1020 (Definitions).		X
British Thermal Unit (Btu): the amount of heat required to raise the temperature of one pound of water from 59 ^{o}F to 60 ^{o}F at one atmosphere.		X
Calendar Day: any day starting at twelve o'clock AM and ending at 11:59 PM.		X
Coanda Effect Flare: A flare in which the high pressure flare gas flows along a curved surface inspirating air into the gas to promote combustion.		X
Emergency: any situation or a condition arising from a sudden and reasonablyunforeseeable event beyond the control of the operator. An emergency situation requires immediate corrective action to restore safe operation. A planned flaring event shall not be considered as an emergency.	X	

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
Emergency: any situation or a condition arising from a sudden and reasonably unforeseeable and unpreventable event beyond the control of the operator. Examples include, but are not limited to, not preventable equipment failure, natural disaster, act of war or terrorism, or external power curtailment, excluding a power curtailment due to an interruptible power service agreement from a utility. A flaring event due to improperly designed equipment, lack of preventative maintenance, careless or improper operation, operator error or willful misconduct does not quality as an emergency. An emergency situation requires immediate corrective action to restore safe operation. A planned flaring event shall not be considered as an emergency.		X
Enclosed Flare: a flare composed of multiple gas burners that are grouped in an enclosure, and are staged to operate at a wide range of flow rates.	X	
Enclosed Flare: a flare composed of multiple gas burners that are grouped in an enclosure, and are staged to operate at a wide range of flow rates.		X
Feasible: Capable of being accomplished in a successful manner within a reasonable period of time, taking into account economic, environmental, legal, social, and technological factors.		X
Flare: a direct combustion device in which air and all combustible gases react at the burner with the objective of complete and instantaneous oxidation of the combustible gases. Flares are used either continuously or intermittently and are not equipped with devices for fuel-air mix control or for temperature control.	X	
Flare: a direct combustion device in which air and all combustible gases react at the burner with the objective of complete and instantaneous oxidation of the combustible gases. Flares are used either continuously or intermittently and are not equipped with devices for fuel-air mix control or for temperature control.		X
Flare Event: any intentional or unintentional combustion of vent gas in a flare. The flare event ends when the flow velocity drops below 0.12 feet per second or when the operator can demonstrate that no more vent gas was combusted based upon the monitoring records of the flare water seal level and/or other parameters as approved by the APCO in the Flare Monitoring and Recording Plan. For a flare event that continues for more than one calendar day, each calendar day or venting of gases shall constitute a separate flare event.		X
Flare Gas: gas burned in a flare.	X	

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
Flare Gas: gas burned in a flare.		X
Flare Minimization Plan (FMP): a document intended to meet the requirements of Section 6.5 of this Rule.		X
Flare Monitoring System: all flare monitoring and recording equipment used for the determination of flare operating parameters. Flare monitoring and recording equipment includes, but is not limited to, sample systems, transducers, transmitters, data acquisition equipment, data recording equipment, and video monitoring equipment and video recording equipment.		X
Flexigas: a low BTU fuel gas produced by gasifying coke produced in a fluid-bed Coker. Due to the air used in the gasifying process, Flexigas is approximately 50% nitrogen.		X
Gaseous Fuel: any gases used as combustion fuel which include, but are not limited to, any natural, process, synthetic, landfill, sewage digester, or waste gases. Gaseous fuel includes produced gas, pilot gas and, when burned, purge gas.	X	
Gaseous Fuel: any gases used as combustion fuel which include, but are not limited to, any natural, process, synthetic, landfill, sewage digester, or waste gases. Gaseous fuels include produced gas, pilot gas and, when burned, purge gas.		X
Non-Assisted Flare: a combustion device without any auxiliary provision for enhancing the mixing of air into its flame. This definition does not include those flares, that by design, provide excess air at the flare tip.	X	
Non-Assisted Flare: a combustion device without any auxiliary provision for enhancing the mixing of air into its flame. This definition does not include those flares that by design provide excess air at the flare tip.		X
Open Flare: a vertically or horizontally oriented open pipe flare from which gases are eleased into the air before combustion is commenced.	X	
Open Flare: a vertically or horizontally oriented open pipe flare from which gases are released into the air before combustion is commenced.		X
Operator: includes, but not limited to, any person who owns, leases, supervises, or operates a facility.		X
Petroleum Refinery: a facility that processes petroleum, as defined in the Standard Industrial Classification Manual as Industry No. 2911, Petroleum Refining. For the purpose of this rule, all portions of the petroleum refining operation, including those at non-contiguous locations operating flares, shall be considered as one petroleum refinery.		X
Pilot: an auxiliary burner used to ignite the vent gas routed to a flare.		X
Pilot Gas: the gas used to maintain the presence of a flame for ignition of vent gases.		X

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
Planned Flaring: a flaring operation that constitutes a designed and planned process at a source, and which would have been reasonably foreseen ahead of its actual occurrence, or is scheduled to occur. The operation of a flare for the purpose of performing equipment maintenance provided it does not exceed 200 hours per calendar year, or during compliance source testing or visible emission inspections is not considered planned flaring. Planned flaring includes, but is not limited to, the following flaring activities: -Oil or gas well tests, well related work, tests ordered by a regulatory agency. -Equipment depressurization for maintenance purposes. -Equipment start-up or shutdown. -Flaring of gas at production sources where no gas handling, gas injection or gas transmission facilities exists. -Flaring of off-specification gas (i.e. non PUC quality gas), unless the operator can demonstrate that the gas must be flared for engineering or safety reasons, e.g., under emergency.	X	
Planned Flaring: a flaring operation that constitutes a designed and planned process at a source, and which would have been reasonably foreseen ahead of its actual occurrence, or is scheduled to occur. Planned flaring includes, but is not limited to, the following flaring activities: -Oil or gas well tests, well related work, tests ordered by a regulatory agency. -Equipment depressurization for maintenance purposes. -Equipment start-up or shutdown. -Flaring of gas at production sources where no gas handling, gas injection or gas transmission facilities exists. -Flaring of off-specification gas (i.e. non-PUC quality gas), unless the operator can demonstrate that the gas must be flared for engineering or safety reasons, e.g., under emergency. -The operation of a flare for the purpose of performing equipment maintenance.		X
Prevention Measure: a component, system, procedure, or program that will minimize or eliminate flaring.		X
Public Utilities Commission (PUC) Quality Gas: any gaseous fuel, gas containing fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet and no more than five grains of total sulfur per one hundred (100) standard cubic feet. PUC quality gas shall also mean high methane (at least 80 % by volume) gas as specified in PUC's General Order 58-A.	X	
Public Utilities Commission (PUC) Quality Gas: any gaseous fuel, gas containing fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet and no more than five grains of total sulfur per one hundred (100) standard cubic feet. PUC quality gas shall also mean high methane (at least 80% by volume) gas as specified in PUC's General Order 58-A.		X

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
Purge Gas: Nitrogen, carbon dioxide, liquefied petroleum gas, or natural gas, any of which can be used to maintain a non-explosive mixture of gases in the flare header or provide sufficient exit velocity to prevent any regressive flame travel back into the flare header.	X	
Purge Gas: Nitrogen, carbon dioxide, liquefied petroleum gas, refinery fuel gas, or natural gas, any of which can be used to maintain a non-explosive mixture of gases in the flare header or provide sufficient exit velocity to prevent any regressive flame travel back into the flare header.		X
Refinery Fuel Gas: a combustible gas, which is a by-product of the refinery process.		X
Reportable Flaring Event: any flaring where more than 500,000 standard cubic feet of vent gas is flared per calendar day, or where sulfur oxide emissions are greater than 500 pounds per calendar day. A reportable flaring event ends when it can be demonstrated by monitoring required in Section 6.8 that the integrity of the water seal has been maintained sufficiently to prevent vent gas to the flare tip. For flares without water seals or water seal monitors as required by Section 6.8, a reportable flaring event ends when the rate of flow of vent gas falls below 0.12 feet per second.		X
Representative Sample: a sample of vent gas collected from the location as approved for flare monitoring and analyzed utilizing test methods specified in Section 6.3.4.		X
Shutdown: the procedure by which the operation of a process unit or piece of equipment is stopped due to the end of a production run, or for the purpose of performing maintenance, repair and replacement of equipment. Stoppage caused by frequent breakdown due to poor maintenance or operator error shall not be deemed a shutdown.		X
Startup: the procedure by which a process unit or piece of equipment achieves normal operational status, as indicated by such parameters as temperature, pressure, feed rate and product quality.		X
Steam-Assisted Flare: a combustion device where steam is injected into the combustion zone to promote turbulence for the mixing of the combustion air before it is introduced to the flame.	X	
Steam-Assisted Flare: a combustion device where steam is injected into the combustion zone to promote turbulence for the mixing of the combustion air before it is introduced to the flame.		X
Thermal oxidizer: an enclosed or partially enclosed combustion device, other than a flare, that is used to oxidize combustible gases.		X
Total Organic Gases: all hydrocarbon compounds containing hydrogen and carbon with or without other chemical elements.	X	
Total Organic Gases (TOG): all hydrocarbon compounds containing hydrogen and carbon with or without other chemical elements.		X

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
Turnaround: a planned activity involving shutdown and startup of one or several process units for the purpose of performing periodic maintenance, repair, replacement of equipment or installation of new equipment.		X
Vent Gas: any gas directed into a flare, excluding assisting air or steam, flare pilot gas, and any continuous purge gases.		X
Volatile Organic Compound (VOC): defined in Rule 1020 (Definitions).	X	
Volatile Organic Compound (VOC): as defined in Rule 1020 (Definitions).		X
Water Seal: a liquid barrier, or seal, to prevent the passage of gas. Water seals provide a positive means of flash-back prevention in addition to enabling the upstream flare system header to operate at a slight positive pressure at all times.		X
4.0 EXEMPTIONS		
Flares operated in municipal solid waste landfills subject to the requirements of Rule 4642 (Solid Waste Disposal Sites) are exempt from this rule.	X	
Flares operated in municipal solid waste landfills subject to the requirements of Rule 4642 (Solid Waste Disposal Sites) are exempt from this rule.		X
Flares that are subject to the requirements of 40 CFR 60 Subpart WWW (Standards of Performance for Municipal Waste Landfills), or Subpart Cc (Emission Guidelines and Compliance Times for Municipal Solid Waste Landfills) are exempt from this rule.	X	
Flares that are subject to the requirements of 40 CFR 60 Subpart WWW (Standards of Performance for Municipal Waste Landfills), or Subpart Cc (Emission Guidelines and Compliance Times for Municipal Solid Waste Landfills) are exempt from this rule.		X
Except for the recordkeeping requirements in Section 6.1.4 the requirements of this rule shall not apply to any stationary source that has the potential to emit, for all processes, less than ten (10.0) tons per year of VOC and less than ten (10.0) tons per year of NOx.		X
5.0 REQUIREMENTS		
Flares that are permitted to operate only during an emergency are not subject to the requirements of Sections 5.6 and 5.7.	X	
Flares that are permitted to operate only during an emergency are not subject to the requirements of Sections 5.6 and 5.7.		X
The flame shall be present at all times when combustible gases are vented through the flare.	X	
The flame shall be present at all times when combustible gases are vented through the flare.		X
The outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares.	X	
The outlet shall be equipped with an automatic ignition system,		X

<table>
<tr><th>District Rule 4311 Requirements</th><th>SIP Rule (Adopted 6/20/02)</th><th>Non-SIP Rule (Amended 6/18/09)</th></tr>
<tr><td>or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares.</td><td></td><td></td></tr>
<tr><td>Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present shall be installed and operated.</td><td>X</td><td></td></tr>
<tr><td>Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an alternative equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present shall be installed and operated.</td><td></td><td>X</td></tr>
<tr><td>Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging.</td><td>X</td><td></td></tr>
<tr><td>Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging.</td><td></td><td>X</td></tr>
<tr><td>Open flares (air-assisted, steam-assisted, or non-assisted) in which the flare gas pressure is less than 5 psig shall be operated in such a manner that meets the provisions of 40 CFR 60.18.</td><td>X</td><td></td></tr>
<tr><td>Open flares (air-assisted, steam-assisted, or non-assisted) in which the flare gas pressure is less than 5 psig shall be operated in such a manner that meets the provisions of 40 CFR 60.18. The requirements of this section shall not apply to Coanda effect flares.</td><td></td><td>X</td></tr>
<tr><td>Ground-level enclosed flares shall meet the following emission standards:

<table><tr><th>Type of Flare and Heat Release Rate in MMBtu/hr</th><th>VOC (lb/MMBtu)</th><th>NOx (lb/MMBtu)</th></tr><tr><td>Without Steam-assist</td><td></td><td></td></tr><tr><td><10 MMBtu</td><td>0.0051</td><td>0.0952</td></tr><tr><td>10-100 MMBtu</td><td>0.0027</td><td>0.1330</td></tr><tr><td>>100 MMBtu</td><td>0.0013</td><td>0.5240</td></tr><tr><td>With Steam-assist</td><td></td><td></td></tr><tr><td>All</td><td>0.14 as TOG</td><td>0.068</td></tr></table></td><td>X</td><td></td></tr>
<tr><td>Ground-level enclosed flares shall meet the following emission standards:

<table><tr><th>Type of Flare and Heat Release Rate in MMBtu/hr</th><th>VOC (lb/MMBtu)</th><th>NOx (lb/MMBtu)</th></tr><tr><td>Without Steam-assist</td><td></td><td></td></tr><tr><td><10 MMBtu</td><td>0.0051</td><td>0.0952</td></tr><tr><td>10-100 MMBtu</td><td>0.0027</td><td>0.1330</td></tr><tr><td>>100 MMBtu</td><td>0.0013</td><td>0.5240</td></tr><tr><td>With Steam-assist</td><td></td><td></td></tr><tr><td>All</td><td>0.14 as TOG</td><td>0.068</td></tr></table></td><td></td><td>X</td></tr>
</table>

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
Flare Minimization Plan Effective on and after July 1, 2011, flaring is prohibited unless it is consistent with an approved flare minimization plan (FMP), pursuant to Section 6.5, and all commitments listed in that plan have been met. This standard shall not apply if the APCO determines that the flaring is caused by an emergency as defined by Section 3.7 and is necessary to prevent an accident, hazard or release of vent gas directly to the atmosphere.		X
Petroleum Refinery SO_2 Performance Targets 5.9.1 Effective on and after January 1, 2011, the operator of a petroleum refinery shall minimize sulfur dioxide flare emissions to less than 1.50 tons per million barrels of crude processing capacity, calculated as an average over one calendar year. 5.9.2 Effective on and after January 1, 2017, the operator of a petroleum refinery shall minimize sulfur dioxide flare emissions to less than 0.50 tons per million barrels of crude processing capacity, calculated as an average over one calendar year.		X
Effective on and after July 1, 2011, the operator of a flare subject to flare minimization requirements pursuant to Section 5.8 shall monitor the vent gas flow to the flare with a flow measuring device or other parameters as specified in the Permit to Operate. The operator shall maintain records pursuant to Section 6.1.7. Flares that the operator can verify, based on permit conditions, are not capable of producing reportable flare events pursuant to Section 6.2.2 shall not be required to monitor vent gas flow to the flare.		X
Effective on and after July 1, 2011, the operator of a petroleum refinery or a flare with a flaring capacity equal to or greater than 50 MMBtu/hr shall monitor the flare pursuant to Sections 6.6, 6.7, 6.8, 6.9, and 6.10.		X
6.0 ADMINISTRATIVE REQUIREMENTS - COMPLIANCE DETERMINATION		
6.1.1 Upon request the operator of flares that are subject to Section 5.6 shall makeavailable to the APCO the compliance determination records that demonstrate compliance with the provisions of 40 CFR 60.18, (c)(3) through (c)(5).	X	
6.4.1 Upon request, the operator of flares that are subject to Section 5.6 shall make available, to the APCO, the compliance determination records that demonstrate compliance with the provisions of 40 CFR 60.18, (c)(3) through (c)(5).		X
6.1.2 The operator of ground-level enclosed flares shall conduct source testing at least once every 12 months to demonstrate compliance with Section 5.7. The operator shall submit a copy of the testing protocol to the APCO at least 30 days in advance of the scheduled testing. The operator shall submit the source test results not later than 45 days after completion of the source testing.	X	

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
6.4.2 The operator of ground-level enclosed flares shall conduct source testing at least once every 12 months to demonstrate compliance with Section 5.7. The operator shall submit a copy of the testing protocol to the APCO at least 30 days in advance of the scheduled testing. The operator shall submit the source test results not later than 45 days after completion of the source testing.		X
6.0 ADMINISTRATIVE REQUIREMENTS - RECORDKEEPING		
6.2.1 Copy of the compliance determination conducted pursuant to Section 6.1.1. 6.2.2 Copy of the source testing result conducted pursuant to Section 6.1.2. 6.2.3 For flares used during an emergency, record of the duration of flare operation, amount of gas burned, and the nature of the emergency situation.	X	
6.1.1 Copy of the compliance determination conducted pursuant to Section 6.4.1. 6.1.2 Copy of the source testing result conducted pursuant to Section 6.4.2. 6.1.3 For flares used during an emergency, record of the duration of flare operation, amount of gas burned, and the nature of the emergency situation. 6.1.4 Operators claiming an exemption pursuant to Section 4.3 shall record annual throughput, material usage, or other information necessary to demonstrate an exemption under that section. 6.1.5 Effective on and after July 1, 2011, a copy of the approved flare minimization plan pursuant to Section 6.5. 6.1.6 Effective on and after July 1, 2012, where applicable, a copy of annual reports submitted to the APCO pursuant to Section 6.2. 6.1.7 Effective on and after July 1, 2011, where applicable, monitoring data collected pursuant to Sections 5.10, 6.6, 6.7, 6.8, 6.9, and 6.10.		X
6.0 ADMINISTRATIVE REQUIREMENTS - TEST METHODS		
6.3.1 VOC, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case Method 25a may be used, and analysis of halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422 "Determination of Volatile organic Compounds in Emission from Stationary Sources". The VOC concentration in ppmv shall be converted to pounds per million Btu (lb/MMBtu) by using the following equation: VOC in lb/MMBtu = *(ppmv dry) x (F,dscf/MMBtu) / (1.135x10^6) x (20.9-%O_2)* Where: F = As determined by EPA Method 19	X	

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
6.3.1 VOC, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case Method 25a may be used, and analysis of halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422 "Determination of Volatile organic Compounds in Emission from Stationary Sources". The VOC concentration in ppmv shall be converted to pounds per million Btu (lb/MMBtu) by using the following equation: VOC in lb/MMBtu = *(ppmv dry) x (F,dscf/MMBtu) / (1.135x10^6) x (20.9-%O_2)* Where: F = As determined by EPA Method 19		X
6.3.2 NOx emissions in pounds per million BTU shall be determined by using EPA Method 19.	X	
6.3.2 NOx emissions in pounds per million BTU shall be determined by using EPA Method 19.		X
6.3.3 NOx and O2 concentrations shall be determined by using EPA Method 3A, EPA Method 7E, or ARB 100.	X	
6.3.3 NOx and O_2 concentrations shall be determined by using EPA Method 3A, EPA Method 7E, or ARB 100.		X
6.3.4 Testing and Sampling Methods for Flare Monitoring Effective on and after July 1, 2011 operators subject to vent gas composition monitoring requirements pursuant to Section 6.6 shall use the following test methods as appropriate, or by an alternative method approved by the APCO, ARB and EPA: 6.3.4.1 Total hydrocarbon content and methane content of vent gas shall be determined using ASTM Method D 1945-96, ASTM Method UOP 539-97, EPA Method 18, or EPA Method 25A or 25B, 6.3.4.2 Hydrogen sulfide content of vent gas shall be determined using ASTM Method D 1945-96, ASTM Method UOP 539-97, ASTM Method D 4084-94, or ASTM Method D 4810-88. 6.3.4.3 If vent gas composition is monitored with a continuous analyzer employing gas chromatography the minimum sampling frequency shall be one sample every 30 minutes. 6.3.4.4 If vent gas composition is monitored using continuous analyzers not employing gas chromatography, the total reduced sulfur content of vent gas shall be determined by using EPA Method D4468-85.		X
6.3.5 Flow Verification Test Methods For purposes of the flow verification report required by Section 6.2.3.8, vent gas flow shall be determined using one or more of the following methods, or by any alternative method approved by the APCO, ARB, and EPA: 6.3.5.1 EPA Methods 1 and 2; 6.3.5.2 A verification method recommended by the manufacturer of the flow monitoring equipment installed pursuant to Section 5.10. 6.3.5.3 Tracer gas dilution or velocity. 6.3.5.4 Other flow monitors or process monitors that can		X

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
provide comparison data on a vent stream that is being directed past the ultrasonic flow meter.		
6.4 Compliance Determination 6.4.1 Upon request, the operator of flares that are subject to Section 5.6 shall make available, to the APCO, the compliance determination records that demonstrate compliance with the provisions of 40 CFR 60.18, (c)(3) through (c)(5). 6.4.2 The operator of ground-level enclosed flares shall conduct source testing at least once every 12 months to demonstrate compliance with Section 5.7. The operator shall submit a copy of the testing protocol to the APCO at least 30 days in advance of the scheduled testing. The operator shall submit the source test results not later than 45 days after completion of the source testing.		X
6.5 Flare Minimization Plan 6.5.1 By July 1, 2010, the operator of a petroleum refinery flare or any flare that has a flaring capacity of greater than or equal to 5.0 MMBtu per hour shall submit a flare minimization plan (FMP) to the APCO for approval. The FMP shall include, but not be limited to: 6.5.1.1 A description and technical specifications for each flare and associated knock-out pots, surge drums, water seals and flare gas recovery systems. 6.5.1.2 Detailed process flow diagrams of all upstream equipment and process units venting to each flare, identifying the type and location of all control equipment. 6.5.1.3 A description of equipment, processes, or procedures the operator plans to install or implement to eliminate or minimize flaring and planned date of installation or implementation. 6.5.1.4 An evaluation of prevention measures to reduce flaring that has occurred or may be expected to occur during planned major maintenance activities, including startup and shutdown. 6.5.1.5 An evaluation of preventative measures to reduce flaring that may be expected to occur due to issues of gas quantity and quality. The evaluation shall include an audit of the vent gas recovery capacity of each flare system, the storage capacity available for excess vent gases, and the scrubbing capacity available for vent gases including any limitations associated with scrubbing vent gases for use as a fuel; and shall determine the feasibility of reducing flaring though the recovery, treatment and use of the gas or other means. 6.5.1.6 An evaluation of preventative measures to reduce flaring caused by the recurrent failure of air pollution control equipment, process equipment, or a process to operate in a normal or usual manner. The evaluation shall determine the adequacy of existing maintenance schedules and protocols for such equipment. For purposes of this section, a failure is recurrent if it occurs more than twice during any five year period as a result of the same cause as identified in accordance with Section 6.2.2. 6.5.1.7 Any other information requested by the APCO as necessary for determination of compliance with applicable		X

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
provisions of this rule. 6.5.2 Every five years after the initial FMP submittal, the operator shall submit an updated FMP for each flare to the APCO for approval. The current FMP shall remain in effect until the updated FMP is approved by the APCO. If the operator fails to submit an updated FMP as required by this section, the existing FMP shall no longer be considered an approved plan. 6.5.3 An updated FMP shall be submitted by the operator pursuant to Section 6.5 addressing new or modified equipment, prior to installing the equipment. Updated FMP submittals are only required if: 6.5.3.1 The equipment change would require an authority to construct (ATC) and would impact the emissions from the flare, and 6.5.3.2 The ATC is deemed complete after June 18, 2009, and 6.5.3.3 The modification is not solely the removal or decommissioning of equipment that is listed in the FMP, and has no associated increase in flare emissions. 6.5.4 When submitting the initial FMP, or updated FMP, the operator shall designate as confidential any information claimed to be exempt from public disclosure under the California Public Records Act, Government Code Section 6250 et seq. If a document is submitted that contains information designated confidential, the operator shall provide a justification for this designation and shall submit a separate copy of the document with the information designated confidential redacted.		
6.6 Vent Gas Composition Monitoring Effective on and after July 1, 2011, the operator of a petroleum refinery flare or any flare that has a flaring capacity equal to or greater than 50 MMBtu per hour shall monitor vent gas composition using one of the five methods pursuant to Section 6.6.1 through Section 6.6.5 as appropriate. 6.6.1 Sampling that meets the following requirements: 6.6.1.1 If the flow rate of vent gas flared in any consecutive 15-minute period continuously exceeds 330 standard cubic feet per minute (SCFM), a sample shall be taken within 15 minutes. The sampling frequency thereafter shall be one sample every three hours and shall continue until the flow rate of vent gas flared in any consecutive 15-minute period is continuously 330 SCFM or less. In no case shall a sample be required more frequently than once every 3 hours. 6.6.1.2 Samples shall be analyzed pursuant to Section 6.3.4. 6.6.2 Integrated sampling that meets the following requirements: 6.6.2.1 If the flow rate of vent gas flared in any consecutive 15 minute period continuously exceeds 330 SCFM, integrated sampling shall begin within 15 minutes and shall continue until the flow rate of vent gas flared in any consecutive 15 minute period is continuously 330 SCFM or less. 6.6.2.2 Integrated sampling shall consist of a minimum of one aliquot for each 15-minute period until the sample container is full. If sampling is still required pursuant to Section 6.6.2.1, a new sample container shall be placed in service within one hour		X

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
after the previous sample was filled. A sample container shall not be used for a sampling period that exceeds 24 hours. 6.6.2.3 Samples shall be analyzed pursuant to Section 6.3.4. 6.6.3 Continuous analyzers that meet the following requirements: 6.6.3.1 The analyzers shall continuously monitor for total hydrocarbon methane, and depending upon the analytical method used pursuant to Section 6.3.4, hydrogen sulfide or total reduced sulfur. 6.6.3.2 The hydrocarbon analyzer shall have a full-scale range of 100% total hydrocarbon. 6.6.3.3 Each analyzer shall be maintained to be accurate to within 20% when compared to any field accuracy tests or to within 5% of full scale. 6.6.4 Continuous analyzers employing gas chromatography that meet the following requirements: 6.6.4.1 The gas chromatography system shall monitor for total hydrocarbon, methane, and hydrogen sulfide. 6.6.4.2 The gas chromatography system shall be maintained to be accurate within 5% of full scale. 6.6.5 Monitor sulfur content using a colorimetric tube system on a daily basis, and monitor vent gas hydrocarbon on a weekly basis by collecting samples and having them tested pursuant to a method in Section 6.3.4. 6.6.6 If flares share a common header, a sample from the header will be deemed representative of vent gas composition for all flares served by the header. 6.6.7 The operator shall provide the APCO with access to the monitoring system to collect vent gas samples to verify the analysis required by Section 5.11.		
6.7 Pilot and Purge Gas Monitoring Effective on and after July 1, 2011, the operator of a petroleum refinery flare or any flare that has a flaring capacity equal to or greater than 50 MMBtu per hour shall monitor the volumetric flows of purge and pilot gases with flow measuring devices or other parameters as specified on the Permit to Operate so that volumetric flows of pilot and purge gas may be calculated based on pilot design and the parameters monitored.		X
6.8 Water Seal Monitoring Effective on and after July 1, 2011, the operator of a petroleum refinery flare or any flare that has a flaring capacity equal to or greater than 50 MMBtu per hour with a water seal shall monitor and record the water level and pressure of the water seal that services each flare daily or as specified on the Permit to Operate.		X
6.9 General Monitoring Effective on and after July 1, 2011, the operator of a petroleum refinery flare or any flare that has a flaring capacity equal to or greater than 50 MMBtu per hour shall comply with the following, as applicable: 6.9.1 Periods of flare monitoring system inoperation greater than 24 continuous hours shall be reported by the following working day, followed by notification of resumption of		X

District Rule 4311 Requirements	SIP Rule (Adopted 6/20/02)	Non-SIP Rule (Amended 6/18/09)
monitoring. Periods of inoperation of monitoring equipment shall not exceed 14 days per any 18-consecutive-month period. Periods of flare monitoring system inoperation do not include the periods when the system feeding the flare is not operating. 6.9.2 During periods of inoperation of continuous analyzers or auto-samplers installed pursuant to Section 6.6, operators responsible for monitoring shall take one sample within 30 minutes of the commencement of flaring, from the flare header or from an alternate location at which samples are representative of vent gas composition and have samples analyzed pursuant to Section 6.3.4. During periods of inoperation of flow monitors required by Section 5.10, flow shall be calculated using good engineering practices. 6.9.3 Maintain and calibrate all required monitors and recording devices in accordance with the applicable manufacturer's specifications. In order to claim that a manufacturer's specification is not applicable, the person responsible for emissions must have, and follow, a written maintenance policy that was developed for the device in question. The written policy must explain and justify the difference between the written procedure and the manufacturer's procedure. 6.9.4 All in-line continuous analyzer and flow monitoring data must be continuously recorded by an electronic data acquisition system capable of one-minute averages. Flow monitoring data shall be recorded as one-minute averages.		
6.10 Video Monitoring Effective on and after July 1, 2011, the operator of a petroleum refinery flare shall install and maintain equipment that records a real-time digital image of the flare and flame at a frame rate of no less than one frame per minute. The recorded image of the flare shall be of sufficient size, contrast, and resolution to be readily apparent in the overall image or frame. The image shall include an embedded date and time stamp. The equipment shall archive the images for each 24-hour period. In lieu of video monitoring the operator may use an alternative monitoring method that provides data to verify date, time, vent gas flow, and duration of flaring events.		X
7.0 COMPLIANCE SCHEDULE		
7.1 Flares that are installed and in operation before June 20, 2002 shall be in compliance with this rule by December 20, 2003. 7.2 Flares that are installed or constructed on or after June 20, 2002, shall be in compliance with this rule upon initial operation, and thereafter.	X	
Operators of flares, that are exempt under Section 4.0 and that lose exemption status, shall not operate flares until in full compliance with all applicable requirements of this rule effective on the date the exemption status is lost.		X

Attachment E

EPA and Facility Comments/District Response

EPA Comments/District Response

EPA submitted public comments regarding the District's analysis and preliminary decision on the issuance of Occidental of Elk Hills Inc.'s Initial Title V Permit, Facility S-1216, Project #S-1075158. A copy of the December 16, 2011 letter containing these comments is available at the District.

1. EPA COMMENT

Comment 1:
On page 72 of the Districts evaluation, under Section 19, several emission units are evaluated for CAM (Part 64 applicability). EPA notes that in numerous cases where the equipment includes vapor recovery, the evaluation states that the VOC control system is not a control device as defined in CAM and is therefore not subject to CAM. This is an insufficient analysis. The evaluation must include an explanation as to why a "control system" is not a "control device." EPA has recently noted in other proposed Title V permit actions that the District has determined that some vapor recovery systems are "inherent process equipment" and are therefore not subject to CAM requirements. EPA has disagreed with those determinations and provided comments to the District on how to reevaluate for CAM applicability.

This proposed permit has numerous tanks equipped with vapor recovery systems that EPA believes may be subject to CAM and for which a more detailed CAM applicability determination is required. In general, for tanks connected to a vapor recovery system, there are three parts to the system. First there is the storage tank which is the emitting source. The control device then consists of two parts, the capture and collection system, and finally the device that condenses or destroys the captured emissions. It is not clear from the current CAM evaluation whether any of the permitted vapor recovery systems are vented to control devices, but it is reasonable to expect that most systems are vented to some type of control device. The vapor recovery systems are not inherent process equipment because they are required to control emissions and do not affect the ability to operate a storage tank. Thus to properly evaluate CAM applicability the District must determine the uncontrolled emission rates from the emission units to determine if the emissions are over the major source thresholds. Any fugitive emissions from the capture and control system must be included in the emission rates.

Please review all permits for all tanks connected to a vapor recovery system for CAM applicability using the methodology EPA has outlined above and revise the CAM evaluation section as necessary.

DISTRICT RESPONSE

For oilfield tanks and wells, CAM is required if an emission unit is subject to emission limit or standard to the pollutant of concern, uses a control device to comply with the emission limit or standard, and has a potential pre-control emissions greater than 10 ton/year.

While most tanks and wells equipped with a vapor control system include an emission limit or standard and have uncontrolled potential to emit greater than 10 ton/year, we have concluded that the vapor control systems that they are equipped with do not meet the criteria of control device as defined in 40 CFR part 64.

The definition of control device from 40 CFR Part 64 is as follows (emphasis added):

> *Control device* means equipment, other than inherent process equipment, that is used to destroy or remove air pollutant(s) prior to discharge to the atmosphere. The types of equipment that may commonly be used as control devices include, but are not limited to, fabric filters, mechanical collectors, electrostatic precipitators, inertial separators, afterburners, thermal or catalytic incinerators, adsorption devices (such as carbon beds), condensers, scrubbers (such as wet collection and gas absorption devices), selective catalytic or non-catalytic reduction systems, flue gas recirculation systems, spray dryers, spray towers, mist eliminators, acid plants, sulfur recovery plants, injection systems (such as water, steam, ammonia, sorbent or limestone injection), and combustion devices independent of the particular process being conducted at an emissions unit (e.g., the destruction of emissions achieved by venting process emission streams to flares, boilers or process heaters). For purposes of this part, a control device does not include passive control measures that act to prevent pollutants from forming, such as the use of seals, lids, or roofs to prevent the release of pollutants, use of low-polluting fuel or feedstocks, or the use of combustion or other process design features or characteristics. If an applicable requirement establishes that particular equipment which otherwise meets this definition of a control device does not constitute a control device as applied to a particular pollutant-specific emissions unit, then that definition shall be binding for purposes of this part.

It is important to note that this definition includes an exemption for "inherent process equipment. Inherent process equipment is by definition not a control device. Emission units equipped with inherent process equipment are not subject to the requirements of CAM.

40 CFR Part 64 defines inherent process equipment as (emphasis added):

Inherent process equipment means equipment that is necessary for the proper or safe functioning of the process, or material recovery equipment that the owner or operator documents is installed and operated primarily for purposes other than compliance with air pollution regulations. Equipment that must be operated at an efficiency higher than that achieved during normal process operations in order to comply with the applicable emission limitation or standard is not inherent process equipment. For the purposes of this part, inherent process equipment is not considered a control device.

Please note that the above definition requires that inherent process equipment must be used "... for the proper or safe operation of the process ..." It is important to note that the equipment need not be used solely for the proper or safe operation of the process. Such systems could be used for compliance with regulations as well.

We have concluded that vapor control systems installed on oilfield tanks and oil production wells are inherent process equipment (and by definition not a control device) for the reasons stated below.

- Tank and well vapor control systems reduce emission of H2S (a toxic substance) from the tanks/wells and as such assure worker safety for OSHA and other regulatory requirements.

- Tank vapor control systems minimize air intrusion into the vapor space and as such reduce corrosion of the tank interior. Such systems are commonly installed even though they are not required to comply with District regulations. District Rule 4623 – Storage of Organic Liquids does not require vapor control on storage tanks storing liquids with a true vapor pressure of less than 0.5 psia. Due to the relatively low actual emissions from such tanks, vapor control is typically not a Rule 2201 best available control technology (BACT) requirement for most heavy crude oil storage tanks. Even though not required by District rules, facilities commonly install vapor control on storage tanks for safety and corrosion prevention purposes.

- As stated above, facilities commonly install vapor control on tanks even though there is not a requirement to do so. Vapor control has historically been installed on crude oil production well vents as well prior to the requirement to install such controls. In fact, the District has issued emission reduction credits for the installation of well vent vapor control systems.

- Vapors collected by tank and well vapor control systems are commonly burned in multiple existing units, e.g. steam generators, in which useful energy is recovered. Steam generators, are used in oil production to

enhance oil recovery from production wells. The steam generators, wells and tanks (with their associated vapor control systems) are part of the overall process to thermally enhance oil production.

Such systems typically distribute the vapors to multiple steam generators (or other devices) for use as a fuel. The quantity of vapors from such vapor control systems combusted in a particular steam generator varies as the operational needs of the facility change. For example, vapors that are typically combusted in a given steam generator would d be burned in a different approved steam generator instead if the first steam generator is taken out of service.

For all of the reasons stated above, we believe that tank and well vapor control systems are truly inherent to the oil production process. As such we believe that these systems meet the criteria for "inherent process systems" and as such are not a control device for the purposes of CAM applicability. Therefore, we do not believe that the emission units that are served by such systems are subject to the requirements of CAM.

Notwithstanding the above, we agree to work cooperatively with EPA Region IX to address CAM applicability issues on a programmatic basis in the future.

2. EPA COMMENT

On page 76 of the Districts evaluation, under Section 19.t., the District determines that permit unit S-1216-71-1 is subject to CAM, and states that the facility will monitor and record the catalyst inlet and outlet temperatures daily. Recent studies have shown that monitoring the temperature change across the catalyst is not an adequate indicator of compliance. EPA suggests setting a minimum inlet temperature to ensure the catalyst is at the proper operating temperature (determined by source testing) and periodic monitoring of the NOx emissions with a portable monitor. EPA notes that permit condition numbers 19-22 require periodic monitoring with a portable monitor and include conditions to ensure proper operation of the monitor. However the current frequency of this monitoring is only quarterly unless two consecutive violations are found, then monitoring would be required monthly for 12 months. EPA believes that since this emission unit is large enough to trigger CAM (i.e., the emission unit is an uncontrolled major source), that the periodic monitoring should be at least monthly.

Please revise condition 19 as needed to require monthly monitoring and the evaluation to indicate the type of monitoring required to comply with Part 64 CAM requirements.

DISTRICT RESPONSE

The monitoring parameters had been revised to daily monitoring and recording of the engine's O_2 sensor output voltage to meet the air/fuel ration setting. The O_2 voltage range of 0.1 volts DC to 0.9 volts DC shall be correlated to NO_X emissions limit during source testing and adjusted when necessary based on the results of the source test.

Facility Comments/District Response

Occidental of Elk Hills, Inc. submitted public comments regarding the District's analysis and preliminary decision of their Title V Permit Renewal. A copy of the September 26, 2011 letter containing these comments is available at the District.

1. FACILITY COMMENT

Proposed Modification to Equipment Description:

Permit Number	Proposed Modification
S-1216-42-1	500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (#.05GF17) SERVED BY VAPOR CONTROL SYSTEM INCLUDING COMPRESSOR(S) AND PIPING ~~TO GAS PIPELINE~~ SHARED WITH S-1216-43
S-1216-48-1	210 BBL FIXED ROOF SHIPPING TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH S-1216-49, S-1216-50, S-1216-59, S-1216-63, AND S-1216-86 ~~DISCHARGING TO FIELD GAS GATHERING LINE~~ (SEC 26 BUENA VISTA LEASE)
S-1216-86-1	100 BBL FIXED ROOF PRODUCTION TANK SERVED BY VAPOR CONTROL SYSTEM SHARED WITH ~~1212-48~~ S-1216-48
S-1216-95-3	WATERFLOOD PLANT/WATER CLEANING AND INJECTION OPERATION INCLUDING ONE 5,000 BBL WASH TANK (T1) SERVED BY A VAPOR CONTROL SYSTEM ~~AT GAS PLANT S-48~~
S-1216-96-2	2,000 BBL FIXED ROOF STORAGE/SHIPPING TANK (#3) SERVED BY A VAPOR RECOVERY SYSTEM ~~AT GAS PLANT S-48~~
S-1216-97-2	1,000 BBL FIXED ROOF FILTER FEED TANK (T5) SERVED BY A VAPOR CONTROL SYSTEM ~~AT GAS PLANT S-48~~
S-1216-98-2	2,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T4) SERVED BY A VAPOR CONTROL SYSTEM ~~AT GAS PLANT S-48~~
S-1216-122-1	1,000 BBL CRUDE OIL STORAGE TANK SERVED BY A VAPOR RECOVERY SYSTEM ~~AT GAS PLANT S-48~~ SHARED WITH S-1216-111
S-1216-123-1	10,000 BBL FIXED ROOF PETROLEUM STORAGE TANK SERVED BY A VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1216-125 AND '-126 ~~AT GAS PLANT S-48~~
S-1216-124-1	10,221 BBL FIXED ROOF STORAGE TANK SERVED BY A VAPOR RECOVERY SYSTEM ~~AT GAS PLANT S-48~~
S-1216-125-1	10,221 BBL FIXED ROOF STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM (SHARED WITH S-1216-123 AND '-126) ~~AT GAS PLANT S-48~~
S-1216-126-1	10,221 BBL FIXED ROOF STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM (SHARED WITH S-1216-123 AND '-125) ~~AT GAS PLANT S-48~~
S-1216-128-1	2,000 BBL FIXED ROOF WASH TANK SERVED BY A VAPOR CONTROL SYSTEM ~~INCLUDING PIPING TO CHEVRON 1-C GAS PLANT (S-48)~~
S-1216-132-2	WEMCO MODEL 84 OIL/WATER SEPARATOR RATED AT 40,000 BBL/DAY ~~AND~~ SERVED BY ~~GAS PLANT~~ VAPOR RECOVERY SYSTEM ~~AT FACILITY S-48~~
S-1216-133-2	500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T6) SERVED BY VAPOR CONTROL SYSTEM ~~AT GAS PLANT S-48~~
S-1216-134-2	500 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T7) SERVED BY VAPOR CONTROL SYSTEM ~~AT GAS PLANT S-48~~
S-1216-135-2	10,000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T2) SERVED BY VAPOR CONTROL SYSTEM ~~AT GAS PLANT S-48~~
S-1216-136-2	2000 BBL FIXED ROOF CRUDE OIL PRODUCTION TANK (T8) SERVED BY VAPOR CONTROL SYSTEM ~~AT GAS PLANT S-48~~
S-1216-137-2	500 BBL FIXED ROOF CRUDE OIL STORAGE TANK T9 SERVED BY VAPOR

	CONTROL SYSTEM ~~AT GAS PLANT S-48~~
S-1216-152-1	2000 BBL PRODUCED WATER TANK WITH VAPOR CONTROL SYSTEM UNDER PERMIT S-1216-142 (STEVENS LEASE)
S-1216-153-1	2000 BBL PRODUCED WATER TANK WITH VAPOR CONTROL SYSTEM UNDER PERMIT S-1216-142 (STEVENS LEASE)
S-1216-154-1	1000 BBL PRODUCED WATER TANK #508 WITH VAPOR CONTROL SYSTEM UNDER PERMIT S-1216-142 (STEVENS LEASE)

DISTRICT RESPONSE

Revised equipment descriptions as proposed.

2. FACILITY COMMENT

S-1216-0-1: a) Remove Condition 42: PTO indicates that it is part of "Light Oil Western"

DISTRICT RESPONSE

The condition is retained. The condition is utilized by the District to identify facilities that are part of one stationary source.

3. FACILITY COMMENT

S-1216-1-2, -2-2, -3-2, -7-2, -8-2, -10-2, -11-2, -20-2, -21-2, -55-1, -56-1:

a) Move Conditions 3, 4, 10, 11, and 12 to Facility Wide Permit
b) Move Condition 13 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 9: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are tank cleaning conditions for storage tanks that are exempt from the requirements of District Rule 4623 and are not applicable to all storage tanks.
b) Added tank to the beginning of the condition but the condition is not moved to the Facility Wide Permit for reasons stated in the prior response.
c) Condition 9 remains on the permit. The condition refers to applicable requirements for tanks that are not subject to the requirements of District Rule 4623.

4. FACILITY COMMENT

S-1216-22-2:

a) Move Conditions 3, 12, 13, and 14 to Facility Wide Permit
b) Move Condition 15 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 2: Streamline using template condition.
d) Remove Condition 4: Condition 5 satisfies requirement.
e) Remove Condition 11: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"
f) Modify Condition 1 to read, "True vapor pressure of liquids introduced, placed, stored or held in this tank shall be less than 11.0 psia." Pursuant to Rule 4623.

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Conditions 2 and 4 are NSR conditions and will not be removed under Title V. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 11 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.
e) Condition 1 is an NSR condition and will not be modified under Title V. The facility needs to submit an application to modify the permit to remove the conditions.

5. FACILITY COMMENT

S-1216-42-1, -43-1, -101-1, -102-1, -103-1, -104-1, -105-1, -111-1, -122-1, and -124-1:

a) Move Conditions 6, 7, 8, 9, 10, 11, 12, 14, 15, and 16 to Facility Wide Permit
b) Move Condition 13 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 5: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate."

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.

b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 11 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

6. FACILITY COMMENT

S-1216-44-1:

a) Move Conditions 13, 14, 15, 16, 17, 18, 19, 21, 22, and 23 to Facility Wide Permit
b) Move Condition 20 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 3: Condition 10 satisfies requirement.
d) Remove Condition 6: Streamline to match template conditions.
e) Remove Condition 7: Streamline to match template conditions.
f) Remove Condition 8: Streamline to match template conditions.
g) Remove Condition 12: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Conditions 3, 6, 7, and 8 are NSR conditions and will be retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 12 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

7. FACILITY COMMENT

S-1216-45-1:

a) Move Conditions 4, 9, 10, and 11 to Facility Wide Permit
b) Move Condition 12 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 8: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 8 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

8. FACILITY COMMENT

S-1216-46-1:

a) Move Conditions 12, 13, 14, 15, 16, 17, 18, 20, 21 and 22 to Facility Wide Permit
b) Move Condition 19 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 1: Condition 9 satisfies requirement.
d) Remove Condition 11: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 1 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 11 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

9. FACILITY COMMENT

S-1216-47-1:

a) Move Conditions 4, 5, 11, 12, and 13 to Facility Wide Permit
b) Move Condition 14 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 10: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 10 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

10. FACILITY COMMENT

S-1216-48-1:

a) Move Conditions 10, 11, 12, 13, 14, 15, 16, 18, 19 and 20 to Facility Wide Permit
b) Move Condition 17 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 3: Tank is served by vapor control system.
d) Remove Condition 7: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 3 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 7 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

11. FACILITY COMMENT

S-1216-49-1, -94-1, -96-2, -123-1, -125-1, -126-1, and -128-1:

a) Move Conditions 7, 8, 9, 10, 11, 12, 13, 15, 16 and 17 to Facility Wide Permit
b) Move Condition 14 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 2: Condition 1 satisfies requirement.
d) Remove Condition 6: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 2 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 6 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

12. FACILITY COMMENT

S-1216-50-1, -65-1 and -100-1:

a) Move Conditions 8, 9, 10, 11, 12, 13, 14, 16, 17 and 18 to Facility Wide Permit
b) Move Condition 15 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 3: Condition 1 satisfies requirement.
d) Remove Condition 7: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 3 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 7 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

13. FACILITY COMMENT

S-1216-53-1:

a) Move Conditions 4, 10, 11, and 12 to Facility Wide Permit
b) Move Condition 13 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."

c) Remove Condition 9: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are tank cleaning conditions for storage tanks that are exempt from the requirements of District Rule 4623 and are not applicable to all storage tanks.
b) Added tank to the beginning of the condition but the condition is not moved to the Facility Wide Permit for reasons stated in the prior response.
c) Condition 9 remains on the permit. The condition refers to applicable requirements for tanks that are not subject to the requirements of District Rule 4623.

14. FACILITY COMMENT

S-1216-54-1:

a) Move Conditions 7, 8, 9, 10, 11, 12, 13, 15, 16 and 17 to Facility Wide Permit
b) Move Condition 14 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 5: Tank vents to vapor recovery system as indicated in equipment description.
d) Remove Condition 6: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 5 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 6 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

15. FACILITY COMMENT

S-1216-59-1, -72-1, -73-1, -75-1, and -78-1

a) Move Conditions 10, 11, 12, 13, 14, 15, 16, 18, 19 and 20 to Facility Wide Permit

b) Move Condition 17 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 2: Condition 1 satisfies requirement.
d) Remove Condition 9: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 2 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 9 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

16. FACILITY COMMENT

S-1216-60-1, -61-1, and -62-1,

a) Move Conditions 7, 8, 9, 10, 11, 12, 13, 15, 16 and 17 to Facility Wide Permit
b) Move Condition 14 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) ATC removed Condition 4.
d) Remove Condition 6: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 4 is a NSR condition and retained in the permit. The condition will be removed upon implementation of the ATC.
d) Condition 6 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

17. FACILITY COMMENT

S-1216-63-1

a) Move Conditions 11, 12, 13, 14, 15, 16, 17, 19, 20 and 21 to Facility Wide Permit
b) Move Condition 18 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 4: Condition 1 satisfies requirement.
d) Remove Condition 6: Tank is equipped with vapor control system.
e) Remove Condition 10: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Conditions 4 and 6 are NSR conditions and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 10 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

18. FACILITY COMMENT

S-1216-64-3

a) Move Conditions 9, 10, 11, 12, 13, 14, 15, 17, 18 and 19 to Facility Wide Permit
b) Move Condition 16 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 2: Condition 1 satisfies requirement.
d) Remove Condition 8: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.

c) Condition 2 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 8 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

19. FACILITY COMMENT

S-1216-66-1

a) Move Conditions 12, 13, 14, 15, 16, 17, 18, 20, 21, and 22 to Facility Wide Permit
b) Move Condition 19 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 2: Condition 101 in Facility Wide Permit satisfies requirement.
d) Remove Condition 11: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"
e) Modify Condition 4 to read, "Tank shall be maintained in a leak-free condition."

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 2 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 11 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.
e) Condition 4 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.

20. FACILITY COMMENT

S-1216-70-1

a) Combine Conditions 6, 7, and 8 into one condition that reads "Upon recommencing operation the emission concentration shall not exceed 5 ppmvd @ 15% O2 for NOx, 56 ppmvd @ 15% O2 for CO, and 25 ppmvd, as methane, @ 15% O2 for VOC."
b) Remove Conditions 7, and 8: Look at change in condition 6.

c) Combine Conditions 9 and 10 into one condition that reads "Upon recommencing operation emissions shall not exceed 10.0 lbs/MMscf for PM10 and 2.85 lbs/MMscf for SOx of natural gas used."
d) Remove Condition 10: Look at change in condition 9.

DISTRICT RESPONSE

a) Revised condition as proposed.
b) Removed conditions as proposed.
c) Revised condition as proposed.
d) Removed conditions as proposed.

21. FACILITY COMMENT

S-1216-71-1

a) Combine Conditions 2, 3, and 4 into one condition that reads "The emission concentration shall not exceed 5 ppmvd @ 15% O2 for NOx, 56 ppmvd @ 15% O2 for CO, and 25 ppmvd, as methane, @ 15% O2 for VOC."
b) Remove Conditions 3, and 4: Look at change in condition 2.
c) Remove Condition 32: Catalyst temperature range provided (750-1250 degree F).

DISTRICT RESPONSE

a) Revised condition as proposed.
b) Removed conditions as proposed.
c) Per applicant's revised comment, the monitoring of the catalyst temperature range was changed to the monitoring of the O_2 sensor output voltage within 0.1 volts DC to 0.9 volts DC on a daily basis.

22. FACILITY COMMENT

S-1216-86-1

a) Move Conditions 11, 12, 13, 14, 15, 16, 17, 19, 20, and 21 to Facility Wide Permit
b) Move Condition 18 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 3: Tank is served by vapor control system.
d) Remove Condition 10: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 3 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 10 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

23. FACILITY COMMENT

S-1216-93-2, -109-2, and -110-2

a) Move Conditions 13, 14, 15, 16, 17, 18, 19, 21, 22, and 23 to Facility Wide Permit
b) Move Condition 20 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 2: Condition 1 satisfies requirement.
d) Remove Condition 26: PTO indicates that it is part of "Light Oil Western,"
e) Remove Condition 12: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 2 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 26 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
e) Condition 12 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

24. FACILITY COMMENT

S-1216-95-3

a) Move Conditions 14, 15, 16, 17, 18, 19, 20, 22, 23, and 24 to Facility Wide Permit
b) Move Condition 21 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove "1 C gas plant (S-48) collection system" ADD "vapor control system" Condition 3 will now read, "The operation shall include vapor piping from tanks T1 (S-1216-95), T2 (S-1216-135), T3 (S-1216-96), T4 (S-1216-98), T5 (S-1216-97), T6 (S-1216-133), T7 (S-1216-134), T8 (S-1216-136) and Wemco (S-1216-132) to vapor control system."
d) ATC removed Condition 6.
e) ATC changed Condition 9.
f) Remove Condition 13: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Revised condition as proposed.
d) Condition 6 is a NSR condition and retained in the permit. The condition will be removed upon implementation of the Authority to Construct (ATC).
e) Condition 9 is a NSR condition and retained in the permit. The condition will be changed upon implementation of the Authority to Construct (ATC).
f) Condition 13 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

25. FACILITY COMMENT

S-1216-97-2, and -98-2

a) Move Conditions 12, 13, 14, 15, 16, 17, 18, 20, 21 and 22 to Facility Wide Permit
b) Move Condition 19 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) ATC removed Condition 4.

d) ATC changed Condition 7.
e) Remove Condition 11: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 4 is a NSR condition and retained in the permit. The condition will be removed upon implementation of the Authority to Construct (ATC).
d) Condition 7 is a NSR condition and retained in the permit. The condition will be changed upon implementation of the Authority to Construct (ATC).
e) Condition 11 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

26. FACILITY COMMENT

S-1216-106-1

a) Move Conditions 4, 5, 11, 12, and 13 to Facility Wide Permit
b) Move Condition 14 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 1: Satisfied by condition #2.
d) Remove Condition 10: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are tank cleaning conditions for storage tanks that are exempt from the requirements of District Rule 4623 and are not applicable to all storage tanks.
b) Added tank to the beginning of the condition but the condition is not moved to the Facility Wide Permit for reasons stated in the prior response.
c) Removed condition as proposed.
d) Condition 10 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

27. FACILITY COMMENT

S-1216-107-2

a) Move Conditions 10, 16, 17, and 18 to Facility Wide Permit
b) Move Condition 19 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 15: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are tank cleaning conditions for storage tanks that are exempt from the requirements of District Rule 4623 and are not applicable to all storage tanks.
b) Added tank to the beginning of the condition but the condition is not moved to the Facility Wide Permit for reasons stated in the prior response.
c) Condition 15 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

28. FACILITY COMMENT

S-1216-127-2

a) Move Conditions 7, 11, 12, and 13 to Facility Wide Permit
b) Move Condition 14 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 10: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 10 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

29. FACILITY COMMENT

S-1216-129-1

a) Move Conditions 4, 5, 11, 12, and 13 to Facility Wide Permit
b) Move Condition 14 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 10: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"
d) Modify Condition 16 to read "Formerly S-2010-194."

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are tank cleaning conditions for storage tanks that are exempt from the requirements of District Rule 4623 and are not applicable to all storage tanks.
b) Added tank to the beginning of the condition but the condition is not moved to the Facility Wide Permit for reasons stated in the prior response.
c) Condition 10 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.
d) Revised condition as proposed.

30. FACILITY COMMENT

S-1216-130-1

a) Move Conditions 8, 9, 10, 11, 12, 13, 14, 16, 17, and 18 to Facility Wide Permit
b) Move Condition 15 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 7: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 7 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

31. FACILITY COMMENT

S-1216-131-1

a) Move Conditions 14, 15, 16, 17, 18, 19, 20, 22, 23 and 24 to Facility Wide Permit
b) Move Condition 21 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 2: Condition 1 satisfies requirement.
d) Remove Condition 8: Streamline to match template conditions.
e) Remove Condition 9: Streamline to match template conditions.
f) Remove Condition 10: Streamline to match template conditions.
Remove Condition 13: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Conditions 2, 8, 9, and 10 are NSR conditions and will be retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 13 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

32. FACILITY COMMENT

S-1216-133-2

a) Move Conditions 10, 11, 12, 13, 14, 15, 16, 18, 19 and 20 to Facility Wide Permit
b) Move Condition 17 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) ATC removed Condition 3.
d) ATC changed Condition 6.
e) Remove Condition 9: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.

b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 3 is a NSR condition and retained in the permit. The condition will be removed upon implementation of the Authority to Construct (ATC).
d) Condition 6 is a NSR condition and retained in the permit. The condition will be changed upon implementation of the Authority to Construct (ATC).
e) Condition 9 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

33. FACILITY COMMENT

S-1216-134-2, -135-2, and -136-2

a) Move Conditions 11, 12, 13, 14, 15, 16, 17, 19, 20 and 21 to Facility Wide Permit
b) Move Condition 18 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) ATC removed Condition 3.
d) ATC changed Condition 6.
e) Remove Condition 10: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 3 is a NSR condition and retained in the permit. The condition will be removed upon implementation of the Authority to Construct (ATC).
d) Condition 6 is a NSR condition and retained in the permit. The condition will be changed upon implementation of the Authority to Construct (ATC).
e) Condition 10 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

34. FACILITY COMMENT

S-1216-137-2, and -143-1

a) Move Conditions 9, 10, 11, 12, 13, 14, 15, 17, 18 and 19 to Facility Wide Permit
b) Move Condition 16 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations

where wastewater treatment facilities are limited, or during the months of December through March."

c) Remove Condition 8: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 8 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

35. FACILITY COMMENT

S-1216-142-2

a) Move Conditions 8, 9, 10, 11, 12, 13, 14, 16, 17 and 18 to Facility Wide Permit
b) Move Condition 15 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 5: Tank vents to vapor control system.
d) Remove Condition 7: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 7 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the conditions.
d) Condition 7 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

36. FACILITY COMMENT

S-1216-144-1, and -145-1

a) Move Conditions 7, 8, 9, 10, 11, 12, 13, 15, 16 and 17 to Facility Wide Permit

b) Move Condition 14 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 6: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 6 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

37. FACILITY COMMENT

S-1216-146-1, and -147-1

a) Move Conditions 3, 8, 9, and 10 to Facility Wide Permit
b) Move Condition 11 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 7: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 7 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.

38. FACILITY COMMENT

S-1216-152-1, -153-1, and -154-1

a) Move Conditions 10, 11, 12, 13, 14, 15, 16, 18, 19 and 20 to Facility Wide Permit
b) Move Condition 17 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations

where wastewater treatment facilities are limited, or during the months of December through March."

c) Remove Condition 9: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"
d) Remove Condition 1: Requirement added to Equipment Description.

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 9 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.
d) Condition 1 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the condition.

39. FACILITY COMMENT

S-1216-155-1 and -156-1

a) Move Conditions 14, 15, 16, 17, 18, 19, 20, 22, 23 and 24 to Facility Wide Permit
b) Move Condition 21 to Facility Wide Permit, Add "Tank" to the beginning of the condition, so it will read "Tank steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March."
c) Remove Condition 13: Redundant condition, each permit contains compliance statement "These terms and conditions are part of the Facility Wide Permit to Operate"
d) Remove Condition 1: Tank vents to vapor control system as indicated in equipment description

DISTRICT RESPONSE

a) The conditions are not moved to the Facility Wide Permit since these conditions are applicable to storage tanks subject to the requirements of District Rule 4623.
b) Added tank to the beginning of the condition but retained in the permit since the condition is only applicable to storage tanks subject to the requirements of District Rule 4623.
c) Condition 13 refers to applicable requirements in the Facility Wide Permit and is retained on the permit.
d) Condition 1 is a NSR condition and retained in the permit. The facility needs to submit an application to modify the permit to remove the condition.