



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765

Title Page
Facility I.D.#: 019130
Revision #: 2
Date: November 27, 2007

FACILITY PERMIT TO OPERATE

**HALLMARK SW CORP
25525 REDLANDS BLVD
LOMA LINDA, CA 92354**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By *Carol Coy*
Carol Coy
Deputy Executive Officer
Engineering & Compliance



**FACILITY PERMIT TO OPERATE
HALLMARK SW CORP**

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	0	03/06/2006
B	RECLAIM Annual Emission Allocation	0	03/06/2006
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	2	11/27/2007
E	Administrative Conditions	0	03/06/2006
F	RECLAIM Monitoring and Source Testing Requirements	0	03/06/2006
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	0	03/06/2006
H	Permit To Construct and Temporary Permit to Operate	0	03/06/2006
I	Compliance Plans & Schedules	0	03/06/2006
J	Air Toxics	0	03/06/2006
K	Title V Administration	0	03/06/2006
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	0	03/06/2006
B	Rule Emission Limits	0	03/06/2006



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
443297	F78058	SPRAY BOOTH PAINT AND SOLVENT
443298	F78060	SPRAY BOOTH PAINT AND SOLVENT
443299	F78061	SPRAY BOOTH PAINT AND SOLVENT
443300	F78062	SPRAY BOOTH PAINT AND SOLVENT
443301	F78063	SPRAY BOOTH PAINT AND SOLVENT
444361	F78064	SPRAY BOOTH PAINT AND SOLVENT
458642	F93935	OPEN SPRAY SYSTEM NO. 1
458643	F93936	OPEN SPRAY SYSTEM NO. 2
458644	F93937	OPEN SPRAY SYSTEM NO. 3

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.
[RULE 401]
2. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 68 POUNDS IN ANY ONE DAY.
[RULE 1303 (b) (2)-OFFSET]
3. THE TOTAL QUANTITY OF VOC EMISSIONS FROM THE USE OF ALL VOC-CONTAINING MATERIALS IN EQUIPMENT OR PROCESSES SUBJECT TO RULE 442 AT THIS FACILITY SHALL NOT EXCEED 833 POUNDS IN ANY ONE CALENDAR MONTH. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH CALENDAR MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE CALENDAR MONTH FROM ALL EQUIPMENT AND OPERATIONS SUBJECT TO RULE 442 AT THE FACILITY.
[RULE 442]
4. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY DAILY VOC EMISSIONS IN POUNDS, AND THE VOC CONTENT OF COATINGS AND SOLVENTS IN POUNDS PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT SOLVENTS.
[RULE 109, 1303(b) (2)-OFFSET]
5. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b) (2)-OFFSET]
6. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE KEPT IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED AT THE FACILITY FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 1303(b) (2)-OFFSET]



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMIT TO OPERATE

Permit No. F78058
A/N 443297

Equipment Description:

SPRAY BOOTH, COLEMAN INDUSTRIES, FLOOR TYPE, 16'-0" W. X 6'-0" D. X 8'-0" H., WITH EIGHT 36" X 48" EXHAUST FILTERS, AND ONE 3 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST TWO INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED AND MAINTAINED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS, AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS), AND TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT.
[RULE 109, RULE 1303(b)(2)-OFFSET]

Periodic Monitoring:

6. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER MEDIA ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
7. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
- [RULE 3004 (a)(4)]

Emissions And Requirements:

- 8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - VOC: RULE 109
 - VOC: RULE 1136, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 481



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMIT TO OPERATE

Permit No. F78060
A/N 443298

Equipment Description:

SPRAY BOOTH, BINKS MODEL FA-16-17-T, FLOOR TYPE, 16'-0" W. X 7'-0" D. X 7'-0" H., WITH ONE FOOT WIDE PRE-CLEANING BAFFLES, TWO 16 FT X 3 FT EXHAUST FILTERS, AND ONE 3 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST TWO INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED AND MAINTAINED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS, AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS), AND TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT.
[RULE 109, RULE 1303(b)(2)-OFFSET]

Periodic Monitoring:

6. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER MEDIA ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
7. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
- [RULE 3004 (a)(4)]

Emissions And Requirements:

- 8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - VOC: RULE 109
 - VOC: RULE 1136, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 481



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMIT TO OPERATE

Permit No. F78061
A/N 443299

Equipment Description:

SPRAY BOOTH, BINKS MODEL FA-16-7-T, FLOOR TYPE, 16'-0" W. X 10'-0" D. X 7'-0" H., WITH ONE FOOT WIDE PRE-CLEANING BAFFLES, TWO 16 FT X 3 FT EXHAUST FILTERS, AND ONE 3 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST TWO INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED AND MAINTAINED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS, AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS), AND TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT.
[RULE 109, RULE 1303(b)(2)-OFFSET]

Periodic Monitoring:

6. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER MEDIA ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
7. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
- [RULE 3004 (a)(4)]

Emissions And Requirements:

- 8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - VOC: RULE 109
 - VOC: RULE 1136, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 481



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMIT TO OPERATE

Permit No. F78062
A/N 443300

Equipment Description:

SPRAY BOOTH, HALLMARK, WATER-WASH, FLOOR TYPE, 10'-0" W. X 2'-0" D. X 8'-0" H., WITH ONE 1/2 HP RECIRCULATING PUMP AND ONE 2 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS THE WATER-WASH UNIT IS PROPERLY MAINTAINED AND IS IN FULL OPERATION WITH THE WATER CURTAIN COMPLETELY COVERING THE EXHAUST SECTION OF THE BOOTH.
[RULE 1303(a)(1)-BACT]
4. THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS, AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS), AND TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT.
[RULE 109, RULE 1303(b)(2)-OFFSET]

Periodic Monitoring:

5. THE OPERATOR SHALL NOT OPERATE THIS EQUIPMENT UNLESS THE WATER WASH UNIT IS PROPERLY MAINTAINED AND IN FULL OPERATION WITH THE WATER CURTAIN COMPLETELY COVERING THE EXHAUST SECTION OF THE BOOTH. THE OPERATOR SHALL ALSO PERFORM A WEEKLY INSPECTION OF THE WATER CURTAIN INTEGRITY. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE WATER WASH;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 1136, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMIT TO OPERATE

Permit No. F78063
A/N 443301

Equipment Description:

SPRAY BOOTH, HALLMARK, WATER-WASH, FLOOR TYPE, 10'-0" W. X 2'-0" D. X 8'-0" H., WITH ONE 1/2 HP RECIRCULATING PUMP AND ONE 2 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS THE WATER-WASH UNIT IS PROPERLY MAINTAINED AND IS IN FULL OPERATION WITH THE WATER CURTAIN COMPLETELY COVERING THE EXHAUST SECTION OF THE BOOTH.
[RULE 1303(a)(1)-BACT]
4. THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS, AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS), AND TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT.
[RULE 109, RULE 1303(b)(2)-OFFSET]

Periodic Monitoring:

5. THE OPERATOR SHALL NOT OPERATE THIS EQUIPMENT UNLESS THE WATER WASH UNIT IS PROPERLY MAINTAINED AND IN FULL OPERATION WITH THE WATER CURTAIN COMPLETELY COVERING THE EXHAUST SECTION OF THE BOOTH. THE OPERATOR SHALL ALSO PERFORM A WEEKLY INSPECTION OF THE WATER CURTAIN INTEGRITY. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE WATER WASH;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109

VOC: RULE 1136, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

PM: RULE 481



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMIT TO OPERATE

Permit No. F78064
A/N 444361

Equipment Description:

SPRAY BOOTH, HALLMARK, WATER-WASH, FLOOR TYPE, 10'-0" W. X 2'-0" D. X 8'-0" H., WITH ONE 1 HP RECIRCULATING PUMP AND ONE 2 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS THE WATER-WASH UNIT IS PROPERLY MAINTAINED AND IS IN FULL OPERATION WITH THE WATER CURTAIN COMPLETELY COVERING THE EXHAUST SECTION OF THE BOOTH.
[RULE 1303(a)(1)-BACT]
4. THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS, AND THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS), AND TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT.
[RULE 109, RULE 1303(b)(2)-OFFSET]

Periodic Monitoring:

5. THE OPERATOR SHALL NOT OPERATE THIS EQUIPMENT UNLESS THE WATER WASH UNIT IS PROPERLY MAINTAINED AND IN FULL OPERATION WITH THE WATER CURTAIN COMPLETELY COVERING THE EXHAUST SECTION OF THE BOOTH. THE OPERATOR SHALL ALSO PERFORM A WEEKLY INSPECTION OF THE WATER CURTAIN INTEGRITY. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE WATER WASH;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
[RULE 3004 (a)(4)]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 1136, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 481



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMIT TO OPERATE

Permit No. F93935
A/N 458642

Equipment Description:

OPEN SPRAY SYSTEM NO. 1, PRIMARY, WITH ONE GRACO BULLDOG PUMP AND TWO GRACO ALPHA PLUS AIRLESS SPRAY GUNS MODEL 243283.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE VOC CONTENT OF MATERIALS USED IN THIS EQUIPMENT SHALL NOT EXCEED 1.25 POUND OF VOC PER GALLON OF COATING, AS APPLIED, LESS WATER AND EXEMPT COMPOUNDS.
[RULE 1303(a) (1)-BACT]
4. THIS EQUIPMENT SHALL ONLY BE USED TO SPRAY THE INTERIOR OF THE MOBILE HOMES.
[RULE 1303(a) (1)-BACT, RULE 1303(b) (2)-OFFSET]
5. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS THE MOBILE HOME SECTION IT IS USED TO COAT IS COMPLETELY COVERED BY PLASTIC ON ITS OPEN SIDE, AND ALL OTHER WINDOW AND DOOR OPENINGS OF THE MOBILE HOME. THE PLASTIC COVERING SHALL BE KEPT IN PLACE FOR AT LEAST TWENTY MINUTES AFTER THE COATING OPERATION IS COMPLETED.
[RULE 1303(a) (1)-BACT, RULE 1303(b) (2)-OFFSET]
6. THE TOTAL QUANTITY OF PARTICULATE MATTER LESS THAN TEN MICRON DIAMETER (PM₁₀) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 9.84 POUNDS IN ANY ONE DAY.
[RULE 1303(b) (1)-MODELING, RULE 1303(b) (2)-OFFSET]
7. THE TOTAL QUANTITY OF PM₁₀ EMISSIONS FROM SPRAY SYSTEM NOS. 1 - 3 UNDER A/Ns 458642, 458643 AND 458644 COMBINED SHALL NOT EXCEED 630 POUNDS IN ANY CALENDAR MONTH.
[RULE 1303(b) (2)-OFFSET]
8. THE PM₁₀ EMISSIONS FROM THIS EQUIPMENT SHALL BE CALCULATED USING THE FORMULA:
$$PM_{10} \text{ LB/DAY} = (\text{QUANTITY OF COATING SPRAYED, IN GALLONS/DAY}) \times (\text{COATING SOLID CONTENT, IN POUNDS PER GALLON}) \times (1-0.45) \times (1-0.95) \times (0.50)$$

[RULE 1303(b) (2)-OFFSET]



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

9. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS, THE DAILY AND CALENDAR MONTHLY PM₁₀ EMISSIONS IN POUNDS, AND THE VOC CONTENT AND SOLIDS CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS).
[RULE 109, RULE 1303(b) (2)-OFFSET]
10. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER.
[RULE 1401]

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 442
 - VOC: RULE 1136, SEE APPENDIX B FOR EMISSIONS LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMIT TO OPERATE

Permit No. F93936
A/N 458643

Equipment Description:

OPEN SPRAY SYSTEM NO. 2, PRIMARY, WITH ONE GRACO BULLDOG PUMP AND TWO GRACO ALPHA PLUS AIRLESS SPRAY GUNS MODEL 243283.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE VOC CONTENT OF MATERIALS USED IN THIS EQUIPMENT SHALL NOT EXCEED 1.25 POUND OF VOC PER GALLON OF COATING, AS APPLIED, LESS WATER AND EXEMPT COMPOUNDS.
[RULE 1303(a) (1)-BACT]
4. THIS EQUIPMENT SHALL ONLY BE USED TO SPRAY THE INTERIOR OF THE MOBILE HOMES.
[RULE 1303(a) (1)-BACT, RULE 1303(b) (2)-OFFSET]
5. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS THE MOBILE HOME SECTION IT IS USED TO COAT IS COMPLETELY COVERED BY PLASTIC ON ITS OPEN SIDE, AND ALL OTHER WINDOW AND DOOR OPENINGS OF THE MOBILE HOME. THE PLASTIC COVERING SHALL BE KEPT IN PLACE FOR AT LEAST TWENTY MINUTES AFTER THE COATING OPERATION IS COMPLETED.
[RULE 1303(a) (1)-BACT, RULE 1303(b) (2)-OFFSET]
6. THE TOTAL QUANTITY OF PARTICULATE MATTER LESS THAN TEN MICRON DIAMETER (PM₁₀) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 9.84 POUNDS IN ANY ONE DAY.
[RULE 1303(b) (1)-MODELING, RULE 1303(b) (2)-OFFSET]
7. THE TOTAL QUANTITY OF PM₁₀ EMISSIONS FROM SPRAY SYSTEM NOS. 1 - 3 UNDER A/Ns 458642, 458643 AND 458644 COMBINED SHALL NOT EXCEED 630 POUNDS IN ANY CALENDAR MONTH.
[RULE 1303(b) (2)-OFFSET]
8. THE PM₁₀ EMISSIONS FROM THIS EQUIPMENT SHALL BE CALCULATED USING THE FORMULA:
$$PM_{10} \text{ LB/DAY} = (\text{QUANTITY OF COATING SPRAYED, IN GALLONS/DAY}) \times (\text{COATING SOLID CONTENT, IN POUNDS PER GALLON}) \times (1-0.45) \times (1-0.95) \times (0.50)$$

[RULE 1303(b) (2)-OFFSET]



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

9. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS, THE DAILY AND CALENDAR MONTHLY PM₁₀ EMISSIONS IN POUNDS, AND THE VOC CONTENT AND SOLIDS CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS).

[RULE 109, RULE 1303(b) (2)-OFFSET]

10. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER.

[RULE 1401]

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109

VOC: RULE 442

VOC: RULE 1136, SEE APPENDIX B FOR EMISSIONS LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

PERMIT TO OPERATE

Permit No. F93937
A/N 458644

Equipment Description:

OPEN SPRAY SYSTEM NO. 3, TOUCH-UP, WITH ONE KREMLIN 1014 PUMP AND TWO GRACO ALPHA PLUS AIRLESS SPRAY GUNS MODEL 243283.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE VOC CONTENT OF MATERIALS USED IN THIS EQUIPMENT SHALL NOT EXCEED 1.25 POUND OF VOC PER GALLON OF COATING, AS APPLIED, LESS WATER AND EXEMPT COMPOUNDS.
[RULE 1303(a) (1)-BACT]
4. THIS EQUIPMENT SHALL ONLY BE USED TO SPRAY THE INTERIOR OF THE MOBILE HOMES.
[RULE 1303(a) (1)-BACT, RULE 1303(b) (2)-OFFSET]
5. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS THE MOBILE HOME SECTION IT IS USED TO COAT IS COMPLETELY COVERED BY PLASTIC ON ITS OPEN SIDE, AND ALL OTHER WINDOW AND DOOR OPENINGS OF THE MOBILE HOME. THE PLASTIC COVERING SHALL BE KEPT IN PLACE FOR AT LEAST TWENTY MINUTES AFTER THE COATING OPERATION IS COMPLETED.
[RULE 1303(a) (1)-BACT, RULE 1303(b) (2)-OFFSET]
6. THE TOTAL QUANTITY OF PARTICULATE MATTER LESS THAN TEN MICRON DIAMETER (PM₁₀) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 9.84 POUNDS IN ANY ONE DAY.
[RULE 1303(b) (1)-MODELING, RULE 1303(b) (2)-OFFSET]
7. THE TOTAL QUANTITY OF PM₁₀ EMISSIONS FROM SPRAY SYSTEM NOS. 1 - 3 UNDER A/Ns 458642, 458643 AND 458644 COMBINED SHALL NOT EXCEED 630 POUNDS IN ANY CALENDAR MONTH.
[RULE 1303(b) (2)-OFFSET]
8. THE PM₁₀ EMISSIONS FROM THIS EQUIPMENT SHALL BE CALCULATED USING THE FORMULA:
$$PM_{10} \text{ LB/DAY} = (\text{QUANTITY OF COATING SPRAYED, IN GALLONS/DAY}) \times (\text{COATING SOLID CONTENT, IN POUNDS PER GALLON}) \times (1-0.45) \times (1-0.95) \times (0.50)$$

[RULE 1303(b) (2)-OFFSET]



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

9. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS, THE DAILY AND CALENDAR MONTHLY PM₁₀ EMISSIONS IN POUNDS, AND THE VOC CONTENT AND SOLIDS CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS).
[RULE 109, RULE 1303(b) (2)-OFFSET]

10. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER.
[RULE 1401]

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 442
VOC: RULE 1136, SEE APPENDIX B FOR EMISSIONS LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSIONS LIMITS



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

[RULE 3004 (a) (4)]

Emissions and Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
REFRIGERANT: RULE 1415



FACILITY PERMIT TO OPERATE HALLMARK SW CORPORATION

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, ADHESIVE APPLICATION EQUIPMENT, LOW USE OR EMISSIONS

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - VOC: RULE 109
 - VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS