



## FACILITY PERMIT TO OPERATE


**TED LEVINE DRUM CO  
1729 - 1927 CHICO AVE  
SOUTH EL MONTE, CA 91733**

### NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.  
EXECUTIVE OFFICER

  
By \_\_\_\_\_

Carol Coy  
Deputy Executive Officer  
Engineering & Compliance

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM CO

### TABLE OF CONTENTS

| Section  | Description   | Revision #      | Date Issued |
|----------|---|-----------------|-------------|
| A        | Facility Information  | 1               | 02/04/2007  |
| B        | RECLAIM Annual Emission Allocation  | 1               | 02/04/2007  |
| C        | Facility Plot Plan  | TO BE DEVELOPED |             |
| D        | Facility Description<br>and Equipment Specific Conditions                         | 5               | 03/04/2008  |
| E        | Administrative Conditions   | 1               | 02/04/2007  |
| F        | RECLAIM Monitoring and<br>Source Testing Requirements                             | 1               | 02/04/2007  |
| G        | Recordkeeping and Reporting Requirements<br>for RECLAIM Sources                   | 1               | 02/04/2007  |
| H        | Permit To Construct<br>and Temporary Permit to Operate                            | 1               | 02/04/2007  |
| I        | Compliance Plans & Schedules  | 1               | 02/04/2007  |
| J        | Air Toxics  | 1               | 02/04/2007  |
| K        | Title V Administration  | 2               | 03/04/2008  |
| Appendix |   |                 |             |
| A        | NOx and SOx Emitting Equipment<br>Exempt From Written Permit Pursuant to Rule 219 | 1               | 02/04/2007  |
| B        | Rule Emission Limits  | 2               | 03/04/2008  |

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

### **Facility Equipment and Requirements (Section D)**

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

| <b>Application number</b> | <b>Permit to Operate number</b> | <b>Equipment description</b>        |
|---------------------------|---------------------------------|-------------------------------------|
| 247334                    | D60465                          | BOILER(5-20 MMBTU/HR) NAT GAS ONLY  |
| 274766                    | D79611                          | SCRUBBER, OTHER VENTING S.S.        |
| 339734                    | F27257                          | BOILER(5-20 MMBTU/HR) NAT GAS ONLY  |
| 346906                    | F45309                          | TANK, SURFACE PREP                  |
| 346907                    | F45310                          | SCRUBBER                            |
| 361709                    | F45311                          | TANK, SURFACE PREP                  |
| 404650                    | F66256                          | SPRAY BOOTH / THERMAL OXIDIZER      |
| 423887                    | F65975                          | SOIL VAPOR EXTRACTION/TREATMENT     |
| 474820                    |                                 | BOILER (5-20 MMBTU/HR) NAT GAS ONLY |

**NOTE:** EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### FACILITY WIDE CONDITION(S)

**Condition(s):**

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
  - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
  - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.  
[RULE 401]
2. MATERIAL SAFETY DATA SHEETS FOR ALL COATINGS AND SOLVENTS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.  
[RULE 109, 1303(b)(2)-OFFSET]
3. ACCIDENTAL RELEASE PREVENTION REQUIREMENTS OF SECTION 112(r)(7):  
THE OPERATOR SHALL COMPLY WITH THE ACCIDENTAL RELEASE PREVENTION REQUIREMENTS PURSUANT TO 40 CFR Part 68 AND SHALL SUBMIT TO THE EXECUTIVE OFFICER, AS PART OF ANNUAL COMPLIANCE CERTIFICATION, A STATEMENT THAT CERTIFIES COMPLIANCE WITH ALL THE REQUIREMENTS OF 40 CFR Part 68, INCLUDING THE REGISTRATION AND SUBMISSION OF A RISK MANAGEMENT PLAN (RMP).  
  
THE OPERATOR SHALL SUBMIT ANY ADDITIONAL RELEVANT INFORMATION REQUESTED BY THE EXECUTIVE OFFICER OR DESIGNATED AGENCY.  
[40 CFR68-ACCIDENTAL RELEASE PREVENTION]
4. TO MAINTAIN EXMPTION FROM THE NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (NESHA) REQUIREMENTS, THE TOTAL QUANTITY OF HAZARDOUS AIR POLLUTANT (HAP) EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 10 TONS (20,000 POUNDS) OF A SINGLE HAP OR 25 TONS (50,000 POUNDS) OF A COMBINATION OF HAPS IN ANY TWELVE CALENDAR MONTH PERIOD.  
[40CFR63 SUBPART MMMM]
5. TO ENSURE COMPLIANCE WITH THE HAP(S) EMISSION CAPS, THE FACILITY OPERATOR SHALL:
  - (A) IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT AND THIS FACILITY TO VERIFY THE MONTHLY HAP EMISSIONS IN POUNDS AND THE HAP CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). THE RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT.
  - (B) WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, TOTAL AND RECORD HAP EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS THAT ARE REQUIRED TO HAVE WRITTEN PERMITS OR ARE EXEMPT FROM WRITTEN PERMITS PURSUANT TO RULE 219. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.

- (C) MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED HAP-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
- (D) RETAIN ALL PURCHASE INVOICES FOR ALL HAP-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE HAP-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.

[40CFR63 SUBPART MMMM]

- 6. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE KEPT IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED AT THE FACILITY FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.

[RULE 109, 1303(b)(2)-OFFSET, 40CFR63 SUBPART MMMM]

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### PERMIT TO OPERATE

**Permit No. D60465**  
**A/N 247334**

#### **Equipment Description:**

BOILER #1, CONTINENTAL, 5.3-MMBTU/HR, NATURAL GAS FIRED, WITH POWER FLAME LOW-NOX BURNER, MODEL NO. LNC3-G-25B.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS BOILER SHALL BE FIRED WITH NATURAL GAS ONLY.  
[RULE 1303(a)(1)-BACT]
4. THE BURNER AND ITS ASSOCIATED AIR FUEL SYSTEM SHOULD BE ADJUSTED AT LEAST TWICE A YEAR IN THE FOLLOWING MANNER:
  - A. ACCORDING TO MANUFACTURER'S SPECIFICATION TO ENSURE COMPLIANCE WITH RULE 1146.
  - B. THE ADJUSTMENTS SHALL INCLUDE AT LEAST MEASUREMENTS OF EFFLUENT CO, NO<sub>2</sub>, AND O<sub>2</sub> CONCENTRATIONS BY USING A PORTABLE CHEMICAL CELL TYPE OR EQUIVALENT INSTRUMENT.
  - C. RECORDS OF SUCH ADJUSTMENTS, TUNE-UP, AND CALIBRATION AS STATED ABOVE SHALL BE KEPT FOR AT LEAST FIVE YEARS AND BE MADE AVAILABLE TO THE DISTRICT PERSONNEL UPON REQUEST  
[RULE 1146, 1303(a)(1)-BACT]
5. THIS EQUIPMENT SHALL BE REMOVED FROM SERVICE WHEN THE EQUIPMENT UNDER APPLICATION NO. 474820 BECOMES FULLY OPERATIONAL.  
[RULE 1303(b)(2)-OFFSET]

#### **Periodic Monitoring:**

6. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE NOX EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

AND AQMD-APPROVED TEST METHOD OR, IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH RULE 1146 CONCENTRATION LIMIT. THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.

[RULE 3004 (a)(4)]

7. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE CO EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER AND AQMD-APPROVED TEST METHOD OR, IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH RULE 1146 CONCENTRATION LIMIT. THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.

[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 400 PPMV, RULE 1146  
CO: 2000 PPMV, RULE 407  
NO<sub>x</sub>: 30 PPMV, RULE 1146  
PM: 0.1 GR/SCF, RULE 409

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### PERMIT TO OPERATE

Permit No. D79611  
A/N 274766

#### Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. SCRUBBER, VIRON, COUNTER CURRENT TYPE, 3'-8" W. X 11'-0" L. X 4'-8" H., WITH MIST ELIMINATOR, AND A 3/4 H.P. RECIRCULATING PUMP.
2. EXHAUST SYSTEM WITH A 5 H.P. BLOWER VENTING TWO FLUSH TANKS.

#### Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS THE FLUSH TANKS ARE VENTED ONLY TO THE AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.  
[RULE 1303(a)(1)-BACT]
4. NOT LESS THAN 0.8 GALLONS PER MINUTE OF MAKE-UP WATER SHALL BE ADDED TO THE SCRUBBER WHEN THE EQUIPMENT IT SERVES IS IN OPERATION.  
[RULE 1303(a)(1)-BACT]
5. NOT LESS THAN 16 GALLONS PER MINUTE OF WATER SHALL BE SUPPLIED TO THE SCRUBBER SPRAY NOZZLES WHEN THE EQUIPMENT IT SERVES IS IN OPERATION.  
[RULE 1303(a)(1)-BACT]
6. A FLOW METER, INDICATING GPM (AND A PRESSURE GAUGE, INDICATING PSI) SHALL BE INSTALLED IN THE WATER SUPPLY LINE TO THE SCRUBBER.  
[RULE 1303(a)(1)-BACT]

#### Periodic Monitoring:

7. THE OPERATOR SHALL INSTALL AND MAINTAIN A FLOW METER TO ACCURATELY INDICATE THE FLOW RATE OF THE SCRUBBING SOLUTION. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY DAY.  
[RULE 3004 (a)(4)]

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

8. THE OPERATOR SHALL INSTALL AND MAINTAIN A pH METER TO ACCURATELY INDICATE THE pH OF THE SCRUBBING SOLUTION. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY DAY.  
[RULE 3004 (a)(4)]

**Emissions And Requirements:**

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULE AND REGULATION:  
  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### PERMIT TO OPERATE

Permit No. F27257  
A/N 339734

#### Equipment Description:

BOILER, HOT WATER AND STEAM, CYCLOTHERM, SERIAL NO. 13950, 6.3-MMBTU/HR NATURAL GAS FIRED, WITH ONE GORDON PIATT LOW-NOX BURNER, MODEL NO. LNS 12.9-6-30-A, AND ONE FLUE GAS RECIRCULATION.

#### Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS BOILER SHALL BE FIRED WITH NATURAL GAS ONLY.  
[RULE 1303(a)(1)-BACT]
4. EMISSIONS FROM THIS BOILER SHALL NOT EXCEED MORE THAN 30 PPM OF OXIDES OF NITROGEN (NOX), CALCULATED AS NO<sub>2</sub>, AND NO MORE THAN 400 PPM OF CARBON MONOXIDE (CO), ALL MEASURED BY VOLUME ON A DRY BASIS AT 3% O<sub>2</sub>.  
[RULE 1146, 1303(a)(1)-BACT]
5. THE BURNER'S AUTOMATIC CONTROL SYSTEM TO REGULATE COMBUSTION AIR, FUEL, AND RECIRCULATED FLUE GAS SHALL BE ADJUSTED AND TUNED AT LEAST TWICE A YEAR ACCORDING TO MANUFACTURER'S SPECIFICATIONS TO ASSURE ITS ABILITY TO REPEAT THE SAME PERFORMANCE AT THE SAME FIRING RANGE.  
[RULE 1146, 1303(a)(1)-BACT]
6. RECORDS OF SUCH ADJUSTMENTS, TUNE-UP, AND CALIBRATION AS STATED ABOVE SHALL BE KEPT FOR AT LEAST FIVE YEARS AND BE MADE AVAILABLE TO THE DISTRICT PERSONNEL UPON REQUEST.  
[RULE 1146, 1303(a)(1)-BACT]
7. A MECHANICAL GAUGE SHALL BE MAINTAINED TO INDICATE THE AMOUNT OF FLUE GAS RECIRCULATED FROM THE EXHAUST GAS STACK TO THE BURNER.  
[RULE 1146, 1303(a)(1)-BACT]
8. THE AMOUNT OF FLUE GAS RECIRCULATED BACK TO THE BURNER SHALL BE AUTOMATICALLY REGULATED IN CONJUNCTION WITH THE COMBUSTION AIR AND FUEL.  
[RULE 1146, 1303(a)(1)-BACT]

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

9. THE FLUE GAS RECIRCULATION SYSTEM SHALL BE IN FULL USE WHENEVER THE BOILER IS IN OPERATION.  
[RULE 1146, 1303(a)(1)-BACT]
10. THE OPERATOR SHALL INSTALL AND MAINTAIN A NON-RESETTABLE TOTALIZING FUEL METER TO ACCURATELY INDICATE THE FUEL USAGE IN THE BOILER.  
[RULE 1303(b)(2)-OFFSET]

### **Periodic Monitoring:**

11. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE NOX EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER AND AQMD-APPROVED TEST METHOD OR, IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH RULE 1146 CONCENTRATION LIMIT. THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.  
[RULE 3004 (a)(4)]
12. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE CO EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER AND AQMD-APPROVED TEST METHOD OR, IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH RULE 1146 CONCENTRATION LIMIT. THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.  
[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:  
  
CO: 400 PPMV, RULE 1146  
CO: 2000 PPMV, RULE 407  
NOx: 30 PPMV, RULE 1146, 1303(a)(1)-BACT  
PM: 0.1 GR/SCF, RULE 409

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### PERMIT TO OPERATE

**Permit No. F45309**  
**A/N 346906**

#### **Equipment Description:**

CLOSED TOP DRUM RECONDITIONING LINE, CONSISTING OF:

1. INTERNAL DRUM FLUSH STATION WITH A SODIUM HYDROXIDE TANK, 3'-0" W. X 25'-0" L. X 3'-0" D., STEAM HEATED, WITH TWELVE ROTATING NOZZLES, VENTED TO THE SCRUBBER.
2. EXTERNAL DRUM STRIPPING STATION WITH A SODIUM HYDROXIDE TANK, 4'-0" W. X 16'-0" L. X 2'-4" D., STEAM HEATED, VENTED TO THE SCRUBBER.
3. SODIUM NITRITE SOLUTION TANK, 4'-0" W. X 14'-6" L. X 2'-4" D., STEAM HEATED.
4. ASSOCIATED RINSE TANKS.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. INTERNAL DRUM FLUSH STATION AND EXTERNAL DRUM STRIPPING STATION SHALL NOT BE OPERATED UNLESS THEY ARE VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID OPERATING PERMIT BY THE EXECUTIVE OFFICER.  
[RULE 1303(a)(1)-BACT]
4. THE MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF SEPTEMBER 8, 1998 OR EARLIER.  
[RULE 1401]
5. VOC CONTAINING MATERIALS SHALL NOT BE USED IN THIS EQUIPMENT.  
[RULE 1303(b)(2)-OFFSET]

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### PERMIT TO OPERATE

Permit No. F45310  
A/N 346907

#### Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. SCRUBBER, VIRON, PACKED BED TYPE, MODEL NO. VBS-60-PVC-7.5-36-S-1-E460-3-60, 5'-0" DIA. X 16'-0" H., WITH A 5 FOOT DEPTH OF JAEGER TRI-PACK PACKING, A MISTELIMINATOR, ONE 2 HP RECIRCULATION PUMP AND A CHEMICAL INJECTION SYSTEM WITH ONE 1/4 HP MIXING MOTOR, ONE 55 GALLON MIXING TANK, AND ONE AUTOMATIC pH SENSOR AND METERING PUMP.
2. EXHAUST SYSTEM WITH A 20 HP BLOWER VENTING AN INTERNAL DRUM FLUSH STATION AND AN EXTERNAL DRUM STRIPPING STATION.

#### Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. A FLOWMETER INDICATING THE FLOW RATE IN GALLONS PER MINUTE (GPM), SHALL BE INSTALLED IN THE RECIRCULATING SOLUTION LINE.  
[RULE 1303(a)(1)-BACT]
4. NOT LESS THAN 78 GPM OF SCRUBBING SOLUTION SHALL BE SUPPLIED TO THE SCRUBBER SPRAY NOZZLES WHEN THE EQUIPMENT IT SERVES IS IN OPERATION.  
[RULE 1303(a)(1)-BACT]
5. A pH TRANSMITTER/ANALYZER, INDICATING pH SHALL BE INSTALLED ON OR NEXT TO THE SCRUBBER RECIRCULATION SUMP.  
[RULE 1303(a)(1)-BACT]
6. THE RECIRCULATING SOLUTION TO THE SCRUBBER SHALL BE MAINTAINED AT A pH OF 7.5 OR LOWER EXCEPT DURING CLEANING AND MAINTENANCE OF EQUIPMENT.  
[RULE 1303(a)(1)-BACT]

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

7. A pH SENSOR SHALL BE INSTALLED IN THE SCRUBBING SOLUTION SUPPLY LINE BETWEEN THE SUMP AND THE SCRUBBING NOZZLES.  
[RULE 1303(a)(1)-BACT]

### **Periodic Monitoring:**

8. THE OPERATOR SHALL INSTALL AND MAINTAIN A FLOW METER TO ACCURATELY INDICATE THE FLOW RATE OF THE SCRUBBING SOLUTION. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY DAY.  
[RULE 3004 (a)(4)]
9. THE OPERATOR SHALL INSTALL AND MAINTAIN A pH METER TO ACCURATELY INDICATE THE pH OF THE SCRUBBING SOLUTION. THE OPERATOR SHALL DETERMINE AND RECORD THE PARAMETER BEING MONITORED ONCE EVERY DAY.  
[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULE AND REGULATION:  
  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### PERMIT TO OPERATE

**Permit No. F45311  
A/N 361709**

#### **Equipment Description:**

FLUSH DRUM CLEANING SYSTEM CONSISTING OF:

TWO FLUSH TANKS, CAUSTIC SOLUTION, EACH 2'-6" W. X 28'-0" L. X 2'-6" D., STEAM HEATED, WITH TWELVE FLASHER NOZZLES AND ONE 15 HP PUMP WITH ALL LINES VENTING TO A VIRON SCRUBBER.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THESE TANKS SHALL NOT BE OPERATED UNLESS THEY ARE VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID OPERATING PERMIT BY THE EXECUTIVE OFFICER.  
[RULE 1303(a)(1)-BACT]
4. THE MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.  
[RULE 1401]
5. VOC CONTAINING MATERIALS SHALL NOT BE USED IN THIS EQUIPMENT.  
[RULE 1303(b)(2)-OFFSET]

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### PERMIT TO OPERATE

**Permit No. F66256  
A/N 404650**

#### **Equipment Description:**

COATING LINE, CONVEYORIZED, CONSISTING OF:

1. SPRAY BOOTH, 8'-0" W. X 7'-0" H. X 10'-0" D., WITH TWENTY 20" X 20" EXHAUST FILTERS, AND A 2 HP EXHAUST FAN.
2. DRYING TUNNEL.
3. AIR POLLUTION CONTROL SYSTEM CONSISTING OF:
  - A. THERMAL OXIDIZER, TELLKAMP SYSTEMS, HOT ROCK DUAL-BED TYPE, MODEL NO. 5, WITH NATURAL GAS INJECTION, ONE 700,000 BTU PER HOUR NATURAL GAS FIRED START-UP BURNER, 2,000,000 BTU PER HOUR MAXIMUM FIRING RATE.
  - B. EXHAUST SYSTEM WITH, ONE 25 H.P. EXHAUST FAN VENTING ONE SPRAY BOOTH, ONE DRYING TUNNEL, AND TWO DRUM/PAIL ACETONE WASHERS.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS EQUIPMENT SHALL BE IN FULL OPERATION WHENEVER ANY OF THE EQUIPMENT SERVED BY THIS APC SYSTEM IS IN OPERATION.  
[RULE 1303(a)(1)-BACT]
4. A TEMPERATURE INDICATOR SHALL BE INSTALLED AND MAINTAINED TO MEASURE THE COMBUSTION CHAMBER TEMPERATURE IN THE THERMAL OXIDIZER.  
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL OPERATE AND MAINTAIN THIS EQUIPMENT ACCORDING TO THE FOLLOWING REQUIREMENTS:

THE COMBUSTION CHAMBER TEMPERATURE SHALL BE MAINTAINED AT A MINIMUM OF 1,500 DEGREES FAHRENHEIT WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

THE OPERATOR SHALL OPERATE AND MAINTAIN A TEMPERATURE MEASURING AND RECORDING SYSTEM TO CONTINUOUSLY MEASURE AND RECORD THE COMBUSTION CHAMBER TEMPERATURE PURSUANT TO THE OPERATION AND MAINTENANCE REQUIREMENTS SPECIFIED IN 40 CFR PART 64.7. SUCH A SYSTEM SHALL HAVE AN ACCURACY OF WITHIN 1% OF THE TEMPERATURE BEING MONITORED AND SHALL BE INSPECTED, MAINTAINED, AND CALIBRATED ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

FOR THE PURPOSE OF THIS CONDITION, A DEVIATION SHALL BE DEFINED AS WHEN A COMBUSTION CHAMBER TEMPERATURE OF LESS THAN 1,500 DEGREES FAHRENHEIT OCCURS DURING NORMAL OPERATION OF THE EQUIPMENT IT SERVES. THE OPERATOR SHALL REVIEW THE RECORDS OF THE COMBUSTION CHAMBER TEMPERATURE ON A DAILY BASIS TO DETERMINE IF A DEVIATION OCCURS OR SHALL INSTALL AN ALARM SYSTEM TO ALERT THE OPERATOR WHEN A DEVIATION OCCURS.

WHENEVER A DEVIATION OCCURS, THE OPERATOR SHALL INSPECT THIS EQUIPMENT TO IDENTIFY THE CAUSE OF SUCH A DEVIATION, TAKE IMMEDIATE CORRECTIVE ACTION TO MAINTAIN THE COMBUSTION CHAMBER TEMPERATURE AT OR ABOVE 1,500 DEGREES FAHRENHEIT, AND KEEP RECORDS OF THE DURATION AND CAUSE (INCLUDING UNKNOWN CAUSE, IF APPLICABLE) OF THE DEVIATION AND THE CORRECTIVE ACTION TAKEN.

ALL DEVIATIONS SHALL BE REPORTED TO THE AQMD PURSUANT TO THE REQUIREMENTS SPECIFIED IN 40 CFR PART 64.9 AND CONDITION NOS. 22 AND 23 IN SECTION K OF THIS PERMIT. THE REPORT SHALL INCLUDE THE TOTAL OPERATING TIME OF THIS EQUIPMENT AND THE TOTAL ACCUMULATED DURATION OF ALL DEVIATIONS FOR EACH SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL SUBMIT AN APPLICATION WITH A QUALITY IMPROVEMENT PLAN (QIP) IN ACCORDANCE WITH 40 CFR PART 64.8 TO THE AQMD IF AN ACCUMULATION OF DEVIATIONS EXCEEDS 5 PERCENT DURATION OF THIS EQUIPMENT'S TOTAL OPERATING TIME FOR ANY SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT. THE REQUIRED QIP SHALL BE SUBMITTED TO THE AQMD WITHIN 90 CALENDAR DAYS AFTER THE DUE DATE FOR THE SEMI-ANNUAL MONITORING REPORT.

THE OPERATOR SHALL INSPECT AND MAINTAIN ALL COMPONENTS OF THIS EQUIPMENT ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

THE OPERATOR SHALL KEEP ADEQUATE RECORDS IN A FORMAT THAT IS ACCEPTABLE TO THE AQMD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE REQUIREMENTS SPECIFIED IN THIS CONDITION AND 40 CFR PART 64.9 FOR A MINIMUM OF FIVE YEARS.

[RULE 1303(a)(1)-BACT, 3004(a)(4)-PERIODIC MONITORING, 40CFR PART 64]

6. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE SPRAY BOOTH EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.  
[RULE 1303(a)(1)-BACT]

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

7. THIS EQUIPMENT SHALL OPERATE WITH A MINIMUM OVERALL CONTROL OF 95 % AND A MINIMUM DESTRUCTION EFFICIENCY OF 95 %.  
[RULE 1303(a)(1)-BACT]
8. THE SPRAY BOOTH AND THE DRYING TUNNEL SHALL BE MAINTAINED AS PERMANENT TOTAL ENCLOSURES AS PER THE REQUIREMENTS OF EPA METHOD 204.  
[RULE 1303(a)(1)-BACT]
9. THE TOTAL QUANTITY OF VOC EMITTED TO THE ATMOSPHERE FROM THIS EQUIPMENT SHALL NOT EXCEED 1320 LBS. IN ANY ONE MONTH. AN OVERALL CONTROL EFFICIENCY OF 95 % SHALL BE USED TO DETERMINE COMPLIANCE WITH THIS CONDITION.  
[RULE 1303(b)(2)-OFFSET]
10. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE 1, WITH AN EFFECTIVE DATE OF MAY 3, 2002 OR EARLIER, EXCEPT FOR ETHYLENE GLYCOL MONOBUTYL ETHER (EGBE).  
[RULE 1401]
11. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITIONS 5, 7, 8, 9 AND 10. THESE RECORDS SHALL BE RETAINED ON FILE FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.  
[RULE 1303(b)(2)-OFFSET]
12. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, THE OPERATOR SHALL TOTAL AND RECORD VOC EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS COVERED BY THE MONTHLY LIMIT. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.  
[RULE 1303(b)(2)-OFFSET]
13. THE OPERATOR SHALL MAINTAIN A SINGLE LIST, WHICH INCLUDES ONLY THE NAME, AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.  
[RULE 1303(b)(2)-OFFSET]
14. THE OPERATOR SHALL RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL VOC-CONTAINING WASTE MATERIAL REMOVED FROM THE FACILITY, FOR 60 MONTHS.  
[RULE 1303(b)(2)-OFFSET]
15. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE RETAINED AT THE FACILITY FOR 60 MONTHS, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.  
[RULE 1303(b)(2)-OFFSET]

### **Periodic Monitoring:**

16. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

MEDIA ONCE EVERY WEEK.  
[RULE 3004 (a)(4)]

17. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
  - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
  - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004 (a)(4)]

18. THE OPERATOR SHALL CONDUCT SOURCE TEST(S) IN ACCORDANCE WITH THE FOLLOWING SPECIFICATIONS:
- A. THE TEST SHALL BE CONDUCTED AT LEAST ONCE DURING THE LIFE OF THE PERMIT.
  - B. THE TEST SHALL BE CONDUCTED NO LATER THAN FEBRUARY 4, 2011 UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
  - C. THE TEST SHALL BE CONDUCTED TO DETERMINE THE VOC EMISSIONS USING AN APPROVED DISTRICT METHOD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE PERMIT CONDITION(S), RULES AND REGULATIONS.
  - D. THE SOURCE TEST SHALL BE CONDUCTED WHILE THE OXIDIZER IS OPERATING AT A TEMPERATURE OF NOT LESS THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT. IF THE OPERATING TEMPERATURE DURING THE SOURCE TEST IS GREATER THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT, THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT MAY BE INCREASED TO REFLECT THE OPERATING TEMPERATURE DURING THE SOURCE TEST.
  - E. THE OPERATOR SHALL COMPLY WITH ADMINISTRATIVE CONDITIONS NOs. 8, 9, AND 10 OF SECTION E OF THIS FACILITY PERMIT.
  - F. THE OPERATOR SHALL SUBMIT TWO COMPLETE COPIES OF THE SOURCE TEST REPORT SPECIFIED IN CONDITION NO. 9 OF SECTION E OF THIS FACILITY PERMIT TO THE DISTRICT ENGINEERING AND COMPLIANCE DIVISION. THE ENGINEERING COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, COATING, PRINTING AND AEROSPACE OPERATIONS, ATTN: AIR QAULITY AND COMPLIANCE SUPERVISOR, 21865 COPLEY DRIVE, DIAMOND BAR, CA 91765. THE COMPLIANCE COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, P.O. BOX 4941, DIAMOND BAR, CA 91765

[RULE 3004(a)(4)]

### **Emissions And Requirements:**

19. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109

VOC: RULE 1125, SEE APPENDIX B FOR EMISSION LIMITS

**FACILITY PERMIT TO OPERATE  
TED LEVINE DRUM COMPANY**

VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS  
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS  
PM: RULE 481

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

### **PERMIT TO OPERATE**

**Permit No. F65975  
A/N 423887**

#### **Equipment Description:**

UNDERGROUND VAPOR EXTRACTION AND TREATMENT SYSTEM CONSISTING OF

1. VAPOR EXTRACTION WELLS AND DUCTS.
2. WATER KNOCKOUT POT.
3. AIR EXTRACTION BLOWER, MAXIMUM TOTAL FLOW RATE 665 SCFM.
4. ONE PRIMARY CARBON ADSORBER, WESTSTATES, MODEL VSC-2000, CONTAINING 1,800 POUNDS OF ACTIVATED CARBON IN SERIES WITH UP TO FIVE SECONDARY ADSORBERS IN PARALLEL, EACH CONTAINING 185 POUNDS OF ACTIVATED CARBON.

OR

ONE PRIMARY CARBON ADSORBER, WESTSTATES, MODEL VSC-3000, CONTAINING 3,000 POUNDS OF ACTIVATED CARBON IN SERIES WITH UP TO EIGHT SECONDARY ADSORBERS IN PARALLEL, EACH CONTAINING 185 POUNDS OF ACTIVATED CARBON.

#### **Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. UPON COMPLETION, ANY VAPOR EXTRACTION WELL AND/OR DUCT NOT VENTED TO THE VAPOR CONTROL SYSTEM, SHALL BE CAPPED TO PREVENT VAPORS FROM VENTING TO THE ATMOSPHERE. VAPORS SHALL NOT BE EXTRACTED FROM THE SOIL UNLESS THEY ARE VENTED TO THE VAPOR CONTROL SYSTEM, WITH NO DETECTABLE LEAK BETWEEN THE OUTLET OF THE BLOWER AND THE OUTLET OF THE VAPOR CONTROL SYSTEM.  
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
4. THE VOC CONCENTRATION MEASURED AT THE OUTLET OF THE PRIMARY ADSORBER SHALL NOT EXCEED 8 PPMV.  
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
5. THE PRIMARY ADSORBER ADSORBENT SHALL BE REPLACED WITH FRESH ADSORBENT WHENEVER THE VOC CONCENTRATION AT THE OUTLET OF THE PRIMARY ADSORBER EXCEEDS THE LEVEL DESCRIBED IN CONDITION NO. 4, OR BOTH THE PRIMARY AND

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

SECONDARY ADSORBERS ADSORBENT SHALL BE REPLACED WITH FRESH ADSORBENT WHENEVER THE VOC CONCENTRATION AT THE OUTLET OF THE SECONDARY ADSORBER EXCEEDS THE LEVEL DESCRIBED IN CONDITION NO 4.

[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]

6. SPENT CARBON REMOVED FROM THE SYSTEM SHALL BE STORED IN CLOSED CONTAINERS PRIOR TO DISPOSAL.  
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
7. AN IDENTIFICATION TAG OR NAME PLATE(S) SHALL BE DISPLAYED ON THE EQUIPMENT TO SHOW MANUFACTURER MODEL NO AND SERIAL NO THE TAG(S) OR PLATE(S) SHALL BE ISSUED BY THE MANUFACTURER AND SHALL BE AFFIXED TO THE EQUIPMENT IN A PERMANENT AND CONSPICUOUS POSITION.  
[RULE 1303(a)(1)-BACT]
8. THE CURRENT CONTACT PERSON'S NAME, COMPANY AND PHONE NUMBER SHALL BE DISPLAYED IN A PERMANENT AND CONSPICUOUS POSITION.  
[RULE 204]
9. A FLOW INDICATOR SHALL BE INSTALLED AND MAINTAINED AT ALL INLET STREAM(S) TO THE VAPOR CONTROL SYSTEM TO INDICATE THE TOTAL AIR FLOW RATE IN CUBIC FEET PER MINUTE (CFM). THE TOTAL FLOW RATE SHALL NOT EXCEED 665 SCFM. IN CASE A PRESSURE SENSOR DEVICE IS USED INSTEAD OF THE FLOW INDICATOR, A CONVERSION CHART SHALL BE POSTED TO INDICATE THE FLOW RATE, IN CFM, CORRESPONDING TO THE PRESSURE READING.  
[RULE 1303(a)(1)-BACT]
10. THE VOLATILE ORGANIC COMPOUND (VOC) CONCENTRATION SHALL BE MONITORED BY USING A FLAME IONIZATION DETECTOR OR A DISTRICT APPROVED ORGANIC VAPOR ANALYZER CALIBRATED IN PARTS PER MILLION BY VOLUME (PPMV) OF HEXANE. THE VOC CONCENTRATION SHALL BE MEASURED AT THE OUTLET OF THE PRIMARY AND SECONDARY ADSORBERS AT LEAST ONCE EVERY OPERATING DAY FOR THE FIRST TWO WEEKS AND WEEKLY THEREAFTER.  
[RULE 1303(a)(1)-BACT]
11. RECORDS SHALL BE MAINTAINED TO PROVE COMPLIANCE WITH CONDITION NUMBERS 5, 9 AND 10. THE RECORDS SHALL BE KEPT ON SITE FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO THE DISTRICT UPON REQUEST.  
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]

### **Emissions And Requirements:**

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1166

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### PERMIT TO CONSTRUCT

**A/N 474820**  
**Granted as of**  
**March 4, 2008**

**Equipment Description:**

BOILER, PARKER, MODEL NO. 150LR, WATER-TUBE, WITH EIGHTEEN PARKER LOW NOX BURNERS, NATURAL GAS FIRED, 6,250,000 BTU PER HOUR.

**Conditions:**

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.  
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.  
[RULE 204]
3. THIS EQUIPMENT SHALL BE FIRED ON NATURAL GAS ONLY.  
[RULE 1303(a)(1)-BACT]
4. THIS EQUIPMENT SHALL NOT DISCHARGE MORE THAN 12 PPM OF OXIDES OF NITROGEN (NOX) CALCULATED AS NO<sub>2</sub> AND 100 PPM OF CARBON MONOXIDE (CO), ALL CALCULATED BY VOLUME ON A DRY BASIS @ 3% OXYGEN.  
[RULE 1303(a)(1)-BACT]
5. THE COMBUSTION BURNERS SHALL BE INSPECTED AND MAINTAINED PER MANUFACTURER'S SPECIFICATIONS. INSPECTION AND MAINTENANCE RECORDS SHALL BE RETAINED AT THE FACILITY FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.  
[RULE 1146, 1303(a)(1)-BACT]
6. THE OWNER OR OPERATOR OF THIS EQUIPMENT SHALL CONDUCT SOURCE TESTS UNDER THE FOLLOWING CONDITIONS:
  - A. THE SOURCE TESTS SHALL BE CONDUCTED NO LATER THAN 180 DAYS AFTER THE INITIAL START-UP OF THIS EQUIPMENT UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
  - B. A SOURCE TEST PROTOCOL SHALL BE SUBMITTED TO THE DISTRICT NO LATER THAN 60 DAYS AFTER THE INITIAL START-UP OF THIS EQUIPMENT UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT. THE TEST PROTOCOL SHALL BE APPROVED IN WRITING BY THE DISTRICT BEFORE THE TEST COMMENCES. THE TEST PROTOCOL SHALL INCLUDE THE COMPLETED DISTRICT FORMS ST-1 AND ST-2 SPECIFYING THE PROPOSED OPERATING CONDITIONS OF THE EQUIPMENT DURING THE TEST, THE

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

IDENTITY OF THE TESTING LABORATORY, A STATEMENT FROM THE TESTING LABORATORY CERTIFYING IT MEETS THE CRITERIA IN DISTRICT RULE 304(K), AND A DESCRIPTION OF THE SAMPLING AND ANALYTICAL PROCEDURES TO BE USED.

- C. THE SOURCE TEST SHALL BE PERFORMED TO VERIFY COMPLIANCE WITH THE NOX AND CO EMISSION LIMIT SPECIFIED BY THIS PERMIT.
- D. THE TEST SHALL BE CONDUCTED IN ACCORDANCE WITH SCAQMD METHOD 100.1.
- E. THE TEST SHALL BE PERFORMED WHEN THE BOILER IS OPERATING AT MAXIMUM, AVERAGE, AND MINIMUM FIRING RATES AND ALSO WHILE OPERATING UNDER NORMAL CONDITIONS. THE SAMPLING DURATION SHALL BE AT LEAST 15 CONSECUTIVE MINUTES FOR MAXIMUM, AVERAGE, MINIMUM, AND NORMAL LOADS.
- F. WRITTEN NOTICE OF THE SOURCE TESTS SHALL BE SUBMITTED TO THE DISTRICT AT LEAST 14 DAYS PRIOR TO SOURCE TESTING DATE SO THAT AN OBSERVER FROM THE DISTRICT MAY BE PRESENT.
- G. TWO COMPLETE COPIES OF THE SOURCE TEST REPORTS SHALL BE SUBMITTED TO THE DISTRICT WITHIN 45 DAYS AFTER THE SOURCE TESTING DATE. THE SOURCE TEST REPORT SHALL INCLUDE, BUT NOT BE LIMITED TO EMISSION RATES IN POUNDS PER HOUR AND CONCENTRATIONS IN PPMV AT THE OUTLET OF THE BOILER, MEASURED ON A DRY BASIS AT 3% OXYGEN. THE FOLLOWING OPERATING DATA SHALL ALSO BE INCLUDED FOR EACH FIRING RATE:
  - I. THE EXHAUST FLOW RATES, IN ACTUAL CUBIC FEET PER MINUTE (ACFM).
  - II. THE FIRING RATES IN BTU PER HOUR.
  - III. THE EXHAUST TEMPERATURE, IN DEGREES F.
  - IV. THE OXYGEN CONTENT OF THE EXHAUST GASES, IN PERCENT.
  - V. THE FUEL FLOW RATE.
- H. A TESTING LABORATORY CERTIFIED BY THE CALIFORNIA AIR RESOURCES BOARD IN THE REQUIRED TEST METHODS FOR CRITERIA POLLUTANTS TO BE MEASURED, AND IN COMPLIANCE WITH DISTRICT RULE 304 (NO CONFLICT OF INTEREST) SHALL CONDUCT THE TEST.
- I. SAMPLING FACILITIES SHALL COMPLY WITH THE DISTRICT GUIDELINES FOR CONSTRUCTION OF SAMPLING AND TESTING FACILITIES, PURSUANT TO RULE 217.

[RULE 1146, 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]

### **Periodic Monitoring:**

- 7. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE NOX EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER AND AQMD-APPROVED TEST METHOD OR, IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH THE NO<sub>x</sub> CONCENTRATION LIMIT(S). THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.

[RULE 3004 (a)(4)]

8. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE CO EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER AND AQMD-APPROVED TEST METHOD OR, IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH THE CO CONCENTRATION LIMIT(S). THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.

[RULE 3004 (a)(4)]

### **Emissions And Requirements:**

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 400 PPMV, RULE 1146  
CO: 2000 PPMV, RULE 407  
CO: 100 PPMV, RULE 1303(a)(1)-BACT  
NO<sub>x</sub>: 30 PPMV, RULE 1146  
NO<sub>x</sub>: 12 PPMV, RULE 1303(a)(1)-BACT  
PM: 0.1 GR/SCF, RULE 409

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY

### RULE 219 EQUIPMENT

#### Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

#### Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATING AND (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATINGS.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS AND (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATINGS.

[RULE 3004 (a) (4)]

#### Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

### **RULE 219 EQUIPMENT**

**Equipment Description:**

RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL UNHEATED, NON-CONVEYORIZED

**Emissions And Requirements:**

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM COMPANY**

### **RULE 219 EQUIPMENT**

**Equipment Description:**

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

**Emissions And Requirements:**

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

## **FACILITY PERMIT TO OPERATE TED LEVINE DRUM CO**

### SECTION K: TITLE V Administration

#### **GENERAL PROVISIONS**

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

#### **Permit Renewal and Expiration**

3. (A) Except for solid waste incineration facilities subject to standards under Section 129(e) of the Clean Air Act, this permit shall expire five years from the date that the initial Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]  
  
(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

#### **Duty to Provide Information**

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

#### **Payment of Fees**

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

#### **Reopening for Cause**

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
  - (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM CO

### SECTION K: TITLE V Administration

- (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
- (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

### COMPLIANCE PROVISIONS

- 8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
  - (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
  - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

- 9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
  - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
  - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
  - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
  - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]
- 10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM CO

### SECTION K: TITLE V Administration

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]
12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]
13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]
14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
  - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
  - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
  - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
  - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
  - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
  - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after

**FACILITY PERMIT TO OPERATE  
TED LEVINE DRUM CO**

SECTION K: TITLE V Administration

commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM CO

### SECTION K: TITLE V Administration

#### **EMERGENCY PROVISIONS**

17. An emergency<sup>1</sup> constitutes an affirmative defense to an action brought for non-compliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
    - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
    - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
    - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
    - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
  - (B) The operator complies with the breakdown provisions of Rule 430 - Breakdown Provisions, or subdivision (i) of Rule 2004 - Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

---

<sup>1</sup> "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM CO

### SECTION K: TITLE V Administration

#### RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
  - (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
  - (B) The date(s) analyses were performed;
  - (C) The company or entity that performed the analyses;
  - (D) The analytical techniques or methods used;
  - (E) The results of such analyses; and
  - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

#### REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
  - (A) Breakdowns shall be reported as required by Rule 430 - Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.
  - (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM CO

### SECTION K: TITLE V Administration

- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;
- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.
- The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]
25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

**FACILITY PERMIT TO OPERATE  
TED LEVINE DRUM CO**

SECTION K: TITLE V Administration

**PERIODIC MONITORING**

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the Title V application file. [3004(a)(4)]

## FACILITY PERMIT TO OPERATE TED LEVINE DRUM CO

### SECTION K: TITLE V Administration

*FACILITY RULES*

*This facility is subject to the following rules and regulations:*

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

| <b>RULE SOURCE</b>                  | <b>Adopted/Amended Date</b> | <b>FEDERAL Enforceability</b> |
|-------------------------------------|-----------------------------|-------------------------------|
| RULE 109                            | 5-2-2003                    | Federally enforceable         |
| RULE 1113                           | 11-8-1996                   | Federally enforceable         |
| RULE 1113                           | 7-13-2007                   | Non federally enforceable     |
| RULE 1125                           | 1-13-1995                   | Federally enforceable         |
| RULE 1145                           | 12-3-2004                   | Non federally enforceable     |
| RULE 1145                           | 2-14-1997                   | Federally enforceable         |
| RULE 1146                           | 11-17-2000                  | Federally enforceable         |
| RULE 1166                           | 5-11-2001                   | Non federally enforceable     |
| RULE 1166                           | 7-14-1995                   | Federally enforceable         |
| RULE 1171                           | 11-7-2003                   | Federally enforceable         |
| RULE 1171                           | 7-14-2006                   | Non federally enforceable     |
| RULE 118                            | 12-7-1995                   | Non federally enforceable     |
| RULE 1303(a)(1)-BACT                | 12-6-2002                   | Non federally enforceable     |
| RULE 1303(a)(1)-BACT                | 5-10-1996                   | Federally enforceable         |
| RULE 1303(b)(2)-O set               | 12-6-2002                   | Non federally enforceable     |
| RULE 1303(b)(2)-O set               | 5-10-1996                   | Federally enforceable         |
| RULE 1401                           | 1-8-1999                    | Non federally enforceable     |
| RULE 1401                           | 12-7-1990                   | Non federally enforceable     |
| RULE 1401                           | 5-3-2002                    | Non federally enforceable     |
| RULE 204                            | 10-8-1993                   | Federally enforceable         |
| RULE 217                            | 1-5-1990                    | Federally enforceable         |
| RULE 219                            | 6-1-2007                    | Non federally enforceable     |
| RULE 219                            | 9-4-1981                    | Federally enforceable         |
| RULE 3002                           | 11-14-1997                  | Federally enforceable         |
| RULE 3003                           | 11-14-1997                  | Federally enforceable         |
| RULE 3003                           | 3-16-2001                   | Non federally enforceable     |
| RULE 3004                           | 12-12-1997                  | Federally enforceable         |
| RULE 3004(a)(4)-Periodic Monitoring | 12-12-1997                  | Federally enforceable         |
| RULE 3005                           | 11-14-1997                  | Federally enforceable         |

**FACILITY PERMIT TO OPERATE  
 TED LEVINE DRUM CO**

SECTION K: TITLE V Administration

| <b>RULE SOURCE</b>                       | <b>Adopted/Amended Date</b> | <b>FEDERAL Enforceability</b> |
|--|-----------------------------|-------------------------------|
| RULE 3005                                | 3-16-2001                   | Non federally enforceable     |
| RULE 3007                                | 10-8-1993                   | Federally enforceable         |
| RULE 304                                 | 6-9-2006                    | Non federally enforceable     |
| RULE 401                                 | 11-9-2001                   | Non federally enforceable     |
| RULE 401                                 | 3-2-1984                    | Federally enforceable         |
| RULE 402                                 | 5-7-1976                    | Non federally enforceable     |
| RULE 404                                 | 2-7-1986                    | Federally enforceable         |
| RULE 407                                 | 4-2-1982                    | Federally enforceable         |
| RULE 408                                 | 5-7-1976                    | Federally enforceable         |
| RULE 409                                 | 8-7-1981                    | Federally enforceable         |
| RULE 430                                 | 7-12-1996                   | Non federally enforceable     |
| RULE 442                                 | 12-15-2000                  | Federally enforceable         |
| RULE 481                                 | 1-11-2002                   | Federally enforceable         |
| 40CFR 63 Subpart MMMM                    | 4-20-2006                   | Federally enforceable         |
| 40CFR 68 - Accidental Release Prevention | 5-24-1996                   | Federally enforceable         |
| RULE 701                                 | 6-13-1997                   | Federally enforceable         |
| 40CFR Part 64                            | 10-22-1997                  | Federally enforceable         |

## FACILITY PERMIT TO OPERATE

### TED LEVINE DRUM CO

#### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

#### TABLE OF STANDARDS

#### VOC LIMITS

#### Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

| COATING                            | Limit* | Effective<br>Date of<br>Adoption | Effective<br>1/1/1998 | Effective<br>1/1/1999 | Effective<br>7/1/2001 | Effective<br>1/1/2005 | Effective<br>7/1/2008 |
|------------------------------------|--------|----------------------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Bond Breakers                      | 350    |                                  |                       |                       |                       |                       |                       |
| Clear Wood Finishes                |        |                                  |                       |                       |                       |                       |                       |
| Varnish                            | 350    |                                  |                       |                       |                       |                       |                       |
| Sanding Sealers                    | 350    |                                  |                       |                       |                       |                       |                       |
| Lacquer                            | 680    |                                  | 550                   |                       |                       | 275                   |                       |
| Concrete-Curing Compounds          | 350    |                                  |                       |                       |                       |                       |                       |
| Dry-Fog Coatings                   | 400    |                                  |                       |                       |                       |                       |                       |
| Fire-proofing Exterior<br>Coatings | 350    | 450                              |                       | 350                   |                       |                       |                       |
| Fire-Retardant Coatings            |        |                                  |                       |                       |                       |                       |                       |
| Clear                              | 650    |                                  |                       |                       |                       |                       |                       |
| Pigmented                          | 350    |                                  |                       |                       |                       |                       |                       |
| Flats                              | 250    |                                  |                       |                       |                       |                       |                       |
| Graphic Arts (Sign) Coatings       | 500    |                                  |                       |                       |                       | 100                   | 50                    |
| Industrial Maintenance             |        |                                  |                       |                       |                       |                       |                       |

## FACILITY PERMIT TO OPERATE

### TED LEVINE DRUM CO

#### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

|                             |     |     |     |     |  |     |  |
|-----------------------------|-----|-----|-----|-----|--|-----|--|
| Primers and Topcoats        |     |     |     |     |  |     |  |
| Alkyds                      | 420 |     |     |     |  |     |  |
| Catalyzed Epoxy             | 420 |     |     |     |  |     |  |
| Bituminous Coatings         | 420 |     |     |     |  |     |  |
| Materials                   |     |     |     |     |  |     |  |
| Inorganic Polymers          | 420 |     |     |     |  |     |  |
| Vinyl Chloride Polymers     | 420 |     |     |     |  |     |  |
| Chlorinated Rubber          | 420 |     |     |     |  |     |  |
| Acrylic Polymers            | 420 |     |     |     |  |     |  |
| Urethane Polymers           | 420 |     |     |     |  |     |  |
| Silicones                   | 420 |     |     |     |  |     |  |
| Unique Vehicles             | 420 |     |     |     |  |     |  |
| Japans/Faux Finishing       | 350 | 700 |     | 350 |  |     |  |
| Coatings                    |     |     |     |     |  |     |  |
| Magnesite Cement Coatings   | 600 |     |     | 450 |  |     |  |
| Mastic Coatings             | 300 |     |     |     |  |     |  |
| Metallic Pigmented Coatings | 500 |     |     |     |  |     |  |
| Multi-Color Coatings        | 420 |     | 250 |     |  |     |  |
| Pigmented Lacquer           | 680 |     | 550 |     |  | 275 |  |
| Pre-Treatment Wash Primers  | 780 |     |     |     |  |     |  |
| Primers, Sealers, and       | 350 |     |     |     |  |     |  |
| Undercoaters                |     |     |     |     |  |     |  |
| Quick-Dry Enamels           | 400 |     |     |     |  |     |  |
| Roof Coatings               | 300 |     |     |     |  |     |  |
| Shellac                     |     |     |     |     |  |     |  |
| Clear                       | 730 |     |     |     |  |     |  |
| Pigmented                   | 550 |     |     |     |  |     |  |
| Stains                      | 350 |     |     |     |  |     |  |
| Swimming Pool Coatings      |     |     |     |     |  |     |  |
| Repair                      | 650 |     |     |     |  |     |  |
| Other                       | 340 |     |     |     |  |     |  |
| Traffic Coatings            | 250 |     | 150 |     |  |     |  |
| Waterproofing Sealers       | 400 |     |     |     |  |     |  |
| Wood Preservatives          |     |     |     |     |  |     |  |
| Below-Ground                | 350 |     |     |     |  |     |  |
| Other                       | 350 |     |     |     |  |     |  |

\* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

**FACILITY PERMIT TO OPERATE  
TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS  
[RULE 1113 11-8-1996]**

**TABLE OF STANDARDS (cont.)**

**VOC LIMITS**

**Grams of VOC Per Liter of Material**

| COATING            | Limit |
|--------------------|-------|
| Low-Solids Coating | 120   |

## **FACILITY PERMIT TO OPERATE**

### **TED LEVINE DRUM CO**

#### **APPENDIX B: RULE EMISSION LIMITS [RULE 1113 7-13-2007]**

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1113 7-13-2007]**

**TABLE OF STANDARDS**  
**VOC LIMITS**

**Grams of VOC Per Liter of Coating,**  
**Less Water and Less Exempt Compounds**

| COATING CATEGORY                                     | Ceiling Limit* | Current Limit | Effective Date |        |        |        |        |        |
|--|----------------|---------------|----------------|--------|--------|--------|--------|--------|
|  |                |               | 1/1/03         | 1/1/04 | 1/1/05 | 7/1/06 | 7/1/07 | 7/1/08 |
| Bond Breakers  | 350            |               |                |        |        |        |        |        |
| Clear Wood Finishes                                  | 350            |               |                |        |        | 275    |        |        |
| Varnish  | 350            |               |                |        |        | 275    |        |        |
| Sanding Sealers                                      | 350            |               |                |        |        | 275    |        |        |
| Lacquer  | 680            | 550           |                |        | 275    |        |        |        |
| Clear Brushing Lacquer                               | 680            |               |                |        | 275    |        |        |        |
| Concrete-Curing Compounds                            | 350            |               |                |        |        |        | 100    |        |
| Concrete-Curing Compounds For Roadways and Bridges** | 350            |               |                |        |        |        |        |        |
| Dry-Fog Coatings                                     | 400            |               |                |        |        |        | 150    |        |
| Fire-Proofing Exterior Coatings                      | 450            | 350           |                |        |        |        |        |        |
| Fire-Retardant Coatings***                           |                |               |                |        |        |        |        |        |
| Clear  | 650            |               |                |        |        |        |        |        |
| Pigmented  | 350            |               |                |        |        |        |        |        |
| Flats  | 250            | 100           |                |        |        |        |        | 50     |
| Floor Coatings                                       | 420            |               | 100            |        |        | 50     |        |        |
| Graphic Arts (Sign) Coatings                         | 500            |               |                |        |        |        |        |        |
| Industrial Maintenance (IM) Coatings                 | 420            |               |                | 250    |        | 100    |        |        |
| High Temperature IM Coatings                         |                |               | 420            |        |        |        |        |        |
| Zinc-Rich IM Primers                                 | 420            |               | 340            |        |        | 100    |        |        |
| Japans/Faux Finishing Coatings                       | 700            | 350           |                |        |        |        |        |        |
| Magnesite Cement Coatings                            | 600            | 450           |                |        |        |        |        |        |
| Mastic Coatings                                      | 300            |               |                |        |        |        |        |        |
| Metallic Pigmented Coatings                          | 500            |               |                |        |        |        |        |        |
| Multi-Color Coatings                                 | 420            | 250           |                |        |        |        |        |        |
| Nonflat Coatings                                     | 250            |               | 150            |        |        | 50     |        |        |
| Nonflat High Gloss                                   | 250            |               | 150            |        |        |        | 50     |        |

## FACILITY PERMIT TO OPERATE

### TED LEVINE DRUM CO

### APPENDIX B: RULE EMISSION LIMITS [RULE 1113 7-13-2007]

| COATING CATEGORY                             | Ceiling Limit* | Current Limit | Effective Date |        |        |        |        |        |
|--|----------------|---------------|----------------|--------|--------|--------|--------|--------|
|  |                |               | 1/1/03         | 1/1/04 | 1/1/05 | 7/1/06 | 7/1/07 | 7/1/08 |
| Pigmented Lacquer                            | 680            | 550           |                |        | 275    |        |        |        |
| Pre-Treatment Wash Primers                   | 780            |               | 420            |        |        |        |        |        |
| Primers, Sealers, and Undercoaters           | 350            |               | 200            |        |        | 100    |        |        |
| Quick-Dry Enamels                            | 400            |               | 250            |        |        | 150    | 50     |        |
| Quick-Dry Primers, Sealers, and Undercoaters | 350            |               | 200            |        |        | 100    |        |        |
| Recycled Coatings                            |                |               | 250            |        |        |        |        |        |
| Roof Coatings                                | 300            |               | 250            |        | 50     |        |        |        |
| Roof Coatings, Aluminum                      | 500            |               |                |        | 100    |        |        |        |
| Roof Primers, Bituminous                     | 350            |               | 350            |        |        |        |        |        |
| Rust Preventative Coatings                   | 420            |               | 400            |        |        | 100    |        |        |
| Shellac                                      |                |               |                |        |        |        |        |        |
| Clear  | 730            |               |                |        |        |        |        |        |
| Pigmented                                    | 550            |               |                |        |        |        |        |        |
| Specialty Primers                            | 350            |               |                |        |        | 250    | 100    |        |
| Stains                                       | 350            |               | 250            |        |        |        | 100    |        |
| Stains, Interior                             | 250            |               |                |        |        |        |        |        |
| Swimming Pool Coatings                       |                |               |                |        |        |        |        |        |
| Repair                                       | 650            |               | 340            |        |        |        |        |        |
| Other  | 340            |               |                |        |        |        |        |        |
| Traffic Coatings                             | 250            | 150           |                |        |        |        | 100    |        |
| Waterproofing Sealers                        | 400            |               | 250            |        |        | 100    |        |        |
| Waterproofing                                | 400            |               |                |        |        | 100    |        |        |
| Concrete/Masonry Sealers                     |                |               |                |        |        |        |        |        |
| Wood Preservatives                           |                |               |                |        |        |        |        |        |
| Below-Ground                                 | 350            |               |                |        |        |        |        |        |
| Other  | 350            |               |                |        |        |        |        |        |

\* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

\*\* Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

\*\*\* The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1113 7-13-2007]**

**TABLE OF STANDARDS (cont.)**  
**VOC LIMITS**

**Grams of VOC Per Liter of Material**

| COATING            | Limit |
|--------------------|-------|
| Low-Solids Coating | 120   |

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1125 1-13-1995]**

Except as otherwise provided in Rule 1125, the operator shall not use or apply any coating on any coating line of the type designated below which contains any volatile organic compound in excess of the following limits:

| <u>COATING</u>  | <b>VOC LIMITS</b>  |               |
|---|--|---------------|
|   | Grams per Liter of Coating,<br>Less Water and<br>Less Exempt Compounds |               |
|   | <u>g/L</u>   | <u>lb/gal</u> |
| Can Coating   |  |               |
| (A) Three-Piece Can Sheet Basecoat<br>(exterior and interior and overvarnish) | 225  | 1.9           |
| (B) Two-Piece Can Exterior Basecoat<br>and Overvarnish                        | 250  | 2.1           |
| (C) Inks  | 300  | 2.5           |
| (D) Can Interior Body Spray   |  |               |
| (i) Two-Piece Can   | 440  | 3.7           |
| (ii) Three-Piece Can  | 510  | 4.2           |
| (E) Three-Piece Can Side Seam Spray   | 660  | 5.5           |
| (F) End Sealing Compound  |  |               |
| (i) Food/Beverage Cans  | 440  | 3.7           |
| (ii) Non-Food Cans<br>(After March 1, 1991)                                   | 440<br>0   | 3.7<br>0      |
| (G) Drums, Pails, and Lids Coating  |  |               |
| (i) New   |  |               |
| Exterior  | 340  | 2.8           |
| Interior  | 420  | 3.5           |
| (ii) Reconditioned  |  |               |
| Exterior  | 420  | 3.5           |
| Interior  | 510  | 4.2           |
| (H) Necker Lubricants   | 100  | 0.8           |
| Coil Coating  | 200  | 1.7           |



**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1145 2-14-1997]**

Except as otherwise provided in Rule 1145, the operator shall not apply on plastics, glass, or rubber any coatings which are applied with a VOC content in excess of the limits specified below:

| COATING   | VOC LIMITS                        |         |                     |         |
|---|-----------------------------------|---------|---------------------|---------|
|   | <u>Less Water and Less Exempt</u> |         |                     |         |
|   | <u>Compounds</u>                  |         |                     |         |
|   | Current                           |         | On and After 1-1-98 |         |
|   | g/L                               | lbs/gal | g/L                 | lbs/gal |
| General Coatings                                      |                                   |         |                     |         |
| One-component   | 275                               | 2.3     | 275                 | 2.3     |
| Two-component   | 420                               | 3.5     | 420                 | 3.5     |
| Military Spec. Coating                                |                                   |         |                     |         |
| One-component   | 340                               | 2.8     | 340                 | 2.8     |
| Two-component   | 420                               | 3.5     | 420                 | 3.5     |
| Multi-Colored Coatings                                | 685                               | 5.7     | 685                 | 5.7     |
| Mold Seal Coatings                                    | 750                               | 6.3     | 750                 | 6.3     |
| Vacuum Metalizing Coatings                            | 800                               | 6.7     | 800                 | 6.7     |
| Mirror Backing  |                                   |         |                     |         |
| Curtain Coated  | 500                               | 4.2     | 500                 | 4.2     |
| Roll Coated   | 430                               | 3.6     | 430                 | 3.6     |
| Optical Coatings                                      | 800                               | 6.7     | 800                 | 6.7     |
| Electric Dissipating Coatings and Shock-Free Coatings | 800                               | 6.7     | 360                 | 3.0     |
| Metallic Coatings                                     | 420                               | 3.5     | 420                 | 3.5     |

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1171 11-7-2003]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| SOLVENT CLEANING ACTIVITY  | CURRENT LIMITS         |
|--|------------------------|
|  | VOC<br>g/l<br>(lb/gal) |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application |                        |
| (i) General  | 25<br>(0.21)           |
| (ii) Electrical Apparatus Components & Electronic Components   | 500<br>(4.2)           |
| (iii) Medical Devices & Pharmaceuticals  | 800<br>(6.7)           |
| (B) Repair and Maintenance Cleaning  |                        |
| (i) General  | 25<br>(0.21)           |
| (ii) Electrical Apparatus Components & Electronic Components   | 900<br>(7.5)           |
| (iii) Medical Devices & Pharmaceuticals  |                        |
| (A) Tools, Equipment, & Machinery  | 800<br>(6.7)           |
| (B) General Work Surfaces  | 600<br>(5.0)           |

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1171 11-7-2003]**

| SOLVENT CLEANING ACTIVITY   | CURRENT LIMITS         |
|---|------------------------|
|   | VOC<br>g/l<br>(lb/gal) |
| (C) Cleaning of Coatings or Adhesives Application Equipment                               | 550<br>(4.6)           |
| (D) Cleaning of Ink Application Equipment   |                        |
| (i) General   | 25<br>(0.21)           |
| (ii) Flexographic Printing  | 25<br>(0.21)           |
| (iii) Gravure Printing  |                        |
| (A) Publication   | 750<br>(6.3)           |
| (B) Packaging   | 25<br>(0.21)           |
| (iv) Lithographic or Letter Press Printing  |                        |
| (A) Roller Wash – Step 1  | 600<br>(5.0)           |
| (B) Roller Wash-Step 2,<br>Blanket Wash, & On-Press Components                            | 800<br>(6.7)           |
| (C) Removable Press Components  | 25<br>(0.21)           |
| (v) Screen Printing   | 750<br>(6.3)           |
| (vi) Ultraviolet Ink/ Electron Beam Ink<br>Application Equipment (except screen printing) | 800<br>(6.7)           |

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1171 11-7-2003]**

| SOLVENT CLEANING ACTIVITY                             | CURRENT LIMITS         |
|---|------------------------|
|   | VOC<br>g/l<br>(lb/gal) |
| (vii) Specialty Flexographic Printing                 | 600<br>(5.0)           |
| (E) Cleaning of Polyester Resin Application Equipment | 25<br>(0.21)           |

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1171 7-14-2006]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

|  | <b>CURRENT<br/>LIMITS*</b>      | <b>EFFECTIVE<br/>1/1/2008</b>   |
|--|---------------------------------|---------------------------------|
| <b>SOLVENT CLEANING ACTIVITY</b>   | <b>VOC<br/>g/l<br/>(lb/gal)</b> | <b>VOC<br/>g/l<br/>(lb/gal)</b> |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application |                                 |                                 |
| (i) General  | 25<br>(0.21)                    |                                 |
| (ii) Electrical Apparatus Components & Electronic Components   | 100<br>(0.83)                   |                                 |
| (iii) Medical Devices & Pharmaceuticals  | 800<br>(6.7)                    |                                 |
| (B) Repair and Maintenance Cleaning  |                                 |                                 |
| (i) General  | 25<br>(0.21)                    |                                 |
| (ii) Electrical Apparatus Components & Electronic Components   | 100<br>(0.83)                   |                                 |

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1171 7-14-2006]**

|   | <b>CURRENT<br/>LIMITS*</b>      | <b>EFFECTIVE<br/>1/1/2008</b>   |
|---|---------------------------------|---------------------------------|
| <b>SOLVENT CLEANING ACTIVITY<br/>(cont.)</b>                | <b>VOC<br/>g/l<br/>(lb/gal)</b> | <b>VOC<br/>g/l<br/>(lb/gal)</b> |
| (iii) Medical Devices & Pharmaceuticals                     |                                 |                                 |
| (A) Tools, Equipment, & Machinery                           | 800<br>(6.7)                    |                                 |
| (B) General Work Surfaces                                   | 600<br>(5.0)                    |                                 |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 25<br>(0.21)                    |                                 |
| (D) Cleaning of Ink Application Equipment                   |                                 |                                 |
| (i) General   | 25<br>(0.21)                    |                                 |
| (ii) Flexographic Printing                                  | 25<br>(0.21)                    |                                 |
| (iii) Gravure Printing                                      |                                 |                                 |
| (A) Publication   | 100<br>(0.83)                   |                                 |
| (B) Packaging   | 25<br>(0.21)                    |                                 |
| (iv) Lithographic (Offset) or Letter Press Printing         |                                 |                                 |
| (A) Roller Wash, Blanket Wash, & On-Press Components        |                                 |                                 |
| (I) Newsprint   | 100<br>(0.83)                   |                                 |

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 1171 7-14-2006]**

|  | <b>CURRENT<br/>LIMITS*</b>      | <b>EFFECTIVE<br/>1/1/2008</b>   |
|--|---------------------------------|---------------------------------|
| <b>SOLVENT CLEANING ACTIVITY<br/>(cont.)</b>   | <b>VOC<br/>g/l<br/>(lb/gal)</b> | <b>VOC<br/>g/l<br/>(lb/gal)</b> |
| (II) Other Substrates  | 500<br>(4.2)                    | 100<br>(0.83)                   |
| (B) Removable Press Components   | 25<br>(0.21)                    |                                 |
| (v) Screen Printing  | 500<br>(4.2)                    | 100<br>(0.83)                   |
| (vi) Ultraviolet Ink/ Electron Beam Ink<br>Application Equipment (except<br>screen printing) | 650<br>(5.4)                    | 100<br>(0.83)                   |
| (vii) Specialty Flexographic Printing  | 100<br>(0.83)                   |                                 |
| (E) Cleaning of Polyester Resin Application<br>Equipment                                     | 25<br>(0.21)                    |                                 |

\* The specified limits remain in effect unless revised limits are listed in subsequent columns.

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 404 2-7-1986]**

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

**TABLE 404(a)**

| Volume Discharged Calculated as Dry Gas At Standard Conditions |                       | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions |                       | Volume Discharged Calculated as Dry Gas At Standard Conditions |                       | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions |                       |
|--|-----------------------|--|-----------------------|--|-----------------------|--|-----------------------|
| Cubic meters Per Minute  | Cubic feet Per Minute | Milligrams per Cubic Meter   | Grains per Cubic Foot | Cubic meters Per Minute  | Cubic feet Per Minute | Milligrams per Cubic Meter   | Grains per Cubic Foot |
| 25 or less   | 883 or less           | 450  | 0.196                 | 900  | 31780                 | 118  | 0.0515                |
| 30   | 1059                  | 420  | .183                  | 1000   | 35310                 | 113  | .0493                 |
| 35   | 1236                  | 397  | .173                  | 1100   | 38850                 | 109  | .0476                 |
| 40   | 1413                  | 377  | .165                  | 1200   | 42380                 | 106  | .0463                 |
| 45   | 1589                  | 361  | .158                  | 1300   | 45910                 | 102  | .0445                 |
| 50   | 1766                  | 347  | .152                  | 1400   | 49440                 | 100  | .0437                 |
| 60   | 2119                  | 324  | .141                  | 1500   | 52970                 | 97   | .0424                 |
| 70   | 2472                  | 306  | .134                  | 1750   | 61800                 | 92   | .0402                 |

**FACILITY PERMIT TO OPERATE**  
**TED LEVINE DRUM CO**

**APPENDIX B: RULE EMISSION LIMITS**  
**[RULE 404 2-7-1986]**

| Volume Discharged Calculated as Dry Gas At Standard Conditions |                       | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions |                       | Volume Discharged Calculated as Dry Gas At Standard Conditions |                       | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions |                       |
|--|-----------------------|--|-----------------------|--|-----------------------|--|-----------------------|
| Cubic meters Per Minute  | Cubic feet Per Minute | Milligrams per Cubic Meter   | Grains per Cubic Foot | Cubic meters Per Minute  | Cubic feet Per Minute | Milligrams per Cubic Meter   | Grains per Cubic Foot |
| 80   | 2825                  | 291  | .127                  | 2000   | 70630                 | 87   | .0380                 |
| 90   | 3178                  | 279  | .122                  | 2250   | 79460                 | 83   | .0362                 |
| 100  | 3531                  | 267  | .117                  | 2500   | 88290                 | 80   | .0349                 |
| 125  | 4414                  | 246  | .107                  | 3000   | 105900                | 75   | .0327                 |
| 150  | 5297                  | 230  | .100                  | 4000   | 141300                | 67   | .0293                 |
| 175  | 6180                  | 217  | .0947                 | 5000   | 176600                | 62   | .0271                 |
| 200  | 7063                  | 206  | .0900                 | 6000   | 211900                | 58   | .0253                 |
| 250  | 8829                  | 190  | .0830                 | 8000   | 282500                | 52   | .0227                 |
| 300  | 10590                 | 177  | .0773                 | 10000  | 353100                | 48   | .0210                 |
| 350  | 12360                 | 167  | .0730                 | 15000  | 529700                | 41   | .0179                 |
| 400  | 14130                 | 159  | .0694                 | 20000  | 706300                | 37   | .0162                 |
| 450  | 15890                 | 152  | .0664                 | 25000  | 882900                | 34   | .0148                 |
| 500  | 17660                 | 146  | .0637                 | 30000  | 1059000               | 32   | .0140                 |
| 600  | 21190                 | 137  | .0598                 | 40000  | 1413000               | 28   | .0122                 |
| 700  | 24720                 | 129  | .0563                 | 50000  | 1766000               | 26   | .0114                 |
| 800  | 28250                 | 123  | .0537                 | 70000<br>or more   | 2472000<br>or more    | 23   | .0100                 |