WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 11979
Rec. 19
Well No. WW 36
Permit No. 25399
Do not fill in

Owner: THE ANACONDA COMPANY Driller: THE ANACONDA COMPANY

Address: Weed Heights, Nevada 89443 Address: Weed Heights, Nev. 89443 Lic. No.

Location of well: SE ¼ SE ¼ Sec. 16, T13 N, R25 E, in Lyon County

or

Water will be used for: Milling, Mining, Domestic Total depth of well: 300'

Size of drilled hole: 20" ϕ Weight of casing per linear foot: 18" - 47 lbs.

Thickness of casing: 1/4" Temp. of water: 62°

Diameter and length of casing: 20" to 178', 18" to 300'.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 60'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: February 1, 1969 Date of completion of well: April 15, 1969

Type of well rig: Bucyrus-Erie 42 T. Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	60	60	Gravel
60	300	240	Porphyry

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 60 to 300 ft.

Other aquifers

First water at 60 feet.

Casing perforated
from 100 to 300 ft.

Size of perforations
1/4" x 10"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

WW-36

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
20"	0	178	178	15 cu. yds. pea gravel around top of casing.
18"	0	300	300	may have pulled 20"

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No.....

Dated....., 19.....

(Not to be filled in by Driller)