



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 East Copley Drive, Diamond Bar, CA 91765

Title Page	
Facility I.D.#:	124904
Revision #:	5
Date:	March 26, 2008

FACILITY PERMIT TO OPERATE

**LOS ANGELES TIMES COMMUNICATIONS LLC
2000 E 8TH ST
LOS ANGELES, CA 90021**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By 
Carol Coy
Deputy Executive Officer
Engineering & Compliance



**FACILITY PERMIT TO OPERATE
LOS ANGELES TIMES COMMUNICATIONS LLC**

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	1	05/06/2007
B	RECLAIM Annual Emission Allocation	1	05/06/2007
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	4	03/26/2008
E	Administrative Conditions	1	05/06/2007
F	RECLAIM Monitoring and Source Testing Requirements	1	05/06/2007
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	1	05/06/2007
H	Permit To Construct and Temporary Permit to Operate	1	05/06/2007
I	Compliance Plans & Schedules	1	05/06/2007
J	Air Toxics	1	05/06/2007
K	Title V Administration	2	05/06/2007
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	1	05/06/2007
B	Rule Emission Limits	2	05/06/2007

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
374562	F35205	STORAGE TANK MISC MATERIALS
374568	F35233	BOILER (5-20 MMBTU/HR) NAT GAS ONLY
374570	F35256	WASTE INK RECLAMATION
374580	F35173	BOILER (5-20 MMBTU/HR) COMB GAS-LPG
386010	F40302	I C E (>500 HP) N-EM STAT DIESEL
403615	F56139	I C E (50 - 500 HP) EM STAT DIESEL
427656	F69227	PRINTING PRESS LITHOGRAPHIC AIR DRY
427657	F69228	PRINTING PRESS LITHOGRAPHIC AIR DRY
427658	F69229	PRINTING PRESS LITHOGRAPHIC AIR DRY
427659	F69230	PRINTING PRESS LITHOGRAPHIC AIR DRY
427660	F69231	PRINTING PRESS LITHOGRAPHIC AIR DRY
427661	F69232	PRINTING PRESS LITHOGRAPHIC AIR DRY
471432	F96101	I C E (>500 HP) N-EM STAT DIESEL
471433	F96102	I C E (>500 HP) N-EM STAT DIESEL
471434	F96103	I C E (>500 HP) N-EM STAT DIESEL

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.
[RULE 401]
2. THE OPERATOR SHALL NOT USE FUEL OIL CONTAINING SULFUR COMPOUNDS IN EXCESS OF 0.05% BY WEIGHT.
[RULE 431.2]
3. AFTER JUNE 1, 2004, THE OPERATOR SHALL NOT PURCHASE ANY DIESEL FUEL UNLESS THE FUEL IS LOW SULFUR DIESEL FOR WHICH THE SULFUR CONTENT SHALL NOT EXCEED 15 PPM BY WEIGHT AS SUPPLIED BY THE SUPPLIER
[RULE 431.2]
4. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS DISCHARGED TO THE ATMOSPHERE FROM THIS FACILITY SHALL NOT EXCEED 432 POUNDS IN ANY ONE DAY.
[RULE 1302(b)(2)-OFFSET]
5. IN ADDITION TO THE REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY COMPLIANCE WITH ALL CONDITIONS STATED IN THIS PERMIT. SUCH RECORDS SHALL BE MAINTAINED IN A MANNER ACCEPTABLE TO THE DISTRICT, RETAINED AT THE FACILITY FOR AT LEAST FIVE YEARS, AND MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
6. MATERIAL SAFETY DATA SHEETS FOR ALL INKS, COATINGS AND SOLVENTS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO OPERATE

Permit No. F35205
A/N 374562

Equipment Description:

STORAGE TANK, AQUEOUS AMMONIA STORAGE, 1,500-GAL CAPACITY, 4'-7" DIA. X 12'-1" L., WITH A VAPOR BALANCE SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS TANK CAN ONLY STORE AQUEOUS AMMONIA.
[RULE 1303(a)(1)-BACT]
4. DURING FILLING, THIS EQUIPMENT SHALL BE VENTED ONLY TO THE VESSEL FROM WHICH IT IS BEING FILLED.
[RULE 1303(a)(1)-BACT]
5. THE MAXIMUM QUANTITY OF AQUEOUS AMMONIA FILLED INTO THIS EQUIPMENT SHALL NOT EXCEED 750 GALLONS PER DAY.
[RULE 1303(a)(1)-BACT]
6. LOS ANGELES TIMES SHALL COMPLY WITH RULE 1113 DURING PAINTING OF THIS EQUIPMENT.
[RULE 1113]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO OPERATE

Permit No. F35233
A/N 374568

Equipment Description:

BOILER, CLEAVER-BROOKS, WATERTUBE TYPE, MODEL NUMBER M4700-5000, 4,980,000 BTU/HR, WITH ONE CLEAVER-BROOKS, MODEL NUMBER M4700 GAS BURNER, WITH AN OXYGEN TRIM SYSTEM, AND A FLUE GAS RECIRCULATION SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE FIRED ON NATURAL GAS ONLY, EXCEPT DURING PERIODS OF NATURAL GAS CURTAILMENT, OR MAINTENANCE, OR PERFORMANCE TESTING WITH PROPANE/AIR MIXTURE. MAINTENANCE OR PERFORMANCE TESTING SHALL NOT EXCEED 4 DAYS PER CALENDAR YEAR, AND THE ACTUAL FUEL SUPPLIED TO THE BURNER SHALL NOT EXCEED 3 HOURS PER YEAR.
[RULE 1303(a)(1)-BACT]
4. OXIDES OF NITROGEN CONCENTRATIONS IN THE FLUE GAS SHALL NOT EXCEED 30 PPM (DRY) CALCULATED AT 3 PERCENT OXYGEN.
[RULE 1146.1, 1303(a)(1)-BACT]
5. THE FLUE GAS RECIRCULATION AND OXYGEN TRIM SYSTEM SHALL BE IN FULL OPERATION WHENEVER THIS BOILER IS IN OPERATION. THE BURNER SHALL BE EQUIPPED WITH A CONTROL SYSTEM TO REGULATE THE COMBUSTION AIR, FUEL, AND RECIRCULATED FLUE GAS AS THE LOAD VARIES. THIS CONTROL SYSTEM SHALL BE ADJUSTED AND TUNED AT LEAST TWICE A YEAR, ACCORDING TO THE MANUFACTURER'S SPECIFICATIONS TO ASSURE ITS ABILITY TO REPEAT THE SAME PERFORMANCE AT THE SAME BURNER FIRING RATE.
[RULE 1303(a)(1)-BACT]
6. THE OWNER OR OPERATOR OF THIS BOILER SHALL MAINTAIN ALL BOILER TUNE-UP RECORDS, AS SPECIFIED IN CONDITION NUMBER 5, FOR A PERIOD OF AT LEAST FIVE YEARS AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1146.1, 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

Periodic Monitoring:

7. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE CO EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER AND AQMD-APPROVED TEST METHOD OR , IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH THE CO CONCENTRATION LIMIT(S). THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.
[RULE 3004 (a)(4)]

8. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE NOX EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER AND AQMD-APPROVED TEST METHOD OR , IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH THE NO_x CONCENTRATION LIMIT(S). THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.
[RULE 3004 (a)(4)]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

NOX: 30 PPMV, RULE 1146.1, 1303(a)(1)-BACT
CO: 400 PPMV, RULE 1146.1
CO: 2000 PPMV, RULE 407
PM: 0.1gr/scf, RULE 409

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO OPERATE

Permit No. F35256
A/N 374570

Equipment Description:

WASTE INK RECLAMATION AND BLENDING SYSTEM CONSISTING OF:

1. WASTE INK HOLDING TANK, 4'-0" DIA. X 5'-6" H., 500 GALLON CAPACITY.
2. STILL, BRIGHTON, 3'-6" DIA. X 4'-8" H., 150 GALLON CAPACITY, STEAM HEATED, 102 KW WATER HEATER, WITH A 1 H.P. AGITATOR.
3. CONDENSER, 1'-1" DIA. X 8'-4" H., 81 SQ. FT. SURFACE AREA, TUBE AND SHELL TYPE.
4. VACUUM PUMP, LIQUID RING SEAL, 2 H.P.
5. CONDENSATE RECEIVING TANK.
6. INLINE CENTRIFUGE, 5 H.P. DRIVE.
7. INLINE FILTER.
8. BLEND TANK, 5'-6" DIA. X 5'-0" H., 1000 GALLON CAPACITY, WITH A 5 H.P. AGITATOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. A FLOWMETER INDICATING G.P.M. AND A TEMPERATURE GAUGE SHALL BE INSTALLED IN THE WATER SUPPLY LINE TO THE CONDENSER. THE FLOW RATE SHALL NOT BE LESS THAN 49 GALLONS PER MINUTE AT A TEMPERATURE OF NOT MORE THAN 55 °F.
[RULE 1303(a)(1)-BACT]
4. A TEMPERATURE GAUGE SHALL BE INSTALLED IN THE STILL. THE TEMPERATURE OF THE STILL CONTENTS SHALL NOT EXCEED 150 °F WHEN OPERATING UNDER VACUUM.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

5. THE STILL SHALL BE CHARGED ONLY WITH WASTE PRINTING INK CONTAINING WATER AND PAPER DUST.
[RULE 1303(a)(1)-BACT]
6. THE STILL SHALL NOT PROCESS MORE THAN 2000 POUNDS OF WASTE PRINTING INK IN ANY ONE DAY.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
7. RECORDS SHALL BE MAINTAINED TO PROVE COMPLIANCE WITH CONDITIONS 3, 4, 5, AND 6. THESE RECORDS SHALL BE KEPT IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT. THE RECORDS SHALL BE MAINTAINED FOR AT LEAST FIVE YEARS AND MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO OPERATE

Permit No. F35173
A/N 374580

Equipment Description:

BOILER, SELLERS, FIRETUBE TYPE, MODEL NUMBER 125 HPW-LN390, 5,230,000 BTU/HR, WITH ONE SELLERS, MODEL NUMBER 125 HPW-LN390 GAS BURNER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE FIRED ON NATURAL GAS ONLY, EXCEPT DURING PERIODS OF NATURAL GAS CURTAILMENT, OR MAINTENANCE, OR PERFORMANCE TESTING WITH PROPANE/AIR MIXTURE. MAINTENANCE OR PERFORMANCE TESTING SHALL NOT EXCEED 4 DAYS PER CALENDAR YEAR, AND THE ACTUAL FUEL SUPPLIED TO THE BURNER SHALL NOT EXCEED 3 HOURS PER YEAR.
[RULE 1303(a)(1)-BACT]
4. OXIDES OF NITROGEN CONCENTRATIONS IN THE FLUE GAS SHALL NOT EXCEED 30 PPM (DRY) CALCULATED AT 3 PERCENT OXYGEN AND CARBON MONOXIDE CONCENTRATIONS IN THE FLUE GAS SHALL NOT EXCEED 400 PPM.
[RULE 1146, 1303(a)(1)-BACT]
5. THE BURNER SHALL BE EQUIPPED WITH A CONTROL SYSTEM TO REGULATE THE COMBUSTION AIR AND FUEL AS THE LOAD VARIES. THIS CONTROL SYSTEM SHALL BE ADJUSTED AND TUNED AT LEAST TWICE A YEAR, ACCORDING TO THE MANUFACTURER'S SPECIFICATIONS TO ASSURE ITS ABILITY TO REPEAT THE SAME PERFORMANCE AT THE SAME BURNER FIRING RATE.
[RULE 1303(a)(1)-BACT]
6. THE OWNER OR OPERATOR OF THIS BOILER SHALL MAINTAIN ALL BOILER TUNE-UP RECORDS, AS SPECIFIED IN CONDITION NUMBER 5, FOR A PERIOD OF AT LEAST FIVE YEARS AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1146, 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

Periodic Monitoring:

7. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE NOX EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER AND AQMD-APPROVED TEST METHOD OR , IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH THE NO_x CONCENTRATION LIMIT(S). THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.
[RULE 3004 (a)(4)]

8. THE OPERATOR SHALL DETERMINE COMPLIANCE WITH THE CO EMISSION LIMIT(S) BY CONDUCTING A TEST AT LEAST ONCE EVERY FIVE YEARS USING A PORTABLE ANALYZER AND AQMD-APPROVED TEST METHOD OR , IF NOT AVAILABLE, A NON-AQMD APPROVED TEST METHOD. THE TEST SHALL BE CONDUCTED WHEN THE EQUIPMENT IS OPERATING UNDER NORMAL CONDITIONS TO DEMONSTRATE COMPLIANCE WITH THE CO CONCENTRATION LIMIT(S). THE OPERATOR SHALL COMPLY WITH ALL GENERAL TESTING, REPORTING, AND RECORDKEEPING REQUIREMENTS IN SECTIONS E AND K OF THIS PERMIT.
[RULE 3004 (a)(4)]

Emissions and Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

NOX: 30 PPM, RULE 1146, 1303(a)(1)-BACT
CO: 400 PPM, RULE 1146
CO: 2000 PPMV, RULE 407
PM: 0.1gr/scf, RULE 409

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO OPERATE

**Permit No. F40302
A/N 386010**

Equipment Description:

INTERNAL COMBUSTION ENGINE, CATERPILLAR, MODEL NO. 3406B, DIESEL-FUELED, FOUR CYCLE, TURBOCHARGED, AFTERCOOLED, 6 CYLINDERS, 417 BHP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. AN ELAPSED OPERATING TIME METER SHALL BE INSTALLED AND MAINTAINED ON THIS ENGINE, SO AS TO INDICATE, IN CUMULATIVE HOURS, THE AMOUNT OF TIME THE ENGINE HAS OPERATED.
[RULE 1303(a)(1)-BACT]
4. THIS ENGINE SHALL BE OPERATED LESS THAN 200 HOURS PER CALENDAR YEAR.
[RULE 1110.2, 1303(a)(1)-BACT, 1304(a)(4)-MODELING AND OFFSET EXEMPTION]
5. THE EMISSION RATE OF REACTIVE ORGANIC GASES SHALL NOT EXCEED 0.12 LB/HR. THE EMISSION RATE OF OXIDES OF NITROGEN SHALL NOT EXCEED 6.4 LB/HR.
[RULE 1303(a)(1)-BACT]
6. THE FUEL INJECTION TIMING OF THIS ENGINE SHALL BE SET AND MAINTAINED AT 4 DEGREES RETARDED RELATIVE TO STANDARD TIMING.
[RULE 1303(a)(1)-BACT]
7. THE FUEL INJECTION TIMING OF THIS ENGINE SHALL BE INSPECTED, ADJUSTED, AND CERTIFIED, AT A MINIMUM, ONCE EVERY THREE YEARS. INSPECTIONS, ADJUSTMENTS, AND CERTIFICATIONS SHALL BE PERFORMED BY A QUALIFIED MECHANIC ACCORDING TO THE ENGINE MANUFACTURER'S RECOMMENDED PROCEDURES.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

8. AN OPERATING LOG OF THIS EQUIPMENT SHALL BE MAINTAINED IN A FORMAT ACCEPTABLE TO THE DISTRICT. THE RECORD SHALL INCLUDE, AT A MINIMUM, THE HOURS AND DAYS OF OPERATION, AND THE QUANTITY OF FUEL USED. THE OPERATING RECORD SHALL BE KEPT FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

PM: RULE 1470

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO OPERATE

**Permit No. F56139
A/N 403615**

Equipment Description:

INTERNAL COMBUSTION ENGINE, CUMMINS, DIESEL-FUELED, MODEL NO. NT855 F-5, 6 CYLINDERS, FOUR CYCLE, TURBOCHARGED, AFTERCOOLED, 250 BHP, WITH 1 EXHAUST, DRIVING A FIRE PUMP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. AN ELAPSED OPERATING TIME METER SHALL BE INSTALLED AND MAINTAINED ON THIS ENGINE, SO AS TO INDICATE, IN CUMULATIVE HOURS, THE AMOUNT OF TIME THE ENGINE HAS OPERATED.
[RULE 1303(a)(1)-BACT]
4. THIS ENGINE SHALL BE OPERATED LESS THAN 200 HOURS PER CALENDAR YEAR.
[RULE 1110.2, 1303(a)(1)-BACT, 1304(a)(4)-MODELING AND OFFSET EXEMPTION]
5. THE FUEL INJECTION TIMING OF THIS ENGINE SHALL BE INSPECTED, ADJUSTED, AND CERTIFIED, AT A MINIMUM, ONCE EVERY THREE YEARS. INSPECTIONS, ADJUSTMENTS, AND CERTIFICATIONS SHALL BE PERFORMED BY A QUALIFIED MECHANIC ACCORDING TO THE ENGINE MANUFACTURER'S RECOMMENDED PROCEDURES.
[RULE 1303(a)(1)-BACT]
6. AN OPERATING LOG OF THIS EQUIPMENT SHALL BE MAINTAINED IN A FORMAT ACCEPTABLE TO THE DISTRICT. THE RECORD SHALL INCLUDE, AT A MINIMUM, THE HOURS AND DAYS OF OPERATION, AND THE QUANTITY OF FUEL USED. THE OPERATING RECORD SHALL BE KEPT FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1470

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO CONSTRUCT/OPERATE

Permit No. F69227
A/N 427656

Equipment Description:

LITHOGRAPHIC NEWSPAPER PRINTING SYSTEM "B" COLORLINER, AIR DRY, TWELVE UNIT PLUS FOLDER CONSISTING OF:

1. SEVEN GOSS COLORLINER MONO UNITS, BLACK ONLY.
2. ONE MANROLAND COLORMAN FOUR-HIGH FOUR-COLOR UNIT.
3. FOUR GOSS COLORLINER. FOUR-HIGH FOUR-COLOR TOWER UNITS.
4. ONE GOSS FOLDER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT OF THE FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT EXCEED 0.17 POUNDS PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOC IN THE BLANKET AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 25 mm Hg AT 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOC EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 175 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING:
 - A. DENSITY OF EACH INK IN POUNDS PER GALLON.
 - B. THE PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN EACH INK.

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

- C. THE INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT DISTRICT GUIDELINES.
 - D. THE VOC CONTENT OF FOUNTAIN SOLUTIONS, WASH MATERIALS, AND ANY OTHER VOC-CONTAINING MATERIALS IN POUNDS PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
 - E. THE DAILY VOC EMISSIONS IN POUNDS.
 - F. OTHER DATA AS REQUIRED TO VERIFY COMPLIANCE WITH THE CONDITIONS SPECIFIED IN THIS PERMIT.
[RULE 109, 1303(b)(2)-OFFSET]
7. THIS PERMIT SHALL EXPIRE IF THE MODIFICATION OF THIS EQUIPMENT IS NOT COMPLETED BY JUNE 29, 2005 UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.
[RULE 205]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO CONSTRUCT/OPERATE

Permit No. F69228
A/N 427657

Equipment Description:

LITHOGRAPHIC NEWSPAPER PRINTING SYSTEM "A" COLORLINER, AIR DRY, TWELVE UNIT PLUS FOLDER CONSISTING OF:

1. SEVEN GOSS COLORLINER MONO UNITS, BLACK ONLY
2. ONE MANROLAND COLORMAN FOUR-HIGH FOUR-COLOR UNIT
3. FOUR GOSS COLORLINER. FOUR-HIGH FOUR-COLOR TOWER UNITS
4. ONE GOSS FOLDER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT OF THE FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT EXCEED 0.17 POUNDS OF VOC PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOC IN THE BLANKET AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 25 mm Hg AT 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOC EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 175 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING:
 - A. DENSITY OF EACH INK IN POUNDS PER GALLON.
 - B. THE PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN EACH INK.

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

- C. THE INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT DISTRICT GUIDELINES.
 - D. THE VOC CONTENT OF FOUNTAIN SOLUTIONS, WASH MATERIALS, AND ANY OTHER VOC-CONTAINING MATERIALS IN POUNDS PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
 - E. THE DAILY VOC EMISSIONS IN POUNDS.
 - F. OTHER DATA AS REQUIRED TO VERIFY COMPLIANCE WITH THE CONDITIONS SPECIFIED IN THIS PERMIT.
[RULE 109, 1303(b)(2)-OFFSET]
7. THIS PERMIT SHALL EXPIRE IF THE MODIFICATION OF THIS EQUIPMENT IS NOT COMPLETED BY JUNE 29, 2005 UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.
[RULE 205]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO CONSTRUCT/OPERATE

Permit No. F69229
A/N 427658

Equipment Description:

LITHOGRAPHIC NEWSPAPER PRINTING SYSTEM "C" COLORLINER, AIR DRY, TWELVE UNIT PLUS FOLDER CONSISTING OF:

1. SEVEN GOSS COLORLINER MONO UNITS, BLACK ONLY
2. ONE MANROLAND COLORMAN FOUR-HIGH FOUR-COLOR UNIT
3. FOUR GOSS COLORLINER. FOUR-HIGH FOUR-COLOR TOWER UNITS
4. ONE GOSS FOLDER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT OF THE FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT EXCEED 0.17 POUNDS OF VOC PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOC IN THE BLANKET AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 25 mm Hg AT 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOC EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 175 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING:
 - A. DENSITY OF EACH INK IN POUNDS PER GALLON.
 - B. THE PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN EACH INK.

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

- C. THE INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT DISTRICT GUIDELINES.
 - D. THE VOC CONTENT OF FOUNTAIN SOLUTIONS, WASH MATERIALS, AND ANY OTHER VOC-CONTAINING MATERIALS IN POUNDS PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
 - E. THE DAILY VOC EMISSIONS IN POUNDS.
 - F. OTHER DATA AS REQUIRED TO VERIFY COMPLIANCE WITH THE CONDITIONS SPECIFIED IN THIS PERMIT.
[RULE 109, 1303(b)(2)-OFFSET]
7. THIS PERMIT SHALL EXPIRE IF THE MODIFICATION OF THIS EQUIPMENT IS NOT COMPLETED BY JUNE 29, 2005 UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.
[RULE 205]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO CONSTRUCT/OPERATE

Permit No. F69230
A/N 427659

Equipment Description:

LITHOGRAPHIC NEWSPAPER PRINTING SYSTEM "D" COLORLINER, AIR DRY, TWELVE UNIT PLUS FOLDER CONSISTING OF:

1. SEVEN GOSS COLORLINER MONO UNITS, BLACK ONLY.
2. ONE MANROLAND COLORMAN FOUR-HIGH FOUR-COLOR UNIT.
3. FOUR GOSS COLORLINER. FOUR-HIGH FOUR-COLOR TOWER UNITS.
4. ONE GOSS FOLDER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT OF THE FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT EXCEED 0.17 POUNDS OF VOC PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOC IN THE BLANKET AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 25 mm Hg AT 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOC EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 175 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING:
 - A. DENSITY OF EACH INK IN POUNDS PER GALLON.
 - B. THE PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN EACH INK.

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

- C. THE INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT DISTRICT GUIDELINES.
 - D. THE VOC CONTENT OF FOUNTAIN SOLUTIONS, WASH MATERIALS, AND ANY OTHER VOC-CONTAINING MATERIALS IN POUNDS PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
 - E. THE DAILY VOC EMISSIONS IN POUNDS.
 - F. OTHER DATA AS REQUIRED TO VERIFY COMPLIANCE WITH THE CONDITIONS SPECIFIED IN THIS PERMIT.
[RULE 109, 1303(b)(2)-OFFSET]
7. THIS PERMIT SHALL EXPIRE IF THE MODIFICATION OF THIS EQUIPMENT IS NOT COMPLETED BY JUNE 29, 2005 UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.
[RULE 205]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO CONSTRUCT/OPERATE

**Permit No. F69231
A/N 427660**

Equipment Description:

LITHOGRAPHIC NEWSPAPER PRINTING SYSTEM "F" COLORLINER, AIR DRY, TWELVE UNIT PLUS FOLDER CONSISTING OF:

1. SEVEN GOSS COLORLINER MONO UNITS, BLACK ONLY
2. ONE MANROLAND COLORMAN FOUR-HIGH FOUR-COLOR UNIT
3. FOUR GOSS COLORLINER. FOUR-HIGH FOUR-COLOR TOWER UNITS
4. ONE GOSS FOLDER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT OF THE FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT EXCEED 0.17 POUNDS OF VOC PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOC IN THE BLANKET AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 25 mm Hg AT 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOC EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 175 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING:
 - A. DENSITY OF EACH INK IN POUNDS PER GALLON.
 - B. THE PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN EACH INK.

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

- C. THE INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT DISTRICT GUIDELINES.
 - D. THE VOC CONTENT OF FOUNTAIN SOLUTIONS, WASH MATERIALS, AND ANY OTHER VOC-CONTAINING MATERIALS IN POUNDS PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
 - E. THE DAILY VOC EMISSIONS IN POUNDS.
 - F. OTHER DATA AS REQUIRED TO VERIFY COMPLIANCE WITH THE CONDITIONS SPECIFIED IN THIS PERMIT.
[RULE 109, 1303(b)(2)-OFFSET]
7. THIS PERMIT SHALL EXPIRE IF THE MODIFICATION OF THIS EQUIPMENT IS NOT COMPLETED BY JUNE 29, 2005 UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.
[RULE 205]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO CONSTRUCT/OPERATE

Permit No. F69232
A/N 427661

Equipment Description:

LITHOGRAPHIC NEWSPAPER PRINTING SYSTEM "E" COLORLINER, AIR DRY, TWELVE UNIT PLUS FOLDER CONSISTING OF:

1. SEVEN GOSS COLORLINER MONO UNITS, BLACK ONLY
2. ONE MANROLAND COLORMAN FOUR-HIGH FOUR-COLOR UNIT
3. FOUR GOSS COLORLINER. FOUR-HIGH FOUR-COLOR TOWER UNITS
4. ONE GOSS FOLDER.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT OF THE FOUNTAIN SOLUTION USED IN THIS EQUIPMENT SHALL NOT EXCEED 0.17 POUNDS OF VOC PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 1303(a)(1)-BACT]
4. THE COMPOSITE VAPOR PRESSURE OF THE VOC IN THE BLANKET AND ROLLER WASHES USED ON THIS EQUIPMENT SHALL NOT EXCEED 25 mm Hg AT 20 DEGREES CELSIUS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOC EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 175 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE FOLLOWING:
 - A. DENSITY OF EACH INK IN POUNDS PER GALLON.
 - B. THE PERCENTAGE BY WEIGHT OF LITHOGRAPHIC OILS IN EACH INK.

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

- C. THE INK ABSORPTION FACTOR AS SPECIFIED BY CURRENT DISTRICT GUIDELINES.
 - D. THE VOC CONTENT OF FOUNTAIN SOLUTIONS, WASH MATERIALS, AND ANY OTHER VOC-CONTAINING MATERIALS IN POUNDS PER GALLON AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
 - E. THE DAILY VOC EMISSIONS IN POUNDS.
 - F. OTHER DATA AS REQUIRED TO VERIFY COMPLIANCE WITH THE CONDITIONS SPECIFIED IN THIS PERMIT.
[RULE 109, 1303(b)(2)-OFFSET]
7. THIS PERMIT SHALL EXPIRE IF THE MODIFICATION OF THIS EQUIPMENT IS NOT COMPLETED BY JUNE 29, 2005 UNLESS AN EXTENSION IS GRANTED BY THE EXECUTIVE OFFICER.
[RULE 205]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 109
 - VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO OPERATE

**Permit No. F96101
A/N 471432**

Equipment Description:

INTERNAL COMBUSTION ENGINE NO. 1, CATERPILLAR, MODEL NO. 3516, DIESEL-FUELED, TURBOCHARGED, AFTERCOOLED, 16 CYLINDERS, 2151 BHP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. AN OPERATIONAL NON-RESETTABLE TOTALIZING TIME METER SHALL BE INSTALLED AND MAINTAINED TO INDICATE THE ENGINE ELAPSED OPERATING TIME.
[RULE 1303(a)(1)-BACT]
4. THE OPERATOR SHALL NOT PURCHASE OR USE DIESEL FUEL WITH A SULFUR CONTENT THAT EXCEEDS 15 PPM BY WEIGHT.
[RULE 431.2]
5. THIS ENGINE SHALL NOT BE OPERATED MORE THAN 1 HOUR IN ANY ONE DAY FOR TESTING.
[RULE 1303(a)(1)-BACT]
6. THIS ENGINE SHALL NOT BE OPERATED MORE THAN 200 HOURS IN ANY ONE CALENDAR YEAR, WHICH INCLUDES NO MORE THAN 50 HOURS PER CALENDAR YEAR FOR MAINTENANCE AND TESTING AS REQUIRED IN RULE 1470(c)(3).
[RULE 1470]
7. OPERATION BEYOND THE ALLOTTED TIME FOR ENGINE MAINTENANCE AND TESTING SHALL BE ALLOWED ONLY IN THE EVENT OF A LOSS OF GRID POWER OR UP TO 30 MINUTES PRIOR TO A ROTATING OUTAGE, PROVIDED THAT THE UTILITY DISTRIBUTION COMPANY HAS ORDERED ROTATING OUTAGES IN THE CONTROL AREA WHERE THE ENGINE IS LOCATED OR HAS INDICATED THAT IT EXPECTS TO ISSUE SUCH AN ORDER AT A CERTAIN TIME, AND THE ENGINE IS LOCATED IN A UTILITY SERVICE BLOCK THAT IS SUBJECT TO THE ROTATING OUTAGE. ENGINE OPERATION SHALL BE TERMINATED IMMEDIATELY AFTER THE UTILITY DISTRIBUTION COMPANY ADVISES THAT A ROTATING OUTAGE IS NO LONGER IMMINENT OR IN EFFECT.
[RULE 1470]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

8. THIS ENGINE SHALL NOT BE USED AS PART OF AN INTERRUPTIBLE SERVICE CONTRACT IN WHICH A FACILITY RECEIVES A PAYMENT OR REDUCED RATES IN RETURN FOR REDUCING ELECTRIC LOAD ON THE GRID WHEN REQUESTED BY THE UTILITY OR THE GRID OPERATOR.
[RULE 1303(a)(1)-BACT]

9. AN ENGINE OPERATING LOG SHALL BE KEPT AND MAINTAINED ON FILE TO RECORD WHEN THIS ENGINE IS STARTED MANUALLY. THE LOG SHALL LIST THE DATE OF OPERATION, THE TIMER READING IN HOURS AT THE BEGINNING AND END OF OPERATION, AND THE REASON FOR OPERATION. BY JANUARY 15TH OF EACH YEAR, THE OPERATOR SHALL TOTAL AND RECORD THE TOTAL HOURS OF OPERATION (INCLUDING HOURS FOR BOTH MANUAL OPERATION AND AUTOMATIC OPERATION) FOR THE PREVIOUS CALENDAR YEAR.
[RULE 1303(a)(1)-BACT]

10. AN ENGINE OPERATING LOG LISTING THE DATE OF OPERATION, THE ELAPSED TIME IN HOURS, AND THE REASON FOR OPERATION SHALL BE KEPT AND MAINTAINED ON FILE FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT]

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1470

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO OPERATE

**Permit No. F96102
A/N 471433**

Equipment Description:

INTERNAL COMBUSTION ENGINE NO. 2, CATERPILLAR, MODEL NO. 3516, DIESEL-FUELED, TURBOCHARGED, AFTERCOOLED, 16 CYLINDERS, 2151 BHP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. AN OPERATIONAL NON-RESETTABLE TOTALIZING TIME METER SHALL BE INSTALLED AND MAINTAINED TO INDICATE THE ENGINE ELAPSED OPERATING TIME.
[RULE 1303(a)(1)-BACT]
4. THE OPERATOR SHALL NOT PURCHASE OR USE DIESEL FUEL WITH A SULFUR CONTENT THAT EXCEEDS 15 PPM BY WEIGHT.
[RULE 431.2]
5. THIS ENGINE SHALL NOT BE OPERATED MORE THAN 1 HOUR IN ANY ONE DAY FOR TESTING.
[RULE 1303(a)(1)-BACT]
6. THIS ENGINE SHALL NOT BE OPERATED MORE THAN 200 HOURS IN ANY ONE CALENDAR YEAR, WHICH INCLUDES NO MORE THAN 50 HOURS PER CALENDAR YEAR FOR MAINTENANCE AND TESTING AS REQUIRED IN RULE 1470(c)(3).
[RULE 1470]
7. OPERATION BEYOND THE ALLOTTED TIME FOR ENGINE MAINTENANCE AND TESTING SHALL BE ALLOWED ONLY IN THE EVENT OF A LOSS OF GRID POWER OR UP TO 30 MINUTES PRIOR TO A ROTATING OUTAGE, PROVIDED THAT THE UTILITY DISTRIBUTION COMPANY HAS ORDERED ROTATING OUTAGES IN THE CONTROL AREA WHERE THE ENGINE IS LOCATED OR HAS INDICATED THAT IT EXPECTS TO ISSUE SUCH AN ORDER AT A CERTAIN TIME, AND THE ENGINE IS LOCATED IN A UTILITY SERVICE BLOCK THAT IS SUBJECT TO THE ROTATING OUTAGE. ENGINE OPERATION SHALL BE TERMINATED IMMEDIATELY AFTER THE UTILITY DISTRIBUTION COMPANY ADVISES THAT A ROTATING OUTAGE IS NO LONGER IMMINENT OR IN EFFECT.
[RULE 1470]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

8. THIS ENGINE SHALL NOT BE USED AS PART OF AN INTERRUPTIBLE SERVICE CONTRACT IN WHICH A FACILITY RECEIVES A PAYMENT OR REDUCED RATES IN RETURN FOR REDUCING ELECTRIC LOAD ON THE GRID WHEN REQUESTED BY THE UTILITY OR THE GRID OPERATOR.
[RULE 1303(a)(1)-BACT]
9. AN ENGINE OPERATING LOG SHALL BE KEPT AND MAINTAINED ON FILE TO RECORD WHEN THIS ENGINE IS STARTED MANUALLY. THE LOG SHALL LIST THE DATE OF OPERATION, THE TIMER READING IN HOURS AT THE BEGINNING AND END OF OPERATION, AND THE REASON FOR OPERATION. BY JANUARY 15TH OF EACH YEAR, THE OPERATOR SHALL TOTAL AND RECORD THE TOTAL HOURS OF OPERATION (INCLUDING HOURS FOR BOTH MANUAL OPERATION AND AUTOMATIC OPERATION) FOR THE PREVIOUS CALENDAR YEAR.
[RULE 1303(a)(1)-BACT]
10. AN ENGINE OPERATING LOG LISTING THE DATE OF OPERATION, THE ELAPSED TIME IN HOURS, AND THE REASON FOR OPERATION SHALL BE KEPT AND MAINTAINED ON FILE FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT]

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1470

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

PERMIT TO OPERATE

Permit No. F96103
A/N 471434

Equipment Description:

INTERNAL COMBUSTION ENGINE NO. 3, CATERPILLAR, MODEL NO. 3516, DIESEL-FUELED, TURBOCHARGED, AFTERCOOLED, 16 CYLINDERS, 2151 BHP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. AN OPERATIONAL NON-RESETTABLE TOTALIZING TIME METER SHALL BE INSTALLED AND MAINTAINED TO INDICATE THE ENGINE ELAPSED OPERATING TIME.
[RULE 1303(a)(1)-BACT]
4. THE OPERATOR SHALL NOT PURCHASE OR USE DIESEL FUEL WITH A SULFUR CONTENT THAT EXCEEDS 15 PPM BY WEIGHT.
[RULE 431.2]
5. THIS ENGINE SHALL NOT BE OPERATED MORE THAN 1 HOUR IN ANY ONE DAY FOR TESTING.
[RULE 1303(a)(1)-BACT]
6. THIS ENGINE SHALL NOT BE OPERATED MORE THAN 200 HOURS IN ANY ONE CALENDAR YEAR, WHICH INCLUDES NO MORE THAN 50 HOURS PER CALENDAR YEAR FOR MAINTENANCE AND TESTING AS REQUIRED IN RULE 1470(c)(3).
[RULE 1470]
7. OPERATION BEYOND THE ALLOTTED TIME FOR ENGINE MAINTENANCE AND TESTING SHALL BE ALLOWED ONLY IN THE EVENT OF A LOSS OF GRID POWER OR UP TO 30 MINUTES PRIOR TO A ROTATING OUTAGE, PROVIDED THAT THE UTILITY DISTRIBUTION COMPANY HAS ORDERED ROTATING OUTAGES IN THE CONTROL AREA WHERE THE ENGINE IS LOCATED OR HAS INDICATED THAT IT EXPECTS TO ISSUE SUCH AN ORDER AT A CERTAIN TIME, AND THE ENGINE IS LOCATED IN A UTILITY SERVICE BLOCK THAT IS SUBJECT TO THE ROTATING OUTAGE. ENGINE OPERATION SHALL BE TERMINATED IMMEDIATELY AFTER THE UTILITY DISTRIBUTION COMPANY ADVISES THAT A ROTATING OUTAGE IS NO LONGER IMMINENT OR IN EFFECT.
[RULE 1470]

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

8. THIS ENGINE SHALL NOT BE USED AS PART OF AN INTERRUPTIBLE SERVICE CONTRACT IN WHICH A FACILITY RECEIVES A PAYMENT OR REDUCED RATES IN RETURN FOR REDUCING ELECTRIC LOAD ON THE GRID WHEN REQUESTED BY THE UTILITY OR THE GRID OPERATOR.
[RULE 1303(a)(1)-BACT]

9. AN ENGINE OPERATING LOG SHALL BE KEPT AND MAINTAINED ON FILE TO RECORD WHEN THIS ENGINE IS STARTED MANUALLY. THE LOG SHALL LIST THE DATE OF OPERATION, THE TIMER READING IN HOURS AT THE BEGINNING AND END OF OPERATION, AND THE REASON FOR OPERATION. BY JANUARY 15TH OF EACH YEAR, THE OPERATOR SHALL TOTAL AND RECORD THE TOTAL HOURS OF OPERATION (INCLUDING HOURS FOR BOTH MANUAL OPERATION AND AUTOMATIC OPERATION) FOR THE PREVIOUS CALENDAR YEAR.
[RULE 1303(a)(1)-BACT]

10. AN ENGINE OPERATING LOG LISTING THE DATE OF OPERATION, THE ELAPSED TIME IN HOURS, AND THE REASON FOR OPERATION SHALL BE KEPT AND MAINTAINED ON FILE FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT]

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1470

**FACILITY PERMIT TO OPERATE
LOS ANGELES TIMES COMMUNICATIONS LLC**

PERMIT TO CONSTRUCT

None

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.
[RULE 3004(a)(4)]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, BOILER, > 400,000 BTU/HR BUT < 2 MMBTU/HR.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: 0.1 gr/scf, RULE 409
NOx: 30 PPMV, RULE 1146.2
CO: 400 PPMV, RULE 1146.2
CO: 2000 PPMV, RULE 407

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL UNHEATED, NON-CONVEYORIZED

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1122

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COOLING TOWERS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CR⁺⁶: RULE 1404

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, PRINTING EQUIPMENT, LOW USE OR EMISSIONS, WITH RELATED COATING, LAMINATING AND DRYING EQUIPMENT.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1130, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, FIRE EXTINGUISHING EQUIPMENT

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

HALON: RULE 1418

FACILITY PERMIT TO OPERATE LOS ANGELES TIMES COMMUNICATIONS LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

REFRIGERANT: RULE 1415
REFRIGERANT: 40CFR 82 SUBPART F