



**FACILITY PERMIT TO OPERATE
CHEVRON PRODUCTS COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type	Emissions and Requirements	Conditions
Process 16: STORAGE TANKS					P13.1
System 10: DOMED EXTERNAL FLOATING ROOF TANK					S13.9
STORAGE TANK, DOMED EXTERNAL FLOATING ROOF, NO. 189, RIVETED SHELL, WITH EXTERNAL HEATING SYSTEM (STEAM HEAT SOURCE); 61790 BBL; DIAMETER: 115 FT; HEIGHT: 34 FT 6 IN, WITH DOMED COVER, GEODESIC FLOATING ROOF, PONTOON, WELDED PRIMARY SEAL, CATEGORY A, LIQUID MOUNTED, WIPER TYPE SECONDARY SEAL, CATEGORY A, RIM MOUNTED, WIPER TYPE GUIDEPOLE, SLOTTED, WITH GASKETED SLIDING COVER, POLE SLEEVE, AND POLE WIPER A/N 511145	D1364			BENZENE: (10) [40CFR61 Subpart FF_02, 12-4-2003]; HAP: (10) [40CFR 63 Subpart CC, #3A, 5-25-2001]	H23.1, K67.51, K171.13
STORAGE TANK, DOMED EXTERNAL FLOATING ROOF, NO. 458, RIVETED SHELL, 59300 BBL; DIAMETER: 115 FT; HEIGHT: 34 FT 7 IN, WITH DOMED COVER, GEODESIC FLOATING ROOF, PONTOON PRIMARY SEAL, CATEGORY A, METALLIC TYPE SECONDARY SEAL, CATEGORY A, RIM MOUNTED, WIPER TYPE GUIDEPOLE, UNSLOTTED, WITH GASKETED SLIDING COVER AND WIPER A/N 511146	D1381			BENZENE: (10) [40CFR61 Subpart FF_02, 12-4-2003]; HAP: (10) [40CFR 63 Subpart CC, #3A, 5-25-2001]	H23.1, K67.51, K171.13

* (1) Denotes RE CLAIM emission factor (2) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAP, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements
 ** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



FACILITY PERMIT TO OPERATE CHEVRON PRODUCTS COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

PROCESS CONDITIONS

P13.1 All devices under this process are subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Benzene	40CFR61,	SUBPART FF

[40CFR 61 Subpart FF, 12-4-2003]

[Processes subject to this condition: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16]

SYSTEM CONDITIONS:

S13.9 All devices under this system are subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	463
VOC	District Rule	1149
VOC	District Rule	1178

For Rule 463 applicability, only subdivision (d) in the March 11, 1994 amendment, or equivalent requirements in the future amendments, shall apply to domed external floating roof tanks. This does not preclude any requirements specified in Rule 1178.

[RULE 463, 5-6-2005; RULE 1149, 5-2-2008; RULE 1178, 4-7-2006]

[Systems subject to this condition : Process 16, System 10]

DEVICE CONDITIONS

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Benzene	40CFR61, Subpart	FF

[40CFR 61 Subpart FF, 12-4-2003]

[Devices subject to this condition: D1237, D1318, D1326, D1338, D1343, D1345, D1354, D1364, D1365, D1369, D1379, D1380, D1381, D1383, D1385, D1388, D1396, D1406, D1407, D1427, D1434, D2151, D3958]



FACILITY PERMIT TO OPERATE CHEVRON PRODUCTS COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.51 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Tank throughput in barrels.

Commodity/product stored and time period of its storage.

Actual vapor pressure, in psia, of each commodity/product stored.

Hydrocarbon concentration measurements done in the vapor space above the floating roof of the tank.

Other records that may be required to comply with the applicable requirements of District Rules 463(d), 1149, 1178, 40CFR 61 Subpart FF, and 40CFR 63 Subpart CC.

[RULE 1149, 5-2-2008; RULE 1178, 4-7-2006; RULE 463, 5-6-2005; 40CFR 61 Subpart FF, 12-4-2003; 40CFR 63 Subpart CC, 6-23-2003]

[Devices subject to this condition: D1364, D1380, D1381]

K171.13 The operator shall provide to the District the following items:

Final Drawings and/or specifications of the geodesic dome cover to be installed/constructed shall be submitted to the District within 30 days after its construction..

[RULE 1178, 4-7-2006]

[Devices subject to this condition: D1364, D1380, D1381, D1396]