



South Coast Air Quality Management District

21865 Copley Drive, Diamond Bar, CA 91765-4178
(909) 396-2000 • www.aqmd.gov

September 27, 2011

Mr. Glenn Stevens
EHS Officer
Kirkhill-TA Company (Facility ID 1744)
300 E. Cypress Street
Brea, CA 92821

Subject: Final Title V Renewal Permit

Dear Mr. Stevens:

Enclosed is your final Title V renewal permit that has been issued by the South Coast Air Quality Management District (AQMD) under Application No. 441900 for your facility located at 300 E. Cypress Street, Brea, CA 92821. This final Title V renewal permit became effective on August 25, 2011.

Please review all sections of your Title V renewal permit carefully and make sure that you comply with all requirements including, but not limited to, the monitoring, recordkeeping, and reporting requirements (i.e. semi-annual monitoring report, annual compliance certification report, etc.) specified in this Title V permit. All reporting forms can be downloaded from the AQMD website at <http://www.aqmd.gov/titlev/apply.html>.

Thank you for providing the necessary information that allowed the AQMD to complete the renewal of your Title V permit. If you have any questions, please contact Erwin dela Cruz at 909.396.2528

Sincerely,

A handwritten signature in black ink, appearing to read "Brian L. Yeh", is written over a faint, larger version of the same signature.

Brian L. Yeh
Senior Manager
Mechanical, Chemical, and Public Services

Enclosures

BLY:edd

FACILITY PERMIT TO OPERATE


**KIRKHILL - TA COMPANY
300 E CYPRESS ST
BREA, CA 92821**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER


By _____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	16	08/25/2011
B	RECLAIM Annual Emission Allocation	18	08/25/2011
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	12	08/25/2011
E	Administrative Conditions	8	08/25/2011
F	RECLAIM Monitoring and Source Testing Requirements	5	08/25/2011
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	5	08/25/2011
H	Permit To Construct and Temporary Permit to Operate	8	08/25/2011
I	Compliance Plans & Schedules	3	08/25/2011
J	Air Toxics	1	08/25/2011
K	Title V Administration	1	08/25/2011
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	2	08/25/2011
B	Rule Emission Limits	1	08/25/2011



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR: KIRKHILL - TA COMPANY

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION: 300 E CYPRESS ST
BREA, CA 92821

MAILING ADDRESS: 300 E CYPRESS ST
BREA, CA 92821-4097

RESPONSIBLE OFFICIAL: SCOTT CRAWFORD

TITLE: GENERAL MANAGER

TELEPHONE NUMBER: (714) 529-4901

CONTACT PERSON: TOM KILSBY

TITLE: FACILITY MANAGER

TELEPHONE NUMBER: (714) 529-4901

TITLE V PERMIT ISSUED: August 25, 2011

TITLE V PERMIT EXPIRATION DATE: August 24, 2016

TITLE V	RECLAIM
YES	NOx: YES
	SOx: NO
	CYCLE: 2
	ZONE: COASTAL



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NOx RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NOx emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Year Begin End (month/year)	Zone	NOx RTC Initially Allocated	NOx RTC ¹ Holding as of 08/25/2011 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
7/2008 6/2009	Coastal	3112	110	84
7/2009 6/2010	Coastal	3112	412	168
7/2010 6/2011	Coastal	3112	4196	252
7/2011 6/2012	Coastal	3112	2412	336
7/2012 6/2013	Coastal	3112	2412	336
7/2013 6/2014	Coastal	3112	2412	336
7/2014 6/2015	Coastal	3112	2412	336
7/2015 6/2016	Coastal	3112	2412	336
7/2016 6/2017	Coastal	3112	2412	336
7/2017 6/2018	Coastal	3112	2412	336
7/2018 6/2019	Coastal	3112	2412	336
7/2019 6/2020	Coastal	3112	2412	336
7/2020 6/2021	Coastal	3112	2412	336
7/2021 6/2022	Coastal	3112	2412	336
7/2022 6/2023	Coastal	3112	2412	336
7/2023 6/2024	Coastal	3112	2412	336
7/2024 6/2025	Coastal	3112	2412	336

Footnotes:

1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.
2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NOx RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NOx emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Year Begin End (month/year)	Zone	NOx RTC Initially Allocated	NOx RTC ¹ Holding as of 08/25/2011 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
7/2025 6/2026	Coastal	3112	2412	336

Footnotes:

1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.
2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. If the facility submits a permit application to increase in an annual allocation to a level greater than the facility's starting Allocation plus Non-Tradable credits as listed below, the application will be evaluated for compliance with Rule 2005 (c)(4). Rule 2005 (e) - Trading Zone Restrictions applies if an annual allocation is increased to a level greater than the facility's Starting Allocation plus Non-Tradable Credits:

Year		Zone	NOx RTC	Non-Tradable
Begin	End		Starting Allocation	Credits(NTC)
(month/year)			(pounds)	(pounds)
7/1994	6/1995	Coastal	4308	8132



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765




**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765





**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1: EXTERNAL COMBUSTION					
BOILER, NATURAL GAS, SUPERIOR, MODEL 4-X-2007-S150-M-LNDG-175, WITH LOW NOX BURNER, FLUE GAS RECIRCULATION, 17.5 MMBTU/HR WITH A/N: 223694 BURNER, LOW NOX, NATURAL GAS, INDUSTRIAL COMBUSTION, MODEL LNDG-175, WITH LOW NOX BURNER, 17.5 MMBTU/HR	D1		NOX: LARGE SOURCE**	CO: 400 PPMV (5) [RULE 1146, 11-17-2000; RULE 1146, 9-5-2008]; CO: 2000 PPMV (5A) [RULE 407, 4-2-1982]; NOX: 30 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; NOX: 30 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	D111.1, D328.1, E113.1
BOILER, NATURAL GAS, DIXON, MODEL SMWW, WITH LOW NOX BURNER, FLUE GAS RECIRCULATION, 18.9 MMBTU/HR WITH A/N: 260667 BURNER, LOW NOX, NATURAL GAS, INDUSTRIAL COMBUSTION, MODEL LNDG-210P, WITH LOW NOX BURNER, 18.9 MMBTU/HR	D2		NOX: LARGE SOURCE**	CO: 400 PPMV (5) [RULE 1146, 11-17-2000; RULE 1146, 9-5-2008]; CO: 2000 PPMV (5A) [RULE 407, 4-2-1982]; NOX: 37 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	D111.1, D328.1, E113.1
Process 2: RUBBER PRODUCTS MANUFACTURE					
System 1: CARBON BLACK UNLOADING AND CONVEYING SYSTEM					

* (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 2: RUBBER PRODUCTS MANUFACTURE					
BULK MATERIAL UNLOADING STATION, CARBON BLACK BAG DISCHARGER, 3 FT. 2 IN. W, 3 FT. 2 IN. L., 7 FT. H., FLEXICON, MODEL BFC. A/N: 484289	D130			PM: (9) [RULE 405, 2-7-1986]	C1.5, C1.6, D323.2
BULK MATERIAL UNLOADING STATION, FLOW FLEXER, PNEUMATIC BULK BAG AGITATOR, REGULATOR WITH GAUGE. A/N: 484289	D131			PM: (9) [RULE 405, 2-7-1986]	D323.2
BULK MATERIAL UNLOADING STATION, POWER CINCHER, BULK BAG FLOW CONTROL VALVE, FILTER & REGULATOR WITH GAUGE. A/N: 484289	D132			PM: (9) [RULE 405, 2-7-1986]	D323.2
BULK MATERIAL UNLOADING STATION, TELESCOPING TUBE WITH SPOUT-LOCK CLAMP RING, 9.0 IN. DIA., FLEXIBLE/CORRUGATED CYLINDRICAL SPOUT. A/N: 484289	D133	C136		PM: (9) [RULE 405, 2-7-1986]	D323.2, E57.2

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 - (3) Denotes RECLAIM concentration limit
 - (5) (5A) (5B) Denotes command and control emission limit
 - (7) Denotes NSR applicability limit
 - (9) See App B for Emission Limits
 - (2) (2A) (2B) Denotes RECLAIM emission rate
 - (4) Denotes BACT emission limit
 - (6) Denotes air toxic control rule limit
 - (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 - (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: RUBBER PRODUCTS MANUFACTURE					
HOPPER, FLOOR TYPE, 1 CU.FT. CAPACITY, 1 FT. 6 IN. W. X 1 FT. 6 IN. L. X 2 FT. 4 IN. H., FIXED LID WITH INLET PORT AND AGITATOR ASSEMBLY, ELECTRIC MOTOR, 0.5 HP. WITH A/N: 484289	D134	C100 C136		PM: (9) [RULE 405, 2-7-1986]	D323.2, E57.1
CONVEYOR, SCREW TYPE, FLEXICON BEV-CON, MODEL 1500, 4.5 IN. DIA. X 15 FT. L, GEAR, ASSEMBLY WITH 5 H.P MOTOR	D135			PM: (9) [RULE 405, 2-7-1986]	
BAGHOUSE, , FLEXICON, BAG-VAC, 2 FT. 4 IN. W. X 2 FT. 2 IN. L. X 5 FT. 3 IN. H., 50 SQ.FT, FILTER AREA, REVERSE PULSE JET CLEAN SYS., 0.5 HP BLOWER VENTING COLLAPSED BAGS A/N: 490668	C136	D133 D134		PM: (9) [RULE 404, 2-7-1986]	D12.5, D381.4, E102.1, K67.1
BULK MATERIAL LOAD/UNLOAD STATION, PORTABLE TOTE ASSEMBLY, CARBON BLACK, UNFLANGED INLET PORT AND VENT PORT. A/N: 484289	D137	C100		PM: (9) [RULE 405, 2-7-1986]	E57.1
CONVEYOR, , SCREW, CARBON BLACK A/N: 334271	D126	C24		PM: (9) [RULE 405, 2-7-1986]	D323.2
System 2: RUBBER CONVEYING AND MIXING SYSTEM					
MIXER, BOLLING, RUBBER A/N: 517155	D12	C100		PM: (9) [RULE 405, 2-7-1986]	B27.3, C1.9, D323.2

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 RUBBER PRODUCTS MANUFACTURE					
HOPPER, DUMP, 100 CU.FT. A/N: 517155	D13			PM: (9) [RULE 405, 2-7-1986]	D323.2
HOPPER, DUMP, 100 CU.FT. A/N: 517155	D14			PM: (9) [RULE 405, 2-7-1986]	D323.2
HOPPER, DUMP, 100 CU.FT. A/N: 517155	D15			PM: (9) [RULE 405, 2-7-1986]	D323.2
HOPPER, DUMP, 100 CU.FT. A/N: 517155	D16			PM: (9) [RULE 405, 2-7-1986]	D323.2
HOPPER, WEIGH A/N: 517155	D17			PM: (9) [RULE 405, 2-7-1986]	D323.2
BULK MATERIAL LOAD/UNLOAD STATION, FLO-BIN A/N: 517155	D18			PM: (9) [RULE 405, 2-7-1986]	D323.2
WEIGH STATION A/N: 517155	D19			PM: (9) [RULE 405, 2-7-1986]	D323.2
MILL, BLACK RUBBER, TWO ROLL A/N: 517157	D20	C100		PM: (9) [RULE 405, 2-7-1986]	B27.3, D323.2
MIXER, BANBURY MIXER NO. 3A, RUBBER A/N: 514870	D21	C139		PM: (9) [RULE 405, 2-7-1986]	B27.3, D323.2
MIXER, BANBURY MIXER NO. 11, RUBBER A/N: 10934W	D23	C24		PM: (9) [RULE 405, 2-7-1986]	D323.2
BAGHOUSE, PULVERIZING MACHINE CO., MODEL MIKRO-O-PULSAIR, 1131 SQ.FT. A/N: 334313	C24	D23 D126		PM: (9) [RULE 404, 2-7-1986]	D12.1, D381.2, E102.1, E160.1, H23.7
MILL, ROLL, SILICON RUBBER A/N: 514871	D25	C139		PM: (9) [RULE 405, 2-7-1986]	B27.3, D323.2

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 - (3) Denotes RECLAIM concentration limit
 - (5) (5A) (5B) Denotes command and control emission limit
 - (7) Denotes NSR applicability limit
 - (9) See App B for Emission Limits
 - (2) (2A) (2B) Denotes RECLAIM emission rate
 - (4) Denotes BACT emission limit
 - (6) Denotes air toxic control rule limit
 - (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 - (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 2: RUBBER PRODUCTS MANUFACTURE					
MILL, BLACK, NO. 2, PACIFIC MODEL NO. 48, SILICONE RUBBER, 4 FT-9 INCH W X 13 FT-10 INCH L X 5 FT-10 INCH H, 50 HP A/N: 514856	D138	C100		PM10: (9) [RULE 405, 2-7-1986]	B27.3, D323.2
BAGHOUSE, PULSE JET TYPE, 196 FILTERS, TOTAL FILTER AREA 3,079 SQ. FT., POLYESTER, MAC, MODEL 120-LST-196, WITH FABRIC FILTER A/N: 514857	C139	D21 D25 D141 D147 D149 D152		PM: (9) [RULE 404, 2-7-1986]	D12.1, D322.1, D381.2, E102.1, E160.1, H23.7, K67.1
MILL, ROLL, NO. 2,, SILICONE RUBBER, 6 FT-3 INCH W X 21 FT-4 INCH L X 6 FT-8 INCH H, 125 HP A/N: 514858	D152	C139		PM10: (9) [RULE 405, 2-7-1986]	B27.3, D323.2
MILL, ROLL, NO. 3,, SILICONE RUBBER, 4 FT-0 INCH W X 3 FT-8 INCH L X 5 FT-4.5 INCH H, 5 HP A/N: 514859	D141	C139		PM10: (9) [RULE 405, 2-7-1986]	B27.3, D323.2
MILL, ROLL, NO. 1, ERIE ENGINE & MANUFACTURING CO., CLEAN ROOM, SILICONE RUBBER, 6 FT-8 INCH W X 21 FT-6 INCH L X 5 FT-0 INCH H, 150 HP A/N: 514866	D147	C139		PM10: (9) [RULE 405, 2-7-1986]	B27.3, D323.2
MILL, ROLL, NO. 153, MODEL NO. 3760 BCD, SILICONE RUBBER, 8 FT-0 INCH W X 18 FT-10 INCH L X 5 FT-9 INCH H, 75 HP A/N: 514868	D149	C139		PM10: (9) [RULE 405, 2-7-1986]	B27.3, D323.2
System 3: RUBBER EXTRUDING AND CURING SYSTEM					
EXTRUDER A/N: 118013	D31			PM: (9) [RULE 405, 2-7-1986]	

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: RUBBER PRODUCTS MANUFACTURE					
OVEN, CURING, MICROWAVE, COBER, 18 KW A/N: 118013	D32	C35 C127			D323.2
OVEN, CURING, ELECTRIC, INFATROL, 60 KW A/N: 118013	D33	C35 C127			D323.2
CONVEYOR, BELT A/N: 118013	D34	C35 C127		PM: (9) [RULE 405, 2-7-1986]	D323.2
ELECTROSTATIC PRECIPITATOR, SMOG-HOG, MODEL SH-20-PE, 1.5 KW A/N: 118014	C35	D32 D33 D34 D36 C127		PM: (9) [RULE 404, 2-7-1986]	D323.1, E202.1, K67.3
COOLER, AIR COOLER A/N: 118014	D36	C35 C127		PM: (9) [RULE 405, 2-7-1986]	D323.1
OVEN, CURING, MICROWAVE, MONSANTO, 2.5 KVA A/N: 01445A	D37	C124			D323.2
OVEN, CURING, ELECTRIC, INFRATROL, 76 KVA A/N: 01445A	D38	C124			D323.2
CONVEYOR, BELT A/N: 01445A	D39	C124		PM: (9) [RULE 405, 2-7-1986]	D323.2
TANK, HEATED, RUBBER CURING, SALT, WIDTH: 1 FT ; HEIGHT: 1 FT ; LENGTH: 30 FT A/N: 273082	D42	C44			D323.2
TANK, HEATED, RUBBER CURING, SALT, WIDTH: 1 FT ; HEIGHT: 1 FT ; LENGTH: 40 FT A/N: 273082	D43	C44			D323.2
COOLER, EVAPORATIVE, ANDERSON 2000 INC. A/N: 386208	C44	D42 D43 C45			D323.2

- * (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5) (5A) (5B) Denotes RECLAIM command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 2: RUBBER PRODUCTS MANUFACTURE					
FILTER, FIBERGLASS, HIGH EFFICIENCY, ANDERSON 2000 INC., MODEL M-2.0-50 A/N: 386208	C45	C44 C46		PM: (9) [RULE 404, 2-7-1986]	D323.2, K67.1
MIST ELIMINATOR A/N: 386208	C46	C45			
ELECTROSTATIC PRECIPITATOR, SMOG HOG, MODEL SG-4 TANDEM A/N: 386207	C124	D37 D38 D39		PM: (9) [RULE 404, 2-7-1986]	D323.2, H23.7, K67.1
BLOWER, EXHAUST, 4,400 - 6,000 CFM, 5 H.P. A/N: 386207	C125				
ELECTROSTATIC PRECIPITATOR, UNITED AIR SPECIALISTS, SMOG HOG, MODEL SH-PE-40 A/N: 339583	C127	D32 D33 D34 C35 D36		PM: (9) [RULE 404, 2-7-1986]	D323.2, E202.1, H23.7, K67.1
ELECTROSTATIC PRECIPITATOR, UNITED AIR SPECIALISTS, SMOG-HOG, MODEL NO. SHN-40, 5 HP BLOWER A/N: 514872	C150	D142 D143 D144 D145 D146		PM: (9) [RULE 404, 2-7-1986]	D323.2, E202.1, H23.7, K67.1
System 4: RUBBER COATING SYSTEM					
SPRAY COATING OPERATION, WITH SPRAY BOOTH A/N: 517158	D50			PM: (9) [RULE 404, 2-7-1986]; ROG: (9) [RULE 1124, 9-21-2001; RULE 1145, 12-3-2004; RULE 1145, 12-4-2009; RULE 1171, 11-7-2003; RULE 1171, 5-1-2009]	A63.3, B59.2, C6.1, D322.1, E175.1, H23.1, H23.6, K67.1, K67.6
System 5: RUBBER CURING SYSTEM					
OVEN, CURING, ELECTRIC, DISPATCH, 224 KW A/N: 445544	D53	C129		PM: (9) [RULE 404, 2-7-1986]	C1.2, D323.2

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 RUBBER PRODUCTS MANUFACTURE					
OVEN, CURING, ELECTRIC, YOUNG BROTHERS, 90 KVA A/N: 04330A	D54	C61			C1.3, D323.2
OVEN, CURING, NATURAL GAS, K. J. CALLAHAN, 0.6 MMBTU/HR A/N: 06581A	D55	C61	NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	C1.3, D323.2
OVEN, CURING, ELECTRIC, GRIEVE-HENDRY, 40 KW A/N: 06582A	D56	C61			C1.3, D323.2
OVEN, CURING, NO. 7, NATURAL GAS, MILMETCO, 0.5 MMBTU/HR A/N: 09767A	D57	C61	NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	D323.2
OVEN, CURING, NO. 8, NATURAL GAS, CALLAHAN, 0.6 MMBTU/HR A/N: 09766A	D58	C61	NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	A63.2, D323.2
OVEN, CURING, NATURAL GAS, IMMERSOPAK BURNER, 0.33 MMBTU/HR A/N: 512745	D59	C61	NOX: PROCESS UNIT**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981]	B27.2, C1.7, C6.2, D12.6, D323.2, E57.3
SCRUBBER, WIDTH: 3 FT ; HEIGHT: 8 FT 3 IN; LENGTH: 7 FT A/N: 09881A	C61	D54 D55 D56 D57 D58 D59 C62 D128		PM: (9) [RULE 404, 2-7-1986]	H23.7, K67.4

- * (1) (1A) (1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5) (5A) (5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 2: RUBBER PRODUCTS MANUFACTURE					
MIST ELIMINATOR A/N: 09881A	C62	C61 C63			
MIST ELIMINATOR A/N: 09881A	C63	C62 C64			
ELECTROSTATIC PRECIPITATOR, INDUSTRIAL SPECIALISTS, INC., MODEL SMOG HOG MS-6-2T A/N: 09881A	C64	C63		PM: (9) [RULE 404, 2-7-1986]	D323.1, E202.1, H23.7, K67.3
OVEN, CURING, ELECTRIC, BLUE M, 23.8 KW A/N: 118015	D65	C66			C6.3, D323.1
ELECTROSTATIC PRECIPITATOR, UNITED AIR SPECIALISTS, MODEL SH-20-P.E. A/N: 138768	C66	D65		PM: (9) [RULE 404, 2-7-1986]	D323.1, E202.1, H23.7, K67.3
ELECTROSTATIC PRECIPITATOR, UNITED AIR SPECIALISTS, MODEL SH-20-P.E. A/N: 138769	C67	D68		PM: (9) [RULE 404, 2-7-1986]	D323.1, E202.1, H23.7, K67.3
OVEN, ELECTRIC, BLUE M, RUBBER CURING, 13.75 KVA A/N: 138769	D68	C67			D323.1
ELECTROSTATIC PRECIPITATOR, UNITED AIR SPECIALISTS, MODEL SH-20-P.E. A/N: 145364	C69	D70 D95 D96 D97		PM: (9) [RULE 404, 2-7-1986]	D323.1, E202.1, H23.7, K67.3
OVEN, CURING, ELECTRIC, RUBBER CURING, 28 KW A/N: 145364	D70	C69			D323.1
PRESS, NO. 1, SPONGE RUBBER CURING, STEAM HEATED A/N: 202578	D71				

* (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: RUBBER PRODUCTS MANUFACTURE					
PRESS, NO. 2, SPONGE RUBBER CURING, STEAM HEATED A/N: 202577	D72				
PRESS, NO. 77, SPONGE RUBBER CURING, STEAM HEATED A/N: 202564	D73				
PRESS, NO. 88, SPONGE RUBBER CURING, STEAM HEATED A/N: 202561	D74				
PRESS, NO. 96, SPONGE RUBBER CURING, STEAM HEATED A/N: 202563	D75				
PRESS, NO. 98, SPONGE RUBBER CURING, STEAM HEATED A/N: 202562	D76				
PRESS, NO. 106, SPONGE RUBBER CURING, STEAM HEATED A/N: 202579	D77				
PRESS, NO. 35, MECHANICAL SPONGE RUBBER CURING, STEAM HEATED A/N: 202582	D79				
PRESS, NO. 36, MECHANICAL SPONGE RUBBER CURING, STEAM HEATED A/N: 202584	D80				
PRESS, NO. 97, MECHANICAL SPONGE RUBBER CURING, STEAM HEATED A/N: 202591	D83				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 RUBBER PRODUCTS MANUFACTURE					
PRESS, NO. 99, MECHANICAL SPONGE RUBBER CURING, STEAM HEATED A/N: 202593	D84				
PRESS, NO. SP11, MECHANICAL SPONGE RUBBER CURING, STEAM HEATED A/N: 202594	D85				
PRESS, NO. 109, MECHANICAL SPONGE RUBBER CURING, STEAM HEATED A/N: 202595	D86				
PRESS, NO. SP19, SPONGE RUBBER CURING, STEAM HEATED A/N: 202596	D87				
PRESS, NO. SP20, SPONGE RUBBER CURING, STEAM HEATED A/N: 202599	D88				
PRESS, NO. 104, SPONGE RUBBER CURING, STEAM HEATED A/N: 202600	D89				
OVEN, CURING, ELECTRIC, 18 KW A/N: 145364	D95	C69			D323.1
OVEN, CURING, ELECTRIC, 11.5 KW A/N: 145364	D96	C69			D323.1
OVEN, CURING, ELECTRIC, 1 KW A/N: 145364	D97	C69			D323.1
PRESS, NO. SP23, SPONGE RUBBER CURING, STEAM HEATED A/N: 202602	D99				

- * (1) (1A) (1B) Denotes RECLAIM emission factor
 - (3) Denotes RECLAIM concentration limit
 - (5) (5A) (5B) Denotes command and control emission limit
 - (7) Denotes NSR applicability limit
 - (9) See App B for Emission Limits
 - (2) (2A) (2B) Denotes RECLAIM emission rate
 - (4) Denotes BACT emission limit
 - (6) Denotes air toxic control rule limit
 - (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 - (10) See section J for NESHAP/MACT requirements
- ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2: RUBBER PRODUCTS MANUFACTURE					
OVEN, CURING, DESPATCH, ELECTRIC, MODEL PSC3-24, SERIAL NO. 11109, 51KW. A/N: 436876	D128	C61			C1.3, D323.2
ELECTROSTATIC PRECIPITATOR, , UNITED AIR SPECIALISTS, SMOG-HOG, MODEL SH-40-PE-S A/N: 432258	C129	D53		PM: (9) [RULE 404, 10-5-1979]	D323.1, E202.1, H23.7, K67.1
OVEN, CURING, ELECTRIC, MODEL NO. E 4006-6, 18 KW A/N: 514860	D142	C150			B27.1, C1.10, D323.2
OVEN, CURING, ELECTRIC, MODEL NO. E 4006-6, 18 KW. A/N: 514861	D143	C150			B27.1, C1.10, D323.2
OVEN, CURING, ELECTRIC, MODEL NO. E 4006-6, 12 KW. A/N: 514863	D144	C150			B27.1, C1.10, D323.2
OVEN, CURING, ELECTRIC, MODEL NO. E 4004-4, 4 KW. A/N: 514864	D145	C150			B27.1, C1.10, D323.2
OVEN, CURING, ELECTRIC, MODEL NO. E 4004-4, 8 KW. A/N: 514865	D146	C150			B27.1, C1.10, D323.2
System 6: AIR POLLUTION CONTROL SYSTEM					
BAGHOUSE, PULSE JET CLEANING SYS., FARR, MODEL 50 TENKAY CARTRIDGE TYPE, BAG LEAK DETECTION SYSTEM, GOYEN, MODEL BBD5, WITH 25 HP. BLOWER, 10000 SQ.FT.; 50 CARTRIDGE A/N: 514869	C100	D12 D20 D134 D137 D138		PM: (9) [RULE 404, 2-7-1986]	D12.1, D322.1, D381.2, E102.1, E160.1, H23.7, K67.1
Process 3: Rule 219 Exempt Equipment Subject to Source-Specific Requirements					

- * (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
- (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
- (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
- (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 3 - Rule 219 Exempt Equipment Subject to Source Specific Requirements					
System 1 - RULE 219 EXEMPT EQUIPMENT					
RULE 219 EXEMPT EQUIPMENT, SPRAY COATING EQUIPMENT, EDUCATIONAL, AND ANY DRYERS AND CONTROL ENCLOSURES	E103			ROG: (9) [RULE 1145, 2-14-1997; RULE 1171, 6-13-1997; RULE 1171, 10-8-1999]	
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS	E104			ROG: (9) [RULE 1113, 11-8-1996; RULE 1113, 5-14-1999; RULE 1171, 6-13-1997; RULE 1171, 10-8-1999]	K67.2
RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING, SHOT BLAST, RUBBER/PLASTIC REMOVAL, AND CONTROL EQUIPMENT	E105			PM: (9) [RULE 1140, 8-2-1985; RULE 404, 2-7-1986; RULE 405, 2-7-1986]	D381.2, E102.1, K67.1
RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, GLOVE-BOX, <= 53 FT3, WITH DUST FILTER	E106			PM: (9) [RULE 1140, 8-2-1985; RULE 404, 2-7-1986; RULE 405, 2-7-1986]	D381.2, E102.1, K67.1
RULE 219 EXEMPT EQUIPMENT, OIL WATER SEPARATORS, GRAVITY-TYPE, < 45 FT2 AIR/LIQUID INTERFACIAL AREA	E107				H23.2
RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, WET, AND ANY CONTROL EQUIPMENT	E108			PM: (9) [RULE 1140, 8-2-1985; RULE 405, 2-7-1986]	D323.1
RULE 219 EXEMPT EQUIPMENT, PRINTING EQUIPMENT, WITH RELATED COATING, LAMINATING AND DRYING EQUIPMENT	E109			ROG: (9) [RULE 1130, 3-8-1996; RULE 1130, 10-8-1999; RULE 1171, 6-13-1997; RULE 1171, 10-8-1999]	
RULE 219 EXEMPT EQUIPMENT, REFRIGERATION UNITS	E110				H23.3

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 3 Rule 219 Exempt Equipment Subject to Source-Specific Requirements					
RULE 219 EXEMPT EQUIPMENT, PRESSES, RAM DIA < 26 IN., TEMP. < 400 DEG. F.	E153				

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D1	1	1	0
D2	1	1	0
D12	3	2	2
D13	4	2	2
D14	4	2	2
D15	4	2	2
D16	4	2	2
D17	4	2	2
D18	4	2	2
D19	4	2	2
D20	4	2	2
D21	4	2	2
D23	4	2	2
C24	4	2	2
D25	4	2	2
D31	5	2	3
D32	6	2	3
D33	6	2	3
D34	6	2	3
C35	6	2	3
D36	6	2	3
D37	6	2	3
D38	6	2	3
D39	6	2	3
D42	6	2	3
D43	6	2	3
C44	6	2	3
C45	7	2	3
C46	7	2	3
D50	7	2	4
D53	7	2	5
D54	8	2	5
D55	8	2	5
D56	8	2	5
D57	8	2	5



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
D58	8	2	5
D59	8	2	5
C61	8	2	5
C62	9	2	5
C63	9	2	5
C64	9	2	5
D65	9	2	5
C66	9	2	5
C67	9	2	5
D68	9	2	5
C69	9	2	5
D70	9	2	5
D71	9	2	5
D72	10	2	5
D73	10	2	5
D74	10	2	5
D75	10	2	5
D76	10	2	5
D77	10	2	5
D79	10	2	5
D80	10	2	5
D83	10	2	5
D84	11	2	5
D85	11	2	5
D86	11	2	5
D87	11	2	5
D88	11	2	5
D89	11	2	5
D95	11	2	5
D96	11	2	5
D97	11	2	5
D99	11	2	5
C100	12	2	6
E103	13	3	1
E104	13	3	1

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY
SECTION D: DEVICE ID INDEX

Device Index For Section D			
Device ID	Section D Page No.	Process	System
E105	13	3	1
E106	13	3	1
E107	13	3	1
E108	13	3	1
E109	13	3	1
E110	13	3	1
C124	7	2	3
C125	7	2	3
D126	3	2	1
C127	7	2	3
D128	12	2	5
C129	12	2	5
D130	2	2	1
D131	2	2	1
D132	2	2	1
D133	2	2	1
D134	3	2	1
D135	3	2	1
C136	3	2	1
D137	3	2	1
D138	5	2	2
C139	5	2	2
D141	5	2	2
D142	12	2	5
D143	12	2	5
D144	12	2	5
D145	12	2	5
D146	12	2	5
D147	5	2	2
D149	5	2	2
C150	7	2	3
D152	5	2	2
E153	14	3	1



FACILITY PERMIT TO OPERATE KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F1.1 The operator shall limit the material processed to no more than 855,500 lb(s) in any one month.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

For the purpose of this condition, material processed shall be defined as all material processed through equipment vented to air pollution control device C100.

For the purpose of this condition, equipment vented to air pollution control device C100 shall be defined as Devices D12, D20, D134, D137 and D138.

F1.2 The operator shall limit the material processed to no more than 284,507 lb(s) in any one month.

The operator shall maintain records in a manner approved by the District to demonstrate compliance with this condition.

For the purpose of this condition, material processed shall be defined as all material processed through equipment vented to air pollution control device C139.

For the purpose of this condition, equipment vented to air pollution control device C139 shall be defined as Devices D21, D25, D141, D147, D149 and D152.

DEVICE CONDITIONS

A. Emission Limits

A63.2 The operator shall limit emissions from this equipment as follows:



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

CONTAMINANT	EMISSIONS LIMIT
ROG	Less than or equal to 0.1 LBS IN ANY ONE DAY
CO	Less than or equal to 0.48 LBS IN ANY ONE DAY
PM	Less than or equal to 0.1 LBS IN ANY ONE DAY
SOX	Less than or equal to 0.011 LBS IN ANY ONE DAY

[RULE 109, 5-2-2003; RULE 1124, 9-21-2001; RULE 1145, 12-4-2009; RULE 442, 12-15-2000; RULE 481, 1-11-2002]

[Devices subject to this condition : D58]

A63.3 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT	AMOUNT	TIME SPAN
ROG	Less than or equal to	202	LBS IN ANY 30-DAY PERIOD

For the purposes of this condition, ROG shall be defined as less water and exempt solvent.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D50]

B. Material/Fuel Type Limits

B27.1 The operator shall not use materials containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401, as amended 06/05/2009.



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D142, D143, D144, D145, D146]

B27.2 The operator shall not use materials containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401 (except for those compounds listed below), as amended 06/05/2009.

COMPOUND	CAS NO.
Acrylonitrile	107-13-1
Bis(2-ethylhexyl)phthalate	117-81-7
Cadmium and cadmium compounds	7440-43-9
Carbon tetrachloride	56-23-5
Ethylene thiourea	96-45-7
Lead chromate	7758-97-6
Lead and lead compounds	7439-92-1

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D59]

B27.3 The operator shall not use materials containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401 (except for those compounds listed below), as amended 09/10/2010.

COMPOUND	CAS NO.
Acrylonitrile	107-13-1
Arsenic	7440-38-2



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Bis(2-chloroethyl)phthalate (DEHP)	117-81-7
Cadmium and Cadmium Compounds	7440-43-9
Carbon Tetrachloride	56-23-5
Chloroprene	126-99-8
Ethylene Thiourea	96-45-7
Lead and Lead Compounds	7439-92-1
Lead Chromate	7758-97-6
Nickel and Nickel Compounds	7440-02-0
Zinc and Zinc Compounds	7440-66-6

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D12, D20, D21, D25, D138, D141, D147, D149, D152]

B59.2 The operator shall not use the following material(s) in this device :

photochemically reactive organic solvents and/or coatings containing
photochemically reactive organic solvents

[RULE 442, 12-15-2000]

[Devices subject to this condition : D50]

C. Throughput or Operating Parameter Limits



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.2 The operator shall limit the material processed to no more than 4800 lb(s) in any one day.

For the purpose of this condition, material processed shall be defined as total quantity of all materials processed in this oven.

[RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D53]

C1.3 The operator shall limit the material processed to no more than 4000 lb(s) in any one day.

For the purpose of this condition, material processed shall be defined as total quantity of rubber processed in this equipment.

[RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D54, D55, D56, D128]

C1.5 The operator shall limit the material processed to no more than 20,000 lb(s) in any one day.

The operator shall maintain adequate records to verify compliance with this condition. Such records shall be kept on the premises for at least two years and be made available to the executive officer or his representative upon request.

Materials processed in this equipment shall not contain any compounds identified as carcinogenic or toxic air contaminants in Rule 1401, as amended March 4, 2005.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 9-10-2010]



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D130]

- C1.6 The operator shall limit the material processed to no more than 168,000 lb(s) in any one month.

The operator shall maintain adequate records to verify compliance with this condition. Such records shall be kept on the premises for at least two years and be made available to the executive officer or his representative upon request.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D130]

- C1.7 The operator shall limit the fuel usage to no more than 7,550 cubic feet in any one day.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D59]

- C1.9 The operator shall limit the material processed to no more than 22,222 lb(s) in any one day.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D12]

- C1.10 The operator shall limit the material processed to no more than 340 lb(s) in any one day.

This limit shall be based on the total combined limit for equipment D142, D143, D144, D145, D146.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D142, D143, D144, D145, D146]

- C6.1 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 0.25 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the filter.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D50]

- C6.2 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 450 Deg F.

The operator shall automatically regulate the temperature by a fully modulated control system.

To comply with this condition, the operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature of the oven.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D59]

- C6.3 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 600 Deg F.

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall automatically regulate the temperature by a fully modulated control system.

To comply with this condition, the operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature of the oven.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D65]

D. Monitoring/Testing Requirements

D12.1 The operator shall install and maintain a(n) pressure gauge to accurately indicate the differential pressure across the filter.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C24, C100, C139]

D12.5 The operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the filter.

The pressure drop across the filter shall not exceed 3 inches of water column.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C136]

D12.6 The operator shall install and maintain a(n) non-resettable totalizing fuel flow meter to accurately indicate the fuel usage in the curing oven.



FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall also install and maintain a device to continuously record the parameter being measured.

The operator shall maintain adequate records to verify the gas usage once a day. Such records shall be kept on the premises for at least two years and be made available to the executive officer or his representative upon request.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D59]

D111.1 The operator shall comply with the tune-up requirements of Rule 1146. Records shall be maintained for the date of each tune-up, the company performing the tune-up, and the tune-up results for NOX, CO and O2.

[RULE 1146, 11-17-2000; RULE 1146, 9-5-2008]

[Devices subject to this condition : D1, D2]

D322.1 The operator shall perform a weekly inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D50, C100, C139]

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C35, D36, C64, D65, C66, C67, D68, C69, D70,
D95, D96, D97, E108, C129]

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D12, D13, D14, D15, D16, D17, D18, D19, D20, D21, D23, D25, D32, D33, D34, D37, D38, D39, D42, D43, C44, C45, D53, D54, D55, D56, D57, D58, D59, C124, D126, C127, D128, D130, D131, D132, D133, D134, D138, D141, D142, D143, D144, D145, D146, D147, D149, C150, D152]

D328.1 The operator shall determine compliance with the CO emission limit(s) either: (a) conducting a source test at least once every five years using AQMD Method 100.1 or 10.1; or (b) conducting a test at least annually using a portable analyzer and AQMD-approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with Rule 1146 concentration limit. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D1, D2]

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D381.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C24, C100, E105, E106, C139]



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D381.4 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C136]

E. Equipment Operation/Construction Requirements

E57.1 The operator shall vent this equipment to the baghouse whenever it is in operation.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D134, D137]

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E57.2 The operator shall vent this equipment to the integrated Bag-Vac baghouse whenever the carbon black bags are fully discharged.

The Bag-Vac baghouse shall fully vent each bag containing carbon black powder material to ensure complete collection of residual powder material prior to the collapse and removal of the bag.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D133]

E57.3 The operator shall vent this equipment to the scrubber system whenever it is in operation.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D59]

E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C24, C100, E105, E106, C136, C139]

E113.1 The operator shall have the burner equipped with a control system to automatically regulate the combustion air, fuel and, if applicable, recirculated flue gas as the boiler load varies. This control system shall be adjusted and tuned at least twice a year according to the manufacturer's specifications to maintain its ability to repeat the same performance at the same firing rate.

[RULE 1146, 11-17-2000; RULE 1146, 9-5-2008]



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D1, D2]

E160.1 The operator shall clean the filters whenever the static differential pressure across the bags is 4 inches water column or greater.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C24, C100, C139]

E175.1 The operator shall not use this equipment unless all exhaust air passes through the following:

filter media at least 2 inches thick

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D50]

E202.1 The operator shall clean and maintain this equipment according to the following specifications:

Clean at least once every 3 months

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C35, C64, C66, C67, C69, C127, C129, C150]

H. Applicable Rules

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	109
VOC	District Rule	442
PM	District Rule	481
VOC	District Rule	1124
VOC	District Rule	1145

[RULE 109, 5-2-2003; RULE 1124, 9-21-2001; RULE 1145, 2-14-1997; RULE 1145, 12-4-2009; RULE 442, 12-15-2000; RULE 481, 1-11-2002]

[Devices subject to this condition : D50]

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	464

[RULE 464, 12-7-1990]

[Devices subject to this condition : E107]

H23.3 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Refrigerants	District Rule	1415



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1415, 12-3-2010]

[Devices subject to this condition : E110]

H23.6 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	109
PM	District Rule	481

[RULE 109, 5-2-2003; RULE 481, 1-11-2002]

[Devices subject to this condition : D50]

H23.7 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
PM	District Rule	1155

[RULE 1155, 12-4-2009]

[Devices subject to this condition : C24, C61, C64, C66, C67, C69, C100, C124, C127, C129, C139, C150]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The name of the person performing the inspection and/or maintenance of the filter media

The date, time, and results of the inspection

The date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C45, D50, C100, E105, E106, C124, C127, C129, C136, C139, C150]

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : E104]

K67.3 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Quarterly cleaning and maintenance

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C35, C64, C66, C67, C69]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Daily flow rate of scrubbing water

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C61]

K67.6 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):



Daily record of pressure drop across the filter media

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D50]



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765





FACILITY PERMIT TO OPERATE KIRKHILL - TA COMPANY

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations or statutes of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]



FACILITY PERMIT TO OPERATE
~~KIRKHILL - TA COMPANY~~

SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation.[204]
6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least: [204]
 - a. Three years for a facility not subject to Title V; or
 - b. Five years for a facility subject to Title V.
7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134, 204]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For a large NO_x source, compliance with a RECLAIM concentration limit shall be measured over a continuous 60 minutes for that source; [2012]
 - d. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes. [204]



FACILITY PERMIT TO OPERATE KIRKHILL - TA COMPANY

SECTION E: ADMINISTRATIVE CONDITIONS

- e. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compound which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO₂) and be averaged over 15 consecutive minutes; [407]
- f. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent carbon dioxide (CO₂) at standard conditions and averaged over 15 consecutive minutes. [409]
- g. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O₂) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]
8. All equipment operating under the RECLAIM program shall comply concurrently with all provisions of AQMD Rules and Regulation, except those listed in Table 1 of Rule 2001 for NO_x RECLAIM sources and Table 2 of Rule 2001 for SO_x RECLAIM sources. Those provisions listed in Tables 1 or 2 shall not apply to NO_x or SO_x emissions after the date the facility has demonstrated compliance with all monitoring and reporting requirements of Rules 2011 or 2012, as applicable. Provisions of the listed AQMD rules in Tables 1 or 2 which have initial implementation dates in 1994 shall not apply to a RECLAIM NO_x or SO_x source, respectively. [2001]
9. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
 - a. Brief description of the equipment tested.



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION E: ADMINISTRATIVE CONDITIONS

- b. Brief process description, including maximum and normal operating temperatures, pressures, through-put, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts/stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (no conflict of interest).
10. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD Rules or equipment-specific conditions. The report shall contain the following information: [204]
- a. The results of the source test.
 - b. Brief description of the equipment tested.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts/stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Field and laboratory data forms, strip charts and analyses.




**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION E: ADMINISTRATIVE CONDITIONS

- f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
- 11. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]
- 12. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765





**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

The Facility shall comply with all applicable monitoring and source testing requirements in Regulation XX. These requirements may include but are not limited to the following:

I. NOx Monitoring Conditions

A. The Operator of a NOx Major Source, as defined in Rule 2012, shall, as applicable:

Not Applicable

B. The Operator of a NOx large Source, as defined in Rule 2012, shall, as applicable:

1. Install, maintain, and operate a totalizing fuel meter and any device specified by the Executive Officer as necessary to determine monthly fuel usage or other applicable variables specified in Rule 2012, Appendix A, Table 3-A. The sharing of totalizing fuel meter may be allowed by the Executive Officer if the fuel meter serves large sources which have the same emission factor, concentration limit, or emission rate. The sharing of totalizing fuel meters shall not be allowed for large sources which are required to comply with an annual heat input limit. [2012]
2. Comply at all times with the specified NOx concentration limit in PPM measured over any continuous 60 minutes for that source or establish an equipment-specific emission rate that is reliable, accurate, representative of that sources emissions, and in accordance with the requirements specified in Rule 2012, Appendix A, Chapter 5. [2012]

C. The Operator of a NOx Process Unit, as defined in Rule 2012, shall, as applicable:

1. Install, maintain, and operate a totalizing fuel meter or any device approved by the Executive Officer to measure quarterly fuel usage or other applicable variables specified in Rule 2012, Table 2012-1, and Rule 2012, Appendix A, Table 4-A. The sharing of totalizing fuel meters may be allowed by the Executive Officer if the fuel meter serves process units which have the same emission factor or emission rate. The sharing of totalizing meter shall not be allowed for process units which are required to comply with an annual heat input limit. [2012]



FACILITY PERMIT TO OPERATE
~~KIRKHILL - TA COMPANY~~

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

II. NO_x Source Testing and Tune-up conditions

1. The operator shall conduct all required NO_x source testing in compliance with an AQMD-approved source test protocol. [2012]
2. The operator shall, as applicable, conduct source tests for every large NO_x source no later than June 30, 1997 and every 3 years thereafter. The source test shall include the determination of NO_x concentration and a relative accuracy audit of the exhaust stack flow determination (e.g. in-stack flow monitor or fuel flow monitor based F-factor calculation). Such source test results shall be submitted per the schedule described by APEP. In lieu of submitting the first source test report, the facility permit holder may submit the results of a source test not more than 3 years old which meets the requirements when conducted. [2012]
3. All NO_x large sources and NO_x process units shall be tuned-up in accordance with the schedule specified in Rule 2012, Appendix A, Chapter 5, Table 5-B. [2012]



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR
RECLAIM SOURCES**

The Facility shall comply with all applicable reporting and recordkeeping requirements in Regulation XX. These requirements may include but are not limited to the following:

I. Recordkeeping Requirements for all RECLAIM Sources

1. The operator shall maintain all monitoring data required to be measured or reported pursuant to Rule 2011 and Rule 2012, whichever is applicable. All records shall be made available to AQMD staff upon request and be maintained for at least:
 - a. Three years after each APEP report is submitted to AQMD for a facility not subject to Title V, unless a different time period is required in Rule 2011 or Rule 2012 [2011 & 2012]; or
 - b. Five years after each APEP report is submitted to AQMD for a facility subject to Title V. [3004(a)(4)(E)]
 - c. Notwithstanding the above, all data gathered or computed for intervals of less than 15 minutes shall only be maintained a minimum of 48 hours. [2011 & 2012]
2. The operator shall store on site and make available to the Executive Officer upon request: records used to determine emissions, maintenance records, sources test reports, relative accuracy test audit reports, relative accuracy audit reports and fuel meter calibration records. [2011 & 2012]

II. Reporting Requirements for all RECLAIM Sources

1. The operator shall submit a quarterly certification of emissions including the facility's total NOx or SOx emissions, whichever is applicable, for the quarter within 30 days after the end of the first three quarters and 60 days after the end of the fourth quarter of a compliance year. [2011 & 2012]

NOx Reporting Requirements

A. The Operator of a NOx Major Source, as defined in Rule 2012, shall, as applicable:

Not Applicable



FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

**SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR
RECLAIM SOURCES**

B. The Operator of a NOx Large Source, as defined in Rule 2012, shall:

1. Install, maintain and operate a modem or any reporting device approved by the Executive Officer to report, to the AQMD, the total monthly NOx mass emissions from each large NOx source. The Operator shall comply with this requirement within 12 months of the date of entry to the RECLAIM Program. Such data shall be reported within 15 days after the end of each calendar month. [2012]

C. The Operator of a NOx Process Unit, as defined in Rule 2012, shall:

1. Electronically report the calculated quarterly NOx emissions for each NOx process unit. The Operator shall comply with this requirement within 12 months of the date of entry to the RECLAIM Program. [2012]



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765

Section H	Page: 1
Facility ID:	001744
Revision #:	8
Date:	August 25, 2011

FACILITY PERMIT TO OPERATE
~~KIRKHILL - TA COMPANY~~

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

NONE

FACILITY PERMIT TO OPERATE
~~KIRKHILL - TA COMPANY~~

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765

Section J	Page: 1
Facility ID:	001744
Revision #:	1
Date:	August 25, 2011

FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY

SECTION J: AIR TOXICS

NOT APPLICABLE



**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
- (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]



FACILITY PERMIT TO OPERATE KIRKHILL - TA COMPANY

SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**SECTION K: TITLE V Administration
RECORDKEEPING PROVISIONS**

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:

- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
- (B) The date(s) analyses were performed;
- (C) The company or entity that performed the analyses;
- (D) The analytical techniques or methods used;
- (E) The results of such analyses; and
- (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]

20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]

21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:

- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.



FACILITY PERMIT TO OPERATE KIRK HILL - TA COMPANY

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]



FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	7-13-2007	Non federally enforceable
RULE 1124	9-21-2001	Federally enforceable
RULE 1130	10-8-1999	Federally enforceable
RULE 1140	2-1-1980	Federally enforceable
RULE 1140	8-2-1985	Non federally enforceable
RULE 1145	12-3-2004	Non federally enforceable
RULE 1145	12-4-2009	Non federally enforceable
RULE 1145	2-14-1997	Federally enforceable
RULE 1146	11-17-2000	Federally enforceable
RULE 1146	9-5-2008	Non federally enforceable
RULE 1155	12-4-2009	Non federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	9-10-2010	Non federally enforceable
RULE 1415	12-3-2010	Non federally enforceable

FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 2012	5-6-2005	Federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 2202	11-8-1996	Non federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	1-14-1982	Non federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 464	12-7-1990	Federally enforceable
RULE 481	1-11-2002	Federally enforceable
RULE 701	6-13-1997	Federally enforceable





FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN PERMIT PURSUANT TO RULE 219

1. HOT WATER BOILER, NATURAL GAS
2. I.C. ENGINE, GASOLINE
3. STEAM CLEANER, KEROSENE
4. EXTRUSION EQUIPMENT
5. SPACE HEATERS, NATURAL GAS

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765





**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-08-1996]**

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

**Grams of VOC Per Liter of Coating,
Less Water And Less Exempt Compounds**

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers	350						
Clear Wood Finishes							
Varnish	350						
Sanding Sealers	350						
Lacquer	680		550			275	
Concrete-Curing Compounds	350						
Dry-Fog Coatings	400						
Fire-proofing Exterior Coatings	350	450		350			
Fire-Retardant Coatings							
Clear	650						
Pigmented	350						
Flats	250				100		50
Graphic Arts (Sign) Coatings	500						

**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-08-1996]**

Industrial Maintenance						
Primers and Topcoats						
Alkyds	420					
Catalyzed Epoxy	420					
Bituminous Coatings	420					
Materials						
Inorganic Polymers	420					
Vinyl Chloride Polymers	420					
Chlorinated Rubber	420					
Acrylic Polymers	420					
Urethane Polymers	420					
Silicones	420					
Unique Vehicles	420					
Japans/Faux Finishing	350	700		350		
Coatings						
Magnesite Cement Coatings	600			450		
Mastic Coatings	300					
Metallic Pigmented Coatings	500					
Multi-Color Coatings	420		250			
Pigmented Lacquer	680		550			
Pre-Treatment Wash Primers	780				275	
Primers, Sealers, and	350					
Undercoaters						
Quick-Dry Enamels	400					
Roof Coatings	300					
Shellac						
Clear	730					
Pigmented	550					
Stains	350					
Swimming Pool Coatings						
Repair	650					
Other	340					
Traffic Coatings	250		150			
Waterproofing Sealers	400					
Wood Preservatives						
Below-Ground	350					
Other	350					

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120



FACILITY PERMIT TO OPERATE KIRKHILL - TA COMPANY

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 05-14-1999]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6) of Rule 1113, the operator shall not supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, the operator shall not supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings for residential use; or of any rust-preventative coating for industrial use.

**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 05-14-1999]
TABLE OF STANDARDS
VOC LIMITS**

**Grams of VOC Per Liter of Coating,
Less Water And Less Exempt Compounds**

COATING	Limit*	Effective 1/1/1998	Effective 1/1/1999	Effective 5/14/99	Effective 7/1/2001	Effective 7/1/2002	Effective 1/1/2005	Effective 7/1/2006	Effective 7/1/2008
Bond Breakers	350								
Chemical Storage Tank Coatings	420							100	
Clear Wood Finishes									
Varnish	350								
Sanding Sealers	350								
Lacquer	680	550					275		
Concrete-Curing Compounds	350								
Dry-Fog Coatings	400								
Essential Public Service Coating	420					340		100	
Fire-proofing Exterior Coatings	450		350						
Fire-Retardant Coatings									
Clear	650								
Pigmented	350								
Flats	250				100				50
Floor Coatings	420					100		50	
Graphic Arts (Sign) Coatings	500								
High Temperature Industrial Maintenance Coatings						550		420	
Industrial Maintenance Coatings	420					250		100	
Japans/Faux Finishing Coatings	700		350						
Magnesite Cement Coatings	600		450						
Mastic Coatings	300								
Metallic Pigmented Coatings	500								
Multi-Color Coatings	420	250							
Non-Flat Coatings	250					150		50	
Pigmented Lacquer	680	550					275		
Pre-Treatment Wash Primers	780								
Primers, Sealers, and Undercoaters	350					200		100	
Quick-Dry Enamels	400					250		50	



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 05-14-1999]**

Quick-Dry Primers, Sealers, and Undercoaters	350**					200		100	
Recycled Coatings				250		250		100	
Roof Coatings	300			250					
Bituminous Roof Coatings	300					250			
Rust Preventative Coatings	420			400				100	
Shellac									
Clear	730								
Pigmented	550								
Specialty Primers	350							100	
Stains	350					250			
Swimming Pool Coatings									
Repair	650								
Other	340								
Traffic Coatings	250	150							
Waterproofing Sealers									
Wood	400					250			
Concrete/Masonry	400								
Wood Preservatives									
Below-Ground	350								
Other	350								

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

** The specified limit applies unless the manufacturer submits a report pursuant to Rule 1113(g)(2).

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120



FACILITY PERMIT TO OPERATE KIRKHILL - TA COMPANY

APPENDIX B: RULE EMISSION LIMITS [RULE 1124 09-21-2001]

Except as otherwise provided in Rule 1124

- (1) VOC Content of Aerospace Materials
- (A) A person shall not apply to aerospace components any materials, including any VOC-containing materials added to the original material supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC Limit			
Grams of VOC per Liter, Less Water and Less Exempt Compounds			
Primers	Current VOC Limit	VOC Limit Effective 1-1-03	VOC Limit Effective 1-1-05
General Primer	350	350	350
Low-Solids Corrosion Resistant Primer	350	350	350
Pretreatment Primer	780	780	780
Rain Erosion-Resistant Coating Compatible Primer	850	850	850
Adhesion Promoter	850	850	250
Adhesive Bonding Primer			
New Commercial Aircraft	805	250	250
All Military Aircraft	805	805	805
Remanufactured Commercial Aircraft Parts	805	805	805
Sonic and Acoustic Applications	805	805	805
Adhesive Bonding Primer			
Long Term	250	250	250
Short Term	250	250	250



**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1124 09-21-2001]**

Coatings	Current VOC Limit	VOC Limit Effective 3-01-02
Topcoat	420	420
Clear Topcoat	520	520
Unicoat	420	420
Wing Coating	750	750
Impact Resistant Coating	420	420
High-Temperature Coating	850	850
Antichafe Coating	600	420
Rain Erosion-Resistant Coating	800	800
Conformal Coating	750	750
Optical Anti-Reflective Coating	700	700
Scale Inhibitor	880	880
Metallized Epoxy Coating	700	700
Electric or Radiation Effect Coating	800	800
Temporary Protective Coating	250	250
Fuel Tank Coatings	420	420
Mold Release Coatings	780	780
Flight Test Coatings		
Used on Missiles or Single Use Target Craft	420	420
All Other	840	840
Fire Resistant Coatings		
Commercial	650	650
Military	970	800
Wire Coatings		
Phosphate Ester Resistant Ink	925	925
Other	420	420
Space Vehicle Coatings		
Electrostatic Discharge Protection Coating	800	800
Other	1000	1000

**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1124 09-21-2001]**

Adhesives	Current VOC Limit
Non-Structural Adhesive	250
Structural Adhesive	
Autoclavable	50
Non-Autoclavable	850
Space Vehicle Adhesive	800
Fuel Tank Adhesive	620

Sealants	Current VOC Limit	VOC Limit Effective 3-01-02
Fastener Sealant	675	675
Extrudable, Rollable or Brushable Sealant	600	280
Other	600	600

Maskants	Current VOC Limit
For Chemical Processing	250
For Chemical Milling	
Type I	250
Type II	160
Photolithographic	850
Touch-up, Line Sealer Maskants	750

Lubricants	Current VOC Limit
Fastener Installation	
Solid-Film Lubricant	880
Dry Lubricative Materials	675
Fastener-Lubricative Coatings, Fastener Manufacturing	
Solid Film Lubricant	250
Dry Lubricative Materials	120
Barrier Coating	420
Non-Fastener Lubricative Coatings, Fastener Manufacturing	
Solid Film Lubricant	880
Dry Lubricative Materials	675



**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1124 09-21-2001]**

VOC LIMIT	
Grams of VOC per Liter of Material	
Cleaning Solvents and Strippers	Current VOC Limit
Cleaning Solvents	200 g/L or 45 mm Hg VOC Composite Partial Pressure
Strippers	300 g/L or 9.5 mm Hg VOC Composite Partial Pressure

- (B) Documents shall be provided to the Executive Officer or his designee demonstrating that unicoat is being used in lieu of the application of a primer and topcoat, and the applicant must receive written approval for the use of unicoat specifying the conditions of application from the Executive Officer or his designee.
 - (C) For low-solids adhesives, coatings, primers or sealants, the appropriate limits in subparagraph (c)(1)(A) shall be expressed in grams of VOC per liter of material.
- (2) Solvent Cleaning Operations; Storage and Disposal of VOC-Containing Materials
- (A) Cleaning of material application equipment and storage of solvent laden cloth and paper shall comply with provisions of Rule 1171.
 - (B) A person shall not atomize any solvent into open air.



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1130 10-08-1999]**

(Amended October 8, 1999)

RULE 1130. GRAPHIC ARTS

Except as otherwise provided in Rule 1130

(1) **VOC Content of Graphic Arts Materials**

The operator shall not apply any graphic arts material, including any VOC-containing materials added to the original graphic arts materials, which contains a total VOC in excess of the limits specified below:

<u>GRAPHIC ARTS MATERIAL</u>	VOC LIMIT	
	Grams per Liter of Coating (or Ink or Adhesive), Less Water <u>and Less Exempt Compounds</u>	
	<u>(October 8, 1999)</u>	<u>Effective January 1, 2000</u>
Lithographic Ink	300	300
Letterpress Ink	300	300
Gravure Ink	300	300
Flexographic Ink Non-Porous Substrate	300	300
Flexographic Ink Porous Substrate	300	225
Flexographic Fluorescent Ink	300	300
Coating	300	300
Adhesive	300	150



FACILITY PERMIT TO OPERATE KIRK HILL - TA COMPANY

APPENDIX B: RULE EMISSION LIMITS [RULE 1130 10-08-1999]

(2) VOC Content of Fountain Solution

Through December 31, 1999, the operator shall not apply in any graphic arts operation any fountain solution, including any VOC-containing materials added to the original fountain solution, which contains a total VOC in excess of 100 grams per liter of material. Effective January 1, 2000, the VOC content of fountain solution, including any VOC containing material added to the original fountain solution as applied, shall be:

- (A) no greater than 80 grams per liter of material, or
- (B) no greater than 100 grams per liter of material, if a refrigerated chiller is used.



**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1130 03-08-1996]**

Except as otherwise provided in Rule 1130

(1) VOC Content of Graphic Arts Materials

The operator shall not apply any graphic arts material, including any VOC-containing materials added to the original graphic arts materials supplied by the manufacturer, which contains a total VOC in excess of the limits specified below:

	VOC LIMIT
	Grams per Liter of
	Coating (or Ink or adhesive), Less Water
<u>GRAPHIC ARTS MATERIAL and Less Exempt Compounds</u>	
Printing Ink	300
Coating	300
Adhesive	300

(2) VOC Content of Fountain Solution

The operator shall not use in any graphic arts operation any fountain solution, including any VOC-containing materials added to the original fountain solution supplied by the manufacturer, which contains a total VOC in excess of 100 grams per liter of material.



FACILITY PERMIT TO OPERATE KIRK HILL - TA COMPANY

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 08-02-1985]

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).

- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1145 12-04-2009]**

Except as otherwise provided in Rule 1145, no person shall apply on plastics, rubber, leather, or glass any coatings which are applied with a VOC content in excess of the limits listed in the Table of Standards.

TABLE OF STANDARDS

VOC LIMITS LESS WATER AND LESS EXEMPT COMPOUNDS		
COATING CATEGORIES	g/L	lbs/gal
Electrical dissipating and shock free coatings	360	3.0
Extreme performance two-component coatings	420	3.5
General one-component coatings	120	1.0
General two-component coatings	120	1.0
Leather antique coatings	156	1.3
Leather color coatings	60	0.5
Leather sealer coatings	60	0.5
Leather stain coatings	216	1.8
Leather top coatings	120	1.0
Metallic coatings	420	3.5
Military specification one-component coatings	340	2.8
Military specification two-component coatings	420	3.5
Mirror backing curtain coated coatings	500	4.2
Mirror backing rolled coated coatings	312	2.6
Mold seal coatings	750	6.3
Multi-color coatings	680	5.7
Refrigerated glass door coatings	480	4.0
Optical coatings	50	0.4
Vacuum metalizing coatings	800	6.7



FACILITY PERMIT TO OPERATE KIRKHILL - TA COMPANY

APPENDIX B: RULE EMISSION LIMITS [RULE 1145 02-14-1997]

Except as otherwise provided in Rule 1145, the operator shall not apply on plastics, glass, or rubber any coatings which are applied with a VOC content in excess of the limits specified below:

COATING	VOC LIMITS			
	<u>Less Water and Less Exempt Compounds</u>			
	Current		On and After 1-1-98	
	g/L	lbs/gal	g/L	lbs/gal
General Coatings				
One-component	275	2.3	275	2.3
Two-component	420	3.5	420	3.5
Military Spec. Coating				
One-component	340	2.8	340	2.8
Two-component	420	3.5	420	3.5
Multi-Colored Coatings	685	5.7	685	5.7
Mold Seal Coatings	750	6.3	750	6.3
Vacuum Metalizing Coatings	800	6.7	800	6.7
Mirror Backing				
Curtain Coated	500	4.2	500	4.2
Roll Coated	430	3.6	430	3.6
Optical Coatings	800	6.7	800	6.7
Electric Dissipating Coatings and Shock-				
Free Coatings	800	6.7	360	3.0
Metallic Coatings	420	3.5	420	3.5



**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 10-08-1999]**

Except as otherwise provided in Rule 1171, the operator shall not use a solvent to perform solvent cleaning unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	Current limits		Effective 12/1/2001	Effective 7/1/2005
	VOC g/l (lb/gal)	VOC Composite Partial Pressure mm Hg @ 20°C (68°F)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application				
(i) General	70 (0.58)		50 (0.42)	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)	33	500 (4.2)	100 (0.83)
(iii) Medical Devices & Pharmaceuticals	900 (7.5)	33	800 (6.7)	800 (6.7)
(B) Repair and Maintenance Cleaning				
(i) General	50 (0.42)		50 (0.42)	25 (0.21)

**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 10-08-1999]**

SOLVENT CLEANING ACTIVITY	Current limits		Effective 12/1/2001	Effective 7/1/2005
	VOC g/l (lb/gal)	VOC Composite Partial Pressure mm Hg @ 20°C (68°F)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)	20	900 (7.5)	100 (0.83)
(iii) Medical Devices & Pharmaceuticals	900 (7.5)	33		
(I) Tools, Equipment, & Machinery			800 (6.7)	800 (6.7)
(II) General Work Surfaces			600 (5.0)	600 (5.0)
(C) Cleaning of Coatings, or Adhesives Application Equipment	950 (7.9)	35	550 (4.6)	25 (0.21)
(D) Cleaning of Ink Application Equipment				
(i) General	100 (0.83)	3	50 (0.42)	25 (0.21)
(ii) Flexographic Printing	100 (0.83)	3	50 (0.42)	25 (0.21)
(iii) Gravure Printing				
(I) Publication	900 (7.5)	25	750 (6.3)	100 (0.83)
(II) Packaging	100 (0.83)	3	50 (0.42)	25 (0.21)



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 10-08-1999]**

SOLVENT CLEANING ACTIVITY	Current limits		Effective 12/1/2001	Effective 7/1/2005
	VOC g/l (lb/gal)	VOC Composite Partial Pressure mm Hg @ 20°C (68°F)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iv) Lithographic or Letter Press Printing				
(I) Roller Wash – Step 1	900	10	600 (5.0)	100 (0.83)
(II) Roller Wash- Step 2, Blanket Wash, & On- Press Components	900	10	800 (6.7)	100 (0.83)
(III) Removable Press Components			50 (0.42)	25 (0.21)
(v) Screen Printing	1070 (8.9)	5	750 (6.3)	100 (0.83)
(vi) Ultraviolet Ink Application Equipment (except screen printing)	800 (6.7)	33	800 (6.7)	100 (0.83)
(vii) Specialty Flexographic Printing	810 (6.8)	21	600 (5.0)	100 (0.83)
(E) Cleaning of Polyester Resin Application Equipment	50 (0.42)		50 (0.42)	25 (0.21)

**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)



**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	

**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-07-2003]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS
	VOC g/l (lb/gal)
(A) Roller Wash - Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)



FACILITY PERMIT TO OPERATE KIRK HILL - TA COMPANY

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

**FACILITY PERMIT TO OPERATE
 KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 05-01-2009]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 05-01-2009]**

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

**FACILITY PERMIT TO OPERATE
 KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 06-13-1997]**

Except as otherwise provided in Rule 1171, the operator shall not use a solvent to perform solvent cleaning unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS		Effective 1/1/1999	
	VOC g/l (lb/gal)	VOC Composite Partial Pressure mm Hg @ 20°C (68°F)	VOC g/l (lb/gal)	VOC Composite Partial Pressure mm Hg @ 20°C (68°F)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application				
(i) General	70 (0.58)			
(ii) Electronic Components or Medical Devices	900 (7.5)	33		
(B) Repair and Maintenance Cleaning				
(i) General	900 (7.5)	20	50 (0.42)	
(ii) Electrical Apparatus Components	900 (7.5)	20		
(iii) Medical Devices	900 (7.5)	33		



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 06-13-1997]**

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS		Effective 1/1/1999	
	VOC g/l (lb/gal)	VOC Composite Partial Pressure mm Hg @ 20°C (68°F)	VOC g/l (lb/gal)	VOC Composite Partial Pressure mm Hg @ 20°C (68°F)
(C) Cleaning of Coatings, or Adhesives Application Equipment	950 (7.9)	35		
(D) Cleaning of Ink Application Equipment				
(i) General	100 (0.83)	3		
(ii) Flexographic or Gravure Printing	100 (0.83)	3		
(iii) Lithographic or Letter Press Printing	900 (7.5)	25		10
(iv) Screen Printing	1070 (8.9)	5		
(v) Ultraviolet Inks (except screen printing)	800 (6.7)	33		
(vi) Specialty Flexographic Printing	810 (6.8)	21		
(E) Cleaning of Polyester Resin Application Equipment	50 (0.42)			
or		1		

**FACILITY PERMIT TO OPERATE
 KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 10-05-1979]**

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a).

Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445



**FACILITY PERMIT TO OPERATE
 KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 10-05-1979]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

**FACILITY PERMIT TO OPERATE
 KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 10-05-1979]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]**

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 404 02-07-1986]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148



**FACILITY PERMIT TO OPERATE
 KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 404 02-07-1986]**

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter ⁷ Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot	Cubic meters Per Minute	Cubic feet Per Minute	Milligrams per Cubic Meter	Grains per Cubic Foot
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100



**FACILITY PERMIT TO OPERATE
KIRKHILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 405 02-07-1986]**

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process)		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process)	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6



**FACILITY PERMIT TO OPERATE
KIRK HILL - TA COMPANY**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 405 02-07-1986]**

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process)		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process)	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0