

FACILITY PERMIT TO OPERATE IPS CORP

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE IPS CORP

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
127024	M42127	ADHESIVES PACKAGING
165513	D16377	ADHESIVES PACKAGING
352347	F21178	STORAGE TANK ORGANIC CHEM MISC
454116	F82119	BAGHOUSE, AMBIENT TEMP (<100 SQ. FT)
454118	F82120	BAGHOUSE, AMBIENT TEMP (<100 SQ. FT)
454119	F82121	BAGHOUSE, AMBIENT TEMP (<100 SQ. FT)
456674	F97831	STORAGE TANK OTHER W/CTL MISC HYDROCARBS
456675	F97832	STORAGE TANK KETONES
456676	F97833	STORAGE TANK OTHER SOLVENTS N.E.C.
456678	F97834	STORAGE TANK OTHER SOLVENTS N.E.C.
456679	F97835	STORAGE TANK OTHER SOLVENTS N.E.C.
456680	F97836	STORAGE TANK OTHER SOLVENTS N.E.C.
456681	F97837	STORAGE TANK OTHER SOLVENTS N.E.C.
456682	F97838	ADHESIVES BLENDING
456683	F97839	ADHESIVES BLENDING
456684	F97840	ADHESIVES BLENDING
456686	F97841	ADHESIVES BLENDING
456687	F97842	ADHESIVES BLENDING
456688	F97843	ADHESIVES BLENDING
456690	F97844	ADHESIVES BLENDING
456691	F97845	ADHESIVES BLENDING
456692	F97846	ADHESIVES BLENDING
456693	F97847	ADHESIVES BLENDING
456694	F97848	ADHESIVES BLENDING
456695	F97849	ADHESIVES BLENDING
456697	F97850	ADHESIVES BLENDING
456699	F97851	ADHESIVES BLENDING
456700	F97852	ADHESIVES BLENDING
456702	F97853	ADHESIVES BLENDING
456704	F97854	ADHESIVES BLENDING
456706	F97855	ADHESIVES BLENDING
456708	F97856	ADHESIVES BLENDING
456711	F97857	ADHESIVES PACKAGING
456714	F97858	ADHESIVES PACKAGING

**FACILITY PERMIT TO OPERATE
 IPS CORP**

Application number	Permit to Operate number	Equipment description
456716	F97859	CONTAINER FILLING LIQUID ADHESIVES
456718	F97860	CONTAINER FILLING LIQUID ADHESIVES
456941	F97861	BAGHOUSE, AMBIENT TEMP (>500 SQ. FT)
456942	F97862	BAGHOUSE, AMBIENT TEMP (>500 SQ. FT)
456943	F97863	ACTIVATED CARBON ADSORBER
456944	F97864	ACTIVATED CARBON ADSORBER
457555	F97865	STORAGE TANK CYCLOHEXANONE
457556	F97866	STORAGE TANK METHYLENE CHLORIDE
475027		CONTAINER FILLING LIQUID ADHESIVES
475028		CONTAINER FILLING LIQUID ADHESIVES
475029		REGENERATIVE THERMAL OXIDIZER
482765		CONTAINER FILLING LIQUID ADHESIVES
482766		CONTAINER FILLING LIQUID ADHESIVES
482767		CONTAINER FILLING LIQUID ADHESIVES
482768		REGENERATIVE THERMAL OXIDIZER

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE IPS CORP

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - (A) AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGLEMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - (B) OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.
[RULE 401]

2. TO MAINTAIN AN EXEMPTION FROM THE NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (NESHAP) REQUIREMENTS, THE TOTAL QUANTITY OF HAZARDOUS AIR POLLUTANT (HAP) EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 10 TONS (20,000 POUNDS) OF A SINGLE HAP OR 25 TONS (50,000 POUNDS) OF A COMBINATION OF HAPS IN ANY TWELVE CALENDAR MONTH PERIOD.
[40CFR 63, SUBPART FFFF]

3. TO ENSURE COMPLIANCE WITH THE HAP(S) EMISSION CAPS, THE FACILITY OPERATOR SHALL:
 - (A) IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT AND THIS FACILITY TO VERIFY THE MONTHLY HAP EMISSIONS IN POUNDS AND THE HAP CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). THE RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT.
 - (B) WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, TOTAL AND RECORD HAP EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS THAT ARE REQUIRED TO HAVE WRITTEN PERMITS OR ARE EXEMPT FROM WRITTEN PERMITS PURSUANT TO RULE 219. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
 - (C) MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED HAP-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
 - (D) RETAIN ALL PURCHASE INVOICES FOR ALL HAP-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE HAP-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.
[RULE 109, 40CFR63, SUBPART FFFF]

**FACILITY PERMIT TO OPERATE
IPS CORP**

4. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, RETAINED AT THE FACILITY FOR FIVE YEARS, AND MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 40CFR63, SUBPART FFFF]

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. M42127
A/N 127024

Equipment Description:

STATION NO. 3, CONTAINER-FILLING.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Emissions And Requirements:

- 3) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. D16377
A/N 165513

Equipment Description:

STATION NO. 4, CONTAINER-FILLING, RUE, MODEL 2400 - 8 HEAD AUTOMATIC PISTON FILLER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Emissions And Requirements:

- 3) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F21178
A/N 352347

Equipment Description:

STORAGE TANK, NO. T107 MMA, METHYL METHACRYLATE, UNDERGROUND, 9'-4.5" DIA X 20'-1.5" L., 10,000 GALLON CAPACITY, UNHEATED, DOUBLE WALLED.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL ONLY BE USED TO STORE COMMERCIAL GRADE METHYL METHACRYLATE MONOMER.
[RULE 1303(b)(2)-OFFSET]
- 4) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL CONTAINED IN THIS EQUIPMENT TO NOT MORE THAN 8,750 GALLONS PER MONTH.
[RULE 1303(b)(2)-OFFSET]
- 5) THIS TANK SHALL NOT BE FILLED UNLESS THE DISPLACED VAPORS ARE RETURNED TO THE TRUCK OR TANK CAR THROUGH A GAS TIGHT VAPOR RETURN LINE.
[RULE 1303(a)(1)-BACT]
- 6) THE DISPLACED VAPORS COLLECTED BY THE TANK TRUCK DURING THE FILLING OF THE STORAGE TANKS SHALL BE VENTED TO A VAPOR RECOVERY SYSTEM OR AIR POLLUTION CONTROL SYSTEM OPERATING WITH A VALID PERMIT FROM SCAQMD.
[RULE 1303(a)(1)-BACT]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY COMPLIANCE WITH CONDITIONS NOS. 3 AND 4. ALL RECORDS SHALL BE KEPT IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT. THE RECORDS SHALL BE RETAINED FOR AT LEAST FIVE YEARS AND MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

Emissions And Requirements:

- 8) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1149

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F82119
A/N 454116

Equipment Description:

BAG BREAK STATION, NO. 1, DYNAMIC AIR, MODEL BAG BUSTER SERIES 319, WITH INTEGRAL FILTER VENT, REVERSE JET AIR CLEANING, TWO CARTRIDGE FILTERS, 76 SQ.FT. TOTAL AREA, AND A 1 H.P. BLOWER, VENTING MIXING TANKS NO. BM-11, BM-12, BM-13, BM-14, BM-15, AND BM-16.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 4) THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(A)(4)]
- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

FACILITY PERMIT TO OPERATE IPS CORP

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F82120
A/N 454118

Equipment Description:

BAG BREAK STATION, NO. 2, DYNAMIC AIR, MODEL BAG BUSTER SERIES 319, WITH INTEGRAL FILTER VENT, REVERSE JET AIR CLEANING, TWO CARTRIDGE FILTERS, 76 SQ.FT. TOTAL AREA, AND A 1 H.P. BLOWER, VENTING MIXING TANK NO. BM-17.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 4) THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(A)(4)]
- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
 - A. STACK OR EMISSION POINT IDENTIFICATION;

FACILITY PERMIT TO OPERATE IPS CORP

- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F82121
A/N 454119

Equipment Description:

BAG BREAK STATION, NO. 3, DYNAMIC AIR, MODEL BAG BUSTER SERIES 319, WITH INTEGRAL FILTER REVERSE JET AIR CLEANING, TWO CARTRIDGE FILTERS, 76 SQ.FT. TOTAL AREA, AND A 1 H.P. BLOWER, VENTING MIXING TANKS NO. BM-11 AND BM-14.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) DUST COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 4) THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(A)(4)]
- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
 - A. STACK OR EMISSION POINT IDENTIFICATION;

FACILITY PERMIT TO OPERATE IPS CORP

- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97831
A/N 456674

Equipment Description:

TANK NO. T101, TETRAHYDROFURAN, UNDERGROUND, DUAL RESERVOIR, 9'-7" DIA. X 38'-1" H., 20,000 GALLON CAPACITY TOTAL, WITH TWO SUBMERGED FILL TUBES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL NOT BE FILLED UNLESS THE DISPLACED VAPORS ARE RETURNED TO THE TRUCK OR TANK CAR THROUGH A GAS TIGHT VAPOR RETURN LINE.
[RULE 1303(a)(1)-BACT]
- 4) THE DISPLACED VAPORS COLLECTED BY THE TANK TRUCK DURING THE FILLING OF THE STORAGE TANKS SHALL BE VENTED TO A VAPOR RECOVERY SYSTEM OR AIR POLLUTION CONTROL SYSTEM OPERATING WITH A VALID PERMIT FROM SCAQMD.
[RULE 1303 (a)(1)-BACT]
- 5) THIS TANK SHALL ONLY BE USED TO STORE TETRAHYDROFURAN.
[RULE 1303(b)(2)-OFFSET]
- 6) MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC COMPOUNDS IDENTIFIED IN RULE 1401 AS AMENDED DECEMBER 7,1990.
[RULE 1401]
- 7) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]
- 8) THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY COMPLIANCE WITH CONDITION NO. 5. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST TO THE EXECUTIVE OFFICER OR REPRESENTATIVE.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 9) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1149

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97832
A/N 456675

Equipment Description:

TANK NO. T102, METHYL ETHYL KETONE, UNDERGROUND, DUAL RESERVOIR, 9'-7" DIA. X 38'-1" H., 20,000 GALLON CAPACITY, WITH TWO SUBMERGED FILL TUBES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL NOT BE FILLED UNLESS THE DISPLACED VAPORS ARE RETURNED TO THE TRUCK OR TANK CAR THROUGH A GAS TIGHT VAPOR RETURN LINE.
[RULE 1303(a)(1)-BACT]
- 4) THE DISPLACED VAPORS COLLECTED BY THE TANK TRUCK DURING THE FILLING OF THE STORAGE TANKS SHALL BE VENTED TO A VAPOR RECOVERY SYSTEM OR AIR POLLUTION CONTROL SYSTEM OPERATING WITH A VALID PERMIT FROM SCAQMD.
[RULE 1303 (a)(1)-BACT]
- 5) THIS TANK SHALL ONLY BE USED TO STORE METHYL ETHYL KETONE.
[RULE 1303(b)(2)-OFFSET]
- 6) MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC COMPOUNDS IDENTIFIED IN RULE 1401 AS AMENDED DECEMBER 7,1990.
[RULE 1401]
- 7) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]
- 8) THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY COMPLIANCE WITH CONDITION NO. 3. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST TO THE EXECUTIVE OFFICER OR REPRESENTATIVE.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 9) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1149

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97833
A/N 456676

Equipment Description:

HOLDING TANK H-1, FINISHED PRODUCT, 6'-5" DIA. X 6'-0" H., 1,400 GALLONS CAPACITY, WITH A 1 H.P. AGITATOR.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL NOT BE USED TO STORE A MATERIAL HAVING A VAPOR PRESSURE GREATER THAN 190 MM HG AT 68 DEGREES FAHRENHEIT.
[RULE 1303(b)(2)-OFFSET]
- 4) THIS TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A) RECORD THE NAME OF THE MATERIAL.
 - B) RECORD THE VAPOR PRESSURE IN MM HG OF EACH MATERIAL.[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97834
A/N 456678

Equipment Description:

HOLDING TANK H-2, FINISHED PRODUCT, 6'-5" DIA. X 6'-0" H., 1,400 GALLONS CAPACITY, WITH A 1 H.P. AGITATOR.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL NOT BE USED TO STORE A MATERIAL HAVING A VAPOR PRESSURE GREATER THAN 190 MM HG AT 68 DEGREES FAHRENHEIT.
[RULE 1303(b)(2)-OFFSET]
- 4) THIS TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A) RECORD THE NAME OF THE MATERIAL.
 - B) RECORD THE VAPOR PRESSURE IN MM HG OF EACH MATERIAL.[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97835
A/N 456679

Equipment Description:

HOLDING TANK H-3, FINISHED PRODUCT, 6'-5" DIA. X 6'-0" H., 1,400 GALLONS CAPACITY, WITH A 1 H.P. AGITATOR.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL NOT BE USED TO STORE A MATERIAL HAVING A VAPOR PRESSURE GREATER THAN 190 MM HG AT 68 DEGREES FAHRENHEIT.
[RULE 1303(b)(2)-OFFSET]
- 4) THIS TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A) RECORD THE NAME OF THE MATERIAL.
 - B) RECORD THE VAPOR PRESSURE IN MM HG OF EACH MATERIAL.[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97836
A/N 456680

Equipment Description:

HOLDING TANK H-4, FINISHED PRODUCT, 6'-5" DIA. X 6'-0" H., 1,400 GALLONS CAPACITY, WITH A 3 H.P. AGITATOR.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL NOT BE USED TO STORE A MATERIAL HAVING A VAPOR PRESSURE GREATER THAN 190 MM HG AT 68 DEGREES FAHRENHEIT.
[RULE 1303(b)(2)-OFFSET]
- 4) THIS TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A) RECORD THE NAME OF THE MATERIAL.
 - B) RECORD THE VAPOR PRESSURE IN MM HG OF EACH MATERIAL.[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97837
A/N 456681

Equipment Description:

HOLDING TANK H-5, FINISHED PRODUCT, 6'-5" DIA. X 6'-0" H., 1,400 GALLONS CAPACITY, WITH A 3 H.P. AGITATOR.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL NOT BE USED TO STORE A MATERIAL HAVING A VAPOR PRESSURE GREATER THAN 190 MM HG AT 68 DEGREES FAHRENHEIT.
[RULE 1303(b)(2)-OFFSET]
- 4) THIS TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A) RECORD THE NAME OF THE MATERIAL.
 - B) RECORD THE VAPOR PRESSURE IN MM HG OF EACH MATERIAL.[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97838
A/N 456682

Equipment Description:

MIXER MM-1, 6'-5" DIA. X 6'-0" H., 1,400 GALLON CAPACITY, WITH TWO AGITATORS, 50 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER POWDERY MATERIALS ARE BEING LOADED;
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER OR OBTAINING QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

FACILITY PERMIT TO OPERATE IPS CORP

- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97839
A/N 456683

Equipment Description:

MIXER MM-2, 6'-5" DIA. X 6'-0" H., 1,400 GALLON CAPACITY, WITH TWO AGITATORS, 50 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER POWDERY MATERIALS ARE BEING LOADED;
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER OR OBTAINING QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

FACILITY PERMIT TO OPERATE IPS CORP

- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97840
A/N 456684

Equipment Description:

MIXER MM-3, 6'-5" DIA. X 7'-0" H., 1,600 GALLON CAPACITY, WITH TWO AGITATORS, 50 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER POWDERY MATERIALS ARE BEING LOADED;
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER OR OBTAINING QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

FACILITY PERMIT TO OPERATE IPS CORP

- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97841
A/N 456686

Equipment Description:

MIXER MM-4, 6'-5" DIA. X 6'-0" H., 1,400 GALLON CAPACITY, WITH TWO AGITATORS, 50 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER POWDERY MATERIALS ARE BEING LOADED;
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER OR OBTAINING QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

FACILITY PERMIT TO OPERATE IPS CORP

- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97842
A/N 456687

Equipment Description:

MIXER MM-5, 6'-5" DIA. X 6'-0" H., 1,400 GALLON CAPACITY, WITH TWO AGITATORS, 50 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER POWDERY MATERIALS ARE BEING LOADED;
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER OR OBTAINING QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

FACILITY PERMIT TO OPERATE IPS CORP

- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97843
A/N 456688

Equipment Description:

MIXER MM-6, 6'-5" DIA. X 6'-0" H., 1,400 GALLON CAPACITY, WITH TWO AGITATORS, 50 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER POWDERY MATERIALS ARE BEING LOADED;
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER OR OBTAINING QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

FACILITY PERMIT TO OPERATE IPS CORP

- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

Emissions And Requirements:

- 6) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97844
A/N 456690

Equipment Description

MIXER MM-7, UNHEATED, 5'-11" DIA. X 7'-7" H., 1,600 GALLON CAPACITY, WITH TWO AGITATORS, 35 H.P. EACH, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER POWDERY MATERIALS ARE BEING LOADED;
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX PIPE CEMENT AND PRIMER MATERIALS.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456691, 456692, 456693, 456694, 456695, 456697, 456699, 456700, 456702, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.

B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;

B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR

C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

A. STACK OR EMISSION POINT IDENTIFICATION;

B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;

C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND

D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97845
A/N 456691

Equipment Description:

MIXER MM-8, UNHEATED, 5'-11" DIA. X 6'-8" H., 1,500 GALLON CAPACITY, WITH A 10 H.P. AGITATOR.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO A CARBON ADSORBER WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THIS MIXER SHALL NOT BE CHARGED WITH DRY MATERIALS.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 5) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 6) THIS MIXER SHALL ONLY BE USED TO MIX PRIMER MATERIALS.
[RULE 1303(a)(1)-BACT]
- 7) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456692, 456693, 456694, 456695, 456697, 456699, 456700, 456702, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 8) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 9) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

10) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

11) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

12) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 13) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97846
A/N 456692

Equipment Description:

MIXER MM-9, UNHEATED, 5'-11" DIA. X 6'-8" H., 1,500 GALLON CAPACITY, WITH A 10 H.P. AGITATOR

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO A CARBON ADSORBER WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THIS MIXER SHALL NOT BE CHARGED WITH DRY MATERIALS.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 5) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 6) THIS MIXER SHALL ONLY BE USED TO MIX PLASTIC PRIMER MATERIALS.
[RULE 1303(a)(1)-BACT]
- 7) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456693, 456694, 456695, 456697, 456699, 456700, 456702, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 8) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 9) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

10) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

11) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

12) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 13) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97847
A/N 456693

Equipment Description

MIXER MM-10, UNHEATED, 5'-11" DIA. X 6'-8" H., 1,500 GALLON CAPACITY, WITH A 10 H.P. AGITATOR.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO A CARBON ADSORBER WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THIS MIXER SHALL NOT BE CHARGED WITH DRY MATERIALS.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 5) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 6) THIS MIXER SHALL ONLY BE USED TO MIX PLASTIC PRIMER MATERIALS.
[RULE 1303(a)(1)-BACT]
- 7) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456694, 456695, 456697, 456699, 456700, 456702, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 8) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 9) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

- 10) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
 - B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]
- 11) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.
- THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
 - D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004(A)(4)]
- 12) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 13) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97848
A/N 456694

Equipment Description:

MIXER MM-11, UNHEATED, 6'-6" DIA. X 7'-0" H., 1,600 GALLON CAPACITY, WITH A 10 H.P. AGITATOR.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER POWDERY MATERIALS ARE BEING LOADED;
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX PIPE CEMENT AND PLASTIC PRIMER MATERIALS.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456693, 456695, 456697, 456699, 456700, 456702, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97849
A/N 456695

Equipment Description:

MIXER MM-12, UNHEATED, 6' - 6" DIA. X 7' -0" H., 1,600 GALLON CAPACITY, WITH THREE AGITATORS, 81 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER POWDERY MATERIALS ARE BEING LOADED;
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX PIPE CEMENT AND PRIMER MATERIALS.
[RULE 1303(b)(2)-OFFSET]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456693, 456694, 456697, 456699, 456700, 456702, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

- 9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
 - B. DATE, TIME AND RESULT OF THE INSPECTION.
[RULE 3004(a)(4)]
- 10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.
- THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
 - D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004(A)(4)]
- 11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.
[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 109

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97850
A/N 456697

Equipment Description:

MIXER BM-11, UNHEATED, 5'-4" DIA. X 5'-6" H., 800 GALLON CAPACITY, WITH THREE AGITATORS, 75 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER DRY MATERIALS ARE BEING LOADED.
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX ADHESIVES FOR PLASTIC PIPE MATERIALS.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456693, 456694, 456695, 456699, 456700, 456702, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97851
A/N 456699

Equipment Description:

MIXER BM-12, UNHEATED, 5'-4" DIA. X 5'-6" H., 800 GALLON CAPACITY, WITH THREE AGITATORS, 75 H.P.TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER DRY MATERIALS ARE BEING LOADED.
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX ADHESIVES AND PRIMERS FOR PLASTIC PIPE MATERIALS.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456693, 456694, 456695, 456697, 456700, 456702, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97852
A/N 456700

Equipment Description:

MIXER BM-13, UNHEATED, 5'-4" DIA. X 5'-6" H., 800 GALLON CAPACITY, WITH THREE AGITATORS, 75 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER DRY MATERIALS ARE BEING LOADED.
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX ADHESIVES AND PRIMERS FOR PLASTIC PIPE MATERIALS.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456693, 456694, 456695, 456697, 456699, 456702, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97853
A/N 456702

Equipment Description:

MIXER BM-14, UNHEATED, 5'-4" DIA. X 5'-6" H., 800 GALLON CAPACITY, WITH THREE AGITATORS, 75 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER DRY MATERIALS ARE BEING LOADED.
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX ADHESIVES AND PRIMERS FOR PLASTIC PIPE MATERIALS.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456693, 456694, 456695, 456697, 456699, 456700, 456704, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

10). THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97854
A/N 456704

Equipment Description:

MIXER BM-15, UNHEATED, 5'-4" DIA. X 5'-6" H., 800 GALLON CAPACITY, WITH THREE AGITATORS, 75 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER DRY MATERIALS ARE BEING LOADED.
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX ADHESIVES AND PRIMERS FOR PLASTIC PIPE MATERIALS.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456693, 456694, 456695, 456697, 456699, 456700, 456702, 456706, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97855
A/N 456706

Equipment Description:

MIXER BM-16, UNHEATED, 5'-4" DIA. X 5'-6" H., 800 GALLON CAPACITY, WITH THREE AGITATORS, 75 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER DRY MATERIALS ARE BEING LOADED.
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX ADHESIVES AND PRIMERS FOR PLASTIC PIPE MATERIALS.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456693, 456694, 456695, 456697, 456699, 456700, 456702, 456704, AND 456708 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97856
A/N 456708

Equipment Description:

MIXER BM-17, 5'-4" DIA. X 5'-0" H., 600 GALLON CAPACITY, WITH THREE AGITATORS, 130 H.P. TOTAL, AND A VAPOR CONDENSER.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE MIXING TANK SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO OPERATE BY THE EXECUTIVE OFFICER, IN THE FOLLOWING MANNER:
 - A. TO A BAGHOUSE WHENEVER DRY MATERIALS ARE BEING LOADED.
 - B. TO A CARBON ADSORBER WHENEVER LIQUIDS ARE BEING ADDED, MIXING IS OCCURRING, OR THE TANK COVER IS OPEN, EXCEPT DURING THE LOADING OF DRY MATERIALS OR TAKING OF QUALITY CONTROL SAMPLES.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) THE CHARGING PORT OR HATCH SHALL REMAIN CLOSED EXCEPT DURING THE CHARGING OF THE MIXER.
[RULE 1303(a)(1)-BACT]
- 5) THIS MIXER SHALL ONLY BE USED TO MIX ADHESIVES AND PRIMERS FOR PLASTIC PIPE MATERIALS.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NOS. 456690, 456691, 456692, 456693, 456694, 456695, 456697, 456699, 456700, 456702, 456704, AND 456706 TO NOT MORE THAN 375,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 7) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 5 AND 6. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
- 8) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109]

FACILITY PERMIT TO OPERATE IPS CORP

Periodic Monitoring:

9) THE OPERATOR SHALL PERFORM SEMI-ANNUAL INSPECTION OF THE EQUIPMENT TO ENSURE THAT THE MOVABLE COVERS ARE CLOSED. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. NAME OF THE PERSON PERFORMING THE INSPECTION OF THE COVER.
- B. DATE, TIME AND RESULT OF THE INSPECTION.

[RULE 3004(a)(4)]

10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004(A)(4)]

11) THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE CLEANING LOG THAT INCLUDES STATEMENT OF THE APPROVED CLEANING METHOD.

[RULE 3004(a)(4)]

FACILITY PERMIT TO OPERATE IPS CORP

Emissions And Requirements:

- 12) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:
- VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
 - VOC: RULE 109
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97857
A/N 456711

Equipment Description:

STATION NO. 2, CONTAINER-FILLING, SIMPLEX AIR, MODEL V-400, WITH FOUR NOZZLES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT TO NOT MORE THAN 62,352 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 4) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 3. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

- 5) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97858
A/N 456714

Equipment Description:

STATION NO. 1, CONTAINER-FILLING, SIMPLEX AIR, MODEL V-800, WITH EIGHT NOZZLES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT TO NOT MORE THAN 62,352 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 4) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 3. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

- 5) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97859
A/N 456716

Equipment Description:

STATION NO. 10, CONTAINER-FILLING, SIMPLEX AIR V-400, 3'-0" W. X 4'-7" L. X 5'-0" H., WITH 4 NOZZLES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT TO NOT MORE THAN 17,330 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 4) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 3. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

- 5) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97860
A/N 456718

Equipment Description:

STATION NO. 11, CONTAINER-FILLING, SIMPLEX AIR V-400, 3'-0" W. X 4'-7" L. X 5'-0" H., WITH 4 NOZZLES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT TO NOT MORE THAN 17,330 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 4) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 3. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

Emissions And Requirements:

- 5) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97861
A/N 456941

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. BAGHOUSE, RICHTER ENGINEERING. MODEL NO. 500, 4'-11" W. X 5'-6" L. X 12'-9" H., WITH A 1/4 H.P. SHAKER
2. EXHAUST SYSTEM WITH A 3 H.P. BLOWER VENTING NINE MIXERS.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE USED TO VENT MORE THAN TWO MIXERS AT ANY ONE TIME WHILE LOADING OF MIXERS IS OCCURING.
[RULE 1303(b)(2)-OFFSET]
- 4) DUSTS COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 5) THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(A)(4)]
- 6) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE

FACILITY PERMIT TO OPERATE IPS CORP

EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004(A)(4)]

Emissions And Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97862
A/N 456942

Equipment Description:

MATERIAL DELIVERY AND AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. BAGBREAK STATION, DYNAMIC AIR, STANDARD BAG BUSTER, 3'-2" W. X 3'-8" L. X 7'-2" H., WITH A FILTER CARTRIDGE, 100 SQ.FT. TOTAL AREA, A 5 CU. FT. HOPPER, AND PULSE JET CLEANING.
2. EXHAUST SYSTEM WITH A 2 H.P. BLOWER VENTING THE BAG BREAKING STATION.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) DUSTS COLLECTED IN THE BAGHOUSE SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 4) THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(A)(4)]
- 5) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING

FACILITY PERMIT TO OPERATE IPS CORP

REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
[RULE 3004(A)(4)]

Emissions And Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97863
A/N 456943

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. TWO (2) CARBON ADSORPTION UNITS, U.S. FILTER - WESTATES, MODEL VSC-400, MEASURING 2'-8" DIA. X 3'-6 $\frac{3}{4}$ "H., 14 CU.FT. EACH, CONNECTED IN SERIES
2. PASSIVE EXHAUST VAPOR DISPLACEMENT SYSTEM VENTING TWELVE MIXING TANKS AND FIVE HOLDING TANKS.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) EACH CARBON ADSORBER BED SHALL CONTAIN A MINIMUM OF 400 LBS. OF ACTIVATED CARBON.
[RULE 1303(a)(1)-BACT]
- 4) VOLATILE ORGANIC COMPOUND (VOC) CONCENTRATION SHALL BE MEASURED AT THE OUTLET OF THE PRIMARY CARBON ADSORBER, AT LEAST ONCE EVERY WEEK, BY USING A FLAME IONIZATION DETECTOR OR A DISTRICT APPROVED ORGANIC VAPOR ANALYZER CALIBRATED IN PPMV OF HEXANE.
[RULE 1303(a)(1)-BACT]
- 5) THE PRIMARY CARBON ADSORBER SHALL BE TAKEN OUT OF SERVICE WHEN THE VOC CONCENTRATION MEASURED AT THE EXIT OF THE PRIMARY ADSORBER EXCEEDS 5 PPMV. A NEW ADSORBER WITH FRESH CARBON SHALL REPLACE THE SECONDARY CARBON ADSORBER WHICH WILL TAKE PLACE OF THE PRIMARY CARBON ADSORBER.
[RULE 1303(a)(1)-BACT]
- 6) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NOS. 4 AND 5. SUCH RECORDS SHALL BE KEPT IN A FORMAT APPROVED BY THE DISTRICT, SHALL BE RETAINED FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97864
A/N 456944

Equipment Description:

AIR POLLUTION CONTROL SYSTEM, CONSISTING OF:

1. TWO (2) CARBON ADSORPTION UNITS, U.S. FILTER - WESTATES, MODEL VSC-400, MEASURING 2'-8" DIA. X 3'-6 $\frac{3}{4}$ "H., 14 CU.FT. EACH, CONNECTED IN SERIES.
2. PASSIVE EXHAUST VAPOR DISPLACEMENT SYSTEM VENTING SEVEN MIXING TANKS.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE USED TO VENT MORE THAN TWO MIXERS AT ANY ONE TIME.
[RULE 1303(a)(1)-BACT]
- 4) EACH CARBON ADSORBER BED SHALL CONTAIN A MINIMUM OF 400 LBS. OF ACTIVATED CARBON.
[RULE 1303(a)(1)-BACT]
- 5) VOLATILE ORGANIC COMPOUND (VOC) CONCENTRATION SHALL BE MEASURED AT THE OUTLET OF THE PRIMARY CARBON ADSORBER, AT LEAST ONCE EVERY WEEK, BY USING A FLAME IONIZATION DETECTOR OR A DISTRICT APPROVED ORGANIC VAPOR ANALYZER CALIBRATED IN PPMV OF HEXANE.
[RULE 1303(a)(1)-BACT]
- 6) THE PRIMARY CARBON ADSORBER SHALL BE TAKEN OUT OF SERVICE WHEN THE VOC CONCENTRATION MEASURED AT THE EXIT OF THE PRIMARY ADSORBER EXCEEDS 5 PPMV. A NEW ADSORBER WITH FRESH CARBON SHALL REPLACE THE SECONDARY CARBON ADSORBER WHICH WILL TAKE PLACE OF THE PRIMARY CARBON ADSORBER.
[RULE 1303(a)(1)-BACT]
- 7) RECORDS SHALL BE MAINTAINED TO DEMONSTRATE COMPLIANCE WITH CONDITION NOS. 5 AND 6. THE RECORDS SHALL BE KEPT FOR AT LEAST FIVE YEARS AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97865
A/N 457555

Equipment Description:

TANK NO. T106, ACETONE AND CYCLOHEXANONE, UNDERGROUND, DUAL RESERVOIR, 9'-7" DIA. X 38'-1" H., 20,000 GALLON CAPACITY TOTAL, WITH TWO SUBMERGED FILL TUBES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL ONLY BE USED TO STORE ACETONE AND CYCLOHEXANONE.
[RULE 1303(b)(2)-OFFSET]
- 4) MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC COMPOUNDS IDENTIFIED IN RULE 1401 AS AMENDED DECEMBER 7,1990.
[RULE 1401]
- 5) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]
- 6) THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY COMPLIANCE WITH CONDITION NO. 3. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST TO THE EXECUTIVE OFFICER OR REPRESENTATIVE.
[RULE 109; 1303(b)(2)-OFFSET]

Emissions And Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1149

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO OPERATE

Permit No. F97866
A/N 457556

Equipment Description:

STORAGE TANK, NO. T108, METHYLENE CHLORIDE, 5'-4" DIA. X 6'-0" H., 1,000 GALLONS CAPACITY.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS TANK SHALL ONLY BE USED TO STORE METHYLENE CHLORIDE.
[RULE 1303(b)(2)-OFFSET]
- 4) MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 1303(b)(2)-OFFSET]
- 5) THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY COMPLIANCE WITH CONDITION NO. 3. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST TO THE EXECUTIVE OFFICER OR REPRESENTATIVE.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO CONSTRUCT

A/N 475027
Granted as of
April 15, 2008

Equipment Description:

STATION NO. 21, CONTAINER-FILLING, IME, SERIES 2400, WITH 12 NOZZLES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO CONSTRUCT BY THE EXECUTIVE OFFICER.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NUMBER 475028 TO NOT MORE THAN 417,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 5) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 4. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
- 6) MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS A TOXIC AIR CONTAMINANT IN DISTRICT RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF METHYL ETHYL KETONE (CAS # 78-93-3).
[RULE 1401]

Emissions And Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO CONSTRUCT

A/N 475028
Granted as of
April 15, 2008

Equipment Description:

STATION NO. 22, CONTAINER-FILLING, IME, SERIES 2400, WITH 12 NOZZLES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO CONSTRUCT BY THE EXECUTIVE OFFICER.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NUMBER 475027 TO NOT MORE THAN 417,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 5) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 4. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
- 6) MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS A TOXIC AIR CONTAMINANT IN DISTRICT RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF METHYL ETHYL KETONE (CAS # 78-93-3).
[RULE 1401]

Emissions And Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO CONSTRUCT

A/N 475029
Granted as of
April 15, 2008

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. REGENERATIVE THERMAL OXIDIZER, ADWEST TECHNOLOGIES, MODEL 8.0 RTO95, WITH A MAXON KINEMAX 3G NATURAL GAS-FIRED BURNER, 2,295,000 BTU PER HOUR, A NATURAL GAS INJECTION SYSTEM, A 7.5-H.P. COMBUSTION AIR BLOWER, TWO COMBUSTION CHAMBERS, 360 CU. FT. TOTAL VOLUME, A FLOW DIVERTER VALVE, AND TWO CERAMIC BEDS, 6'-4" W. X 8'-6" L. X 4'-0" H. EACH.
2. EXHAUST SYSTEM CONSISTING OF:
 - A. FILLING ROOM PERMANENT TOTAL ENCLOSURE (PTE), 49'-0" W. X 55'-0" L. X 23'-0" H. OVERALL, ENCOMPASSING FOUR CONTAINER FILLING STATIONS NOS 3, 4, 21, AND 22.
 - B. 40-H.P. BLOWER WITH A 2'-0" DIA. X 40'-0" H. EXHAUST STACK.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE COMBUSTION CHAMBER TEMPERATURE SHALL BE MAINTAINED AT A MINIMUM OF 1,500 DEGREES FAHRENHEIT WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) A CONTINUOUS TEMPERATURE INDICATOR AND RECORDER SHALL BE INSTALLED TO MEASURE AND RECORD THE TEMPERATURE IN THE COMBUSTION CHAMBER OF THE OXIDIZER. SUCH A SYSTEM SHALL HAVE AN ACCURACY OF WITHIN 1% OF THE TEMPERATURE BEING MONITORED AND SHALL BE INSPECTED, MAINTAINED, AND CALIBRATED ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS. THE TEMPERATURE INDICATING AND RECORDING SYSTEM SHALL BE IN OPERATION WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT]
- 5) THE OXIDIZER SHALL BE FIRED ON NATURAL GAS ONLY.
[RULE 1303(a)(1)-BACT]
- 6) ALL ACCESS DOORS TO THE PERMANENT TOTAL ENCLOSURES SHALL BE KEPT CLOSED DURING NORMAL OPERATIONS.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE IPS CORP

- 7) THE OPERATOR SHALL MAINTAIN AND OPERATE THE PERMANENT TOTAL ENCLOSURE TO COMPLY WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
- 8) THIS EQUIPMENT SHALL BE MAINTAINED AND OPERATED AT A MINIMUM DESTRUCTION EFFICIENCY OF 98% AND AN OVERALL VOC CONTROL EFFICIENCY (COLLECTION AND DESTRUCTION) OF 98% WHEN THE BASIC EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT]
- 9) THE BURNER OF THE REGENERATIVE THERMAL OXIDIZER SHALL ONLY BE USED FOR THE START-UP OF THE EQUIPMENT BEFORE THE PROCESS AIR STREAM FROM THE FILLING OPERATIONS IS INTRODUCED INTO THE OXIDIZER.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 10) THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THE START UP BURNER SHALL NOT EXCEED 60 PPMV, CALCULATED AS NO₂ BY VOLUME ON A DRY BASIS @ 3% O₂.
[RULE 1303(a)(1)-BACT]
- 11) THE OWNER OR OPERATOR OF THIS EQUIPMENT SHALL CONDUCT SOURCE TESTING UNDER THE FOLLOWING CONDITIONS TO DEMONSTRATE COMPLIANCE WITH THE PERMIT CONDITIONS:
 - A) THE TEST SHALL BE CONDUCTED TO DEMONSTRATE COMPLIANCE WITH THE VOC DESTRUCTION EFFICIENCY AND VOC OVERALL CONTROL EFFICIENCY.
 - B) THE TEST SHALL BE CONDUCTED TO DEMONSTRATE COMPLIANCE WITH EPA METHOD 204.
 - C) THE SOURCE TEST SHALL BE CONDUCTED NO LATER THAN 180 DAYS AFTER THE INITIAL START-UP OF THIS EQUIPMENT UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
 - D) A SOURCE TEST PROTOCOL SHALL BE SUBMITTED TO THE DISTRICT NO LATER THAN 60 DAYS AFTER THE INITIAL START-UP OF THIS EQUIPMENT UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT. THE TEST PROTOCOL SHALL BE APPROVED IN WRITING BY THE DISTRICT BEFORE THE TEST COMMENCES. THE TEST PROTOCOL SHALL INCLUDE THE COMPLETED DISTRICT FORMS ST-1 AND ST-2 SPECIFYING THE PROPOSED OPERATING CONDITIONS OF THE EQUIPMENT DURING THE TEST, THE IDENTITY OF THE TESTING LABORATORY, A STATEMENT FROM THE TESTING LABORATORY CERTIFYING IT MEETS THE CRITERIA IN DISTRICT RULE 304(k), AND A DESCRIPTION OF THE SAMPLING AND ANALYTICAL PROCEDURES TO BE USED.
 - E) THE SOURCE TEST SHALL CONSIST OF, BUT MAY NOT BE LIMITED TO, TESTING AT THE INLET AND THE EXHAUST OF THE OXIDIZER FOR:
 - (1) VOLATILE ORGANIC COMPOUNDS (VOC), IN PPMV, AND LBS/HR
 - (2) VOC DESTRUCTION EFFICIENCY
 - (3) OXIDES OF NITROGEN (NO_x) IN PPMV AND LBS/HR (OXIDIZER EXHAUST ONLY)
 - (4) CARBON MONOXIDE (CO) IN PPMV AND LBS/HR (OXIDIZER EXHAUST ONLY)
 - (5) VOC COLLECTION EFFICIENCY PER EPA METHOD 204 DESIGN CRITERIA
 - (6) OXYGEN CONTENT
 - (7) MOISTURE CONTENT
 - (8) FLOW RATE

FACILITY PERMIT TO OPERATE IPS CORP

- (9) TEMPERATURE
- F) THE SOURCE TEST SHALL BE CONDUCTED WHILE THE OXIDIZER IS OPERATING AT A TEMPERATURE OF NOT LESS THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THE PERMIT. IF THE OPERATING TEMPERATURE DURING THE SOURCE TEST IS GREATER THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THE PERMIT, THE MINIMUM OPERATING TEMPERATURE MAY BE INCREASED AT THE TIME A PERMIT TO OPERATE IS ISSUED TO REFLECT THE OPERATING TEMPERATURE DURING THE SOURCE TEST. IN ADDITION, THE USAGE OF ALL VOC-CONTAINING MATERIALS (PRIMERS, ADHESIVES, ETC.) AND OPERATING TEMPERATURE IN THE COMBUSTION CHAMBER SHALL BE RECORDED DURING THE TEST.
- G) IN ADDITION TO THE TEST DURING NORMAL OPERATION, A SOURCE TEST FOR NO_x AND CO EMISSIONS SHALL ALSO BE CONDUCTED DURING THE START-UP OF THE OXIDIZER BEFORE THE PROCESS AIR STREAM FROM THE FILLING OPERATIONS IS INTRODUCED INTO THE OXIDIZER.
- H) A WRITTEN NOTICE OF THE SOURCE TESTS SHALL BE SUBMITTED TO THE DISTRICT AT LEAST 14 DAYS PRIOR TO THE SOURCE TESTING DATE SO THAT AN OBSERVER FROM THE DISTRICT MAY BE PRESENT.
- I) TWO COMPLETE COPIES OF THE SOURCE TEST REPORT SHALL BE SUBMITTED TO THE DISTRICT WITHIN 45 DAYS AFTER THE SOURCE TEST DATE UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT. THE SOURCE TEST REPORT SHALL INCLUDE, BUT MAY NOT BE LIMITED TO, ALL TESTING DATA REQUIRED BY THIS CONDITION.
- J) A TESTING LABORATORY CERTIFIED BY THE CALIFORNIA AIR RESOURCES BOARD IN THE REQUIRED TEST METHODS FOR CRITERIA POLLUTANTS TO BE MEASURED, AND IN COMPLIANCE WITH DISTRICT RULE 304 (NO CONFLICT OF INTEREST) SHALL CONDUCT THE TEST.
- K) SAMPLING FACILITIES SHALL COMPLY WITH THE DISTRICT GUIDELINES FOR CONSTRUCTION OF SAMPLING AND TESTING FACILITIES, PURSUANT TO RULE 217.
[RULE 1303(a)(1)-BACT]
- 12) THE OWNER OR OPERATOR OF THIS EQUIPMENT SHALL SUBMIT THE RESULTS OF ALL PERLIMINARY TESTS THAT ARE CONDUCTED ON THIS EQUIPMENT FOR INFORMATIONAL PURPOSES TO THE DISTRICT WITHIN 45 DAYS AFTER THE TESTING DATE UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 13) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
- A) VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION

FACILITY PERMIT TO OPERATE IPS CORP

AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;

- B) TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C) HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A) STACK OR EMISSION POINT IDENTIFICATION;
- B) DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C) DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D) VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

- 14) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO CONSTRUCT

A/N 482765
Granted as of:

Equipment Description:

STATION NO. 1, CONTAINER-FILLING, SIMPLEX AIR, MODEL V-800, WITH EIGHT NOZZLES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO CONSTRUCT/OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NUMBERS 482766 AND 482767 TO NOT MORE THAN 300,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 5) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 4. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
- 6) MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS A TOXIC AIR CONTAMINANT IN DISTRICT RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF METHYL ETHYL KETONE (CAS # 78-93-3).
[RULE 1401]

Emissions And Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO CONSTRUCT

A/N 482766
Granted as of:

Equipment Description:

STATION NO. 10, CONTAINER-FILLING, SIMPLEX AIR V-400, 3'-0" W. X 4'-7" L. X 5'-0" H., WITH 4 NOZZLES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO CONSTRUCT/OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NUMBERS 482765 AND 482767 TO NOT MORE THAN 300,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 5) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 4. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
- 6) MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS A TOXIC AIR CONTAMINANT IN DISTRICT RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF METHYL ETHYL KETONE (CAS # 78-93-3).
[RULE 1401]

Emissions And Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO CONSTRUCT

A/N 482767
Granted as of:

Equipment Description:

STATION NO. 11, CONTAINER-FILLING, SIMPLEX AIR V-400, 3'-0" W. X 4'-7" L. X 5'-0" H., WITH 4 NOZZLES.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED ONLY TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO CONSTRUCT/OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(b)(2)-OFFSET, 1303(a)(1)-BACT]
- 4) THE OPERATOR SHALL LIMIT THE THROUGHPUT OF THE MATERIAL PROCESSED IN THIS EQUIPMENT AND OTHER EQUIPMENT UNDER APPLICATION NUMBERS 482765 AND 482766 TO NOT MORE THAN 300,000 GALLONS OF MATERIAL IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
- 5) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY COMPLIANCE WITH CONDITION NO. 4. SUCH RECORDS SHALL BE RETAINED AT LEAST FIVE YEARS AND MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]
- 6) MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS A TOXIC AIR CONTAMINANT IN DISTRICT RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER, WITH THE EXCEPTION OF METHYL ETHYL KETONE (CAS # 78-93-3).
[RULE 1401]

Emissions And Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1168, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE IPS CORP

PERMIT TO CONSTRUCT

A/N 475029
Granted as of:

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. REGENERATIVE THERMAL OXIDIZER, ADWEST TECHNOLOGIES, MODEL 6.0 RTO95, WITH A MAXON KINEMAX 3G NATURAL GAS-FIRED BURNER, 1,734,000 BTU PER HOUR, A NATURAL GAS INJECTION SYSTEM, A 3-H.P. COMBUSTION AIR BLOWER, TWO COMBUSTION CHAMBERS, 250 CU. FT. TOTAL VOLUME, A FLOW DIVERTER VALVE, AND TWO CERAMIC BEDS, 5'-0" W. X 17'-8" L. X 2'-10" H. EACH.
2. EXHAUST SYSTEM CONSISTING OF:
 - A. FILLING ROOM PERMANENT TOTAL ENCLOSURE (PTE), 79'-0" W. X 29'-0" L. X 17'-0" H. OVERALL, ENCOMPASSING THREE CONTAINER FILLING STATIONS NOS. 1, 10 AND 11.
 - B. 25-H.P. BLOWER WITH A 2'-4" DIA. X 25'-0" H. EXHAUST STACK.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THE COMBUSTION CHAMBER TEMPERATURE SHALL BE MAINTAINED AT A MINIMUM OF 1,500 DEGREES FAHRENHEIT WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 4) A CONTINUOUS TEMPERATURE INDICATOR AND RECORDER SHALL BE INSTALLED TO MEASURE AND RECORD THE TEMPERATURE IN THE COMBUSTION CHAMBER OF THE OXIDIZER. SUCH A SYSTEM SHALL HAVE AN ACCURACY OF WITHIN 1% OF THE TEMPERATURE BEING MONITORED AND SHALL BE INSPECTED, MAINTAINED, AND CALIBRATED ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS. THE TEMPERATURE INDICATING AND RECORDING SYSTEM SHALL BE IN OPERATION WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT]
- 5) THE OXIDIZER SHALL BE FIRED ON NATURAL GAS ONLY.
[RULE 1303(a)(1)-BACT]
- 6) ALL ACCESS DOORS TO THE PERMANENT TOTAL ENCLOSURES SHALL BE KEPT CLOSED DURING NORMAL OPERATIONS.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE IPS CORP

- 7) THE OPERATOR SHALL MAINTAIN AND OPERATE THE PERMANENT TOTAL ENCLOSURE TO COMPLY WITH ALL CRITERIA SPECIFIED IN EPA METHOD 204.
[RULE 1303(a)(1)-BACT]
- 8) THIS EQUIPMENT SHALL BE MAINTAINED AND OPERATED AT A MINIMUM DESTRUCTION EFFICIENCY OF 98% AND AN OVERALL VOC CONTROL EFFICIENCY (COLLECTION AND DESTRUCTION) OF 98% WHEN THE BASIC EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT]
- 9) THE BURNER OF THE REGENERATIVE THERMAL OXIDIZER SHALL ONLY BE USED FOR THE START-UP OF THE EQUIPMENT BEFORE THE PROCESS AIR STREAM FROM THE FILLING OPERATIONS IS INTRODUCED INTO THE OXIDIZER.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
- 10) THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THE START UP BURNER SHALL NOT EXCEED 60 PPMV, CALCULATED AS NO₂ BY VOLUME ON A DRY BASIS @ 3% O₂.
[RULE 1303(a)(1)-BACT]
- 11) THE OWNER OR OPERATOR OF THIS EQUIPMENT SHALL CONDUCT SOURCE TESTING UNDER THE FOLLOWING CONDITIONS TO DEMONSTRATE COMPLIANCE WITH THE PERMIT CONDITIONS:
 - A) THE TEST SHALL BE CONDUCTED TO DEMONSTRATE COMPLIANCE WITH THE VOC DESTRUCTION EFFICIENCY AND VOC OVERALL CONTROL EFFICIENCY.
 - B) THE TEST SHALL BE CONDUCTED TO DEMONSTRATE COMPLIANCE WITH EPA METHOD 204.
 - C) THE SOURCE TEST SHALL BE CONDUCTED NO LATER THAN 180 DAYS AFTER THE INITIAL START-UP OF THIS EQUIPMENT UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
 - D) A SOURCE TEST PROTOCOL SHALL BE SUBMITTED TO THE DISTRICT NO LATER THAN 60 DAYS AFTER THE INITIAL START-UP OF THIS EQUIPMENT UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT. THE TEST PROTOCOL SHALL BE APPROVED IN WRITING BY THE DISTRICT BEFORE THE TEST COMMENCES. THE TEST PROTOCOL SHALL INCLUDE THE COMPLETED DISTRICT FORMS ST-1 AND ST-2 SPECIFYING THE PROPOSED OPERATING CONDITIONS OF THE EQUIPMENT DURING THE TEST, THE IDENTITY OF THE TESTING LABORATORY, A STATEMENT FROM THE TESTING LABORATORY CERTIFYING IT MEETS THE CRITERIA IN DISTRICT RULE 304(k), AND A DESCRIPTION OF THE SAMPLING AND ANALYTICAL PROCEDURES TO BE USED.
 - E) THE SOURCE TEST SHALL CONSIST OF, BUT MAY NOT BE LIMITED TO, TESTING AT THE INLET AND THE EXHAUST OF THE OXIDIZER FOR:
 - (1) VOLATILE ORGANIC COMPOUNDS (VOC), IN PPMV, AND LBS/HR
 - (2) VOC DESTRUCTION EFFICIENCY
 - (3) OXIDES OF NITROGEN (NO_x) IN PPMV AND LBS/HR (OXIDIZER EXHAUST ONLY)
 - (4) CARBON MONOXIDE (CO) IN PPMV AND LBS/HR (OXIDIZER EXHAUST ONLY)
 - (5) VOC COLLECTION EFFICIENCY PER EPA METHOD 204 DESIGN CRITERIA
 - (6) OXYGEN CONTENT
 - (7) MOISTURE CONTENT

FACILITY PERMIT TO OPERATE IPS CORP

- (8) FLOW RATE
(9) TEMPERATURE
- F) THE SOURCE TEST SHALL BE CONDUCTED WHILE THE OXIDIZER IS OPERATING AT A TEMPERATURE OF NOT LESS THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THE PERMIT. IF THE OPERATING TEMPERATURE DURING THE SOURCE TEST IS GREATER THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THE PERMIT, THE MINIMUM OPERATING TEMPERATURE MAY BE INCREASED AT THE TIME A PERMIT TO OPERATE IS ISSUED TO REFLECT THE OPERATING TEMPERATURE DURING THE SOURCE TEST. IN ADDITION, THE USAGE OF ALL VOC-CONTAINING MATERIALS (PRIMERS, ADHESIVES, ETC.) AND OPERATING TEMPERATURE IN THE COMBUSTION CHAMBER SHALL BE RECORDED DURING THE TEST.
- G) IN ADDITION TO THE TEST DURING NORMAL OPERATION, A SOURCE TEST FOR NO_x AND CO EMISSIONS SHALL ALSO BE CONDUCTED DURING THE START-UP OF THE OXIDIZER BEFORE THE PROCESS AIR STREAM FROM THE FILLING OPERATIONS IS INTRODUCED INTO THE OXIDIZER.
- H) A WRITTEN NOTICE OF THE SOURCE TESTS SHALL BE SUBMITTED TO THE DISTRICT AT LEAST 14 DAYS PRIOR TO THE SOURCE TESTING DATE SO THAT AN OBSERVER FROM THE DISTRICT MAY BE PRESENT.
- I) TWO COMPLETE COPIES OF THE SOURCE TEST REPORT SHALL BE SUBMITTED TO THE DISTRICT WITHIN 45 DAYS AFTER THE SOURCE TEST DATE UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT. THE SOURCE TEST REPORT SHALL INCLUDE, BUT MAY NOT BE LIMITED TO, ALL TESTING DATA REQUIRED BY THIS CONDITION.
- J) A TESTING LABORATORY CERTIFIED BY THE CALIFORNIA AIR RESOURCES BOARD IN THE REQUIRED TEST METHODS FOR CRITERIA POLLUTANTS TO BE MEASURED, AND IN COMPLIANCE WITH DISTRICT RULE 304 (NO CONFLICT OF INTEREST) SHALL CONDUCT THE TEST.
- K) SAMPLING FACILITIES SHALL COMPLY WITH THE DISTRICT GUIDELINES FOR CONSTRUCTION OF SAMPLING AND TESTING FACILITIES, PURSUANT TO RULE 217.
[RULE 1303(a)(1)-BACT]
- 12) THE OWNER OR OPERATOR OF THIS EQUIPMENT SHALL SUBMIT THE RESULTS OF ALL PERLIMINARY TESTS THAT ARE CONDUCTED ON THIS EQUIPMENT FOR INFORMATIONAL PURPOSES TO THE DISTRICT WITHIN 45 DAYS AFTER THE TESTING DATE UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

- 13) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

FACILITY PERMIT TO OPERATE IPS CORP

- A) VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B) TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C) HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A) STACK OR EMISSION POINT IDENTIFICATION;
- B) DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C) DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D) VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

- 14) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409

FACILITY PERMIT TO OPERATE IPS CORP

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

[RULE 3004(a)(4)]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE IPS CORP

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS