



South Coast Air Quality Management District

21865 Copley Drive, Diamond Bar, CA 91765-4178
(909) 396-2000 • www.aqmd.gov

July 17, 2015

Mr. Kevin Austin
Senior Environmental Engineer
California Steel Industries, Inc.
14000 San Bernardino Avenue
Fontana, CA 92335

SUBJECT: RECLAIM/Title V Facility Permit, I.D. No. 046268

Dear Mr. Austin:

Please find the revised Title Page, Table of Contents, and Section H of your RECLAIM/Title V Facility Permit. The revised sections reflect the approval of the permit revision requested in your Application Nos. 573201 and 575450. The proposed revision under Application No. 573201 was submitted to EPA for a 45-day review on May 27, 2015 and EPA completed their review with no comments. This permit revision includes replacement of 22 burners in the Reducing Furnace. The proposed revision under Application No. 575453 was submitted to EPA for a 45-day review on June 17, 2015 and EPA completed their review with no comments. This proposed revision includes the replacement of two Dust Collectors.

Equipment	Application No.	Device No.	Permit Type
Reducing Furnace, Zones 6 & 7	573200	D82	Permit to Construct
Dust Collector	575450	C244	Permit to Construct
Dust Collector	575452	C245	Permit to Construct

Even though EPA has concluded their review early for the Dust Collectors, the 60-day period for the public to petition the Administrator to object to the permit begins the day after the EPA's 45-day review period ends on August 4, 2015.

Please review the attached sections carefully. Insert the attached section into your Facility Permit and discard earlier versions. Questions concerning changes to your permit should be directed to Ms. Monica Fernandez-Neild at 909.396.2202.

Very truly yours,

Mohan Balagopalan
Sr. Air Quality Engineering Manager
Mechanical, Chemical and Ports Permitting

MB:mfn
Enclosure

c: Gerardo Rios, EPA Region IX (R9Airpermits_sc@epa.gov)
Cher Snyder, Compliance



FACILITY PERMIT TO OPERATE


**CALIFORNIA STEEL INDUSTRIES INC
14000 SAN BERNARDINO AVE
FONTANA, CA 92335**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By 
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	5	02/01/2011
B	RECLAIM Annual Emission Allocation	24	01/01/2015
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	41	06/17/2014
E	Administrative Conditions	9	01/01/2001
F	RECLAIM Monitoring and Source Testing Requirements	6	01/01/2000
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	7	01/01/2000
H	Permit To Construct and Temporary Permit to Operate	41	07/17/2015
I	Compliance Plans & Schedules	3	01/01/2000
J	Air Toxics	2	02/01/2011
K	Title V Administration	2	02/01/2011
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	3	01/01/2000
B	Rule Emission Limits	2	02/01/2011



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 3: STEEL ANNEALING OPERATION					
FURNACE, ANNEALING, PREHEATER SECTION, NATURAL GAS, ELECTRIC FURNACE COMPANY, WITH 32 BURNERS TOTAL, CONTINUOUS GALVANIZING LINE NO. 1, 63.84 MMBTU/HR A/N: 573200 Permit to Construct Issued: 07/17/15	D81		NOX: MAJOR SOURCE**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	A63.7, B59.4, C1.26, D82.1, E71.1
FURNACE, REDUCING SECTION, NATURAL GAS, ELECTRIC FURNACE COMPANY, NO. 1 CONTINUOUS GALVANIZING LINE, 32.671 MMBTU/HR WITH A/N: 573200 Permit to Construct Issued: 07/17/15 BURNER, NATURAL GAS, NORTH AMERICAN MFG CO, MODEL 4725-2-E, 127 TOTAL; 0.233 MMBTU/HR BURNER, NATURAL GAS, ECLIPSE, MODEL SER600-VCO, 22 TOTAL; 0.14 MMBTU/HR	D82		NOX: LARGE SOURCE**	CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 101.4 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	A63.7, C1.26, D29.1
FURNACE, ANNEALING SECTION, NATURAL GAS, ELECTRIC FURNACE COMPANY, WITH 30 BURNERS TOTAL, CONTINUOUS GALVANIZING LINE NO. 1, 24.369 MMBTU/HR A/N: 573200 Permit to Construct Issued: 07/17/15	D83		NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 101.4 PPMV NATURAL GAS (3) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	C1.3, D12.4

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 3: STEEL ANNEALING OPERATION					
FURNACE, CHEM TREAT SECTION, GALVINIZING, NATURAL GAS, 1 MMBTU/HR A/N: 573200 Permit to Construct Issued: 07/17/15	D84		NOX: PROCESS UNIT**	CO: 2000 PPMV NATURAL GAS (5) [RULE 407, 4-2-1982]; NOX: 130 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409, 8-7-1981]	D323.1
Process 11: PIPE MILL					
PLASMA ARC CUTTER, PRIMARY CROPPER, HYPER THERM, MODEL POWERMAX 125, EACH 21.9 KW, 2 TOTAL A/N: 570717 Permit to Construct Issued: 03/24/15	D240	C241 C244			B27.2, C1.30
DUST COLLECTOR, CLEAN AIR TECH, MODEL CPC-100, 1033 SQ.FT.; 24 BAGS A/N: 563566 Permit to Construct Issued: 08/13/14	C241	D240			A72.1, D29.5, D322.3, D381.2, E102.1, H23.6, K67.1
PLASMA ARC CUTTER, REWORK CROPPER, HYPER THERM, MODEL POWERMAX 125, EACH 21.9 KW, 2 TOTAL A/N: 570718 Permit to Construct Issued: 03/24/15	D242	C243 C245			B27.2, C1.30
DUST COLLECTOR, CLEAN AIR TECH, MODEL CPC-100, 1033 SQ.FT.; 24 BAGS A/N: 563568 Permit to Construct Issued: 08/13/14	C243	D242			A72.1, D29.5, D322.3, D381.2, E102.1, H23.6, K67.1

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
 CALIFORNIA STEEL INDUSTRIES INC**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions* And Requirements	Conditions
Process 11: PIPE MILL					
DUST COLLECTOR, US AIR FILTRATION, MODEL 4DCP-16-13.8, 4064 SQ.FT.; 16 BAGS A/N: 575450 Permit to Construct Issued: 07/17/15	C244	D240			A72.1, D29.5, D322.3, D381.2, E102.1, H23.6, K67.1
DUST COLLECTOR, US AIR FILTRATION, MODEL 4DCP-16-13.8, 4064 SQ.FT.; 16 BAGS A/N: 575452 Permit to Construct Issued: 07/17/15	C245	D242			A72.1, D29.5, D322.3, D381.2, E102.1, H23.6, K67.1

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5) (5A) (5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See section J for NESHAP/MACT requirements
 ** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.



**FACILITY PERMIT TO OPERATE
CALIFORNIA STEEL INDUSTRIES INC**

SECTION H: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**



**FACILITY PERMIT TO OPERATE
CALIFORNIA STEEL INDUSTRIES INC**

SECTION H: DEVICE ID INDEX

Device Index For Section H			
Device ID	Section H Page No.	Process	System
D81	1	3	0
D82	1	3	0
D83	1	3	0
D84	2	3	0
D240	2	11	0
C241	2	11	0
D242	2	11	0
C243	2	11	0
C244	3	11	0
C245	3	11	0



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F10.1 Material(s) that contain the following compound(s) shall not be used in this facility;

0.004 percent or more of arsenic and 0.002 percent or more of cadmium by weight

No scrap other than clean non-ferrous scrap or rerun scrap shall be melted at this facility

[RULE 1407, 7-8-1994]

F14.1 The operator shall not use diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

PROCESS CONDITIONS

P28.1 Except for diesel transfers, Phase I vapor recovery systems shall be in full operation whenever fuel is being transferred into storage tanks.

Except for diesel transfers, Phase II vapor recovery systems shall be in full operation whenever fuel is being transferred into motor vehicles, as defined in Rule 461.

All Phase I and Phase II vapor recovery equipment at this facility shall be installed, operated and maintained to meet all California Air Resources Board certification requirements.

[RULE 461, 6-3-2005; RULE 461, 4-6-2012; RULE 461, Balance Conditions, 1-9-2004;
RULE 461, OPW Phase I EVR Conditions, 6-3-2005]

[Processes subject to this condition : 15]



**FACILITY PERMIT TO OPERATE
CALIFORNIA STEEL INDUSTRIES INC**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

DEVICE CONDITIONS

A. Emission Limits

A63.7 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
ROG	Less than or equal to 120 LBS IN ANY ONE MONTH
SOX	Less than or equal to 150 LBS IN ANY ONE MONTH
CO	Less than or equal to 52110 LBS IN ANY ONE MONTH
PM10	Less than or equal to 360 LBS IN ANY ONE MONTH

For the purposes of this condition, the limit(s) shall be based on the total combined emissions from equipment Preheat Section, device D81, and Reducing Section, device D82.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D81, D82]

A72.1 The operator shall maintain this equipment to achieve a minimum overall control efficiency of 99 percent for PM10 during the normal operation of the equipment it vents.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 9-10-2010]

[Devices subject to this condition : C241, C243, C244, C245]

B. Material/Fuel Type Limits



**FACILITY PERMIT TO OPERATE
CALIFORNIA STEEL INDUSTRIES INC**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

B27.2 The operator shall not use materials containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401 (except for those compounds listed below), as amended 09/10/2010.

COMPOUND	CAS NO.	Weight %
CHROMIUM	18540-29-9	0.10
COPPER	7440-50-8	0.15
MANGANESE	7439-96-5	1.65
NICKLE	7440-02-0	0.10

[RULE 1401, 9-10-2010]

[Devices subject to this condition : D240, D242]

B59.4 The operator shall not use the following material(s) in this device :

metal contaminated with rubber, plastics, paper, rags, oil, grease, or similar smoke-producing material

fluorides, chlorine, or aluminum chloride

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition : D81]

C. Throughput or Operating Parameter Limits

C1.3 The operator shall limit the heat input to no more than 23000 MM Btu in any one year.

The purpose(s) of this condition is to ensure that this equipment qualifies as a process unit.

[RULE 2012, 5-6-2005]



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D83]

- C1.26 The operator shall limit the fuel usage to no more than 48.571428 MM cubic feet in any one calendar month.

To comply with this condition, the operator shall install and maintain a(n) non-resettable totalizing fuel flow meter to accurately indicate the fuel usage from the fuel supply line.

This limit shall be based on the total combined limit for equipment devices, D81 and D82 (Preheat and Reducing Sections).

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D81, D82]

- C1.30 The operator shall limit the throughput to no more than 1444 in any one day.

For the purpose of this condition, throughput shall be defined as cuts of carbon steel pipe.

This limit shall be based on the total combined limit for equipment D240 and D242.

The maximum outer diameter of the carbon steel pipe shall not exceed 24 inches.

The thickness of the carbon steel pipe cut shall not exceed 0.75 inches.

The width of the Kerf shall not exceed 0.11811 inches (3 mm).

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 9-10-2010]

[Devices subject to this condition : D240, D242]

D. Monitoring/Testing Requirements

D12.4 The operator shall install and maintain a(n) non-resettable totalizing fuel flow meter to accurately indicate the fuel usage of the equipment.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 2012, 5-6-2005]

[Devices subject to this condition : D83]

D29.1 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
CO emissions	Approved District method	District-approved averaging time	Outlet
NOX emissions	Approved District method	District-approved averaging time	Outlet



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

In addition to the source test requirements of Section E of this facility permit, the facility permit holder shall submit a protocol to the SCAQMD engineer no later than 45 days prior to the proposed test date, and notify the District of the date and time of the test at least 10 days prior to the test.

The test(s) shall be conducted within 60 days after achieving maximum production rate, but no later than 180 cumulative days of operation after initial start-up.

The test shall be conducted while firing at normal production rates.

The test shall be conducted to demonstrate compliance with the NOx BACT limit of 50 ppmv at 3 percent oxygen..

Notwithstanding the requirements of Section E conditions, the source test results shall be submitted to the District no later than 60 days after the source test was conducted.

The subject of this source test are the 12 Eclipse burners of Zone 6 and 10 Eclipse burners of Zone 7.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D82]

D29.5 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
PM10 emissions	Approved District method	District-approved averaging time	Simultaneous inlet and outlet
Multiple metals	Approved District method	District-approved averaging time	Outlet
Hexavalent chromium	Approved District method	District-approved averaging time	Outlet



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

In addition to the source test requirements of Section E of this facility permit, the Facility permit holder shall submit the protocol to the SCAQMD no later than 45 days prior to the proposed test date and notify the SCAQMD of the date and time of the test at least 10 days prior to the test.

The test(s) shall be conducted within 90 days after achieving maximum production rate, but no later than 180 cumulative days of operation after initial start-up.

The test shall be conducted during normal production.

For the PM/PM10 test a minimum two different ERW pipe diameters and/or thicknesses is required.

For the multiple metals and hexavalent chrome test, only one ERW pipe diameter and thickness is required.

Notwithstanding the requirements of Section E conditions, the source test results shall be submitted to the District no later than 60 days after the source test was conducted.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C241, C243, C244, C245]

D82.1 The operator shall install and maintain a CEMS to measure the following parameters:

NOX concentration in ppmv

The CEMS shall be installed prior to start-up. The operator shall certify the CEMS within 180 days after start-up. During this 180 day period the operator shall comply with the monitoring and reporting requirements of Rule 2012(h)

[RULE 2012, 5-6-2005]

[Devices subject to this condition : D81]



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D322.3 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C241, C243, C244, C245]



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D84]

D381.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a weekly basis, at least, unless the equipment did not operate during the entire weekly period. The routine weekly inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C241, C243, C244, C245]

E. Equipment Operation/Construction Requirements

E71.1 The operator shall not conduct refining or fluxing in this equipment during steel milling process.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D81]



FACILITY PERMIT TO OPERATE CALIFORNIA STEEL INDUSTRIES INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C241, C243, C244, C245]

H. Applicable Rules

H23.6 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
PM10	District Rule	1155

[RULE 1155, 12-4-2009]

[Devices subject to this condition : C241, C243, C244, C245]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the filter media

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C241, C243, C244, C245]