

FACILITY PERMIT TO OPERATE

**MICROMETALS, INC
5615 E LA PALMA AVE
ANAHEIM, CA 92807**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By _____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE MICROMETALS, INC

TABLE OF CONTENTS

| Section | Description | Revision # | Date Issued |
|----------|--|-----------------|-------------|
| A | Facility Information | DRAFT | 04/28/2013 |
| B | RECLAIM Annual Emission Allocation | DRAFT | 04/28/2013 |
| C | Facility Plot Plan | TO BE DEVELOPED | |
| D | Facility Description and Equipment Specific Conditions | DRAFT | 04/28/2013 |
| E | Administrative Conditions | DRAFT | 04/28/2013 |
| F | RECLAIM Monitoring and Source Testing Requirements | DRAFT | 04/28/2013 |
| G | Recordkeeping and Reporting Requirements for RECLAIM Sources | DRAFT | 04/28/2013 |
| H | Permit To Construct and Temporary Permit to Operate | DRAFT | 04/28/2013 |
| I | Compliance Plans & Schedules | DRAFT | 04/28/2013 |
| J | Air Toxics | DRAFT | 04/28/2013 |
| K | Title V Administration | DRAFT | 04/28/2013 |
| Appendix | | | |
| A | NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219 | DRAFT | 04/28/2013 |
| B | Rule Emission Limits | DRAFT | 04/28/2013 |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR: MICROMETALS, INC

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION: 5615 E LA PALMA AVE
ANAHEIM, CA 92807-2109

MAILING ADDRESS: 5615 E LA PALMA AVE
ANAHEIM, CA 92807-2109

RESPONSIBLE OFFICIAL: WILLIAM KEMPER

TITLE: VICE PRESIDENT/OPERATIONS

TELEPHONE NUMBER: (714) 970-9400

CONTACT PERSON: GEORGE BRADLEY

TITLE: MFG ENGINEER

TELEPHONE NUMBER: (714) 970-9400

TITLE V PERMIT ISSUED: July 28, 2008

TITLE V PERMIT EXPIRATION DATE: July 27, 2013

| TITLE V | RECLAIM |
|---------|--|
| YES | NOx: NO SOx: NO CYCLE: 0 ZONE: INLAND |

**FACILITY PERMIT TO OPERATE
MICROMETALS, INC**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
MICROMETALS, INC**

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

FACILITY PERMIT TO OPERATE MICROMETALS, INC

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

| Application number | Permit to Operate number | Equipment description |
|--------------------|--------------------------|-----------------------------------|
| 408071 | F56443 | SPRAY BOOTH PAINT AND SOLVENT |
| 408072 | F56444 | SPRAY BOOTH PAINT AND SOLVENT |
| 300342 | D88862 | SPRAY BOOTH PAINT AND SOLVENT |
| 300343 | D88863 | SPRAY BOOTH PAINT AND SOLVENT |
| 300345 | D88865 | OVEN, DRYING |
| 300346 | D88866 | OVEN, DRYING |
| 300347 | D88867 | OVEN, DRYING |
| 405734 | F56438 | OVEN, DRYING |
| 300355 | D88645 | OTHER AGGREGATE SIZE REDUCTION |
| 300356 | D88646 | OTHER AGGREGATE SIZE REDUCTION |
| 300358 | D88648 | OTHER AGGREGATE SIZE REDUCTION |
| 300359 | D88649 | DRY FILTER (<=100 SQ FT) |
| 311541 | F16433 | OVEN, BAKING |
| 312335 | F16434 | OVEN, DRYING |
| 329735 | F16050 | OTHER AGGREGATE SIZE REDUCTION |
| 366124 | F30545 | SPRAY BOOTH PAINT AND SOLVENT |
| 369011 | F30546 | SPRAY BOOTH PAINT AND SOLVENT |
| 407877 | F56449 | THERMAL OXIDIZER, REGENERATIVE |
| 405732 | F56436 | OTHER AGGREGATE BLENDING |
| 408073 | F56445 | OTHER AGGREGATE BLENDING |
| 408074 | F56446 | OTHER AGGREGATE BLENDING |
| 408075 | F56447 | MISC MATERIALS BLENDING |
| 405733 | F56437 | MISC MATERIALS BLENDING |
| 405735 | F56439 | OVEN, DRYING |
| 405736 | F56440 | OVEN, DRYING |
| 405737 | F56441 | OVEN, DRYING |
| 405738 | F55925 | MISC MINERALS SIZE CLASSIFICATION |
| 405739 | F55934 | MISC MINERALS SIZE CLASSIFICATION |
| 405740 | F55930 | MISC MINERALS SIZE CLASSIFICATION |
| 405741 | F55931 | MISC MINERALS SIZE CLASSIFICATION |
| 405742 | F55929 | IRON ORE BLENDING |
| 405743 | F55932 | IRON ORE BLENDING |
| 405744 | F55933 | IRON ORE BLENDING |
| 405745 | F56442 | IRON ORE BLENDING |

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.
[RULE 401]
2. THE TOTAL QUANTITY OF ETHYL ALCOHOL USED IN ALL MIXERS AT THIS FACILITY SHALL NOT EXCEED 9,342 GALLONS IN ANY ONE MONTH.
[RULE 1303(b)(2)-OFFSET]
3. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE OF ALL VOC CONTAINING MATERIALS AT THIS FACILITY.
[RULE 109, 1303(b)(2)-OFFSET]
4. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]
5. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY AND SUBJECT TO DISTRICT RULES SHALL BE KEPT CURRENT, AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F56443
A/N 408071**

Equipment Description:

SPRAY BOOTH, NO. 1, BENCH-FILTER TYPE, 5'-0" W. X 3'-0" L. X 4'-0" H., WITH FOUR 20" X 20" EXHAUST FILTERS, AND ONE 3/4 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM SPRAY BOOTH NOS. 1 AND 2 UNDER APPLICATION NOS. 408071 AND 408072 COMBINED SHALL NOT EXCEED 35 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN DISTRICT RULE 1401 TABLE I WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990, OR EARLIER.
[RULE 1401]
7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THE EQUIPMENT TO VERIFY THE VOC CONTENT OF EACH MATERIAL AND VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS PER DAY. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 109
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F56444
A/N 408072**

Equipment Description:

SPRAY BOOTH, NO. 2, BENCH-FILTER TYPE, 5'-0" W. X 3'-0" L. X 4'-0" H., WITH FOUR 20" X 20" EXHAUST FILTERS, AND ONE 3/4 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUNDS (VOC) EMISSIONS FROM SPRAY BOOTH NOS. 1 AND 2 UNDER APPLICATION NOS. 408071 AND 408072 COMBINED SHALL NOT EXCEED 35 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN DISTRICT RULE 1401 TABLE I WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990, OR EARLIER.
[RULE 1401]
7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THE EQUIPMENT TO VERIFY THE VOC CONTENT OF EACH MATERIAL AND VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS IN POUNDS PER DAY. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 109
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. D88862
A/N 300342

Equipment Description:

SPRAY BOOTH, NO. 3, BENCH-FILTER TYPE, 5'-0" W. X 3'-0" L. X 4'-0" H., INSIDE DIMENSIONS, WITH FOUR 20" X 20" EXHAUST FILTERS AND ONE 3/4 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER
[RULE 1303(a)(1)-BACT]
5. THE TOTAL AMOUNT OF VOLATILE ORGANIC COMPOUND (VOC) EMITTED FROM THIS EQUIPMENT SHALL NOT EXCEED 20 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2) -OFFSET]
6. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY VOC EMISSIONS IN POUNDS. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, REDUCERS, CLEAN-UP SOLVENTS AND ANY OTHER MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401 AMENDED DECEMBER 7, 1990.
[RULE 1401]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 109
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. D88863
A/N 300343**

Equipment Description:

SPRAY BOOTH, NO. 4, BENCH-FILTER TYPE, 5'-0" W. X 3'-0" L. X 4'-0" H., INSIDE DIMENSIONS, WITH FOUR 20" X 20" EXHAUST FILTERS, AND ONE 3/4 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER
[RULE 1303(a)(1)-BACT]
5. THE TOTAL AMOUNT OF VOLATILE ORGANIC COMPOUND (VOC) EMITTED FROM THIS EQUIPMENT SHALL NOT EXCEED 20 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY DAILY VOC EMISSIONS IN POUNDS. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, REDUCERS, CLEAN-UP SOLVENTS AND ANY OTHER MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUND IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401 AMENDED DECEMBER 7, 1990.
[RULE 1401]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 109
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. D88865
A/N 300345**

Equipment Description:

OVEN, GRIEVE, MODEL NO. TBH-500, COMPANY I.D. NO. O-41, 6'-0" W. X 7'-0" L. X 5'-10" H., 175,000 BTU PER HOUR NATURAL GAS FIRED, WITH ONE 2 HP. CIRCULATING AIR FAN, AND ONE 1/2 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE COATINGS CONTAINING MORE THAN 2.3 POUNDS OF VOC PER GALLON, LESS WATER AND LESS EXEMPT SOLVENT SHALL NOT BE DRIED ABOVE 194 DEGREES FAHRENHEIT.
[RULE 401]
4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

5. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004(a)(4)]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NOx: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. D88866
A/N 300346**

Equipment Description:

OVEN, GRIEVE, MODEL NO. TBH-500, COMPANY I.D. NO. O-33, 6'-0" W. X 7'-0" L. X 5'-10" H., 175,000 BTU PER HOUR NATURAL GAS FIRED, WITH ONE 2 H.P. CIRCULATING AIR FAN AND ONE 1/2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE COATINGS CONTAINING MORE THAN 2.3 POUNDS OF VOC PER GALLON, LESS WATER AND LESS EXEMPT SOLVENT, SHALL NOT BE DRIED ABOVE 194 DEGREES FAHRENHEIT.
[RULE 401]
4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

5. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004(a)(4)]

Emissions And Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NOx: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. D88867
A/N 300347**

Equipment Description:

OVEN, GRIEVE, MODEL NO. TBH-500, COMPANY I.D. NO. O-37, 6'-0" W. X 7'-0" L. X 5'-10" H., 175,000 BTU PER HOUR NATURAL GAS FIRED, WITH ONE 2 HP. CIRCULATING AIR FAN, AND ONE 1/2 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 250 DEGREES FAHRENHEIT.
[RULE 401]
4. THE TOTAL QUANTITY OF COATINGS USED IN THE COATING OF ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 40 GALLONS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

6. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004(a)(4)]

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NOx: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F56438
A/N 405734**

Equipment Description:

OVEN, O36, GRIEVE, MODEL NO. TBH-500, SERIAL NO. 640894, 6'-0" W. X 7'-0" L. X 5'-10" H., 175,000 BTU PER HOUR NATURAL GAS FIRED, WITH ONE 2 HP. CIRCULATING FAN, AND ONE 1/2 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 401, 1303(a)(1)-BACT]
4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NO_x: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. D88645
A/N 300355**

Equipment Description:

METALLIC POWDER SCREENING AND GRINDING SYSTEM CONSISTING OF:

1. FEEDER, SMC, VIBRATING TYPE, MODEL F-010, 1/3 KVA.
2. SCREEN, S2, UNIVERSAL, VIBRATING TYPE, ¼ HP.
3. MILL, FITZ PATRICK, MODEL D, 3 HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 3,200 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

FACILITY PERMIT TO OPERATE MICROMETALS, INC

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

- 5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. D88646
A/N 300356**

Equipment Description:

METALLIC POWDER SCREENING AND GRINDING SYSTEM CONSISTING OF:

1. FEEDER, SMC, VIBRATING TYPE, MODEL F-010, 1/3 KVA.
2. SCREEN, S4, UNIVERSAL, VIBRATING TYPE, ¼ HP.
3. MILL, FITZ PATRICK, MODEL D, 3 HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 3,200 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24

FACILITY PERMIT TO OPERATE MICROMETALS, INC

- HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:
- PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. D88648
A/N 300358**

Equipment Description:

METALLIC POWDER SCREENING AND GRINDING SYSTEM CONSISTING OF:

1. FEEDER, SMC, VIBRATING TYPE, MODEL F-010, 1/3 KVA.
2. HAMMER MILL, HM1, JACOBSON, SPEEDY, 7 ½ HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
4. THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS THE HAMMER MILL IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A PERMIT TO CONSTRUCT OR PERMIT TO OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

Periodic Monitoring:

5. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER

FACILITY PERMIT TO OPERATE MICROMETALS, INC

WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
 - D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
- [RULE 3004 (a)(4)]

Emissions And Requirements:

- 6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. D88649
A/N 300359**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. VACUUM MACHINE, MILWAUKEE, 9 GALLONS, 1.2 KVA.
2. EXHAUST SYSTEM VENTING A HAMMER MILL.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]

Periodic Monitoring:

3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
 - A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004(a)(4)]

Emissions And Requirements:

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1155
PM: 0 PERCENT OPACITY, RULE 1155

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F16433
A/N 311541**

Equipment Description:

OVEN, GRIEVE, MODEL NO. TBH-500, 6'-0" W. X 7'-0" L. X 5'-10" H., 175,000 BTU PER HR, NATURAL GAS-FIRED, WITH ONE 2 HP. CIRCULATING AIR FAN, AND ONE 1/2 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401 AS AMENDED DECEMBER 7, 1990.
[RULE 1401]
4. THIS OVEN SHALL ONLY BE USED TO BAKE IRON CORES PROCESSED AT THE MIXER WHICH HAS A VALID PERMIT TO CONSTRUCT OR OPERATE FROM THE DISTRICT.
[RULE 1303(b)(2)-OFFSET]
5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

6. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY

FACILITY PERMIT TO OPERATE MICROMETALS, INC

AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
 - D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
- [RULE 3004 (a)(4)]

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NO_x: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F16434
A/N 312335**

Equipment Description:

OVEN, GRIEVE, MODEL NO. TBH-500, 6'-0" W. X 7'-0" L. X 5'-10" H., 175,000 BTU PER HR, NATURAL GAS-FIRED, WITH ONE 2 HP. CIRCULATING AIR FAN, AND ONE 1/2 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL ONLY BE USED TO CURE COATINGS APPLIED IN THE SPRAY BOOTHS WHICH HAVE A VALID PERMIT TO CONSTRUCT OR OPERATE FROM THE DISTRICT.
[RULE 1303(b)(2)-OFFSET]
4. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN RULE 1401 AS AMENDED DECEMBER 7, 1990.
[RULE 1401]
5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

6. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY

FACILITY PERMIT TO OPERATE MICROMETALS, INC

ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
 - D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
- [RULE 3004 (a)(4)]

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NOx: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F16050
A/N 329735**

Equipment Description:

METALLIC POWDER SCREENING AND GRINDING SYSTEM CONSISTING OF:

1. FEEDER, SMC, VIBRATING TYPE M, MODEL F-010, 1/3 KVA.
2. ENCLOSED SCREEN, S5, UNIVERSAL, VIBRATING TYPE, ¼ HP.
3. ENCLOSED MILL, FITZ PATRICK, MODEL D, 3 HP.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE TOTAL QUANTITY OF MATERIAL PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 6,000 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
4. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE OF MATERIALS IN POUNDS PROCESSED IN THIS EQUIPMENT. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS/HER REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]
5. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC AIR CONTAMINANTS IN DISTRICT RULE 1401 AS AMENDED DECEMBER 7, 1990.
[RULE 1401]
6. ALL HOSES AND LIDS SHALL BE SEALED AT ALL TIMES DURING OPERATION EXCEPT DURING LOADING AND UNLOADING.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. F30545
A/N 366124

Equipment Description:

SPRAY BOOTH, NO. 6, BENCH-TYPE, BLEEKER BROS., MODEL NO. BF-4-7, 4'-0" W. X 5'-2" L. X 7'-0" H., WITH FOUR 24" X 24" X 2" MGHF FILTERS, ONE 0.5-HP. EXHAUST FAN, AND ONE 18"-DIAMETER DUCT.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL AMOUNT OF VOLATILE ORGANIC COMPOUND (VOC) EMITTED FROM EQUIPMENT UNDER APPLICATIONS, NOS. 366124 AND 369011, SHALL NOT EXCEED 30 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE WITH AN EFFECTIVE DATE OF AUGUST 13, 1999, OR EARLIER, EXCEPT STYRENE AND TOLUENE.
[RULE 1401]
7. THE OPERATOR SHALL KEEP DAILY RECORDS OF VOC EMISSIONS IN ACCORDANCE WITH DISTRICT RULE 109. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 109
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F30546
A/N 369011**

Equipment Description:

SPRAY BOOTH, NO. 5, BENCH TYPE, 5'-0" W. X 3'-0" L. X 4'-0" H., WITH FOUR 20" X 20" EXHAUST FILTERS, AND ONE ¾ HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCH OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL AMOUNT OF VOLATILE ORGANIC COMPOUNDS (VOC) EMITTED FROM EQUIPMENT UNDER APPLICATIONS NOS. 366124 AND 369011, SHALL NOT EXCEED 30 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE WITH AN EFFECTIVE DATE OF AUGUST 13, 1999, OR EARLIER, EXCEPT STYRENE AND TOLUENE.
[RULE 1401]
7. THE OPERATOR SHALL KEEP DAILY RECORDS OF VOC EMISSIONS IN ACCORDANCE WITH DISTRICT RULE 109. ALL RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

Periodic Monitoring:

8. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004(a)(4)]

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004(a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 109
VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. F56449
A/N 407877

Equipment Description:

AIR POLLUTION CONTROL SYSTEM CONSISTING OF:

1. REGENERATIVE THERMAL OXIDIZER, ADWEST/AIREX CORPORATION, MODEL NO. RETOX 8.0, RTO 95, SERIAL NO. 23608 RT02148, 5'-8" W. X 19'-6" L. X 9'-0" H., 2,295,000 BTU PER HOUR NATURAL GAS FIRED, WITH TWO HEAT EXCHANGER BEDS WITH CERAMIC MEDIA, A NATURAL GAS INJECTION SYSTEM, AND ONE 7.5 HP. COMBUSTION AIR BLOWER
2. EXHAUST SYSTEM WITH ONE 40 HP. (8000 CFM) FAN VENTING MIXER NOS. M-10, M-11, AND M-31 (219 EXEMPT), M-13, M-17, M-19, M-20, M-26, M-42, AND FOUR CURING OVENS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OPERATOR SHALL OPERATE AND MAINTAIN THE REGENERATIVE THERMAL OXIDIZER ACCORDING TO THE FOLLOWING REQUIREMENTS:

THE COMBUSTION CHAMBER TEMPERATURE SHALL BE MAINTAINED AT A MINIMUM OF 1,500 DEGREES FAHRENHEIT WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.

THE OPERATOR SHALL OPERATE AND MAINTAIN A TEMPERATURE MEASURING AND RECORDING SYSTEM TO CONTINUOUSLY MEASURE AND RECORD THE COMBUSTION CHAMBER TEMPERATURE PURSUANT TO THE OPERATION AND MAINTENANCE REQUIREMENTS SPECIFIED IN 40 CFR PART 64.7. SUCH A SYSTEM SHALL HAVE AN ACCURACY OF WITHIN 1% OF THE TEMPERATURE BEING MONITORED AND SHALL BE INSPECTED, MAINTAINED, AND CALIBRATED ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS. THE TEMPERATURE INDICATING AND RECORDING SYSTEM SHALL BE IN OPERATION WHENEVER THE EQUIPMENT IT SERVES IS IN OPERATION.

FOR THE PURPOSE OF THIS CONDITION, A DEVIATION SHALL BE DEFINED AS WHEN A COMBUSTION CHAMBER TEMPERATURE OF LESS THAN 1,500 DEGREES FAHRENHEIT OCCURS DURING NORMAL OPERATION OF THE EQUIPMENT IT SERVES. THE OPERATOR SHALL REVIEW THE RECORDS OF THE COMBUSTION CHAMBER TEMPERATURE ON A DAILY BASIS TO DETERMINE IF A DEVIATION OCCURS OR SHALL INSTALL AN ALARM SYSTEM TO ALERT THE

FACILITY PERMIT TO OPERATE MICROMETALS, INC

OPERATOR WHEN A DEVIATION OCCURS.

WHENEVER A DEVIATION OCCURS, THE OPERATOR SHALL INSPECT THIS EQUIPMENT TO IDENTIFY THE CAUSE OF SUCH A DEVIATION, TAKE IMMEDIATE CORRECTIVE ACTION TO MAINTAIN THE COMBUSTION CHAMBER TEMPERATURE AT OR ABOVE 1,500 DEGREES FAHRENHEIT, AND KEEP RECORDS OF THE DURATION AND CAUSE (INCLUDING UNKNOWN CAUSE, IF APPLICABLE) OF THE DEVIATION AND THE CORRECTIVE ACTION TAKEN.

ALL DEVIATIONS SHALL BE REPORTED TO THE AQMD PURSUANT TO THE REQUIREMENTS SPECIFIED IN 40 CFR PART 64.9 AND CONDITION NOS. 22 AND 23 IN SECTION K OF THIS PERMIT. THE REPORT SHALL INCLUDE THE TOTAL OPERATING TIME OF THIS EQUIPMENT AND THE TOTAL ACCUMULATED DURATION OF ALL DEVIATIONS FOR EACH SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL SUBMIT AN APPLICATION WITH A QUALITY IMPROVEMENT PLAN (QIP) IN ACCORDANCE WITH 40 CFR PART 64.8 TO THE AQMD IF AN ACCUMULATION OF DEVIATIONS EXCEEDS 5 PERCENT DURATION OF THIS EQUIPMENT'S TOTAL OPERATING TIME FOR ANY SEMI-ANNUAL REPORTING PERIOD SPECIFIED IN CONDITION NO. 23 IN SECTION K OF THIS PERMIT. THE REQUIRED QIP SHALL BE SUBMITTED TO THE AQMD WITHIN 90 CALENDAR DAYS AFTER THE DUE DATE FOR THE SEMI-ANNUAL MONITORING REPORT.

THE OPERATOR SHALL INSPECT AND MAINTAIN ALL COMPONENTS OF THIS EQUIPMENT ON AN ANNUAL BASIS IN ACCORDANCE WITH THE MANUFACTURER'S SPECIFICATIONS.

THE OPERATOR SHALL KEEP ADEQUATE RECORDS IN A FORMAT THAT IS ACCEPTABLE TO THE AQMD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE REQUIREMENTS SPECIFIED IN THIS CONDITION AND 40 CFR PART 64.9 FOR A MINIMUM OF FIVE YEARS.
[RULE 1303(a)(1)-BACT, 1303(b)(2)-OFFSET, 3004(a)(4), 40CFR Part 64]

4. THIS EQUIPMENT SHALL BE MAINTAINED AND OPERATED AT A MINIMUM OVERALL VOC CONTROL EFFICIENCY (COLLECTION AND DESTRUCTION) OF 93% WHEN THE BASIC EQUIPMENT IT SERVES IS IN OPERATION.
[RULE 1303(a)(1)-BACT]
5. THE OPERATOR SHALL KEEP ADEQUATE RECORDS PURSUANT TO THE REQUIREMENTS OF RULE 109. SUCH RECORDS SHALL BE RETAINED FOR A PERIOD OF FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS/HER REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]
6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT SOURCE TEST(S) IN ACCORDANCE WITH THE FOLLOWING SPECIFICATIONS:

FACILITY PERMIT TO OPERATE MICROMETALS, INC

- A. THE TEST SHALL BE CONDUCTED AT LEAST ONCE DURING THE LIFE OF THE PERMIT.
 - B. THE TEST SHALL BE CONDUCTED NO LATER THAN JULY 28, 2017 UNLESS OTHERWISE APPROVED IN WRITING BY THE DISTRICT.
 - C. THE TEST SHALL BE CONDUCTED TO DETERMINE THE VOC EMISSIONS USING AN APPROVED DISTRICT METHOD TO DEMONSTRATE COMPLIANCE WITH ALL APPLICABLE PERMIT CONDITION(S), RULES AND REGULATIONS.
 - D. THE SOURCE TEST SHALL BE CONDUCTED WHILE THE OXIDIZER IS OPERATING AT A TEMPERATURE OF NOT LESS THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT. IF THE OPERATING TEMPERATURE DURING THE SOURCE TEST IS GREATER THAN THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT, THE MINIMUM OPERATING TEMPERATURE SPECIFIED IN THIS PERMIT MAY BE INCREASED TO REFLECT THE OPERATING TEMPERATURE DURING THE SOURCE TEST.
 - E. THE OPERATOR SHALL COMPLY WITH ADMINISTRATIVE CONDITIONS NOs. 8, 9, AND 10 OF SECTION E OF THIS FACILITY PERMIT.
 - F. THE OPERATOR SHALL SUBMIT TWO COMPLETE COPIES OF THE SOURCE TEST REPORT SPECIFIED IN CONDITION NO. 9 OF SECTION E OF THIS FACILITY PERMIT TO THE DISTRICT ENGINEERING AND COMPLIANCE DIVISION. THE ENGINEERING COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, COATING, PRINTING AND AEROSPACE OPERATIONS, ATTN: AIR QAULITY AND COMPLIANCE SUPERVISOR, 21865 COPLEY DRIVE, DIAMOND BAR, CA 91765. THE COMPLIANCE COPY OF THE REPORT SHALL BE SENT TO: SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, P.O. BOX 4941, DIAMOND BAR, CA 91765
- [RULE 3004(a)(4)]

Emissions And Requirements:

- 8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:
 - CO: 2000 PPMV, RULE 407
 - PM: 0.1 GR/SCF, RULE 409
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - NOx: 60 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F56436
A/N 405732**

Equipment Description:

METALLIC POWDER MIXING SYSTEM CONSISTING OF:

1. HOPPER, 3'-0" W. X 3'-0" L. X 3'-0" H.
2. IRON ORE MIXER, M17, SCOTT, 75 CUBIC FEET CAPACITY, WITH A HOT WATER JACKET VENTED TO AN AIR POLLUTION CONTROL SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. NO VOC-CONTAINING MATERIALS SHALL BE USED IN THIS MIXER EXCEPT ETHYL ALCOHOL AND BINDER.
[RULE 1303(b)(2)-OFFSET]
4. DURING CHARGING, MIXING AND DISCHARGING OPERATIONS, THE MIXER SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. DUST CONTAINMENT SOCKS SHALL BE USED AT ALL TRANSFER POINTS WHEN MATERIAL IS BEING LOADED AND UNLOADED.
[RULE 1303(a)(1)-BACT]
6. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

7. RECORDS SHALL BE KEPT TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT. RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

8. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 442

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F56445
A/N 408073**

Equipment Description:

METTALIC POWDER MIXING SYSTEM CONSISTING OF:

1. HOPPER, 3'-0" W. X 3'-0" L. X 3'-0" H.
2. IRON ORE MIXER, M13, SCOTT, 75 CUBIC FEET CAPACITY, WITH A HOT WATER JACKET, AND ONE 2 HP. TIPPING MOTOR VENTED TO AN AIR POLLUTION CONTROL SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. NO VOC-CONTAINING MATERIALS SHALL BE USED IN THIS MIXER EXCEPT ETHYL ALCOHOL AND BINDER.
[RULE 1303(b)(2)-OFFSET]
4. DURING CHARGING, MIXING AND DISCHARGING OPERATIONS, THE MIXER SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. DUST CONTAINMENT SOCKS SHALL BE USED AT ALL TRANSFER POINTS WHEN MATERIAL IS BEING LOADED AND UNLOADED.
[RULE 1303(a)(1)-BACT]
6. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

7. RECORDS SHALL BE KEPT TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT. RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

8. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 442

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F56446
A/N 408074**

Equipment Description:

METALLIC POWDER MIXING SYSTEM CONSISTING OF:

1. HOPPER, 3'-0" W. X 3'-0" L. X 3'-0" H.
2. MIXER, M19, J.H. DAY, 45 CUBIC FEET CAPACITY, WITH A HOT WATER HEATED, AND ONE 15 HP. MOTOR VENTED TO AN AIR POLLUTION CONTROL SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. NO VOC-CONTAINING MATERIALS SHALL BE USED IN THIS MIXER EXCEPT ETHYL ALCOHOL AND BINDER.
[RULE 1303(b)(2)-OFFSET]
4. DURING CHARGING, MIXING AND DISCHARGING OPERATIONS, THE MIXER SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. THE MAXIMUM QUANTITY OF POWDER CHARGED TO THIS EQUIPMENT SHALL NOT EXCEED 16,000 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. DUST CONTAINMENT SOCKS SHALL BE USED AT ALL TRANSFER POINTS WHEN MATERIAL IS BEING LOADED AND UNLOADED.
[RULE 1303(a)(1)-BACT]
7. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

8. RECORDS SHALL BE KEPT TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT. RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

9. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:
- VOC: RULE 442
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F56447
A/N 408075**

Equipment Description:

METALLIC POWDER MIXING SYSTEM CONSISTING OF:

1. HOPPER, 3'-0" W. X 3'-0" L. X 3'-0" H.
2. MIXER, M20, J.H. DAY, 45 CUBIC FEET CAPACITY, WITH A HOT WATER JACKET, AND ONE 15 HP. MOTOR VENTED TO AN AIR POLLUTION CONTROL SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. NO VOC-CONTAINING MATERIALS SHALL BE USED IN THIS MIXER EXCEPT ETHYL ALCOHOL AND BINDER.
[RULE 1303(b)(2)-OFFSET]
4. DURING CHARGING, MIXING AND DISCHARGING OPERATIONS, THE MIXER SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. THE MAXIMUM QUANTITY OF POWDER CHARGED TO THIS EQUIPMENT SHALL NOT EXCEED 16,000 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. DUST CONTAINMENT SOCKS SHALL BE USED AT ALL TRANSFER POINTS WHEN MATERIAL IS BEING LOADED AND UNLOADED.
[RULE 1303(a)(1)-BACT]
7. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

8. RECORDS SHALL BE KEPT TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT. RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

9. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:
- VOC: RULE 442
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F56437
A/N 405733**

Equipment Description:

METTALIC POWDER MIXING SYSTEM CONSISTING OF:

1. HOPPER, 3'-0" W. X 3'-0" L. X 3'-0" H.
2. IRON ORE MIXER, M26, SCOTT, 75 CUBIC FEET CAPACITY, WITH A HOT WATER JACKET VENTED TO AN AIR POLLUTION CONTROL SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. NO VOC-CONTAINING MATERIALS SHALL BE USED IN THIS MIXER EXCEPT ETHYL ALCOHOL AND BINDER.
[RULE 1303(b)(2)-OFFSET]
4. DURING CHARGING, MIXING AND DISCHARGING OPERATIONS, THE MIXER SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
5. DUST CONTAINMENT SOCKS SHALL BE USED AT ALL TRANSFER POINTS WHEN MATERIAL IS BEING LOADED AND UNLOADED.
[RULE 1303(a)(1)-BACT]
6. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

7. RECORDS SHALL BE KEPT TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT. RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

8. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

9. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 442
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. F56439
A/N 405735

Equipment Description:

OVEN, O57, GRIEVE, MODEL NO. TBH-500, SERIAL NO. 641340, 6'-0" W. X 7'-0" L. X 5'-10" H., 175,000 BTU PER HOUR NATURAL GAS FIRED, WITH ONE 2 HP. CIRCULATING FAN, AND ONE 1/2 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 401, 1303(a)(1)-BACT]
4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NO_x: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. F56440
A/N 405736

Equipment Description:

OVEN, O47, GRIEVE, MODEL NO. TBH-500, SERIAL NO. 641051, 6'-0" W. X 7'-0" L. X 5'-10" H., 175,000 BTU PER HOUR NATURAL GAS FIRED, WITH ONE 2 HP. CIRCULATING FAN, AND ONE 1/2 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 401, 1303(a)(1)-BACT]
4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NO_x: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. F56441
A/N 405737

Equipment Description:

OVEN, O61, GRIEVE, MODEL NO. TBH-500, SERIAL NO. 641413, 6'-0" W. X 7'-0" L. X 5'-10" H., 175,000 BTU PER HOUR NATURAL GAS FIRED, WITH ONE 2 HP. CIRCULATING FAN, AND ONE 1/2 HP. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 401, 1303(a)(1)-BACT]
4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF RULE 1147. PRIOR TO MODIFICATION OF THIS EQUIPMENT TO COME INTO COMPLIANCE WITH THE EMISSION LIMIT OF THIS RULE, THE OPERATOR SHALL SUBMIT AN APPLICATION AND RECEIVE APPROVAL FOR CONSTRUCTION OR MODIFICATION OF THE EQUIPMENT.
[RULE 1147]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
NO_x: 30 PPMV, RULE 1147

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. F55925
A/N 405738

Equipment Description:

SIFTER, S8, MIDWESTERN, WITH ONE 2.5 HP. MOTOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE SIFTER AND ALL HOPPERS SHALL BE KEPT COVERED WHEN THIS EQUIPMENT IS IN OPERATION.
[RULE 401, 1303(a)(1)-BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F55934
A/N 405739**

Equipment Description:

SIFTER, S9, SWECO, WITH ONE 2.5 HP. MOTOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE SIFTER AND ALL HOPPERS SHALL BE KEPT COVERED WHEN THIS EQUIPMENT IS IN OPERATION.
[RULE 401, 1303(a)(1)-BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:
 - A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F55930
A/N 405740**

Equipment Description:

SIFTER, S15, MIDWESTERN, WITH ONE 2.5 HP. MOTOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE SIFTER AND ALL HOPPERS SHALL BE KEPT COVERED WHEN THIS EQUIPMENT IS IN OPERATION.
[RULE 401, 1303(a)(1)-BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:
 - A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

- 5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:
 - PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
 - PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F55931
A/N 405741**

Equipment Description:

SIFTER, S16, MIDWESTERN, WITH ONE 2.5 HP. MOTOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE SIFTER AND ALL HOPPERS SHALL BE KEPT COVERED WHEN THIS EQUIPMENT IS IN OPERATION.
[RULE 401, 1303(a)(1)-BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:
 - A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. F55929
A/N 405742

Equipment Description:

DOUBLE CONE BLENDER, M30, P-K, 20 CUBIC FEET CAPACITY, WITH ONE 10 HP. MOTOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) SHALL NOT BE USED IN THIS BLENDER.
[RULE 1303(b)(2)-OFFSET]
4. DUST CONTAINMENT SOCKS SHALL BE USED AT ALL TRANSFER POINTS WHEN MATERIAL IS BEING LOADED AND UNLOADED.
[RULE 1303(a)(1)-BACT]
5. RECORDS SHALL BE KEPT TO VERIFY COMPLIANCE WITH CONDITIONS 3. RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

6. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING

FACILITY PERMIT TO OPERATE MICROMETALS, INC

TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1155
PM: 0 PERCENT OPACITY, RULE 1155

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

**Permit No. F55932
A/N 405743**

Equipment Description:

DOUBLE CONE BLENDER, M33, GEMCO, 66 CUBIC FEET CAPACITY, WITH ONE 25 HP. MOTOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) SHALL NOT BE USED IN THIS BLENDER.
[RULE 1303(b)(2)-OFFSET]
4. DUST CONTAINMENT SOCKS SHALL BE USED AT ALL TRANSFER POINTS WHEN MATERIAL IS BEING LOADED AND UNLOADED.
[RULE 1303(a)(1)-BACT]
5. RECORDS SHALL BE KEPT TO VERIFY COMPLIANCE WITH CONDITIONS 3. RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

6. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING

FACILITY PERMIT TO OPERATE MICROMETALS, INC

TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1155
PM: 0 PERCENT OPACITY, RULE 1155

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. F55933
A/N 405744

Equipment Description:

DOUBLE CONE BLENDER, M34, ABBE, 60 CUBIC FEET CAPACITY, WITH ONE 10 HP. MOTOR.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) SHALL NOT BE USED IN THIS BLENDER.
[RULE 1303(b)(2)-OFFSET]
4. DUST CONTAINMENT SOCKS SHALL BE USED AT ALL TRANSFER POINTS WHEN MATERIAL IS BEING LOADED AND UNLOADED.
[RULE 1303(a)(1)-BACT]
5. RECORDS SHALL BE KEPT TO VERIFY COMPLIANCE WITH CONDITIONS 3. RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

6. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A SEMI-ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE SEMI-ANNUAL PERIOD. THE ROUTINE SEMI-ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING

FACILITY PERMIT TO OPERATE MICROMETALS, INC

TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.

[RULE 3004 (a)(4)]

Emissions And Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1155
PM: 0 PERCENT OPACITY, RULE 1155

FACILITY PERMIT TO OPERATE MICROMETALS, INC

PERMIT TO OPERATE

Permit No. F56442
A/N 405745

Equipment Description:

METALLIC POWDER MIXING SYSTEM CONSISTING OF:

1. HOPPER, 3'-0" W. X 3'-0" L. X 3'-0" H.
2. IRON ORE MIXER, M42, SCOTT, 45 CUBIC FEET CAPACITY, WITH A HOT WATER JACKET AND ONE 30 HP. MOTOR, VENTED TO AN AIR POLLUTION CONTROL SYSTEM.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE MAXIMUM QUANTITY OF BINDER CHARGED TO THIS MIXER SHALL NOT EXCEED 6,000 POUNDS IN ANY ONE CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
4. THE MAXIMUM VOLATILE ORGANIC COMPOUND (VOC) CONTENT IN THE BINDER USED IN THIS EQUIPMENT SHALL NOT EXCEED 29.5% BY WEIGHT.
[RULE 1303(b)(2)-OFFSET]
5. THE MAXIMUM FORMALDEHYDE CONTENT IN THE BINDER USED IN THIS EQUIPMENT SHALL NOT EXCEED 0.2% BY WEIGHT.
[RULE 1401]
6. THE MAXIMUM QUANTITY OF POWDER CHARGED TO THIS EQUIPMENT SHALL NOT EXCEED 24,000 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
7. NO VOC-CONTAINING MATERIALS SHALL BE USED IN THIS MIXER EXCEPT ETHYL ALCOHOL AND BINDER.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

8. DURING CHARGING, MIXING AND DISCHARGING OPERATIONS, THE MIXER SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
9. DUST CONTAINMENT SOCKS SHALL BE USED AT ALL TRANSFER POINTS WHEN MATERIAL IS BEING LOADED AND UNLOADED.
[RULE 1303(a)(1)-BACT]
10. THIS EQUIPMENT SHALL BE VENTED TO AIR POLLUTION CONTROL EQUIPMENT FOR VOC WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT TO CONSTRUCT OR OPERATE BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
11. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC COMPOUNDS IDENTIFIED IN RULE 1401 TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990, OR EARLIER, WITH THE EXCEPTION OF FORMALDEHYDE.
[RULE 1401]
12. RECORDS SHALL BE KEPT TO VERIFY COMPLIANCE WITH THE CONDITIONS ON THIS PERMIT. RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS, AND SHALL BE MADE AVAILABLE UPON REQUEST OF THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

13. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS.

IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE HOUR, THE OPERATOR SHALL VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST, AND EITHER:

- A. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- B. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO THE DISTRICT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

FACILITY PERMIT TO OPERATE MICROMETALS, INC

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions And Requirements:

14. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 442
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

[RULE 3004 (a) (4)]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE MICROMETALS, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109

FACILITY PERMIT TO OPERATE MICROMETALS, INC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, BOILER, > 400,000 BTU/HR BUT < 2 MMBTU/HR.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

PM: 0.1 GR/SCF, RULE 409
NOX: 30 PPMV, RULE 1146.2
CO: 400 PPMV, RULE 1146.2
CO: 2000 PPMV, RULE 407

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statutes of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]
7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]
 - d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO₂) and be averaged over 15 consecutive minutes; [407]
 - e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO₂) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION E: ADMINISTRATIVE CONDITIONS

- f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O₂) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]
8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
- a. Brief description of the equipment tested.
 - b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).
9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]
- a. The results of the source test.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION E: ADMINISTRATIVE CONDITIONS

- b. Brief description of the equipment tested.
 - c. Operating conditions under which the test was performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Field and laboratory data forms, strip charts and analyses.
 - f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]
11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

**FACILITY PERMIT TO OPERATE
MICROMETALS, INC**

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
MICROMETALS, INC**

**SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR
RECLAIM SOURCES**

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
MICROMETALS, INC**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

See Section D of this permit for any Permit to Construct issued to this facility.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

**FACILITY PERMIT TO OPERATE
MICROMETALS, INC**

SECTION J: AIR TOXICS

NOT APPLICABLE

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]

15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]

16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

| RULE SOURCE | Adopted/Amended Date | FEDERAL Enforceability |
|------------------------|-----------------------------|-------------------------------|
| RULE 109 | 5-2-2003 | Federally enforceable |
| RULE 1107 | 1-6-2006 | Federally enforceable |
| RULE 1113 | 6-3-2011 | Non federally enforceable |
| RULE 1113 | 7-13-2007 | Federally enforceable |
| RULE 1146.2 | 5-5-2006 | Federally enforceable |
| RULE 1147 | 9-9-2011 | Non federally enforceable |
| RULE 1155 | 12-4-2009 | Non federally enforceable |
| RULE 1171 | 2-1-2008 | Federally enforceable |
| RULE 1171 | 5-1-2009 | Non federally enforceable |
| RULE 118 | 12-7-1995 | Non federally enforceable |
| RULE 1303(a)(1)-BACT | 12-6-2002 | Non federally enforceable |
| RULE 1303(a)(1)-BACT | 5-10-1996 | Federally enforceable |
| RULE 1303(b)(2)-Offset | 12-6-2002 | Non federally enforceable |
| RULE 1303(b)(2)-Offset | 5-10-1996 | Federally enforceable |
| RULE 1401 | 12-7-1990 | Non federally enforceable |
| RULE 1401 | 8-13-1999 | Non federally enforceable |
| RULE 204 | 10-8-1993 | Federally enforceable |
| RULE 217 | 1-5-1990 | Federally enforceable |
| RULE 219 | 6-1-2007 | Non federally enforceable |
| RULE 219 | 9-4-1981 | Federally enforceable |
| RULE 3002 | 11-14-1997 | Federally enforceable |
| RULE 3002 | 11-5-2010 | Non federally enforceable |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

SECTION K: TITLE V Administration

| RULE SOURCE | Adopted/Amended Date | FEDERAL Enforceability |
|-------------------------------------|-----------------------------|-------------------------------|
| RULE 3003 | 11-14-1997 | Federally enforceable |
| RULE 3003 | 11-5-2010 | Non federally enforceable |
| RULE 3004 | 12-12-1997 | Federally enforceable |
| RULE 3004(a)(4)-Periodic Monitoring | 12-12-1997 | Federally enforceable |
| RULE 3005 | 11-14-1997 | Federally enforceable |
| RULE 3005 | 11-5-2010 | Non federally enforceable |
| RULE 3007 | 10-8-1993 | Federally enforceable |
| RULE 304 | 6-1-2012 | Non federally enforceable |
| RULE 401 | 11-9-2001 | Non federally enforceable |
| RULE 401 | 3-2-1984 | Federally enforceable |
| RULE 402 | 5-7-1976 | Non federally enforceable |
| RULE 403 | 4-2-2004 | Federally enforceable |
| RULE 403 | 6-3-2005 | Non federally enforceable |
| RULE 404 | 2-7-1986 | Federally enforceable |
| RULE 405 | 2-7-1986 | Federally enforceable |
| RULE 407 | 4-2-1982 | Federally enforceable |
| RULE 408 | 5-7-1976 | Federally enforceable |
| RULE 409 | 8-7-1981 | Federally enforceable |
| RULE 430 | 7-12-1996 | Non federally enforceable |
| RULE 442 | 12-15-2000 | Federally enforceable |
| RULE 480 | 10-7-1977 | Federally enforceable |
| RULE 481 | 1-11-2002 | Federally enforceable |
| RULE 701 | 6-13-1997 | Federally enforceable |
| 40CFR Part 64 | 10-22-1997 | Federally enforceable |

**FACILITY PERMIT TO OPERATE
MICROMETALS, INC**

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN
PERMIT PURSUANT TO RULE 219

NONE

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

| VOC LIMITS | | | | | | | | |
|---|------------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|
| Less Water and Less Exempt Compounds | | | | | | | | |
| Effective Dates | | | | | | | | |
| Coating | Air-Dried | | | | Baked | | | |
| | gm/l | | lb/gal | | gm/l | | lb/gal | |
| | Current | 7/1/07 | Current | 7/1/07 | Current | 7/1/07 | Current | 7/1/07 |
| General One-Component | 275 | 275 | 2.3 | 2.3 | 275 | 275 | 2.3 | 2.3 |
| General Multi-Component | 340 | 340 | 2.8 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Military Specification | 340 | 340 | 2.8 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Etching Filler | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Solar-Absorbent | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Heat-Resistant | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Extreme High-Gloss | 420 | 340 | 3.5 | 2.8 | 360 | 360 | 3.0 | 3.0 |
| Metallic | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

| VOC LIMITS | | | | | | | | |
|---|------------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|
| Less Water and Less Exempt Compounds | | | | | | | | |
| Effective Dates, cont. | | | | | | | | |
| Coating | Air-Dried | | | | Baked | | | |
| | gm/l | | lb/gal | | gm/l | | lb/gal | |
| | Current | 7/1/07 | Current | 7/1/07 | Current | 7/1/07 | Current | 7/1/07 |
| Extreme Performance | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Prefabricated Architectural One-Component | 420 | 275 | 3.5 | 2.3 | 275 | 275 | 2.3 | 2.3 |
| Prefabricated Architectural Multi-Component | 420 | 340 | 3.5 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Touch Up | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Repair | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Silicone Release | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| High-Performance Architectural | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Camouflage | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Vacuum-Metalizing | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Mold-Seal | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| High-Temperature | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Electric-Insulating Varnish | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Pan Backing | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Pretreatment Coatings | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:
 - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
 - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

TABLE OF STANDARDS 1 VOC LIMITS

**Grams of VOC Per Liter of Coating,
Less Water and Less Exempt Compounds**

| COATING CATEGORY | Ceiling Limit ¹ | Current Limit ² | Effective Date | | |
|--|----------------------------|----------------------------|----------------|--------|--------|
| | | | 7/1/08 | 1/1/12 | 1/1/14 |
| Bond Breakers | | 350 | | | |
| Clear Wood Finishes | | 275 | | | |
| Varnish | 350 | 275 | | | |
| Sanding Sealers | 350 | 275 | | | |
| Lacquer | | 275 | | | |
| Concrete-Curing Compounds | | 100 | | | |
| Concrete-Curing Compounds For Roadways and Bridges ³ | | 350 | | | |
| Concrete Surface Retarder | | 250 | | | 50 |
| Driveway Sealer | | 100 | | 50 | |
| Dry-Fog Coatings | | 150 | | | 50 |
| Faux Finishing Coatings | | | | | |
| Clear Topcoat | | 350 | | 200 | |
| Decorative Coatings | | 350 | | | 100 |
| Glazes | | 350 | | | |
| Japan | | 350 | | | |
| Trowel Applied Coatings | | 350 | | 150 | 50 |
| Fire-Proofing Coatings | | 350 | | | 150 |
| Flats | 250 | 50 | 50 | | |
| Floor Coatings | 100 | 50 | | | |
| Form Release Compound | | 250 | | | 100 |
| Graphic Arts (Sign) Coatings | | 500 | | | 150 |
| Industrial Maintenance (IM) Coatings | 420 | 100 | | | |
| High Temperature IM Coatings | | 420 | | | |
| Non-Sacrificial Anti-Graffiti Coatings | | 100 | | | |
| Zinc-Rich IM Primers | 340 | 100 | | | |
| Magnesite Cement Coatings | | 450 | | | |
| Mastic Coatings | | 300 | | | 100 |
| Metallic Pigmented Coatings | 500 | 500 | | | 150 |
| Multi-Color Coatings | | 250 | | | |
| Nonflat Coatings | 150 | 50 | | | |
| Pre-Treatment Wash Primers | | 420 | | | |
| Primers, Sealers, and Undercoaters | 200 | 100 | | | |
| Reactive Penetrating Sealers | | 350 | | | |
| Recycled Coatings | | 250 | | | |
| Roof Coatings | 250 | 50 | | | |
| Roof Coatings, Aluminum | | 100 | | | |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

| | | | | | |
|------------------------------------|-----|-----|--|----|--|
| Roof Primers, Bituminous | 350 | 350 | | | |
| Rust Preventative Coatings | 400 | 100 | | | |
| Stone Consolidant | | 450 | | | |
| Sacrificial Anti-Graffiti Coatings | | 100 | | 50 | |
| Shellac | | | | | |
| Clear | | 730 | | | |
| Pigmented | | 550 | | | |
| Specialty Primers | 350 | 100 | | | |
| Stains | | 100 | | | |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

| COATING CATEGORY | Ceiling Limit ¹ | Current Limit ² | Effective Date | | |
|--|----------------------------|----------------------------|----------------|--------|--------|
| | | | 7/1/08 | 1/1/12 | 1/1/14 |
| Stains, Interior | 250 | 250 | | | |
| Swimming Pool Coatings | | | | | |
| Repair | | 340 | | | |
| Other | | 340 | | | |
| Traffic Coatings | | 100 | | | |
| Waterproofing Sealers | 250 | 100 | | | |
| Waterproofing Concrete/Masonry Sealers | 400 | 100 | | | |
| Wood Preservatives | | 350 | | | |

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

TABLE OF STANDARDS 1 (cont.) VOC LIMITS

Grams of VOC Per Liter of Material

| COATING | Limit |
|--------------------|-------|
| Low-Solids Coating | 120 |

TABLE OF STANDARDS 2 VOC LIMITS FOR COLORANTS

Grams of VOC Per Liter of Colorant Less Water and Less Exempt Compounds

| COLORANT | Limit ⁴ |
|---|--------------------|
| Architectural Coatings, excluding IM Coatings | 50 |
| Solvent-Based IM | 600 |
| Waterborne IM | 50 |

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007] TABLE OF STANDARDS VOC LIMITS

**Grams of VOC Per Liter of Coating,
Less Water and Less Exempt Compounds**

| COATING CATEGORY | Ceiling Limit* | Current Limit | Effective Date | | | | | |
|--|----------------|---------------|----------------|--------|--------|--------|--------|--------|
| | | | 1/1/03 | 1/1/04 | 1/1/05 | 7/1/06 | 7/1/07 | 7/1/08 |
| Bond Breakers | 350 | | | | | | | |
| Clear Wood Finishes | 350 | | | | | 275 | | |
| Varnish | 350 | | | | | 275 | | |
| Sanding Sealers | 350 | | | | | 275 | | |
| Lacquer | 680 | 550 | | | 275 | | | |
| Clear Brushing Lacquer | 680 | | | | 275 | | | |
| Concrete-Curing Compounds | 350 | | | | | | 100 | |
| Concrete-Curing Compounds For Roadways and Bridges** | 350 | | | | | | | |
| Dry-Fog Coatings | 400 | | | | | | 150 | |
| Fire-Proofing Exterior Coatings | 450 | 350 | | | | | | |
| Fire-Retardant Coatings*** | | | | | | | | |
| Clear | 650 | | | | | | | |
| Pigmented | 350 | | | | | | | |
| Flats | 250 | 100 | | | | | | 50 |
| Floor Coatings | 420 | | 100 | | | 50 | | |
| Graphic Arts (Sign) Coatings | 500 | | | | | | | |
| Industrial Maintenance (IM) Coatings | 420 | | | 250 | | 100 | | |
| High Temperature IM Coatings | | | 420 | | | | | |
| Zinc-Rich IM Primers | 420 | | 340 | | | 100 | | |
| Japans/Faux Finishing Coatings | 700 | 350 | | | | | | |
| Magnesite Cement Coatings | 600 | 450 | | | | | | |
| Mastic Coatings | 300 | | | | | | | |
| Metallic Pigmented Coatings | 500 | | | | | | | |
| Multi-Color Coatings | 420 | 250 | | | | | | |
| Nonflat Coatings | 250 | | 150 | | | 50 | | |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

| COATING CATEGORY | Ceiling Limit* | Current Limit | Effective Date | | | | | |
|--|----------------|---------------|----------------|--------|--------|--------|--------|--------|
| | | | 1/1/03 | 1/1/04 | 1/1/05 | 7/1/06 | 7/1/07 | 7/1/08 |
| Nonflat High Gloss | 250 | | 150 | | | | 50 | |
| Pigmented Lacquer | 680 | 550 | | | 275 | | | |
| Pre-Treatment Wash Primers | 780 | | 420 | | | | | |
| Primers, Sealers, and Undercoaters | 350 | | 200 | | | 100 | | |
| Quick-Dry Enamels | 400 | | 250 | | | 150 | 50 | |
| Quick-Dry Primers, Sealers, and Undercoaters | 350 | | 200 | | | 100 | | |
| Recycled Coatings | | | 250 | | | | | |
| Roof Coatings | 300 | | 250 | | 50 | | | |
| Roof Coatings, Aluminum | 500 | | | | 100 | | | |
| Roof Primers, Bituminous | 350 | | 350 | | | | | |
| Rust Preventative Coatings | 420 | | 400 | | | 100 | | |
| Shellac | | | | | | | | |
| Clear | 730 | | | | | | | |
| Pigmented | 550 | | | | | | | |
| Specialty Primers | 350 | | | | | 250 | 100 | |
| Stains | 350 | | 250 | | | | 100 | |
| Stains, Interior | 250 | | | | | | | |
| Swimming Pool Coatings | | | | | | | | |
| Repair | 650 | | 340 | | | | | |
| Other | 340 | | | | | | | |
| Traffic Coatings | 250 | 150 | | | | | 100 | |
| Waterproofing Sealers | 400 | | 250 | | | 100 | | |
| Waterproofing | 400 | | | | | 100 | | |
| Concrete/Masonry Sealers | | | | | | | | |
| Wood Preservatives | | | | | | | | |
| Below-Ground | 350 | | | | | | | |
| Other | 350 | | | | | | | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

** Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

*** The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-13-2007]

TABLE OF STANDARDS (cont.) VOC LIMITS

Grams of VOC Per Liter of Material

| COATING | Limit |
|--------------------|-------|
| Low-Solids Coating | 120 |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| | CURRENT LIMITS* | EFFECTIVE 1/1/2008* | EFFECTIVE 1/1/2009 |
|--|---------------------------------|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY | VOC g/l (lb/gal) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application | | | |
| (i) General | 25 (0.21) | | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | | |
| (iii) Medical Devices & Pharmaceuticals | 800 (6.7) | | |
| (B) Repair and Maintenance Cleaning | | | |
| (i) General | 25 (0.21) | | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | | |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2008* | EFFECTIVE 1/1/2009 |
|---|---------------------------------|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY (cont.) | VOC g/l (lb/gal) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (iii) Medical Devices & Pharmaceuticals | | | |
| (A) Tools, Equipment, & Machinery | 800 (6.7) | | |
| (B) General Work Surfaces | 600 (5.0) | | |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 25 (0.21) | | |
| (D) Cleaning of Ink Application Equipment | | | |
| (i) General | 25 (0.21) | | |
| (ii) Flexographic Printing | 25 (0.21) | | |
| (iii) Gravure Printing | | | |
| (A) Publication | 100 (0.83) | | |
| (B) Packaging | 25 (0.21) | | |
| (iv) Lithographic (Offset) or Letter Press Printing | | | |
| (A) Roller Wash, Blanket Wash, & On-Press Components | | | |
| (I) Newsprint | 100 (0.83) | | |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2008* | EFFECTIVE 1/1/2009 |
|--|---------------------------------|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY (cont.) | VOC g/l (lb/gal) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (II) Other Substrates | 500 (4.2) | 100 (0.83) | |
| (B) Removable Press Components | 25 (0.21) | | |
| (v) Screen Printing | 500 (4.2) | 100 (0.83) | |
| (vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing) | 650 (5.4) | 650 (5.4) | 100 (0.83) |
| (vii) Specialty Flexographic Printing | 100 (0.83) | | |
| (E) Cleaning of Polyester Resin Application Equipment | 25 (0.21) | | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| | CURRENT LIMITS* | EFFECTIVE 1/1/2010 |
|--|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application | | |
| (i) General | 25 (0.21) | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | |
| (iii) Medical Devices & Pharmaceuticals | 800 (6.7) | |
| (B) Repair and Maintenance Cleaning | | |
| (i) General | 25 (0.21) | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2010 |
|---|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY (cont.) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (iii) Medical Devices & Pharmaceuticals | | |
| (A) Tools, Equipment, & Machinery | 800 (6.7) | |
| (B) General Work Surfaces | 600 (5.0) | |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 25 (0.21) | |
| (D) Cleaning of Ink Application Equipment | | |
| (i) General | 25 (0.21) | |
| (ii) Flexographic Printing | 25 (0.21) | |
| (iii) Gravure Printing | | |
| (A) Publication | 100 (0.83) | |
| (B) Packaging | 25 (0.21) | |
| (iv) Lithographic (Offset) or Letter Press Printing | | |
| (A) Roller Wash, Blanket Wash, & On-Press Components | 100 (0.83) | |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2010 |
|--|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY (cont.) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (B) Removable Press Components | 25 (0.21) | |
| (v) Screen Printing | 100 (0.83) | |
| (vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing) | 650 (5.4) | 100 (0.83) |
| (vii) Specialty Flexographic Printing | 100 (0.83) | |
| (E) Cleaning of Polyester Resin Application Equipment | 25 (0.21) | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|--|--------------------------------|--|--------------------------|--|--------------------------------|---|-----------------------------|
| | | Milligrams per Cubic Meter | Grains per Cubic Foot | | | Milligrams per Cubic Meter | Grains per Cubic Foot |
| Cubic meters Per Minute | Cubic feet Per Minute | | | Cubic meters Per Minute | Cubic feet Per Minute | | |
| 25 or less | 883 or less | 450 | 0.196 | 900 | 31780 | 118 | 0.0515 |
| 30 | 1059 | 420 | .183 | 1000 | 35310 | 113 | .0493 |
| 35 | 1236 | 397 | .173 | 1100 | 38850 | 109 | .0476 |
| 40 | 1413 | 377 | .165 | 1200 | 42380 | 106 | .0463 |
| 45 | 1589 | 361 | .158 | 1300 | 45910 | 102 | .0445 |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|--|--------------------------------|---|--------------------------|--|--------------------------------|---|-----------------------------|
| | | Milligrams per Cubic Meter | Grains per Cubic Foot | | | Milligrams per Cubic Meter | Grains per Cubic Foot |
| Cubic meters Per Minute | Cubic feet Per Minute | | | Cubic meters Per Minute | Cubic feet Per Minute | | |
| 50 | 1766 | 347 | .152 | 1400 | 49440 | 100 | .0437 |
| 60 | 2119 | 324 | .141 | 1500 | 52970 | 97 | .0424 |
| 70 | 2472 | 306 | .134 | 1750 | 61800 | 92 | .0402 |
| 80 | 2825 | 291 | .127 | 2000 | 70630 | 87 | .0380 |
| 90 | 3178 | 279 | .122 | 2250 | 79460 | 83 | .0362 |
| 100 | 3531 | 267 | .117 | 2500 | 88290 | 80 | .0349 |
| 125 | 4414 | 246 | .107 | 3000 | 105900 | 75 | .0327 |
| 150 | 5297 | 230 | .100 | 4000 | 141300 | 67 | .0293 |
| 175 | 6180 | 217 | .0947 | 5000 | 176600 | 62 | .0271 |
| 200 | 7063 | 206 | .0900 | 6000 | 211900 | 58 | .0253 |
| 250 | 8829 | 190 | .0830 | 8000 | 282500 | 52 | .0227 |
| 300 | 10590 | 177 | .0773 | 10000 | 353100 | 48 | .0210 |
| 350 | 12360 | 167 | .0730 | 15000 | 529700 | 41 | .0179 |
| 400 | 14130 | 159 | .0694 | 20000 | 706300 | 37 | .0162 |
| 450 | 15890 | 152 | .0664 | 25000 | 882900 | 34 | .0148 |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|--|--------------------------------|---|--------------------------|--|--------------------------------|---|-----------------------------|
| | | Milligrams per Cubic Meter | Grains per Cubic Foot | | | Milligrams per Cubic Meter | Grains per Cubic Foot |
| Cubic meters Per Minute | Cubic feet Per Minute | | | Cubic meters Per Minute | Cubic feet Per Minute | | |
| 500 | 17660 | 146 | .0637 | 30000 | 1059000 | 32 | .0140 |
| 600 | 21190 | 137 | .0598 | 40000 | 1413000 | 28 | .0122 |
| 700 | 24720 | 129 | .0563 | 50000 | 1766000 | 26 | .0114 |
| 800 | 28250 | 123 | .0537 | 70000 or more | 2472000 or more | 23 | .0100 |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

| Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process | | Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process | |
|----------------------------|----------------|---|--------------------|----------------------------|-------|---|--------------------|
| | | Kilograms Per Hour | Pounds Per Hour | | | Kilograms Per Hour | Pounds Per Hour |
| 100 or less | 220 or less | 0.450 | 0.99 | 9000 | 19840 | 5.308 | 11.7 |
| 150 | 331 | 0.585 | 1.29 | 10000 | 22050 | 5.440 | 12.0 |
| 200 | 441 | 0.703 | 1.55 | 12500 | 27560 | 5.732 | 12.6 |
| 250 | 551 | 0.804 | 1.77 | 15000 | 33070 | 5.982 | 13.2 |
| 300 | 661 | 0.897 | 1.98 | 17500 | 38580 | 6.202 | 13.7 |
| 350 | 772 | 0.983 | 2.17 | 20000 | 44090 | 6.399 | 14.1 |
| 400 | 882 | 1.063 | 2.34 | 25000 | 55120 | 6.743 | 14.9 |
| 450 | 992 | 1.138 | 2.51 | 30000 | 66140 | 7.037 | 15.5 |
| 500 | 1102 | 1.209 | 2.67 | 35000 | 77160 | 7.296 | 16.1 |
| 600 | 1323 | 1.340 | 2.95 | 40000 | 88180 | 7.527 | 16.6 |

FACILITY PERMIT TO OPERATE MICROMETALS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

| Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process | | Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process | |
|----------------------------|--------------------|---|--------------------|----------------------------|--------------------|---|--------------------|
| Kilograms Per Hour | Pounds Per Hour | Kilograms Per Hour | Pounds Per Hour | Kilograms Per Hour | Pounds Per Hour | Kilograms Per Hour | Pounds Per Hour |
| 700 | 1543 | 1.461 | 3.22 | 45000 | 99210 | 7.738 | 17.1 |
| 800 | 1764 | 1.573 | 3.47 | 50000 | 110200 | 7.931 | 17.5 |
| 900 | 1984 | 1.678 | 3.70 | 60000 | 132300 | 8.277 | 18.2 |
| 1000 | 2205 | 1.777 | 3.92 | 70000 | 154300 | 8.582 | 18.9 |
| 1250 | 2756 | 2.003 | 4.42 | 80000 | 176400 | 8.854 | 19.5 |
| 1500 | 3307 | 2.206 | 4.86 | 90000 | 198400 | 9.102 | 20.1 |
| 1750 | 3858 | 2.392 | 5.27 | 100000 | 220500 | 9.329 | 20.6 |
| 2000 | 4409 | 2.563 | 5.65 | 125000 | 275600 | 9.830 | 21.7 |
| 2250 | 4960 | 2.723 | 6.00 | 150000 | 330700 | 10.26 | 22.6 |
| 2500 | 5512 | 2.874 | 6.34 | 175000 | 385800 | 10.64 | 23.5 |
| 2750 | 6063 | 3.016 | 6.65 | 200000 | 440900 | 10.97 | 24.2 |
| 3000 | 6614 | 3.151 | 6.95 | 225000 | 496000 | 11.28 | 24.9 |
| 3250 | 7165 | 3.280 | 7.23 | 250000 | 551200 | 11.56 | 25.5 |
| 3600 | 7716 | 3.404 | 7.50 | 275000 | 606300 | 11.82 | 26.1 |
| 4000 | 8818 | 3.637 | 8.02 | 300000 | 661400 | 12.07 | 26.6 |
| 4500 | 9921 | 3.855 | 8.50 | 325000 | 716500 | 12.30 | 27.1 |
| 5000 | 11020 | 4.059 | 8.95 | 350000 | 771600 | 12.51 | 27.6 |
| 6000 | 13230 | 4.434 | 9.78 | 400000 | 881800 | 12.91 | 28.5 |
| 7000 | 15430 | 4.775 | 10.5 | 450000 | 992100 | 13.27 | 29.3 |
| 8000 | 17640 | 5.089 | 11.2 | 500000 or more | 1102000 or more | 13.60 | 30.0 |