

FACILITY PERMIT TO OPERATE

**EXXONMOBIL OIL CORPORATION
3700 W 190TH ST
TORRANCE, CA 90504**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By _____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

TABLE OF CONTENTS

| Section | Description | Revision # | Date Issued |
|----------|--|-----------------|-------------|
| A | Facility Information | 12 | 06/17/2014 |
| B | RECLAIM Annual Emission Allocation | 33 | 04/01/2013 |
| C | Facility Plot Plan | TO BE DEVELOPED | |
| D | Facility Description and Equipment Specific Conditions | 58 | 06/17/2014 |
| E | Administrative Conditions | 11 | 01/25/2010 |
| F | RECLAIM Monitoring and Source Testing Requirements | 9 | 01/25/2010 |
| G | Recordkeeping and Reporting Requirements for RECLAIM Sources | 10 | 01/25/2010 |
| H | Permit To Construct and Temporary Permit to Operate | 69 | 12/17/2013 |
| I | Compliance Plans & Schedules | 16 | 01/29/2014 |
| J | Air Toxics | 4 | 01/25/2010 |
| K | Title V Administration | 5 | 01/18/2013 |
| Appendix | | | |
| A | NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219 | 6 | 01/25/2010 |
| B | Rule Emission Limits | 4 | 01/25/2010 |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR: EXXONMOBIL OIL CORPORATION

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION: 3700 W 190TH ST
TORRANCE, CA 90504-5790

MAILING ADDRESS: 3700 W 190TH ST
TORRANCE, CA 90509-2929

RESPONSIBLE OFFICIAL: E. PABLO BORGNINO

TITLE: REFINERY MANAGER

TELEPHONE NUMBER: (310) 212-4500

CONTACT PERSON: VALERIE B. TSE

TITLE: ENVIRONMENTAL PERMITTING ADVISOR

TELEPHONE NUMBER: (310) 212-1781

INITIAL TITLE V PERMIT ISSUED: January 25, 2010

TITLE V PERMIT EXPIRATION DATE: January 24, 2015

| TITLE V | | RECLAIM | |
|---------|--|---------------|----------------|
| YES | | NOx: | YES |
| | | SOx: | YES |
| | | CYCLE: | 1 |
| | | ZONE: | COASTAL |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---------------------------------|------------|
| Process 17: PETROLEUM MISCELLANEOUS PROCESSES | | | | | |
| System 1: BUTANE SYSTEM | | | | | |
| COMPRESSOR, 55K-1, FULLER MODEL CB30, ELECTRIC MOTOR, 15 HP, 60,000 CU.FT./DAY, WITH NITROGEN BARRIER FLUID SEAL SYSTEM A/N: 553380 | D1556 | | | | H23.34 |
| System 2: JET FUEL FINISHING SYSTEM | | | | | S31.5 |
| FILTER, CLAY TREATER, 55C-6 & 55C-7, KEROSENE, IN PARALLEL, HEIGHT: 22 FT ; DIAMETER: 10 FT A/N: 422381 | D2519 | | | | |
| FILTER, SEPARATOR, 55C-8 & 55C-9, VESSEL TYPE, JET FUEL, IN PARALLEL, HEIGHT: 52 FT 6 IN; DIAMETER: 35 FT A/N: 422381 | D2520 | | | | |
| FILTER, SEPARATOR, 55C-23, VESSEL TYPE, JET FUEL,, HEIGHT: 4 FT 6 IN; DIAMETER: 3 FT A/N: 422381 | D2521 | | | | |
| FILTER, SEPARATOR, 55C-24, VESSEL TYPE, JET FUEL,, HEIGHT: 4 FT 6 IN; DIAMETER: 3 FT 6 IN A/N: 422381 | D2522 | | | | |
| FILTER, SEPARATOR, 55C-26, VESSEL TYPE, JET FUEL,, HEIGHT: 4 FT 6 IN; DIAMETER: 3 FT A/N: 422381 | D2523 | | | | |

- * (1) (1A) (1B) Denotes RECLAIM emission factor
- (3) Denotes RECLAIM concentration limit
- (5) (5A) (5B) Denotes command and control emission limit
- (7) Denotes NSR applicability limit
- (9) See App B for Emission Limits
- (2) (2A) (2B) Denotes RECLAIM emission rate
- (4) Denotes BACT emission limit
- (6) Denotes air toxic control rule limit
- (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
- (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|--|---|---|
| Process 17: PETROLEUM MISCELLANEOUS PROCESSES | | | | | |
| FILTER, SEPARATOR, 56C-19 A & B, VESSEL TYPE, JET FUEL, IN PARALLEL, HEIGHT: 7 FT ; DIAMETER: 2 FT A/N: 422381 | D2524 | | | | |
| FILTER, PRETREATER, 55C-10, HEIGHT: 12 FT ; DIAMETER: 8 FT A/N: 422381 | D2525 | | | | |
| FUGITIVE EMISSIONS, MISCELLANEOUS A/N: 422381 | D1877 | | | HAP: (10) [40CFR 63 Subpart CC, #5A, 6-23-2003] | H23.34 |
| System 3: EMERGENCY FIRE-WATER SUPPLY SYSTEM | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, 67J-6, DIESEL FUEL, CATERPILLAR, MODEL #3408, WITH TURBOCHARGER, 510 HP A/N: 219444 | D955 | | NOX: PROCESS UNIT**; SOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; SOX: 6.24 LBS/1000 GAL DIESEL (1) [RULE 2011, 5-6-2005] | B61.2, C1.15, C1.69, D12.4, D135.1, K67.1 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, 67J-8, DIESEL FUEL, CATERPILLAR, MODEL #3408, WITH TURBOCHARGER, 510 HP A/N: 219446 | D957 | | NOX: PROCESS UNIT**; SOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; SOX: 6.24 LBS/1000 GAL DIESEL (1) [RULE 2011, 5-6-2005] | B61.2, C1.15, C1.69, D12.4, D135.1, K67.1 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, 67J-4, DIESEL FUEL, CUMMINS, MODEL NT-855-F1, WITH AFTERCOOLER, TURBOCHARGER, 250 HP A/N: 178647 | D959 | | NOX: PROCESS UNIT**; SOX: PROCESS UNIT** | NOX: 469 LBS/1000 BBLs DIESEL (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; SOX: 6.24 LBS/1000 BBLs DIESEL (1) [RULE 2011, 5-6-2005] | B61.2, C1.15, C1.69, D12.4, D135.1, K67.1 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|---|
| Process 17: PETROLEUM MISCELLANEOUS PROCESSES | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, 67J-7, DIESEL FUEL, CATERPILLAR, MODEL #3408, WITH AFTERCOOLER, TURBOCHARGER, 510 HP A/N: 219445 | D961 | | NOX: PROCESS UNIT**; SOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; SOX: 6.24 LBS/1000 GAL DIESEL (1) [RULE 2011, 5-6-2005] | B61.2, C1.15, C1.69, D12.4, D135.1, K67.1 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, DIESEL FUEL, CATERPILLAR, MODEL 3406C DITA, 460 BHP A/N: 364686 | D1785 | | NOX: PROCESS UNIT**; SOX: PROCESS UNIT** | CO: 2.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 2005, 5-6-2005]; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; SO2: 6.24 LBS/1000 GAL DIESEL (1) [RULE 2011, 5-6-2005]; VOC: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996] | B61.2, C1.15, C1.69, D12.4, D135.1, K67.1 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|--|
| Process 17: PETROLEUM MISCELLANEOUS PROCESSES | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, 67G-4C, CARB DIESEL FUEL, CUMMINS, MODEL CFP9E-F30 (QSL9 SERIES), WITH CHARGE AIR COOLED, TURBOCHARGER, 323 HP A/N: 519368 | D2428 | | NOX: PROCESS UNIT**; SOX: PROCESS UNIT** | CO: 2.6 GRAM/BHP-HR (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; NOX: 128 LBS/1000 GAL (1) [RULE 2012, 5-6-2005]; NOX + ROG: 3 GRAM/BHP-HR (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 2005, 6-3-2011]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.15 GRAM/BHP-HR (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; SOX: 6.24 LBS/1000 GAL (1) [RULE 2011, 5-6-2005] | B61.7, C1.71, D135.1, E71.16, H23.37, I297.1, I297.2, K67.21 |
| System 4: RESID RECIRCULATION | | | | | |
| HEATER, RESID RECIRCULATION, 50F-1, INFREQUENTLY OPERATED, NATURAL GAS, REFINERY GAS, WITH 5 S-6 GAS BURNER, 12 MMBTU/HR WITH A/N: 455159 BURNER, NATURAL GAS, REFINERY GAS, WITH LOW NOX BURNER, 3 TOTAL; 12 MMBTU/HR | D833 | | NOX: LARGE SOURCE**; SOX: MAJOR SOURCE** | CO: 400 PPMV (5A) [RULE 1146, 11-17-2000; RULE 1146, 9-5-2008]; CO: 2000 PPMV (5) [RULE 407, 4-2-1982]; NOX: 40 PPMV (3) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981] | B61.3, D90.12, D328.1, E193.16, E318.1, H23.13 |
| FUGITIVE EMISSIONS, MISCELLANEOUS A/N: 455159 | D2377 | | | HAP: (10) [40CFR 63 Subpart CC, #5A, 6-23-2003] | H23.34 |
| System 5: REFINERY FUEL GAS SYSTEM | | | | | S13.2, S15.1 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|--|---|---|
| Process 17: PETROLEUM MISCELLANEOUS PROCESSES | | | | | |
| VESSEL, 64C-4, FUEL GAS MIX, HEIGHT: 10 FT ; DIAMETER: 10 FT A/N: 314183 | D838 | | | | |
| KNOCK OUT POT, 53C-16, EDISON DRYERS, LENGTH: 108 FT ; DIAMETER: 24 FT A/N: 314183 | D2445 | | | | |
| KNOCK OUT POT, 53C-17, EDISON DRYERS, LENGTH: 108 FT ; DIAMETER: 24 FT A/N: 314183 | D2446 | | | | |
| FILTER, REFINERY FUEL GAS, OFF PLOT, 11 TOTAL, HEIGHT: 6 FT 6 IN; DIAMETER: 1 FT 8 IN A/N: 314183 | D868 | | | | |
| FUGITIVE EMISSIONS, MISCELLANEOUS A/N: 314183 | D869 | | | | H23.34 |
| System 6: EMERGENCY POWER GENERATION | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, 24J-06, DIESEL FUEL, CATERPILLAR, MODEL 3306DI, WITH AFTERCOOLER, TURBOCHARGER, 345 HP A/N: 273519 | D394 | | NOX: PROCESS UNIT**; SOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; SOX: 6.24 LBS/1000 GAL DIESEL (1) [RULE 2011, 5-6-2005] | B61.2, C1.15, C1.70, D12.4, D135.1, K67.1 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, 29J-5, DIESEL FUEL, CATERPILLAR, MODEL 3306 DJ, CATERPILLAR, WITH AFTERCOOLER, TURBOCHARGER, 245 HP A/N: 316831 | D1686 | | NOX: PROCESS UNIT**; SOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; SOX: 6.24 LBS/1000 GAL DIESEL (1) [RULE 2011, 5-6-2005] | B61.2, C1.15, C1.70, D12.4, D135.1, K67.1 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|---|
| Process 17: PETROLEUM MISCELLANEOUS PROCESSES | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC CORPOARATION, MODEL 40DTA-SD075, WITH AFTERCOOLER, TURBOCHARGER, 114 BHP A/N: 366928 | D1786 | | NOX: PROCESS UNIT**; SOX: PROCESS UNIT** | CO: 0.78 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; NOX: 5.884 GRAM/BHP-HR DIESEL (4) [RULE 2005, 5-6-2005]; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 5-6-2005]; PM: (9) [RULE 404, 2-7-1986]; PM: 0.328 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996]; SOX: 0.184 GRAM/BHP-HR DIESEL (4) [RULE 2005, 5-6-2005]; SOX: 6.24 LBS/1000 GAL DIESEL (1) [RULE 2011, 5-6-2005]; VOC: 0.648 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996] | B61.2, C1.15, C1.70, D12.4, D135.1, K67.1 |
| System 7: PROPANE TRANSFER FACILITY | | | | | |
| FUGITIVE EMISSIONS, MISCELLANEOUS A/N: 225029 | D1888 | | | HAP: (10) [40CFR 63 Subpart CC, #5A, 6-23-2003] | H23.34 |
| System 8: Odorizing System Serving LPG Rail Car and Tank Truck Rack | | | | | |
| TANK, HOLDING, 64C-5, ODORANT, 250 GALS; DIAMETER: 2 FT 6 IN; LENGTH: 7 FT 10 IN A/N: 391812 | D2195 | | | | E144.1 |
| TANK, HOLDING, 52C-107, ETHYL MERCAPTAN, SERVING LPG TANK TRUCK RACK, 500 GALS; DIAMETER: 3 FT 1.4 IN; LENGTH: 9 FT 11 IN A/N: 391813 | D2196 | | | | E144.1 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---------------------------------|--|
| Process 17: PETROLEUM MISCELLANEOUS PROCESSES | | | | | |
| TANK, HOLDING, 51C-111, ETHYL MERCAPTAN, 250 GALS; DIAMETER: 2 FT 6 IN; LENGTH: 7 FT 10 IN A/N: 391814 | D2197 | | | | E144.1 |
| FUGITIVE EMISSIONS, MISCELLANEOUS A/N: 391812 | D1889 | | | | H23.34 |
| System 12: SLUDGE TRANSFER ODOR CONTROL | | | | | |
| CARBON ADSORBER, 55-GALLON DRUM, SERVING VACUUM TRUCK AT API SEPARATOR A/N: 380822 | C1729 | | | | E71.5 |
| System 13: FUEL STORAGE AND DISPENSING | | | | | |
| STORAGE TANK, ABOVEGROUND, CONTAINMENT SOLUTIONS, HOOVER VAULT TANK, (VR-302-C), RECTANGULAR, EQUIPPED WITH A HUSKY 5885 PRESSURE/VACUUM RELIEF VALVE, AND, 2000 GALS; WIDTH: 6 FT 11 IN; HEIGHT: 4 FT 7 IN; LENGTH: 11 FT 10 IN WITH A/N: 563079 VAPOR RETURN LINE, VAPOR RETURN LINE, A MORRISON BROTHERS PHASE I ENCHANCED VAPOR RECOVERY (EVR) SYSTEM (VR-402-B) | D2544 | | | | D182.8, D330.1, J109.1, J373.2, J373.4, K67.23, K67.24, K67.25 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|--|
| Process 17: PETROLEUM MISCELLANEOUS PROCESSES | | | | | |
| FUEL DISPENSING NOZZLE, BALANCE TYPE PHASE II CONTROL, TOTAL OF 2, ON TWO TANK MOUNTED DISPENSERS,, GASOLINE, EQUIPPED WITH PHASE II VAPOR RECOVERY SYSTEM, BALANCE RETRACTOR A/N: 563079 | D2546 | | | | C1.77, C1.78, D182.7, D182.10, D182.11, D182.12, D182.13, D330.1, J110.1, J373.2, J373.3, J373.4, J373.5, K67.23, K67.24, K67.25 |
| FUGITIVE EMISSIONS, MISCELLANEOUS A/N: 563079 | D2547 | | | HAP: (10) [40CFR 63 Subpart CC, #5A, 6-23-2003] | H23.34 |
| System 17: SUMP, COVERED & CONTROLLED | | | | | |
| SUMP, VACUUM TRUCK WASH OUT, FIXED COVER, CONCRETE WALLS, SPLASH FILLING, QUICK-CONNECT/GRAVITY DRAIN INLET, WITH ACTIVATED CARBON ADSORPTION, 599 BBL; WIDTH: 18 FT 4 IN; DEPTH: 10 FT ; LENGTH: 18 FT 4 IN A/N: 432298 | D1671 | C2479 | | VOC: 500 PPMV (5) [RULE 1176, 9-13-1996; 40CFR 61 Subpart FF, 12-4-2003] | E71.19, K67.22 |
| CARBON ADSORBER, TOTAL OF 3, CONNECTED IN SERIES, EACH 198 LBS, ACTIVATED CARBON A/N: 432298 | C2479 | D1671 | | | D90.19, E128.1, E153.8 |
| SUMP, NO. 1 PUMP PAD, WIDTH: 9 FT 11 IN; DEPTH: 11 FT 4 IN; LENGTH: 9 FT 11 IN A/N: 361854 | D1783 | C1784 | | | |

* (1) (1A) (1B) Denotes RECLAIM emission factor (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|-----------------------|
| Process 17: PETROLEUM MISCELLANEOUS PROCESSES | | | | | |
| TANK, WITH 6075 GALLON FLEXIBLE CONTAINMENT BLADDER, LENGTH: 16 FT 2 IN; DIAMETER: 8 FT A/N: 361852 | C1784 | D1783 | | | |
| FUGITIVE EMISSIONS, MISCELLANEOUS A/N: 361854 | D1794 | | | HAP: (10) [40CFR 63 Subpart CC, #5A, 6-23-2003] | H23.34 |
| SUMP, WASH WATER COLLECTION SERVING A MACHINE SHOP WASH PAD, THREE COMPARTMENTS, CONCRETE WITH 6 IN. WALLS, FIXED COVER, WITH ACTIVATED CARBON ADSORPTION, SUBMERGED FILLING, 6434 GALS; WIDTH: 10 FT 10 IN; DEPTH: 8 FT ; LENGTH: 18 FT 6 IN A/N: 416818 | D2136 | C2135 | | VOC: 500 PPMV (5) [RULE 1176, 9-13-1996; 40CFR 61 Subpart FF, 12-4-2003] | E71.8, K67.22 |
| CARBON ADSORBER, TOTAL OF 2, CONNECTED IN SERIES, EACH 180 LBS A/N: 416818 | C2135 | D2136 | | | D90.6, E128.2, E153.4 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
 (2) (2A) (2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit
 (4) Denotes BACT emission limit
 (5) (5A) (5B) Denotes command and control emission limit
 (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit
 (8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits
 (10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: DEVICE ID INDEX

| Device Index For Section D | | | |
|----------------------------|--------------------|---------|--------|
| Device ID | Section D Page No. | Process | System |
| D394 | 5 | 17 | 6 |
| D833 | 4 | 17 | 4 |
| D838 | 5 | 17 | 5 |
| D868 | 5 | 17 | 5 |
| D869 | 5 | 17 | 5 |
| D955 | 2 | 17 | 3 |
| D957 | 2 | 17 | 3 |
| D959 | 2 | 17 | 3 |
| D961 | 3 | 17 | 3 |
| D1556 | 1 | 17 | 1 |
| D1671 | 8 | 17 | 17 |
| D1686 | 5 | 17 | 6 |
| C1729 | 7 | 17 | 12 |
| D1783 | 8 | 17 | 17 |
| C1784 | 9 | 17 | 17 |
| D1785 | 3 | 17 | 3 |
| D1786 | 6 | 17 | 6 |
| D1794 | 9 | 17 | 17 |
| D1877 | 2 | 17 | 2 |
| D1888 | 6 | 17 | 7 |
| D1889 | 7 | 17 | 8 |
| C2135 | 9 | 17 | 17 |
| D2136 | 9 | 17 | 17 |
| D2195 | 6 | 17 | 8 |
| D2196 | 6 | 17 | 8 |
| D2197 | 7 | 17 | 8 |
| D2377 | 4 | 17 | 4 |
| D2428 | 4 | 17 | 3 |
| D2445 | 5 | 17 | 5 |
| D2446 | 5 | 17 | 5 |
| C2479 | 8 | 17 | 17 |
| D2519 | 1 | 17 | 2 |
| D2520 | 1 | 17 | 2 |
| D2521 | 1 | 17 | 2 |
| D2522 | 1 | 17 | 2 |

**FACILITY PERMIT TO OPERATE
EXXONMOBIL OIL CORPORATION
SECTION D: DEVICE ID INDEX**

| Device Index For Section D | | | |
|-----------------------------------|---------------------------|----------------|---------------|
| Device ID | Section D Page No. | Process | System |
| D2523 | 1 | 17 | 2 |
| D2524 | 2 | 17 | 2 |
| D2525 | 2 | 17 | 2 |
| D2544 | 7 | 17 | 13 |
| D2546 | 8 | 17 | 13 |
| D2547 | 8 | 17 | 13 |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

F14.1 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F24.1 Accidental release prevention requirements of Section 112(r)(7):

a). The operator shall comply with the accidental release prevention requirements pursuant to 40 CFR Part 68 and shall submit to the Executive Officer, as a part of an annual compliance certification, a statement that certifies compliance with all of the requirements of 40 CFR Part 68, including the registration and submission of a risk management plan (RMP).

b). The operator shall submit any additional relevant information requested by the Executive Officer or designated agency.

[40CFR 68 - Accidental Release Prevention, 5-24-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

F25.1 The permit holder of this facility shall not install, alter, or operate a refinery process unit or other non-Rule 219 exempt equipment without a valid RECLAIM/Title V permit issued by the AQMD pursuant to Rule 201 - Permit to Construct, Rule 203 - Permit to Operate, Rule 2004 - Requirements, and Rule 3002 - Requirements, as applicable.

Notwithstanding the above, the provisions of Rules 201, 203, 2004, and 3002 shall not apply to installations or alterations that involve only the equipment listed in Table 1 below, nor shall they apply to the operation of equipment listed in Table 1, when directly associated with permitted process units or other permitted equipment.

Notwithstanding the above, all new equipment listed in Table 1, including associated fugitive components installed with such equipment, shall have Best Available Control Technology installed in conformance with the Best Available Control Technology Guidelines in effect at the time of the installation.

TABLE 1

- (a) Heat Exchanger (including air-cooler, reboiler, cooler, condenser, and shell and tube exchanger)
- (b) In-line Mixer
- (c) Pump
- (d) Knockout Pot - Compressor inlet (immediate inlet) and interstage
- (e) Knockout Pot - Fuel Gas System (downstream of fuel gas mix drums)

This condition applies only to the facility that processes petroleum as defined in the Standard Industrial Classification Manual as Industry No. 2911 - Petroleum Refining, as well as its directly associated sulfur recovery plant which may be located outside of the facility.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 2004, 5-11-2001]

- F34.1 The operator shall not sell refinery gas containing sulfur compounds in excess of 40 ppmv, calculated as hydrogen sulfide, averaged over 4-hour period.

[RULE 431.1, 6-12-1998]

- F52.1 This facility is subject to the applicable requirements of the following rules or regulation(s):

40CFR79

40CFR80

California Code of Regulations, Title 13, Division 3, Chapter 5

[40CFR 79, 7-1-1999; 40CFR 80, 7-1-1999; CCR Title 13, 9-24-1999]

- F52.2 This facility is subject to the applicable requirements of the following rules or regulation(s):

CONSENT DECREE CIVIL CASE No. 05 C 5809. The facility shall send the District a copy of the semiannual updates sent to the EPA of the specific requirement of emission standards and limitations from the Consent Decree as well as dates of compliance for the requirement not yet fulfilled

40CFR60, Subpart A

40CFR61 Subpart A

40CFR63, Subpart A

[40CFR 60 Subpart A, 5-16-2007; 40CFR 61 Subpart A, 5-16-2007; 40CFR 63 Subpart A, 5-16-2007; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

F60.1 The emission limits identified in Section D and H of the permit shall be defined as emissions discharged to the atmosphere from the originating equipment.

PROCESS CONDITIONS

P13.1 All devices under this process are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| HAPs | 40CFR61, SUBPART | FF |

[40CFR 61 Subpart FF, 12-4-2003]

[Processes subject to this condition : 1, 2, 3, 4, 5, 7, 8, 9, 11, 12, 13, 14, 15, 20, 22, 23]

P13.2 All devices under this process are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| HAPs | 40CFR63, SUBPART | CC |

[40CFR 63 Subpart CC, 6-23-2003]

[Processes subject to this condition : 9, 15]

SYSTEM CONDITIONS

S1.2 The operator shall limit the production rate to no more than 1.4e+06 ton(s) in any one year.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The purpose(s) of this condition is to require Mobil to maintain production records on a monthly basis on site, and available for District inspection.

The purpose(s) of this condition is to limit the coke production for both North and South Delayed Coking Units at 1400000 dry tons/yr.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 2, System 1 , 2]

S1.3 The operator shall limit the throughput to no more than 300000 barrel(s) in any one month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 13, System 9]

S1.4 The operator shall limit the throughput to no more than 1400000 ton(s) in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 2, System 3]

S1.5 The operator shall limit the throughput to no more than 8000 ton(s) in any one day.

Throughput shall be defined as coke material with a moisture content of 10 % or less

[RULE 1303, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 2, System 7]

S2.1 The operator shall limit emissions from this system as follows

| CONTAMINANT | EMISSIONS LIMIT |
|-------------|--|
| VOC | Less than 2.5 lbs/mmscf of hydrogen produced |

[RULE 1189, 1-21-2000]

[Systems subject to this condition : Process 6, System 1 , 2]

S4.1 The following condition(s) shall apply to all affected devices listed under Section D of this system for fugitive emissions of volatile organic compounds (VOC):

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All new valves in VOC service except those specifically exempted by Rule 1173, shall be bellow-sealed valves for 2-inch and smaller sizes, except in the following applications: heavy liquid service, control valve, instrument piping/tubing, applications requiring torsional valve stem motion, applications where valve failure could pose safety hazard (e.g. drain valves with valve stems in horizontal position), and retrofits with space limitations.

All new valves greater than 2-inch size and major components in VOC service as defined by Rule 1173, except those specifically exempted by Rule 1173 shall be distinctly identified from other components through their tag numbers (e.g. numbers ending in the letter "N"), and shall be noted in the records.

All new components in VOC service as defined in Rule 1173, except valves and flanges shall be inspected quarterly using EPA reference Method 21.

All new valves & flanges in VOC service except those specifically exempted by Rule 1173, shall be inspected monthly using EPA Method 21. The operator may revert to quarterly inspection upon District approval, after 2 consecutive monthly inspections in which only 2 percent or less are found to be leaking above 500 ppmv. For leaks greater than 500 ppmv, repair shall be attempted within 5 days of detection. Repair or replacement shall be completed within 15 days, unless demonstrated otherwise.

[RULE 1173, 5-13-1994; RULE 1173, 2-6-2009; RULE 1303(a)(1)-BACT, 5-10-1996]

[Systems subject to this condition : Process 3, System 1 , 5; Process 4, System 1; Process 5, System 1 , 2; Process 6, System 1; Process 7, System 1; Process 8, System 1 , 2 , 6; Process 9, System 1 , 2; Process 11, System 3 , 4; Process 23, System 1]

S4.2 The following condition(s) shall apply to all affected devices listed under Section D of this system for fugitive emissions of volatile organic compounds (VOC):

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall monitor the groundwater extraction well caps, pumps (except submerged pump(s)), fittings, and hatches with no detectable VOC leak emissions of greater than 500 ppmv

The operator shall monitor the emissions quarterly after the first three (3) monthly monitoring events. All VOC leak emissions greater than 500 ppmv shall be repaired within 14 days of detection

The operator shall keep records of each inspection, subsequent repair, and reinspection, in a manner approved by the District

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Systems subject to this condition : Process 22, System 2]

S4.3 The following condition(s) shall apply to all affected devices listed under Section H of this system for fugitive emissions of volatile organic compounds (VOC):

The operator shall keep records of each inspection, subsequent repair, and reinspection, in a manner approved by the District

The operator shall monitor the pumps (except submerged pump(s)) and valves located before the liquid phase activated carbon, the groundwater extraction well caps, and process drains with no detectable VOC leak emissions of greater than 500 ppmv

The operator shall monitor the emissions quarterly after the first three (3) monthly monitoring events. All VOC leak emissions greater than 500 ppmv shall be repaired within 14 days of detection

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Systems subject to this condition : Process 22, System 1]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

S7.2 The following conditions shall apply to all refinery operation and related devices from this system:

The operator shall not operate this equipment unless the vessel receiver (10C-9), additive storage tank (10D-1) and the two steam ejectors (10H-1A/B and 10H-2A/B) are vented to a vapor recovery system whenever they are in use.

For all valves in VOC service, except those specifically exempted by Rule 1173, bellows seal valves shall be used for two inches and smaller service, except in the following applications: heavy liquid service, control valves, instrument piping/tubing, applications requiring torsional valve stem motion, applications where failures could pose safety hazards (e.g., drain valves with valve stems in horizontal position), and retrofits with space limitations.

All new valves and flanges in VOC services except bellow sealed valves and those specifically exempted by Rule 1173 shall be inspected monthly using EPA Reference Method 21. If 98 percent or greater of the new valve and flange population inspected is found to leak gaseous or liquid VOCs at a rate less than 500 ppm, then the operator may revert to a quarterly inspection program with the approval of the Executive Officer.

All new components in VOC service as defined by Rule 1173, except those specifically exempt by Rule 1173, shall be identified by listing or tag numbers from other components. All new major components shall have distinct tag numbers (e.g., numbers ending in the letter "N"), and shall be noted in the records.

All new components in VOC service, except pressure relief devices for which a leak in excess of 200 ppm, shall be repaired within 5 days of detection. A leak greater than 500 ppm but less than 1000 ppm measured as methane above background by EPA Method 21 shall be repaired within 14 days of detection.

[RULE 1173, 5-13-1994; RULE 1173, 2-6-2009; RULE 1303(a)(1)-BACT, 5-10-1996]

[Systems subject to this condition : Process 8, System 3]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

S7.3 The following conditions shall apply to all refinery operation and related devices from this system:

All new components in VOC service as defined by Rule 1173, except those specifically exempt by Rule 1173, shall be identified by listing or tag numbers from other components. All new major components shall have distinct tag numbers (e.g., numbers ending in the letter "N"), and shall be noted in the records.

For all valves in VOC service, except those specifically exempted by Rule 1173, bellows seal valves shall be used for two inches and smaller service, except in the following applications: heavy liquid service, control valves, instrument piping/tubing, applications requiring torsional valve stem motion, applications where failures could pose safety hazards (e.g., drain valves with valve stems in horizontal position), and retrofits with space limitations.

All new valves and flanges in VOC services except bellow sealed valves and those specifically exempted by Rule 1173 shall be inspected monthly using EPA Reference Method 21. If 98 percent or greater of the new valve and flange population inspected is found to leak gaseous or liquid VOCs at a rate less than 500 ppm, then the operator may revert to a quarterly inspection program with the approval of the Executive Officer.

All new components in VOC service, except pressure relief devices for which a leak in excess of 200 ppm, shall be repaired within 5 days of detection. A leak greater than 500 ppm but less than 1000 ppm measured as methane above background by EPA Method 21 shall be repaired within 14 days of detection.

[RULE 1173, 5-13-1994; RULE 1173, 2-6-2009; RULE 1303(a)(1)-BACT, 5-10-1996]

[Systems subject to this condition : Process 8, System 4]

S7.5 The following conditions shall apply to all refinery operation and related devices from this system:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall only operate this equipment if it complies with all applicable mitigation measures stipulated in the "Mitigation Monitoring Plan" document which is part of the AQMD Certified Environmental Impact Report dated 12-October-2001.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with the applicable measures stipulated in the "Mitigation Monitoring Plan" document.

[CA PRC CEQA, 11-23-1970]

[Systems subject to this condition : Process 8, System 5; Process 13, System 1, 3, 4, 11; Process 19, System 3]

S7.6 The following conditions shall apply to all refinery operation and related devices from this system:

The operator shall not use this system to process wastewater having VOC content of 5 mg per liter or more as determined by test method specified in District Rule 1176.

[RULE 1176, 9-13-1996]

[Systems subject to this condition : Process 14, System 4]

S13.1 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| PM | District Rule | 1158 |

[RULE 1158, 6-11-1999; RULE 1158, 7-11-2008]

[Systems subject to this condition : Process 2, System 3, 7, 8]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

S13.2 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 1123 |

[RULE 1123, 12-7-1990]

[Systems subject to this condition : Process 1, System 1 , 2 , 4 , 7; Process 2, System 1 , 2 , 4 , 5 , 9; Process 3, System 1 , 5 , 7; Process 4, System 1 , 3 , 5; Process 5, System 1 , 2; Process 6, System 1 , 2 , 6; Process 7, System 1 , 3; Process 8, System 1 , 2 , 3 , 4 , 6; Process 9, System 1 , 2 , 5 , 6; Process 11, System 1 , 2 , 3 , 4 , 5 , 6 , 7 , 8 , 9 , 10 , 11 , 12; Process 16, System 3; Process 17, System 5; Process 19, System 1 , 3 , 7; Process 22, System 1; Process 23, System 1]

S13.3 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 1149 |
| VOC | District Rule | 463 |

[RULE 1149, 7-14-1995; RULE 1149, 5-2-2008; RULE 463, 5-6-2005]

[Systems subject to this condition : Process 15, System 3]

S13.4 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 463 |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

VOC | District Rule | 1178

[RULE 1178, 4-7-2006; RULE 463, 5-6-2005]

[Systems subject to this condition : Process 15, System 1 , 2 , 5]

S13.5 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 1189 |

[RULE 1189, 1-21-2000]

[Systems subject to this condition : Process 6, System 1 , 2]

S13.6 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| SOX | 40CFR60, SUBPART | J |

[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Systems subject to this condition : Process 12, System 1 , 2 , 3 , 4]

S13.7 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------|--------------|
| | | |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| | | |
|-----|------------------|-----|
| VOC | District Rule | 462 |
| VOC | 40CFR60, SUBPART | XX |

[RULE 462, 5-14-1999; 40CFR 60 Subpart XX, 12-19-2003]

[Systems subject to this condition : Process 13, System 3 , 4]

S13.8 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 462 |

[RULE 462, 5-14-1999]

[Systems subject to this condition : Process 13, System 9]

S13.9 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 1176 |

[RULE 1176, 9-13-1996]

[Systems subject to this condition : Process 1, System 3; Process 14, System 1;
 Process 17, System 17]

S13.11 All devices under this system are subject to the applicable requirements of the following rules or regulations:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| VOC | District Rule | 1176 |
| VOC | 40CFR60, SUBPART | QQQ |

[RULE 1176, 9-13-1996; 40CFR 60 Subpart QQQ, 10-17-2000]

[Systems subject to this condition : Process 14, System 2]

S13.12 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 463 |
| VOC | District Rule | 1149 |
| VOC | District Rule | 1178 |

[RULE 1149, 7-14-1995; RULE 1149, 5-2-2008; RULE 1178, 4-7-2006; RULE 463, 5-6-2005]

[Systems subject to this condition : Process 15, System 6]

S13.13 All devices under this system are subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| HAPs | 40CFR61, SUBPART | FF |

[40CFR 61 Subpart FF, 12-4-2003]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 17, System 17]

S15.1 The vent gases from all affected devices of this process/system shall be vented as follows:

All emergency vent gases shall be directed to a blowdown flare system except Devices IDs D35, D57-D62, D68, D71, D86-D91, D98, D152, D237, D349, D360, D629, D630, D631, D638, D657, D668, D671, D1503-D1505, D1250, D1507, D2145, D2465 that vent to the atmosphere.

This process/system shall not be operated unless the blowdown flare system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 1, System 1, 2, 3, 4, 7; Process 2, System 1, 2, 4, 5; Process 3, System 1, 5, 7; Process 4, System 1, 3, 5; Process 5, System 1, 2; Process 6, System 1, 2; Process 7, System 1; Process 8, System 1, 2, 3, 4, 6; Process 9, System 1, 2, 5; Process 11, System 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12; Process 12, System 1, 2, 3, 4; Process 13, System 1, 2, 3, 4; Process 17, System 5, 8; Process 18, System 1; Process 19, System 3; Process 23, System 1]

S15.2 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be directed to a vapor recovery system.

This process/system shall not be operated unless the vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 1, System 1, 2; Process 2, System 4, 5; Process 3, System 5; Process 4, System 1, 3, 5; Process 5, System 1, 2; Process 6, System 1, 2; Process 7, System 1; Process 8, System 1, 2, 3, 4, 6; Process 9, System 1, 2, 5, 6; Process 11, System 1, 2; Process 12, System 1, 2, 3, 4; Process 13, System 1, 2, 3, 4; Process 17, System 8]

S15.4 The vent gases from all affected devices of this process/system shall be vented as follows:

All acid gases under normal operating conditions shall be directed to the sulfur recovery unit(s).

This process/system shall not be operated unless the sulfur recovery unit is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Systems subject to this condition : Process 11, System 4, 6, 7, 9, 10, 11]

S15.5 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be directed to a sulfur vapor collection system.

This process/system shall not be operated unless the vapor collection system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 12, System 6; Process 13, System 6]

S15.6 The vent gases from all affected devices of this process/system shall be vented as follows:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All vent gases under normal operating conditions shall be directed to a vapor control system.

This process/system shall not be operated unless the vapor control system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 13, System 7 , 9]

S15.7 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases under normal operating conditions shall be directed to a vapor recovery system except devices IDs 57 to 62, 71, 86 to 91, and 98 that vent to the atmosphere.

This process/system shall not be operated unless the vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 2, System 1 , 2]

S15.8 The vent gases from all affected devices of this process/system shall be vented as follows:

All sour gases shall be directed to the absorber located within this system.

This process/system shall not be operated unless the absorber is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 9, System 1]

S15.9 The vent gases from all affected devices of this process/system shall be vented as follows:

All sour gases shall be directed to the absorber located within this system or the absorber located in the Product (Jet Fuel/Diesel/Other) Hydrodesulfurization Unit (P4/S5).

This process/system shall not be operated unless the absorber is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 4, System 1]

S15.10 The vent gases from all affected devices of this process/system shall be vented as follows:

All sour gases shall be directed to the absorber located in the Saturate Gas Plant (P9/S1), the Unsaturate Gas Plant (P9/S2), or the DEA Absorption System (P11/S5).

This process/system shall not be operated unless the absorber is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 1, System 1; Process 4, System 5]

S15.11 The vent gases from all affected devices of this process/system shall be vented as follows:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All sour gases shall be directed to the absorber located in the Unsaturate Gas Plant (P9/S2) or the DEA Absorption System (P11/S5).

This process/system shall not be operated unless the absorber is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 3, System 5]

S15.12 The vent gases from all affected devices of this process/system shall be vented as follows:

All sour gases shall be directed to the absorber located in the Saturate Gas Plant (P9/S1), the Unsaturate Gas Plant (P9/S2), the Product (Jet Fuel/Diesel/Other) Hydrodesulfurization Unit (P4/S5), or the DEA Absorption System (P11/S5).

This process/system shall not be operated unless the absorber is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 4, System 3]

S15.13 The vent gases from all affected devices of this process/system shall be vented as follows:

All sour gases shall be directed to the absorber located in the Saturate Gas Plant (P9/S1), the Product (Jet Fuel/Diesel/Other) Hydrodesulfurization Unit (P4/S5), or the DEA Absorption System (P11/S5).

This process/system shall not be operated unless the absorber is in full use and has a valid permit to receive vent gases from this system.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 5, System 1 , 2; Process 7, System 1]

S15.14 The vent gases from all affected devices of this process/system shall be vented as follows:

All sour gases shall be directed to the absorber located in the Fuel Gas Treating Unit (P11/S3), the Unsaturate Gas Plant (P9/S2), or the DEA Absorption System (P11/S5).

This process/system shall not be operated unless the absorber is in full use and has a valid permit to receive vent gases from this system.

During periods of maintenance and/or repair of the Fuel Gas Treating Unit Absorbers (P11/S3), all sour gases shall be directed to the Fuel Gas Treating Unit (P11/S12), the absorber located in the Unsaturate Gas Plant (P9/S2) or the DEA Absorption System (P11/S5).

During periods of maintenance and/or repair of the Fuel Gas Treating Unit Absorbers (P11/S3), the subject process/system shall not be operated unless the equipment specified is in full used and has a valid permit to receive vent gases from this system

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 19, System 3]

S15.15 The vent gases from all affected devices of this process/system shall be vented as follows:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All emergency vent gases shall be directed to the vapor recovery system and/or flare.

This process/system shall not be operated unless the vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

This process/system shall not be operated unless the flare is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 2, System 9; Process 6, System 6; Process 7, System 3; Process 9, System 6; Process 16, System 3]

S15.16 The vent gases from all affected devices of this process/system shall be vented as follows:

All vent gases shall be directed to the vapor recovery system unless otherwise specified in this permit.

All blowdown water shall be directed to knockout vessel(s) at the vapor recovery system for water removal.

This process/system shall not be operated unless the vapor recovery system is in full use and has a valid permit to receive vent gases from this system.

[RULE 1303(a)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 15, System 3]

S18.1 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Loading/Unloading Process (Process: 13, System: 1, 2, 3 & 4)

Hydrogen Production (Process: 6, System: 1, 2 & 6)

Gas Production Process (Process: 9, System: 1, 2, 5 & 6)

Catalytic Reforming (Process: 5, System: 1 & 2)

Treating/Stripping Process (Process: 11, System: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11 & 12)

Fluid Catalytic Cracking Unit (Process: 3, System: 1, 5 & 7)

Petroleum Miscellaneous Process (Process: 17, System: 5, 8 & 11)

Hydrocracking Unit (Process: 7, System: 1 & 3)

Air Pollution Control Process (Process: 19, System: 3)

Crude Distillation Unit (Process: 1, System: 1, 2, 3, 4 & 7)

Coking and Residual Conditioning (Process: 2, System: 1, 2, 4, 5 & 9)

Hydrotreating Process (Process: 4, System: 1, 3 & 5)

Alkylation Unit (Process: 8, System: 1, 2, 3, 4 & 6)

Sulfur Production Process (Process: 12, System: 1, 2, 3 & 4)

Steam Generation Process (Process: 16, System: 3)

Electricity Generation (Process: 18, System: 1)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 19, System 1]

S18.2 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Hydrocracking Unit (Process: 7, System: 1)

Platinum Reformer Unit (Process: 5, System: 1 & 2)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 9, System 1]

S18.3 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Treating/Stripping Units (Process: 11, System: 6, 7, 9, 10 & 11)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 12, System 1 , 2]

S18.4 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Sulfur Storage (Process: 12, System: 6)

Sulfur Loading (Process: 13, System: 6)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Systems subject to this condition : Process 13, System 7]

- S18.5 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Sulfur Vapor Collection System (Process: 13, System: 7)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 13, System 8]

- S18.6 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Resid Loading Sytem (Process: 13, System: 9)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 13, System 10]

- S18.7 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Wastewater Treatment System (Process: 14, System: 1)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 14, System 2]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

S18.12 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

Sulfur Production, Claus Trains A & B (Process: 12, System: 1 & 2)

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 12, System 3 , 4]

S18.13 All affected devices listed under this process/system shall be used only to receive, recover and/or dispose of vent gases routed from the system(s) or process(es) listed below, in addition to specific devices identified in the "connected to" column:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Loading/Unloading Process (Process: 13, System: 1, 2, 3 & 4)

Catalyst Regeneration Process (Process: 10, System: 1)

Hydrogen Production (Process: 6, System: 1, 2 & 6)

Gasoline Blending (Process: 20, System: 1)

Gas Production Process (Process: 9, System: 1, 2, 5 & 6)

Catalytic Reforming (Process: 5, System: 1 & 2)

Treating/Stripping Process (Process: 11, System: 1, 2, 3 & 5)

Fluid Catalytic Cracking Unit (Process: 3, System: 1 & 5)

Petroleum Miscellaneous Process (Process: 17, System: 5, 8 & 11)

Hydrocracking Unit (Process: 7, System: 1 & 3)

Crude Distillation Unit (Process: 1, System: 1, 2, 3 & 4)

Coking and Residual Conditioning (Process: 2, System: 1, 2, 4, 5 & 9)

Hydrotreating Process (Process: 4, System: 1, 3 & 5)

Alkylation Unit (Process: 8, System: 1, 2, 3 & 4)

Dehydrator Unit (Process: 17, System: 16)

Pressurized Storage Tanks (Process: 15, System: 3)

Steam Generation Process (Process: 16, System: 3)

Sulfur Production Process (Process: 12, System: 4)

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 19, System 3]

S31.2 The following BACT requirements shall apply to VOC service fugitive components associated with the devices that are covered by application number(s) 280605, 384499, 385155, 389291, 389292, 411508, 411586, 422171, 422931, 431362, 471343, 483739 and 435111:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All valves shall be bellow-sealed except in the following applications: valves in heavy liquid service, control valves, instrument piping/tubing valves, valves requiring torsional stem motion, situations where valve failure could pose safety hazard (e.g., drain valves with stems in the horizontal position), retrofit/special application valves with space limitation and valves not commercially available. District shall approve all exceptions to this requirement.

All valves and new major components shall be physically identified in the field with special markings that distinguish the components from non-BACT components. Additionally, all new components shall be identified as BACT components in the record.

All valves shall be inspected monthly using EPA Reference Method 21. The operator may revert to quarterly inspection upon District approval, after two consecutive monthly inspections in which only two percent or less are found to be leaking above 500 ppmv. For leaks greater than 500 ppmv above background, repair shall be attempted within five (5) days of detection. Repair or replacement shall be completed within 15 days, unless demonstrated otherwise.

The operator shall keep records of the monthly inspections, subsequent repairs and reinspections, if any, in a manner approved by the District.

The operator shall provide the following information to the District no later than 60 days after initial startup of the equipment in the system:

- a) Piping and instrumentation diagrams (or some other equivalent District-approved diagrams) that identify all valves. The operator shall also provide a listing of all valves (bellows and non-bellows) categorized by location, type, size, accessibility, and service; and
- b) Recalculation of fugitive emissions based on actual fugitive components installed and removed from service. All valves shall be categorized by tag number, type, size, body material, service, and reason(s) why bellow seal valves were not used.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 4, System 1, 3; Process 6, System 2; Process 7, System 1, 3; Process 9, System 6; Process 13, System 1, 3, 4, 11; Process 18, System 1]

S31.3 The following BACT requirements shall apply to VOC service fugitive components associated with the devices that are covered by application number(s) 435112 & subsequent application number 475236:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All valves shall be bellow-sealed except in the following applications: valves in heavy liquid service, control valves, instrument piping/tubing valves, valves requiring torsional stem motion, situations where valve failure could pose safety hazard (e.g., drain valves with stems in the horizontal position), retrofit/special application valves with space limitation and valves not commercially available. District shall approve all exceptions to this requirement.

All valves and new major components shall be physically identified in the field with special markings that distinguish the components from non-BACT components. Additionally, all new components shall be identified as BACT components in the record.

All valves shall be inspected monthly using EPA Reference Method 21. The operator may revert to quarterly inspection upon District approval, after two consecutive monthly inspections in which only two percent or less are found to be leaking above 500 ppmv. For leaks greater than 500 ppmv above background, repair shall be attempted within five (5) days of detection. Repair or replacement shall be completed within 15 days, unless demonstrated otherwise.

The operator shall keep records of the monthly inspections, subsequent repairs and reinspections, if any, in a manner approved by the District.

The operator shall provide the following information to the District no later than 60 days after initial startup of the equipment in the system:

- a) Piping and instrumentation diagrams (or some other equivalent District-approved diagrams) that identify all valves. The operator shall also provide a listing of all valves (bellows and non-bellows) categorized by location, type, size, accessibility, and service; and
- b) Recalculation of fugitive emissions based on actual fugitive components installed and removed from service. All valves shall be categorized by tag number, type, size, body material, service, and reason(s) why bellow seal valves were not used.

The operator shall provide the following information to the District prior to

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

converting AN 435112 and subsequent AN 475236 from PC to PO (Process 11, System 12):

Recalculation of fugitive emissions based on actual fugitive components installed in Process 11, Systems 3 & 4 (ANs 422300 & 377122), which were combined with System 12 in the previously issued permit, for NSR adjustment

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 11, System 3 , 4]

S31.4 The following BACT requirements shall apply to VOC service fugitive components associated with the devices that are covered by application number(s) 448496:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All valves shall be bellow-sealed except in the following applications: valves in heavy liquid service, control valves, instrument piping/tubing valves, valves requiring torsional stem motion, situations where valve failure could pose safety hazard (e.g., drain valves with stems in the horizontal position), retrofit/special application valves with space limitation and valves not commercially available. District shall approve all exceptions to this requirement.

All valves and new major components shall be physically identified in the field with special markings that distinguish the components from non-BACT components. Additionally, all new components shall be identified as BACT components in the record.

All valves shall be inspected monthly using EPA Reference Method 21. The operator may revert to quarterly inspection upon District approval, after two consecutive monthly inspections in which only two percent or less are found to be leaking above 500 ppmv. For leaks greater than 500 ppmv above background, repair shall be attempted within five (5) days of detection. Repair or replacement shall be completed within 15 days, unless demonstrated otherwise.

The operator shall keep records of the monthly inspections, subsequent repairs and reinspections, if any, in a manner approved by the District.

The operator shall provide the following information to the District no later than 60 days after initial startup of the equipment in the system:

- a) Piping and instrumentation diagrams (or some other equivalent District-approved diagrams) that identify all valves. The operator shall also provide a listing of all valves (bellows and non-bellows) categorized by location, type, size, accessibility, and service; and
- b) Recalculation of fugitive emissions based on actual fugitive components installed and removed from service. All valves shall be categorized by tag number, type, size, body material, service, and reason(s) why bellow seal valves were not used.

The operator shall provide the following information to the District prior to

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

converting AN 448496 from PC to PO (Process 1, System 4):

Recalculation of fugitive emissions based on actual fugitive components installed in Process 1, Systems 1 & 4 (ANs 431770 & 448496), which were combined with System 1 in the previously issued permit, for NSR adjustment

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 1, System 4]

S31.5 The following BACT requirements shall apply to VOC service fugitive components associated with the devices that are covered by application number(s) 422369, 422169, 422177, 422381, 422935 & 528281:

All valves and major components shall be physically identified in the field with special markings that distinguish the components from non-BACT components. Additionally, all new components shall be identified as BACT components in the record.

All valves shall be inspected monthly using EPA Reference Method 21. The operator may revert to quarterly inspection upon District approval, after two consecutive monthly inspections in which only two percent or less are found to be leaking above 500 ppmv. For leaks greater than 500 ppmv above background, repair shall be attempted within five (5) days of detection. Repair or replacement shall be completed within 15 days, unless demonstrated otherwise.

The operator shall keep records of the monthly inspections, subsequent repairs and reinspections, if any, in a manner approved by the District.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 2, System 9; Process 6, System 6; Process 16, System 3; Process 17, System 2]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

S42.2 The operator shall not operate the FCCU unless the operator complies with the emission limits of the following rule by May 30, 2009 or 90 days from the date of start up of the FCCU from turnaround, whichever is earlier:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| PM10 | District Rule | 1105.1 |
| NH3 | District Rule | 1105.1 |

If the operator fails to comply with any of the terms and conditions listed below, the operator shall be subject to the compliance deadlines as specified in Rule 1105.1(d) (1).

1. Award contract(s) to construct and install the control technology by May 1, 2007
2. Begin construction of the control technology permitted by the AQMD for compliance with Rule 1105.1(d)(1) by October 1, 2007, or within 30 days of receiving all necessary permits, whichever is later. These dates may be extended in writing by the Executive Officer upon request by ExxonMobil if the CEQA document is not finalized by July 1, 2007. Any such extension(s) shall not be for a period of more than five months after the original deadline listed in this paragraph.
3. Start operation of at least one (1) new ESP (i.e., either C2283 or C2284) along with two (2) existing ESPs, C165 and C166) to ensure compliance with Rule 1105.1(d)(1) by March 1, 2009 with the startup of the FCCU. If one (1) new ESP is operated, the inlet flowrate to the ESP shall not exceed 160,000 dscfm
4. Comply with all Rule 1105.1(d)(1) requirements no later than May 30, 2009, or 90 days after the startup of the FCCU, whichever is earlier

[RULE 1105.1, 11-7-2003]

[Systems subject to this condition : Process 3, System 1; Process 23, System 1]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

S46.1 The following conditions shall apply to VOC service fugitive components in this system:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, leakless valve shall be defined as any valve equipped with sealed bellow or equivalent as approved in writing by the District prior to installation. Components shall be defined as any valve, flange, fitting, pump, compressor, pressure relief device, diaphragm, hatch, sight-glass, and meter, which are not exempted by Rule 1173.

For the purpose of this condition, existing component shall be defined as any component that was installed under a permit to construct/operate that was issued prior to June 1, 1993. New component shall be defined as any component that was installed or modified under a permit to construct that triggered BACT for VOCs issued between June 1, 1993 and December 27, 2001.

All new valves in VOC service shall be of leakless type, except those specifically exempted by Rule 1173 or approved by the District in the following applications: heavy liquid service, control valves, instrument piping/tubing, applications requiring torsional valve stem motion, applications where failures could pose safety hazards (e.g. drain valves with valve stems in horizontal position), retrofits with space limitations, and valves not commercially available.

All new valves and new major components, as defined in Rule 1173, shall be physically identified in the field with special marking that distinguishes the components from existing. Additionally all new components shall be distinctly identified from existing components through their tag numbers (e.g. numbers ending in the letter "N"), and shall be noted in the records.

All new components in VOC service with a leak greater than 500 ppm but less than 1,000 ppm, as methane, measured above background using EPA Method 21, shall be repaired within 14 days of detection. A leak greater than 1,000 ppm shall be repaired according to Rule 1173.

All new pressure relief valves shall be connected to closed vent system or equipped with rupture disc.

All new sampling connections shall be closed-purge, closed-loop, or closed-vent system.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Systems subject to this condition : Process 8, System 5]

DEVICE CONDITIONS

A. Emission Limits

A63.3 The operator shall limit emissions from this equipment as follows:

| CONTAMINANT | EMISSIONS LIMIT |
|-------------------|------------------------------|
| Visible emissions | Less than 10 Percent opacity |

The emission limit applies for discharges of duration of greater than 3 minutes in any one hour

[RULE 1158, 6-11-1999; RULE 1158, 7-11-2008]

[Devices subject to this condition : D129, D130, D919, D2291, D2292, D2293, D2294, D2295, D2296, D2297, D2298, D2299, D2300, D2301, D2302, D2303, D2331, D2332, D2333, D2334, D2335, D2389]

A63.4 The operator shall limit emissions from this equipment as follows:

| CONTAMINANT | EMISSIONS LIMIT |
|-------------------|--|
| Visible emissions | Less than or equal to 30 Percent opacity |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : D151]

A63.5 The operator shall limit emissions from this equipment as follows:

| CONTAMINANT | EMISSIONS LIMIT | Header 3 | Header 4 |
|-------------------|-----------------------|----------|-----------------|
| Visible emissions | Less than or equal to | 20 | Percent opacity |

[40CFR 60SubpartD, 2-16-2012]

[Devices subject to this condition : D805]

A72.1 The operator shall maintain this equipment to achieve a minimum overall control efficiency of 95 percent for VOC during the normal operation of the equipment it vents.

[RULE 1176, 9-13-1996; 40CFR 60 Subpart QQQ, 10-17-2000]

[Devices subject to this condition : C686, C687]

A99.1 The 2.8 lb/1000 bbl fresh feed PM10 emission limit(s) shall only apply when the fresh feed to the FCCU is 105 thousand barrels per day or less.

For the purposes of this condition, PM10 emissions shall be defined as filterable PM10 collected on the cyclone exit, probe and filters of the applicable test methods referenced in the Rule.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : D151]

A99.2 The 0.005 gr/dscf PM10 emission limit(s) shall only apply when the flow rate is 320,000 dscfm or less.

For the purposes of this condition, PM10 emissions shall be defined as filterable PM10 collected on the cyclone exit, probe and filters of the applicable test methods referenced in the Rule.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : D151]

A99.3 The 3.6 Lbs/hr PM10 emission limit(s) shall only apply when the fresh feed exceeds 105 thousand barrels per day and the flow rate exceeds 320,000 dscfm.

For the purposes of this condition, PM10 emissions shall be defined as filterable PM10 collected on the cyclone exit, probe and filters of the applicable test methods referenced in the Rule.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : D151]

A99.4 The 42 Lbs/hr NOX emission limit(s) shall not apply during startup, shutdown or malfunction..

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For purpose of this condition, start-up and shutdown shall be defined as the time period during the startup and shutdown of the heater unit when the temperature of the exhaust gas at the inlet to SCR is below 550 degree F.

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : D926]

A195.1 The 9 PPMV NOX emission limit(s) is averaged over 15 minutes corrected to 15% excess oxygen, dry basis.

For purpose of this condition, the limit applies at all times except during startup, shutdown, or malfunction when the temperature of the exhaust gas at the inlet to the SCR is below 550 degrees F.

[RULE 2005, 5-6-2005]

[Devices subject to this condition : D925, D926]

A195.2 The 10 PPMV NH3 emission limit(s) is averaged over consecutive 60 minutes at 3% oxygen, dry basis.

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : D151, C1772]

A195.3 The 20 PPMV NOX emission limit(s) is averaged over 365-day rolling and at 0% oxygen.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purposes of this condition, this limit is a long term limit which applies at all times except during startup, shut down or malfunction.

For purpose of this condition, start-up and shutdown shall be defined as the time period during the startup and shutdown of the SCR (Device C1772) when the temperature of the exhaust gas at the inlet to SCR is below 500 degree F and NH₃ is not injected.

[CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D151]

A195.4 The 40 PPMV NOX emission limit(s) is averaged over 7-day rolling and at 0% oxygen.

For the purposes of this condition, this limit is a short term limit which applies at all times except during startup, shutdown, malfunction, or when the Waste Heat Boiler 2F-7 is shutdown for inspection per California Code of Regulation Title 8, Section 770(b).

For purpose of this condition, start-up and shutdown shall be defined as the time period during the startup and shutdown of the SCR (Device C1772) when the temperature of the exhaust gas at the inlet to SCR is below 500 degree F and NH₃ is not injected.

[CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D151]

A195.5 The 140 PPMV NOX emission limit(s) is averaged over 24-hour rolling and at 0% oxygen.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purposes of this condition, this limit is not to exceed 14 days per occurrence, when the SCR is shutdown because the waste heat boiler 2F-7 is shutdown for inspection per California Code of Regulations, Title 8, Section 770(b).

For purpose of this condition, start-up and shutdown shall be defined as the time period during the startup and shutdown of the SCR (Device C1772) when the temperature of the exhaust gas at the inlet to SCR is below 500 degree F and NH3 is not injected.

[CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D151]

A195.6 The 25 PPMV SOX emission limit(s) is averaged over 365-day rolling and at 0% oxygen.

For the purposes of this condition, this limit is a long term limit which applies at all times.

[CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D151]

A195.7 The 50 PPMV SOX emission limit(s) is averaged over 7-day rolling and at 0% oxygen.

For the purposes of this condition, this limit is a short term limit which applies at all times except during startup, shutdown, or malfunction.

[CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D151]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A195.9 The 9 PPMV NOX emission limit(s) is averaged over 60 minutes corrected to 3% excess oxygen, dry basis. For the purpose of this condition, this limit is a long term limit which applies at all times except during startup, shut down, or malfunction.

For purpose of this condition, start-up and shutdown shall be defined as the time period during the start-up and shutdown of the SCR (Devices C1238, C1241) when the temperature of the exhaust gas at the inlet to SCR is below 550 degrees F and NH3 is not injected.

SUGGESTED CHAR . CONDITION PARAMETER NOT SET UP

[RULE 2005, 5-6-2005]

[Devices subject to this condition : D1236, D1239]

A195.10 The 82 PPMV NOX emission limit(s) is averaged over 365-day rolling and at 3% oxygen.

For the purposes of this condition, this limit is a short term limit which applies at all times except during startup, shut down or malfunction.

For purpose of this condition, the 2F-4 FGR is in full used when it is operating and the NOx emission limit specified in this condition is met.

[CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D803]

A327.1 For the purpose of determining compliance with District Rule 475, combustion contaminant emissions may exceed the concentration limit or the mass emission limit listed, but not both limits at the same time.

[RULE 475, 10-8-1976; RULE 475, 8-7-1978]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D926]

A327.2 For the purpose of determining compliance with District Rule 476, combustion contaminant emissions may exceed the concentration limit or the mass emission limit listed, but not both limits at the same time.

[RULE 476, 10-8-1976]

[Devices subject to this condition : D803, D805, D1236, D1239]

B. Material/Fuel Type Limits

B22.1 The operator shall not use this equipment with materials having a(n) true vapor pressure of 11 psia or greater under actual operating conditions.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D692, D730, D747, D773, D774, D776, D778, D779]

B22.3 The operator shall only use this equipment with materials having a(n) true vapor pressure of 5.23 psia or less under actual operating conditions.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1763]

B22.5 The operator shall not use this equipment with materials having a(n) Reid vapor pressure of 13 psia or greater under actual operating conditions.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D708]

B22.8 The operator shall not use this equipment with materials having a(n) true vapor pressure of 1 psia or greater under actual operating conditions.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D751]

B22.9 The operator shall not use this equipment with materials having a(n) true vapor pressure of 0.1 psia or greater under actual operating conditions.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D716, D719]

B22.10 The operator shall not use this equipment with materials having a(n) true vapor pressure of 4 psia or greater under actual operating conditions.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D765]

B22.11 The operator shall not use this equipment with materials having a(n) true vapor pressure of 1.13 psia or greater under actual operating conditions.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1743, D1747, D1751, D1755]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

B22.12 The operator shall not use this equipment with materials having a(n) true vapor pressure of 0.1 psia or greater under actual operating conditions.

[RULE 1301, 12-7-1995; RULE 3004(a)(1), 12-12-1997]

[Devices subject to this condition : D725, D2447]

B22.13 The operator shall only use this equipment with materials having a(n) true vapor pressure of 0.1 psia or less under actual operating conditions.

[RULE 1301, 12-7-1995; RULE 3004(a)(1), 12-12-1997]

[Devices subject to this condition : D718]

B27.1 The operator shall not use materials containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401, as amended 03-07-2008.

[RULE 1401, 6-5-2009]

[Devices subject to this condition : D2395]

B27.2 The operator shall not use materials containing any toxic air contaminants (TACs) identified in the SCAQMD Rule 1401, as amended 06-05-2009.

[RULE 1401, 6-5-2009]

[Devices subject to this condition : D167]

B59.1 The operator shall only use the following material(s) in this device :

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Finished Gasoline, Oxygenated gasoline additives, Dehexanizer overhead/bottoms, Alkylate, Light/Heavy FCC, Light/heavy hydrocracked naphtha, Reformate, Light straight run, Hydrotreated naphtha, Isooctane/isooctene, Raffinate, Cat poly gasoline, RBOB

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1401, 6-5-2009]

[Devices subject to this condition : D761, D762]

B59.2 The operator shall only use the following material(s) in this device :

Diesel fuel, acid soluble oil, clarified slurry oil, vacuum gas oil, light vacuum gas oil, full range vacuum gas oil, heavy vacuum gas oil, ligh cycle oil

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D702]

B61.1 The operator shall only use fuel gas containing the following specified compounds:

| Compound | ppm by volume |
|--|---------------|
| total sulfur calculated as H2S less than | 100 |

[RULE 2005, 5-6-2005]

[Devices subject to this condition : D925, D1236, D1239]

B61.2 The operator shall only use diesel fuel containing the following specified compounds:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Compound | weight percent |
|------------------------------|----------------|
| Sulfur less than or equal to | 0.05 |

[RULE 2005, 5-6-2005]

[Devices subject to this condition : D394, D955, D957, D959, D961, D1686, D1785, D1786]

B61.3 The operator shall not use fuel gas containing the following specified compounds:

| Compound | ppm by volume |
|------------------|---------------|
| H2S greater than | 160 |

[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D83, D84, D85, D120, C164, D231, D232, D234, D235, D367, C626, D803, D805, D833, D913, D914, D917, D918, D920, D925, D927, D928, D929, D930, D931, D949, D950, D1403]

B61.4 The operator shall not use fuel gas containing the following specified compounds:

| Compound | ppm by volume |
|---|---------------|
| Total sulfur compounds calculated as H2S greater than | 30 |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 2005, 5-6-2005]

[Devices subject to this condition : D926]

B61.5 The operator shall not use (or combust) vent gas containing the following specified compounds:

| Compound | ppm by volume |
|------------------|---------------|
| H2S greater than | 160 |

The 160 ppmv limit is averaged over three hours, excluding any vent gas resulting from an emergency, shutdown, startup, process upset or relief valve leakage

[RULE 1118, 11-4-2005]

[Devices subject to this condition : C891, C892, C894, C1558]

B61.6 The operator shall not use fuel gas containing the following specified compounds:

| Compound | ppm by volume |
|------------------|---------------|
| H2S greater than | 160 |

[40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : D926]

B61.7 The operator shall only use diesel fuel containing the following specified compounds:

| Compound | Header 2 | ppm by weight |
|----------|-----------------------|---------------|
| Sulfur | less than or equal to | 15 |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 2005, 6-3-2011]

[Devices subject to this condition : D2428]

B61.8 The operator shall not use fuel gas containing the following specified compounds:

| Compound | Header 2 | ppm by weight |
|----------|--------------|---------------|
| H2S | greater than | 400 |

The 400 ppmv H2S limit is equivalent to 0.06 lb/MMBtu SO2 emissions specified in Subpart D.

By compliance with SO2 limit of 0.06 lb/MMBtu, the operator is not required to comply with PM limit of 0.1 lb/MMBtu specified in Subpart D.

[40CFR 60 Subpart D, 10-4-1991]

[Devices subject to this condition : D805]

C. Throughput or Operating Parameter Limits

C1.1 The operator shall limit the firing rate to no more than 108 MM Btu per hour.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D920]

C1.2 The operator shall limit the firing rate to no more than 129 MM Btu per hour.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D930]

C1.3 The operator shall limit the firing rate to no more than 73 MM Btu per hour.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D931]

C1.4 The operator shall limit the fuel usage to no more than 1.6 MM cubic feet per day.

For the purpose of this condition, fuel usage shall be defined as gas usage.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D917]

C1.5 The operator shall limit the firing rate to no more than 64 MM Btu per hour.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D950]

C1.6 The operator shall limit the number of turnovers to no more than 146 in any one year.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D692]

C1.7 The operator shall limit the number of turnovers to no more than 39 in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D716]

C1.8 The operator shall limit the throughput to no more than 5000000 barrels in any one calendar year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D776]

C1.9 The operator shall limit the throughput to no more than 9250000 barrels in any one calendar year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D778, D779]

C1.10 The operator shall limit the number of turnovers to no more than 34 in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D724]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.11 The operator shall limit the number of turnovers to no more than 41 in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D773, D774]

C1.12 The operator shall limit the firing rate to no more than 931 MM Btu per hour.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 2005, 5-6-2005]

[Devices subject to this condition : D925]

C1.13 The operator shall limit the number of turnovers to no more than 40 in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D726]

C1.14 The operator shall limit the firing rate to no more than 340 MM Btu per hour.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1236, D1239]

C1.15 The operator shall limit the operating time to no more than 199 hour(s) in any one year.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1110.2, 2-1-2008; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]

[Devices subject to this condition : D394, D955, D957, D959, D961, D1686, D1785, D1786]

C1.17 The operator shall limit the throughput to no more than 1.59505e+07 barrel(s) in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1763]

C1.18 The operator shall limit the number of turnovers to no more than 24.5 in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1685]

C1.19 The operator shall limit the throughput to no more than 216720 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1925]

C1.20 The operator shall limit the throughput to no more than 1000 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D1926]

C1.21 The operator shall limit the throughput to no more than 1517 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1927]

C1.22 The operator shall limit the throughput to no more than 8333 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1928]

C1.23 The operator shall limit the throughput to no more than 1473 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1930]

C1.25 The operator shall limit the throughput to no more than 4442 gallon(s) per month.

To comply with this condition, the operator shall maintain purchase records in a manner approved by the District. Such records shall be made available to District personnel upon request.

[RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D1917]

C1.26 The operator shall limit the throughput to no more than 2000 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1918]

C1.27 The operator shall limit the throughput to no more than 1474 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1919]

C1.29 The operator shall limit the throughput to no more than 220000 barrel(s) in any one calendar month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall calculate the throughput, in barrels, by the following equation: $0.14 \times D \times D \times L$, where D is the diameter of the tank in feet based on the tank strapping chart and L is the total vertical one-way roof travel in feet per month.

The operator shall install and maintain an automatic tank level gauge (ATLG) and recorder to continuously record the vertical movement of the roof. For the purpose of this condition, continuous recording is defined as once per every 15 minutes.

The operator shall calculate the total one-way roof movement, in feet, on a daily and monthly basis.

The ATLG installed shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 1.0 inch or 0.8 percent, whichever is greater, the ATLG shall be repaired and put back into service within 10 days. While the ATLG is being repaired, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the discovery of the discrepancy.

In the event of a failure or routine maintenance of the ATLG, the ATLG shall be repaired (if necessary) and put back into service within 10 days of the time that the ATLG failed or was removed from service for maintenance. While the ATLG is being repaired or maintained, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the time that the ATLG went out of service.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D742, D743]

- C1.30 The operator shall limit the throughput to no more than 737000 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: $V / H(\text{subscript: t}) \times H(\text{subscript: a})$, where V is the volume of the tank in barrels based on the most recent version of API Standard 2550, H(subscript: t) is the height of the tank based on tank strapping chart and H(subscript: a) is the total vertical one-way liquid surface level travel in feet per month.

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 0.8 percent, the ATLG shall be repaired. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the previous 30 days, prior to the discovery of the discrepancy.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D757]

C1.31 The operator shall limit the throughput to no more than 703500 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: V/H (subscript: t) x H (subscript: a), where V is the volume of the tank in barrels based on the most recent version of API Standard 2550, H (subscript: t) is the height of the tank based on the tank strapping chart and H (subscript: a) is the total vertical one-way liquid surface level travel in feet per month..

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis..

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than .8 percent, the ATLG shall be repaired. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the previous 30 days, prior to the discovery of the discrepancy..

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1220]

C1.32 The operator shall limit the throughput to no more than 270000 barrel(s) in any one calendar month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall comply with the following throughput measuring practices:

The operator shall calculate the throughput, in barrels, by the following equation: V/H (subscript: t) x H (subscript: a), where V is the volume of the tank in barrels based on the most recent version of the API Standard 2550, H (subscript: t) is the height of the tank based on the tank strapping chart and H (subscript: a) is the total vertical one-way liquid surface level travel in feet month.

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement and record the liquid level reading every 15 minutes. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 0.8 percent, the ATLG shall be repaired.

While the ATLG is being repaired, throughput shall be determined by the hourly tank level data averaged for the previous 30 days, prior to the discovery of the discrepancy.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1743, D1747, D1751, D1755]

- C1.33 The operator shall limit the throughput to no more than 145000 barrel(s) in any one calendar month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall calculate the throughput, in barrels, by the following equation: $0.14 \times D \times D \times L$, where D is the diameter of the tank in feet based on the tank strapping chart and L is the total vertical one-way roof travel in feet per month.

The operator shall install and maintain an automatic tank level gauge (ATLG) and recorder to continuously record the vertical movement of the roof. For the purpose of this condition, continuous recording is defined as once per every 15 minutes.

The operator shall calculate the total one-way roof movement, in feet, on a daily and monthly basis.

The ATLG installed shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 1.0 inch or 0.8 percent, whichever is greater, the ATLG shall be repaired and put back into service within 10 days. While the ATLG is being repaired, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the discovery of the discrepancy.

In the event of a failure or routine maintenance of the ATLG, the ATLG shall be repaired (if necessary) and put back into service within 10 days of the time that the ATLG failed or was removed from service for maintenance. While the ATLG is being repaired or maintained, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the time that the ATLG went out of service.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D734, D735]

C1.37 The operator shall limit the number of turnovers to no more than 50 in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D715]

C1.42 The operator shall limit the number of turnovers to no more than 10 in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D751]

C1.44 The operator shall limit the throughput to no more than 439342 barrel(s) in any one month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1924]

C1.45 The operator shall limit the throughput to no more than 135972 barrel(s) in any one month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D915]

C1.46 The operator shall limit the throughput to no more than 46666 barrel(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as throughput of fuel oil.

[RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D1897, D1898]

C1.47 The operator shall limit the loading rate to no more than 730000 barrel(s) in any one month.

This limit shall be based on the total combined limit for equipment D1526 & D1520, Loading Racks # 1 & 3, respectively.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1520, D1526]

C1.48 The operator shall limit the throughput to no more than 457833 barrel(s) in any one month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D761, D762]

C1.49 The operator shall limit the number of turnovers to no more than 52 in any one year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1787]

C1.50 The operator shall limit the throughput to no more than 240000 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, throughput shall be defined as throughput of gasoline, light gas oil, light vacuum gas oil, heavy gas oil, heavy vacuum gas oil, hydrotreated kerosene, hydrotreated vacuum gas oil, hydrodesulfurized middle distillate, and straight run gas oil combined.

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: V/H (subscript: t) x H (subscript: a), where V is the volume of the tank in barrels based on the most recent version of the API Standard 2550, H (subscript: t) is the height of the tank based on the tank strapping chart and H (subscript: a) is the total vertical one-way liquid surface level travel in feet month.

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement and record the liquid level reading every 15 minutes. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement.

If the ATLG differs from the manual tank level measurement by more than 1.0 inch or 0.8 percent whichever is greater, the ATLG shall be repaired and put back into service within 10 days of the time that the ATLG failed or was removed from service for maintenance. While the ATLG is being repaired, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the discovery of the discrepancy.

In the event of a failure or routine maintenance of the ATLG, the ATLG shall be repaired (if necessary) and put back into service within 10 days of the time that the ATLG failed or was removed from service. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the prior 30 days, prior to the discovery of the discrepancy.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D708]

C1.51 The operator shall limit the throughput to no more than 759,333 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For the purpose of this condition, throughput shall be defined as throughput of gasoline, light vacuum gas oil, heavy vacuum gas oil, kerosene, hydrodesulfurized middle distillate, and straight run gas oil combined.

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: V/H (subscript: t) x H (subscript: a), where V is the volume of the tank in barrels based on the most recent version of the API Standard 2550, H (subscript: t) is the height of the tank based on the tank strapping chart and H (subscript: a) is the total vertical one-way liquid surface level travel in feet month.

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement and record the liquid level reading every 15 minutes. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement.

If the ATLG differs from the manual tank level measurement by more than 1.0 inch 0.8 percent whichever is greater, the ATLG shall be repaired and put back into service within 10 days. While the ATLG is being repaired, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the discovery of the discrepancy.

In the event of a failure or routine maintenance of the ATLG, the ATLG shall be repaired (if necessary) and put back into service within 10 days of the time that the ATLG failed or was removed from service. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the prior 30 days, prior to the discovery of the discrepancy.

[RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D764]

- C1.52 The operator shall limit the throughput to no more than 428333 barrel(s) in any one calendar month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2005]

- C1.53 The operator shall limit the throughput to no more than 428333 barrel(s) in any one calendar month.

For the purpose of this condition, throughput shall be defined as the amount of LSR loaded from Tank 200X1.

[RULE 1304(c)-Offset Exemption, 6-14-1996]

[Devices subject to this condition : D1994]

- C1.54 The operator shall limit the throughput to no more than 8667 gallon(s) in any one calendar month.

To comply with this condition, the operator shall maintain purchase records in a manner approved by the District. Such records shall be made available to District personnel upon request.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D1916, D2025]

- C1.56 The operator shall limit the throughput to no more than 2167 gallon(s) in any one calendar month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

To comply with this condition, the operator shall maintain purchase records in a manner approved by the District. Such records shall be made available to District personnel upon request.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2023, D2024]

- C1.57 The operator shall limit the throughput to no more than 2427 gallon(s) in any one calendar month.

To comply with this condition, the operator shall maintain purchase records in a manner approved by the District. Such records shall be made available to District personnel upon request.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2026]

- C1.58 The operator shall limit the throughput to no more than 446667 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: $V / H(\text{subscript: t}) \times H(\text{subscript: a})$, where V is the volume of the tank in barrels based on the most recent version of API Standard 2550, H(subscript: t) is the height of the tank based on tank strapping chart and H(subscript: a) is the total vertical one-way liquid surface level travel in feet per month.

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

Automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 0.8 percent, the ATLG shall be repaired. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the previous 30 days, prior to the discovery of the discrepancy.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D725]

C1.59 The operator shall limit the throughput to no more than 500000 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: $V / H(\text{subscript: t}) \times H(\text{subscript: a})$, where V is the volume of the tank in barrels based on the most recent version of API Standard 2550, $H(\text{subscript: t})$ is the height of the tank based on tank strapping chart and $H(\text{subscript: a})$ is the total vertical one-way liquid surface level travel in feet per month.

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 0.8 percent, the ATLG shall be repaired. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the previous 30 days, prior to the discovery of the discrepancy.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D728, D747]

C1.60 The operator shall limit the throughput to no more than 1200000 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: $V / H(\text{subscript: t}) \times H(\text{subscript: a})$, where V is the volume of the tank in barrels based on the most recent version of API Standard 2550, H(subscript: t) is the height of the tank based on tank strapping chart and H(subscript: a) is the total vertical one-way liquid surface level travel in feet per month.

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

Automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 0.8 percent, the ATLG shall be repaired. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the previous 30 days, prior to the discovery of the discrepancy.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D750]

C1.61 The operator shall limit the throughput to no more than 525000 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: $V / H(\text{subscript: t}) \times H(\text{subscript: a})$, where V is the volume of the tank in barrels based on the most recent version of API Standard 2550, H(subscript: t) is the height of the tank based on tank strapping chart and H(subscript: a) is the total vertical one-way liquid surface level travel in feet per month.

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

Automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 0.8 percent, the ATLG shall be repaired. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the previous 30 days, prior to the discovery of the discrepancy.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D727]

C1.62 The operator shall limit the throughput to no more than 165000 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: $V / H(\text{subscript: t}) \times H(\text{subscript: a})$, where V is the volume of the tank in barrels based on the most recent version of API Standard 2550, H(subscript: t) is the height of the tank based on tank strapping chart and H(subscript: a) is the total vertical one-way liquid surface level travel in feet per month.

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

Automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 0.8 percent, the ATLG shall be repaired. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the previous 30 days, prior to the discovery of the discrepancy.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D693, D694]

C1.63 The operator shall limit the throughput to no more than 7200 gallon(s) in any one calendar month.

The operator shall comply with the following throughput measurement practices.

A handheld electronic interface probe shall be used to periodically measure the depth (D) of the stored liquid from the bottom of the storage tank to the stored liquid/air interface.

The operator shall measure the D before the storage tank is emptied by the vacuum truck and calculate the throughput in gallons, which will be totaled at the end of a calendar month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2027, D2029, D2030, D2031, D2032, D2037, D2038, D2039, D2040, D2041, D2042, D2043, D2044, D2045, D2046, D2047, D2048, D2049, D2050, D2065, D2066, D2067, D2071, D2073, D2074, D2075, D2076, D2077, D2078, D2085, D2087, D2088, D2089, D2090, D2091, D2092, D2099, D2100, D2101, D2102, D2103, D2104]

C1.64 The operator shall limit the throughput to no more than 416670 barrel(s) in any one month.

The operator shall comply with the following throughput measurement practices..

The operator shall calculate the throughput, in barrels, by the following equation: V/H (subscript: t) x H (subscript: a), where V is the volume of the tank in barrels based on the most recent version of the API Standard 2550, H (subscript: t) is the height of the tank based on the tank strapping chart and H (subscript: a) is the total vertical one-way liquid surface level travel in feet per month..

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis..

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than .8 percent, the ATLG shall be repaired. While the ATLG is being repaired, throughput shall be determined by hourly tank level data averaged for the previous 30 days, prior to the discovery of the discrepancy..

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D777]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.65 The operator shall limit the throughput to no more than 457834 barrel(s) in any one month.

The operator shall comply with the following throughput measurement practices.

The operator shall calculate the throughput, in barrels, by the following equation: V/H (subscript: t) x H (subscript: a), where V is the volume of the tank in barrels based on the most recent version of the API Standard 2550, H (subscript: t) is the height of the tank based on the tank strapping chart and H (subscript: a) is the total vertical one-way liquid surface level travel in feet per month.

The operator shall calculate the total one-way liquid surface level movement, in feet, on a monthly basis.

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than 0.8 percent, the ATLG shall be repaired.

In the event of a failure or routine maintenance of the ATLG, the ATLG shall be repaired (if necessary) and put back into service within 10 days of the time that the ATLG failed or was removed from service for maintenance. While the ATLG is being repaired or maintained, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the time that the ATLG went out of service.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D752]

C1.66 The operator shall limit the throughput to no more than 100 lb(s) in any one day.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2278]

C1.67 The operator shall limit the loading rate to no more than 24000 lb(s) in any one day.

For the purpose of this condition, loading rate shall be defined as the total loading of base catalyst (GRACE Davison Genesis-2634), base catalyst (Sinopec Ripp ZDOS-T), base catalyst (GRACE ALCYON-U411), catalyst additives (GRACE Davison Olefinsmax ZSM-5), CO promoter (GRACE Davison CP-5), and SOx reducing catalyst (GRACE Davison Super DESOX).

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2395]

C1.68 The operator shall limit the throughput to no more than 2000 ton(s) in any one day.

[RULE 1303, 5-10-1996]

[Devices subject to this condition : D2293]

C1.69 The operator shall limit the maintenance and testing to no more than 34 hour(s) in any one year.

The purpose(s) of this condition is to ensure compliance with requirements of National Fire Protection Association (NFPA) 25 standards.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

**[RULE 1110.2, 2-1-2008; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996;
RULE 1470, 6-1-2007]**

[Devices subject to this condition : D955, D957, D959, D961, D1785]

C1.70 The operator shall limit the maintenance and testing to no more than 20 hour(s) in any one year.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

**[RULE 1110.2, 2-1-2008; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996;
RULE 1470, 6-1-2007]**

[Devices subject to this condition : D394, D1686, D1786]

C1.71 The operator shall limit the operating time to no more than 199 hour(s) in any one year.

This engine shall not be operated more than 199 hours in any one year, which includes no more than 34 hours in any one year and no more than 4.2 hours in any one month, both for maintenance and testing.

The 34 hours limit for maintenance and testing is to ensure compliance with requirements of National Fire Protection Association (NFPA) publication 25.

**[RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 1470, 5-4-2012;
RULE 2012, 5-6-2005]**

[Devices subject to this condition : D2428]

C1.72 The operator shall limit the number of turnovers to no more than 78 in any one year.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D730]

C1.73 The operator shall limit the throughput to no more than 100,000 barrel(s) in any one month.

The operator shall comply with the following throughput measurement practices:.

The operator shall calculate the throughput, in barrels, by the following equation: V/H (subscript: t) x H (subscript: a), where V is the volume of the tank in barrels based on the most recent version of API standard 2550, H (subscript: t) is the height of the tank based on the strapping chart, and H (subscript: a) is the total vertical one-way liquid surface level in feet per month.

The operator shall calculate the total one-way surface level movement, in feet, on a monthly basis..

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than plus or minus 0.8 percent, the ATLG shall be repaired.

In the event of a failure or routine maintenance of the ATLG, the ATLG shall be repaired (if necessary) and put back into service within 10 days of the time that the ATLG failed or was removed from service for maintenance. While the ATLG is being repaired or maintained, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the time that the ATLG went out of service.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D709]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.74 The operator shall limit the throughput to no more than 68,677 barrel(s) in any one month.

The operator shall comply with the following throughput measurement practices:

The operator shall calculate the throughput, in barrels, by the following equation: V/H (subscript: t) x H (subscript: a), where V is the volume of the tank in barrels based on the most recent version of API standard 2550, H (subscript: t) is the height of the tank based on the strapping chart, and H (subscript: a) is the total vertical one-way liquid surface level in feet per month.

The operator shall calculate the total one-way surface level movement, in feet, on a monthly basis..

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than plus or minus 0.8 percent, the ATLG shall be repaired.

In the event of a failure or routine maintenance of the ATLG, the ATLG shall be repaired (if necessary) and put back into service within 10 days of the time that the ATLG failed or was removed from service for maintenance. While the ATLG is being repaired or maintained, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the time that the ATLG went out of service.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D710]

C1.75 The operator shall limit the throughput to no more than 97,200 barrel(s) in any one month.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall comply with the following throughput measurement practices:.

The operator shall calculate the throughput, in barrels, by the following equation: V/H (subscript: t) x H (subscript: a), where V is the volume of the tank in barrels based on the most recent version of API standard 2550, H (subscript: t) is the height of the tank based on the strapping chart, and H (subscript: a) is the total vertical one-way liquid surface level in feet per month.

The operator shall calculate the total one-way surface level movement, in feet, on a monthly basis..

An automatic tank level gauge (ATLG) shall be used to continuously measure the liquid surface level movement. The ATLG shall be verified once per quarter by comparing against a manual tank level measurement. If the ATLG differs from the manual tank level measurement by more than plus or minus 0.8 percent, the ATLG shall be repaired.

In the event of a failure or routine maintenance of the ATLG, the ATLG shall be repaired (if necessary) and put back into service within 10 days of the time that the ATLG failed or was removed from service for maintenance. While the ATLG is being repaired or maintained, the throughput shall be determined by the hourly tank level data averaged from the previous 30 days prior to the time that the ATLG went out of service.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D723]

C1.76 The operator shall limit the throughput to no more than 1,237.5 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D2543]

- C1.77 The operator shall limit the gasoline dispensed to no more than 20,000 gallon(s) in any one calendar month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2546]

- C1.78 The operator shall limit the gasoline dispensed to no more than 240,000 gallon(s) per year.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2546]

- C6.1 The operator shall use this equipment in such a manner that the hydrocarbon concentration being monitored, as indicated below, does not exceed 30 percent of the Lower Explosive Limit.

The operator shall use a lower explosive meter to monitor the hydrocarbon concentration.

[RULE 463, 5-6-2005]

[Devices subject to this condition : D761, D762, D1763]

- C6.3 The operator shall use this equipment in such a manner that the hydrocarbon concentration being monitored, as indicated below, does not exceed 30 percent of the Lower Explosive Limit.

The operator shall use a lower explosimeter to monitor the hydrocarbon concentration.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1178, 4-7-2006]

[Devices subject to this condition : D701, D729, D734, D735, D740, D742, D743, D745, D746, D752, D755, D756, D758, D759, D760, D764, D768, D775]

- C6.4 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 4 inches HG.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the filter.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C2397]

- C8.1 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 1200 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature in the firebox or in the ductwork immediately downstream from the firebox.

The measuring device or gauge shall be accurate to within plus or minus 50 degrees F. It shall be calibrated once every 12 months.

The operator shall also install and maintain a device to continuously record the parameter being measured.

**[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring,
12-12-1997]**

[Devices subject to this condition : C686, C687]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C8.3 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 900 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature in the firebox or in the ductwork immediately downstream from the firebox.

The measuring device or gauge shall be accurate to within plus or minus 50 degrees F. It shall be calibrated once every 12 months.

The operator shall also install and maintain a device to continuously record the parameter being measured.

[RULE 2005, 5-6-2005; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C626]

C8.8 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, is not less than 1000 Deg F.

To comply with this condition, the operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature in the firebox or in the ductwork immediately downstream from the firebox.

The measuring device or gauge shall be accurate to within plus or minus 50 degrees F. It shall be calibrated once every 12 months.

The operator shall also install and maintain a device to continuously record the parameter being measured.

[RULE 2005, 5-6-2005; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C952]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C12.1 The operator shall use this equipment in such a manner that the daily average secondary voltage and current (or total power input) and total primary current being monitored as indicated below are greater than or equal to the values in the most recent source test which demonstrated compliance with the emission limits.

The operator shall install and maintain a continuous monitoring and recording system to accurately measure and record the:

1. primary and secondary current
2. primary and secondary voltage
3. spark rate

at each ESP field. In addition, the operator shall keep records, in a manner approved by the District, for each of these parameters.

If the daily average ESP total power input falls below the level measured in the most recent source test which demonstrated compliance with the emission limit, a source test shall be performed within 90 days at the new minimum daily average ESP total power level. The source test shall be performed for the FCCU regenerator (Device D151) according to the requirements specified in Permit Condition D29.3

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 401, 3-2-1984; RULE 401, 11-9-2001; RULE 404, 2-7-1986; RULE 405, 2-7-1986; RULE 409, 8-7-1981]

[Devices subject to this condition : C165, C166]

C12.2 The operator shall use this equipment in such a manner that the ESP daily average voltage and secondary current (or total power input) being monitored as indicated below are greater than or equal to the average value in the most recent source test which demonstrated compliance with the emission limits.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall install and maintain a continuous monitoring and recording system to accurately measure and record the:

1. Total flue gas inlet temperature to ESPs
2. Total flue gas flow rate
3. Current across each ESP
4. Voltage across each ESP

at each ESP field, in accordance with the approved plan. In addition, the operator shall keep records, in a manner approved by the District, for each of these parameters.

If the daily average ESP total power input falls below the level measured in the most recent source test which demonstrated compliance with the emission limit, a source test shall be performed within 90 days at the new minimum daily average ESP total power level. The source test shall be performed for the FCCU regenerator (Device D151) according to the requirements specified in Permit Condition D29.4

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : C2283, C2284]

- C12.3 The operator shall use this equipment in such a manner that the pressure being monitored as indicated below is less than the pressure setting of the pressure relief device (PRD) for the equipment except during emergencies.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For this condition, the operator shall calculate the pressure of the liquid commodity using Antoine equation with the temperature measured as indicated below and Antoine constants of the commodity

The operator shall install and maintain a continuous monitoring and recording system to accurately measure and record the:

1. Temperature of the stored LPG commodity

The operator shall also keep a record of the LPG commodity being stored in the tank. In addition, the operator shall keep records, in a manner approved by the District, for a minimum of three years.

The operator shall keep records of the PRD pressure setting for this equipment.

The operator shall be allowed to blow down/remove water from each device listed under this system at a rate of two times per shift for a total of three shifts per day.

The operator shall keep records of the amount in gallons per day for each device under this system vented to to the vapor recovery system

[RULE 463, 5-6-2005]

[Devices subject to this condition : D42, D780, D781, D782, D783, D784, D785, D786, D787, D788, D789, D790, D791, D792, D793, D794, D795, D796, D797, D798, D799, D800, D1418]

D. Monitoring/Testing Requirements

D12.1 The operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature across the SCR bed.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 2005, 5-6-2005]

[Devices subject to this condition : C1772]

- D12.2 The operator shall install and maintain a(n) pressure gauge to accurately indicate the differential pressure across the SCR bed.

[RULE 2005, 5-6-2005]

[Devices subject to this condition : C233, C236, C301, C395, C916, C923, C1238, C1241, C1772]

- D12.3 The operator shall install and maintain a(n) flow meter to accurately indicate the fuel usage in the heater.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D917]

- D12.4 The operator shall install and maintain a(n) non-resettable elapsed time meter to accurately indicate the elapsed operating time of the engine.

**[RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 3004(a)(4)
-Periodic Monitoring, 12-12-1997]**

[Devices subject to this condition : D394, D955, D957, D959, D961, D1686, D1785, D1786]

- D12.6 The operator shall install and maintain a(n) infrared flame detector to accurately indicate the presence of a flame at the pilot light.

The operator shall also install and maintain a device to continuously record the parameter being measured.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

**[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; 40CFR 63 Subpart A, 5-16-2007;
CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]**

[Devices subject to this condition : C891, C892, C1558]

- D12.8 The operator shall install and maintain a(n) temperature reading device to accurately indicate the temperature at the SCR inlet.

[RULE 2005, 5-6-2005]

[Devices subject to this condition : C233, C236, C301, C395, C916, C923, C1238,
C1241]

- D12.9 The operator shall install and maintain a(n) pressure gauge to accurately indicate the differential pressure across the equipment. The operator shall record the parameter being monitored daily.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C1769]

- D12.10 The operator shall install and maintain a(n) thermocouple to accurately indicate the presence of a flame at the pilot light.

The operator shall also install and maintain a device to continuously record the parameter being measured.

**[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; 40CFR 60 Subpart A, 5-16-2007;
CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]**

[Devices subject to this condition : C894]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D28.8 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted for NO_x and SO_x (for initial and any subsequent tests) until the CEMS serving 4F-1 is RECLAIM certified. Once certified, source tests data may be substituted with CEMS data. Mobil may choose to conduct CO testing every three years, or concurrently with a RATA (9 x 30 minute runs).

The District shall be notified of the date and time of the test at least 10 days prior to the test.

The test shall be conducted to determine the NO_x emissions at the outlet.

The test shall be conducted to determine the PM₁₀ emissions at the outlet.

The test shall be conducted to determine the ROG emissions at the outlet.

The test shall be conducted within 60 days after achieving maximum production rate, but no later than 180 days after initial startup, and every five years thereafter.

The test shall be conducted to determine the SO_x emissions at the outlet.

The test shall be conducted to determine the CO emissions at the outlet.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D367]

D28.11 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted annually to determine the NH₃ emission.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C233, C236, C301, C395, C916, C1238, C1241]

D28.12 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted annually, once this equipment is operated that it is no longer be classified as non-operational, to determine the NH₃ emission.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C923]

D28.13 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted once every three years to determine the CO, PM, and VOC emissions at the outlet and the VOC control efficiency of the thermal oxidizer.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C686, C687]

D28.23 The operator shall conduct source test(s) in accordance with the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The test shall be conducted yearly after the initial performance test using the test protocol approved by the District.

The test shall be conducted to determine the emission rates (lb/hr) of ROG, CO & PM emissions at the outlet.

The District shall be notified of the date and time of the test at least 10 days prior to the test.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D925, D926]

D28.25 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted once every three years to determine the CO & PM emissions at the outlet.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C952]

D28.26 The operator shall conduct source test(s) in accordance with the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The test shall be conducted at least once to demonstrate compliance with NH3 emission limit per Rule 1105.1.

The test shall be conducted with the operation of the FCCU Regenerator bypass SCR/waste heat boiler/ID fan.

The test shall be conducted to determine the NH3 emissions at FCC Stack (Device S1739).

The test shall be conducted according to District Method 207.1.

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : D151]

D29.2 The operator shall conduct source test(s) for the pollutant(s) identified below.

| Pollutant(s) to be tested | Required Test Method(s) | Averaging Time | Test Location |
|---------------------------|--------------------------|----------------------------------|--|
| PM emissions | Approved District method | 1 hour | Outlet of the SCR serving this equipment |
| ROG emissions | Approved District method | District-approved averaging time | Outlet of the SCR serving this equipment |

The test(s) shall be conducted at least once every three years.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D1236, D1239]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D29.3 The operator shall conduct source test(s) for the pollutant(s) identified below.

| Pollutant(s) to be tested | Required Test Method(s) | Averaging Time | Test Location |
|---------------------------|--------------------------|----------------|-------------------|
| PM emissions | Approved District method | 1 hour | Outlet of the SCR |

The test(s) shall be conducted at least annually.

The test shall be conducted when the equipment is operating under normal conditions.

Source test result shall be submitted to the District no later than 60 days after the source test was conducted

Source test results shall include the following parameters: FCCU feed rate; catalyst recirculation rate; coke burn rate; oxygen content of exhaust gases; exhaust flow rate; exhaust gas moisture content; the flue gas temperature at the outlet of the ESP; and the average current, voltage, and spark rate at each of the ESP fields

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 404, 2-7-1986; RULE 405, 2-7-1986; RULE 409, 8-7-1981]

[Devices subject to this condition : D151]

D29.4 The operator shall conduct source test(s) for the pollutant(s) identified below.

| Pollutant(s) to be tested | Required Test Method(s) | Averaging Time | Test Location |
|---------------------------|--|----------------------------------|---------------|
| PM10 emissions | District Method 5.2 (filterables compliance, condensables information) | District-approved averaging time | Outlet |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| | | | |
|----------------|--|----------------------------------|--------|
| PM10 emissions | District Method 5.2 Modified with EPA Method 201A Cyclone (filterables compliance, condensables information) | District-approved averaging time | Outlet |
| PM10 emissions | District Method 5.2 with Previously Determined PM10 to PM Ratio Applied (filterables compliance, condensables information) | District-approved averaging time | Outlet |
| PM10 emissions | EPA Method 5 (filterables compliance) and District Method 5.2 (condensables information) | District-approved averaging time | Outlet |
| NH3 emissions | District method 207.1 | 1 hour | Outlet |
| NOX emissions | District method 100.1 | 1 hour | Outlet |
| SOX emissions | District method 100.1 | 1 hour | Outlet |
| CO emissions | District Method 100.1 or 10.1 | 1 hour | Outlet |
| VOC emissions | District Method 25.1 or 25.3 | 1 hour | Outlet |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall choose any of the PM10 test methods as indicated above to comply with Rule 1105.1 requirements and the test results of any of the selected test methods shall be used to determine compliance with Rules 404 and 405

The test shall be conducted after SCAQMD approval of the source test protocol, but no later than 180 days after initial startup of the new ESP's. The SCAQMD engineer shall be notified in writing of the date and time of the test at least 10 days prior to the test.

The test shall be conducted in accordance with an SCAQMD approved source test protocol. The protocol shall be submitted to SCAQMD no later than 45 days before the proposed test date and shall be approved by SCAQMD before test commences.

The test shall be conducted with the following operating modes of the ESPs:.

1. Two ESPs C2283 and C2284 in full operating mode and two ESPs C165 and C166 in idle mode
2. One ESP (C2283 or C2284) in full operating mode and two ESPs C165 and C166 in full operating mode with flue gas flow rate not to exceed 160,000 dscfm
3. One ESP (C2283 or C2284) in full operating mode and two ESPs C165 and C166 in idle mode with flue gas flow rate not to exceed 160,000 dscfm

The test shall be conducted .:

1. when the FCCU is operating with at least 80 percent of total FCCU feed rate (or 84 thousand barrels per day of total FCCU feed) with two ESPs in full operating mode
2. when the FCCU is operating with at least 40 percent of total FCCU feed rate (or 42 thousand barrels per day of total FCCU feed) with one new ESP in full operating mode
3. at least every year with three different operating modes after initial source test

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall provide sampling port(s) at the inlet of the ESPs (C2283 and C2284) in accordance with SCAQMD Method 1.1 - "Sample and Velocity Traverses for Stationary Source" and shall obtain a final approval from SCAQMD for the sampling port(s) installation and operation, which should be included in the source test protocol

4. to determine the control efficiency of the ESPs in each mode

Source test results shall include the following parameters in each mode: FCCU feed rate in KBD; catalyst recirculation rate in TPM; fresh catalyst (make-up & additives) rate in TPD; coke burn rate in lb/hr; oxygen & moisture content of flue gases; flue gas flow rate in dscfm; flue gas temperature at the inlet of the ESP; ammonia injection rate (at ESPs inlet and SCR inlet); and the average current in amps, voltage in volts and spark rate at each ESP field in use

A source test report shall be submitted to SCAQMD no later than 60 days after the source test was completed

[RULE 1105.1, 11-7-2003; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 404, 2-7-1986; RULE 405, 2-7-1986; RULE 407, 4-2-1982; RULE 409, 8-7-1981; 40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : C1772, C2283, C2284]

D29.5 The operator shall conduct source test(s) for the pollutant(s) identified below.

| Pollutant(s) to be tested | Required Test Method(s) | Averaging Time | Test Location |
|---------------------------|--------------------------|----------------|---------------|
| PM emissions | Approved District method | 1 hour | Outlet |

The test(s) shall be conducted at least once every three years.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 404, 2-7-1986; RULE 409, 8-7-1981]

[Devices subject to this condition : C626]

D29.6 The operator shall conduct source test(s) for the pollutant(s) identified below.

| Pollutant(s) to be tested | Required Test Method(s) | Averaging Time | Test Location |
|---------------------------|--------------------------|----------------|----------------------|
| PM emissions | Approved District method | 1 hour | Outlet of the filter |
| PM10 emissions | Approved District method | 1 hour | Outlet of the filter |

The initial test(s) shall be conducted within 120 days after achieving maximum production rate, but no later than 180 days after initial start-up

The test(s) shall be conducted at least annually if the equipment is utilized more than 30 days in a calendar year.

The test shall be conducted when this equipment is operating at least 80 percent of the maximum allowable capacity.

Report of the test and operating condition of the equipment shall be submitted to the District within 60 days after the test

The District shall be notified of the date and time of the test at least 10 days prior to the test

The operator shall submit a test protocol to the District at least 60 days prior to the initial testing. The initial and annual tests shall be conducted according to the approved test protocol or any subsequent approved revisions

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C2397]

D82.1 The operator shall install and maintain a CEMS to measure the following parameters:

SOX concentration in ppmv

Oxygen concentration in percent volume

[RULE 2011, 5-6-2005; 40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D925, C952]

D82.2 The operator shall install and maintain a CEMS to measure the following parameters:

CO concentration in ppmv

Oxygen concentration in percent volume

[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D151, C164]

D82.3 The operator shall install and maintain a CEMS to measure the following parameters:

SOX concentration in ppmv

Oxygen concentration in percent volume

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : D926]

D82.4 The operator shall install and maintain a CEMS to measure the following parameters:

NOX concentration in ppmv

SOX concentration in ppmv

Oxygen concentration in percent volume

[RULE 2011, 5-6-2005; RULE 2012, 5-6-2005; 40CFR 60 Subpart GG, 2-24-2006]

[Devices subject to this condition : D926]

D82.5 The operator shall install and maintain a CEMS to measure the following parameters:

NOX concentration in ppmv

SOX concentration in ppmv

Oxygen concentration in percent volume

The NO_x and SO_x CEMS shall be certified prior to the startup of the new ESPs with a range covering the emission limits

**[RULE 2004, 5-11-2001; RULE 2011, 5-6-2005; RULE 2012, 5-6-2005; CONSENT
DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]**

[Devices subject to this condition : D151]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D82.6 The operator shall install and maintain a CEMS to measure the following parameters:

NOX concentration in ppmv

Oxygen concentration in percent volume

The CEMS shall convert the actual NOx concentrations in ppmv to lb/MMBtu.

The CEMS shall record the emissions on the hourly continuous basis on the format approved by the District.

The operator shall periodically measure the NOx according to the following specifications:

The Alternative Monitoring Plan (AMP) approved by the United States Environmental Protection Agency (USEPA) on April 12, 2012, for the periodic monitoring and reporting of NOx in lb/MMBtu for the Boiler 75F-1.

In addition, the operator shall also comply with all other requirements of the AMP issued by the USEPA on April 12, 2012, for the Boiler 75F-1.

**[RULE 2004, 5-11-2001; RULE 2012, 5-6-2005; 40CFR 60SubpartD, 2-16-2012;
CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]**

[Devices subject to this condition : D805]

D90.1 The operator shall periodically monitor the hydrocarbon concentration at the outlet of the carbon canister according to the following specifications:

The operator shall monitor once every month.

The operator shall monitor the hydrocarbon concentration according to EPA Method 21.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : C1561, C2219, C2223, C2229]

D90.3 The operator shall continuously monitor the H₂S concentration in the fuel gases before being burned in this device according to the following specifications:

The operator shall monitor the concentration of the total sulfur compounds at the outlet of the fuel gas mix drum/knockout pot 24C-1 (Device D2234).

The operator shall use Gas Chromatography (GC 61) to monitor the parameter.

The operator shall also install and maintain a device to continuously record the parameter being monitored.

[RULE 2005, 5-6-2005; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D926]

D90.4 The operator shall continuously monitor the opacity at stack according to the following specifications:

The operator shall use opacity meter to monitor the parameter.

The operator shall also install and maintain a device to continuously record the parameter being monitored.

**[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809,
12-13-2005]**

[Devices subject to this condition : D151]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D90.5 The operator shall periodically monitor the volatile organic compounds and benzene emissions at the outlet of the primary carbon canister according to the following specifications:

The operator shall monitor once every week during tank filling operations utilizing EPA Method 21 for volatile organic compounds and Draeger indicating tube for benzene.

The operator shall monitor volatile organic compounds at times when there is actual flow to the carbon canister (at tank filling period)

The operator shall calibrate the instrument used to monitor the parameter in ppmv methane

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : C2028, C2033, C2034, C2035, C2036, C2051, C2052, C2053, C2054, C2055, C2056, C2057, C2058, C2059, C2060, C2061, C2062, C2063, C2064, C2068, C2069, C2070, C2072, C2079, C2080, C2081, C2082, C2083, C2084, C2086, C2093, C2094, C2095, C2096, C2097, C2098, C2105, C2106, C2107, C2108, C2109, C2110, C2113, C2118]

D90.6 The operator shall periodically monitor the concentration of volatile organic compounds at the outlet of the primary carbon canister according to the following specifications:

The operator shall monitor once every week for VOCs when the sump is being filled with wastewater from the cleaning activity in accordance with (a) EPA Reference Method 21, using an appropriate analyzer calibrated with methane, or (b) District Grab Sample Method described in Attachment A of SCAQMD Rule 1176.

If a cleaning activity is scheduled during a week, the VOC measurement shall be taken during the cleaning of the heat exchangers. If no cleaning activity is scheduled, the VOC measurement may be taken at anytime.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1176, 9-13-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : C2135]

D90.7 The operator shall periodically monitor the hydrocarbon concentration at the outlet of the primary and secondary carbon canisters according to the following specifications:

The operator shall monitor once every week, while Tank D935 (5D-1) is being filled or out-breathing. Measurements shall not be taken when Tank D935 is inbreathing or emptying.

If breakthrough occurs in two consecutive weeks, the operator shall monitor on a daily basis, and provide notification to the District.

Weekly monitoring may be resumed after 3 months, provided breakthrough does not occur within any consecutive 14 day period.

The operator shall monitor the VOC concentration according to EPA Reference Method 21.

The operator shall calibrate the instrument used to monitor the VOC concentration in PPMV with a calibration gas that is C4 or lighter.

The operator shall keep records for a minimum of five years, in a manner approved by the District, for the measured VOC concentrations.

[RULE 1176, 9-13-1996; RULE 1303, 5-10-1996]

[Devices subject to this condition : C2250]

D90.8 The operator shall continuously monitor the temperature in degrees F of the flue gas at the inlet to the ESP according to the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall monitor once every 15 minutes.

The operator shall automatically record electronically the above parameter at least one measurement every hour. These records shall be maintained for at least five years and made available to SCAQMD personnel upon request

The continuous monitor shall be installed and operated whenever the ESP is operating in accordance with the monitoring plan as approved by SCAQMD

Monitoring and recording of this parameter shall not be required during periods of routine maintenance or malfunction of the monitoring and recording devices

The temperature monitor shall have a minimum range from 500 to 800 degrees F and be accurate to within plus or minus 5 percent and shall be inspected for replacement, if needed, at least once every 12 months

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : C2283, C2284]

D90.9 The operator shall continuously monitor the flow rate in scfm (wet) of the flue gas at the inlet to the ESP according to the following specifications:

The monitoring shall be conducted in accordance with the monitoring plan as approved by SCAQMD

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : C2283, C2284]

D90.10 The operator shall continuously monitor the ESP total power input across the ESP according to the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall monitor once every 15 minutes.

The operator shall automatically record electronically the above parameter at least one measurement every hour. These records shall be maintained for at least five years and made available to SCAQMD personnel upon request

The continuous monitor shall be installed and operated whenever the ESP is operating in accordance with the monitoring plan as approved by SCAQMD

Monitoring and recording of this parameter shall not be required during periods of routine maintenance or malfunction of the monitoring and recording devices

The power monitor shall have a range from 0 to 1500 mA and 0 to 100 KV per transformer/rectifier set, which shall be accurate to within plus or minus 5 percent and shall be calibrated at least once every 12 months

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : C2283, C2284]

D90.11 The operator shall continuously monitor the NH₃ injection rate in lb/hr at the inlet to the ESP according to the following specifications:

The monitoring shall be conducted in accordance with the monitoring plan as approved by SCAQMD

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : C2283, C2284]

D90.12 The operator shall continuously monitor the H₂S concentration in the fuel gases before being burned in this device according to the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall monitor the H₂S concentration at the outlet of the fuel gas mix drum 64C-4 (Device D838) for fuel combustion devices.

The operator shall use Gas Chromatography (GC 34) meeting the requirements of 40CFR60 Subpart J, Method 11 to monitor the parameter.

The operator shall also install and maintain a device to continuously record the parameter being monitored.

**[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809,
12-13-2005]**

[Devices subject to this condition : D83, D84, D85, D120, C164, D231, D232, D234, D235, D367, C626, D803, D805, D833, D913, D914, D917, D918, D920, D927, D928, D929, D930, D931, D949, D950, D1236, D1239, D1403]

D90.13 The operator shall periodically monitor the H₂S compounds at the outlet of the carbon vessel in service according to the following specifications:

The operator shall monitor once every day during the truck loading operations utilizing the Draeger tube.

**[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809,
12-13-2005]**

[Devices subject to this condition : C2393, C2394]

D90.14 The operator shall continuously monitor the H₂S concentration in the fuel gas, after being H₂S treated by carbon vessels 28C-107 or 28C-108, before being combusted in the incinerator 28F-11 according to the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall monitor the H₂S concentration at the outlet of the H₂S treated carbon vessels 28C-107 or 28C-108 (Devices C2393 & C2394) for fuel combustion device

The operator shall use an H₂S analyzer (Western Research Model 932 multi-gas analyzer) meeting the requirements of 40CFR60 Subpart J, Method 11 to monitor the parameter.

The operator shall obtain a written approval from the AQMD for the H₂S analyzer, following the 40CFR60 Subpart A

The operator shall also install and maintain a device to continuously record the parameter being monitored.

[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : C626, C2393, C2394]

D90.15 The operator shall periodically monitor the H₂S concentration at the inlet of this device according to the following specifications:

The Alternative Monitoring Plan (AMP) approved by the United States Environmental Protection Agency (USEPA) on December 18, 2006 for the periodic monitoring and reporting of H₂S concentration for the off-gas streams from tanks 400x30, 400x31 and 510x4 in P15/S3 to the Clean Service flare (C1558) in P19/S6.

In addition, the operator shall also comply with all other requirements of the AMP issued by the USEPA on December 18, 2006 for the Clean Service flare (C1558).

[40CFR 60 Subpart A, 6-13-2007; 40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : C1558]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D90.16 The operator shall continuously monitor the total sulfur concentration in fuel gases before being burned in this device according to the following specifications:

During times when the operator uses refinery fuel gas from 8C-5 (Device D500), the operator will use Gas Chromatography (GC 33) to monitor total sulfur concentration for the 8C-5 (Device D500 refinery fuel gas.

During times when the operator uses refinery fuel gas from 64C-4 (Device D838), the operator will use a SO_x CEMS on RECLAIM SOX reference source 75F-1 (Device D805) or 3F-3/4 (Device D930/D931) with common Device (S1975) that only use refinery fuel gas from fuel gas mix drum 64C-4 (Device D838) to calculate total sulfur concentration in the 64C-4 (Device D838) refinery fuel gas.

For the purposes of this condition and with regards to total sulfur concentration, natural gas and PSA waste gas used in 24F-1 (Device D925) shall be deemed to meet SCAQMD Clean Fuels Policy BACT Guidelines (10-20-2000). As such, no additional monitoring shall be required for these fuels.

The operator shall also install and maintain a device to continuously record the parameter being monitored.

[40CFR 60 Subpart A, 6-13-2007; 40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : D925]

D90.17 The operator shall periodically monitor the H₂S concentration at the inlet of this device according to the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

During times when the operator uses refinery fuel gas from 8C-5 (Device D500), the operator will use Gas Chromatography (GC 33) to monitor total sulfur concentration for the 8C-5 (Device D500 refinery fuel gas.

During times when the operator uses refinery fuel gas from 64C-4 (Device D838), the operator will use a SO_x CEMS on RECLAIM SO_x reference source 75F-1 (Device D805) or 3F-3/4 (Device D930/D931) with common Device (S1975) that only use refinery fuel gas from fuel gas mix drum 64C-4 (Device D838) to calculate total sulfur concentration in the 64C-4 (Device D838) refinery fuel gas.

For the purposes of this condition and with regards to total sulfur concentration, natural gas and PSA waste gas used in 24F-1 (Device D925) shall be deemed to meet SCAQMD Clean Fuels Policy BACT Guidelines (10-20-2000). As such, no additional monitoring shall be required for these fuels.

The operator shall also install and maintain a device to continuously record the parameter being monitored.

[40CFR 60 Subpart A, 6-13-2007; 40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : D925, D926]

D90.18 The operator shall continuously monitor the H₂S concentration in the fuel gases before being burned in this device according to the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall monitor the H₂S concentration at the outlet of the fuel gas mix drum 64C-4 (Device D838) for fuel combustion devices.

The operator shall use Gas Chromatography (GC 34) meeting the requirements of 40CFR60 Subpart J, Method 11 to monitor the parameter.

The operator shall also install and maintain a device to continuously record the parameter being monitored.

The operator, by compliance with this condition shall not be required to measure 1) the opacity of emissions utilizing a continuous opacity monitoring system (COMS) and 2) the SO₂ emissions utilizing a continuous monitoring system (CEMS).

[40CFR 60SubpartD, 2-16-2012]

[Devices subject to this condition : D805]

D90.19 The operator shall periodically monitor the concentration of volatile organic compounds at the outlet of the primary carbon canister according to the following specifications:

The operator shall monitor monthly for VOCs during cleaning of a vacuum truck, when the sump (device D1671) receives the oily wash water in accordance with (a) EPA Reference Method 21, or (b) District Grb Sample Method described in Attachment A of SCAQMD Rule 1176.

If a cleaning activity is scheduled during a week, the VOC measurement shall be taken during the cleaning activity, while the sump is receiving wash water. If no cleaning activity is scheduled, the VOC measurement may be taken at any time when the sump is in service.

[RULE 1176, 9-13-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : C2479]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D94.1 The operator shall install, maintain and operate a sampling line at the inlet and outlet of the carbon canisters to allow measurement of the volatile organic compounds

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C2028, C2033, C2034, C2035, C2036, C2051, C2052, C2053, C2054, C2055, C2056, C2057, C2058, C2059, C2060, C2061, C2062, C2063, C2064, C2068, C2069, C2070, C2072, C2079, C2080, C2081, C2082, C2083, C2084, C2086, C2093, C2094, C2095, C2096, C2097, C2098, C2105, C2106, C2107, C2108, C2109, C2110, C2113, C2118]

D135.1 The operator shall inspect, adjust, and certify the ignition or fuel injection timing of this engine a minimum of once every 3 years of operation. Inspections, adjustments, and certifications shall be performed by a qualified mechanic and performed in accordance with the engine manufacturer's specifications and procedures.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D394, D955, D957, D959, D961, D1686, D1785, D1786, D2428]

D182.3 The operator shall test this equipment in accordance with the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

To determine the control efficiency of the SCR, after June 29, 2006, the operator shall, prior to the first physical modification where a permit to construct is required, file a permit application for that modification and include with the application a method for determining the control efficiency of the SCR

Such method may include, sampling port at the inlet of the SCR, monitor/analyzer for NOx concentration at the inlet of the SCR, or other equivalent method to determine SCR efficiency as approved by the Executive Officer

Until the above method(s) is approved, the operator shall keep record of the ammonia injection rate and shall make it available upon AQMD request

Once the above method(s) is approved, the operator shall conduct the SCR control efficiency determination and annually thereafter

[RULE 2005, 5-6-2005; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D925]

D182.4 The operator shall test this equipment in accordance with the following specifications:

To determine the PM10 emissions, after June 29, 2006, the operator shall, prior to the first physical modification where a permit to construct is required, file a permit application for that modification and include with the application a method for determining the PM10 emissions. Such method shall be provided in compliance with EPA or SCAQMD source test method

Until such time that a permit is issued for the modification, the PM10 emissions are assumed to equal to the PM emissions

Once the above method(s) is approved, the operator shall conduct the PM10 emissions determination and annually thereafter

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D925]

D182.5 The operator shall test this equipment in accordance with the following specifications:

The operator shall determine the true vapor pressure (VP) by one of the following methods: 1)sample and test the material stored, 2)derive the VP using engineering calculations, or 3)maintain on file a copy of the Material Safety Data Sheet (MSDS) of the material stored

Records of material stored, and their MSDS if applicable, shall be retained for a period of five years and made available to the Executive Officer upon request

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D692, D708, D709, D716, D719, D723, D730, D751, D765, D773, D774, D776, D778, D779, D1743, D1747, D1751, D1755, D1763]

D182.6 The operator shall test this equipment in accordance with the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall install and maintain an automatic tank level gauge (ATLG) and recorder to continuously measure and record the liquid surface level movement. The throughput, in barrels, shall be calculated using the following equation: $0.14 \times D \times D \times L$, where D is the diameter of the tank in feet based on the tank strapping chart and L is the total vertical one-way liquid surface level travel in feet per month. For the purpose of this condition, continuous recording is defined as once per hour

Alternately, for tanks which do not have an ATLG device, the throughput shall be derived by using engineering calculations using parameters obtained from process records, shipping invoices, manual tank level gauging, etc.

Records of throughput shall be retained for a period of five years and made available to the Executive Officer upon request

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D692, D709, D710, D715, D716, D723, D724, D726, D730, D751, D761, D762, D773, D774, D776, D778, D779, D915, D1685, D1763, D1787, D1897, D1898, D1916, D1917, D1918, D1919, D1924, D1925, D1926, D1927, D1928, D1930, D2005, D2023, D2024, D2025, D2026, D2543]

D182.7 The operator shall test this equipment in accordance with the following specifications:

If the Carb Executive Order requires the installation of a liquid removal device, a liquid removal rate test shall be conducted to demonstrate the removal of gasoline from the vapor passage of the coaxial hose. The test shall be conducted in accordance with Carb test procedure Method TP-201.6 (April 28, 2000) as a performance test and as a reverification test. Results shall be submitted to the SCAQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

[RULE 461, 6-3-2005; RULE 461, 4-6-2012]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D2546]

D182.8 The operator shall test this equipment in accordance with the following specifications:

A static pressure performance test shall be conducted to quantify the vapor tightness of the aboveground storage tank. The test shall be conducted in accordance with the latest version of Exhibit 4 of Carb Executive Order VR-402, as a performance test and as a reverification test. Results shall be submitted to the SCAQMD, Office of Engineering and Compliance, within seventy-two (72) hours of test.

[RULE 461, 6-3-2005; RULE 461, 4-6-2012]

[Devices subject to this condition : D2544]

D182.10 The operator shall test this equipment in accordance with the following specifications:

The SCAQMD shall be notified by methods specified at the time by the executive officer at least seventy-two (72) hours prior to any of the above mentioned testing requirements. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the tests to be performed.

[RULE 461, 6-3-2005; RULE 461, 4-6-2012]

[Devices subject to this condition : D2546]

D182.11 The operator shall test this equipment in accordance with the following specifications:

The vapor recovery tests shall be conducted in accordance with the most recent Rule 461 amendment or Carb Executive Order requirements, whichever is more stringent.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[**RULE 461, 6-3-2005**; RULE 461, 4-6-2012]

[Devices subject to this condition : D2546]

D182.12 The operator shall test this equipment in accordance with the following specifications:

A copy of the pass/fail test results shall be sent by methods specified at the time by the Executive Officer within seventy-two (72) hours after each test is conducted. Furthermore, the final test results demonstrating compliance shall be submitted by methods specified at the time by the Executive Officer within fourteen (14) calendar days from the date when all tests were passed.

The test report shall include at a minimum all the required records of all tests performed, test data, current SCAQMD facility ID number of the location being tested, the equipment permit to operate or application number, the SCAQMD ID number of the company performing the tests, a statement whether the system or component tested meets the required standards, and the name, SCAQMD tester ID number and signature of the person responsible for conducting the tests.

[**RULE 461, 6-3-2005**; RULE 461, 4-6-2012]

[Devices subject to this condition : D2546]

D182.13 The operator shall test this equipment in accordance with the following specifications:

Unless SCAQMD Rule 461 requires a more frequent testing or inspection schedule, the owner/operator shall be responsible to perform the scheduled weekly, quarterly, and annual inspections as outlined in the Carb approved installation, operation, and maintenance manual for the Morrison Bros. Phase I EVR system, as well as all the required vapor recovery system tests as per the current and appropriate Carb Executive Order.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[**RULE 461, 6-3-2005**; RULE 461, 4-6-2012]

[Devices subject to this condition : D2546]

D322.3 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

To comply with this condition, the operator shall maintain records in a manner approved by the District, to demonstrate compliance with this condition.

[**RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : C2397]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.
in accordance with the reporting requirements in Section K of this permit

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition : D129, D130, D167, D168, D919, C1558, C2283, C2284, D2291, D2292, D2293, D2294, D2295, D2296, D2297, D2298, D2299, D2300, D2301, D2302, D2303, C2314, D2316, C2317, D2331, D2332, D2333, D2334, D2335, D2384, D2385, D2386, D2388, D2389, C2397]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a bi-weekly basis, at least, unless the equipment did not operate during the entire bi-weekly period. The routine bi-weekly inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.
in accordance with the reporting requirements in Section K of this permit

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition : C891, C892, C894]

D328.1 The operator shall determine compliance with the CO emission limit(s) either: (a) conducting a source test at least once every five years using AQMD Method 100.1 or 10.1; or (b) conducting a test at least annually using a portable analyzer and AQMD-approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with the emission limits. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 407, 4-2-1982]

[Devices subject to this condition : D83, D84, D85, D120, D231, D232, D234, D235, D269, D803, D805, D833, D913, D914, D917, D918, D920, D922, D924, D927, D928, D929, D930, D931, D949, D950, D1236, D1239, D1403]

D328.2 The operator shall determine compliance with the CO emission limit(s) either: (a) conducting a source test at least once every five years using AQMD Method 100.1 or 10.1; or (b) conducting a test at least annually using a portable analyzer and AQMD-approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with the emission limits. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 407, 4-2-1982]

[Devices subject to this condition : C626]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D330.1 The operator shall have a person that has been trained in accordance with Rule 461 conduct a semi-annual inspection of the gasoline transfer and dispensing equipment. The first inspection shall be in accordance with Rule 461, Attachment B, the second inspection shall be in accordance with Rule 461, Attachment C, and the subsequent inspections shall alternate protocols. The operator shall keep records of the inspection and the repairs in accordance to Rule 461 and Section K of this Permit.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 461, 6-3-2005; RULE 461, 4-6-2012**]

[Devices subject to this condition : D2544, D2546]

E. Equipment Operation/Construction Requirements

E54.1 The operator is not required to vent this equipment to the following equipment if all of the requirements listed below are met:

Device ID: C395 [SELECTIVE CATALYTIC REDUCTION REACTOR]

Requirement number 1: During startups and shutdowns. For the purpose of this condition, start-up and shutdown shall be defined as the time period during the startup and shutdown of the heater unit when the temperature of the exhaust gas at the inlet to SCR is below 550 degree F.

Requirement number 2: The operator shall limit startups and shutdowns to no more than 60 hours, not including the refractory dryout peiriod. Refreactory dryout shall be permitted up to a total of 144 consecutive hours to allow the curing of refractory materials.

Requirement number 3: During startup and shutdown, the operator shall used 244.05 lbs NOx per hur for reporting purposes under RECLAIM.

Requirement number 4: ExxonMobil shall submit a report tto the District annually with a summary of the number of hours for startups and shutdowns.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 2012, 5-6-2005]

[Devices subject to this condition : D925]

- E71.5 The operator shall only use this equipment to control odors from miscellaneous sources at the refinery. This equipment does not qualify as air pollution control equipment for compliance with SCAQMD, State, or Federal air pollution rules and regulations except for SCAQMD Rule 402 and Health & Safety Code 41700. The operator shall keep all spent carbon in a tightly covered container which shall remain closed except when it is being transferred into or out of the container.

[RULE 402, 5-7-1976]

[Devices subject to this condition : C1729]

- E71.6 The operator shall only maintain a vacuum pressure of 4 inches Hg or higher in this equipment during normal operations.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D981, D982, D983, D984]

- E71.7 The operator shall only inject NH₃ into this equipment if the flue gas inlet temperature is at least 550 degrees F.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C301, C395, C916, C923, C1238, C1241]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E71.8 The operator shall only use this equipment during turnarounds and maintenance activities to collect wastewater from the cleaning of the Alkylation Unit's heat exchangers at the machine shop.

[RULE 1401, 6-5-2009]

[Devices subject to this condition : D2136]

E71.9 The operator shall only inject NH₃ into this equipment if the flue gas inlet temperature is at least 500 degrees F.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C233, C236]

E71.10 The operator shall only use this equipment for the storage of any of the following materials/commodities: Crude oil of more than 97 % by volume.

[RULE 1178, 4-7-2006]

[Devices subject to this condition : D766, D770, D771]

E71.11 The operator shall only vent this equipment to the water sump whenever it is being filled. The operator shall not fill this silo unless the air/steam ejector is utilized and the vent gas is sparged at least 6 inches below the water surface of the sump.

[RULE 404, 2-7-1986; RULE 405, 2-7-1986]

[Devices subject to this condition : D167, D168, D2316]

E71.12 The operator shall not use this equipment to store anhydrous ammonia unless the pressure relief valve is set at 265 psig or higher.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1401, 6-5-2009]

[Devices subject to this condition : D2336, D2339, D2340, D2341]

E71.13 The operator shall not operate this equipment if the existing Catalyst Loading System is in operation.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2395]

E71.14 The operator shall not operate this equipment when the standby eductor 28H-6B is in operation except during the transition periods from one eductor to the other.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2391]

E71.15 The operator shall not operate this equipment when the main eductor 28H-6A is in operation except during the transition periods from one eductor to the other.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2409]

E71.16 The operator shall only use this equipment to directly drive fire-fighting pumps.

[RULE 1110.2, 7-9-2010; **RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996;**
RULE 1470, 5-4-2012]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D2428]

E71.19 The operator shall only use this equipment to receive oily wash water from the cleaning of an emptied cargo tank on a vacuum truck..

[RULE 1303(a)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D1671]

E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C2397]

E102.2 The operator shall discharge dust collected in this equipment only into closed containers.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition : C165, C166, C2283, C2284, C2314]

E128.1 The operator shall keep all spent carbon in a tightly covered container which shall remain closed except when it is being transferred into or out of the container.

[RULE 1303(a)(1)-BACT, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C1561, C2028, C2033, C2034, C2035, C2036, C2051, C2052, C2053, C2054, C2055, C2056, C2057, C2058, C2059, C2060, C2061, C2062, C2063, C2064, C2068, C2069, C2070, C2072, C2079, C2080, C2081, C2082, C2083, C2084, C2086, C2093, C2094, C2095, C2096, C2097, C2098, C2105, C2106, C2107, C2108, C2109, C2110, C2113, C2118, C2219, C2223, C2229, C2479]

E128.2 The operator shall keep all spent carbon in a tightly covered container which shall remain closed except when it is being transferred into or out of the container.

[RULE 1401, 6-5-2009]

[Devices subject to this condition : C2135]

E144.1 The operator shall vent this equipment, during filling, only to the vessel from which it is being filled.

[**RULE 1303(b)(2)-Offset, 5-10-1996**]

[Devices subject to this condition : D2195, D2196, D2197, D2232]

E153.1 The operator shall change over the spent carbon with activated carbon, within 24 hours, in the adsorber whenever breakthrough occurs.

The operator shall replace the carbon as follows: The primary carbon canister shall be replaced with either a fresh carbon canister or the secondary canister, and the secondary canister shall be replaced with a fresh carbon canister

For the purpose of this condition, breakthrough shall be defined as any organic compound reading of 50 ppmv or more, or any benzene reading of 5 ppmv or more.

[**RULE 1303(a)(1)-BACT, 5-10-1996**]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C2028, C2033, C2034, C2035, C2036, C2051, C2052, C2053, C2054, C2055, C2056, C2057, C2058, C2059, C2060, C2061, C2062, C2063, C2064, C2068, C2069, C2070, C2072, C2079, C2080, C2081, C2082, C2083, C2084, C2086, C2093, C2094, C2095, C2096, C2097, C2098, C2105, C2106, C2107, C2108, C2109, C2110, C2113, C2118]

E153.2 The operator shall change over the carbon in the adsorber whenever breakthrough occurs.

For the purpose of this condition, breakthrough occurs when the hydrocarbon monitor reading indicates a concentration of 500 ppmv at the outlet of the canister.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C1561]

E153.4 The operator shall change over the spent carbon with fresh activated carbon, within 24 hours, in the adsorber whenever breakthrough occurs.

The operator shall replace the carbon as follows: The primary carbon canister shall be replaced with either a fresh carbon canister or the secondary carbon canister, and the secondary carbon canister shall be replaced with a fresh carbon

For the purpose of this condition, breakthrough shall be defined as any volatile organic compounds (inclusive of methane and ethane) reading of 500 ppmv or greater.

The volatile organic compounds (inclusive of methane and ethane) reading shall be measured in accordance to Condition D90.6.

[RULE 1176, 9-13-1996]

[Devices subject to this condition : C2135]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E153.5 The operator shall change over the carbon in the adsorber whenever breakthrough occurs.

For the purpose of this condition, breakthrough occurs when the hydrocarbon monitor reading indicates a concentration of 500 ppmv or greater at the outlet of the primary canister.

A change over shall consist of the following: Removal or regeneration of the primary carbon adsorption unit. Promotion of the secondary unit to the primary position, provided breakthrough has not occurred on the secondary unit. Installation of a new or regenerated adsorption canister at the secondary position. Both canisters shall be replaced or regenerated if breakthrough has occurred at the second canister.

Records shall be kept for a period of five years indicating the date and time when a carbon canister is replaced.

[RULE 1303, 5-10-1996; RULE 1303, 12-6-2002]

[Devices subject to this condition : C2250]

E153.6 The operator shall change over the carbon in the adsorber whenever breakthrough occurs.

For the purpose of this condition, breakthrough occurs when the hydrocarbon monitors reading indicates a concentration of 500 ppmv at the outlet of the canister in service or the last canister (when two canister are operated in series)

[RULE 1303(a)-BACT, 5-10-1996]

[Devices subject to this condition : C2219, C2223, C2229]

E153.8 The operator shall change over the spent carbon with fresh activated carbon, within 24 hours, in the adsorber whenever breakthrough occurs.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall replace the carbon as follows: the primary carbon canister shall be replaced with the secondary carbon adsorber, the secondary carbon adsorber shall be replaced with the tertiary carbon adsorber, and the tertiary carbon shall be replaced with a fresh activated carbon adsorber such that it vents to the atmosphere.

For the purpose of this condition, breakthrough shall be defined as any volatile organic compounds reading of 500 ppmv or greater measured at the outlet of the primary carbon adsorber..

The volatile organic compounds reading shall be measured in accordance to Condition D90.19.

[RULE 1176, 9-13-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : C2479]

E175.2 The operator shall not use this equipment unless all exhaust air passes through the following:

CO boiler in fired mode

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D2278]

E193.2 The operator shall operate and maintain this equipment according to the following specifications:

The operator shall comply with all applicable requirements specified in Subpart A of the 40CFR60

**[40CFR 60 Subpart A, 5-16-2007; CONSENT DECREE CIVIL CASE No. 05 C 5809,
12-13-2005]**

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C891, C892, C894, C1558]

E193.3 The operator shall operate and maintain this equipment according to the following specifications:

The circulating caustic solution in the relief gas scrubber must be recharged to the 4 percent by weight. NaOH strength immediately following an alkylation unit upset necessitating the deinventory of any HF acid to the acid evacuation drum, 5C-54

The relief gas scrubber (RGS) system shall be in full and continuous operation whenever the HF alkylation unit is in operation

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C940]

E193.5 The operator shall operate and maintain this equipment according to the following specifications:

The District shall be notified seven days prior to first starting the spray filling operation

The operator shall monitor and record the initial, midpoint, and final temperature in the railcar, and the product line pressure during the spray filling operation

The operator shall use a hydrocarbon analyzer to monitor the equipment daily for fugitive leaks during the spray filling operation

The product line pressure shall not exceed 225 psig during the spray filling operation

The operator shall install and maintain a temperature and pressure gauge to accurately indicate product temperature and product line pressure during the filling operation

[RULE 1303(a)(1)-BACT, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D675]

E193.6 The operator shall operate and maintain this equipment according to the following specifications:

The operator shall notify the District at least seven days prior to first starting the spray filling operation

The operator shall monitor and record the initial, midpoint and final temperature in the railcar and the product line pressure during the spray filling operation of LPG

The operator shall use a hydrocarbon analyzer to monitor the equipment daily for fugitive leaks during the spray filling operation

The product line pressure shall not exceed 225 psig during the spray filling operation

The operator shall install and maintain a temperature and pressure gauge to accurately indicate product temperature and product line pressure during the filling operation

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D675]

E193.8 The operator shall operate and maintain this equipment according to the following specifications:

The operator shall only operate this equipment if it complies with all applicable mitigation measures stipulated in the "Mitigation Monitoring Plan" document which is part of the AQMD Certified EIR dated 12-October-2001.

The operator shall maintain records in a manner approved by the District, to demonstrate compliance with the applicable measures stipulated in the "Mitigation Monitoring Plan" document.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[CA PRC CEQA, 11-23-1970]

[Devices subject to this condition : D2005]

E193.9 The operator shall construct, operate, and maintain this equipment according to the following specifications:

The operator shall monitor the groundwater in compliance with the Regional Water Quality Control Board Cleanup Requirements specified under the current order for abatement

[Devices subject to this condition : D2115]

E193.12 The operator shall operate and maintain this equipment according to the following specifications:

The work area shall be kept free of any dried particles of selenium or its compounds.

Roll-off containers shall be fully covered when the loading of solid waste is completed.

[RULE 1401, 6-5-2009]

[Devices subject to this condition : D2166]

E193.15 The operator shall construct, operate, and maintain this equipment as follows:

Install and maintain sampling ports for the measurement of VOC emissions at an intermediary point between the first and second stage carbon adsorption canisters.

[**RULE 1303, 5-10-1996**; RULE 1303, 12-6-2002]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C2250]

E193.16 The operator shall operate and maintain this equipment according to the following specifications:

The operator shall comply with all applicable requirements specified in Subpart A of the 40CFR60

[40CFR 60 Subpart A, 5-16-2007; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D83, D84, D85, D120, C164, D231, D232, D234, D235, D269, D367, C626, C686, C687, D803, D805, D833, D913, D914, D917, D918, D920, D922, D924, D925, D927, D928, D929, D930, D931, D949, D950, C952, D1236, D1239, D1403]

E193.18 The operator shall construct, operate, and maintain this equipment according to the following specifications:

The operator shall comply with all mitigation measures stipulated by SCAQMD Final Environmental Impact Report dated March 23, 2007

[CA PRC CEQA, 11-23-1970]

[Devices subject to this condition : D151, C2283, C2284]

E193.19 The operator shall operate and maintain this equipment as follows:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Whenever the ESP system (Devices C165, C166, C2283, and C2284) is in operation and venting the FCCU Regenerator catalyst dust exhaust, the operator shall maintain in operation the following modes

1. Two ESPs C2283 and C2284 in full operating mode and two ESPs C165 and C166 in idle mode, or
2. One ESP (C2283 or C2284) in full operating mode and two ESPs C165 and C166 in full operating mode with flue gas flow rate not to exceed 160,000 dscfm, or
3. One ESP (C2283 or C2284) in full operating mode and two ESPs C165 and C166 in idle mode with flue gas flow rate not to exceed 160,000 dscfm

The operator shall not operate the FCCU if emissions from the FCCU to the atmosphere exceed the following limits for filterable PM10: 0.005 gr/dscf or 2.8 lb per 1000 bbl fresh feed

The operator shall not operate any of the modes, if the source test results of Condition D29.4 show the PM10 and/or NH3 emissions exceed the rule limits, after May 30, 2009

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : C2283, C2284]

E193.21 The operator shall operate and maintain this equipment according to the following specifications:

The operator shall keep all sulfur compound contaminated condensate in a tightly covered container (Pot 28SP-1) which shall be remain closed at all times. The operator shall only discharge/collect/transfer the sulfur compound contaminated condensate from this equipment (Pot 28SP-1) into a closed container (portable drum), which can be opened during filling or sampling for lab analysis

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1401, 6-5-2009; RULE 402, 5-7-1976]

[Devices subject to this condition : D2408]

E193.22 The operator shall operate and maintain this equipment according to the following specifications:

On a weekly basis, the liquid level in the pot (28SP-1) and the liquid color shall be monitored/inspected visually. Such level and color shall be recorded

During the transferring of the sulfur compound contaminated condensate to the portable collection drum, the sample shall be taken for lab analysis to determine the compositions and pH level in accordance with State and Federal criteria for hazardous waste

The analytical results shall be submitted to the District upon request

The requirements of this condition and any associated reporting/recorkeeping requirements may be terminated or adjusted as determined to be appropriate by the District based on the adequacy of information provided and the equipment's ability to comply with all applicable rules and regulations

[RULE 1401, 6-5-2009]

[Devices subject to this condition : D2408]

E193.23 The operator shall operate and maintain this equipment according to the following specifications:

The operator shall only discharge/collect the sulfur compound contaminated condensate, if any, from this equipment and associated piping system into closed container (Pot 28SP-1)

[RULE 1401, 6-5-2009; RULE 402, 5-7-1976]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D2391, D2409]

E193.24 The operator shall install this equipment as follows:

The operator shall arrange two carbon adsorbers in parallel, put one (primary) in service, and the other one (secondary) in standby mode as backup

The operator shall change over the spent carbon in primary vessel with activated carbon whenever breakthrough occurs

The operator shall put the backup carbon vessel (secondary) in service, or replace the spent carbon in service vessel(primary) with the activated carbon

Breakthrough shall be defined as H₂S compounds reading of 120 ppmv or more at the exit of the primary vessel

The operator shall use the bituminous coal type carbon material with a density in the range of 0.46 to 0.52 gram/cc, and a H₂S capacity of at least 0.3 gram/cc per ASTM D6646-01 Test.

[40CFR 60 Subpart A, 5-16-2007; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : C2393, C2394]

E204.1 The operator shall tag the valves according to the following specifications:

This condition applies to all new valves greater than 2 inches in size, and major components in VOC service as defined by Rule 1173, except those specifically exempt by Rule 1173.

The affected valves shall be distinctly identified from other components through their tag numbers (e.f. numbers ending in the letter "N"), and shall be noted in the records.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D1202, D1204]

E204.3 The operator shall repair the valves according to the following specifications:

For all new components in VOC service, a leak greater than 500 ppm but less than 1000 ppm measured as methane above background by EPA Method 21 shall be repaired within 14 days of detection.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D1202, D1204, D1208, D1209, D1210]

E204.4 The operator shall inspect the valves and flanges according to the following specifications:

All new valves and flanges in VOC services except bellow sealed valves and those specifically exempted by Rule 1173 shall be inspected monthly using EPA reference method 21. If 98 percent or greater of the new valve and flange population inspected is found to leak gaseous or liquid volatile organic compound(s) at a rate less than 500 ppm, then the operator may revert to a quarterly inspection program with the approval of the Executive Officer.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D1661]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E313.1 This device is classified as a non-operated major SO_x and NO_x source as defined under Rules 2011 and 2012 and shall not be operated unless the Facility Permit holder provides written notification to the Executive Officer 30 days prior to starting operation. In order to maintain the non-operational classification, the Facility Permit holder shall:

(a) Remove a section of the fuel feed line(s) to the device and place a blind flange on both ends of the fuel feed line(s); and

(b) Remove a section of the process feed line(s) and place a blind flange on both ends of the process feed line(s).

Removal of parts or components solely to qualify the device for non-operated classification pursuant to this condition, or replacement of the same removed parts or components resulting in the device no longer being classified as non-operated shall not be deemed to affect the potential to emit within the meanings of Rule 2005, Regulation XIII and Regulation XXX.

[RULE 2011, 5-6-2005; RULE 2012, 5-6-2005]

[Devices subject to this condition : D922]

E315.1 Once this device is operated, it shall no longer be classified as non-operational. This device shall also meet the monitoring requirements of Rules 2011 and 2012, subparagraph (c)(2)(A) or (c)(2)(B) no later than 30 calendar days after the start of operation except as provided in Rule 2011, paragraph (c)(11) and Rule 2012, paragraph (c)(10).

[RULE 2011, 5-6-2005; RULE 2012, 5-6-2005]

[Devices subject to this condition : D922]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E318.1 This major SO_x source shall no longer be considered an infrequently-operated major SO_x source once it is operated in excess of 30 days in any compliance year. This device shall meet the monitoring requirements of Rule 2011, subparagraph (c)(2)(A) or (c)(2)(B) on and after the thirty-first day of operation in any compliance year unless it qualifies for a one-time only CEMS certification period as provided in Rule 2011, subparagraph (c)(11).

[RULE 2011, 5-6-2005]

[Devices subject to this condition : D833]

E336.1 The operator shall vent the vent gases from this equipment as follows:

All vent gases during normal operations shall be vented to a vapor recovery system.

This equipment shall not be operated unless the blowdown vapor recovery equipment is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 463, 5-6-2005]

[Devices subject to this condition : D629, D657, D690, D691, D692, D693, D694, D695, D696, D699, D700, D702, D706, D708, D709, D710, D714, D715, D720, D721, D722, D723, D724, D727, D728, D915, D1417, D1428, D1437, D1685, D1787, D1924, D1925]

E336.2 The operator shall vent the vent gases from this equipment as follows:

This equipment shall not be operated unless the vapor recovery system, when no spray filling takes place, is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D675]

E336.3 The operator shall vent the vent gases from this equipment as follows:

All vent gases under normal operating conditions shall be directed to the clean service flare system (Process 19, System 6) and that under emergency conditions may be vented to the atmosphere.

This equipment shall not be operated unless the clean service flare system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1118, 11-4-2005; RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D801, D802]

E336.4 The operator shall vent the vent gases from this equipment as follows:

All vent gases under normal operating conditions shall be directed to the East butane refrigeration system (Process 19, System 5) and, as necessary, clean service flare system (Process 19, System 6), and that under emergency conditions may be vented to the atmosphere.

This equipment shall not be operated unless the East butane refrigeration and clean service flare systems are in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1118, 11-4-2005; RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D1379]

E336.5 The operator shall vent the vent gases from this equipment as follows:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

This equipment shall not be operated unless the vapor recovery system(s) is in full use and has a valid permit to receive vent gases from this equipment.

All vent gases under normal operating conditions shall be directed to the West butane refrigeration system (Process 19, System 7) or refinery vapor recovery system (Process 19, System 3) and that under emergency conditions shall be vent to the atmosphere.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D1439]

E336.6 The operator shall vent the vent gases from this equipment as follows:

All vent gases under normal operating conditions shall be vented to a vapor recovery system or kept inside the railcar during spray loading of LPG only. Light straight run shall be loaded using the vapor recovery system, which is in full use and has a valid permit to operate.

This equipment shall not be operated unless the vapor recovery system, when no spray filling takes place, is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D1994]

E336.7 The operator shall vent the vent gases from this equipment as follows:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

This equipment shall not be operated unless the vapor recovery system, when no spray filling takes place, is in full use and has a valid permit to receive vent gases from this equipment.

All vent gases under normal operating conditions shall be vented to a vapor recovery system when loading LSR, or kept inside the railcar during spray filling LPG.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D675]

E336.8 The operator shall vent the vent gases from this equipment as follows:

All vent gases under normal operating conditions shall be directed to the Air Pollution Control (APC) system (Process 14, System 2).

This equipment shall not be operated unless the APC system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1176, 9-13-1996; RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D684, D685, D1773]

E336.9 The operator shall vent the vent gases from this equipment as follows:

All vent gases during normal operations shall be vented to a vapor recovery system.

This equipment shall not be operated unless the vapor recovery system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D21, D22, D155, D156, D585, D594, D1250, D1328, D1341, D1419, D2145, D2247, D2251, D2252]

E336.11 The operator shall vent the vent gases from this equipment as follows:

All vent gases under normal operating conditions shall be directed to the Air Pollution Control (APC) system (Process 14, System 2).

This equipment shall not be operated unless the APC system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1176, 9-13-1996; RULE 1303(a)(1)-BACT, 5-10-1996; 40CFR 60 Subpart QQQ, 10-17-2000]

[Devices subject to this condition : D680, D681, D683]

E336.12 The operator shall vent the vent gases from this equipment as follows:

All emergency vent gases shall be directed to a VRS/flare system except three PRV (PSV01-002, PSV01-003, and PSV01-045) set at 38 psig that vent to the atmosphere.

This equipment shall not be operated unless the VRS/flare system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D1]

E336.15 The operator shall vent the vent gases from this equipment as follows:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All vent gases from the dog house during normal operations shall be vented to a vapor recovery system.

This equipment shall not be operated unless the vapor recovery system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D2235]

E336.16 The operator shall vent the vent gases from this equipment as follows:

All vent gases under normal depressurizing or degassing operations shall be directed to the vapor recovery system.

This equipment shall not be operated unless the vapor recovery system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1149, 7-14-1995; RULE 1149, 5-2-2008]

[Devices subject to this condition : D42, D780, D781, D782, D783, D784, D785, D786, D787, D788, D789, D790, D791, D792, D793, D794, D795, D796, D797, D798, D799, D800, D1418, D2005]

E336.17 The operator shall vent the vent gases from this equipment as follows:

All vent gases under normal operating conditions shall be directed to the incinerator (Process 13, System 8).

This equipment shall not be operated unless the incinerator is in full use and has a valid permit to receive vent gases from this equipment.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; 40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D1324]

E336.18 The operator shall vent the vent gases from this equipment as follows:

All vent gases under normal operating conditions shall be vented to the H₂S adsorption system (Process 13, System 8) and then to the sulfur vapor collection system (Process 13, System 7), and then to the incinerator (Process 13, System 8).

This equipment shall not be operated unless the above air pollution control system is in full use and has a valid permit to receive vent gases from this equipment.

[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D644, D1375]

E336.20 The operator shall vent the vent gases from this equipment as follows:

All vent gases shall be directed to a vapor recovery system during filter purging operation. Only nitrogen gas shall be used to purge this equipment.

This equipment shall not be operated unless the vapor recovery system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D2411]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E336.21 The operator shall vent the vent gases from this equipment as follows:

All emergency vent gases shall be directed to a blowdown flare system.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D1194]

E336.22 The operator shall vent the vent gases from this equipment as follows:

The equipment shall vent to CO2 reclamation equipment or to the atmosphere.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 463, 5-6-2005]

[Devices subject to this condition : D1265]

E336.23 The operator shall vent the vent gases from this equipment as follows:

All emergency vent gases shall be directed to a vapor control system..

This equipment shall not be operated unless the vapor control system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D653, D654, D655, D656]

E336.24 The operator shall vent the vent gases from this equipment as follows:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All vent gases from the dog house during normal operations shall be vented to a vapor recovery system, Process 19, System 3..

This equipment shall not be operated unless the vapor recovery system is in full use and has a valid permit to receive vent gases from this equipment.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 463, 11-4-2011]

[Devices subject to this condition : D2538]

E440.1 The operator shall operate and maintain this equipment according to the following specifications:

The closed vent system shall be operated with no detectable VOC emissions, as indicate by an instrument reading of less than 500 ppm above background, as determined during the initial and semiannual inspections by methods specified in 40 CFR 60.696

[40CFR 60 Subpart QQQ, 10-17-2000]

[Devices subject to this condition : C686, C687]

E448.2 The operator shall comply with the following requirements:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall maintain in operation the following modes:

1. CO boiler C164 in maintenance mode: The emissions from the regenerator/cyclones may be vented directly to ESPs system and bypass CO boiler C164 during required maintenance of the CO boiler
2. CO boiler C164 in unfired mode: When ESP C2283 or C2284 is in maintenance mode, the emissions from the regenerator/cyclones shall be vented to the CO boiler C164, which may be operated in the unfired or waste heat boiler mode

The above modes shall not be in operation when the expander cleaning system (walnut shells injection period) is in operation

The District shall be notified 24 hours in advance of any scheduled maintenance and unfired mode of the CO boiler

The District shall be notified within 24 hours after any unscheduled maintenance and unfired mode of the CO boiler

An annual report shall be submitted to the District which includes a summary of the number of hours the CO boiler was operated in each mode, a description of maintenance, all scheduled and unscheduled work performed for each mode, CO concentration in PPM and hourly CO emissions calculated based on 40CFR 60 Subpart J monitoring data during each mode. The report shall be submitted within 90 days from the end of the calendar year

The operator shall not operate the FCCU if the CO emissions from the FCCU to the atmosphere exceed the 500 ppmv limits set forth in 40CFR60 Subpart J and Consent Decree

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996; 40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : D151, C164]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E448.3 The operator shall comply with the following requirements:

The operator shall maintain the SCR bypass stack dampers for Heaters 1F-1 and 1F-2 (Device IDs D913 and D914) at a fully closed position such that no emissions will be exhausted through the bypass stacks whenever fuel is supplied to the heaters, unless a contractor, who is certified under the Laboratory Approval Program (LAP), is continuously monitoring NO_x and SO_x emissions from the bypass stack(s) using a District-approved test method

The operator shall install and maintain damper limit switches or other equivalent device to accurately indicate the fully closed position of the SCR bypass stack dampers

The operator shall record the position of the dampers at least once every 15 minutes and any time the damper position changes

The operator shall maintain records in a manner approved by the District to demonstrate compliance with the requirements specified in this condition

The District shall be notified of the date and time of each opening of any bypass stack damper(s) for Heaters 1F-1 and 1F-2 at least 24 hours prior to opening for a planned event or no more than one hour after opening for an unplanned event

The District shall be notified of the date, time, and duration of each instance of the opening of any bypass stack dampers for Heaters 1F-1 and 1F-2 and of the uncontrolled emissions resulting from the event within 24 hours of closing the damper(s)

[RULE 2011, 5-6-2005; RULE 2012, 5-6-2005]

[Devices subject to this condition : D913, D914, S2425, S2426]

E448.4 The operator shall comply with the following requirements:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall maintain the SCR bypass stack dampers for Platinum Reformer Heater 19F-1 (Device ID D924) at a fully closed position such that no emissions will be exhausted through the bypass stacks whenever fuel is supplied to the heater

The operator shall install and maintain damper limit switches or other equivalent device to accurately indicate the fully closed position of the SCR bypass stack dampers

The operator shall record the position of the dampers at least once every 15 minutes and any time the damper position changes

The operator shall install and maintain an automatic fuel shutoff system to cut off the fuel supply to the heater whenever any of the bypass stack dampers is not in the fully closed position

The operator shall maintain records in a manner approved by the District to demonstrate compliance with the requirements specified in this condition

The District shall be notified of the date and time of each opening of any bypass stack damper(s) for Platinum Reforming Heater 19F-1 when fuel will be or was supplied to the heater while a Damper(s) were open at least 24 hours prior to opening for a planned event or no more than one hour after opening for an unplanned event

The District shall be notified of the date, time, duration of each instance of the opening of any bypass stack damper(s) for Platinum Reforming Heater 19F-1, as well as if fuel was supplied to the heater while a damper was open, within 24 hours of closing the damper(s)

[RULE 2012, 5-6-2005]

[Devices subject to this condition : D924, S2427]

E448.5 The operator shall comply with the following requirements:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The operator shall maintain in operation the following modes:

1. HDS Reactor 24C-11 (Device D368) in standard mode: The feed shall be directed to the HDS Reactor followed by either or both of the Zinc Oxide Reactors 24C-12 (Device D369) and/or 24C-13 (Device D370).
2. HDS Reactor 24C-11 (Device D368) in bypass mode: The feed shall bypass the HDS Reactor in whole or in part to the Zinc Oxide Reactors 24C-12 (Device D369) and 24C-13 (Device D370), which shall be operated in series.

The HDS Reactor shall not operate in bypass mode unless a blend or layered arrangement of HDS catalyst and ZnO catalyst is present in ZnO Reactor 24C-12 (Device D369).

The operator shall maintain records of the catalyst type installed in the ZnO Reactor 24C-12 (Device D369).

The operator shall maintain records of the number of days the HDS Reactor is operated in each mode.

The operator shall notify the AQMD at least 10 days prior to switching from standard to bypass mode.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D368, D369, D370]

E448.6 The operator shall comply with the following requirements:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The emissions from the regenerator (Device D151) may be vented from ESP's C165, C166, C2283, and C2284 directly to atmosphere via Device S1739 and bypass the waste heat boiler (Device D1511), the SCR (Device C1772), and the ID fan (2K-2). During the inspection and maintenance of waste heat boiler per California Code of Regulations, Title 8, Section 770(b), the bypass of the SCR/waste heat boiler/ID fan will be limited to 14 days per occurrence.

The District shall be notified 24 hours in advance of any scheduled bypass of the SCR/waste heat boiler/ID fan

The District shall be notified within 24 hours following any unscheduled bypass of the SCR/waste heat boiler/ID fan

Records should be kept to demonstrate compliance with this condition

[RULE 3004(a)(1), 12-12-1997; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D151, C1772]

E448.7 The operator shall comply with the following requirements:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The emissions from the boiler may be vented from CO catalyst reactor, economizer, and SCR directly to atmosphere via stacl. After the CalOSHA-mandated inspections and other maintenance activities are completed, boiler must be started up.

A startup or shutdown period shall not exceed 30 non-consecutive hours when the SCR system has no control effect for the subject devices.

Initial startup period of the subject devices shall be permitted to 144 hours per occurrence in each boiler.

The District shall be notified 24 hours in advance of any scheduled startup when SCR has no control effect.

The District shall be notified within 24 hours following any unscheduled startup when SCR has no control effect.

Records should be kept to demonstrate compliance with this condition.

[RULE 2005, 6-3-2011]

[Devices subject to this condition : D1236, C1238, D1239, C1241]

H. Applicable Rules

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 1176 |

[RULE 1176, 9-13-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D688, D1773, D1775]

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 463 |
| VOC | District Rule | 1178 |

[RULE 1178, 4-7-2006; RULE 463, 5-6-2005]

[Devices subject to this condition : D609, D610, D681, D683]

H23.4 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| VOC | District Rule | 1149 |
| VOC | 40CFR60, SUBPART | Kb |

[RULE 1149, 7-14-1995; RULE 1149, 5-2-2008; 40CFR 60 Subpart Kb, 10-15-2003]

[Devices subject to this condition : D691, D692, D693, D694, D708, D724, D757, D761, D762, D778, D779, D915, D1220, D1685, D1743, D1747, D1751, D1755]

H23.5 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| VOC | 40CFR60, SUBPART | QQQ |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[40CFR 60 Subpart QQQ, 10-17-2000]

[Devices subject to this condition : D680, D681, D683, D1907]

H23.6 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| VOC | District Rule | 1149 |
| VOC | 40CFR60, SUBPART | Ka |

[RULE 1149, 7-14-1995; RULE 1149, 5-2-2008; 40CFR 60 Subpart Ka, 12-14-2000]

[Devices subject to this condition : D727, D728, D776, D777]

H23.7 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|--------------|------------------|--------------|
| Refrigerants | District Rule | 1415 |
| Refrigerants | 40CFR82, SUBPART | F |

[RULE 1415, 10-14-1994; 40CFR 82 Subpart F, 5-14-1993]

[Devices subject to this condition : E1899, E1900]

H23.8 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------|--------------|
|-------------|------|--------------|

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| | | |
|-------------------------|---------------|------|
| Chromium, Hexavalent | District Rule | 1404 |
|-------------------------|---------------|------|

[RULE 1404, 4-6-1990]

[Devices subject to this condition : E1901]

H23.9 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| Halon | District Rule | 1418 |

[RULE 1418, 9-10-1999]

[Devices subject to this condition : E1906]

H23.11 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|---------------------|---------------|--------------|
| VOC | District Rule | 465 |
| Sulfur compounds | District Rule | 465 |

[RULE 465, 8-13-1999]

[Devices subject to this condition : D2137, D2138, D2139, D2140, D2141, D2142, D2143, D2144, D2435]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.13 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| H2S | 40CFR60, SUBPART | J |

[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D83, D84, D85, D120, C164, D231, D232, D234, D235, D269, D367, C626, C686, C687, D803, D805, D833, C891, C892, C894, D913, D914, D917, D918, D920, D922, D924, D927, D928, D929, D930, D931, D949, D950, C952, D1236, D1239, D1403, C1558]

H23.15 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| NOX | 40CFR60, SUBPART | GG |
| SOX | 40CFR60, SUBPART | GG |
| SOX | 40CFR60, SUBPART | J |

[40CFR 60 Subpart GG, 2-24-2006; 40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : D926]

H23.17 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------|--------------|
|-------------|------|--------------|

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| | | |
|-------------------|------------------|---|
| CO | 40CFR60, SUBPART | J |
| PM | 40CFR60, SUBPART | J |
| Visible Emissions | 40CFR60, SUBPART | J |
| SOX | 40CFR60, SUBPART | J |

[40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : D151]

H23.18 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| VOC | 40CFR60, SUBPART | QQQ |
| VOC | District Rule | 1149 |

[RULE 1149, 7-14-1995; RULE 1149, 5-2-2008; 40CFR 60 Subpart QQQ, 10-17-2000]

[Devices subject to this condition : D730, D731, D741, D751, D1763]

H23.19 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| H2S | 40CFR60, SUBPART | J |
| NOX | 40CFR60, SUBPART | Db |

[40CFR 60 Subpart Db, 1-28-2009; 40CFR 60 Subpart J, 6-24-2008]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D1236, D1239]

H23.24 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| HAPs | 40CFR61, SUBPART | FF |

[40CFR 61 Subpart FF, 12-4-2003]

[Devices subject to this condition : D680, D681, D683, D684, D685, D693, D694, D705, D1685, D1860, D1907, D2253, D2254, D2255]

H23.25 This equipment is subject to the applicable requirements of the following rules or regulations:

TABLE CONDITION PARAMETER NOT SET UP

[RULE 1173, 5-13-1994]

[Devices subject to this condition : D1855]

H23.26 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|--------------|------------------|--------------|
| Refrigerants | District Rule | 1411 |
| Refrigerants | 40CFR82, SUBPART | B |

[RULE 1411, 3-1-1991; 40CFR 82 Subpart B, 7-14-1992]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : E1902]

H23.27 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 1122 |

[RULE 1122, 10-1-2004; RULE 1122, 5-1-2009]

[Devices subject to this condition : E2022]

H23.29 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 109 |

[RULE 109, 5-2-2003]

[Devices subject to this condition : E2020]

H23.30 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 464 |

[RULE 464, 12-7-1990]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : C236, D680, D684, D685, D1250, D2145]

H23.31 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| VOC | 40CFR60, SUBPART | Kb |

[40CFR 60 Subpart Kb, 10-15-2003]

[Devices subject to this condition : D752]

H23.32 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 1149 |

[RULE 1149, 7-14-1995; RULE 1149, 5-2-2008]

[Devices subject to this condition : D690, D695, D696, D701, D715, D720, D721, D722, D732, D733, D734, D735, D736, D737, D738, D739, D742, D743, D745, D746, D747, D748, D749, D750, D753, D755, D756, D759, D760, D764, D765, D766, D767, D769, D770, D771, D772, D773, D774, D831, D832, D1417, D1419, D1428, D1437]

H23.33 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------|--------------|
| | | |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

SOX | 40CFR60, SUBPART | J

[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

[Devices subject to this condition : D925, D1236, D1239]

H23.34 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|------------------|--------------|
| VOC | District Rule | 1173 |
| VOC | 40CFR60, SUBPART | GGGa |

This equipment was subject to the applicable requirements of 40CFR60 Subpart GGG per Consent Decree Civil Case No. 05 C 5809 dated 12-13-2005. This equipment is now subject to the applicable requirements of 40CFR60 Subpart GGGa per ExxonMobil's notification to EPA dated 08-24-2009.

[RULE 1173, 5-13-1994; RULE 1173, 2-6-2009; 40CFR 60 Subpart GGGa, 6-2-2008; 40CFR 63 Subpart CC, 6-23-2003; CONSENT DECREE CIVIL CASE No. 05 C 5809, 12-13-2005]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D355, D356, D390, D525, D542, D574, D869, D980, D981, D982, D983, D984, D985, D986, D1298, D1475, D1527, D1556, D1740, D1788, D1789, D1790, D1791, D1792, D1793, D1794, D1800, D1803, D1805, D1807, D1808, D1809, D1810, D1811, D1815, D1819, D1825, D1826, D1827, D1828, D1829, D1830, D1831, D1834, D1838, D1839, D1840, D1842, D1844, D1845, D1849, D1850, D1851, D1852, D1853, D1855, D1860, D1862, D1863, D1864, D1865, D1877, D1888, D1889, D1891, D1892, D1895, D1936, D1937, D1938, D1955, D1956, D1957, D1983, D1987, D1988, D2009, D2111, D2123, D2231, D2235, D2249, D2256, D2259, D2330, D2366, D2367, D2368, D2369, D2370, D2371, D2372, D2373, D2374, D2375, D2376, D2377, D2378, D2379, D2380, D2383, D2412, D2415, D2417, D2422, D2430, D2482, D2518, D2537, D2547]

H23.35 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| SOX | District Rule | 1118 |

[RULE 1118, 11-4-2005]

[Devices subject to this condition : C891, C892, C894, C1558]

H23.37 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| PM | District Rule | 1470 |
| VOC | District Rule | 1110.2 |
| CO | District Rule | 1110.2 |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| | | |
|------|------------------|------|
| CO | 40CFR60, SUBPART | III |
| NOX | 40CFR60, SUBPART | III |
| PM | 40CFR60, SUBPART | III |
| ROG | 40CFR60, SUBPART | III |
| HAPs | 40CFR63, SUBPART | ZZZZ |

[RULE 1110.2, 7-9-2010; RULE 1470, 5-4-2012; **40CFR 60 Subpart IIII, 7-11-2006;**
40CFR 63 Subpart ZZZZ, 1-18-2008]

[Devices subject to this condition : D2428]

H23.38 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|--------------|------------------|--------------|
| Refrigerants | District Rule | 1415.1 |
| Refrigerants | 40CFR82, SUBPART | F |

[RULE 1415.1, 12-3-2010; **40CFR 82 Subpart F, 5-14-1993]**

[Devices subject to this condition : D1939]

H23.39 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------------|------------------|--------------|
| NOX | 40CFR60, SUBPART | D |
| SOX | 40CFR60, SUBPART | D |
| Visible Emissions | 40CFR60, SUBPART | D |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

**[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809,
12-13-2005]**

[Devices subject to this condition : D805]

I. Administrative

I297.1 This equipment shall not be operated unless the facility holds 73 pounds of NO_x RTCs in its allocation account to offset the annual emissions increase for the first year of operation. RTCs held to satisfy this condition may be transferred only after one year from the initial start of operation. If the hold amount is partially satisfied by holding RTCs that expire midway through the hold period, those RTCs may be transferred upon their respective expiration dates. This hold amount is in addition to any other amount of RTCs required to be held under other condition(s) stated in this permit.

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

In lieu of holding RTCs for the entire duration specified above, RTCs held for the purpose of demonstrating compliance with this condition may be transferred as specified below, provided quarterly emissions do not exceed the corresponding quarterly limit listed in the table below. The amount available for transfer shall be as specified in Rule 2005(f)(3). Such amount may be transferred only after the end of the subject quarter. If the first day of operation does not coincide with the first day of a calendar quarter, the emission limit for that calendar quarter shall be prorated based on the number of days remaining in the calendar quarter as of the first day of operation and the amount available for transfer after that calendar quarter shall be the prorated emission limit minus the actual emissions reportable for that calendar quarter pursuant to RECLAIM Monitoring, Recordkeeping, and Reporting protocols (MRR) and the emission limit for the portion of the first year of operation falling in the fifth calendar quarter shall be prorated based on the number of days of the first year of operation occurring in that calendar quarter and the amount available for transfer after that calendar quarter shall be the prorated emission limit minus the actual emissions reportable for the portion of the first year of operation occurring in that calendar quarter pursuant to RECLAIM MRR. If the quarterly certified emissions for any quarter (or portion of a quarter occurring within the first year of operation) exceed the corresponding quarterly emission limit or prorated quarterly emission limit, as applicable, the facility may only sell RTCs held pursuant to Rule 2005(f) after the first calendar quarter ending at least one year after operation commences.

| Calendar Quarter | Emission Limit (Pounds of NOx RTCs) |
|-------------------------------|-------------------------------------|
| January 1 through March 31 | 18 |
| April 1 through June 30 | 18 |
| July 1 through September 30 | 18 |
| October 1 through December 31 | 19 |

[RULE 2005, 6-3-2011]

[Devices subject to this condition : D2428]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

I297.2 This equipment shall not be operated unless the facility holds 4 pounds of SO_x RTCs in its allocation account to offset the annual emissions increase for the first year of operation. RTCs held to satisfy this condition may be transferred only after one year from the initial start of operation. If the hold amount is partially satisfied by holding RTCs that expire midway through the hold period, those RTCs may be transferred upon their respective expiration dates. This hold amount is in addition to any other amount of RTCs required to be held under other condition(s) stated in this permit.

In lieu of holding RTCs for the entire duration specified above, RTCs held for the purpose of demonstrating compliance with this condition may be transferred as specified below, provided quarterly emissions do not exceed the corresponding quarterly limit listed in the table below. The amount available for transfer shall be as specified in Rule 2005(f)(3). Such amount may be transferred only after the end of the subject quarter. If the first day of operation does not coincide with the first day of a calendar quarter, the emission limit for that calendar quarter shall be prorated based on the number of days remaining in the calendar quarter as of the first day of operation and the amount available for transfer after that calendar quarter shall be the prorated emission limit minus the actual emissions reportable for that calendar quarter pursuant to RECLAIM Monitoring, Recordkeeping, and Reporting protocols (MRR) and the emission limit for the portion of the first year of operation falling in the fifth calendar quarter shall be prorated based on the number of days of the first year of operation occurring in that calendar quarter and the amount available for transfer after that calendar quarter shall be the prorated emission limit minus the actual emissions reportable for the portion of the first year of operation occurring in that calendar quarter pursuant to RECLAIM MRR. If the quarterly certified emissions for any quarter (or portion of a quarter occurring within the first year of operation) exceed the corresponding quarterly emission limit or prorated quarterly emission limit, as applicable, the facility may only sell RTCs held pursuant to Rule 2005(f) after the first calendar quarter ending at least one year after operation commences.

| Calendar Quarter | Emission Limit (Pounds of SO _x RTCs) |
|----------------------------|---|
| January 1 through March 31 | 1 |
| April 1 through June 30 | 1 |

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| | | |
|-------------------------------|--|---|
| July 1 through September 30 | | 1 |
| October 1 through December 31 | | 1 |

[RULE 2005, 6-3-2011]

[Devices subject to this condition : D2428]

- I297.3 This equipment shall not be operated unless the facility holds 9 pounds of NOx RTCs in its allocation account to offset the annual emissions increase for the first year of operation. RTCs held to satisfy this condition may be transferred only after one year from the initial start of operation. If the hold amount is partially satisfied by holding RTCs that expire midway through the hold period, those RTCs may be transferred upon their respective expiration dates. This hold amount is in addition to any other amount of RTCs required to be held under other condition(s) stated in this permit.

[RULE 2005, 6-3-2011]

[Devices subject to this condition : C686, C687]

J. Rule 461

- J109.1 The operator shall use, except for diesel transfer, the phase I vapor recovery system in full operation whenever this equipment is in use. This system shall be installed, operated and maintained to meet all CARB certification requirements.

[RULE 461, 6-3-2005]

[Devices subject to this condition : D2544]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

J110.1 The operator shall use, except for diesel transfer, the phase II vapor recovery system in full operation whenever gasoline from this equipment is dispensed to motor vehicles as defined in Rule 461. This system shall be installed, operated and maintained to meet all CARB certification requirements.

[RULE 461, 6-3-2005]

[Devices subject to this condition : D2546]

J373.2 The operator shall comply with the following gasoline transfer and dispensing requirements:

New equipment installations and subsequent service and repairs for any certified component for which this permit was issued, shall only be performed by a current and certified person who has successfully completed the manufacturer's training course and appropriate international code council (ICC) certification. Completion of any SCAQMD training course does not constitute as a substitute for this requirement. Proof of successful completion of any manufacturer training course shall be with the manufacturer.

[RULE 461, 6-3-2005; RULE 461, 4-6-2012]

[Devices subject to this condition : D2544, D2546]

J373.3 The operator shall comply with the following gasoline transfer and dispensing requirements:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

The Phase II vapor recovery system shall be installed, operated, and maintained such that the maximum allowable pressure through the system including nozzle, vapor hose, swivels, and underground piping does not exceed the dynamic back pressures described by the California Air Resources Board Executive Order by which the system was certified:

| NITROGEN FLOWRATES (CFH) | DYNAMIC BACK PRESSURE (INCHES OF WATER) |
|--------------------------|---|
| 60 | 0.35 |
| 80 | 0.62 |

Dynamic back pressure tests shall be conducted to determine the Phase II system vapor recovery back pressures. The tests shall be conducted in accordance with carb test procedure TP-201.4 (July 3, 2002), methodology 1 as a performance test and as a reverification test. Results shall be submitted to the SCAQMD, Office of Engineering and Compliance, within seventy-two (72) hours of tests.

[**RULE 461, 6-3-2005**; RULE 461, 4-6-2012]

[Devices subject to this condition : D2546]

J373.4 The operator shall comply with the following gasoline transfer and dispensing requirements:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A leak rate and cracking pressure test of pressure/vacuum relief vent valves shall be conducted within ten days (10) after the start of operation of the Phase I EVR equipment and at least once every three (3) years thereafter to determine the pressure and vacuum at which the pressure/vacuum vent valve actuates, and to determine the volumetric leak rate at a given pressure. The test shall be conducted in accordance with the test procedure method TP-201.1E (October 8, 2003).

Results shall be submitted to the SCAQMD, office of engineering and compliance, within seventy-two (72) hours of test. This test result shall be kept on site for three (3) years and made available to district representatives upon request.

[RULE 461, 6-3-2005; RULE 461, 4-6-2012]

[Devices subject to this condition : D2544, D2546]

J373.5 The operator shall comply with the following gasoline transfer and dispensing requirements:

All Phase I and Phase II vapor recovery equipment at this facility shall be installed, operated and maintained to meet all California Air Resources Board certification requirements.

[RULE 461, 6-3-2005; RULE 461, 4-6-2012]

[Devices subject to this condition : D2546]

K. Record Keeping/Reporting

K40.3 The operator shall provide to the District a source test report in accordance with the following specifications:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Emission data shall be expressed in terms of concentration (ppmv), corrected to 3 percent oxygen, dry basis.

Emission data shall be expressed in terms of mass rate (lbs/hr). In addition, solid PM emissions, if required to be tested, shall also be reported in terms of grains per DSCF.

Source test results shall also include the heat input (in mmbtu/hr) and the fuel flow rate (in mmscf/hr) of the boiler under which the test was conducted.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C1238, C1241]

K40.4 The operator shall provide to the District a source test report in accordance with the following specifications:

Emission data shall be expressed in terms of mass rate (lbs/hr). In addition, solid PM emissions, if required to be tested, shall also be reported in terms of grains per DSCF.

Source test results shall be submitted to the District no later than 60 days after the source test was conducted.

All exhaust flow rate shall be expressed in terms of dry standard cubic feet per minute (DSCFM) and dry actual cubic feet per minute (DACFM).

Emission data shall be expressed in terms of concentration (ppmv), corrected to 3 percent oxygen, dry basis.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D367, C1772]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the date of operation

the elapsed time in hours

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D394, D955, D957, D959, D961, D1686, D1785, D1786]

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Throughput and vapor pressure of stored liquid

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; RULE 463, 5-6-2005]

[Devices subject to this condition : D690, D691, D695, D696, D697, D698, D699, D700, D701, D702, D703, D704, D706, D709, D710, D714, D715, D718, D719, D723, D729, D731, D732, D733, D734, D735, D736, D737, D738, D739, D740, D741, D742, D743, D744, D745, D746, D748, D749, D753, D754, D755, D756, D758, D759, D760, D763, D764, D765, D766, D767, D768, D769, D770, D771, D772, D775, D776, D830, D831, D832, D1417, D1419, D1425, D1437, D1554, D2447]

K67.3 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 1113, 11-8-1996; RULE 1113, 7-13-2007; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : E1905]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For spray filling only: product loaded, line pressure and railcar initial, midpoint and final temperature, number and magnitude of leaks found

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D675, D1994]

K67.5 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For spray filling only: product loaded; line pressure; and rail car initial, midpoint, and final temperature; number and magnitude of leaks found

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D675]

K67.11 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Catalyst management including periodic addition/replacement

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : C233]

K67.13 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Daily inspections & maintenance of all the valves at this facility

[RULE 1401, 6-5-2009]

[Devices subject to this condition : D2232, D2324, D2325, D2336, D2339, D2340, D2341]

K67.14 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Required maintenance of the CO boiler

Duration of the maintenance and unfired mode of the CO boiler

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

[Devices subject to this condition : D151, C164]

K67.15 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Duration of the planned startup and shutdown of the FCCU

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : D151]

K67.16 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Truck outhauls of the hopper

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : C2283, C2284, C2314]

K67.17 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

VOC concentration at the outlet of the primary carbon adsorber.

VOC concentration at the outlet of the secondary adsorber.

Date and time the VOC measurements were taken.

[RULE 1303(a)-BACT, 5-10-1996]

[Devices subject to this condition : D609, C2250]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.18 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

when switching carbon vessel for services and refilling the activated carbon:

concentration of H₂S (ppm) at outlet upon breakthrough

date of switching or refilling

supplier name of activated carbon

date of purchase

carbon type

density of carbon, gram/cc

H₂S capacity, gram of H₂S /cc

**[40CFR 60 Subpart J, 6-24-2008; CONSENT DECREE CIVIL CASE No. 05 C 5809,
12-13-2005]**

[Devices subject to this condition : C2393, C2394]

K67.19 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Records when emptying the sulfur compound contaminated condensate collection pot 28SP-1

[RULE 1401, 6-5-2009]

[Devices subject to this condition : D2408]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.20 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Records when using the standby eductor (28H-6B) and associated piping system

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D2391, D2409]

K67.21 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A log of engine operations, including manual and automatic operation, documenting the total time the engine is operated each month and the specific reason for operation as:

- A. Emergency use
- B. Maintenance and testing
- C. Other (Describe the reason for the operation)

In addition, for each the engine is manually started, the log shall include the date of engine operation, the specific reason for operation, and the totalizing hour meter readings (in hours and tenths of hours) at the beginning and end of the operation.

On or before January 15th of each year, the operator shall record in the engine log:

- A. the total hours of engine operation for the previous calendar year, and
- B. the total hours of engine operation for maintenance and testing for the previous calendar year.

Engine operation log(s) shall be retained on site for a minimum of five calendar years and shall be made available to the Executive Officer or representative upon request.

[RULE 1110.2, 7-9-2010; **RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996;**
RULE 1470, 5-4-2012]

[Devices subject to this condition : D2428]

K67.22 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- (a) VOC concentration at the outlet of the primary carbon adsorber.
- (b) Date and time the VOC measurements were taken.
- (c) Date of carbonbed breakthrough and date of carbon changeouts or canister switchout.

[RULE 1176, 9-13-1996; RULE 1303(a)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997; 40CFR 61 Subpart FF, 11-12-2002]

[Devices subject to this condition : D1671, D2136]

K67.23 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

All records and test results that are required to be maintained by Rule 461 shall be kept on site and made available to District representatives upon request.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D2544, D2546]

K67.24 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Records of monthly and annual fuel dispensed shall be prepared, shall be retained on site for two years, and shall be made available to District representatives upon request.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D2544, D2546]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.25 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

The owner/operator shall submit the facility's monthly gasoline throughput data for the previous calendar year to the Executive Officer on or before March 1 following each calendar year.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D2544, D2546]

K171.1 The operator shall provide to the District the following items:

Final drawings and/or specifications of the geodesic dome cover, slotted guidepole and wiper and other tank appurtenances upgrades to be installed/constructed shall be submitted to the district within 60 days after construction.

[RULE 1178, 4-7-2006]

[Devices subject to this condition : D729, D752, D754, D763, D776, D778, D779]

K171.6 The operator shall provide to the District the following items:

Final designed data sheets within 60 days after construction of the fuel gas optimization project is completed

[RULE 1301, 12-7-1995]

[Devices subject to this condition : C2219, C2223, C2229]

K171.9 The operator shall provide to the District the following items:

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Update P&ID drawings of the desalter tailwater handling system, including normal and emergency vents, the drain system for brine water and brine oily water, update function of Tanks 72D-10 & 72D-11, and the removal of the oily water sump, shall be submitted to the district within 60 days after permit issuance date

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D1250, D2145]

K171.11 The operator shall provide to the District the following items:

Update P&ID drawings of the fuel gas filter separators and associated reservoirs including emergency vents shall be submitted to the district within 60 days after permit issuance date

Final design data sheet of the filter separators (Vessels 1J-2 & 1J-3) including the internal filter elements shall be submitted to the District within 60 days after permit issuance date

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D2257, D2258]

K171.12 The operator shall provide to the District the following items:

P&ID drawings of the NH₃ injection grid located upstream of the SCR (Grid 3) shall be submitted to the district within 60 days after construction

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : C1772]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K171.13 The operator shall provide to the District the following items:

P&ID drawings of the bypass ducting handling emergency vent, including the dimensions and detailed flow detection with recording system, shall be submitted to the district within 60 days after permit issuance date

[RULE 1105.1, 11-7-2003]

[Devices subject to this condition : C1772]

K171.14 The operator shall provide to the District the following items:

Update and complete P&ID drawings of the equipment shall be submitted to the district within 60 days after permit issuance date

Operating and maintenance description

[RULE 404, 2-7-1986; RULE 405, 2-7-1986]

[Devices subject to this condition : D2316, C2317]

K171.15 The operator shall provide to the District the following items:

Update P&ID drawings of the heater, including the firing rate in MMBtu/hr, fuel gas/utility system, removal of miscellaneous process gases (fume/waste gas) feed line(s) and their knockout pots (e.g., Vessel 2C-20), shall be submitted to the District within 60 days after permit issuance date

[RULE 2011, 5-6-2005; 40CFR 60 Subpart J, 6-24-2008]

[Devices subject to this condition : D920]

FACILITY PERMIT TO OPERATE EXXONMOBIL OIL CORPORATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K171.16 The operator shall provide to the District the following items:

Update P&ID drawings of the particulates/fines knockout pot including emergency vents shall be submitted to the District within 60 days after permit issuance date

Final design data sheet of the knockout pot (Vessel 2C-22) shall be submitted to the District within 60 days after permit issuance date

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D2321]

K171.17 The operator shall provide to the District the following items:

Update P&ID drawings of the fuel gas filter separators and associated reservoirs including emergency vents shall be submitted to the district within 60 days after permit issuance date

Final design data sheet of the filter separator shall be submitted to the District within 60 days after permit issuance date

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D2328, D2329]