

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
460284	F92037	OVEN, CURING
460287	F92038	OVEN, BAKING
460289	F92039	OVEN, DRYING
460290	F92044	OVEN, BAKING
460292	F92047	SPRAY BOOTH, PAINT AND SOLVENT
460293	F92048	SPRAY BOOTH, PAINT AND SOLVENT
460295	F92062	SPRAY BOOTH, PAINT AND SOLVENT
460296	F92064	SPRAY BOOTH, PAINT AND SOLVENT
460297	F92065	SPRAY BOOTH, PAINT AND SOLVENT
460298	F92066	SPRAY BOOTH, PAINT AND SOLVENT
470374	F92067	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470379	F92068	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470380	F92069	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470382	F92070	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470383	F92071	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470384	F92072	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
470386	F92074	SPRAY BOOTH, PAINT AND SOLVENT
470387	F92075	SPRAY BOOTH, PAINT AND SOLVENT
470388	F92076	OVEN, CURING
470389	F92077	OVEN, POWDER COATING
470390	F92078	OVEN, POWDER COATING
470392	F92079	OVEN, POWDER COATING
470393	F92080	OVEN, POWDER COATING
470394	F92081	OVEN, CURING
470463	F92082	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
473461	F98725	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
473462	F98727	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
492529	G4020	AEROSOL CAN RECYCLING SYSTEM
501204	G7336	LASER CUTTER NO. 1
501206	G7337	DUST COLLECTOR NO. 1
501208	G7338	LASER CUTTER NO. 2
501210	G7339	DUST COLLECTOR NO. 2
501212	G7340	LASER CUTTER NO.3
501214	G7341	DUST COLLECTOR NO. 3
500473	G7349	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
500474	G7350	SPRAY BOOTH/ENCLOSURE, POWDER COATING SYSTEM
500475	G7351	WASHER
500476	G7352	OVEN, DRYING
500477	G7353	OVEN, CURING
503450	G7354	OVEN, CURING
503451	G7355	OVEN, CURING
518877		SPRAY BOOTH, PAINT AND SOLVENT
518878		SPRAY BOOTH, PAINT AND SOLVENT

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

NOTE: EQUIPMENT LISTED ABOVE THAT HAVE NO CORRESPONDING PERMITS TO OPERATE NUMBER ARE ISSUED PERMITS TO CONSTRUCT. THE ISSUANCE OR DENIAL OF THEIR PERMITS TO OPERATE IS SUBJECT TO ENGINEERING FINAL REVIEW. ANY OTHER APPLICATIONS THAT ARE STILL BEING PROCESSED AND HAVE NOT BEEN ISSUED PERMITS TO CONSTRUCT OR PERMITS TO OPERATE WILL NOT BE FOUND IN THIS TITLE V PERMIT.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

FACILITY WIDE CONDITION(S)

Condition(s):

1. EXCEPT FOR OPEN ABRASIVE BLASTING OPERATIONS, THE OPERATOR SHALL NOT DISCHARGE INTO THE ATMOSPHERE FROM ANY SINGLE SOURCE OF EMISSIONS WHATSOEVER ANY AIR CONTAMINANT FOR A PERIOD OR PERIODS AGGREGATING MORE THAN THREE MINUTES IN ANY ONE HOUR WHICH IS:
 - A. AS DARK OR DARKER IN SHADE AS THAT DESIGNATED NO. 1 ON THE RINGELMANN CHART, AS PUBLISHED BY THE UNITED STATES BUREAU OF MINES; OR
 - B. OF SUCH OPACITY AS TO OBSCURE AN OBSERVER'S VIEW TO A DEGREE EQUAL TO OR GREATER THAN DOES SMOKE DESCRIBED IN SUBPARAGRAPH (A) OF THIS CONDITION.
[RULE 401]
2. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS DISCHARGED TO THE ATMOSPHERE FROM THIS FACILITY SHALL NOT EXCEED 372 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
3. IN ADDITION TO THE RECORD KEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS FACILITY TO VERIFY THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER COATING SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]
4. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY AND SUBJECT TO DISTRICT RULES SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(a)(1)-BACT, 1303(b)(2)-OFFSET]
5. TO MAINTAIN EXEMPTION FROM THE RULE 1132 REQUIREMENTS, THE TOTAL QUANTITY OF VOC EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 20 TONS (40,000 POUNDS) IN ANY EMISSION INVENTORY YEAR. THE EMISSION INVENTORY YEAR SHALL BE THE ANNUAL EMISSION REPORTING PERIOD BEGINNING FROM JULY 1 OF THE PREVIOUS YEAR THROUGH JUNE 30 OF A GIVEN YEAR. TO ENSURE COMPLIANCE WITH THE EMISSION CAP OF THIS CONDITION, THE FACILITY OPERATOR SHALL:
 - A. COMPLY WITH RULE 109 (RECORDKEEPING FOR VOLATILE ORGANIC COMPOUND EMISSIONS).
 - B. WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH CALENDAR MONTH, TOTAL AND RECORD VOC EMISSIONS FOR THE CALENDAR MONTH FROM ALL EQUIPMENT AND OPERATIONS THAT ARE REQUIRED TO HAVE WRITTEN PERMITS OR ARE EXEMPT FROM WRITTEN PERMITS PURSUANT TO RULE 219. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.

- C. BY JULY 15 OF EACH YEAR, TOTAL AND RECORD VOC EMISSIONS FROM THE FACILITY FOR THE EMISSION INVENTORY YEAR.
- D. MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED VOC-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
- E. RETAIN ALL PURCHASE INVOICES FOR ALL VOC-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE VOC-CONTAINING MATERIAL REMOVED FROM THE FACILITY.

IF THE TOTAL FACILITY VOC EMISSIONS FROM THE MONTHLY RECORDS FOR THE EMISSION INVENTORY YEAR EXCEED THE EMISSION CAP OF THIS CONDITION, THE OPERATOR SHALL SUBMIT APPROPRIATE APPLICATIONS AND ACHIEVE COMPLIANCE PURSUANT TO THE REQUIREMENTS SPECIFIED IN RULE 1132.

[RULE 1132]

- 6. TO MAINTAIN EXMPTION FROM THE NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS (NESHA) REQUIREMENTS, THE TOTAL QUANTITY OF HAZARDOUS AIR POLLUTANT (HAP) EMISSIONS FROM THIS FACILITY SHALL NOT EXCEED 10 TONS (20,000 POUNDS) OF A SINGLE HAP OR 25 TONS (50,000 POUNDS) OF A COMBINATION OF HAPS IN ANY TWELVE CALENDAR MONTH PERIOD.
[40CFR63 SUBPART MMMM]
- 7. TO ENSURE COMPLIANCE WITH THE HAP(S) EMISSION CAPS, THE FACILITY OPERATOR SHALL:
 - (A) IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT AND THIS FACILITY TO VERIFY THE MONTHLY HAP EMISSIONS IN POUNDS AND THE HAP CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS). THE RECORDS SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT.
 - (B) WITHIN 14 CALENDAR DAYS AFTER THE END OF EACH MONTH, TOTAL AND RECORD HAP EMISSIONS FOR THE MONTH FROM ALL EQUIPMENT AND OPERATIONS THAT ARE REQUIRED TO HAVE WRITTEN PERMITS OR ARE EXEMPT FROM WRITTEN PERMITS PURSUANT TO RULE 219. THE RECORD SHALL INCLUDE ANY PROCEDURES USED TO ACCOUNT FOR CONTROL DEVICE EFFICIENCIES AND/OR WASTE DISPOSAL. IT SHALL BE SIGNED AND CERTIFIED FOR ACCURACY BY THE HIGHEST RANKING INDIVIDUAL RESPONSIBLE FOR COMPLIANCE WITH DISTRICT RULES.
 - (C) MAINTAIN A SINGLE LIST WHICH INCLUDES ONLY THE NAME AND ADDRESS OF EACH PERSON FROM WHOM THE FACILITY ACQUIRED HAP-CONTAINING MATERIAL REGULATED BY THE DISTRICT THAT WAS USED OR STORED AT THE FACILITY DURING THE PRECEDING 12 MONTHS.
 - (D) RETAIN ALL PURCHASE INVOICES FOR ALL HAP-CONTAINING MATERIAL USED OR STORED AT THE FACILITY, AND ALL WASTE MANIFESTS FOR ALL WASTE HAP-CONTAINING MATERIAL REMOVED FROM THE FACILITY, FOR FIVE YEARS.

[40CFR63 SUBPART MMMM]

**FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC**

8. ALL RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED AT THE PREMISES FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.
[RULE 109, 1303(a)(1)-BACT, 1303(b)(2)-OFFSET, 40CFR63 SUBPART MMMM]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92037
A/N 460284

Equipment Description:

OVEN, CURING, RAMCO, 8'-0" W. X 14'-0" D. X 8'-0" H., 800,000 BTU/HR NATURAL GAS FIRED, WITH A MAXON CYCLOMAX LOW NO_x BURNER, A 1/2 H.P. COMBUSTION AIR FAN, A 1/2 H.P. EXHAUST FAN, AND A 7-1/2 RECIRCULATION FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO_x, BY VOLUME ON A DRY BASIS @ 3% O₂, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

- 5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92038
A/N 460287

Equipment Description

OVEN, BINKS, MODEL BWN 987, 11'-0" W. X 9'-0" L. X 10'-6" H., 350,000 BTU PER HOUR, NATURAL GAS FIRED WITH ONE 3 H.P. CIRCULATING FAN AND ONE 1/2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

Periodic Monitoring:

4. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92039
A/N 460289

Equipment Description:

OVEN, BINKS, MODEL BWN 987, 11'-0" W. X 9'-0" L. X 10'-6" H., 350,000 BTU PER HOUR, NATURAL GAS FIRED, WITH ONE 3 H.P. CIRCULATING FAN AND ONE 1/2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

Periodic Monitoring:

4. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92044
A/N 460290**

Equipment Description:

OVEN, W. MILLER, MODEL NO. 4910, 18'-0" W. X 29'-0" L. X 10'-3" H., CONVEYORIZED, 1,600,000 BTU PER HOUR NATURAL GAS FIRED, WITH ONE 1/3 H.P. COMBUSTION AIR BLOWER, TWO 5 H.P. AIR KNIFE BLOWERS, ONE 10 H.P. CIRCULATING AIR FAN AND ONE 1/3 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 500 DEGREES FAHRENHEIT.
[RULE 401]

Periodic Monitoring:

4. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92047
A/N 460292**

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 20'-0" W. X 10'-0" D. X 8'-0" H., WITH FOUR 10'-0" W. X 4'-0" H. PREFILTERS, TWO 10'-0" W. X 8'-0" H. BLANKET TYPE FILTERS AND ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92048
A/N 460293**

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 20'-0" W. X 10'-0" D. X 8'-0" H., WITH FOUR 10'-0" W. X 4'-0" H. PREFILTERS, TWO 10'-0" W. X 8'-0" H. BLANKET TYPE FILTERS AND ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92062
A/N 460295

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 20'-0" W. X 10'-2" D. X 8'-10" H., WITH FOUR 4'-0" W. X 8'-0" H. PREFILTERS, TWO 10'-0" W. X 8'-0" H. BLANKET TYPE FILTERS AND ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92064
A/N 460296

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 10'-0" W. X 10'-2" D. X 8'-0" H., WITH TWO 10'-0" W. X 4'-0" H. PREFILTERS, ONE 10'-0" W. X 8'-0" H. BLANKET TYPE FILTER AND ONE 2 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92065
A/N 460297**

Equipment Description:

SPRAY BOOTH, BINKS, FLOOR FILTER TYPE, MODEL PFA 10-8-T-LH. 10'-0" W. X 9'-8" L. X 8'-0" H., WITH TWO 10'-0" W. X 4'-0" H. PREFILTERS, ONE 10'-0" W. X 8'-0" H. BLANKET TYPE FILTERS AND ONE 1 ½ HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92066
A/N 460298**

Equipment Description:

SPRAY BOOTH, FLOOR FILTER TYPE, 10'-0" W. X 9'-8" L. X 8'-0" H., WITH TWO 10'-0" W. X 4'-0" H. PREFILTERS, ONE 10'-0" W. X 8'-0" H. BLANKET TYPE FILTER AND ONE 1 ½ HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92067
A/N 470374**

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 10'-7" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]
4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]
5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]
6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]
9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
- [RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92068
A/N 470379**

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 10'-7" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]
4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]
5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]
6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED
[RULE 109, 1303(b)(2)-OFFSET]
9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
- [RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92069
A/N 470380**

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 11'-2" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]
4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]
5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]
6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]
9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
- [RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92070
A/N 470382

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 10'-7" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]
4. MECHANICAL GAUGES SHALL BE INSTALLED TO INDICATE THE STATIC PRESSURE DIFFERENTIAL ACROSS THE PREFILTERS AND POCKET FILTERS (AS ONE MEASUREMENT) AND THE FINAL FILTERS (AS A SEPARATE MEASUREMENT). IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 1.0 INCH WATER COLUMN ACROSS THE PREFILTERS/POCKET FILTERS COMBINED AND 1.5 INCHES WATER COLUMN ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 550 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

[RULE 1401]

7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.

[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
9. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004 (a)(4)]

10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92071
A/N 470383

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 10'-7" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]
4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]
5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]
6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]
7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

[RULE 1303(b)(2)-OFFSET]

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.

[RULE 109, 1303(b)(2)-OFFSET]

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.

[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.

[RULE 3004 (a)(4)]

11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
- B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
- C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004 (a)(4)]

12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

**FACILITY PERMIT TO OPERATE
AMF ANAHEIM LLC**

PERMIT TO OPERATE

**Permit No. F92072
A/N 470384**

Equipment Description:

POWDER COATING SPRAY BOOTH, BLEEKER BROS., 12'-0" W. X 8'-0" L. X 8'-0" H., WITH TWENTY-EIGHT 20" X 20" FIRST STAGE PRE-FILTERS, TWENTY-EIGHT 20" X 12" SECOND STAGE BAG FILTERS, EIGHT 24" X 24" THIRD STAGE HEPA FILTERS, AND ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTRATION SYSTEM.
[RULE 1303(a)(1)-BACT]
4. MECHANICAL GAUGES SHALL BE INSTALLED TO INDICATE THE STATIC PRESSURE DIFFERENTIAL ACROSS THE PREFILTERS AND POCKET FILTERS (AS ONE MEASUREMENT) AND THE FINAL FILTERS (AS A SEPARATE MEASUREMENT). IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 1.0 INCH WATER COLUMN ACROSS THE PREFILTERS/POCKET FILTERS COMBINED AND 1.5 INCHES WATER COLUMN ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF POWDER COATINGS SPRAYED ON ARTICLES IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF JUNE 15, 2001 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
9. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
- [RULE 3004 (a)(4)]
10. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
- THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
- [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Emissions and Requirements:

11. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 109

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92074
A/N 470386**

Equipment Description:

SPRAY BOOTH, BEATTIE, FLOOR DRY FILTER TYPE, 10'-0" W. X 10'-0" D. X 8'-0" H., WITH TWO 10'-0" W. X 4'-0" H. PREFILTERS, ONE 10'-0" W. X 8'-0" H. BLANKET TYPE FILTER AND ONE 2 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109.
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]

9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92075
A/N 470387**

Equipment Description:

SPRAY BOOTH, BINKS, FLOOR FILTER TYPE, MODEL PFA 10-8-T-LH. 10'-0" W. X 9'-8" L. X 8'-0" H., WITH TWO 10'-0" W. X 4'-0" H. PREFILTERS, ONE 10'-0" W. X 8'-0" H. BLANKET TYPE FILTERS AND ONE 1 ½ HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA OF AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THIS EQUIPMENT SHALL NOT EXCEED 48 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
6. THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO VERIFY DAILY USAGE AND DAILY VOC EMISSIONS IN ACCORDANCE WITH RULE 109
[RULE 109, 1303(b)(2)-OFFSET]
7. COATINGS, ADHESIVES, CLEAN-UP SOLVENTS, AND ANY OTHER MATERIALS CONTAINING VOLATILE ORGANIC COMPOUNDS (VOC) USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92076
A/N 470388

Equipment Description:

OVEN, CURING, RAMCO, 8'-0" W. X 14'-0" D. X 8'-0" H., 800,000 BTU/HR NATURAL GAS FIRED, WITH A MAXON CYCLOMAX LOW NO_x BURNER, A 1/2 H.P. COMBUSTION AIR FAN, A 1/2 H.P. EXHAUST FAN AND A 7-1/2 RECIRCULATION FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO_x, BY VOLUME ON A DRY BASIS @ 3% O₂, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92077
A/N 470389**

Equipment Description:

OVEN, MILLER, 800,000 BTU/HR NATURAL GAS FIRED, WITH A MAXON CYCLOMAX LOW NO_x BURNER, AND ONE 3/4 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURE ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]
4. THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO_x, BY VOLUME ON A DRY BASIS @ 3% O₂, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)BACT]

Periodic Monitoring:

5. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

6. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NO_x: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92078
A/N 470390**

Equipment Description:

OVEN, MILLER, 800,000 BTU/HR NATURAL GAS FIRED, WITH A MAXON CYCLOMAX LOW NO_x BURNER, AND ONE 3/4 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO_x, BY VOLUME ON A DRY BASIS @ 3% O₂, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92079
A/N 470392**

Equipment Description:

POWDER COATING CURING OVEN, MILLER, WITH ONE 800,000 BTU PER HOUR DIRECT NATURAL GAS FIRED MAXON CYCLOMAX 0.8M LOW-NOX BURNER AND ONE 3/4 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE TOTAL QUANTITY OF POWDER COATINGS APPLIED TO ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 550 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
4. THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO_x, BY VOLUME ON A DRY BASIS @ 3% O₂, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED ON THE ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER.
[RULE 1401]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F92080
A/N 470393**

Equipment Description:

POWDER COATING CURING OVEN, MILLER, WITH ONE 800,000 BTU PER HOUR DIRECT NATURAL GAS FIRED ECLIPSE TJ150 LOW-NOX BURNER AND ONE 10 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE TOTAL QUANTITY OF POWDER COATINGS APPLIED TO ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
4. THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO_x, BY VOLUME ON A DRY BASIS @ 3% O₂, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED ON THE ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF JUNE 15, 2001 OR EARLIER.
[RULE 1401]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:

- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
- B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
- C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92081
A/N 470394

Equipment Description:

OVEN, RAMCO, MODEL 10-10-8, 10'-0" W. X 10'-6" L. X 8'-6" H., 800,000 BTU/HR NATURAL GAS FIRED, WITH ONE 1/3 H.P. COMBUSTION AIR BLOWER, ONE 7 1/2 H.P. CIRCULATING FAN, AND ONE 2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

Periodic Monitoring:

4. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F92082
A/N 470463

Equipment Description:

POWDER COATING SYSTEM CONSISTING OF:

1. SPRAY BOOTH, BLEEKER, 12'-5" W. X 11'-2" L. X 8'-5" H.
2. TWENTY-EIGHT PRE-FILTERS, 20" W. X 20" L. X 1" D.
3. TWENTY-EIGHT POCKET FILTERS, 20" W. X 20" L. X 12" D.
4. EIGHT FINAL FILTERS, 24" W. X 24" L. X 12" D.
5. ONE 5 HP EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]
4. TWO GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE POCKET-TYPE AND THE FINAL FILTER MEDIA. IN OPERATION, THE PRESSURE DIFFERENTIAL (BETWEEN CLEAN AND DIRTY FILTERS) SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS THE POCKET-TYPE FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]
5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]
6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

7. THE TOTAL QUANTITY OF POWDER COATING SPRAYED IN THIS EQUIPMENT SHALL NOT EXCEED 370 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]
9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
- [RULE 3004 (a)(4)]

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. F98725
A/N 473461**

Equipment Description:

SPRAY BOOTH, RELCO ENGINEERS, 12'-0" W. X 13'-8" L. X 9'-10" H., WITH THIRTY FIVE 20" X 20" PREFILTERS, THIRTY-FIVE 20" X 20" POCKET FILTERS, EIGHT 24" X 24" X 12" HEPA FINAL FILTERS, AND ONE 5 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]
4. GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL ACROSS THE PRE-FILTERS AND THE POCKET FILTERS SHALL NOT EXCEED 1 INCH OF WATER COMBINED, AND THE PRESSURE DIFFERENTIAL ACROSS THE HEPA FINAL FILTERS SHALL NOT EXCEED 1.5 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE HEPA (FINAL) FILTERS USED IN THIS EQUIPMENT SHALL BE INDIVIDUALLY DOP (OR EQUIVALENT) TESTED WITH 0.3 MICRON PARTICLES AND CERTIFIED TO HAVE AN EFFICIENCY OF NOT LESS THAN 99.97%.
[RULE 1303(a)(1)-BACT]
6. THE TOTAL QUANTITY OF POWDER COATING MATERIALS APPLIED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]
8. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER.
[RULE 1401]

Periodic Monitoring:

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
10. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
11. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
 - A. THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
 - B. STACK OR EMISSION POINT IDENTIFICATION;
 - C. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - D. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Emissions and Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. F98727
A/N 473462

Equipment Description:

POWDER COATING BOOTH, 8'-0" W. X 10'-0" L. X 8'-0" H., WITH SIXTEEN 20" X 20" PREFILTERS, SIXTEEN 20" X 20" POCKET FILTERS, SIX 24" X 24" X 12" HEPA FINAL FILTERS AND ONE 3 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH THE THREE-STAGE FILTER SYSTEM.
[RULE 1303(a)(1)-BACT]
4. GAUGES SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL ACROSS THE PRE-FILTERS AND THE POCKET FILTERS SHALL NOT EXCEED 1 INCH OF WATER COMBINED, AND THE PRESSURE DIFFERENTIAL ACROSS THE HEPA FINAL FILTERS SHALL NOT EXCEED 1.5 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE HEPA (FINAL) FILTERS USED IN THIS EQUIPMENT SHALL BE INDIVIDUALLY DOP (OR EQUIVALENT) TESTED WITH 0.3 MICRON PARTICLES AND CERTIFIED TO HAVE AN EFFICIENCY OF NOT LESS THAN 99.97%.
[RULE 1303(a)(1)-BACT]
6. THE TOTAL QUANTITY OF POWDER COATING MATERIALS APPLIED IN THIS EQUIPMENT SHALL NOT EXCEED 500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

7. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]
8. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF MARCH 4, 2005 OR EARLIER.
[RULE 1401]

Periodic Monitoring:

9. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
10. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]
11. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
 - A. THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
 - B. STACK OR EMISSION POINT IDENTIFICATION;
 - C. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - D. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Emissions and Requirements:

12. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G4020
A/N 492529**

Equipment Description:

AEROSOL CAN RECYCLING SYSTEM CONSISTING OF:

1. 55 GALLON (MAXIMUM) RECEIVING DRUM.
2. AEROSOL CAN HOUSING SLEEVE AND PUNCTURE UNIT, AEROSOLV, MODEL NO. 7000.
3. CARBON FILTER UNIT, AEROSOLV, MODEL NO. 28228, WITH COALESCING FILTER AND 1.25 LBS ACTIVATED CARBON.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE CARBON FILTER UNIT SHALL BE REPLACED AFTER PUNCTURING 1000 CANS IN THE DRUM OR WITHIN 45 DAYS AFTER FILTER INSTALLATION ON THE DRUM, WHICH EVER IS SOONER.
[RULE 1303(a)(1)-BACT]
4. THIS EQUIPMENT SHALL ONLY BE USED TO PROCESS SPENT AEROSOL PAINT CANS THAT WERE USED AT THIS FACILITY.
[RULE 1303(a)(1)-BACT]
5. THE AEROSOL PAINT CAN SHALL BE LEFT IN THE CAN HOUSING SLEEVE FOR AT LEAST 30 SECONDS AFTER IT IS PUNCTURED FOR COMPLETE DEPLETION OF SOLVENT INSIDE THE CAN.
[RULE 1303(a)(1)-BACT]
6. THE RECEIVING DRUM SHALL BE REPLACED WITH A NEW DRUM AFTER NO MORE THAN 4,200 CANS ARE PUNCTURED IN THIS EQUIPMENT. THE LIQUID WASTE COLLECTED INSIDE THE DRUM SHALL BE DISPOSED OF AS HAZARDOUS WASTE.
[RULE 1303(b)(2)-OFFSET]
7. THE LAST CAN PUNCTURED WITHIN THE AEROSOL CAN HOUSING SHALL BE LEFT IN THE CAN HOUSING SLEEVE UNTIL PUNCTURING IS RESUMED FOR ANOTHER BATCH OF AEROSOL CANS.
[RULE 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS OF RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THE EQUIPMENT AND FACILITY TO VERIFY THE VOC CONTENT OF EACH MATERIAL AS APPLIED (INCLUDING WATER AND EXEMPT COMPOUNDS), AND THE DAILY VOC EMISSIONS IN POUNDS. ALL RECORDS SHALL BE PREPARED IN A MANNER THAT IS ACCEPTABLE TO THE DISTRICT. RECORDS SHALL BE RETAINED ON THE PREMISES FOR TWO YEARS AND SHALL BE MADE AVAILABLE TO THE EXECUTIVE OFFICER OR HIS REPRESENTATIVE UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET].

9. MATERIAL SAFETY DATA SHEETS FOR ALL MATERIALS USED AT THIS FACILITY SHALL BE KEPT CURRENT AND BE MADE AVAILABLE TO DISTRICT PERSONNEL UPON REQUEST.
[RULE 109, 1303(b)(2)-OFFSET].

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 109
VOC: RULE 442
PM: RULE 401
PM: RULE 402

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7336
A/N 501204**

Equipment Description:

LASER CUTTING SYSTEM NO. 1, BYSTRONIC, ELECTRICALLY POWERED, CONSISTING OF:

1. LASER CUTTING TABLE, DOWNDRAFT TYPE, 12' - 2" W. X 33' - 0" L. X 7' - 5" H.
2. CHILLER, 4' - 10" W. X 3' - 6" L. X 6' - 0" H.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT, WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
- 4) THE MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC/TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE 1, WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER, EXCEPT CHROMIUM & CHROMIUM COMPOUNDS (CAS # 18540-29-9), NICKEL & NICKEL COMPOUNDS (CAS # 7440-02-0), MANGANESE AND MANGANESE COMPOUNDS (CAS # 7439-96-5), LEAD & LEAD COMPOUNDS (CAS # 7439-92-1) AND COPPER & COPPER COMPOUNDS (CAS # 7440-50-8), AS SPECIFIED IN CONDITION NO. 5.
[RULE 1401]
- 5) THE METAL PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN THE FOLLOWING:

A.	CHROMIUM & CHROMIUM COMPOUNDS	30% BY WEIGHT
B.	NICKEL & NICKEL COMPOUNDS	27% BY WEIGHT
C.	COPPER & COPPER COMPOUNDS	6% BY WEIGHT
D.	MANGANESE & MANGANESE COMPOUNDS	6% BY WEIGHT
C.	LEAD & LEAD COMPOUNDS	0.25% BY WEIGHT

[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

- 6) STAINLESS STEEL CONTAINING CHROMIUM & CHROMIUM COMPOUNDS AND NICKEL & NICKEL COMPOUNDS (EXCEEDING 5% BY WEIGHT EACH) PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 10% OF THE TOTAL METAL PROCESSED IN THIS EQUIPMENT ON A MONTHLY BASIS.
[RULE 1303(b)(2)-OFFSETS, 1401]
- 7) THE SHEET METAL THICKNESS PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 0.15".
[RULE 1303(b)(2)-OFFSETS, 1401]
- 8) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTRATE COMPLIANCE WITH THESE PERMIT CONDITIONS.
[RULE 1303(b)(2)-OFFSETS, 1401]
- 9) RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.

Periodic Monitoring:

- 10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING

REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Emissions and Requirements:

- 11) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7337
A/N 501206**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM NO. 1, CONSISTING OF:

1. DUST COLLECTOR, TORRIT, MODEL NO. DFT 3-6, 3' - 4" W. X 4' - 8" D. X 9' - 7" H., WITH 6 CARTRIDGE FILTERS, MODEL TORIT ULTRA-WEB, EACH 1' - 1" DIA. X 2' - 2" L., 1524 SQ. FT. TOTAL FILTER AREA, AND PULSE JET CLEANED.
2. EXHAUST SYSTEM WITH A 10 H.P. BLOWER VENTING A LASER CUTTING SYSTEM # 1.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) DUST COLLECTED IN THIS EQUIPMENT SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]
- 4) A MAGNEHELIC GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 5.0 INCH OF WATER AND SHALL NOT BE LOWER THAN 0.5 INCH OF WATER.
[RULE 1303(a)(1)-BACT, 1401]

Periodic Monitoring:

- 5) THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004 (a)(4)]

- 6) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004 (a)(4)]

Emissions and Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7338
A/N 501208**

Equipment Description:

LASER CUTTING SYSTEM NO. 2, CINCINNATI, MODEL NO. CL-707 CNC, ELECTRICALLY POWERED, CONSISTING OF:

1. LASER CUTTING TABLE, DOWNDRAFT TYPE, 16' - 0" W. X 26' - 10" L. X 7' - 8" H.
2. CHILLER, 2' - 8" W. X 5' - 0" L. X 5' - 5" H.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT, WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
- 4) THE MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC/TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE 1, WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER, EXCEPT CHROMIUM & CHROMIUM COMPOUNDS (CAS # 18540-29-9), NICKEL & NICKEL COMPOUNDS (CAS # 7440-02-0), MANGANESE AND MANGANESE COMPOUNDS (CAS # 7439-96-5), LEAD & LEAD COMPOUNDS (CAS # 7439-92-1) AND COPPER & COPPER COMPOUNDS (CAS # 7440-50-8), AS SPECIFIED IN CONDITION NO. 5.
[RULE 1401]
- 5) THE METAL PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN THE FOLLOWING:

A.	CHROMIUM & CHROMIUM COMPOUNDS	30% BY WEIGHT
B.	NICKEL & NICKEL COMPOUNDS	27% BY WEIGHT
C.	COPPER & COPPER COMPOUNDS	6% BY WEIGHT
D.	MANGANESE & MANGANESE COMPOUNDS	6% BY WEIGHT
C.	LEAD & LEAD COMPOUNDS	0.25% BY WEIGHT

[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

- 6) STAINLESS STEEL CONTAINING CHROMIUM & CHROMIUM COMPOUNDS AND NICKEL & NICKEL COMPOUNDS (EXCEEDING 5% BY WEIGHT EACH) PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 10% OF THE TOTAL METAL PROCESSED IN THIS EQUIPMENT ON A MONTHLY BASIS.
[RULE 1303(b)(2)-OFFSETS, 1401]
- 7) THE SHEET METAL THICKNESS PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 0.15".
[RULE 1303(b)(2)-OFFSETS, 1401]
- 8) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTRATE COMPLIANCE WITH THESE PERMIT CONDITIONS.
[RULE 1303(b)(2)-OFFSETS, 1401]
- 9) RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.

Periodic Monitoring:

- 10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
 - A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
 - D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Emissions and Requirements:

- 11) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7339
A/N 501210**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM NO. 2, CONSISTING OF:

1. DUST COLLECTOR, TORRIT, MODEL NO. DFT 3-12, 3' - 4" W. X 7' - 1" D. X 12' - 0" H., WITH 12 CARTRIDGE FILTERS, MODEL TORIT ULTRA-WEB, EACH 1' - 1" DIA. X 2' - 2" L., 3048 SQ. FT. TOTAL FILTER AREA, AND PULSE JET CLEANED.
2. EXHAUST SYSTEM WITH A 10 H.P. BLOWER VENTING A LASER CUTTING SYSTEM # 2.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) DUST COLLECTED IN THIS EQUIPMENT SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]
- 4) A MAGNEHELIC GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 5.0 INCH OF WATER AND SHALL NOT BE LOWER THAN 0.5 INCH OF WATER.
[RULE 1303(a)(1)-BACT, 1401]

Periodic Monitoring:

- 5) THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004 (a)(4)]

- 6) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004 (a)(4)]

Emissions And Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7340
A/N 501212

Equipment Description:

LASER CUTTING SYSTEM NO. 3, BYSTRONIC, ELECTRICALLY POWERED, CONSISTING OF:

1. LASER CUTTING TABLE, DOWNDRAFT TYPE, 12' - 2" W. X 33' - 0" L. X 7' - 5" H.
2. CHILLER, 4' - 10" W. X 3' - 6" L. X 6' - 0" H.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) THIS EQUIPMENT SHALL NOT BE OPERATED UNLESS IT IS VENTED TO AIR POLLUTION CONTROL EQUIPMENT, WHICH IS IN FULL USE AND WHICH HAS BEEN ISSUED A VALID PERMIT BY THE EXECUTIVE OFFICER.
[RULE 1303(a)(1)-BACT]
- 4) THE MATERIALS PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC/TOXIC COMPOUNDS IDENTIFIED IN RULE 1401, TABLE 1, WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER, EXCEPT CHROMIUM & CHROMIUM COMPOUNDS (CAS # 18540-29-9), NICKEL & NICKEL COMPOUNDS (CAS # 7440-02-0), MANGANESE AND MANGANESE COMPOUNDS (CAS # 7439-96-5), LEAD & LEAD COMPOUNDS (CAS # 7439-92-1) AND COPPER & COPPER COMPOUNDS (CAS # 7440-50-8), AS SPECIFIED IN CONDITION NO. 5.
[RULE 1401]
- 5) THE METAL PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN MORE THAN THE FOLLOWING:

A.	CHROMIUM & CHROMIUM COMPOUNDS	30% BY WEIGHT
B.	NICKEL & NICKEL COMPOUNDS	27% BY WEIGHT
C.	COPPER & COPPER COMPOUNDS	6% BY WEIGHT
D.	MANGANESE & MANGANESE COMPOUNDS	6% BY WEIGHT
C.	LEAD & LEAD COMPOUNDS	0.25% BY WEIGHT

[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

- 6) STAINLESS STEEL CONTAINING CHROMIUM & CHROMIUM COMPOUNDS AND NICKEL & NICKEL COMPOUNDS (EXCEEDING 5% BY WEIGHT EACH) PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 10% OF THE TOTAL METAL PROCESSED IN THIS EQUIPMENT ON A MONTHLY BASIS.
[RULE 1303(b)(2)-OFFSETS, 1401]
- 7) THE SHEET METAL THICKNESS PROCESSED IN THIS EQUIPMENT SHALL NOT EXCEED 0.15".
[RULE 1303(b)(2)-OFFSETS, 1401]
- 8) THE OPERATOR SHALL KEEP ADEQUATE RECORDS TO DEMONSTRATE COMPLIANCE WITH THESE PERMIT CONDITIONS.
[RULE 1303(b)(2)-OFFSETS, 1401]
- 9) RECORDS REQUIRED BY THIS PERMIT SHALL BE PREPARED IN A FORMAT WHICH IS ACCEPTABLE TO THE DISTRICT, SHALL BE RETAINED ON THE PREMISES FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO ANY DISTRICT REPRESENTATIVE UPON REQUEST.

Periodic Monitoring:

- 10) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING

REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Emissions and Requirements:

- 11) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM RULE 405, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7341
A/N 501214**

Equipment Description:

AIR POLLUTION CONTROL SYSTEM NO. 3, CONSISTING OF:

1. DUST COLLECTOR, TORRIT, MODEL NO. DFT 2-4, 3' - 4" W. X 4'- 8" D. X 9' - 7" H., WITH 4 CARTRIDGE FILTERS, MODEL TORIT ULTRA-WEB, EACH 1' - 1" DIA. X 2' - 2" L., 1016 SQ. FT. TOTAL FILTER AREA, AND PULSE JET CLEANED.
2. EXHAUST SYSTEM WITH A 10 H.P. BLOWER VENTING A LASER CUTTING SYSTEM # 3.

Conditions:

- 1) OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
- 2) THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
- 3) DUST COLLECTED IN THIS EQUIPMENT SHALL BE DISCHARGED ONLY INTO CLOSED CONTAINERS.
[RULE 1303(a)(1)-BACT]
- 4) A MAGNEHELIC GAUGE SHALL BE INSTALLED AND MAINTAINED SO AS TO INDICATE IN INCHES WATER COLUMN, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 5.0 INCH OF WATER AND SHALL NOT BE LOWER THAN 0.5 INCH OF WATER.
[RULE 1303(a)(1)-BACT, 1401]

Periodic Monitoring:

- 5) THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.

[RULE 3004 (a)(4)]

- 6) THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

D. STACK OR EMISSION POINT IDENTIFICATION;

E. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND

F. DATE AND TIME VISIBLE EMISSION WAS ABATED.

[RULE 3004 (a)(4)]

Emissions and Requirements:

- 7) THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7349
A/N 500473**

Equipment Description:

SPRAY BOOTH NO. 1, NORDSON, MODEL CK-7200, 14'-4" W. X 10'-6" L. X 10'-10" H., WITH EXHAUST FILTERS CONSISTING OF EIGHT 3'-0" L. X 1'-0" DIA. PRIMARY CARTRIDGE FILTERS AND FOUR 1'-8" W. X 2'-0" L. SECONDARY BOX-TYPE FILTERS AND ONE 5 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS THE PRIMARY FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]
5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]
6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]
7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 1,500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF JUNE 5, 2009, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
- [RULE 3004 (a)(4)]
12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
- THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
- [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7350
A/N 500474**

Equipment Description:

SPRAY BOOTH NO. 2, NORDSON, MODEL CK-7200, 14'-4" W. X 10'-6" L. X 10'-10" H., WITH EXHAUST FILTERS CONSISTING OF EIGHT 3'-0" L. X 1'-0" DIA. PRIMARY CARTRIDGE FILTERS AND FOUR 1'-8" W. X 2'-0" L. SECONDARY BOX-TYPE FILTERS AND ONE 5 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. A GAUGE SHALL BE INSTALLED TO INDICATE, IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 2.0 INCHES OF WATER ACROSS THE PRIMARY FILTERS AND 1.5 INCHES OF WATER ACROSS THE FINAL FILTERS.
[RULE 1303(a)(1)-BACT]
5. CLEAN-UP MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY VOLATILE ORGANIC COMPOUND (VOC).
[RULE 1303(a)(1)-BACT]
6. NO WET COATINGS SHALL BE APPLIED IN THIS EQUIPMENT.
[RULE 1303(a)(1)-BACT]
7. THE TOTAL QUANTITY OF POWDER COATING USED IN THIS EQUIPMENT SHALL NOT EXCEED 1,500 POUNDS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
8. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE MONTHLY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

9. POWDER COATINGS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS TOXIC AIR CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF JUNE 5, 2009, OR EARLIER.
[RULE 1401]

Periodic Monitoring:

10. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
11. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
- A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.
- [RULE 3004 (a)(4)]
12. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON A QUARTERLY BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE QUARTERLY PERIOD. THE ROUTINE QUARTERLY INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED.
- [RULE 3004 (a)(4)]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Emissions and Requirements:

13. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7351
A/N 500475**

Equipment Description:

SIX STAGE WASHER, INDUSTRIAL PROCESS EQUIPMENT, INC, MODEL 5707-W, 68'-0" L. X 7'-0" W. X 13'-6" H., CONSISTING OF:

1. ONE HEATED PHOSPHATE SPRAY SYSTEM WITH ONE HUNDRED SIXTY SPRAY NOZZLES, ONE 10 H.P. SPRAY TANK, ONE 1,148 GALLONS TANK, WITH ONE 2,000,000 BTU/HOUR ECLIPSE IJ-6 NATURAL GAS FIRED BURNER.
2. ONE HEATED PHOSPHATE SPRAY SYSTEM WITH ONE HUNDRED SIXTY SPRAY NOZZLES, ONE 10 H.P. SPRAY TANK, ONE 1,148 GALLONS TANK, WITH ONE 2,000,000 BTU/HOUR ECLIPSE IJ-6 NATURAL GAS FIRED BURNER.
3. ONE WATER RINSE SPRAY SYSTEM WITH NINETY-SIX SPRAY NOZZLES, ONE 7-1/2 H.P. SPRAY PUMP, ONE 623 GALLONS TANK.
4. ONE PURE WATER RINSE SPRAY SYSTEM WITH NINETY-SIX SPRAY NOZZLES, ONE 7-1/2 H.P. SPRAY PUMP, ONE 623 GALLONS TANK.
5. ONE NON-CHROME SEAL SPRAY SYSTEM WITH FORTY-EIGHT SPRAY NOZZLES, ONE 1 H.P. SPRAY PUMP, ONE 374 GALLONS TANK
6. ONE DEIONIZED WATER RINSE SPRAY SYSTEM WITH FORTY-EIGHT SPRAY NOZZLES, ONE 1 H.P. SPRAY PUMP, ONE 374 GALLONS TANK.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE BURNER IN THIS EQUIPMENT SHALL NOT USE MORE THAN 23,077 CUBIC FEET OF NATURAL GAS IN ANY ONE DAY.
[RULE 1303(b)(2)-OFFSET]
4. A NON-RESETTABLE TOTALIZING FUEL METER SHALL BE INSTALLED AND MAINTAINED TO VERIFY COMPLIANCE WITH THE DAILY NATURAL GAS USAGE LIMIT.
[RULE 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

5. THE OPERATOR SHALL MAINTAIN A NATURAL GAS CONSUMPTION LOG TO VERIFY COMPLIANCE WITH THE NATURAL GAS USAGE LIMIT. THE LOG SHALL INCLUDE, AT A MINIMUM, THE DATE OF OPERATION OF THIS EQUIPMENT, THE GAS METER READING AT THE BEGINNING OF EACH DAY BEFORE THE EQUIPMENT IS OPERATED, AND AT THE END OF EACH DAY AFTER THE EQUIPMENT IS SHUT DOWN.
[RULE 109, 1303(b)(2)-OFFSET]

6. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY TOXIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF JUNE 5, 2009. OR EARLIER.
[RULE 1401]

Periodic Monitoring:

Emissions and Requirements:

7. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7352
A/N 500476

Equipment Description:

POWDER COATING DRYING OVEN, INDUSTRIAL PROCESS EQUIPMENT, INC, MODEL 5707-DO, 14'-7" W. X 23'-7" L. X 13'-11" H., 1,000,000 BTU/HR ECLIPSE WX0100 WINNOX LOW NO_x DIRECT NATURAL GAS FIRED BURNER, WITH ONE 1.5 H.P. COMBUSTION AIR FAN, ONE 1.5 H.P. EXHAUST FAN AND ONE 10 H.P. RECIRCULATION FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURE ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]
4. THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO_x, BY VOLUME ON A DRY BASIS @ 3% O₂, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED ON THE ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER.
[RULE 1401]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
 - D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
- [RULE 3004 (a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NO_x: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

Permit No. G7353
A/N 500477

Equipment Description:

~~POWDER COATING~~ CURING OVEN, INDUSTRIAL PROCESS EQUIPMENT, INC, MODEL 5707-CO, 17'-3" W. X 43'-0" L. X 13'-8" H., 4,000,000 BTU/HR ECLIPSE WX0400 WINNOX LOW NO_x DIRECT NATURAL GAS FIRED BURNER, WITH ONE 5 H.P. COMBUSTION AIR FAN, ONE 3 H.P. EXHAUST FAN AND TWO 25 H.P. RECIRCULATION FANS

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]
4. THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO_x, BY VOLUME ON A DRY BASIS @ 3% O₂, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)-BACT]
5. MATERIALS USED ON THE ARTICLES PROCESSED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY CARCINOGENIC AIR CONTAMINANTS IDENTIFIED IN RULE 1401, TABLE I WITH AN EFFECTIVE DATE OF JUNE 5, 2009 OR EARLIER.
[RULE 1401]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY POWDER COATING USAGE IN POUNDS, THE VOC CONTENT OF LIQUID COATINGS IN POUNDS OF VOC PER GALLON OF MATERIAL AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS, AND THE DAILY VOC EMISSIONS IN POUNDS. THE VOC EMISSIONS FROM THE USE OF POWDER COATINGS SHALL BE CALCULATED USING THE EMISSION FACTOR DETERMINED PURSUANT TO SCAQMD METHOD 316C. IN CASE NO LABORATORY TESTED EMISSION FACTOR IS AVAILABLE, THEN A FACTOR OF 0.01 POUNDS OF VOC PER POUND OF POWDER SPRAYED SHALL BE USED.
[RULE 109, 1303(b)(2)-OFFSET]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

7. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
- A. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - B. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - C. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
 - B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
 - C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
 - D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
- [RULE 3004 (a)(4)]

Emissions and Requirements:

8. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NO_x: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7354
A/N 503450**

Equipment Description:

OVEN, CURING, RAMCO, 8'-0" W. X 9'-0" D. X 8'-0" H., 800,000 BTU/HR NATURAL GAS FIRED, WITH A MAXON CYCLOMAX LOW NO_x BURNER, A 1/2 H.P. COMBUSTION AIR FAN, A 1/2 H.P. EXHAUST FAN AND A 7-1/2 RECIRCULATION FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THE OXIDES OF NITROGEN (NO_x) EMISSIONS DISCHARGED FROM THIS EQUIPMENT SHALL NOT EXCEED 30 PPM, CALCULATED AS NO_x, BY VOLUME ON A DRY BASIS @ 3% O₂, AVERAGED OVER 15 CONSECUTIVE MINUTES.
[RULE 1303(a)(1)BACT]

Periodic Monitoring:

4. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED THAT LAST MORE THAN THREE MINUTES IN ANY ONE-HOUR, THE OPERATOR SHALL EITHER:
 - D. VERIFY AND CERTIFY WITHIN 24 HOURS THAT THE EQUIPMENT CAUSING THE EMISSION AND ANY ASSOCIATED AIR POLLUTION CONTROL EQUIPMENT ARE OPERATING NORMALLY ACCORDING TO THEIR DESIGN AND STANDARD PROCEDURES AND UNDER THE SAME CONDITIONS UNDER WHICH COMPLIANCE WAS ACHIEVED IN THE PAST;
 - E. TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT; OR
 - F. HAVE A CARB-CERTIFIED SMOKE READER DETERMINE COMPLIANCE WITH THE OPACITY STANDARD, USING EPA METHOD 9 OR THE PROCEDURES IN THE CARB MANUAL "VISIBLE EMISSION EVALUATION", WITHIN THREE BUSINESS DAYS AND REPORT ANY DEVIATIONS TO AQMD.

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:

- A. STACK OR EMISSION POINT IDENTIFICATION;
- B. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS;
- C. DATE AND TIME VISIBLE EMISSION WAS ABATED; AND
- D. VISIBLE EMISSION OBSERVATION RECORDED BY A CERTIFIED SMOKE READER.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 407
NOx: 30 PPMV, RULE 1303(a)(1)-BACT
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO OPERATE

**Permit No. G7355
A/N 503451**

Equipment Description:

OVEN, RAMCO, MODEL 10-10-8, 10'-0" W. X 7'-6" L. X 8'-6" H., 800,000 BTU/HR NATURAL GAS FIRED, WITH ONE 1/3 H.P. COMBUSTION AIR BLOWER, ONE 7 1/2 H.P. CIRCULATING FAN, AND ONE 2 H.P. EXHAUST FAN.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS OVEN SHALL NOT BE OPERATED AT TEMPERATURES ABOVE 450 DEGREES FAHRENHEIT.
[RULE 401]

Periodic Monitoring:

4. THE OPERATOR SHALL INSTALL AND MAINTAIN A TEMPERATURE READING DEVICE TO ACCURATELY INDICATE THE TEMPERATURE OF THE OVEN. THE OPERATOR SHALL ALSO DETERMINE AND RECORD THE TEMPERATURE OF THE OVEN ONCE EVERY DAY.
[RULE 3004 (a)(4)]

Emissions and Requirements:

5. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATION:

CO: 2000 PPMV, RULE 407
PM: 0.1 GR/SCF, RULE 409
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO CONSTRUCT

**A/N 518877
Granted as of
April 12, 2011**

Equipment Description:

SPRAY BOOTH L-13, CONVEYORIZED, INDUSTRIAL PROCESS EQUIPMENT, 20'-8" W. x 15'-5" D. x 10'-0" H., WITH TWENTY-FIVE 20" x 20" EXHAUST FILTERS AND TWO 3 HP EXHAUST FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THE TWO SPRAY BOOTHS UNDER A/Ns 518877 & 518878 COMBINED SHALL NOT EXCEED 850 POUNDS IN ANY CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY AND CALENDAR MONTHLY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH COATING IN POUNDS PER GALLON OF MATERIAL AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET]
7. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

PERMIT TO CONSTRUCT

A/N 518878
Granted as of
April 12, 2011

Equipment Description:

SPRAY BOOTH L-15, CONVEYORIZED, INDUSTRIAL PROCESS EQUIPMENT, 20'-8" W. x 15'-5" D. x 10'-0" H., WITH TWENTY-FIVE 20" x 20" FILTERS AND TWO 3 HP EXHAUST FANS.

Conditions:

1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN COMPLIANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
[RULE 204]
2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
[RULE 204]
3. THIS SPRAY BOOTH SHALL NOT BE OPERATED UNLESS ALL EXHAUST AIR PASSES THROUGH FILTER MEDIA AT LEAST 2 INCHES THICK.
[RULE 1303(a)(1)-BACT]
4. A GAUGE SHALL BE INSTALLED TO INDICATE IN INCHES OF WATER, THE STATIC PRESSURE DIFFERENTIAL ACROSS THE EXHAUST FILTERS. IN OPERATION, THE PRESSURE DIFFERENTIAL SHALL NOT EXCEED 0.25 INCHES OF WATER.
[RULE 1303(a)(1)-BACT]
5. THE TOTAL QUANTITY OF VOLATILE ORGANIC COMPOUND (VOC) EMISSIONS FROM THE TWO SPRAY BOOTHS UNDER A/Ns 518877 & 518878 COMBINED SHALL NOT EXCEED 850 POUNDS IN ANY CALENDAR MONTH.
[RULE 1303(b)(2)-OFFSET]
6. IN ADDITION TO THE RECORDKEEPING REQUIREMENTS IN RULE 109, THE OPERATOR SHALL KEEP ADEQUATE RECORDS FOR THIS EQUIPMENT TO VERIFY THE DAILY AND CALENDAR MONTHLY VOC EMISSIONS IN POUNDS AND THE VOC CONTENT OF EACH COATING IN POUNDS PER GALLON OF MATERIAL AS APPLIED, INCLUDING WATER AND EXEMPT COMPOUNDS.
[RULE 109, 1303(b)(2)-OFFSET]
7. MATERIALS USED IN THIS EQUIPMENT SHALL NOT CONTAIN ANY COMPOUNDS IDENTIFIED AS CARCINOGENIC CONTAMINANTS IN RULE 1401, TABLE I, WITH AN EFFECTIVE DATE OF DECEMBER 7, 1990 OR EARLIER.
[RULE 1401]

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

Periodic Monitoring:

8. THE OPERATOR SHALL DETERMINE AND RECORD THE PRESSURE DROP ACROSS THE FILTER ONCE EVERY WEEK.
[RULE 3004 (a)(4)]
9. THE OPERATOR SHALL PERFORM A WEEKLY INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - A. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - B. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - C. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

Emissions and Requirements:

10. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 109
PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 481

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS.

Periodic Monitoring:

1. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):

FOR ARCHITECTURAL APPLICATIONS WHERE NO THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN SEMI-ANNUAL RECORDS OF ALL COATINGS CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS SUPPLIED IN GRAMS PER LITER (g/l) OF MATERIALS FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS SUPPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.

FOR OTHER ARCHITECTURAL APPLICATIONS WHERE THINNERS, REDUCERS, OR OTHER VOC CONTAINING MATERIALS ARE ADDED, MAINTAIN DAILY RECORDS FOR EACH COATING CONSISTING OF (a) COATING TYPE, (b) VOC CONTENT AS APPLIED IN GRAMS PER LITER (g/l) OF MATERIALS USED FOR LOW-SOLIDS COATINGS, AND (c) VOC CONTENT AS APPLIED IN g/l OF COATING, LESS WATER AND EXEMPT SOLVENT, FOR OTHER COATING.
[RULE 3004(a)(4)]

Emissions And Requirements:

2. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1113, SEE APPENDIX B FOR EMISSION LIMITS
VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, HAND WIPING OPERATIONS.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS

Emissions and Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1145, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1107, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 109

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, PRINTING EQUIPMENT, LOW USE OR EMISSIONS, WITH RELATED COATING, LAMINATING AND DRYING EQUIPMENT.

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

VOC: RULE 1130.1, SEE APPENDIX B FOR EMISSION LIMITS

VOC: RULE 1171, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, GLOVE-BOX, < 53 FT3, WITH DUST FILTER.

Periodic Monitoring:

1. THE OPERATOR SHALL PERFORM AN ANNUAL INSPECTION OF THE EQUIPMENT AND FILTER MEDIA FOR LEAKS, BROKEN OR TORN FILTER MEDIA AND IMPROPERLY INSTALLED FILTER MEDIA. THE OPERATOR SHALL KEEP RECORDS, IN A MANNER APPROVED BY THE DISTRICT, FOR THE FOLLOWING PARAMETER(S) OR ITEM(S):
 - D. THE NAME OF THE PERSON PERFORMING THE INSPECTION AND/OR MAINTENANCE OF THE FILTER MEDIA;
 - E. THE DATE, TIME AND RESULTS OF THE INSPECTION; AND
 - F. THE DATE, TIME AND DESCRIPTION OF ANY MAINTENANCE OR REPAIRS RESULTING FROM THE INSPECTION.[RULE 3004 (a)(4)]

2. THE OPERATOR SHALL DISCHARGE DUST COLLECTED IN THIS EQUIPMENT ONLY INTO CLOSED CONTAINERS.
[RULE 3004 (a)(4)]

3. THE OPERATOR SHALL CONDUCT AN INSPECTION FOR VISIBLE EMISSIONS FROM ALL STACKS AND OTHER EMISSION POINTS OF THIS EQUIPMENT WHENEVER THERE IS A PUBLIC COMPLAINT OF VISIBLE EMISSIONS, WHENEVER VISIBLE EMISSIONS ARE OBSERVED, AND ON AN ANNUAL BASIS, AT LEAST, UNLESS THE EQUIPMENT DID NOT OPERATE DURING THE ENTIRE ANNUAL PERIOD. THE ROUTINE ANNUAL INSPECTION SHALL BE CONDUCTED WHILE THE EQUIPMENT IS IN OPERATION AND DURING DAYLIGHT HOURS. IF ANY VISIBLE EMISSIONS (NOT INCLUDING CONDENSED WATER VAPOR) ARE DETECTED, THE OPERATOR SHALL TAKE CORRECTIVE ACTION(S) THAT ELIMINATES THE VISIBLE EMISSIONS WITHIN 24 HOURS AND REPORT THE VISIBLE EMISSIONS AS A POTENTIAL DEVIATION IN ACCORDANCE WITH THE REPORTING REQUIREMENTS IN SECTION K OF THIS PERMIT.
THE OPERATOR SHALL KEEP THE RECORDS IN ACCORDANCE WITH THE RECORDKEEPING REQUIREMENTS IN SECTION K OF THIS PERMIT AND THE FOLLOWING RECORDS:
 - G. STACK OR EMISSION POINT IDENTIFICATION;
 - H. DESCRIPTION OF ANY CORRECTIVE ACTIONS TAKEN TO ABATE VISIBLE EMISSIONS; AND
 - I. DATE AND TIME VISIBLE EMISSION WAS ABATED.[RULE 3004 (a)(4)]

Emissions And Requirements:

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

4. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 405, SEE APPENDIX B FOR EMISSION LIMITS
PM: RULE 1140, SEE APPENDIX B FOR EMISSION LIMITS

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

REFRIGERANT: RULE 1415

FACILITY PERMIT TO OPERATE AMF ANAHEIM LLC

RULE 219 EQUIPMENT

Equipment Description:

RULE 219 EXEMPT EQUIPMENT, COOLING TOWERS

Emissions And Requirements:

1. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CR⁺⁶: RULE 1404