SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT
21865 Copley Drive, Diamond Bar, CA 91765

| | |
|---|---|
| Title Page | |
| Facility ID: | 135729 |
| Revision #: | 3 |
| Date: | July 26, 2011 |

# FACILITY PERMIT TO OPERATE

## CALIFORNIA SPECIALTY PAINTING
## 12236 COAST DR
## WHITTIER, CA 90601

## NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By Ed Mechlberger for
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## TABLE OF CONTENTS


| Section | Description | Revision # | Date Issued |
|---|---|---|---|
| A | Facility Information | 2 | 07/26/2011 |
| B | RECLAIM Annual Emission Allocation | 2 | 07/26/2011 |
| C | Facility Plot Plan | TO BE DEVELOPED | |
| D | Facility Description and Equipment Specific Conditions | 3 | 07/26/2011 |
| E | Administrative Conditions | 2 | 07/26/2011 |
| F | RECLAIM Monitoring and Source Testing Requirements | 2 | 07/26/2011 |
| G | Recordkeeping and Reporting Requirements for RECLAIM Sources | 2 | 07/26/2011 |
| H | Permit To Construct and Temporary Permit to Operate | 2 | 07/26/2011 |
| I | Compliance Plans & Schedules | 2 | 07/26/2011 |
| J | Air Toxics | 2 | 07/26/2011 |
| K | Title V Administration | 2 | 07/26/2011 |
| Appendix | | | |
| A | NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219 | 2 | 07/26/2011 |
| B | Rule Emission Limits | 2 | 07/26/2011 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION A: FACILITY INFORMATION

| | |
|---|---|
| **LEGAL OWNER &/OR OPERATOR:** | CALIFORNIA SPECIALTY PAINTING |
| **LEGAL OPERATOR (if different than owner):** | |
| **EQUIPMENT LOCATION:** | 12236 COAST DR<br>WHITTIER, CA 90601-1607 |
| **MAILING ADDRESS:** | 12236 COAST DR<br>WHITTIER, CA 90601-1607 |
| **RESPONSIBLE OFFICIAL:** | GEORGE GILBERT |
| **TITLE:** | GENERAL MANAGER |
| **TELEPHONE NUMBER:** | (562) 699-5877 |
| **CONTACT PERSON:** | GEORGE GILBERT |
| **TITLE:** | GENERAL MANAGER |
| **TELEPHONE NUMBER:** | (562) 699-5877 |
| **TITLE V PERMIT ISSUED:** | July 26, 2011 |
| **TITLE V PERMIT EXPIRATION DATE:** | July 25, 2016 |

| TITLE V | RECLAIM | |
|---|---|---|
| YES | NOx: | NO |
| | SOx: | NO |
| | CYCLE: | 0 |
| | ZONE: | INLAND |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

NOT APPLICABLE

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|---|---|---|---|---|
| **Process 1: COATING** | | | | | |
| SPRAY COATING OPERATION, NO. 3, FLOOR TYPE WITH TWENTY 20 IN X 25 IN EXHAUST FILTERS, 12 FT. W. X 10 FT- 4 IN. L. X 8 FT. H., 2 HP EXHAUST FAN, WITH SPRAY BOOTH<br>A/N: 412995 | D4 | | | **PM**: (9) [**RULE 404, 2-7-1986**]; **VOC**: (9) [**RULE 1107, 11-9-2001;** *RULE 1107, 1-6-2006;* **RULE 1145, 2-14-1997;** *RULE 1145, 12-4-2009;* **RULE 1171, 11-7-2003;** *RULE 1171, 5-1-2009*] | A63.1, B27.1, C6.1, D322.1, E175.1, H23.1, K67.3, K67.4 |
| SPRAY COATING OPERATION, NO. 4, FLOOR TYPE, WITH TWENTY 20 IN X 25 IN EXHAUST FILTERS, 12 FT. W. X 10 FT - 4 IN L. X 8 FT. H., 2 HP EXHAUST FAN, WITH SPRAY BOOTH<br>A/N: 412985 | D5 | | | **PM**: (9) [**RULE 404, 2-7-1986**]; **VOC**: (9) [**RULE 1107, 11-9-2001;** *RULE 1107, 1-6-2006;* **RULE 1145, 2-14-1997;** *RULE 1145, 12-4-2009;* **RULE 1171, 11-7-2003;** *RULE 1171, 5-1-2009*] | A63.1, B27.1, C6.1, D322.1, E175.1, H23.1, K67.3, K67.4 |
| SPRAY COATING OPERATION, NO. 5, FLOOR TYPE, WITH TWENTY 20 IN X 25 IN EXHAUST FILTERS, 12 FT. W. X 10 FT - 4 IN L. X 8 FT. H., 2 HP EXHAUST FAN, WITH SPRAY BOOTH<br>A/N: 412980 | D6 | | | **HAP**: (10) [**40CFR 63 Subpart JJ, 12-28-1998**]; **PM**: (9) [**RULE 404, 2-7-1986**]; **VOC**: (9) [**RULE 1107, 11-9-2001;** *RULE 1107, 1-6-2006;* **RULE 1136, 6-14-1996; RULE 1145, 2-14-1997;** *RULE 1145, 12-4-2009;* **RULE 1171, 11-7-2003;** *RULE 1171, 5-1-2009*] | A63.1, B27.1, C6.1, D322.1, E175.1, H23.1, K67.3, K67.4 |
| SPRAY COATING OPERATION, NO. 2, FLOOR TYPE, 30 FT W. X 7 FT L. X 11 FT H., WITH TWO PLENUMS,, SIXTY-FOUR 20" X 25" TOTAL EXHAUST FILTERS, 2 @5 HP EXHAUST FANS & 2 MANOMETERS, WITH SPRAY BOOTH<br>A/N: 451000 | D8 | | | **PM**: (9) [**RULE 404, 2-7-1986**]; **VOC**: (9) [**RULE 1107, 11-9-2001;** *RULE 1107, 1-6-2006;* **RULE 1124, 9-21-2001; RULE 1145, 2-14-1997;** *RULE 1145, 12-4-2009;* **RULE 1171, 11-7-2003;** *RULE 1171, 5-1-2009*] | A63.1, B27.1, C6.1, D322.1, E71.1, E175.1, H23.1, K67.3, K67.4 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
(2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|---|---|---|---|---|
| **Process 1: COATING** | | | | | |
| SPRAY COATING OPERATION, NO. 1, FLOOR TYPE, 14 FT. W. X 16 FT. L. X 9 FT. H., WITH SIXTEEN 20 IN. X 20 IN. EXHAUST FILTERS & 3 HP EXHAUST FAN, WITH SPRAY BOOTH<br>A/N: 518863 | D13 | | | **PM**: (9) [**RULE 404, 2-7-1986**]; **VOC**: (9) [**RULE 1107, 11-9-2001;** *RULE 1107, 1-6-2006;* **RULE 1124, 9-21-2001; RULE 1145, 2-14-1997;** *RULE 1145, 12-4-2009;* **RULE 1171, 11-7-2003;** *RULE 1171, 5-1-2009*] | A63.2, B27.1, C6.1, D322.1, E175.1, H23.1, K67.3, K67.4 |
| **Process 3: 219 EXEMPT EQUIPMENT SUBJECT TO SOURCE SPECIFIC RULES** | | | | | |
| RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS | E11 | | | **VOC**: (9) [**RULE 1113, 11-8-1996;** *RULE 1113, 6-3-2011;* **RULE 1171, 11-7-2003;** *RULE 1171, 5-1-2009*] | K67.2 |
| RULE 219 EXEMPT EQUIPMENT, EXEMPT HAND WIPING OPERATIONS | E12 | | | **VOC**: (9) [**RULE 1171, 11-7-2003;** *RULE 1171, 5-1-2009*] | H23.2 |

* (1) (1A) (1B) Denotes RECLAIM emission factor
(2) (2A) (2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5) (5A) (5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8) (8A) (8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See section J for NESHAP/MACT requirements

** Refer to section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: DEVICE ID INDEX

**The following sub-section provides an index to the devices that make up the facility description sorted by device ID.**

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: DEVICE ID INDEX

| Device Index For Section D | | | |
|---|---|---|---|
| **Device ID** | **Section D Page No.** | **Process** | **System** |
| D4 | 1 | 1 | 0 |
| D5 | 1 | 1 | 0 |
| D6 | 1 | 1 | 0 |
| D8 | 1 | 1 | 0 |
| E11 | 2 | 3 | 0 |
| E12 | 2 | 3 | 0 |
| D13 | 2 | 1 | 0 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

### FACILITY CONDITIONS

F2.1 The operator shall limit emissions from this facility as follows:

| CONTAMINANT | EMISSIONS LIMIT |
|---|---|
| VOC | Less than or equal to 128 LBS IN ANY ONE DAY |

The operator shall maintain records in a manner approved by the District for five years and make all records available to any District Personnel upon request.

Keep records of VOC emissions from this facility in lb/day.

Records of Material Safety Data Sheets for all coatings and solvents used at this facility shall be kept current and made available to District Personnel upon request.

[**RULE 109, 5-2-2003; RULE 1303(b)(2)-Offset, 5-10-1996;** RULE 1303(b)(2)-Offset, 12-6-2002]

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[**RULE 401, 3-2-1984;** RULE 401, 11-9-2001]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

### DEVICE CONDITIONS

### A. Emission Limits

A63.1 The operator shall limit emissions from this equipment as follows:

| CONTAMINANT | EMISSIONS LIMIT |
|---|---|
| VOC | Less than or equal to 52 LBS IN ANY ONE DAY |

[**RULE 1303(b)(2)-Offset, 5-10-1996;** RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D4, D5, D6, D8]

A63.2 The operator shall limit emissions from this equipment as follows:

| CONTAMINANT | EMISSIONS LIMIT |
|---|---|
| VOC | Less than or equal to 39 LBS IN ANY ONE DAY |

[**RULE 1303(b)(2)-Offset, 5-10-1996;** RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D13]

### B. Material/Fuel Type Limits

B27.1 The operator shall not use materials containing any compounds identified in the SCAQMD Rule 1401, as amended 07-dec-1990.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D4, D5, D6, D8, D13]

### C. Throughput or Operating Parameter Limits

C6.1 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 0.25 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the exhaust filters.

The operator shall record the parameter being monitored once every 7 days.

[**RULE 1303(a)(1)-BACT, 5-10-1996;** RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D4, D5, D6, D8, D13]

### D. Monitoring/Testing Requirements

D322.1 The operator shall perform a weekly inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : D4, D5, D6, D8, D13]

### E. Equipment Operation/Construction Requirements

E71.1 The operator shall only spray coat articles in this equipment if both exhaust fans are in operation.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

[**RULE 1303(a)(1)-BACT, 5-10-1996;** RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D8]

E175.1 The operator shall not use this equipment unless all exhaust air passes through the following:

filter media at least 2 inches thick

[**RULE 1303(a)(1)-BACT, 5-10-1996;** RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D4, D5, D6, D8, D13]

### H. Applicable Rules

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|---|---|---|
| VOC | District Rule | 109 |
| PM | District Rule | 481 |

[**RULE 109, 5-2-2003; RULE 481, 1-11-2002**]

[Devices subject to this condition : D4, D5, D6, D8, D13]

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|---|---|---|

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

| VOC | District Rule | 109 |
|---|---|---|

[**RULE 109, 5-2-2003**]

[Devices subject to this condition : E12]

### K. Record Keeping/Reporting

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : E11]

K67.3 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

**The operator shall comply with the terms and conditions set forth below:**

Name of the person conducting inspection and maintenance of the filter media.

Date, time and results of inspection.

Date, time and description of repairs made.

[**RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : D4, D5, D6, D8, D13]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

VOC emissions for this equipment in lbs/day and VOC content as applied, including water and exempt solvents of all coatings and solvents.

[**RULE 1303(b)(2)-Offset, 5-10-1996;** RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D4, D5, D6, D8, D13]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
   a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
   b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
   c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statues of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]

6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]

7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]

   a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]

   b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]

   c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]

   d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO2) and be averaged over 15 consecutive minutes; [407]

   e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO2) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION E: ADMINISTRATIVE CONDITIONS

f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O2) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]

8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]

a. Brief description of the equipment tested.

b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.

c. Operating conditions under which the test will be performed.

d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).

e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.

f. Description of calibration and quality assurance procedures.

g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).

9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]

a. The results of the source test.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION E: ADMINISTRATIVE CONDITIONS

b. Brief description of the equipment tested.

c. Operating conditions under which the test was performed.

d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).

e. Field and laboratory data forms, strip charts and analyses.

f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.

10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]

11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

NOT APPLICABLE

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR RECLAIM SOURCES

**NOT APPLICABLE**

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

NONE

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION J: AIR TOXICS
## [40CFR 63 Subpart JJ 12-28-1998]

Emission Limits

| SUMMARY OF EMISSION LIMITS | Existing Sources lb VHAP per lb solids | New Sources lb VHAP per lb solids |
|---|---|---|
| **Finishing Materials: Maximum as applied VHAP Content** | | |
| Stains | 1.0 | 1.0 |
| Washcoats, basecoats and enamels | 1.0 [(a)] | 0.8 [(a)] |
| Sealers and topcoats | 1.0 | 0.8 |
| **Contact Adhesives: Maximum as applied VHAP Content** | | |
| • Aerosol adhesives | no limit | no limit |
| • Contact adhesives applied to non-porous substrates | no limit | no limit |
| • Foam adhesives used in products that must meet regulated flammability requirements | 1.8 | 0.2 |
| • All other contact adhesive uses | 1.0 | 0.2 |

| SUMMARY OF EMISSION LIMITS | Existing Sources | New Sources |
|---|---|---|
| • [(a)] **Thinners** added to washcoats, basecoats and enamels Maximum allowable weight % of HAP | 3.0 | 3.0 |
| • **Solvent & thinner mixtures** used for other purposes Maximum allowable weight % of HAP | 10.0 | 10.0 |
| • **Strippable spray booth materials** Maximum VOC content, lb VOC / lb solids | 0.8 | 0.8 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION J: AIR TOXICS
## [40CFR 63 Subpart JJ 12-28-1998]

General Requirements

1. The operator shall comply with all applicable NESHAP requirements of Subpart JJ - National Emission Standards for Wood Furniture Manufacturing Operations, of Subpart A - General Provisions, and of any other applicable subpart by the date(s) specified in these subparts.
2. The operator shall keep records in a format which is acceptable to the District to demonstrate compliance with all applicable requirements of this subpart and Subpart A, including material VHAP (Volatile Hazardous Air Pollutant) content, work practice standards, notifications and compliance reports.
3. The operator shall keep current all Certified Product Data Sheets (CPDS) for all materials used at the facility.
4. The operator shall keep all records for at least five years, and make them available to District personnel upon request. At a minimum, the most recent 2 years of data shall be retained on-site. The remaining 3 years of data may be retained off-site.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

**GENERAL PROVISIONS**

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]

2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

**Permit Renewal and Expiration**

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

   (B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]

4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

**Duty to Provide Information**

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

**Payment of Fees**

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

**Reopening for Cause**

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:

   (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.

   (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.

   (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

**COMPLIANCE PROVISIONS**

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:

   (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or

   (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

   Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:

   (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;

   (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;

   (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and

   (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]

15. Nothing in this permit or in any permit shield can alter or affect:

    (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;

    (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;

    (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;

    (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;

    (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and

    (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]

16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

**EMERGENCY PROVISIONS**

17. An emergency[1] constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:

    (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:

        (1) An emergency occurred and the operator can identify the cause(s) of the emergency;

        (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;

        (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,

        (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and

    (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]

18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

---

1 "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

**RECORDKEEPING PROVISIONS**

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:

    (A) The date, place as defined in the Title V permit, and time of sampling or measurements;

    (B) The date(s) analyses were performed;

    (C) The company or entity that performed the analyses;

    (D) The analytical techniques or methods used;

    (E) The results of such analyses; and

    (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]

20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]

21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

**REPORTING PROVISIONS**

22. The operator shall comply with the following requirements for prompt reporting of deviations:

    (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

(B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.

(C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.

(D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]

23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]

24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:

(A) Identification of each permit term or condition that is the basis of the certification;

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

(B) The compliance status during the reporting period;

(C) Whether compliance was continuous or intermittent;

(D) The method(s) used to determine compliance over the reporting period and currently, and

(E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

**PERIODIC MONITORING**

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

*FACILITY RULES*

*This facility is subject to the following rules and regulations*

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

| RULE SOURCE | Adopted/Amended Date | FEDERAL Enforceability |
|---|---|---|
| RULE 109 | 5-2-2003 | Federally enforceable |
| RULE 1107 | 1-6-2006 | Non federally enforceable |
| RULE 1107 | 11-9-2001 | Federally enforceable |
| RULE 1113 | 11-8-1996 | Federally enforceable |
| RULE 1113 | 6-3-2011 | Non federally enforceable |
| RULE 1124 | 9-21-2001 | Federally enforceable |
| RULE 1136 | 6-14-1996 | Federally enforceable |
| RULE 1145 | 12-4-2009 | Non federally enforceable |
| RULE 1145 | 2-14-1997 | Federally enforceable |
| RULE 1171 | 11-7-2003 | Federally enforceable |
| RULE 1171 | 5-1-2009 | Non federally enforceable |
| RULE 118 | 12-7-1995 | Non federally enforceable |
| RULE 1303(a)(1)-BACT | 12-6-2002 | Non federally enforceable |
| RULE 1303(a)(1)-BACT | 5-10-1996 | Federally enforceable |
| RULE 1303(b)(2)-Offset | 12-6-2002 | Non federally enforceable |
| RULE 1303(b)(2)-Offset | 5-10-1996 | Federally enforceable |
| RULE 1401 | 12-7-1990 | Non federally enforceable |
| RULE 204 | 10-8-1993 | Federally enforceable |
| RULE 217 | 1-5-1990 | Federally enforceable |
| RULE 219 | 6-1-2007 | Non federally enforceable |
| RULE 219 | 9-4-1981 | Federally enforceable |
| RULE 3002 | 11-14-1997 | Federally enforceable |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## SECTION K: TITLE V Administration

| RULE SOURCE | Adopted/Amended Date | FEDERAL Enforceability |
|---|---|---|
| RULE 3002 | 11-5-2010 | Non federally enforceable |
| RULE 3003 | 11-14-1997 | Federally enforceable |
| RULE 3003 | 11-5-2010 | Non federally enforceable |
| RULE 3004 | 12-12-1997 | Federally enforceable |
| RULE 3004(a)(4)-Periodic Monitoring | 12-12-1997 | Federally enforceable |
| RULE 3005 | 11-14-1997 | Federally enforceable |
| RULE 3005 | 11-5-2010 | Non federally enforceable |
| RULE 3007 | 10-8-1993 | Federally enforceable |
| RULE 304 | 5-6-2011 | Non federally enforceable |
| RULE 401 | 11-9-2001 | Non federally enforceable |
| RULE 401 | 3-2-1984 | Federally enforceable |
| RULE 402 | 5-7-1976 | Non federally enforceable |
| RULE 404 | 2-7-1986 | Federally enforceable |
| RULE 408 | 5-7-1976 | Federally enforceable |
| RULE 430 | 7-12-1996 | Non federally enforceable |
| RULE 442 | 12-15-2000 | Federally enforceable |
| RULE 481 | 1-11-2002 | Federally enforceable |
| RULE 701 | 6-13-1997 | Federally enforceable |
| 40CFR 63 Subpart JJ | 12-28-1998 | Federally enforceable |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN PERMIT PURSUANT TO RULE 219

NONE

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

| VOC LIMITS<br>Less Water and Less Exempt Compounds<br>Effective Dates | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **Coating** | **Air-Dried** | | | | **Baked** | | | |
| | **gm/l** | | **lb/gal** | | **gm/l** | | **lb/gal** | |
| | **Current** | **7/1/07** | **Current** | **7/1/07** | **Current** | **7/1/07** | **Current** | **7/1/07** |
| General One-Component | 275 | 275 | 2.3 | 2.3 | 275 | 275 | 2.3 | 2.3 |
| General Multi-Component | 340 | 340 | 2.8 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Military Specification | 340 | 340 | 2.8 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Etching Filler | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Solar-Absorbent | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Heat-Resistant | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Extreme High-Gloss | 420 | 340 | 3.5 | 2.8 | 360 | 360 | 3.0 | 3.0 |
| Metallic | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1107 01-06-2006]

**VOC LIMITS**
**Less Water and Less Exempt Compounds**
**Effective Dates, cont.**

| Coating | Air-Dried | | | | Baked | | | |
|---|---|---|---|---|---|---|---|---|
| | gm/l | | lb/gal | | gm/l | | lb/gal | |
| | Current | 7/1/07 | Current | 7/1/07 | Current | 7/1/07 | Current | 7/1/07 |
| Extreme Performance | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Prefabricated Architectural One-Component | 420 | 275 | 3.5 | 2.3 | 275 | 275 | 2.3 | 2.3 |
| Prefabricated Architectural Multi-Component | 420 | 340 | 3.5 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Touch Up | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Repair | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Silicone Release | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| High-Performance Architectural | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Camouflage | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Vacuum-Metalizing | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Mold-Seal | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| High-Temperature | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Electric-Insulating Varnish | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Pan Backing | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Pretreatment Coatings | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1107 01-06-2006]

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

| VOC LIMITS<br>Less Water and Less Exempt Compounds<br>Effective Dates | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **Coating** | **Air-Dried** | | | | **Baked** | | | |
| | **gm/l** | | **lb/gal** | | **gm/l** | | **lb/gal** | |
| | **Current** | **7/1/07** | **Current** | **7/1/07** | **Current** | **7/1/07** | **Current** | **7/1/07** |
| General One-Component | 275 | 275 | 2.3 | 2.3 | 275 | 275 | 2.3 | 2.3 |
| General Multi-Component | 340 | 340 | 2.8 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Military Specification | 340 | 340 | 2.8 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Etching Filler | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Solar-Absorbent | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Heat-Resistant | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Extreme High-Gloss | 420 | 340 | 3.5 | 2.8 | 360 | 360 | 3.0 | 3.0 |
| Metallic | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

| VOC LIMITS<br>Less Water and Less Exempt Compounds<br>Effective Dates | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **Coating** | **Air-Dried** | | | | **Baked** | | | |
| | **gm/l** | | **lb/gal** | | **gm/l** | | **lb/gal** | |
| | **Current** | **7/1/07** | **Current** | **7/1/07** | **Current** | **7/1/07** | **Current** | **7/1/07** |
| General One-Component | 275 | 275 | 2.3 | 2.3 | 275 | 275 | 2.3 | 2.3 |
| General Multi-Component | 340 | 340 | 2.8 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Military Specification | 340 | 340 | 2.8 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Etching Filler | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Solar-Absorbent | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Heat-Resistant | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Extreme High-Gloss | 420 | 340 | 3.5 | 2.8 | 360 | 360 | 3.0 | 3.0 |
| Metallic | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1107 11-09-2001]

| VOC LIMITS<br>Less Water and Less Exempt Compounds<br>Effective Dates, cont. | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| **Coating** | **Air-Dried** | | | | **Baked** | | | |
| | **gm/l** | | **lb/gal** | | **gm/l** | | **lb/gal** | |
| | **Current** | **7/1/07** | **Current** | **7/1/07** | **Current** | **7/1/07** | **Current** | **7/1/07** |
| Extreme Performance | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Prefabricated Architectural One-Component | 420 | 275 | 3.5 | 2.3 | 275 | 275 | 2.3 | 2.3 |
| Prefabricated Architectural Multi-Component | 420 | 340 | 3.5 | 2.8 | 275 | 275 | 2.3 | 2.3 |
| Touch Up | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Repair | 420 | 420 | 3.5 | 3.5 | 360 | 360 | 3.0 | 3.0 |
| Silicone Release | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| High-Performance Architectural | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Camouflage | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Vacuum-Metalizing | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Mold-Seal | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| High-Temperature | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Electric-Insulating Varnish | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Pan Backing | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |
| Pretreatment Coatings | 420 | 420 | 3.5 | 3.5 | 420 | 420 | 3.5 | 3.5 |

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1113 11-08-1996]

(1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.

(2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

## TABLE OF STANDARDS

## VOC LIMITS

### Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

| COATING | Limit* | Effective Date of Adoption | Effective 1/1/1998 | Effective 1/1/1999 | Effective 7/1/2001 | Effective 1/1/2005 | Effective 7/1/2008 |
|---|---|---|---|---|---|---|---|
| Bond Breakers | 350 | | | | | | |
| Clear Wood Finishes | | | | | | | |
| Varnish | 350 | | | | | | |
| Sanding Sealers | 350 | | | | | | |
| Lacquer | 680 | | 550 | | | 275 | |
| Concrete-Curing Compounds | 350 | | | | | | |
| Dry-Fog Coatings | 400 | | | | | | |
| Fire-proofing Exterior Coatings | 350 | 450 | | 350 | | | |
| Fire-Retardant Coatings | | | | | | | |
| Clear | 650 | | | | | | |
| Pigmented | 350 | | | | | | |
| Flats | 250 | | | | 100 | | 50 |
| Graphic Arts (Sign) Coatings | 500 | | | | | | |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1113 11-08-1996]

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Industrial Maintenance Primers and Topcoats | | | | | | | |
| Alkyds | 420 | | | | | | |
| Catalyzed Epoxy | 420 | | | | | | |
| Bituminous Coatings | 420 | | | | | | |
| Materials | | | | | | | |
| Inorganic Polymers | 420 | | | | | | |
| Vinyl Chloride Polymers | 420 | | | | | | |
| Chlorinated Rubber | 420 | | | | | | |
| Acrylic Polymers | 420 | | | | | | |
| Urethane Polymers | 420 | | | | | | |
| Silicones | 420 | | | | | | |
| Unique Vehicles | 420 | | | | | | |
| Japans/Faux Finishing Coatings | 350 | 700 | | 350 | | | |
| Magnesite Cement Coatings | 600 | | | 450 | | | |
| Mastic Coatings | 300 | | | | | | |
| Metallic Pigmented Coatings | 500 | | | | | | |
| Multi-Color Coatings | 420 | | 250 | | | | |
| Pigmented Lacquer | 680 | | 550 | | | 275 | |
| Pre-Treatment Wash Primers | 780 | | | | | | |
| Primers, Sealers, and Undercoaters | 350 | | | | | | |
| Quick-Dry Enamels | 400 | | | | | | |
| Roof Coatings | 300 | | | | | | |
| Shellac | | | | | | | |
| Clear | 730 | | | | | | |
| Pigmented | 550 | | | | | | |
| Stains | 350 | | | | | | |
| Swimming Pool Coatings | | | | | | | |
| Repair | 650 | | | | | | |
| Other | 340 | | | | | | |
| Traffic Coatings | 250 | | 150 | | | | |
| Waterproofing Sealers | 400 | | | | | | |
| Wood Preservatives | | | | | | | |
| Below-Ground | 350 | | | | | | |
| Other | 350 | | | | | | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

## TABLE OF STANDARDS (cont.)

## VOC LIMITS

## Grams of VOC Per Liter of Material

| COATING | Limit |
|---|---|
| Low-Solids Coating | 120 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1113 06-03-2011]

(1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:

(A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or

(B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).

(2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1113 06-03-2011]

### TABLE OF STANDARDS 1
### VOC LIMITS

### Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

| COATING CATEGORY | Ceiling Limit[1] | Current Limit[2] | Effective Date | | |
|---|---|---|---|---|---|
| | | | 7/1/08 | 1/1/12 | 1/1/14 |
| Bond Breakers | | 350 | | | |
| Clear Wood Finishes | | 275 | | | |
| Varnish | 350 | 275 | | | |
| Sanding Sealers | 350 | 275 | | | |
| Lacquer | | 275 | | | |
| Concrete-Curing Compounds | | 100 | | | |
| Concrete-Curing Compounds For Roadways and Bridges[3] | | 350 | | | |
| Concrete Surface Retarder | | 250 | | | 50 |
| Driveway Sealer | | 100 | | 50 | |
| Dry-Fog Coatings | | 150 | | | 50 |
| Faux Finishing Coatings | | | | | |
| Clear Topcoat | | 350 | | 200 | |
| Decorative Coatings | | 350 | | | 100 |
| Glazes | | 350 | | | |
| Japan | | 350 | | | |
| Trowel Applied Coatings | | 350 | | 150 | 50 |
| Fire-Proofing Coatings | | 350 | | | 150 |
| Flats | 250 | 50 | 50 | | |
| Floor Coatings | 100 | 50 | | | |
| Form Release Compound | | 250 | | | 100 |
| Graphic Arts (Sign) Coatings | | 500 | | | 150 |
| Industrial Maintenance (IM) Coatings | 420 | 100 | | | |
| High Temperature IM Coatings | | 420 | | | |
| Non-Sacrificial Anti-Graffiti Coatings | | 100 | | | |
| Zinc-Rich IM Primers | 340 | 100 | | | |
| Magnesite Cement Coatings | | 450 | | | |
| Mastic Coatings | | 300 | | | 100 |
| Metallic Pigmented Coatings | 500 | 500 | | | 150 |
| Multi-Color Coatings | | 250 | | | |
| Nonflat Coatings | 150 | 50 | | | |
| Pre-Treatment Wash Primers | | 420 | | | |
| Primers, Sealers, and Undercoaters | 200 | 100 | | | |
| Reactive Penetrating Sealers | | 350 | | | |
| Recycled Coatings | | 250 | | | |
| Roof Coatings | 250 | 50 | | | |
| Roof Coatings, Aluminum | | 100 | | | |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1113 06-03-2011]

| | | | | | |
|---|---|---|---|---|---|
| Roof Primers, Bituminous | 350 | 350 | | | |
| Rust Preventative Coatings | 400 | 100 | | | |
| Stone Consolidant | | 450 | | | |
| Sacrificial Anti-Graffiti Coatings | | 100 | | 50 | |
| Shellac | | | | | |
| Clear | | 730 | | | |
| Pigmented | | 550 | | | |
| Specialty Primers | 350 | 100 | | | |
| Stains | | 100 | | | |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1113 06-03-2011]

| COATING CATEGORY | Ceiling Limit[1] | Current Limit[2] | Effective Date | | |
|---|---|---|---|---|---|
| | | | 7/1/08 | 1/1/12 | 1/1/14 |
| Stains, Interior | 250 | 250 | | | |
| Swimming Pool Coatings | | | | | |
| Repair | | 340 | | | |
| Other | | 340 | | | |
| Traffic Coatings | | 100 | | | |
| Waterproofing Sealers | 250 | 100 | | | |
| Waterproofing Concrete/Masonry Sealers | 400 | 100 | | | |
| Wood Preservatives | | 350 | | | |

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

## TABLE OF STANDARDS 1 (cont.)
## VOC LIMITS

### Grams of VOC Per Liter of Material

| COATING | Limit |
|---|---|
| Low-Solids Coating | 120 |

## TABLE OF STANDARDS 2
## VOC LIMITS FOR COLORANTS

### Grams of VOC Per Liter of Colorant
### Less Water and Less Exempt Compounds

| COLORANT | Limit[4] |
|---|---|
| Architectural Coatings, excluding IM Coatings | 50 |
| Solvent-Based IM | 600 |
| Waterborne IM | 50 |

4. Effective January 1, 2014.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1124 09-21-2001]

Except as otherwise provided in Rule 1124

(1) VOC Content of Aerospace Materials

(A) A person shall not apply to aerospace components any materials, including any VOC-containing materials added to the original material supplied by the manufacturer, which contain VOC in excess of the limits specified below:

| **VOC Limit**<br>**Grams of VOC per Liter, Less Water and Less Exempt Compounds** | | | |
|---|---|---|---|
| **Primers** | **Current VOC Limit** | **VOC Limit Effective 1-1-03** | **VOC Limit Effective 1-1-05** |
| General Primer | 350 | 350 | 350 |
| Low-Solids Corrosion Resistant Primer | 350 | 350 | 350 |
| Pretreatment Primer | 780 | 780 | 780 |
| Rain Erosion-Resistant Coating Compatible Primer | 850 | 850 | 850 |
| Adhesion Promoter | 850 | 850 | 250 |
| Adhesive Bonding Primer | | | |
| New Commercial Aircraft | 805 | 250 | 250 |
| All Military Aircraft | 805 | 805 | 805 |
| Remanufactured Commercial Aircraft Parts | 805 | 805 | 805 |
| Sonic and Acoustic Applications | 805 | 805 | 805 |
| Adhesive Bonding Primer | | | |
| Long Term | 250 | 250 | 250 |
| Short Term | 250 | 250 | 250 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1124 09-21-2001]

| Coatings | Current VOC Limit | VOC Limit Effective 3-01-02 |
|---|---|---|
| Topcoat | 420 | 420 |
| Clear Topcoat | 520 | 520 |
| Unicoat | 420 | 420 |
| Wing Coating | 750 | 750 |
| Impact Resistant Coating | 420 | 420 |
| High-Temperature Coating | 850 | 850 |
| Antichafe Coating | 600 | 420 |
| Rain Erosion-Resistant Coating | 800 | 800 |
| Conformal Coating | 750 | 750 |
| Optical Anti-Reflective Coating | 700 | 700 |
| Scale Inhibitor | 880 | 880 |
| Metallized Epoxy Coating | 700 | 700 |
| Electric or Radiation Effect Coating | 800 | 800 |
| Temporary Protective Coating | 250 | 250 |
| Fuel Tank Coatings | 420 | 420 |
| Mold Release Coatings | 780 | 780 |
| Flight Test Coatings | | |
| Used on Missiles or Single Use Target Craft | 420 | 420 |
| All Other | 840 | 840 |
| Fire Resistant Coatings | | |
| Commercial | 650 | 650 |
| Military | 970 | 800 |
| Wire Coatings | | |
| Phosphate Ester Resistant Ink | 925 | 925 |
| Other | 420 | 420 |
| Space Vehicle Coatings | | |
| Electrostatic Discharge Protection Coating | 800 | 800 |
| Other | 1000 | 1000 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1124 09-21-2001]

| Adhesives | Current VOC Limit |
|---|---|
| Non-Structural Adhesive | 250 |
| Structural Adhesive | |
| Autoclavable | 50 |
| Non-Autoclavable | 850 |
| Space Vehicle Adhesive | 800 |
| Fuel Tank Adhesive | 620 |

| Sealants | Current VOC Limit | VOC Limit Effective 3-01-02 |
|---|---|---|
| Fastener Sealant | 675 | 675 |
| Extrudable,Rollable or Brushable Sealant | 600 | 280 |
| Other | 600 | 600 |

| Maskants | Current VOC Limit |
|---|---|
| For Chemical Processing | 250 |
| For Chemical Milling | |
| Type I | 250 |
| Type II | 160 |
| Photolithographic | 850 |
| Touch-up, Line Sealer Maskants | 750 |

| Lubricants | Current VOC Limit |
|---|---|
| Fastener Installation | |
| Solid-Film Lubricant | 880 |
| Dry Lubricative Materials | 675 |
| Fastener-Lubricative Coatings, Fastener Manufacturing | |
| Solid Film Lubricant | 250 |
| Dry Lubricative Materials | 120 |
| Barrier Coating | 420 |
| Non-Fastener Lubricative Coatings, Fastener Manufacturing | |
| Solid Film Lubricant | 880 |
| Dry Lubricative Materials | 675 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1124 09-21-2001]

| VOC LIMIT<br>Grams of VOC per Liter of Material | |
|---|---|
| **Cleaning Solvents and Strippers** | **Current VOC Limit** |
| Cleaning Solvents | 200 g/L<br>or<br>45 mm Hg VOC Composite Partial Pressure |
| Strippers | 300 g/L<br>or<br>9.5 mm Hg VOC Composite Partial Pressure |

(B) Documents shall be provided to the Executive Officer or his designee demonstrating that unicoat is being used in lieu of the application of a primer and topcoat, and the applicant must receive written approval for the use of unicoat specifying the conditions of application from the Executive Officer or his designee.

(C) For low-solids adhesives, coatings, primers or sealants, the appropriate limits in subparagraph (c)(1)(A) shall be expressed in grams of VOC per liter of material.

(2) Solvent Cleaning Operations; Storage and Disposal of VOC-Containing Materials

(A) Cleaning of material application equipment and storage of solvent laden cloth and paper shall comply with provisions of Rule 1171.

(B) A person shall not atomize any solvent into open air.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1136 06-14-1996]

Except as otherwise provided in Rule 1136

(a) The operator shall not apply any coating to a wood product which has a VOC content, including any VOC-containing material added to the original coating supplied by the manufacturer, which exceeds the applicable limit specified below:

(1)

**VOC LIMITS**
Grams Per Liter (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

| COATING | Current Limit I | Current Limit II | On and After 7/1/2005 |
|---|---|---|---|
| Clear Sealers | 550 (4.6) [1.39] | 680 (5.7) [3.36] | 275 (2.3) [0.36] |
| Clear Topcoat | 550 (4.6) [1.37] | 275 (2.3) [0.35] | 275 (2.3) [0.35] |
| Pigmented Primers, Sealers & Undercoats | 550 (4.6) [1.06] | 600 (5.0) [1.08] | 275 (2.3) [0.21] |
| Pigmented Topcoats | 550 (4.6) [1.10] | 275 (2.3) [0.25] | 275 (2.3) [0.25] |

The operator shall use coatings on a wood product that comply with either all VOC limits in column I or all VOC limits in column II. The operator that applies a primer, sealer or undercoat, but not a topcoat, to a wood product, shall be subject to column I for that wood product.

(2) Notwithstanding the requirements of clause (a)(1), an operator that applies a topcoat and a primer, sealer or undercoat to a shutter may, until July 1, 2005, choose to comply with the VOC limits specified below for that shutter:

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1136 06-14-1996]

**VOC LIMITS**

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

| COATING | |
|---|---|
| Clear Sealers | 275 (2.3) [0.36] |
| Clear Topcoat | 680 (5.7) [2.99] |
| Pigmented Primers, Sealers & Undercoats | 275 (2.3) [0.33] |
| Pigmented Topcoats | 600 (5.0) [1.38] |

(3)

**VOC LIMITS**

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

| COATING | Current Limit | On and After 7/1/2005 |
|---|---|---|
| Barrier Coat - Plastic Components | 760 (6.3) [3.9] | 275 (2.3) [0.28] |
| Composite Wood Edge Filler | 550 (4.6) [1.15] | 275 (2.3) [0.31] |
| Extreme Performance Coatings | 420 (3.5) [0.51] | 275 (2.3) [0.33] |
| Fillers | 500 (4.2) [0.66] | 275 (2.3) [0.18] |
| High-Solid Stains | 550 (4.6) [1.23] | 350 (2.9) [0.42] |
| Inks | 500 (4.2) [0.96] | 500 (4.2) [0.96] |
| Mold-Seal Coatings | 750 (6.3) [4.2] | 750 (6.3) [4.2] |
| Multi-Colored Coatings | 685 (5.7) [2.6] | 275 (2.3) [0.33] |

**VOC LIMITS**

Grams Per Liter (lb/gal) of Material

| COATING | Current Limit | On and After 7/1/2005 |
|---|---|---|
| Low-Solids Barrier Coat - Plastic Components | 760 (6.3) | 120 (1.0) |
| Low-Solid Stains, Toners, and Washcoats | 480 (4.0) | 120 (1.0) |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1136 06-14-1996]

Any coating subject to this rule that meets any of the three VOC limit formats (grams per liter, lb/gal, or lbs VOC/lb of solids) is in compliance with this subparagraph.

(4) The VOC limit for japan coatings is 700 grams per liter of coatings, less water and exempt compounds, as applied.

(b) A person shall not use a stripper on wood products unless:

(1) it contains less than 350 grams of VOC per liter of material; or

(2) the VOC composite vapor pressure is 2 mm Hg (0.04 psia) or less at 20$^{o}$C (68$^{o}$F).

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1145 12-04-2009]

Except as otherwise provided in Rule 1145, no person shall apply on plastics, rubber, leather, or glass any coatings which are applied with a VOC content in excess of the limits listed in the Table of Standards.

## TABLE OF STANDARDS

| VOC LIMITS<br>LESS WATER AND LESS EXEMPT COMPOUNDS | | |
|---|---|---|
| COATING CATEGORIES | g/L | lbs/gal |
| Electrical dissipating and shock free coatings | 360 | 3.0 |
| Extreme performance two-component coatings | 420 | 3.5 |
| General one-component coatings | 120 | 1.0 |
| General two-component coatings | 120 | 1.0 |
| Leather antique coatings | 156 | 1.3 |
| Leather color coatings | 60 | 0.5 |
| Leather sealer coatings | 60 | 0.5 |
| Leather stain coatings | 216 | 1.8 |
| Leather top coatings | 120 | 1.0 |
| Metallic coatings | 420 | 3.5 |
| Military specification one-component coatings | 340 | 2.8 |
| Military specification two-component coatings | 420 | 3.5 |
| Mirror backing curtain coated coatings | 500 | 4.2 |
| Mirror backing rolled coated coatings | 312 | 2.6 |
| Mold seal coatings | 750 | 6.3 |
| Multi-color coatings | 680 | 5.7 |
| Refrigerated glass door coatings | 480 | 4.0 |
| Optical coatings | 50 | 0.4 |
| Vacuum metalizing coatings | 800 | 6.7 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1145 02-14-1997]

Except as otherwise provided in Rule 1145, the operator shall not apply on plastics, glass, or rubber any coatings which are applied with a VOC content in excess of the limits specified below:

| COATING | VOC LIMITS Less Water and Less Exempt Compounds | | | |
|---|---|---|---|---|
| | Current | | On and After 1-1-98 | |
| | g/L | lbs/gal | g/L | lbs/gal |
| General Coatings | | | | |
| One-component | 275 | 2.3 | 275 | 2.3 |
| Two-component | 420 | 3.5 | 420 | 3.5 |
| Military Spec. Coating | | | | |
| One-component | 340 | 2.8 | 340 | 2.8 |
| Two-component | 420 | 3.5 | 420 | 3.5 |
| Multi-Colored Coatings | 685 | 5.7 | 685 | 5.7 |
| Mold Seal Coatings | 750 | 6.3 | 750 | 6.3 |
| Vacuum Metalizing Coatings | 800 | 6.7 | 800 | 6.7 |
| Mirror Backing | | | | |
| Curtain Coated | 500 | 4.2 | 500 | 4.2 |
| Roll Coated | 430 | 3.6 | 430 | 3.6 |
| Optical Coatings | 800 | 6.7 | 800 | 6.7 |
| Electric Dissipating Coatings and Shock-Free Coatings | 800 | 6.7 | 360 | 3.0 |
| Metallic Coatings | 420 | 3.5 | 420 | 3.5 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1171 11-07-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| SOLVENT CLEANING ACTIVITY | CURRENT LIMITS<br>VOC<br>g/l<br>(lb/gal) |
|---|---|
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application | |
| (i) General | 25<br>(0.21) |
| (ii) Electrical Apparatus Components & Electronic Components | 500<br>(4.2) |
| (iii) Medical Devices & Pharmaceuticals | 800<br>(6.7) |
| (B) Repair and Maintenance Cleaning | |
| (i) General | 25<br>(0.21) |
| (ii) Electrical Apparatus Components & Electronic Components | 900<br>(7.5) |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1171 11-07-2003]

| SOLVENT CLEANING ACTIVITY | CURRENT LIMITS<br>VOC<br>g/l<br>(lb/gal) |
|---|---|
| (iii) Medical Devices & Pharmaceuticals | |
| (A) Tools, Equipment, & Machinery | 800<br>(6.7) |
| (B) General Work Surfaces | 600<br>(5.0) |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 550<br>(4.6) |
| (D) Cleaning of Ink Application Equipment | |
| (i) General | 25<br>(0.21) |
| (ii) Flexographic Printing | 25<br>(0.21) |
| (iii) Gravure Printing | |
| (A) Publication | 750<br>(6.3) |
| (B) Packaging | 25<br>(0.21) |
| (iv) Lithographic or Letter Press Printing | |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1171 11-07-2003]

| SOLVENT CLEANING ACTIVITY | CURRENT LIMITS<br>VOC<br>g/l<br>(lb/gal) |
|---|---|
| (A) Roller Wash – Step 1 | 600<br>(5.0) |
| (B) Roller Wash-Step 2,<br>Blanket Wash, & On-Press Components | 800<br>(6.7) |
| (C) Removable Press Components | 25<br>(0.21) |
| (v) Screen Printing | 750<br>(6.3) |
| (vi) Ultraviolet Ink/ Electron Beam Ink<br>Application Equipment (except screen printing) | 800<br>(6.7) |
| (vii) Specialty Flexographic Printing | 600<br>(5.0) |
| (E) Cleaning of Polyester Resin Application Equipment | 25<br>(0.21) |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| | CURRENT LIMITS* | EFFECTIVE 1/1/2010 |
|---|---|---|
| **SOLVENT CLEANING ACTIVITY** | **VOC g/l (lb/gal)** | **VOC g/l (lb/gal)** |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application | | |
| (i) General | 25 (0.21) | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | |
| (iii) Medical Devices & Pharmaceuticals | 800 (6.7) | |
| (B) Repair and Maintenance Cleaning | | |
| (i) General | 25 (0.21) | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1171 05-01-2009]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2010 |
|---|---|---|
| **SOLVENT CLEANING ACTIVITY (cont.)** | **VOC g/l (lb/gal)** | **VOC g/l (lb/gal)** |
| (iii) Medical Devices & Pharmaceuticals | | |
| (A) Tools, Equipment, & Machinery | 800 (6.7) | |
| (B) General Work Surfaces | 600 (5.0) | |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 25 (0.21) | |
| (D) Cleaning of Ink Application Equipment | | |
| (i) General | 25 (0.21) | |
| (ii) Flexographic Printing | 25 (0.21) | |
| (iii) Gravure Printing | | |
| (A) Publication | 100 (0.83) | |
| (B) Packaging | 25 (0.21) | |
| (iv) Lithographic (Offset) or Letter Press Printing | | |
| (A) Roller Wash, Blanket Wash, & On-Press Components | 100 (0.83) | |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 1171 05-01-2009]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2010 |
|---|---|---|
| **SOLVENT CLEANING ACTIVITY (cont.)** | **VOC g/l (lb/gal)** | **VOC g/l (lb/gal)** |
| (B) Removable Press Components | 25 (0.21) | |
| (v) Screen Printing | 100 (0.83) | |
| (vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing) | 650 (5.4) | 100 (0.83) |
| (vii) Specialty Flexographic Printing | 100 (0.83) | |
| (E) Cleaning of Polyester Resin Application Equipment | 25 (0.21) | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

**TABLE 404(a)**

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|---|---|---|---|---|---|---|---|
| Cubic meters Per Minute | Cubic feet Per Minute | Milligrams per Cubic Meter | Grains per Cubic Foot | Cubic meters Per Minute | Cubic feet Per Minute | Milligrams per Cubic Meter | Grains per Cubic Foot |
| 25 or less | 883 or less | 450 | 0.196 | 900 | 31780 | 118 | 0.0515 |
| 30 | 1059 | 420 | .183 | 1000 | 35310 | 113 | .0493 |
| 35 | 1236 | 397 | .173 | 1100 | 38850 | 109 | .0476 |
| 40 | 1413 | 377 | .165 | 1200 | 42380 | 106 | .0463 |
| 45 | 1589 | 361 | .158 | 1300 | 45910 | 102 | .0445 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 404 02-07-1986]

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|---|---|---|---|---|---|---|---|
| Cubic meters Per Minute | Cubic feet Per Minute | Milligrams per Cubic Meter | Grains per Cubic Foot | Cubic meters Per Minute | Cubic feet Per Minute | Milligrams per Cubic Meter | Grains per Cubic Foot |
| 50 | 1766 | 347 | .152 | 1400 | 49440 | 100 | .0437 |
| 60 | 2119 | 324 | .141 | 1500 | 52970 | 97 | .0424 |
| 70 | 2472 | 306 | .134 | 1750 | 61800 | 92 | .0402 |
| 80 | 2825 | 291 | .127 | 2000 | 70630 | 87 | .0380 |
| 90 | 3178 | 279 | .122 | 2250 | 79460 | 83 | .0362 |
| 100 | 3531 | 267 | .117 | 2500 | 88290 | 80 | .0349 |
| 125 | 4414 | 246 | .107 | 3000 | 105900 | 75 | .0327 |
| 150 | 5297 | 230 | .100 | 4000 | 141300 | 67 | .0293 |
| 175 | 6180 | 217 | .0947 | 5000 | 176600 | 62 | .0271 |
| 200 | 7063 | 206 | .0900 | 6000 | 211900 | 58 | .0253 |
| 250 | 8829 | 190 | .0830 | 8000 | 282500 | 52 | .0227 |
| 300 | 10590 | 177 | .0773 | 10000 | 353100 | 48 | .0210 |
| 350 | 12360 | 167 | .0730 | 15000 | 529700 | 41 | .0179 |
| 400 | 14130 | 159 | .0694 | 20000 | 706300 | 37 | .0162 |
| 450 | 15890 | 152 | .0664 | 25000 | 882900 | 34 | .0148 |

# FACILITY PERMIT TO OPERATE
# CALIFORNIA SPECIALTY PAINTING

## APPENDIX B: RULE EMISSION LIMITS
## [RULE 404 02-07-1986]

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|---|---|---|---|---|---|---|---|
| Cubic meters Per Minute | Cubic feet Per Minute | Milligrams per Cubic Meter | Grains per Cubic Foot | Cubic meters Per Minute | Cubic feet Per Minute | Milligrams per Cubic Meter | Grains per Cubic Foot |
| 500 | 17660 | 146 | .0637 | 30000 | 1059000 | 32 | .0140 |
| 600 | 21190 | 137 | .0598 | 40000 | 1413000 | 28 | .0122 |
| 700 | 24720 | 129 | .0563 | 50000 | 1766000 | 26 | .0114 |
| 800 | 28250 | 123 | .0537 | 70000 or more | 2472000 or more | 23 | .0100 |