



JAN 10 2011

Sue Giampietro
The Wine Group, Inc.
PO Box 897
Ripon, CA 95366

**Re: Notice of Significant Title V Permit Modification
District Facility # N-956
Project # N-1103645**

Dear Ms. Giampietro:

Enclosed for you to review is the District's analysis of an application for significant Title V permit modification for the facility identified above. The Wine Group, Inc. is proposing a Title V significant permit modification to incorporate the recently issued N-956-6-4, N-956-11-2 through -40-2, -43-2 through -202-2, -203-1 through -218-1, and -236-0 through -249-0 into the Title V operating permit (see enclosures). The facility proposes to establish a specific limiting condition (SLC) that limits annual wine fermentation and storage emissions from all wine tanks at their facility to the Pre-Project Potential to Emit of the pre-project fermentation and storage capacities of the facility. In addition, the facility is re-rating their current 25 MMBtu/hr boiler to 17.5 MMBtu/hr for District Rule 4320 compliance.

Enclosed are the current Title V permit, recently issued N-956-6-4, N-956-11-2 through -40-2, -43-2 through -202-2, -203-1 through -218-1, and -236-0 through -249-0, proposed modified Title V permit, engineering evaluation, and application. The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period that begins on the date you receive this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

Enclosures

c: Juscelino Siongco, Permit Services
Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



JAN 10 2011

Gerardo C. Rios, Chief
Permits Office
Air Division
U.S. EPA - Region IX
75 Hawthorne St.
San Francisco, CA 94105

**Re: Notice of Significant Title V Permit Modification
District Facility # N-956
Project # N-1103645**

Dear Mr. Rios:

Enclosed for you to review is the District's analysis of an application for significant Title V permit modification for the facility identified above. The Wine Group, Inc. is proposing a Title V significant permit modification to incorporate the recently issued N-956-6-4, N-956-11-2 through -40-2, -43-2 through -202-2, -203-1 through -218-1, and -236-0 through -249-0 into the Title V operating permit (see enclosures). The facility proposes to establish a specific limiting condition (SLC) that limits annual wine fermentation and storage emissions from all wine tanks at their facility to the Pre-Project Potential to Emit of the pre-project fermentation and storage capacities of the facility. In addition, the facility is re-rating their current 25 MMBtu/hr boiler to 17.5 MMBtu/hr for District Rule 4320 compliance.

Enclosed are the current Title V permit, recently issued N-956-6-4, N-956-11-2 through -40-2, -43-2 through -202-2, -203-1 through -218-1, and -236-0 through -249-0, proposed modified Title V permit, engineering evaluation, and application. The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 45-day comment period that begins on the date you receive this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,



David Warner
Director of Permit Services

Enclosures

Seyed Sadredin

Executive Director/Air Pollution Control Officer

c: Juscelino Siongco, Permit Services

Northern Region

4800 Enterprise Way
Modesto, CA 95356-8718

Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)

1990 E. Gettysburg Avenue
Fresno, CA 93726-0244

Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region

34946 Flyover Court
Bakersfield, CA 93308-9725

Tel: 661-392-5500 FAX: 661-392-5585



JAN 10 2011

Mike Tollstrup, Chief
Project Assessment Branch
Air Resources Board
P O Box 2815
Sacramento, CA 95812-2815

**Re: Notice of Significant Title V Permit Modification
District Facility # N-956
Project # N-1103645**

Dear Mr. Tollstrup:

Enclosed for you to review is the District's analysis of an application for significant Title V permit modification for the facility identified above. The Wine Group, Inc. is proposing a Title V significant permit modification to incorporate the recently issued N-956-6-4, N-956-11-2 through -40-2, -43-2 through -202-2, -203-1 through -218-1, and -236-0 through -249-0 into the Title V operating permit (see enclosures). The facility proposes to establish a specific limiting condition (SLC) that limits annual wine fermentation and storage emissions from all wine tanks at their facility to the Pre-Project Potential to Emit of the pre-project fermentation and storage capacities of the facility. In addition, the facility is re-rating their current 25 MMBtu/hr boiler to 17.5 MMBtu/hr for District Rule 4320 compliance.

Enclosed are the current Title V permit, recently issued N-956-6-4, N-956-11-2 through -40-2, -43-2 through -202-2, -203-1 through -218-1, and -236-0 through -249-0, proposed modified Title V permit, engineering evaluation, and application. The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period that begins on the date you receive this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

Enclosures

c: Juscélino Siongco, Permit Services, Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

**NOTICE OF PRELIMINARY DECISION
FOR THE PROPOSED SIGNIFICANT MODIFICATION OF
FEDERALLY MANDATED OPERATING PERMIT**

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District solicits public comment on the proposed modification of the Federally Mandated Operating Permit to The Wine Group, Inc. for its wine production facility, 17000 E Highway 120, Ripon, California. The facility proposes to establish a specific limiting condition (SLC) that limits annual wine fermentation and storage emissions from all wine tanks at their facility to the Pre-Project Potential to Emit of the pre-project fermentation and storage capacities of the facility. In addition, the facility is re-rating their current 25 MMBtu/hr boiler to 17.5 MMBtu/hr for District Rule 4320 compliance.

The District's analysis of the legal and factual basis for this proposed action, project #N-1103645, is available for public inspection at http://www.valleyair.org/notices/public_notices_idx.htm and the District office at the address below. This will be the public's only opportunity to comment on the specific conditions of the modification. If requested by the public, the District will hold a public hearing regarding issuance of this modification. For additional information, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900. Written comments on the proposed initial permit must be submitted within 30 days of the publication date of this notice to DAVID WARNER, DIRECTOR OF PERMIT SERVICES, SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 1990 E. GETTYSBURG AVE, FRESNO, CALIFORNIA 93726-0244.

TITLE V APPLICATION REVIEW

Significant Modification
Project #: N-1103645

Engineer: Juscelino Siongco
Date: January 7, 2011

Facility Number: N-956
Facility Name: The Wine Group, Inc.
Mailing Address: PO Box 897
Ripon, CA 95366

Contact Name: Sue Giampietro
Phone: (559) 528-3033

Responsible Official: Kevin Lacasse
Title: Plant Manager

I. PROPOSAL

The Wine Group, Inc. is proposing a Title V minor permit modification to incorporate the recently issued N-956-6-4, N-956-11-2 through -40-2, -43-2 through -202-2, -203-1 through -218-1, and -236-0 through -249-0 into the Title V operating permit. The facility proposes to establish a specific limiting condition (SLC) that limits annual wine fermentation and storage emissions from all wine tanks at their facility to the Pre-Project Potential to Emit of the pre-project fermentation and storage capacities of the facility. In addition, the facility is re-rating their current 25 MMBtu/hr boiler to 17.5 MMBtu/hr for District Rule 4320 compliance. The proposed modification is a Significant Title V Modification since the proposal is a Title I Modification under District Rule 2520.

The purpose of this evaluation is to identify all applicable requirements, determine if the facility will comply with the applicable requirements and to provide the legal and factual basis for the proposed revisions.

II. FACILITY LOCATION

The facility is located at 17000 E Highway 120, Ripon, CA 95366.

III. EQUIPMENT DESCRIPTION

See attachment A.

IV. SCOPE OF EPA AND PUBLIC REVIEW

This change to a Title V permit is considered to be a significant modification because the facility's proposed modifications result in a Federal Major Modification. As such, this project requires public review.

V. APPLICABLE REQUIREMENTS

District Rule 2520, Federally Mandated Operating Permits (Adopted June 21, 2001)

VI. DESCRIPTION OF PROPOSED MODIFICATIONS

The Wine Group, Inc. is proposing to establish a specific limiting condition (SLC) that limits annual wine fermentation and storage emissions from all wine tanks at their facility to the Pre-Project Potential to Emit of the pre-project fermentation and storage capacities of the facility. In addition, the facility is re-rating their current 25 MMBtu/hr boiler to 17.5 MMBtu/hr for District Rule 4320 compliance.

N-956-6-5:

Permit conditions 1 through 22 on the current permit were included as conditions 1, 2, 3, 4 through 9, and 11 through 24 on the proposed permit to operate.

N-956-11-3 through -40-3, -43-3 through -218-3, and -236-1 through -249-1:

All wine tank permit units modified under this project were identical in function, as such, the previous Title V operating permits are nearly identical. The modifications made to these units were identical in nature, so the modifications to the operating permits were identical. Therefore, the description of the modifications to the permit conditions will be the same for all the wine tank permits.

Permit conditions 1 through 6 on the current permit were included as conditions 4, 5, 6, 11, 10, and 17 on the proposed permit to operate.

VII. COMPLIANCE

District Rule 2520, Section 6.0 describes the source's ability to make changes including significant permit modification. This modification does not meet the minor permit modification criteria pursuant to Section 3.20 described as follows.

1. Do not violate requirements of any applicable federally enforceable local or federal requirement;
2. Do not relax monitoring, reporting, or recordkeeping requirements in the permit and are not significant changes in existing monitoring permit terms or conditions;
3. Do not require or change a case-by-case determination of an emission limitation or other standard, or a source-specific determination for temporary sources of ambient impacts, or a visibility or increment analysis;
4. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include:
 - a. A federally enforceable emission cap assumed to avoid classification as a modification under any provisions of Title I of the Federal Clean Air Act; and
 - b. An alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Federal Clean Air Act; and
5. Are not Title I modifications as defined in District Rule 2520 or modifications as defined in section 111 or 112 of the Federal Clean Air Act; and
6. Do not seek to consolidate overlapping applicable requirements.

In accordance with Rule 2520, the application meets the procedural requirements of Section 11.3 by including;

1. The identification of the source, the name and address of the permit holder, the activities and emissions change involved in the permit action;
2. The name and address of the District, the name and telephone number of District staff to contact for additional information;
3. The availability, upon request, of a statement that sets forth the legal and factual basis for the proposed permit conditions;
4. The location where the public may inspect the complete application, the District analysis, the proposed permit, and all relevant supporting materials;
5. A statement that the public may submit written comments regarding the proposed decision within at least 30 days from the date of publication and a brief description of commenting procedures, and
6. A statement that members of the public may request the APCO or his designee to preside over a public hearing for the purpose of receiving oral public comment, if a hearing has not already been scheduled. The APCO shall provide notice of any public hearing scheduled to address the proposed decision at least 30 days prior to such hearing;

VIII. ATTACHMENTS

- A. Proposed Modified Title V Operating Permit Equipment Descriptions
- B. Proposed Modified Title V Operating Permit No. N-956-6-5, -11-3 through -40-3, -43-3 through -218-3, and -236-1 through -249-1.
- C. Authorities to Construct No. N-956-6-4, N-956-11-2 through -40-2, -43-2 through -202-2, -203-1 through -218-1, and -236-0 through -249-0.
- D. Emissions Increases
- E. Application
- F. Previous Title V Operating Permit No.'s N-956-6-2, -11-1 through -40-1, -43-1 through -202-1, and -203-2 through -218-2

ATTACHMENT A

Proposed Modified Title V Operating Permit
Equipment Descriptions

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|----------------|--|
| N-956 - 6 - 5 | : 17.5 MMBTU/HR HURST SERIES 400 PROPANE-FIRED BOILER WITH AN ALZETA MODEL CSB252 ULTRA LOW NOX BURNER AND INDUCED FLUE GAS RECIRCULATION SYSTEM |
| N-956 - 11 - 3 | : 15,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK B1 WITH PRESSURE/VACUUM VALVE |
| N-956 - 12 - 3 | : 15,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK B2 WITH PRESSURE/VACUUM VALVE |
| N-956 - 13 - 3 | : 10,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 24 WITH PRESSURE/VACUUM VALVE |
| N-956 - 14 - 3 | : 10,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 39 WITH PRESSURE/VACUUM VALVE |
| N-956 - 15 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 44 WITH PRESSURE/VACUUM VALVE |
| N-956 - 16 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 45 WITH PRESSURE/VACUUM VALVE |
| N-956 - 17 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 46 WITH PRESSURE/VACUUM VALVE |
| N-956 - 18 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 47 WITH PRESSURE/VACUUM VALVE |
| N-956 - 19 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 48 WITH PRESSURE/VACUUM VALVE |
| N-956 - 20 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 49 WITH PRESSURE/VACUUM VALVE |
| N-956 - 21 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 50 WITH PRESSURE/VACUUM VALVE |
| N-956 - 22 - 3 | : 30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 51 WITH PRESSURE/VACUUM VALVE |
| N-956 - 23 - 3 | : 30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 52 WITH PRESSURE/VACUUM VALVE |
| N-956 - 24 - 3 | : 30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 53 WITH PRESSURE/VACUUM VALVE |
| N-956 - 25 - 3 | : 30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 54 WITH PRESSURE/VACUUM VALVE |
| N-956 - 26 - 3 | : 20,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 55 WITH PRESSURE/VACUUM VALVE |
| N-956 - 27 - 3 | : 60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 56 WITH PRESSURE/VACUUM VALVE |
| N-956 - 28 - 3 | : 60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 57 WITH PRESSURE/VACUUM VALVE |
| N-956 - 29 - 3 | : 60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 58 WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|----------------|---|
| N-956 - 30 - 3 | : 60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 59 WITH PRESSURE/VACUUM VALVE |
| N-956 - 31 - 3 | : 60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 60 WITH PRESSURE/VACUUM VALVE |
| N-956 - 32 - 3 | : 12,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 62 WITH PRESSURE/VACUUM VALVE |
| N-956 - 33 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 116 WITH PRESSURE/VACUUM VALVE |
| N-956 - 34 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 117 WITH PRESSURE/VACUUM VALVE |
| N-956 - 35 - 3 | : 120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 118 WITH PRESSURE/VACUUM VALVE |
| N-956 - 36 - 3 | : 15,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 131 WITH PRESSURE/VACUUM VALVE |
| N-956 - 37 - 3 | : 15,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 132 WITH PRESSURE/VACUUM VALVE |
| N-956 - 38 - 3 | : 30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 133 WITH PRESSURE/VACUUM VALVE |
| N-956 - 39 - 3 | : 30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 134 WITH PRESSURE/VACUUM VALVE |
| N-956 - 40 - 3 | : 30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 135 WITH PRESSURE/VACUUM VALVE |
| N-956 - 43 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1001 WITH PRESSURE/VACUUM VALVE |
| N-956 - 44 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1002 WITH PRESSURE/VACUUM VALVE |
| N-956 - 45 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1003 WITH PRESSURE/VACUUM VALVE |
| N-956 - 46 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1004 WITH PRESSURE/VACUUM VALVE |
| N-956 - 47 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1005 WITH PRESSURE/VACUUM VALVE |
| N-956 - 48 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1006 WITH PRESSURE/VACUUM VALVE |
| N-956 - 49 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1007 WITH PRESSURE/VACUUM VALVE |
| N-956 - 50 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1008 WITH PRESSURE/VACUUM VALVE |
| N-956 - 51 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1009 WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|----------------|---|
| N-956 - 52 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1011 WITH PRESSURE/VACUUM VALVE |
| N-956 - 53 - 3 | : 105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1012 WITH PRESSURE/VACUUM VALVE |
| N-956 - 54 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1013 WITH PRESSURE/VACUUM VALVE |
| N-956 - 55 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1014 WITH PRESSURE/VACUUM VALVE |
| N-956 - 56 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1015 WITH PRESSURE/VACUUM VALVE |
| N-956 - 57 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1016 WITH PRESSURE/VACUUM VALVE |
| N-956 - 58 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1017 WITH PRESSURE/VACUUM VALVE |
| N-956 - 59 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1018 WITH PRESSURE/VACUUM VALVE |
| N-956 - 60 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1019 WITH PRESSURE/VACUUM VALVE |
| N-956 - 61 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1020 WITH PRESSURE/VACUUM VALVE |
| N-956 - 62 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1021 WITH PRESSURE/VACUUM VALVE |
| N-956 - 63 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1022 WITH PRESSURE/VACUUM VALVE |
| N-956 - 64 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1023 WITH PRESSURE/VACUUM VALVE |
| N-956 - 65 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1024 WITH PRESSURE/VACUUM VALVE |
| N-956 - 66 - 3 | : 106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1025 WITH PRESSURE/VACUUM VALVE |
| N-956 - 67 - 3 | : 103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1026 WITH PRESSURE/VACUUM VALVE |
| N-956 - 68 - 3 | : 103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1027 WITH PRESSURE/VACUUM VALVE |
| N-956 - 69 - 3 | : 103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1028 WITH PRESSURE/VACUUM VALVE |
| N-956 - 70 - 3 | : 103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1029 WITH PRESSURE/VACUUM VALVE |
| N-956 - 71 - 3 | : 103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1030 WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|----------------|---|
| N-956 - 72 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2001 WITH PRESSURE/VACUUM VALVE |
| N-956 - 73 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2002 WITH PRESSURE/VACUUM VALVE |
| N-956 - 74 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2003 WITH PRESSURE/VACUUM VALVE |
| N-956 - 75 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2004 WITH PRESSURE/VACUUM VALVE |
| N-956 - 76 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2005 WITH PRESSURE/VACUUM VALVE |
| N-956 - 77 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2006 WITH PRESSURE/VACUUM VALVE |
| N-956 - 78 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2007 WITH PRESSURE/VACUUM VALVE |
| N-956 - 79 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2008 WITH PRESSURE/VACUUM VALVE |
| N-956 - 80 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2009 WITH PRESSURE/VACUUM VALVE |
| N-956 - 81 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2010 WITH PRESSURE/VACUUM VALVE |
| N-956 - 82 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2011 WITH PRESSURE/VACUUM VALVE |
| N-956 - 83 - 3 | : 218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2012 WITH PRESSURE/VACUUM VALVE |
| N-956 - 84 - 3 | : 218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2013 WITH PRESSURE/VACUUM VALVE |
| N-956 - 85 - 3 | : 218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2014 WITH PRESSURE/VACUUM VALVE |
| N-956 - 86 - 3 | : 218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2015 WITH PRESSURE/VACUUM VALVE |
| N-956 - 87 - 3 | : 218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2016 WITH PRESSURE/VACUUM VALVE |
| N-956 - 88 - 3 | : 218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2017 WITH PRESSURE/VACUUM VALVE |
| N-956 - 89 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2018 WITH PRESSURE/VACUUM VALVE |
| N-956 - 90 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2019 WITH PRESSURE/VACUUM VALVE |
| N-956 - 91 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2020 WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|-----------------|---|
| N-956 - 92 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2021 WITH PRESSURE/VACUUM VALVE |
| N-956 - 93 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2022 WITH PRESSURE/VACUUM VALVE |
| N-956 - 94 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2023 WITH PRESSURE/VACUUM VALVE |
| N-956 - 95 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2025 WITH PRESSURE/VACUUM VALVE |
| N-956 - 96 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2026 WITH PRESSURE/VACUUM VALVE |
| N-956 - 97 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2027 WITH PRESSURE/VACUUM VALVE |
| N-956 - 98 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2028 WITH PRESSURE/VACUUM VALVE |
| N-956 - 99 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2029 WITH PRESSURE/VACUUM VALVE |
| N-956 - 100 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2030 WITH PRESSURE/VACUUM VALVE |
| N-956 - 101 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2031 WITH PRESSURE/VACUUM VALVE |
| N-956 - 102 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2032 WITH PRESSURE/VACUUM VALVE |
| N-956 - 103 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2033 WITH PRESSURE/VACUUM VALVE |
| N-956 - 104 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2034 WITH PRESSURE/VACUUM VALVE |
| N-956 - 105 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2039 WITH PRESSURE/VACUUM VALVE |
| N-956 - 106 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2040 WITH PRESSURE/VACUUM VALVE |
| N-956 - 107 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2041 WITH PRESSURE/VACUUM VALVE |
| N-956 - 108 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2042 WITH PRESSURE/VACUUM VALVE |
| N-956 - 109 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2043 WITH PRESSURE/VACUUM VALVE |
| N-956 - 110 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2044 WITH PRESSURE/VACUUM VALVE |
| N-956 - 111 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2045 WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|-----------------|---|
| N-956 - 112 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2047 WITH PRESSURE/VACUUM VALVE |
| N-956 - 113 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2048 WITH PRESSURE/VACUUM VALVE |
| N-956 - 114 - 3 | : 217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2049 WITH PRESSURE/VACUUM VALVE |
| N-956 - 115 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3001 WITH PRESSURE/VACUUM VALVE |
| N-956 - 116 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3002 WITH PRESSURE/VACUUM VALVE |
| N-956 - 117 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3003 WITH PRESSURE/VACUUM VALVE |
| N-956 - 118 - 3 | : 323,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3004 WITH PRESSURE/VACUUM VALVE |
| N-956 - 119 - 3 | : 323,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3005 WITH PRESSURE/VACUUM VALVE |
| N-956 - 120 - 3 | : 323,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3006 WITH PRESSURE/VACUUM VALVE |
| N-956 - 121 - 3 | : 323,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3007 WITH PRESSURE/VACUUM VALVE |
| N-956 - 122 - 3 | : 323,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3008 WITH PRESSURE/VACUUM VALVE |
| N-956 - 123 - 3 | : 323,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3009 WITH PRESSURE/VACUUM VALVE |
| N-956 - 124 - 3 | : 323,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3010 WITH PRESSURE/VACUUM VALVE |
| N-956 - 125 - 3 | : 323,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3011 WITH PRESSURE/VACUUM VALVE |
| N-956 - 126 - 3 | : 324,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3012 WITH PRESSURE/VACUUM VALVE |
| N-956 - 127 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3013 WITH PRESSURE/VACUUM VALVE |
| N-956 - 128 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3014 WITH PRESSURE/VACUUM VALVE |
| N-956 - 129 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3015 WITH PRESSURE/VACUUM VALVE |
| N-956 - 130 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3016 WITH PRESSURE/VACUUM VALVE |
| N-956 - 131 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3017 WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|-----------------|---|
| N-956 - 132 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3018 WITH PRESSURE/VACUUM VALVE |
| N-956 - 133 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3019 WITH PRESSURE/VACUUM VALVE |
| N-956 - 134 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3020 WITH PRESSURE/VACUUM VALVE |
| N-956 - 135 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3021 WITH PRESSURE/VACUUM VALVE |
| N-956 - 136 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3022 WITH PRESSURE/VACUUM VALVE |
| N-956 - 137 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3023 WITH PRESSURE/VACUUM VALVE |
| N-956 - 138 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3024 WITH PRESSURE/VACUUM VALVE |
| N-956 - 139 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3025 WITH PRESSURE/VACUUM VALVE |
| N-956 - 140 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3026 WITH PRESSURE/VACUUM VALVE |
| N-956 - 141 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3027 WITH PRESSURE/VACUUM VALVE |
| N-956 - 142 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3028 WITH PRESSURE/VACUUM VALVE |
| N-956 - 143 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3029 WITH PRESSURE/VACUUM VALVE |
| N-956 - 144 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3030 WITH PRESSURE/VACUUM VALVE |
| N-956 - 145 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3031 WITH PRESSURE/VACUUM VALVE |
| N-956 - 146 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3032 WITH PRESSURE/VACUUM VALVE |
| N-956 - 147 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3033 WITH PRESSURE/VACUUM VALVE |
| N-956 - 148 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3034 WITH PRESSURE/VACUUM VALVE |
| N-956 - 149 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3035 WITH PRESSURE/VACUUM VALVE |
| N-956 - 150 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3036 WITH PRESSURE/VACUUM VALVE |
| N-956 - 151 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3037 WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|-----------------|---|
| N-956 - 152 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3038 WITH PRESSURE/VACUUM VALVE |
| N-956 - 153 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3039 WITH PRESSURE/VACUUM VALVE |
| N-956 - 154 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3040 WITH PRESSURE/VACUUM VALVE |
| N-956 - 155 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3041 WITH PRESSURE/VACUUM VALVE |
| N-956 - 156 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3042 WITH PRESSURE/VACUUM VALVE |
| N-956 - 157 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3043 WITH PRESSURE/VACUUM VALVE |
| N-956 - 158 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3044 WITH PRESSURE/VACUUM VALVE |
| N-956 - 159 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3045 WITH PRESSURE/VACUUM VALVE |
| N-956 - 160 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3046 WITH PRESSURE/VACUUM VALVE |
| N-956 - 161 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3047 WITH PRESSURE/VACUUM VALVE |
| N-956 - 162 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3048 WITH PRESSURE/VACUUM VALVE |
| N-956 - 163 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3049 WITH PRESSURE/VACUUM VALVE |
| N-956 - 164 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3050 WITH PRESSURE/VACUUM VALVE |
| N-956 - 165 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3051 WITH PRESSURE/VACUUM VALVE |
| N-956 - 166 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3052 WITH PRESSURE/VACUUM VALVE |
| N-956 - 167 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3053 WITH PRESSURE/VACUUM VALVE |
| N-956 - 168 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3054 WITH PRESSURE/VACUUM VALVE |
| N-956 - 169 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3055 WITH PRESSURE/VACUUM VALVE |
| N-956 - 170 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3056 WITH PRESSURE/VACUUM VALVE |
| N-956 - 171 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3057 WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|-----------------|---|
| N-956 - 172 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3058 WITH PRESSURE/VACUUM VALVE |
| N-956 - 173 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3059 WITH PRESSURE/VACUUM VALVE |
| N-956 - 174 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3060 WITH PRESSURE/VACUUM VALVE |
| N-956 - 175 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3061 WITH PRESSURE/VACUUM VALVE |
| N-956 - 176 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3062 WITH PRESSURE/VACUUM VALVE |
| N-956 - 177 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3063 WITH PRESSURE/VACUUM VALVE |
| N-956 - 178 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3064 WITH PRESSURE/VACUUM VALVE |
| N-956 - 179 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3065 WITH PRESSURE/VACUUM VALVE |
| N-956 - 180 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3066 WITH PRESSURE/VACUUM VALVE |
| N-956 - 181 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3067 WITH PRESSURE/VACUUM VALVE |
| N-956 - 182 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3068 WITH PRESSURE/VACUUM VALVE |
| N-956 - 183 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3070 WITH PRESSURE/VACUUM VALVE |
| N-956 - 184 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3072 WITH PRESSURE/VACUUM VALVE |
| N-956 - 185 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3074 WITH PRESSURE/VACUUM VALVE |
| N-956 - 186 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3076 WITH PRESSURE/VACUUM VALVE |
| N-956 - 187 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3077 WITH PRESSURE/VACUUM VALVE |
| N-956 - 188 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3078 WITH PRESSURE/VACUUM VALVE |
| N-956 - 189 - 3 | : 350,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3079 WITH PRESSURE/VACUUM VALVE |
| N-956 - 190 - 3 | : 650,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6013 WITH PRESSURE/VACUUM VALVE |
| N-956 - 191 - 3 | : 650,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6014 WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|-----------------|--|
| N-956 - 192 - 3 | : 650,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6015 WITH PRESSURE/VACUUM VALVE |
| N-956 - 193 - 3 | : 650,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6019 WITH PRESSURE/VACUUM VALVE |
| N-956 - 194 - 3 | : 650,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6020 WITH PRESSURE/VACUUM VALVE |
| N-956 - 195 - 3 | : 650,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6021 WITH PRESSURE/VACUUM VALVE |
| N-956 - 196 - 3 | : 650,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6022 WITH PRESSURE/VACUUM VALVE |
| N-956 - 197 - 3 | : 650,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6023 WITH PRESSURE/VACUUM VALVE |
| N-956 - 198 - 3 | : 650,000 GALLON GLASS LINED RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6024 WITH PRESSURE/VACUUM VALVE |
| N-956 - 199 - 3 | : 705,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 7001 WITH PRESSURE/VACUUM VALVE |
| N-956 - 200 - 3 | : 705,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 7002 WITH PRESSURE/VACUUM VALVE |
| N-956 - 201 - 3 | : 705,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 7003 WITH PRESSURE/VACUUM VALVE |
| N-956 - 202 - 3 | : 705,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 7004 WITH PRESSURE/VACUUM VALVE |
| N-956 - 203 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 205) WITH PRESSURE/VACUUM VALVE |
| N-956 - 204 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 206) WITH PRESSURE/VACUUM VALVE |
| N-956 - 205 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 207) WITH PRESSURE/VACUUM VALVE |
| N-956 - 206 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 208) WITH PRESSURE/VACUUM VALVE |
| N-956 - 207 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 209) WITH PRESSURE/VACUUM VALVE |
| N-956 - 208 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 210) WITH PRESSURE/VACUUM VALVE |
| N-956 - 209 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 211) WITH PRESSURE/VACUUM VALVE |
| N-956 - 210 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 212) WITH PRESSURE/VACUUM VALVE |
| N-956 - 211 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 213) WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|-----------------|--|
| N-956 - 212 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 214) WITH PRESSURE/VACUUM VALVE |
| N-956 - 213 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 215) WITH PRESSURE/VACUUM VALVE |
| N-956 - 214 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 216) WITH PRESSURE/VACUUM VALVE |
| N-956 - 215 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 217) WITH PRESSURE/VACUUM VALVE |
| N-956 - 216 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 218) WITH PRESSURE/VACUUM VALVE |
| N-956 - 217 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 219) WITH PRESSURE/VACUUM VALVE |
| N-956 - 218 - 3 | : 19,500 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 220) WITH PRESSURE/VACUUM VALVE |
| N-956 - 236 - 1 | : 20,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 237 - 1 | : 20,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 238 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 239 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 240 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 241 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 242 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 243 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 244 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 245 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 246 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 247 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |
| N-956 - 248 - 1 | : 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |

PROJECT EQUIPMENT DESCRIPTIONS

| PERMIT NO. | EQUIPMENT DESCRIPTION |
|-----------------|---|
| N-956 - 249 - 1 | 14,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK WITH PRESSURE/VACUUM VALVE |

ATTACHMENT B

Proposed Modified Title V Operating Permit No.

N-956-6-5, -11-3 through -40-3, -43-3 through -
218-3, and -236-1 through -249-1

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-6-5

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

17.5 MMBTU/HR HURST SERIES 400 PROPANE-FIRED BOILER WITH AN ALZETA MODEL CSB252 ULTRA LOW NOX BURNER AND INDUCED FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on propane (LPG). [District NSR Rule] Federally Enforceable Through Title V Permit
4. Emissions rates shall not exceed any of the following limits: 9 ppmvd NOx @ 3% O2 or 0.011 lb-NOx/MMBtu, 0.0024 lb-SOx/MMBtu, 0.0066 lb-PM10/MMBtu, 100 ppmvd CO @ 3% O2 or 0.074 lb-CO/MMBtu, or 0.004 lb-VOC/MMBtu. [District NSR Rule, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
5. The permittee shall monitor and record the stack concentration of NOX, CO, and O2 at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within five days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than one hour of operation after detection. If the portable analyzer show that the emissions continue to exceed the allowable levels after one hour of operation after detection, the permittee shall notify the District within the following one hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
7. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
9. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rules 4320 (amended 10/16/08). [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
10. On and after July 1, 2012, the permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit
11. Source testing to measure propane combustion NO_x and CO emissions from this unit shall be conducted at least once every 12 months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once every 36 months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every 12 months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
15. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
16. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. Stack gas velocities for source test purposes shall be determined using EPA Method 2. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. Stack gas moisture content for source test purposes shall be determined using EPA Method 4. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
21. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
22. The boiler must be fitted with a revised identification plate indicating the re-rated rating, in MMBtu per hour. [District NSR Rule] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
24. The permittee shall keep daily records of the amount of natural gas combusted for a period of five years, and shall make records available for inspection upon request. [District Rule 2520, 9.4.2, and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-11-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

15,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK B1 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-12-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

15,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK B2 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-13-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

10,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 24 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-14-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

10,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 39 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-15-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 44 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-16-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 45 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-17-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 46 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-18-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 47 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-19-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 48 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-20-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 49 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-21-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 50 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-22-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 51 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-23-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 52 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-24-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 53 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-25-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 54 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred; shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-26-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

20,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 55 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-27-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 56 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-28-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 57 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-29-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 58 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-30-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 59 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-31-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

60,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 60 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-32-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

12,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 62 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-33-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 116 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-34-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 117 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-35-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

120,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 118 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-36-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

15,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 131 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-37-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

15,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 132 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-38-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 133 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-39-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 134 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-40-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

30,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 135 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-43-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1001 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-44-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-45-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1003 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-46-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1004 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-47-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-48-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-49-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-50-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-51-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-52-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-53-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

105,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-54-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-55-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1014 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-56-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1015 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-57-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1016 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-58-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1017 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-59-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1018 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-60-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1019 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-61-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1020 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: THE WINE GROUP, INC.

Location: 17000 E HIGHWAY 120, RIPON, CA 95366

N-956-61-3 : Oct 13 2010 11:12AM - SONGCOJ

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-62-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1021 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-63-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1022 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-64-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1023 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-65-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1024 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-66-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

106,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1025 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-67-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1026 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-68-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1027 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-69-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1028 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-70-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1029 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-71-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

103,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1030 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed twice the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-72-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2001 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-73-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-74-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2003 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-75-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2004 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-76-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-77-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-78-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-79-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-80-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-81-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2010 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-82-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-83-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-84-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-85-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2014 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-86-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2015 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-87-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2016 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-88-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

218,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2017 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: THE WINE GROUP, INC.

Location: 17000 E HIGHWAY 120, RIPON, CA 95366

N-956-88-3 - Oct 13 2010 11 13AM -- SIONGCOJ

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-89-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2018 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 581,212 lb. [District NSR Rule] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District NSR Rule] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit
17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District NSR Rule, 1070, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-956-90-3

EXPIRATION DATE: 09/30/2014

EQUIPMENT DESCRIPTION:

217,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2019 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for red wine fermentation shall not exceed 3.46 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for white wine fermentation shall not exceed 1.62 lb/1000 gallons. [District NSR Rule] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District NSR Rule and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District NSR Rule and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District NSR Rule] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed the maximum nominal tank capacity stated in the equipment description. [District NSR Rule] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.