

Bay Area Air Quality Management District

939 Ellis Street
San Francisco, CA 94109
(415) 771-6000

Proposed

MAJOR FACILITY REVIEW PERMIT

Issued To:

C & H Sugar Company, Inc
Facility #B1911

Facility Address:

830 Loring Avenue
Crockett, CA 94525

Mailing Address:

830 Loring Avenue
Crockett, CA 94525

Responsible Official

David G. Koncelik,
President and CEO

Facility Contact

R. Stephen Ball
Manager, Engineering/Operations Services
(510) 787-4343

Type of Facility: Sugar Manufacturing
Primary SIC: 2062
Product: Refined Sugar Products

BAAQMD Permit Division Contact:
Ted Hull, Air Quality Engineer II

ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT

Ellen Garvey, Executive Officer/Air Pollution Control Officer

Date

Draft

h:\pub_data\titlev\permit\f-draft\b1911.doc
Application #16483
02/08/2001 2:09 PM

TABLE OF CONTENTS

I. STANDARD CONDITIONS	3
II. EQUIPMENT	7
III. GENERALLY APPLICABLE REQUIREMENTS	22
IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS	24
V. PERMIT CONDITIONS	67
VI. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS	82
VII. TEST METHODS	118
VIII. SCHEDULE OF COMPLIANCE	67
IX. PERMIT SHIELD	119
X. GLOSSARY	120
XI. APPLICABLE STATE IMPLEMENTATION PLAN	124

I. STANDARD CONDITIONS

A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

- BAAQMD Regulation 1 - General Provisions and Definitions
(as amended by the District Board on 11/15/00);
- SIP Regulation 1 - General Provisions and Definitions
(as approved by EPA through 8/27/99);
- BAAQMD Regulation 2, Rule 1 - Permits, General Requirements
(as amended by the District Board on 11/15/00);
- SIP Regulation 2, Rule 1 - Permits, General Requirements
(as approved by EPA through 2/25/99);
- BAAQMD Regulation 2, Rule 2 - Permits, New Source Review
(as amended by the District Board on 5/17/00);
- SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration
(as approved by EPA through 2/25/99);
- BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking
(as amended by the District Board on 5/17/00); and
- SIP Regulation 2, Rule 4 - Permits, Emissions Banking
(as approved by EPA through 2/25/99).
- BAAQMD Regulation 2, Rule 6 - Permits, Major Facility Review
(as amended by the District Board on 10/20/99).

B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit was issued on [] and expires on [when issued, enter 5th anniversary of issue date]. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than [when issued, enter date 6 months prior to permit expiration date] and no earlier than [when issued, enter date 12 months prior to expiration date]. **If a complete application for renewal has not been submitted in accordance with these deadlines, the facility may not operate after** [when issued, enter 5th anniversary of issue date]. (Regulation 2-6-307, 404.2, & 409.6; MOP Volume II, Part 3, §4.2)
2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and re-issuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part

I. Standard Conditions

- 3, §4.11)
4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)
 5. The filing of a request by the facility for a permit modification, revocation and re-issuance, or termination, or of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
 6. This permit does not convey any property rights of any sort, nor any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
 7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
 8. Any records required to be maintained pursuant to this permit which the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
 9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
 10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)

C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment which is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

E. Records

Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of

I. Standard Conditions

entry. (Regulation 2-6-501, Regulation 3; MOP Volume II, Part 3, §4.7)

F. Monitoring Reports

Reports of all required monitoring must be submitted to the District at least once every six months, except where an applicable requirement specifies more frequent reporting. The first reporting period for this permit shall be [date of issuance] to [six months later]. The report shall be submitted by [one month after end of reporting period]. Subsequent reports shall be for the following periods: [_____ 1st through _____ 30th or 31st] and [_____ 1st through _____ 30th or 31st], and are due on the last day of the month after the end of the reporting period. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported in writing to the District's Compliance and Enforcement Division within 10 calendar days of the discovery of the incident. Within 30 calendar days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. The reports shall be sent to the following address:

Director of Compliance and Enforcement
Bay Area Air Quality Management District
939 Ellis Street
San Francisco, CA 94109
Attn: Title V Reports

(Regulation 2-6-502, Regulation 3; MOP Volume II, Part 3, §4.7)

G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification period will be _____ 1st to _____ 30th or 31st. The certification shall be submitted by _____ 30th or 31st of each year. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms. The certification should be directed to the District's Compliance and Enforcement Division at the address above, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

Director of the Air Division
USEPA, Region IX
75 Hawthorne Street
San Francisco, CA 94105
Attention: Air-3

(MOP Volume II, Part 3, §4.5 and 4.15)

I. Standard Conditions

H. Emergency Provisions

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit caused by conditions beyond the permit holder's reasonable control by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. Any variance granted by the Hearing Board from any term or condition of this permit which lasts longer than 90 days will be subject to EPA approval. (MOP Volume II, Part 3, §4.8)
3. Notwithstanding the foregoing, the granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement. (MOP Volume II, Part 3, §4.8)

I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

J. Miscellaneous Conditions

1. The maximum capacity for each source as shown in Table II-A is the maximum allowable capacity. Exceedance of the maximum allowable capacity for any source is a violation of Regulation 2, Rule 1, Section 301. (Regulation 2-1-301)

II. EQUIPMENT

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits.

S#	Description	Make or Type	Model	Capacity
201	Warehouse Sugar Recovery System	Cambelt Conveyor System	N/A	1 TPH
202	PSS Vacuum Cleaning System	Lamson Exidust Vacuum System	E7V-AD	2 TPH
203	Powdered Carton Packaging Station	Bosch Carton Filler	H-PLD1	3.6 TPH
204	Powdered C/P Packaging Station	Bosch VFFS	SVB 2500	4.8 TPH
205	Powdered Bulk Pack Station	St. Regis Packer	N/A	24 TPH
206	Mikro-Pulverizers (4 units)	Mikro	N/A	1.5 TPH each
207	Fondant Bulk Packer	C&H Fabricated Fill Station	N/A	3 TPH
208	Pulverizer Bin and Conveyors	C&H Fabricated Conveyors/Bin	N/A	47 TPH
209	Pulverizer – Powdered, P1	Baurmeister	AP 80	3 TPH
210	Pulverizer – Powdered, P2	Baurmeister	AP 80	3 TPH
211	Pulverizer – Powdered, P3	Baurmeister	AP 80	3 TPH
212	Pulverizer – Powdered, P4	Baurmeister	AP 80	3 TPH
213	Pulverizer – Fondant, F1	Baurmeister	AP 80	0.9 TPH
214	Pulverizer – Fondant, F2	Baurmeister	AP 80	0.9 TPH
215	Starch Unloading Facility	Schwitzer Air Pump	4509	21 TPH
216	Starch Conveying System	Schwitzer Air Pump	4509	6 TPH
217	Paper Baler, Bosch 12/5 Statopm	Maren Baler	423	0.5 TPH
218	Bosch 12/5 Packing Station, #1	Bosch Form/Fill Machine	H-PLDDBR30E	54 TPH
219	Bosch 12/5 Packing Station, #2	Bosch Form/Fill Machine	H-PLDDBR30E	54 TPH
220	Bosch 12/5 Packing Station, #3	Bosch Form/Fill Machine	H-PLDDBR30E	54 TPH
221	Melt Tank Bosch 12/5 Station	C&H Fabricated Melt Tank	N/A	12 TPH
222	Confectioners Dryer	Standard Steel Corp. 5' x 28' LG Dryer	N/A	5.3 TPH

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits.

S#	Description	Make or Type	Model	Capacity
223	Packing House No. 1 Vacuum System	Lamson Vacuum Blower	N/A	0.03 TPH
224	Bulk Sugar Loading	DCL Loading Spouts	EV24-7-2-1111114	75 TPH
225	Steel Silos Conveying to Bulk Loadout	Bucket Elevator 0E, 80 Ft	N/A	37.5 TPH
226	Concrete Silos Conveying to Bulk Loadout	Bucket Elevator 3E, 50 Ft and 4E, 70 Ft	N/A	26 TPH
227	Concrete Silos Bulk Granulated System	Bucket Elevator 1E, 108 Ft and E 142 Ft. – Concrete Silos #1 and #2	N/A	75 TPH
228	Drivert Production	Centri-Sonic Classifier Bauermeister Pulverizer Schutz-O'Neil Pulverizer Rexnord Blejoer & Dryer	Various	3.1 TPH
229	Scrap Paper Recovery	Lake Engineering Paper Baler	N/A	0.25 TPH
230	No. 1 Granulator (Upper/Lower)	Hersey Mfg. Co.	N/A	16.7 TPH
231	No. 2 Granulator (Upper/Lower)	Hersey Mfg. Co.	N/A	16.7 TPH
232	No. 3 Granulator (Upper/Lower)	Hersey Mfg. Co.	N/A	16.7 TPH
233	No. 4 Granulator (Upper/Lower)	Hersey Mfg. Co.	N/A	16.7 TPH
234	No. 5 Granulator (Upper/Lower)	Standard Steel Corp.	S-6X33-0	37.5 TPH
235	No. 6 Granulator (Upper/Lower)	Hersey Mfg. Co.	N/A	16.7 TPH
236	No. 7 Granulator (Upper/Lower)	Sterns-Roger	N/A	31.3 TPH
240	Screened Sugar Distribution	C&H Fabricated Screw Conveyors and Bins	N/A	170 TPH

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits.

S#	Description	Make or Type	Model	Capacity
241	Confectioners Sugar Distribution	C&H Fabricated Bin	N/A	10 TPH
242	Small Pack Distribution	C&H Fabricated Bin	N/A	85 TPH
243	No. 1 Bemis Packer	Bemis	7115	30 TPH
244	No. 2 Bemis Packer	Bemis	7115	30 TPH
245	No. 3 Bemis Packer	Bemis	7115	30 TPH
246	Supersack Storage Bin	C&H Fabricated Bin	N/A	30 TPH
247	Dry Unscreened Sugar Surge	C&H Fabricated Bin	N/A	125 TPH
248	Fines Collection	C&H Fabricated Bin	N/A	12 TPH
249	Coarse Collection	C&H Fabricated Bin	N/A	14 TPH
250	Herreshoff Char Furnace, Natural Gas Fired	Nichols-Herreshoff, 25 Ft x 9 Hearths	N/A	30 MMBTU/hr
252	Bulk Bins #11 - #15	Five 63 Ton Bins	N/A	20 TPH
253	Bulk Bins #6 - #10	Five 63 Ton Bins	N/A	20 TPH
254	Bulk Bins #1 - #5	Four 45 Ton Bins and One 50 Ton Bin	N/A	25 TPH
255	Paper Shredder	Bloapco Shredder	3CXS-1036VA	2 TPH
256	Paint Spray Booth	Unknown	N/A	4,500 CFM
257	Bulk Granulated Silo A	260 Ton Steel Silo	N/A	25 TPH
258	Bulk Granulated Silo B	260 Ton Steel Silo	N/A	25 TPH
259	Bulk Granulated Silo C	260 Ton Steel Silo	N/A	25 TPH
260	Bulk Granulated Silo D	260 Ton Steel Silo	N/A	25 TPH
261	Vibro Sugar Conveying/Storage	C&H Fabricated Conveyors and Storage	N/A	2.2 TPH
262	12/5 Sugar Conveying/Storage	King Bearing Conveyors	N/A	60 TPH
263	Drivert Packer	Aypac In Line Powder Packer	N/A	15 TPH
264	Airveyor Bin	Sutorbilt Airpump	4LV	47 TPH
265	No. 2 Airveyor	Sutorbilt Airpump	820-4500	7 TPH
266	No. 1 Airveyor	Sutorbilt Airpump	820-4500	7 TPH
267	PSS Sugar Recovery	C&H Fabricated Conveyors	N/A	9 TPH
268	No. 1 6/10 Hesser Packer	Hesser/Bosch Packer	S-PDHBR5e	12 TPH

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits.

S#	Description	Make or Type	Model	Capacity
269	No. 2 6/10 Hesser Packer	Hesser/Bosch Packer	S-PDHBR5e	12 TPH
270	Vibro Cube Packaging	Hesser Carton Filler	N/A	2.2 TPH
271	Warehouse/PSS Melt Tank (Dry Sugar)	C&H Fabricated Melt System	N/A	3.4 TPH
272	Vibro Cube Molding	Buckau R. Wolf Cube Molder	N/A	2.2 TPH
273	Bulk Granulated Elevator 1A	Bucket Elevator 1A, 80 Ft	N/A	10.83 TPH
274	Bulk Granulated Elevator 1	Bucket Elevator 1A, 80 Ft	N/A	10.83 TPH
275	Bulk Granulated Elevator 2	Bulk Elevator 2, 41 Ft	N/A	2.5 TPH
276	Custom Products Handling	Littleford Mixer and Sweco Screener	N/A	1 TPH
278	Carpenter Shop Saw Dust	Unknown	N/A	6,000 CFM
279	Tailings Melt Tank	C&H Fabricated Tank	N/A	11 TPH
280	Diatomaceous Earth Storage Silo	Butler 150 Ton	N/A	0.2 TPH
281	West DE Metering Bin	C&H Design 4 Ton Bin	N/A	0.05 TPH
282	East DE Metering Bin	C&H Design 4 Ton Bin	N/A	0.05 TPH
284	Lime Unloading Station	Tec Tank Silo, 40 Ton	N/A	0.15 TPH
285	Mothers' Dryer (Bulk Sugar Cooler)	Carrier Fluid Bed Cooler	QAC-6065	15 TPH
286	Carbon Regeneration Furnace, Natural Gas Fired	MHF Services	Low NOx	4.7 MMBTU/hr
288	Spent Char Handling System	Fluid Bed Dryers, Dewatering Belts	N/A	21.3 TPH
289	Regenerated Char Handling System	Regenerated Char Conveyor, Specific Gravity Separator	N/A	21.3 TPH
301	Surge Basin	Jet Tech Aerating Equipment	N/A	0.112 MGH
303	(3) Aeration Basins	Pego	7HL	0.112 MGH
304	(2) Clarifiers	Unknown	N/A	0.112 MGH
305	Chlorination/ Dechlorination Basin	Unknown	N/A	0.112 MGH

II. Equipment

Table II A - Permitted Sources

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits.

S#	Description	Make or Type	Model	Capacity
307	Liming System for Filter Cake	Seneca Bag Filter, Roediger Mixer	16-1M LPT249	0.1 TPH
330	Rotex Screen A	Rotex	554	25 TPH
331	Rotex Screen B	Rotex	554	25 TPH
332	Rotex Screen C	Rotex	554	18 TPH
333	Rotex Screen D	Rotex	554	18 TPH
334	Rotex Screen E	Rotex	554	18 TPH
335	Rotex Screen F	Rotex	554	18 TPH
336	Rotex Screen G	Rotex	554	18 TPH
337	Rotex Screen H	Rotex	554	18 TPH
338	Rotex Screen 1	Rotex	554	18 TPH
340	Rotex Screen 3	Rotex	554	18 TPH
341	Rotex Screen 4	Rotex	554	18 TPH
342	Rotex Screen 5	Rotex	554	18 TPH
343	Rotex Screen 6	Rotex	554	18 TPH
344	Rotex Screen 7	Rotex	554	18 TPH
345	Rotex Screen 8	Rotex	554	18 TPH
346	Rotex Screen 9	Rotex	554	18 TPH

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A201	Mikropulsaire Baghouse	S201	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A202	Mikropulsaire Baghouse	S201, S267	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A203	Lamson Exidust 2-Stage Baghouse	S202	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A204	Mikropulsaire Baghouse (3 Units in Parallel)	S203, S204, S205, S206, S207, S208	BAAQMD: Regulation 6-301, 6-310; Condition #15205	Pressure Drop Range	Ringelmann #1; 0.01 gr/dscf
A205	Pulverizer Baghouse	S209	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A206	Pulverizer Baghouse	S210	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A207	Pulverizer Baghouse	S211	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A208	Pulverizer Baghouse	S212	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A209	Pulverizer Baghouse	S213	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A210	Pulverizer Baghouse	S214	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A211	Semco Dust Collector	S215	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A212	Semco Dust Collector	S216	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A213	Saunco Cyclone	S217	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A213	Saunco Cyclone	S218, S219, S220	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A214	Mikropulsaire Baghouse	S218, S219, S220, S262	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A215	Duncon Cyclone	S222	None	None	N/A
A216	Lamson Exidust 2-Stage Baghouse	S223	BAAQMD Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A217	American Air Filter, Rotoclone	S224	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A218	American Air Filter, Rotoclone	S225, S226	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A219	American Air Filter, Rotoclone	S226	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A220	American Air Filter, Rotoclone	S227	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A221	American Air Filter, Rotoclone	S227	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A222	American Air Filter, Rotoclone	S227	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A223	American Air Filter, Rotoclone	S227	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A224	American Air Filter, Baghouse	S228	BAAQMD: Regulation 6-301, 6-310; Condition #15886	None	Ringelmann #1; 0.15 gr/dscf

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A225	American Air Filter, Baghouse	S228	BAAQMD: Regulation 6-301, 6-310; Condition #15886	None	Ringelmann #1; 0.15 gr/dscf
A226	Mikropulsaire Baghouse	S228	BAAQMD: Regulation 6-301, 6-310; Condition #15886	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A227	Mikropulsaire Baghouse	S228	BAAQMD: Regulation 6-301, 6-310; Condition #15886	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A228	Wesco Cyclone	S229, S268, S269	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A229	Sugar Recovery Chambers	S230	Condition #14395	None	N/A
A231	Sugar Recovery Chambers	S231	Condition #14395	None	N/A
A233	Sugar Recovery Chambers	S232	Condition #14395	None	N/A
A235	Sugar Recovery Chambers	S233	Condition #14395	None	N/A
A237	Rotoclone Wet Centrifugal Collector	S234	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A238	Sugar Recovery Chambers	S235	Condition #14395	None	N/A

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A240	Rotoclone Wet Centrifugal Collector	S236	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A241	Sugar Recovery Chambers	S230	Condition #14395	None	N/A
A243	Sugar Recovery Chambers	S231	Condition #14395	None	N/A
A245	Sugar Recovery Chambers	S232	Condition #14395	None	N/A
A247	Sugar Recovery Chambers	S233	Condition #14395	None	N/A
A249	Skimmer	S234	Condition #14395	None	N/A
A250	Rotoclone Wet Centrifugal Collector	S234	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A251	Sugar Recovery Chambers	S235	Condition #14395	None	N/A
A253	Skimmer	S236	Condition #14395	None	N/A
A254	Rotoclone Wet Centrifugal Collector	S236	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A257	Ninth Floor Sugar Surge Cyclones	S246, S247, S248, S249	None	None	N/A
A258	Ninth Floor Sugar Surge Wet Scrubber	S246, S247, S248, S249	BAAQMD: Regulation 6-301, 6-310;	Liquid Flow Rate, Pressure Drop	Ringelmann #1; 0.15 gr/dscf

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A259	Char Furnace Wet Scrubber	S250	BAAQMD: Regulation 6-301, 6-310;	Liquid Flow Rate, Pressure Drop	Ringelmann #1; 0.15 gr/dscf
A260	American Air Filter, Rotoclone	S252	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A261	American Air Filter, Rotoclone	S253	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A262	American Air Filter, Rotoclone	S254	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A263	Mikropulsaire Baghouse	S243, S244, S245, S255	BAAQMD: Regulation 6-301, 6-310;	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A264	American Air Filter, Rotoclone	S257	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A265	American Air Filter, Rotoclone	S258	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A266	American Air Filter, Rotoclone	S259	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A267	American Air Filter, Rotoclone	S260	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A268	Mikropulsaire Baghouse	S228	BAAQMD: Regulation 6-301, 6-310; Condition #15886	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A269	Mikropulsaire Baghouse	S228	BAAQMD: Regulation 6-301, 6-310; Condition #15886	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A270	Clean Air Baghouse	S263	BAAQMD: Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A271	Mikropulsaire Baghouse	S264	BAAQMD: Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A272	Mikropulsaire Baghouse	S265	BAAQMD: Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A273	Mikropulsaire Baghouse	S266	BAAQMD: Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A274	American Air Filter, Rotoclone	S249, S268, S269	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A275	Vibro Cube Packing Cyclone	S270	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A276	American Air Filter, Rotoclone	S261	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A277	Vibro Cube Molding Mist Eliminator	S272	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A278	American Air Filter, Rotoclone	S273	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A279	American Air Filter, Rotoclone	S274	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A280	American Air Filter, Rotoclone	S275	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A281	American Air Filter, Rotoclone	S276	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A282	Carpenter Shop Saw Dust Cyclone	S278	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A283	Tailings Melt Mist Eliminator	S279	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A284	Dust Collector	S280	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A285	Dust Collector	S281	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A286	Dust Collector	S282	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A287	Bin Vent Filter	S284	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A288	Mikropulsaire Baghouse	S285	BAAQMD: Regulation 6-301, 6-310; Condition #14649	Pressure Drop Range	Ringelmann #1; 0.011 gr/dscf
A289	Afterburner	S286	BAAQMD Regulation 8-2-301, Condition #13308, Condition #17430	None	None

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A290	Wet Scrubber	S286	BAAQMD: Regulation 6-301, 6-310; Condition #13308	Liquid Flow Rate, Pressure Drop	Ringelmann #1; 0.15 gr/dscf
A291	Vacuum Receiver	S288	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A292	Mikropulsaire Baghouse	S289	BAAQMD: Regulation 6-301, 6-310	Pressure Drop Range	Ringelmann #1; 0.15 gr/dscf
A293	American Air Filter, Rotoclone	S222	BAAQMD Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A294	American Air Filter, Skimmer	S230	Condition #14395	None	N/A
A295	American Air Filter, Rotoclone	S230	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A296	American Air Filter, Skimmer	S231, S232	Condition #14395	None	N/A
A297	American Air Filter, Rotoclone	S231, S232	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A298	American Air Filter, Skimmer	S233, S235	Condition #14395	None	N/A
A299	American Air Filter, Rotoclone	S233, S235	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A301	Reactor Basins #2 and #3	S301	None	None	None

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A302	American Air Filter, Rotoclone	S230	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A303	American Air Filter, Rotoclone	S231, S232	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A304	American Air Filter, Rotoclone	S233, S235	BAAQMD: Regulation 6-301, 6-310; Condition #14395	None	Ringelmann #1; 0.15 gr/dscf
A307	Lime Silo Bin Vent Filter	S307	BAAQMD: Regulation 6-301, 6-310; Condition #14650	None	Ringelmann #1; 0.15 gr/dscf
A311	American Air Filter, Rotoclone	S261, S262	BAAQMD: Regulation 6-301, 6-310	None	Ringelmann #1; 0.15 gr/dscf
A312	5 th Floor Packing House Skimmer	S230, S231, S232, S233, S234, S235, S236, S240, S241, S242, S330, S331, S332, S333, S334, S335, S336, S337, S338, S340, S341, S342, S343, S344, S345, S346	Condition #17641	None	None

II. Equipment

Table II B – Abatement Devices

A#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Required Efficiency
A313	American Air Filter, Rotoclone	S230, S231, S232, S233, S234, S235, S236, S240, S241, S242, S330, S331, S332, S333, S334, S335, S336, S337, S338, S340, S341, S342, S343, S344, S345, S346	BAAQMD: Regulation 6-301, 6-310; Condition #17641	None	Ringelmann #1; 0.15 gr/dscf

III. GENERALLY APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements would not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit.

The dates in parenthesis in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full language of SIP requirements is included in Appendix A of this permit if the SIP requirement is different from the current BAAQMD requirement.

NOTE:

There are differences between the current BAAQMD rules and the version of the rules in the SIP. For specific information, contact the District's Rule Development Section of the Enforcement Division. All sources must comply with both versions of the rule until US EPA has reviewed and approved the District's revision of the regulation.

**Table III
 Generally Applicable Requirements**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 1	General Provisions and Definitions (5/17/00)	N
SIP Regulation 1	General Provisions and Definitions (8/27/99)	Y
BAAQMD Regulation 4	Air Pollution Episode Plan (3/20/91)	N
SIP Regulation 4	Air Pollution Episode Plan (8/06/90)	Y
BAAQMD Regulation 5	Open Burning (11/2/94)	N
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	Y
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds - General Provisions (6/15/94)	Y

III. Generally Applicable Requirements

Table III
Generally Applicable Requirements

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)
BAAQMD Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (12/20/95)	Y
BAAQMD Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (3/22/95)	Y
BAAQMD Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (12/20/95)	N
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants - Asbestos Demolition, Renovation and Manufacturing (12/4/91)	Y
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (7/11/90)	Y

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parenthesis in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. The full language of SIP requirements is included in Appendix A of this permit if the SIP requirements are different from the current BAAQMD requirements. All other text may be found in the regulations themselves.

Table IV - A
Source-specific Applicable Requirements
S201, S267: WAREHOUSE/PSS SUGAR RECOVERY

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A201, A202		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	

IV. Source-specific Applicable Requirements

Table IV - A
Source-specific Applicable Requirements
S201, S267: WAREHOUSE/PSS SUGAR RECOVERY

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - B
Source-specific Applicable Requirements
S202: PSS VACUUM CLEANING SYSTEM

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A203		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		

IV. Source-specific Applicable Requirements

Table IV - B
Source-specific Applicable Requirements
S202: PSS VACUUM CLEANING SYSTEM

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - C
Source-specific Applicable Requirements
S203, S205, S206, S207, S208: POWDERED SUGAR PACKAGING OPERATIONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A204		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

IV. Source-specific Applicable Requirements

Table IV - D
Source-specific Applicable Requirements
S204: POWDERED C/P PACKER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Cond #15205			
part 1	Abatement Requirement for S204 [BACT]	Y	
part 2	Baghouse Outlet Grain Loading Limit [BACT]	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A204		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

IV. Source-specific Applicable Requirements

Table IV - E
Source-specific Applicable Requirements
S209, S210, S211, S212, S213, S214: POWDERED/FONDANT SUGAR PULVERIZERS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A205, A206, A207, A208, A209, A210		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - F
Source-specific Applicable Requirements
S215, S216: STARCH UNLOADING/CONVEYING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
------------------------	--	-----------------------------	-----------------------

IV. Source-specific Applicable Requirements

Table IV - F
Source-specific Applicable Requirements
S215, S216: STARCH UNLOADING/CONVEYING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17426			
part 1	Particulate Abatement Requirement for S215 [Regulation 2-1-403]	Y	
part 2	Particulate Abatement Requirement for S216 [Regulation 2-1-403]	Y	
part 3	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - G
Source-specific Applicable Requirements
S217: PAPER BALER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	

IV. Source-specific Applicable Requirements

**Table IV - G
 Source-specific Applicable Requirements
 S217: PAPER BALER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17427	Inspection Requirements for Cyclone: A213		
part 1	Proper Cyclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

**Table IV - H
 Source-specific Applicable Requirements
 S218, S219, S220: PACKAGING STATIONS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

**Table IV - H
 Source-specific Applicable Requirements
 S218, S219, S220: PACKAGING STATIONS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A214		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

**Table IV - I
 Source-specific Applicable Requirements
 S221: MELT TANK**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17690	General Throughput Limits		

IV. Source-specific Applicable Requirements

**Table IV - I
 Source-specific Applicable Requirements
 S221: MELT TANK**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

**Table IV - J
 Source-specific Applicable Requirements
 S222: CONFECTIONERS DRYER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A293		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

IV. Source-specific Applicable Requirements

**Table IV - K
 Source-specific Applicable Requirements
 S223: PACKING HOUSE #1 VACUUM SYSTEM**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A216		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

**Table IV - L
 Source-specific Applicable Requirements
 S224: BULK SUGAR LOADING**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		

IV. Source-specific Applicable Requirements

**Table IV - L
 Source-specific Applicable Requirements
 S224: BULK SUGAR LOADING**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Cond #15206			
part 1	Sugar Throughput Limit [Cumulative Increase]	Y	
part 2	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A217		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

**Table IV - M
 Source-specific Applicable Requirements
 S225: STEEL SILOS CONVEYING TO BULK LOADOUT**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	

IV. Source-specific Applicable Requirements

Table IV - M
Source-specific Applicable Requirements
S225: STEEL SILOS CONVEYING TO BULK LOADOUT

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A218		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - N
Source-specific Applicable Requirements
S226, 227: CONCRETE SILOS, CONVEYING, BULK LOADOUT

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A218 A219, A220, A221, A222, A223		

IV. Source-specific Applicable Requirements

Table IV - N
Source-specific Applicable Requirements
S226, 227: CONCRETE SILOS, CONVEYING, BULK LOADOUT

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - O
Source-specific Applicable Requirements
S228: DRIVERT PRODUCTION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Cond #15886			
part 1	Sugar Throughput Limit [Cumulative Increase]	Y	
part 2	Abatement Requirements [Regulation 2-1-403]		
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A224, A225, A226, A227, A268, A269		

IV. Source-specific Applicable Requirements

Table IV - O
Source-specific Applicable Requirements
S228: DRIVERT PRODUCTION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

IV. Source-specific Applicable Requirements

Table IV - P
Source-specific Applicable Requirements
S229: SCRAP PAPER RECOVERY

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17427	Inspection Requirements for Cyclone: A228		
part 1	Proper Cyclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - Q
Source-specific Applicable Requirements
S230, S231, S232, S233, S234, S235, S236: GRANULATORS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	

IV. Source-specific Applicable Requirements

Table IV - Q
Source-specific Applicable Requirements
S230, S231, S232, S233, S234, S235, S236: GRANULATORS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #14395			
part 1	S230 Upper Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 2	S230 Lower Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 3	S231 Upper Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 4	S231 Lower Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 5	S232 Upper Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 6	S232 Lower Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 7	S233 Upper Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 8	S233 Lower Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 9	S234 Upper Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 10	S234 Lower Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 11	S235 Upper Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 12	S235 Lower Granulator Abatement Requirements [Regulation 2-1-403]	Y	
part 13	S236 Upper Granulator Abatement Requirements [Regulation 2-1-403]	Y	

IV. Source-specific Applicable Requirements

Table IV - Q
Source-specific Applicable Requirements
S230, S231, S232, S233, S234, S235, S236: GRANULATORS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
part 14	S236 Lower Granulator Abatement Requirements [Regulation 2-1-403]	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A237, A240 A250, A254 A295, A297, A299, A302, A303, A304, A313		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - R
Source-specific Applicable Requirements
S240, S241, S242: 5TH FLOOR DISTRIBUTION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

Table IV - R
Source-specific Applicable Requirements
S240, S241, S242: 5TH FLOOR DISTRIBUTION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A313		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - S
Source-specific Applicable Requirements
S243, S244: BEMIS PACKERS #1 AND #2

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A263		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	

IV. Source-specific Applicable Requirements

Table IV - S
Source-specific Applicable Requirements
S243, S244: BEMIS PACKERS #1 AND #2

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - T
Source-specific Applicable Requirements
S245, S255: BEMIS PACKER #3 AND 1ST FLOOR SHREDDER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A263		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	

IV. Source-specific Applicable Requirements

Table IV - T
Source-specific Applicable Requirements
S245, S255: BEMIS PACKER #3 AND 1ST FLOOR SHREDDER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - U
Source-specific Applicable Requirements
S246, S247, S248, S249: DRY UNSCREENED SUGAR SURGE OPERATIONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17430	Inspection and Maintenance Requirements for Wet Scrubbers: A258		
part 1	Proper Scrubber Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Operating Parameters [Regulation 2-1-403]	Y	
part 3	Weekly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	

IV. Source-specific Applicable Requirements

Table IV - U
Source-specific Applicable Requirements
S246, S247, S248, S249: DRY UNSCREENED SUGAR SURGE OPERATIONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - V
Source-specific Applicable Requirements
S250: CHAR FURNACE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-310.3	Heat Transfer Operations	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (6/15/94)		
8-2-301	Organic Compounds Emissions Limits	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-302	General Emissions Limitation	Y	

IV. Source-specific Applicable Requirements

**Table IV - V
 Source-specific Applicable Requirements
 S250: CHAR FURNACE**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17430	Inspection and Maintenance Requirements for Wet Scrubbers: A259		
part 1	Proper Scrubber Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Operating Parameters [Regulation 2-1-403]	Y	
part 3	Weekly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

**Table IV - W
 Source-specific Applicable Requirements
 S252, S253, S254: BULK BINS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A260, A261, A262		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	

IV. Source-specific Applicable Requirements

Table IV - W
Source-specific Applicable Requirements
S252, S253, S254: BULK BINS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - X
Source-specific Applicable Requirements
S256: PAINT SPRAY BOOTH

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 19	Organic Compounds – Surface Coating of Miscellaneous Metal Parts and Products (12/20/95)		
8-19-302	Coating VOC Limits	Y	
8-19-307	Prohibition of Specification	Y	
8-19-312	Specialty Coating VOC Limits	Y	
8-19-313	Spray Application Equipment Limitations	Y	
8-19-313.1	HVLP Spray; or	Y	
8-19-313.2	Electrostatic Spray; or	Y	
8-19-313.3	Detailing Gun; or	Y	
8-19-313.4	Other Method Approved in Writing by the APCO	Y	
8-19-320	Solvent Evaporative Loss Minimization	Y	
8-19-320.1	Storage and Disposal of Solvent Impregnated Cloth or Paper	Y	
8-19-320.2	No Organic Compounds for Cleanup of Spray Equipment Unless Controls are Used	Y	
8-19-320.3	Closed Containers for Coatings or Solvents Not in Use	Y	
8-19-501	Records	Y	

IV. Source-specific Applicable Requirements

**Table IV - X
 Source-specific Applicable Requirements
 S256: PAINT SPRAY BOOTH**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-19-501.1	Maintain Data Necessary to Evaluate Compliance	Y	
8-19-501.2	Weekly Coating Usage Records	Y	
8-19-501.4	Monthly Cleaning Solvent Records	Y	
8-19-501.5	Records Retention	Y	

**Table IV - Y
 Source-specific Applicable Requirements
 S257, S258, S259, S260: BULK GRANULATED SILOS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A264, A265, A266, A267		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

IV. Source-specific Applicable Requirements

Table IV - Z
Source-specific Applicable Requirements
S261: VIBRO CONVEYING/STORAGE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A276, A311		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - AA
Source-specific Applicable Requirements
S262: 12/5 SUGAR CONVEYING/STORAGE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		

IV. Source-specific Applicable Requirements

Table IV - AA
Source-specific Applicable Requirements
S262: 12/5 SUGAR CONVEYING/STORAGE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A214		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A311		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - BB
Source-specific Applicable Requirements
S263: DRIVERT PACKER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
------------------------	--	-----------------------------	-----------------------

IV. Source-specific Applicable Requirements

Table IV - BB
Source-specific Applicable Requirements
S263: DRIVERT PACKER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A270		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - CC
Source-specific Applicable Requirements
S264, S265, S266: AIRVEYORS/AIRVEYOR BIN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	

IV. Source-specific Applicable Requirements

Table IV - CC
Source-specific Applicable Requirements
S264, S265, S266: AIRVEYORS/AIRVEYOR BIN

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A271, A272, A273		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - DD
Source-specific Applicable Requirements
S268, S269: 6/10 HESSER PACKAGING STATIONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	

IV. Source-specific Applicable Requirements

Table IV - DD
Source-specific Applicable Requirements
S268, S269: 6/10 HESSER PACKAGING STATIONS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A274		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17427	Inspection Requirements for Cyclone: A228		
part 1	Proper Cyclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - EE
Source-specific Applicable Requirements
S270: CUBE PACKAGING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	

IV. Source-specific Applicable Requirements

Table IV - EE
Source-specific Applicable Requirements
S270: CUBE PACKAGING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17427	Inspection Requirements for Cyclone: A275		
part 1	Proper Cyclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - FF
Source-specific Applicable Requirements
S272: CUBE MOLDING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

Table IV - FF
Source-specific Applicable Requirements
S272: CUBE MOLDING

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - GG
Source-specific Applicable Requirements
S271: WAREHOUSE/PSS MELT SYSTEM

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

IV. Source-specific Applicable Requirements

Table IV - HH
Source-specific Applicable Requirements
S273, S274, S275: BULK GRANULATED ELEVATORS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A278, A279, A280		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - II
Source-specific Applicable Requirements
S276: CUSTOM PRODUCTS STATION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	

IV. Source-specific Applicable Requirements

Table IV - II
Source-specific Applicable Requirements
S276: CUSTOM PRODUCTS STATION

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17428	Inspection Requirements for Rotoclones: A281		
part 1	Proper Rotoclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - JJ
Source-specific Applicable Requirements
S278: CARPENTER SHOP

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-401	Appearance of Emissions	Y	

IV. Source-specific Applicable Requirements

Table IV - JJ
Source-specific Applicable Requirements
S278: CARPENTER SHOP

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17427	Inspection Requirements for Cyclone: A282		
part 1	Proper Cyclone Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	

Table IV - KK
Source-specific Applicable Requirements
S279: TAILINGS MELT TANKS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

IV. Source-specific Applicable Requirements

Table IV - LL
Source-specific Applicable Requirements
S280, S281, S282: DIATOMACEOUS EARTH SYSTEM

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17431			
part 1	Particulate Abatement Requirement for S280 [Regulation 2-1-403]	Y	
part 2	Particulate Abatement Requirement for S281 [Regulation 2-1-403]	Y	
part 3	Particulate Abatement Requirement for S282 [Regulation 2-1-403]	Y	
part 4	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 5	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV - MM
Source-specific Applicable Requirements
S284: LIME UNLOADING STATION - REFINERY

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		

IV. Source-specific Applicable Requirements

Table IV - MM
Source-specific Applicable Requirements
S284: LIME UNLOADING STATION - REFINERY

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17432			
part 1	Particulate Abatement Requirement for S284 [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV – NN
Source-specific Applicable Requirements
S285: MOTHERS DRYER

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	

IV. Source-specific Applicable Requirements

**Table IV – NN
 Source-specific Applicable Requirements
 S285: MOTHERS DRYER**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
6-401	Appearance of Emissions	Y	
BAAQMD Condition #14649			
part 1	Throughput Limit [Cumulative Increase]	Y	
part 2	Limit on Hours of Operation [Cumulative Increase]	Y	
part 3	Baghouse Abatement Requirement [Regulation 2-1-403]	Y	
part 4	Baghouse Outlet Grain Loading Limit [Cumulative Increase]	Y	
part 5	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A288		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

**Table IV – OO
 Source-specific Applicable Requirements
 S286: CARBON REGENERATION FURNACE**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
------------------------	--	-----------------------------	-----------------------

IV. Source-specific Applicable Requirements

Table IV – OO
Source-specific Applicable Requirements
S286: CARBON REGENERATION FURNACE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-310.3	Heat Transfer Operations	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Regulation 8, Rule 2	Organic Compounds – Miscellaneous Operations (6/15/94)		
8-2-301	Organic Compounds Emissions Limits	Y	
BAAQMD Regulation 9, Rule 1	Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)		
9-1-301	Limitations on Ground Level Concentrations	Y	
9-1-302	General Emissions Limitation	Y	
BAAQMD Condition #13308			
part 1	Carbon Regeneration Limit [Cumulative Increase]	Y	
part 2	Natural Gas Fuel Requirement [Cumulative Increase]	Y	
part 3	Requirement for Abatement Devices [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17430	Inspection and Maintenance Requirements for Wet Scrubbers: A290		
part 1	Proper Scrubber Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Operating Parameters [Regulation 2-1-403]	Y	
part 3	Weekly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	

IV. Source-specific Applicable Requirements

Table IV – OO
Source-specific Applicable Requirements
S286: CARBON REGENERATION FURNACE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV – PP
Source-specific Applicable Requirements
S288: SPENT CHAR HANDLING SYSTEM

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

IV. Source-specific Applicable Requirements

Table IV – QQ
Source-specific Applicable Requirements
S289: REGENERATED CHAR HANDLING SYSTEM

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17425	Inspection and Maintenance Requirements for Baghouses: A292		
part 1	Proper Baghouse Maintenance/Operation [Regulation 2-1-403]	Y	
part 2	Pressure Drop Monitor [Regulation 2-1-403]	Y	
part 3	Monthly Inspection Items [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV – RR
Source-specific Applicable Requirements
S301, S303, S304, S305: WASTEWATER TREATMENT

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 7	Odorous Substances		
7-301	General limit on odorous substances	N	

IV. Source-specific Applicable Requirements

Table IV – RR
Source-specific Applicable Requirements
S301, S303, S304, S305: WASTEWATER TREATMENT

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
7-302	Limit on odorous substances at or beyond property line	N	
7-303	Limit on odorous compounds	N	
BAAQMD Regulation 8, Rule 2	Organic Compounds-Miscellaneous Operation (6/15/94)	Y	
8-2-301	Miscellaneous Operations	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

Table IV – SS
Source-specific Applicable Requirements
S307: LIME UNLOADING STATION – FILTER CAKE

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #14650			
part 1	Lime Throughput Limit [Cumulative Increase]	Y	

IV. Source-specific Applicable Requirements

**Table IV – SS
 Source-specific Applicable Requirements
 S307: LIME UNLOADING STATION – FILTER CAKE**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
part 2	Lime Silo Abatement Requirement [Regulation 2-1-403]	Y	
part 3	Enclosure Requirements [Regulation 2-1-403]	Y	
part 4	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17433			
part 1	Particulate Abatement Requirement for Lime Silo [Regulation 2-1-403]	Y	
part 2	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 3	Recordkeeping [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

IV. Source-specific Applicable Requirements

Table IV – TT
Source-specific Applicable Requirements
S330, S331, S332, S333, S334, S335, S336, S337, S338, S340, S341, S342, S343, S344,
S354, S346: ROTEX SCREENS

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)		
6-301	Ringelmann #1 Limitation	Y	
6-305	Visible Particles	Y	
6-310	Particulate Weight Limitation	Y	
6-311	General Operations: Emission Limit Based on Process Weight Rate	Y	
6-401	Appearance of Emissions	Y	
BAAQMD Condition #17641			
part 1	Sugar Throughput Limit; S330, S331 [Cumulative Increase]	Y	
part 2	Sugar Throughput Limit; S332, S333, S334, S335, S336, S337, S338, S340, S341, S342, S343, S344, S345, S346 [Cumulative Increase]	Y	
part 3	Abatement Requirement [Regulation 2-1-403]	Y	
part 4	Annual Visible Emissions Inspection [Regulation 2-1-403]	Y	
part 5	Throughput Records [Regulation 2-6-501]	Y	
part 6	Records of Visible Emission Checks [Regulation 2-6-501]	Y	
BAAQMD Condition #17690	General Throughput Limits		
part 1	Throughput Limit Equal to Stated Capacity for Each Source	Y	
part 2	Demonstration of Throughput	Y	

V. SCHEDULE OF COMPLIANCE

The permit holder shall comply with all applicable requirements cited in this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit.

VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

Condition #13308

For S286: Carbon Regeneration Furnace and A289, Afterburner

1. The total amount of carbon regenerated at S286 shall not exceed 3900 tons during any consecutive 12-month period. (basis: Cumulative Increase)
2. Only natural gas shall be used at S286, carbon furnace and at A289, afterburner. (basis: Cumulative Increase)
3. S286, carbon furnace, shall be abated at all times by A289, afterburner, and A289 shall be abated at all times by A290, scrubber. (basis: Regulation 2-1-403)
4. In order to demonstrate compliance with the above conditions the following records shall be maintained in a District-approved log: (basis: Regulation 2-6-501)
 - a. The amount of carbon regenerated at S286;
 - b. The daily quantities shall be totaled on a monthly basis.

These records shall be kept on site and made available for inspection by District personnel for a period of ~~24 months~~ 5 years from the date on which a record is made.

VI. Permit Conditions

Condition #14395

For S230: No. 1 Granulator

1. The Upper No. 1 Granulator shall be abated by the A229 Sugar Recovery Chambers and the A302 RotoClone Wet Centrifugal Collector (in series) during all times that S230 is processing sugar. (basis: Regulation 2-1-403)
2. The Lower No. 1 Granulator shall be abated by the A241 Sugar Recovery Chambers, the A294 Skimmer, and the A295 RotoClone Wet Centrifugal Collector (in series) during all times that S230 is processing sugar. (basis: Regulation 2-1-403)

For S231, No. 2 Granulator

- ~~13.~~ The Upper No. 2 Granulator shall be abated by the A231 Sugar Recovery Chambers and the A303 RotoClone Wet Centrifugal Collector (in series) during all times that S231 is processing sugar. (basis: Regulation 2-1-403)
- ~~24.~~ The Lower No. 2 Granulator shall be abated by the A243 Sugar Recovery Chambers, the A296 Skimmer, and the A297 RotoClone Wet Centrifugal Collector (in series) during all times that S231 is processing sugar. (basis: Regulation 2-1-403)

For S232, No. 3 Granulator

- ~~15.~~ The Upper No. 3 Granulator shall be abated by the A233 Sugar Recovery Chambers and the A303 RotoClone Wet Centrifugal Collector (in series) during all times that S232 is processing sugar. (basis: Regulation 2-1-403)
- ~~26.~~ The Lower No. 3 Granulator shall be abated by the A245 Sugar Recovery Chambers, the A296 Skimmer, and the A297 RotoClone Wet Centrifugal Collector (in series) during all times that S232 is processing sugar. (basis: Regulation 2-1-403)

VI. Permit Conditions

Condition #14395

For S233, No. 4 Granulator

- ~~17.~~ The Upper No. 4 Granulator shall be abated by the A235 Sugar Recovery Chambers and the A304 RotoClone Wet Centrifugal Collector (in series) during all times that S233 is processing sugar. (basis: Regulation 2-1-403)
- ~~28.~~ The Lower No. 4 Granulator shall be abated by the A247 Sugar Recovery Chambers, the A298 Skimmer, and the A299 RotoClone Wet Centrifugal Collector (in series) during all times that S233 is processing sugar. (basis: Regulation 2-1-403)

For S234, No. 5 Granulator

- ~~19.~~ The Upper No. 5 Granulator shall be abated by the A237 RotoClone Wet Centrifugal Collector during all times that S234 is processing sugar. (basis: Regulation 2-1-403)
- ~~210.~~ The Lower No. 5 Granulator shall be abated by the A249 Skimmer and the A250 RotoClone Wet Centrifugal Collector (in series) during all times that S234 is processing sugar. (basis: Regulation 2-1-403)

For S235, No. 6 Granulator

- ~~11.~~ The Upper No. 6 Granulator shall be abated by the A238 Sugar Recovery Chambers and the A304 RotoClone Wet Centrifugal Collector (in series) during all times that S235 is processing sugar. (basis: Regulation 2-1-403)
- ~~212.~~ The Lower No. 6 Granulator shall be abated by the A251 Sugar Recovery Chambers, the A298 Skimmer, and the A299 RotoClone Wet Centrifugal Collector (in series) during all times that S235 is processing sugar. (basis: Regulation 2-1-403)

For S236, No. 7 Granulator

- ~~13.~~ The Upper No. 7 Granulator shall be abated by the A240 RotoClone Wet Centrifugal Collector during all times that S236 is processing sugar. (basis: Regulation 2-1-403)

VI. Permit Conditions

Condition #14395

214. The Lower No. 7 Granulator shall be abated by the A253 Skimmer and the A254 RotoClone Wet Centrifugal Collector (in series) during all times that S236 is processing sugar. (basis: Regulation 2-1-403)

Condition #14648

For S 190 and S 142/A 142

1. ~~The blowers and spargers at the Waste Water Treatment Plant Surge Basin (S 190) shall be properly maintained and properly operated. The Surge Basin vapor space blower shall maintain a negative pressure in the head space of S 190 during all times that S 190 contains waste water. All vapors collected by this blower shall be vented through the A 142 Reactor Basins. (1-301)~~

Condition #14649

For S285: Mothers Dryer

1. Total throughput of granulated sugar at the S285 Mothers Dryer shall not exceed 11,400 tons during any consecutive 12 month period. (basis: Cumulative Increase)
2. The total operating time for the S285 Mothers Dryer shall not exceed 16 hours during any day. (basis: Cumulative Increase)
3. The S285 Mothers Dryer shall be abated by the properly operated and properly maintained A288 Baghouse during all hours of operation. ~~(basis: Cumulative Increase)~~ (basis: Regulation 2-1-403)
4. Particulate emissions from the A288 Baghouse shall not exceed 0.011 grains per dry standard cubic foot of exhaust. (basis: Cumulative Increase)
5. To demonstrate compliance with Conditions #1 and #2, the owner/operator of S285 shall maintain the following records in a District approved log: (basis: Regulation 2-6-501)
 - a. Daily records of the operating time for the S285 Mothers Dryer, summarized on a monthly basis.

VI. Permit Conditions

- b. Monthly records of the quantity of granulated sugar processed by the S285 Mothers Dryer.

Condition #14649

For S285: Mothers Dryer

These records shall be kept on site for a minimum of ~~24 months~~ 5 years from the date of entry and shall be made available to District personnel upon request.

Condition #14650

For S307: Liming System

1. Total throughput of lime at the S307 Liming System shall not exceed 800 tons during any consecutive 12 month period. (basis: Cumulative Increase)
2. The Lime Silo at the S307 Liming System shall be abated by the A307 Baghouse during all hours of operation. (~~basis: Cumulative Increase~~) (basis: Regulation 2-1-403)
3. The Feeder, Screw Conveyor, and Screw Mixer at S307 shall be completely enclosed during all times that lime is being processed. The two Belt Conveyors at S307 shall be used to transfer wet material only. (~~basis: Cumulative Increase~~) (basis: Regulation 2-1-403)
4. To demonstrate compliance with Condition #1, the owner/operator of S307 shall maintain monthly records of the amount of lime added to the Lime Silo in a District approved log. These records shall be kept on site for a minimum of ~~24 months~~ 5 years from the date of entry and shall be made available to District personnel upon request. (~~basis: Cumulative Increase~~) (basis: Regulation 2-6-501)

Condition #15205

For S204: Powdered C/P Packer

1. The Powdered C/P Packer (S204) shall be abated by the properly maintained and properly operated Baghouse (A204) at all times that S204 is operating. (basis: BACT)

VI. Permit Conditions

2. Particulate emissions from A204 Baghouse shall not exceed 0.01 grains per dry standard cubic foot. (basis: BACT)

VI. Permit Conditions

Condition #15206

For S224: Bulk Sugar Loading

1. The total sugar throughput at the Bulk Sugar Loading Operation (S224) shall not exceed 200,000 tons during any consecutive 12-month period. (basis: Cumulative Increase)
2. To confirm compliance with Condition #1, the owner/operator of S224 shall maintain monthly records of the amount of sugar loaded at S224 in a District approved log. These records shall be kept on site for a minimum of ~~60 months~~ 5 years from the date of entry and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)

Condition #15886

For S228: Drivert Production

1. The total throughput of sugar processed at the Drivert Production (S228) shall not exceed 5000 tons during any 12 consecutive month period. (basis: Cumulative Increase)
2. S228 shall be abated by baghouses (A224, A225, A226, A227, A268 and A269) when in operation. (~~basis: Cumulative Increase~~) (basis: Regulation 2-1-403)
3. To demonstrate compliance with Condition #1, the monthly total throughput of sugar shall be maintained in a District approved log. The throughput records shall be kept on site and made available for District inspection for a period of at least ~~24 months~~ 5 years from the date on which a record is made. (~~basis: Cumulative Increase~~) (basis: Regulation 2-6-501)

VI. Permit Conditions

Condition #17425

General Conditions for the Following Sources Abated by Baghouses:

S201, S202, S203, S204, S205, S206, S207, S208, S209, S210, S211, S212, S213, S214, S218, S219, S220, S223, S228, S243, S244, S245, S255, S262, S263, S264, S265, S266, S267, S285, S289

1. Each baghouse shall be properly maintained and properly operated at all times that its associated PM emissions source(s) is/are in operation. (basis: Regulation 2-1-403)
2. Within 3 months of the issuance of the Title V permit, each baghouse shall be equipped with a magnahelic gauge or other approved device to measure the pressure drop across the filter bags. The pressure drop across the baghouse shall be maintained within the range recommended by the manufacturer or normal operating range established by the facility. The established pressure drop range for each baghouse shall be recorded and kept on file. (basis: Regulation 2-1-403)
3. In order to ensure the proper operation of each affected baghouse, the following items shall be inspected on at least a monthly basis. (basis: Regulation 2-1-403)
 - a. the measured pressure drop across the baghouse is within the established pressure drop range
 - b. evidence of visible particulate emissions from the exhaust of the baghouse
 - c. evidence of holes, tearing, or significant wear of filter bags by visual inspection
4. In order to demonstrate compliance with part 3, the permit holder shall keep monthly inspection records for each affected baghouse in a District approved log. These records shall include the following information for each baghouse:
 - a. the time and date of each inspection
 - b. the name of the person conducting the inspection
 - c. the measured pressure drop versus the established pressure drop range
 - d. the results of each visible particulate emissions check
 - e. the observed condition of the filter bags
 - f. any corrective action taken as a result of the inspection

Condition #17425

VI. Permit Conditions

General Conditions for the Following Sources Abated by Baghouses:

All records shall be kept on-site and made available for District inspection for a period of five years from the date on which a record is made. (basis: Regulation 2-6-501)

Condition #17426

For S215, S216: Starch Unloading/Conveying

1. Particulate matter emissions during loading operations at the Starch Unloading Facility S215, shall be controlled by the Baghouse A211. (basis: Regulation 2-1-403)
2. Particulate generated by the Starch Conveying System S216 shall be controlled by the Baghouse A212. (basis: Regulation 2-1-403)
3. The Baghouses A211 and A212, shall be checked for visible emissions on an annual basis. The visible emissions check shall take place while the equipment is operating and during daylight hours. If any visible emissions are detected, the operator shall take corrective action, and check for visible emissions during the next period of operation. If no visible emissions are detected, the operator shall continue to check for visible emissions every year. (basis: Regulation 2-1-403)
4. The operator shall keep records of all visible emissions checks, the person performing the check, and all maintenance performed. These records shall be retained for five (5) years and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)

Condition #17427

General Conditions for the Following Sources Abated by Cyclones:

S217, S229, S268, S269, S270, S278

1. Each cyclone shall be properly maintained and properly operated at all times that its associated PM emissions source(s) is/are in operation. (basis: Regulation 2-1-403)

VI. Permit Conditions

Condition #17427

General Conditions for the Following Sources Abated by Cyclones:

2. Each cyclone, shall be checked for visible emissions on an annual basis. The visible emissions check shall take place while the equipment is operating and during daylight hours. If any visible emissions are detected, the operator shall take corrective action, and check for visible emissions during the next period of operation. If no visible emissions are detected, the operator shall continue to check for visible emissions every year. (basis: Regulation 2-1-403)

3. The operator shall keep records of all visible emissions checks, the person performing the check, and all maintenance performed. These records shall be retained for five (5) years and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)

Condition #17428

General Conditions for the Following Sources Abated by Rotoclones:

S222, S224, S225, S226, S227, S230, S231, S232, S233, S234, S235, S236, S252, S253, S254, S257, S258, S259, S260, S261, S262, S268, S269, S273, S274, S275, S276

1. Each rotoclone shall be properly maintained and properly operated at all times that its associated PM emissions source(s) is/are in operation. (basis: Regulation 2-1-403)

2. Each rotoclone, shall be checked for visible emissions on an annual basis. The visible emissions check shall take place while the equipment is operating and during daylight hours. If any visible emissions are detected, the operator shall take corrective action, and check for visible emissions during the next period of operation. If no visible emissions are detected, the operator shall continue to check for visible emissions every year. (basis: Regulation 2-1-403)

3. The operator shall keep records of all visible emissions checks, the person performing the check, and all maintenance performed. These records shall be retained for five (5) years and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)

VI. Permit Conditions

Condition #17430

General Conditions for the Following Sources Abated by Wet Scrubbers:

S246, S247, S248, S249, S250, S286

1. Each wet scrubber shall be properly maintained and properly operated at all times that its associated PM emissions source(s) is/are in operation. (basis: Regulation 2-1-403)
2. Each wet scrubber shall be operated within the range of normal operating parameters for the equipment as established by the facility. The acceptable ranges for scrubber liquid flow rate and gas stream pressure drop across the unit shall be recorded for each affected wet scrubber and kept on file. (basis: Regulation 2-1-403)
3. In order to ensure the proper operation of each affected wet scrubber, the following items shall be inspected on at least a weekly basis. (basis: Regulation 2-1-403)
 - a. scrubber operating parameters including liquid flow rate and gas stream pressure drop
 - b. evidence of visible particulate emissions from the exhaust of the scrubber
4. In order to demonstrate compliance with part 3, the permit holder shall keep weekly inspection records for each affected wet scrubber in a District approved log. These records shall include the following information for each unit inspected:
 - a. the time and date of each inspection
 - b. the name of the person conducting the inspection
 - c. the liquid flow rate versus the established range
 - d. the measured gas stream pressure drop versus the established pressure drop range
 - e. the results of each visible particulate emissions check
 - f. any corrective action taken as a result of the inspection

All records shall be kept on-site and made available for District inspection for a period of five years from the date on which a record is made. (basis: Regulation 2-6-501)

VI. Permit Conditions

Condition #17431

For S280, S281, S282: Diatomaceous Earth System

1. Particulate matter emissions during loading operations at the Diatomaceous Earth Storage Silo S280, shall be controlled by the Dust Collector A284. (basis: Regulation 2-1-403)
2. Particulate matter emissions during loading operations at the West DE Metering Bin S281, shall be controlled by the Dust Collector A285. (basis: Regulation 2-1-403)
3. Particulate matter emissions during loading operations at the East DE Metering Bin S282, shall be controlled by the Dust Collector A286. (basis: Regulation 2-1-403)
4. The Dust Collectors A284, A285, and A286, shall be checked for visible emissions on an annual basis. The visible emissions check shall take place while the equipment is operating and during daylight hours. If any visible emissions are detected, the operator shall take corrective action, and check for visible emissions during the next period of operation. If no visible emissions are detected, the operator shall continue to check for visible emissions every year. (basis: Regulation 2-1-403)
5. The operator shall keep records of all visible emissions checks, the person performing the check, and all maintenance performed. These records shall be retained for five (5) years and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)

Condition #17432

For S284: Lime Storage Silo - Refinery

1. Particulate matter emissions during loading operations at the Lime Storage Silo S284, shall be controlled by the Bin Vent Filter A287. (basis: Regulation 2-1-403)
2. The Bin Vent Filter A287, shall be checked for visible emissions on an annual basis. The visible emissions check shall take place while the equipment is operating and during daylight hours. If any visible emissions are detected, the

VI. Permit Conditions

operator shall take corrective action, and check for visible emissions during the next period of operation. If no visible emissions are detected, the operator shall continue to check for visible emissions every

Condition #17432

For S284: Lime Storage Silo - Refinery

year. (basis: Regulation 2-1-403)

3. The operator shall keep records of all visible emissions checks, the person performing the check, and all maintenance performed. These records shall be retained for five (5) years and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)

Condition #17433

For S307: Lime Unloading Station

1. Particulate matter emissions during loading operations at the Lime Storage Silo of S307, shall be controlled by the Bin Vent Filter A307. (basis: Regulation 2-1-403)
2. The Bin Vent Filter A307, shall be checked for visible emissions on an annual basis. The visible emissions check shall take place while the equipment is operating and during daylight hours. If any visible emissions are detected, the operator shall take corrective action, and check for visible emissions during the next period of operation. If no visible emissions are detected, the operator shall continue to check for visible emissions every year. (basis: Regulation 2-1-403)
3. The operator shall keep records of all visible emissions checks, the person performing the check, and all maintenance performed. These records shall be retained for five (5) years and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)

Condition #17641

For S330, S331, S332, S333, S334, S335, S336, S337, S338, S340, S341, S342, S343, S344, S345, S346: Rotex Screens

VI. Permit Conditions

1. The total amount of sugar processed at the Rotex Screens S330 and S331 shall not exceed 219,000 tons during any consecutive 12 month period at each machine. (basis: Cumulative Increase)

Condition #17641

2. The total amount of sugar processed at the Rotex Screens S332, S333, S334, S335, S336, S337, S338, S340, S341, S342, S343, S344, S345, and S346 shall not exceed 157,680 tons during any consecutive 12 month period at each machine. (basis: Cumulative Increase)
3. All Rotex Screens shall be abated by the properly maintained and properly operated Skimmer A312 and Rotoclone A313 during all periods of operation. (basis: Regulation 2-1-403)
4. The exhaust of the Rotoclone A313 shall be checked for visible particulate emissions on an annual basis. The visible emissions check shall take place while the equipment is in operation and during daylight hours. If any visible emissions are detected, the operator shall take corrective action and reinspect the equipment for visible emissions during the next period of operation. If visible emissions are not detected, no further action is required until the next annual inspection. (basis: Regulation 2-1-403)
5. In order to demonstrate compliance with part 1 and part 2 of these conditions, the facility shall keep monthly records of the amount of sugar processed at each Rotex Screen. These records shall be retained for at least 5 years and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)
6. In order to demonstrate compliance with part 4 of these conditions, the facility shall keep records of all visible emissions checks, the person performing the check, and all maintenance performed. These records shall be retained for at least 5 years and shall be made available to District personnel upon request. (basis: Regulation 2-6-501)

VI. Permit Conditions

Condition #17690

General Requirements Pertaining to Maximum Throughput at Each Source:

1. Unless otherwise indicated in a specific permit condition, the maximum throughput for each source will be that which is listed as the capacity of the source in Table II A "Permitted Sources" of the Title V permit. (basis: Cumulative Increase)

2. Unless otherwise indicated in a specific permit condition, the operator shall, upon request from the APCO, make available any records relating to the hourly or daily throughput for each permitted source. (basis: Cumulative Increase)

VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown, either annual (A), quarterly (Q), monthly (M), weekly (W), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

Table VII - A
Applicable Limits and Compliance Monitoring Requirements
S201, S267: WAREHOUSE/PSS SUGAR RECOVERY

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		S201: 4.2 lb/hr (throughput = 1.0 tons/hr) S267: 18.4 lb/hr (throughput = 9.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - B
Applicable Limits and Compliance Monitoring Requirements
S202: PSS VACUUM CLEANING SYSTEM

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		6.7 lb/hr (throughput = 2.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

Table VII - C
Applicable Limits and Compliance Monitoring Requirements
S203, S205, S206, S207, S208: POWDERED SUGAR PACKAGING OPERATIONS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - C
Applicable Limits and Compliance Monitoring Requirements
S203, S205, S206, S207, S208: POWDERED SUGAR PACKAGING OPERATIONS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		S203: 10.0 lb/hr (throughput = 3.6 tons/hr) S205: 35.5 lb/hr (throughput = 24.0 tons/hr) S206: 14.6 lb/hr (throughput = 6.4 tons/hr) S207: 8.8 lb/hr (throughput = 3.0 tons/hr) S208: 40.0 lb/hr (throughput = 47.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

Table VII - D
Applicable Limits and Compliance Monitoring Requirements
S204: POWDERED C/P PACKER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII - D
Applicable Limits and Compliance Monitoring Requirements
S204: POWDERED C/P PACKER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		12.1 lb/hr (throughput = 4.8 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Condition #15205 part 2	Y		0.01 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

Table VII – E
Applicable Limits and Compliance Monitoring Requirements
S209, S210, S211, S212, S213, S214: POWDERED/FONDANT SUGAR PULVERIZERS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – E
Applicable Limits and Compliance Monitoring Requirements
S209, S210, S211, S212, S213, S214: POWDERED/FONDANT SUGAR PULVERIZERS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		S209: 8.8 lb/hr (throughput = 3.0 tons/hr) S210: 8.8 lb/hr (throughput = 3.0 tons/hr) S211: 8.8 lb/hr (throughput = 3.0 tons/hr) S212: 8.8 lb/hr (throughput = 3.0 tons/hr) S213: 3.9 lb/hr (throughput = 0.9 tons/hr) S214: 3.9 lb/hr (throughput = 0.9 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

Table VII – F
Applicable Limits and Compliance Monitoring Requirements
S215, S216: STARCH UNLOADING/CONVEYING

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17426, part 3	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – F
Applicable Limits and Compliance Monitoring Requirements
S215, S216: STARCH UNLOADING/CONVEYING

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		S215: 32.4 lb/hr (throughput = 21.0 tons/hr) S216: 14.0 lb/hr (throughput = 6.0 tons/hr)		N	

Table VII – G
Applicable Limits and Compliance Monitoring Requirements
S217: PAPER BALER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17427, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	

Table VII – H
Applicable Limits and Compliance Monitoring Requirements
S218, S219, S220: PACKAGING STATIONS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
---------------	-------------------------	--------	-----------------------	----------------	---------------------------------	------------------------------	-----------------

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – H
Applicable Limits and Compliance Monitoring Requirements
S218, S219, S220: PACKAGING STATIONS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		S218: 40.0 lb/hr (throughput = 54.0 tons/hr) S219: 40.0 lb/hr (throughput = 54.0 tons/hr) S220: 40.0 lb/hr (throughput = 54.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

Table VII – I
Applicable Limits and Compliance Monitoring Requirements
S221: MELT TANK

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0		N	
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – I
Applicable Limits and Compliance Monitoring Requirements
S221: MELT TANK

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		22.3 lb/hr (throughput = 12.0 tons/hr)		N	

Table VII – J
Applicable Limits and Compliance Monitoring Requirements
S222: CONFECTIONERS DRYER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		12.9 lb/hr (throughput = 5.3 tons/hr)		N	

Table VII – K
Applicable Limits and Compliance Monitoring Requirements
S223: PACKING HOUSE #1 VACUUM SYSTEM

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
---------------	-------------------------	--------	-----------------------	----------------	---------------------------------	------------------------------	-----------------

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – K
Applicable Limits and Compliance Monitoring Requirements
S223: PACKING HOUSE #1 VACUUM SYSTEM

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		0.4 lb/hr (throughput = 0.03 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

Table VII – L
Applicable Limits and Compliance Monitoring Requirements
S224: BULK SUGAR LOADING

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		40.0 lb/hr (throughput = 75.0 tons/hr)		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – L
Applicable Limits and Compliance Monitoring Requirements
S224: BULK SUGAR LOADING

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Usage	BAAQMD Condition #15206 part 1	Y		200,000 tons/yr Sugar Throughput Limit	BAAQMD Condition #15206 part 2	P/M	Sugar Loading Records

Table VII – M
Applicable Limits and Compliance Monitoring Requirements
S225: STEEL SILOS CONVEYING TO BULK LOADOUT

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		40.0 lb/hr (throughput = 37.5 tons/hr)		N	

Table VII – N
Applicable Limits and Compliance Monitoring Requirements
S226, S227: CONCRETE SILOS, CONVEYING, BULK LOADOUT

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
---------------	-------------------------	--------	-----------------------	----------------	---------------------------------	------------------------------	-----------------

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – N
Applicable Limits and Compliance Monitoring Requirements
S226, S227: CONCRETE SILOS, CONVEYING, BULK LOADOUT

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		S226: 37.4 lb/hr (throughput = 26.0 tons/hr) S227: 40.0 lb/hr (throughput = 75.0 tons/hr)		N	

Table VII – O
Applicable Limits and Compliance Monitoring Requirements
S228: DRIVERT PRODUCTION

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		9.0 lb/hr (throughput = 3.1 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – O
Applicable Limits and Compliance Monitoring Requirements
S228: DRIVERT PRODUCTION

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Usage	BAAQMD Condition #15886 part 1	Y		5,000 tons/yr Sugar Throughput Limit	BAAQMD Condition #15886 part 3	P/M	Sugar Throughput Records

Table VII – P
Applicable Limits and Compliance Monitoring Requirements
S229: SCRAP PAPER RECOVERY

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17427, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – Q
Applicable Limits and Compliance Monitoring Requirements
S230, S231, S232, S233, S234, S235, S236: GRANULATORS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A	Visible Emissions Check
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		S230: 27.8 lb/hr (throughput = 16.7 tons/hr) S231: 27.8 lb/hr (throughput = 16.7 tons/hr) S232: 27.8 lb/hr (throughput = 16.7 tons/hr) S233: 27.8 lb/hr (throughput = 16.7 tons/hr) S234: 40.0 lb/hr (throughput = 37.5 tons/hr) S235: 27.8 lb/hr (throughput = 16.7 tons/hr) S236: 40.0 lb/hr (throughput = 31.3 tons/hr)		N	

VII. Applicable Limits and Compliance Monitoring Requirements

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – R
Applicable Limits and Compliance Monitoring Requirements
S240, S241, S242: 5TH FLOOR DISTRIBUTION

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
FP	BAAQMD Regulation 6-311	Y		S240: 40.0 lb/hr (throughput = 170.0 tons/hr) S241: 19.7 lb/hr (throughput = 10.0 tons/hr) S242: 40.0 lb/hr (throughput = 85.0 tons/hr)	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters

Table VII – S
Applicable Limits and Compliance Monitoring Requirements
S243, S244: BEMIS PACKERS #1 AND #2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – S
Applicable Limits and Compliance Monitoring Requirements
S243, S244: BEMIS PACKERS #1 AND #2

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		S243: 40.0 lb/hr (throughput = 30.0 tons/hr) S244: 40.0 lb/hr (throughput = 30.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

Table VII – T
Applicable Limits and Compliance Monitoring Requirements
S245, S255: BEMIS PACKER #3 AND 1ST FLOOR PAPER SHREDDER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – T
Applicable Limits and Compliance Monitoring Requirements
S245, S255: BEMIS PACKER #3 AND 1ST FLOOR PAPER SHREDDER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		S245: 40.0 lb/hr (throughput = 30.0 tons/hr) S255: 6.7 lb/hr (throughput = 2.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – U
Applicable Limits and Compliance Monitoring Requirements
S246, S247, S248, S249: DRY UNSCREENED SUGAR SURGE OPERATIONS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
FP	BAAQMD Regulation 6-311	Y		S246: 40.0 lb/hr (throughput = 30.0 tons/hr) S247: 40.0 lb/hr (throughput = 125.0 tons/hr) S248: 22.3 lb/hr (throughput = 12.0 tons/hr) S249: 24.7 lb/hr (throughput = 14.0 tons/hr)	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters

Table VII – V
Applicable Limits and Compliance Monitoring Requirements
S250: CHAR FURNACE

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – V
Applicable Limits and Compliance Monitoring Requirements
S250: CHAR FURNACE

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-310.3	Y		0.15 gr/dscf @6%O2	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
FP	BAAQMD Regulation 6-311	Y		32.7 lb/hr (throughput = 21.3 tons/hr)	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
POC	BAAQMD Regulation 8-2-301	Y		300 ppm total carbon (dry) (if emission is >15 lb/day)		N	
SO2	BAAQMD Regulation 9-1-301	Y		Ground Level Concentrations: 0.5 ppm for 3 consecutive minutes, 0.25 ppm averaged over 60 consecutive minutes, 0.05 ppm averaged over 24 hours	BAAQMD Regulation 9-1-501	N (unless requested by APCO)	
SO2	BAAQMD Regulation 9-1-302	Y		300 ppm (dry) general emission limitation		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – W
Applicable Limits and Compliance Monitoring Requirements
S252, S253, S254: BULK BINS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A,	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		S252: 31.4 lb/hr (throughput = 20.0 tons/hr) S253: 31.4 lb/hr (throughput = 20.0 tons/hr) S254: 36.5 lb/hr (throughput = 25.0 tons/hr)		N	

Table VII – X
Applicable Limits and Compliance Monitoring Requirements
S256: PAINT SPRAY BOOTH

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Regulation 8-19-302.1	Y		Baked Coatings: 275 g/l (2.3 lb/gal)	BAAQMD Regulation 8-19-501	P/W	Record Keeping
POC	BAAQMD Regulation 8-19-302.2	Y		Air-Dried Coatings: 340 g/l (2.8 lb/gal)	BAAQMD Regulation 8-19-501	P/W	Record Keeping

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – X
Applicable Limits and Compliance Monitoring Requirements
S256: PAINT SPRAY BOOTH

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Regulation 8-19-312.1 to 312.13	Y		Specialty Coatings, Air-dried coating limits: 420 g/l or 3.5 lb/gal	BAAQMD Regulation 8-19-501	P/W	Record Keeping
POC	BAAQMD Regulation 8-19-312.1, 312.2, 312.3, 312.5, 312.9	Y		Specialty Coatings, Baked coating limits: 360 g/l or 3.0 lb/gal	BAAQMD Regulation 8-19-501	P/W	Record Keeping
POC	BAAQMD Regulation 8-19-312.4, 312.7, 312.8, 312.12, 312.13	Y		Specialty Coatings, Baked coating limits: 420 g/l or 3.5 lb/gal	BAAQMD Regulation 8-19-501	P/W	Record Keeping

Table VII – Y
Applicable Limits and Compliance Monitoring Requirements
S257, S258, S259, S260: BULK GRANULATED SILOS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A,	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – Y
Applicable Limits and Compliance Monitoring Requirements
S257, S258, S259, S260: BULK GRANULATED SILOS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		S257: 36.5 lb/hr (throughput = 25.0 tons/hr) S258: 36.5 lb/hr (throughput = 25.0 tons/hr) S259: 36.5 lb/hr (throughput = 25.0 tons/hr) S260: 36.5 lb/hr (throughput = 25.0 tons/hr)		N	

Table VII – Z
Applicable Limits and Compliance Monitoring Requirements
S261: VIBRO CONVEYING/STORAGE

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A,	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		S261: 7.2 lb/hr (throughput = 2.2 tons/hr)		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – AA
Applicable Limits and Compliance Monitoring Requirements
S262: 12/5 SUGAR CONVEYING/STORAGE

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A,	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		40.0 lb/hr (throughput = 60.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

Table VII – BB
Applicable Limits and Compliance Monitoring Requirements
S263: DRIVERT PACKER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – BB
Applicable Limits and Compliance Monitoring Requirements
S263: DRIVERT PACKER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		25.9 lb/hr (throughput = 15.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

Table VII – CC
Applicable Limits and Compliance Monitoring Requirements
S264, S265, S266: AIRVEYORS/AIRVEYOR BIN

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		S264: 40.0 lb/hr (throughput = 47.0 tons/hr) S265: 15.5 lb/hr (throughput = 7.0 tons/hr) S266: 15.5 lb/hr (throughput = 7.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – DD
Applicable Limits and Compliance Monitoring Requirements
S268, S269: 6/10 HESSER PACKAGING STATIONS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A,	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		S268: 22.3 lb/hr (throughput = 12.0 tons/hr) S269: 22.3 lb/hr (throughput = 12.0 tons/hr)		N	

Table VII – EE
Applicable Limits and Compliance Monitoring Requirements
S270: CUBE PACKAGING

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17427, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – EE
Applicable Limits and Compliance Monitoring Requirements
S270: CUBE PACKAGING

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		7.2 lb/hr (throughput = 2.2 tons/hr)		N	

Table VII – FF
Applicable Limits and Compliance Monitoring Requirements
S272: CUBE MOLDING

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0		N	
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		7.2 lb/hr (throughput = 2.2 tons/hr)		N	

Table VII – GG
Applicable Limits and Compliance Monitoring Requirements
S271: WAREHOUSE/PSS MELT SYSTEM

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – GG
Applicable Limits and Compliance Monitoring Requirements
S271: WAREHOUSE/PSS MELT SYSTEM

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		9.6 lb/hr (throughput = 3.4 tons/hr)		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – HH
Applicable Limits and Compliance Monitoring Requirements
S273, S274, S275: BULK GRANULATED ELEVATORS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		S273: 20.8 lb/hr (throughput = 10.8 tons/hr) S274: 20.8 lb/hr (throughput = 10.8 tons/hr) S275: 7.8 lb/hr (throughput = 2.5 tons/hr)		N	

Table VII – II
Applicable Limits and Compliance Monitoring Requirements
S276: CUSTOM PRODUCTS STATION

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17428, part 2	P/A,	Visible Emissions Check

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – II
Applicable Limits and Compliance Monitoring Requirements
S276: CUSTOM PRODUCTS STATION

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		4.2 lb/hr (throughput = 1.0 tons/hr)		N	

Table VII – JJ
Applicable Limits and Compliance Monitoring Requirements
S278: CARPENTER SHOP

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17427, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	

Table VII – KK
Applicable Limits and Compliance Monitoring Requirements
S279: TAILINGS MELT TANKS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – KK
Applicable Limits and Compliance Monitoring Requirements
S279: TAILINGS MELT TANKS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
Opacity	BAAQMD Regulation 6-311	Y		21.0 lb/hr (throughput = 11.0 tons/hr)		N	

Table VII – LL
Applicable Limits and Compliance Monitoring Requirements
S280, S281, S282: DIATOMACEOUS EARTH SYSTEM

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17431, part 4	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		S280: 1.4 lb/hr (throughput = 0.2 tons/hr) S281: 4.2 lb/hr (throughput = 1.0 tons/hr) S282: 4.2 lb/hr (throughput = 1.0 tons/hr)		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – MM
Applicable Limits and Compliance Monitoring Requirements
S284: LIME UNLOADING STATION - REFINERY

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17432, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		1.2 lb/hr (throughput = 0.15 tons/hr)		N	

Table VII – NN
Applicable Limits and Compliance Monitoring Requirements
S285: MOTHERS DRYER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		25.9 lb/hr (throughput = 15.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – NN
Applicable Limits and Compliance Monitoring Requirements
S285: MOTHERS DRYER

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
PM10	BAAQMD Condition #14649, part 4	Y		0.011 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
Usage	BAAQMD Condition #14649 part 1	Y		11,400 tons/yr Sugar Throughput Limit	BAAQMD Condition #14649 part 5(b)	P/M	Sugar Processing Records
Usage	BAAQMD Condition #14649 part 2	Y		16 hours/day Operating Limit	BAAQMD Condition #14649 part 5(a)	P/M	Operating Time Records

Table VII – OO
Applicable Limits and Compliance Monitoring Requirements
S286: CARBON REGENERATION FURNACE

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
FP	BAAQMD Regulation 6-310.3	Y		0.15 gr/dscf @6%O2	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters
FP	BAAQMD Regulation 6-311	Y		3.1 lb/hr (throughput = 0.6 tons/hr)	BAAQMD Condition #17430 part 3, part 4	P/W	Scrubber Operating Parameters

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – OO
Applicable Limits and Compliance Monitoring Requirements
S286: CARBON REGENERATION FURNACE

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Regulation 8-2-301	Y		300 ppm total carbon (dry) (if emission is >15 lb/day)		N	
SO2	BAAQMD Regulation 9-1-301	Y		Ground Level Concentrations: 0.5 ppm for 3 consecutive minutes, 0.25 ppm averaged over 60 consecutive minutes, 0.05 ppm averaged over 24 hours	BAAQMD Regulation 9-1-501	N (unless requested by APCO)	
SO2	BAAQMD Regulation 9-1-302	Y		300 ppm (dry) general emission limitation		N	
Usage	BAAQMD Condition #13308 part 1	Y		3,900 tons/yr Carbon Regeneration Limit	BAAQMD Condition #13308 part 4	P/D	Carbon Throughput Records

Table VII – PP
Applicable Limits and Compliance Monitoring Requirements
S288: SPENT CHAR HANDLING SYSTEM

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0		N	
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – PP
Applicable Limits and Compliance Monitoring Requirements
S288: SPENT CHAR HANDLING SYSTEM

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
FP	BAAQMD Regulation 6-311	Y		32.7 lb/hr (throughput = 21.3 tons/hr)		N	

Table VII – QQ
Applicable Limits and Compliance Monitoring Requirements
S289: REGENERATED CHAR HANDLING SYSTEM

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection
FP	BAAQMD Regulation 6-311	Y		30.3 lb/hr (throughput = 19.0 tons/hr)	BAAQMD Condition #17425, part 2, part 3	P/M	Pressure Drop Inspection

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – RR
Applicable Limits and Compliance Monitoring Requirements
S301, S303, S304, S305: WASTEWATER TREATMENT

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Regulation 8-2-301	Y		300 ppm total carbon (dry) (if emission is >15 lb/day)		N	

Table VII – SS
Applicable Limits and Compliance Monitoring Requirements
S307: LIME UNLOADING STATION – FILTER CAKE

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17433, part 2	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		0.9 lb/hr (throughput = 0.1 tons/hr)		N	
Usage	BAAQMD Condition #14650 part 1	Y		800 tons/yr Lime Throughput Limit	BAAQMD Condition #14650 part 4	P/M	Lime Throughput Records

VII. Applicable Limits and Compliance Monitoring Requirements

Table VII – TT
Applicable Limits and Compliance Monitoring Requirements
S330, S331, S332, S333, S334, S335, S336, S337, S338, S340, S341, S342, S343, S344,
S354, S346: ROTEX SCREENS

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Opacity	BAAQMD Regulation 6-301	Y		Ringelmann 1.0	BAAQMD Condition #17641, part 4	P/A	Visible Emissions Check
FP	BAAQMD Regulation 6-310	Y		0.15 gr/dscf		N	
FP	BAAQMD Regulation 6-311	Y		0.2 lb/hr (throughput = 25 tons/hr)		N	
Usage	BAAQMD Condition #17641 parts 1, 2	Y		Sugar Throughput Limits; S330, S331: 219,000 tons/yr (each) All Others: 157,680 tons/yr (each)	BAAQMD Condition #17641 part 5	P/M	Sugar Throughput Records

VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally referenced in Section 600 of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII, Applicable Emission Limits & Compliance Monitoring Requirements, of this permit.

**Table VIII
 Test Methods**

Applicable Requirement	Description of Requirement	Acceptable Test Methods
BAAQMD 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
BAAQMD 6-310	Particulate Weight Limitation	Manual of Procedures, Volume IV, ST-15, Particulates Sampling
BAAQMD 6-311	Process Weight Rate Based Emissions Limits	Manual of Procedures, Volume IV, ST-15, Particulates Sampling
BAAQMD 8-2-301	Miscellaneous Operations, POC (as Total Carbon)	Manual of Procedures, Volume IV, ST-7, Organic Compounds; or EPA Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon; or EPA Method 25A, Determination of Total Gaseous Nonmethane Organic Emissions Using a Flame Ionization Analyzer
BAAQMD 8-19-302, 312	Surface Coating, VOC Content	Manual of Procedures, Volume III; Method 21, Determination of Compliance of Volatile Organic Compounds for Water Reducible Coatings; or Method 22, Determination of Compliance of Volatile Organic Compounds for Solvent Based Coatings
BAAQMD 8-19-302, 312, 313	Determination of VOC Emissions	Manual of Procedures, Volume IV, ST-7, Organic Compounds; or EPA Method 25, Determination of Total Gaseous Nonmethane Organic Emissions as Carbon; or EPA Method 25A, Determination of Total Gaseous Nonmethane Organic Emissions Using a Flame Ionization Analyzer
BAAQMD 9-1-302	General Emission Limitation	Manual of Procedures, Volume IV, ST-19A, Sulfur Dioxide, Continuous Sampling; or ST-19B, Total Sulfur Oxides Integrated Sample

IX. PERMIT SHIELD

Not Applicable.

X. GLOSSARY

BAAQMD

Bay Area Air Quality Management District

BACT

Best Available Control Technology

CAA

The federal Clean Air Act

CAAQS

California Ambient Air Quality Standards

CEQA

California Environmental Quality Act

CFR

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

CO

Carbon Monoxide

Cumulative Increase

The sum of permitted emissions from each new or modified source since a specified date pursuant to BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95). Used to determine whether threshold-based requirements are triggered.

District

The Bay Area Air Quality Management District

EPA

The federal Environmental Protection Agency.

Excluded

Not subject to any District Regulations.

Federally Enforceable, FE

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part

X. Glossary

52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), and also including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

FP

Filterable Particulate as measured by BAAQMD Method ST-15, Particulate.

HAP

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by both 40 CFR Part 63, and District Regulation 2, Rule 5.

Major Facility

A facility with potential emissions of regulated air pollutants greater than or equal to 100 tons per year, greater than or equal to 10 tons per year of any single hazardous air pollutant, and/or greater than or equal to 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity as determined by the EPA administrator.

MFR

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Act and implemented by District Regulation 2, Rule 6.

MOP

The District's Manual of Procedures.

NAAQS

National Ambient Air Quality Standards

NESHAPs

National Emission Standards for Hazardous Air Pollutants. Contained in 40 CFR Part 61.

NMHC

Non-methane Hydrocarbons

NO_x

Oxides of nitrogen.

NSPS

Standards of Performance for New Stationary Sources. Federal standards for emissions from new stationary sources. Mandated by Title I, Section 111 of the Act, and implemented by both 40 CFR Part 60 and District Regulation 10.

X. Glossary

NSR

New Source Review. A federal program for pre-construction review and permitting of new and modified sources of air pollutants for which the District is classified "non-attainment". Mandated by Title I of the Clean Air Act and implemented by 40 CFR Parts 51 and 52 as well as District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

Offset Requirement

A New Source Review requirement to provide federally enforceable emission offsets at a specified ratio for the emissions from a new or modified source and any pre-existing cumulative increase minus any onsite contemporaneous emission reduction credits. Applies to emissions of POC, NO_x, PM₁₀, and SO₂.

Phase II Acid Rain Facility

A facility that generates electricity for sale through fossil-fuel combustion and by virtue of certain other characteristics (defined in Regulation 2, Rule 6) is subject to Titles IV and V of the Clean Air Act.

POC

Precursor Organic Compounds

PM

Total Particulate Matter

PM₁₀

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

PSD

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

SIP

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.

SO₂

Sulfur dioxide

X. Glossary

Title V

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

VOC

Volatile Organic Compounds

Units of Measure:

bhp	=	brake-horsepower
btu	=	British Thermal Unit
g	=	grams
gal	=	gallon
hp	=	horsepower
hr	=	hour
lb	=	pound
in	=	inches
max	=	maximum
m ²	=	square meter
min	=	minute
mm	=	million
ppmv	=	parts per million, by volume
ppmw	=	parts per million, by weight
psia	=	pounds per square inch, absolute
psig	=	pounds per square inch, gauge
scfm	=	standard cubic feet per minute
yr	=	year

XI. APPLICABLE STATE IMPLEMENTATION PLAN

See Attachments