



JUN 29 2016

Mr. Curtis Larkin
American Ave Landfill
Public Works & Planning, Fresno County
2220 Tulare St, 6th Floor
Fresno, CA 93721

**Re: Notice of Final Action - Title V Permit Renewal
District Facility # C-3115
Project # C-1150035**

Dear Mr. Larkin:

The District has issued the Final Renewed Title V Permit for American Ave Landfill. The preliminary decision for this project was made on April 18, 2016. No comments were received subsequent to the District preliminary decision.

The public notice for issuance of the Final Title V Permit will be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,

Errol Villegas
for Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



Facility # C-3115
AMERICAN AVENUE LANDFILL
2220 TULARE ST, 6TH FLOOR
ATTN: RESOURCES MANAGER
FRESNO, CA 93721

Notice of Permit Issuance

The enclosed permit unit requirements authorize the operation of the equipment as described. These permit unit requirements supersede any and all previous permits for the specified equipment.* Please insert these documents into the Facility Permit to Operate, and post copies on or near the equipment as required by District Rule 2010.

Please contact any of our Small Business Assistance (SBA) staff at the numbers below if you have any questions:

Modesto:	(209) 557-6446
Fresno:	(559) 230-5888
Bakersfield:	(661) 392-5665

*Failure to comply with the permit unit requirements may result in enforcement action.

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



Permit to Operate

FACILITY: C-3115

EXPIRATION DATE: 07/31/2021

LEGAL OWNER OR OPERATOR:
MAILING ADDRESS:

AMERICAN AVENUE LANDFILL
2220 TULARE ST, 6TH FLOOR
ATTN: RESOURCES MANAGER
FRESNO, CA 93721

FACILITY LOCATION:

18950 W AMERICAN AVE
KERMAN, CA

FACILITY DESCRIPTION:

LANDFILL (EG SOURCE)

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

Arnaud Marjollet
Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: C-3115-0-3

EXPIRATION DATE: 07/31/2021

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rules 2010 and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 2080 and 2520] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) (Permits Required) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520] Federally Enforceable Through Title V Permit
10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: AMERICAN AVENUE LANDFILL
Location: 18950 W AMERICAN AVE, KERMAN, CA
C-3115-0-3 Jun 23 2016 10:41AM - LOWELES

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520(6/21/01). [District Rules 2520 and 1100] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere from any source operation (as defined in District Rule 1020) for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (2/17/05), by using EPA method 9. If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall supply, sell, solicit or apply any architectural coating, except specialty coatings, that contains more than 250 grams of VOC per liter of coating (less water and exempt compounds, and excluding any colorant added to tint bases), or manufacture, blend, or repackage such coating with more than 250 grams of VOC per liter (less water and exempt compounds, and excluding any colorant added to tint bases) for use within the District, unless exempted under section 4.0 of District Rule 4601 (Amended 12/17/09). [District Rule 4601] Federally Enforceable Through Title V Permit
24. No person shall apply, sell, solicit, or offer for sale any specialty architectural coating listed in the Table of Standards (District Rule 4601, Table 1 (12/17/09)), nor manufacture, blend, or repackage such coating for use within the District, which contains VOCs (less water and exempt compounds, excluding any colorant added to tint bases) in excess of the specified limits listed in Table 1 of Rule 4601 (12/17/09), unless exempted under section 4.0 of District Rule 4601 (Amended 12/17/09). [District Rule 4601] Federally Enforceable Through Title V Permit
25. All VOC-containing materials shall be stored in closed containers when not in use. In use includes, but is not limited to: being accessed, filled, emptied, maintained or repaired, unless exempted under section 4.0 of District Rule 4601 (Amended 12/17/09). [District Rule 4601] Federally Enforceable Through Title V Permit
26. A person shall not use VOCs for the cleanup of spray equipment unless equipment for collection of the cleaning compounds and minimizing its evaporation to the atmosphere is used, unless exempted under section 4.0 of District Rule 4601 (Amended 12/17/09). [District Rule 4601] Federally Enforceable Through Title V Permit
27. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.2 (12/17/09), unless exempted under section 4.0 of District Rule 4601 (Amended 12/17/09). [District Rule 4601] Federally Enforceable Through Title V Permit
28. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520] Federally Enforceable Through Title V Permit
29. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
30. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
31. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
32. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
33. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
34. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04) [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
35. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8061 and 8011] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/04) or Rule 8011 (8/19/04). [District Rule 8071 and 8011] Federally Enforceable Through Title V Permit
37. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
38. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520] Federally Enforceable Through Title V Permit
39. Any Title V permittee shall submit an application permit renewal to the District at least six months, but not greater than 18 months, prior to the Title V permit expiration date. [District Rule 2520] Federally Enforceable Through Title V Permit
40. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permit shall apply. [District Rule 2520] Federally Enforceable Through Title V Permit
41. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin July 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-3115-2-14

EXPIRATION DATE: 07/31/2021

EQUIPMENT DESCRIPTION:

44.4 MILLION CUBIC YARD CAPACITY (367 ACRES) MUNICIPAL SOLID WASTE LANDFILL WITH A LANDFILL GAS COLLECTION AND CONTROL SYSTEM, INCLUDING COLLECTION WELLS, PIPING, VACUUM PUMP/BLOWER, CONDENSATE TRAPS AND A 3,150 GALLON CONDENSATE STORAGE TANK, CONTROLLED BY ONE 51 MMBTU/HR AND ONE 99 MMBTU/HR ENCLOSED GROUND FLARE USING AN LPG PILOT

PERMIT UNIT REQUIREMENTS

1. Annual amount of soil used for covering shall not exceed 5,920,933 cubic yards of soil, and PM10 emissions shall not exceed 0.008 lb PM10/ton of soil (using a soil density of 3,240 lbs/cubic yard of soil). Permittee shall keep annual records of the amount of soil used for covering. [District Rule 2201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201 and 40 CFR Part 60.752(b)(2)(iii)(B)(2) and (b)(2)(iv), and 62.14353(b)] Federally Enforceable Through Title V Permit
3. All equipment shall be constructed, calibrated, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201 and 40 CFR 60.755(d), 60.756(b), 62.14354(b) and 40 CFR part 64] Federally Enforceable Through Title V Permit
4. No air contaminant shall be discharged from the flare into the atmosphere for a period or periods aggregating more than five minutes in any two hours which is as dark as, or darker than, Ringelmann 1/4 or 5% opacity. [40 CFR 60.18(c)(1)] Federally Enforceable Through Title V Permit
5. Particulate matter emissions from any combustion source shall not exceed 0.1 grains/dscf (calculated to 12% carbon dioxide). [District Rule 4301] Federally Enforceable Through Title V Permit
6. Landfill gas condensate can be injected into the enclosed flares. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The enclosed flares shall be equipped with automatic dampers, an automatic shutdown device, and a flame arrester. [District Rule 2201 and 17 CCR 95464] Federally Enforceable Through Title V Permit
8. VOC emissions from this landfill operation controlled with the 51 MMBtu/hr and 99 MMBtu/hr enclosed flares shall not exceed 804.3 lb/day (includes landfill fugitive, flare landfill gas, flare pilot, and flare condensate emissions). [District Rule 2201] Federally Enforceable Through Title V Permit
9. The enclosed flares shall either reduce VOC by 98 weight percent or reduce the outlet VOC concentration to less than 20 parts per million by volume, dry basis as methane at 3 percent oxygen. [District Rules 2201 and 4102, and 40 CFR 60.752(b)(2)(iii)(B) and 62.14353(b)] Federally Enforceable Through Title V Permit
10. The methane destruction efficiency for the enclosed flares shall be at least 99% by weight. [17 CCR 95464]
11. The landfill gas consumption rate for the 51 MMBtu/hr enclosed flare shall not exceed 51 MMBtu/hr. Heat input shall be calculated daily using landfill gas flow into the flare (cubic feet per minute) and the annually tested landfill gas heat content (Btu/cubic foot). [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The landfill gas consumption rate for the 99 MMBtu/hr enclosed flare shall not exceed 99 MMBtu/hr. Heat input shall be calculated daily using landfill gas flow into the flare (cubic feet per minute) and the annually tested landfill gas heat content (Btu/cubic foot). [District Rule 2201] Federally Enforceable Through Title V Permit
13. Emissions from the 51 MMBtu/hr enclosed flare shall not exceed any of the following limits: 0.05 lb-NO_x/MMBtu; 0.0178 lb-SO_x/MMBtu (46.9 ppmv of H₂S in fuel); 0.2 lb-CO/MMBtu; or 0.008 lb-PM₁₀/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Emissions from the 99 MMBtu/hr enclosed flare shall not exceed any of the following limits: 0.057 lb-NO_x/MMBtu; 0.0178 lb-SO_x/MMBtu (46.9 ppmv of H₂S in fuel); 0.110 lb-CO/MMBtu; or 0.008 lb-PM₁₀/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Landfill design capacity shall not exceed 44.4 million cubic yards, or 367 acres, of solid waste. Annual amount of refuse received shall not exceed 1,300,000 ton/year. [District Rule 2201] Federally Enforceable Through Title V Permit
16. The enclosed flares shall be equipped with an LPG fired pilot. [40 CFR 60.18(c)(2) and (f)(2)] Federally Enforceable Through Title V Permit
17. Emissions from the flare LPG-fired pilot shall not exceed any of the following limits: 0.15 lb-NO_x/MMBtu, 0.0164 lb-SO_x/MMBtu, 0.0044 lb-PM₁₀/MMBtu, 0.021 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Source sampling to determine the compliance status of an emissions source shall be witnessed or authorized by District personnel. [District Rule 1081] Federally Enforceable Through Title V Permit
19. The District must be notified 30 days prior to any compliance source test, and a source test plan must be submitted for approval 15 days prior to testing. The results of each source test shall be submitted to the District within 60 days after testing. [District Rule 1081] Federally Enforceable Through Title V Permit
20. Source testing to demonstrate compliance with VOC, NO_x, and CO emission limits and VOC control efficiency requirements shall be conducted at least once every 12 months for each flare. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Source testing for NO_x shall be conducted using EPA Test Method 7E or CARB Method 100. [District Rule 1081] Federally Enforceable Through Title V Permit
22. Source testing for CO shall be conducted using EPA Test Method 10 or 10B, CARB Methods 1-5 with 10 or CARB Test Method 100. [District Rule 1081] Federally Enforceable Through Title V Permit
23. Gas combusted in the flares shall be tested for H₂S content on a quarterly basis using Draeger tubes. If compliance is shown for two consecutive quarters, the testing frequency may be changed to annual. Quarterly testing shall resume if any annual test shows noncompliance. [District Rule 1081] Federally Enforceable Through Title V Permit
24. VOC emissions shall be measured by USEPA Test Method 18, 25, 25A, or 25C. [District Rule 1081 and 40 CFR 60.754(d) and 62.14354(b)] Federally Enforceable Through Title V Permit
25. The enclosed flares shall be equipped with a temperature indicator and recorder which measures and records the operating temperature. The temperature indicator and recorder must operate continuously. [40 CFR 60.756(b)(1) and 62.14354(b)] Federally Enforceable Through Title V Permit
26. The enclosed flare control devices shall be operated within the parameter ranges established during the initial or most recent performance test. [40 CFR 60.752(b)(2)(iii)(B)(2) and 62.14353(b) and 17 CCR 95464] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. Except during periods of startup, shutdown, and malfunction, the permittee shall continuously monitor and record combustion chamber temperature. The enclosed flare average combustion temperature, for all 3-hour periods of operation, shall not drop more than 28 degrees C below the average combustion temperature, during the most recent performance test at which compliance with 60.752(b)(2)(iii)(B)(2) was determined. Upon detecting any temperature excursion lower than 28 degree C (50 degree F) below the source test average combustion temperature, averaged over a 3-hour period, the permittee shall investigate the excursion and take corrective action to minimize excessive emissions and prevent recurrence of the excursion as expeditiously as practicable. Duration of startup, shutdown, or malfunction shall not exceed 5 days for collection systems and shall not exceed 1 hour for control devices where free venting of landfill gas occurs. [40 CFR 60.758(c)(1)(i), 60.755(e), 62.14354(b), and 40 CFR part 64] Federally Enforceable Through Title V Permit
28. The owner or operator shall measure the gauge pressure in the gas collection header at each individual interior well on a monthly basis as provided in 60.755(a)(3). If a positive pressure exists, action shall be initiated to correct the exceedance within 5 calendar days. If negative pressure cannot be achieved without excess air infiltration within 15 calendar days of the first measurement, the gas collection system shall be expanded to correct the exceedance within 120 days of the initial measurement of positive pressure. Any attempted corrective measure shall not cause exceedances of other operational or performance standards. An alternative timeline for correcting the exceedance may be submitted to the Administrator for approval. [40 CFR 60.755(a)(3), 60.756(a)(1), and 62.14354(b)] Federally Enforceable Through Title V Permit
29. The owner or operator shall monitor each interior well monthly for temperature and oxygen as provided in 60.753(c). If a well exceeds one of these operating parameters, action shall be initiated to correct the exceedance within 5 calendar days. If correction of the exceedance cannot be achieved within 15 calendar days of the first measurement, the gas collection system shall be expanded to correct the exceedance within 120 days of the initial exceedance. Any attempted corrective measure shall not cause exceedances of other operational or performance standards. An alternative timeline for correcting the exceedance may be submitted to the Administrator for approval. [40 CFR 60.753(c), 60.755(a)(3) and (a)(5), 60.756(a)(2) and (a)(3), and 62.14354(b)] Federally Enforceable Through Title V Permit
30. The operator shall record quarterly the surface emission tests including test time, weather conditions, precipitation records, areas sampled, calibration records, and test results. Corrective action shall be taken if required in accordance to 40 CFR 60.755(c). [District Rule 2201, 40 CFR 60.755(c), 60.756(f), and 62.14354(b)] Federally Enforceable Through Title V Permit
31. Permittee shall maintain continuous records of flare combustion temperature and volumetric gas flow rate. Permittee shall record and test the net heating value of landfill gas being combusted at least annually using ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201 and 40 CFR 60.756(b), 60.758(b)(2)(i), (c)(2) and (b)(2)(i), and 62.14354(b)] Federally Enforceable Through Title V Permit
32. Permittee shall keep, for the life of the collection system, an up-to-date, readily accessible plot map showing each existing and planned collector in the system and providing a unique identification location label for each collector. [40 CFR 60.758(d) and 60.34(c)] Federally Enforceable Through Title V Permit
33. The operator shall record emission control device source tests including VOC destruction/treatment efficiency and emissions of CO, NOx, and SOx, in pounds per MMBtu heat input. [District Rule 1081] Federally Enforceable Through Title V Permit
34. Records of the weight of materials received (tons) of Class II/III waste material shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
35. This operating permit may be cancelled upon District approval when the landfill is closed, is not otherwise subject to the requirements of 40 CFR part 70 or part 71, and if the landfill meets the conditions for control system removal specified in 40 CFR 60.752(b)(2)(v). [40 CFR 62.14352(f)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. An active collection system shall be designed to handle the maximum expected gas flow rate from the entire area of the landfill that warrants control over the intended use period of the gas control or treatment system equipment, collect gas from each area, cell, or group of cells in the landfill in which the initial solid waste has been placed for a period of 5 years or more if active; or 2 years or more if closed or at final grade, collect gas at a sufficient extraction rate, and be designed to minimize off-site migration of subsurface gas. [40 CFR 60.752(b)(2)(ii)(A) and 62.14353(b)] Federally Enforceable Through Title V Permit
37. If the landfill is permanently closed, a closure notification shall be submitted to the APCO within 30 days of waste disposal cessation. A permanent closure must take place in accordance with 40 CFR 258.60. If a closure report has been submitted, no additional waste may be placed in the landfill without filing a notification of modification to the APCO, pursuant to 40 CFR 60.7(a)(4). [40 CFR 60.752(b)(1)(ii)(B), 60.757(d), and 62.14354(b)] Federally Enforceable Through Title V Permit
38. For approval of collection and control systems that include any alternatives to the operational standards, test methods, procedures, compliance measures, monitoring, recordkeeping or reporting provisions, owner or operator must follow the procedures in 40 CFR 60.752(b)(2). If alternatives have already been approved under 40 CFR Part 62 subpart GGG, these alternatives can be used to comply with 40 CFR 63 subpart AAAA, except that all affected sources must comply with the startup, shutdown, and malfunction (SSM) requirements in subpart A of 40 CFR 63 as specified in Table 1 of 40 CFR 63 subpart AAAA and all affected sources must submit compliance reports every 6 months as specified in 40 CFR 63.1980(a) and (b), including information on all deviations that occurred during the 6 month reporting period. Deviations for continuous emission monitors or numerical continuous parameter monitors must be determined using a 3 hour monitoring block average. [40 CFR 60.752(b)(2) and 63.1955(c)] Federally Enforceable Through Title V Permit
39. Permittee shall operate the landfill gas collection system with negative pressure at each wellhead except under the following conditions: (1) A fire or increased well temperature. The owner or operator shall record instances when positive pressure occurs in efforts to avoid a fire. These records shall be submitted with the annual reports as provided in 60.757(f)(1); (2) At a wellhead within the immediate vicinity of filling; (3) Use of a geomembrane or synthetic cover. The owner or operator shall develop acceptable pressure limits in the design plan; (4) A decommissioned well. A well may experience a static positive pressure after shut down to accommodate for declining flows. All design changes shall be approved by the APCO. [40 CFR 60.753(b) and 62.14354(b) and 17 CCR 95464, 17 CCR 95468] Federally Enforceable Through Title V Permit
40. Permittee shall operate the collection system so that the methane concentration is less than 500 parts per million above background at the surface of the landfill. To determine if this level is exceeded, the owner or operator shall conduct surface testing around the perimeter of the collection area and along a pattern that traverses the landfill at 30 meter intervals and where visual observations indicate elevated concentrations of landfill gas, such as distressed vegetation and cracks or seeps in the cover. The owner or operator may establish an alternative traversing pattern that ensures equivalent coverage. A surface monitoring design plan shall be developed that includes a topographical map with the monitoring route and the rationale for any site-specific deviations from the 30 meter intervals. Areas with steep slopes or other dangerous areas may be excluded from the surface testing. [40 CFR 60.753(d), 60.755(c)(1) and 62.14354(b)] Federally Enforceable Through Title V Permit
41. Compliance with the surface methane operational standard shall be demonstrated using the procedures outlined in 40 CFR 60.755(c) within 180 days of installation and startup of the collection and control system and quarterly thereafter. [40 CFR 60.753(d), 60.755(c), 62.14354(b), and 60.8] Federally Enforceable Through Title V Permit
42. Permittee shall operate the enclosed flares at all times when the collected gas is routed to it. [40 CFR 60.753(f) and 62.14354(b)] Federally Enforceable Through Title V Permit
43. Permittee shall operate the landfill gas collection system such that gas is collected from each area, cell, or group of cells in the MSW landfill in which solid waste has been in place for: (1) five years or more if active; or (2) two years or more if closed or at final grade. [40 CFR 60.753(a) and 62.14354(b)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

44. Permittee shall operate each interior wellhead in the collection system with a landfill gas temperature less than 55 C and with oxygen level less than 5 percent except under the following conditions: (1) A fire or increased well temperature; or (2) at a wellhead within the immediate vicinity of filling. The owner or operator may establish a higher operating temperature or oxygen value at a particular well. A higher operating value demonstration shall show supporting data that the elevated parameter does not cause fires or significantly inhibit anaerobic decompositions by killing methanogens. [40 CFR 60.753(c) and 62.14354(b)] Federally Enforceable Through Title V Permit
45. The collection system shall be operated so that the methane concentration is less than 500 parts per million above background at the surface of the landfill, and such that all collected gases are sent to a control system designed and operated in compliance with 60.752(b)(2)(iii). In the event the collection or control system is inoperable, the gas mover system shall be shut down and all valves in the collection and control system contributing to venting of the gas to the atmosphere shall be closed within 1 hour. [40 CFR 60.753(d), (e), 60.755(c), and 62.14354(b)] Federally Enforceable Through Title V Permit
46. If monitoring demonstrates that the operational requirements are not met, corrective action shall be taken as specified in 40 CFR 60.755(a)(3) - 5) or (c). [40 CFR 60.753(g) and 62.14354(b)] Federally Enforceable Through Title V Permit
47. For each interior wellhead, unless an alternative test method is established as allowed by 60.752(b)(2)(i) of this subpart, the oxygen shall be determined by a Landtec GEM gas meter or equal, in accordance with the equipment requirements set forth in 40 CFR 60.753 for field measurement of temperature and oxygen or an oxygen meter using Method 3A or 3C except that: (i) The span shall be set so that the regulatory limit is between 20 and 50 percent of the span; (ii) A data recorder is not required; (iii) Only two calibration gases are required, a zero and span, and ambient air may be used as the span; (iv) A calibration error check is not required; (v) The allowable sample bias, zero drift, and calibration drift are +/-10 percent. [40 CFR 60.753(c)(2) and 62.14354(b)] Federally Enforceable Through Title V Permit
48. Surface emission monitoring shall be performed in accordance with section 4.3.1 of Method 21 of appendix A, except that the probe inlet shall be placed within 5 to 10 centimeters of the ground. Monitoring shall be performed during typical meteorological conditions. Any reading of 500 parts per million or more above background at any location shall be recorded as a monitored exceedance and the actions specified in 40 CFR 60.755(c)(4)(i-v) shall be taken. As long as the specified actions are taken, the exceedance is not a violation of the operational requirements of 60.753(d). [40 CFR 60.755(c)(3), (4) and 62.14354(b)] Federally Enforceable Through Title V Permit
49. Permittee shall calculate the NMOC emission rate for purposes of determining when the collection and control system can be removed as provided in 40 CFR 60.752(b)(2)(v) by using the equation found in 40 CFR 60.754(b). [40 CFR 60.754(b) and 62.14354(b)] Federally Enforceable Through Title V Permit
50. For the performance test required in 60.752(b)(2)(iii)(B), Method 25, 25C, or Method 18 of Appendix A must be used to determine compliance with the 98 weight percent efficiency or the 20 ppmv outlet concentration level, unless another method to demonstrate compliance has been approved by the APCO as provided by 60.752(b)(2)(i)(B). Method 3 or 3A shall be used to determine oxygen for correcting the NMOC concentration as hexane to 3 percent. In cases where the outlet concentration is less than 50 ppm NMOC as carbon (8 ppm NMOC as hexane), Method 25A should be used in place of Method 25. If using Method 18 of appendix A, the minimum list of compounds to be tested shall be those published in the most recent Compilation of Air Pollutant Emission Factors (AP-42). The following equation shall be used to calculate efficiency: $(\text{NMOC}_{\text{in}} - \text{NMOC}_{\text{out}}) / \text{NMOC}_{\text{in}}$. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081 and 40 CFR 60.754(d) and 62.14354(b)] Federally Enforceable Through Title V Permit
51. Each owner or operator shall place each well or design component as specified in the approved design plan as provided in 40 CFR 60.752(b)(2)(i). Each well shall be installed no later than 60 days after the date on which the initial solid waste has been in place for a period of: 1) 5 years or more if active or 2) 2 years or more if closed or at final grade. [40 CFR 60.755(b) and 62.14354(b)] Federally Enforceable Through Title V Permit
52. For the purposes of calculating the maximum expected gas generation flow rate from the landfill to determine compliance with 60.752(b)(2)(ii)(A)(1), one of the equations in Section 60.755(a)(1)(i) or (ii) or (iii) shall be used. [40 CFR 60.755(a)(1) and 62.14354(b)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

53. For the purposes of determining sufficient density of gas collectors for compliance with 60.752(b)(2)(ii)(A)(2), the owner or operator shall design a system of vertical wells, horizontal collectors, or other collection devices, satisfactory to the APCO, capable of controlling and extracting gas from all portions of the landfill sufficient to meet all operational and performance standards. [40 CFR 60.755(a)(2) and 62.14354(b)] Federally Enforceable Through Title V Permit
54. Owners or operators are not required to expand the system as required in paragraph 60.755(a)(3) during the first 180 days after gas collection system startup. [40 CFR 60.755(a)(4) and 62.14354(b)] Federally Enforceable Through Title V Permit
55. The provisions of this subpart apply at all times, except during periods of start-up, shutdown, or malfunction, provided that the duration of start-up, shutdown, or malfunction shall not exceed 5 days for collection systems and shall not exceed 1 hour for treatment or control devices. [40 CFR 60.755(e) and 62.14354(b)] Federally Enforceable Through Title V Permit
56. Surface monitoring shall be performed on a quarterly basis using an organic vapor analyzer, flame ionization detector, or other portable monitor meeting the specifications provided in 40 CFR 60.755(d). [40 CFR 60.755(c)(1) and 62.14354(b)] Federally Enforceable Through Title V Permit
57. When performing surface monitoring, the background concentration shall be determined by moving the probe inlet upwind and downwind outside the boundary of the landfill at a distance of at least 30 meters from the perimeter wells. [40 CFR 60.755(c)(2) and 62.14354(b)] Federally Enforceable Through Title V Permit
58. Permittee shall implement a program to monitor for cover integrity and implement cover repairs as necessary on a monthly basis. [40 CFR 60.755(c)(5) and 40 CFR 62.14354(b)] Federally Enforceable Through Title V Permit
59. The portable analyzer shall meet the instrument specifications of Method 21, section 3 (except that "methane" shall replace all references to VOC). The calibration gas shall be methane, diluted to a nominal concentration of 500 parts per million in air. To meet the performance evaluation requirements of Method 21, section 3.1.3, the instrument evaluation procedures of Method 21, section 4.4 shall be used. The calibration procedures provided in Method 21, section 4.2 shall be followed immediately before commencing a surface monitoring survey. The provisions of this condition apply at all times, except during periods of start-up, shutdown, or malfunction which shall not exceed 5 days for collections systems and shall not exceed 1 hour for treatment or control devices. [40 CFR 60.755(d), (e) and 62.14354(b)] Federally Enforceable Through Title V Permit
60. Each wellhead shall have a sampling port and a thermometer, other temperature-measuring device, or an access port for temperature measurements. [40 CFR 60.756(a)] Federally Enforceable Through Title V Permit
61. The enclosed flares shall be equipped with a temperature monitoring device equipped with a continuous recorder and having a minimum accuracy of ± 1 percent of the temperature being measured expressed in degrees Celsius or ± 0.5 degrees Celsius, whichever is greater. The temperature indicator and recorder must operate continuously. [District Rule 2201 and 40 CFR 60.756(b)(1) and 62.14354(b) and 40 CFR part 64] Federally Enforceable Through Title V Permit
62. The owner/operator shall install, calibrate, maintain, and operate a meter with a continuous recording device that measures and records the landfill gas flow rate into the flare at least once every 15 minutes. This meter shall also be capable of measuring the landfill gas flow rate that might bypass the flare in the event of equipment malfunction or maintenance. [40 CFR 60.754(b)(1), 60.756(b)(2) and 62.14354(b)] Federally Enforceable Through Title V Permit
63. When performing surface monitoring, any closed landfill that has no monitored exceedances of the operational standard in three consecutive quarterly monitoring periods may skip to annual monitoring. Any methane reading of 500 ppm or more above background detected during the annual monitoring returns the frequency for that landfill to quarterly monitoring. [40 CFR 60.756(f) and 62.14354(b)] Federally Enforceable Through Title V Permit
64. The operator shall monitor and record maintenance-related and other control system downtimes and individual well shutdowns. Exceedances defined under 60.758(c) shall be reported once every 180 days. [District Rule 4102 and 40 CFR 60.757(f), (g)(4) and 60.758(c) and (e), and 62.14354(b)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

65. Except as provided in 60.752(b)(2)(i)(B), each owner or operator of a controlled landfill shall keep up-to-date, readily accessible records for the life of the control equipment of the data listed in paragraphs 60.758(b)(1) through (b)(4) as measured during the initial performance test or compliance determination. Records of subsequent tests or monitoring shall be maintained for a minimum of 5 years. Records of the control device vendor specifications shall be maintained until removal. [40 CFR 60.758(b) and 62.14354(b)] Federally Enforceable Through Title V Permit
66. Permittee shall keep the following records: (1)(i) the maximum expected gas generation flow rate as calculated in 60.755(a)(1). The owner or operator may use another method to determine the maximum gas generation flow rate, if the method has been approved by the APCO; (ii) the density of wells, horizontal collectors, surface collectors, or other gas extraction devices determined using the procedures specified in 60.759(a)(1); (2)(i) the average combustion temperature measured at least every 15 minutes and averaged over the same time period of the performance test; (ii) the percent reduction of NMOC determined as specified in 60.752(b)(2)(iii)(B) achieved by the control device. [40 CFR 60.758(b)(1) and (2) and 62.14354(b)] Federally Enforceable Through Title V Permit
67. Except as provided in 60.752(b)(2)(i)(B), permittee shall keep, for the life of the collection system, an up-to-date, readily accessible plot map showing each existing and planned collector in the system and providing a unique identification location label for each collector. If applicable, permittee shall keep readily accessible documentation of the nature, date of deposition, amount, and location of asbestos-containing or nondegradable waste excluded from collection as well as any nonproductive areas excluded from collection. [40 CFR 60.758(d), 62.14354(b), and 60.34(c)] Federally Enforceable Through Title V Permit
68. Except as provided in 60.752(b)(2)(i)(B), permittee shall keep for at least 5 years up-to-date, readily accessible records of all collection and control system exceedances of the operational standards in 60.753, the reading in the subsequent month whether or not the second reading is an exceedance, and the location of each exceedance. [40 CFR 60.758(e)] Federally Enforceable Through Title V Permit
69. The landfill is no longer required to comply with the requirements of 40 CFR Part 63 Subpart AAAA when it is no longer required to apply controls as specified in the Federal plan or EPA approved and effective State plan or tribal plan that implements 40 CFR part 60, subpart Cc. [40 CFR 63.1950] Federally Enforceable Through Title V Permit
70. The permittee shall comply with the general provisions specified in Table 1 of 40 CFR Part 63 Subpart AAAA and 63.1960 through 63.1985 starting on the date required to install the gas collection and control system. [40 CFR 63.1955(b)] Federally Enforceable Through Title V Permit
71. The permittee shall maintain a copy of the SSM plan written according to the provisions in 40 CFR 63.6(e)(3). Failure to maintain a copy of the SSM plan is a deviation from the requirements of this subpart. [40 CFR 63.1960] Federally Enforceable Through Title V Permit
72. The permittee shall keep records and reports as specified in the Federal plan, EPA approved State plan or tribal plan that implements 40 CFR part 60, subpart Cc. The annual report described in 40 CFR 60.757(f) must be submitted every 6 months. [40 CFR 63.1980(a)] Federally Enforceable Through Title V Permit
73. The permittee shall maintain records as specified in the general provisions of 40 CFR part 60 and this part as shown in Table 1 of this subpart. Applicable records in the general provisions include items such as SSM plans and the SSM plan reports. [40 CFR 63.1980(b)] Federally Enforceable Through Title V Permit
74. The enclosed flare burner and its associated components and the vapor collection system shall be inspected on an annual basis. The records of inspection shall at least contain date and time of inspection, identification of the person performing an inspection, parts replacement and repairs, and all maintenance actions taken. The records shall be kept and maintained for compliance inspection upon request. [40 CFR part 64] Federally Enforceable Through Title V Permit
75. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR part 64] Federally Enforceable Through Title V Permit
76. The permittee shall comply with the recordkeeping and reporting requirements of 40 CFR part 64.9. [40 CFR part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

77. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR part 64.8. [40 CFR part 64] Federally Enforceable Through Title V Permit
78. All records shall be retained for a minimum of 5 years, and shall be made available for District inspection upon request. [District Rule 1070 and 40 CFR 60.758(a) and (b) and 62.14354(b)] Federally Enforceable Through Title V Permit
79. Permittee may use actual landfill gas generation values in future expansion designs of the gas collection and control system(GCCS). All records and recovery data shall be submitted with GCCS plans. [17 CCR 95468]
80. Landfill collection and control system must be operated such that methane emission from the landfill do not exceed instantaneous or integrated limit requirements. [17 CCR 95464]
81. Landfill gas collection system components downstream of blower have a leak limit of 500 ppmv as methane. Components must be checked quarterly. If compliance with the methane limit has been demonstrated for 4 consecutive quarters, then the component checking frequency shall be annually. If an annual test fails to show compliance, quarterly testing shall resume. [17 CCR 95464]
82. Landfill collection and control system must be operated such that landfill surface methane emissions shall not exceed instantaneous surface emission limit of 500 ppmv as methane or integrated surface emission limit of 25 ppmv as methane. [17 CCR 95464, 17 CCR 95465]
83. Instantaneous and integrated landfill surface emissions measurements shall be done quarterly. The landfill may monitor annually provided they comply with requirements of 17 CCR 95469 (a)(1). [17 CCR 95469]
84. Permittee shall keep records of all gas collection system downtime exceeding five days, including individual well shutdown and disconnection times and the reason for downtime. [17 CCR 95470]
85. Permittee shall keep records of all gas control system downtime in excess of one hour, the reason for the downtime and the length of time the gas control system was shutdown. [17 CCR 95470]
86. Permittee shall keep records of the expected gas generation flow rate calculated pursuant to section 95471(e). [17 CCR 95470]
87. Permittee shall keep records of all instantaneous surface readings of 200 ppmv or greater; all exceedances of the limits in sections 95464(b)(1)(B) or 95465, including the location of the leak (or affected grid), leak concentration in ppmv, date and time of measurement, the action taken to repair the leak, date of repair, any required re-monitoring and the re-monitored concentration in ppmv, and wind speed during surface sampling; and the installation date and location of each well installed as part of a gas collection system expansion. [17 CCR 95470]
88. Permittee shall keep records of any positive wellhead gauge pressure measurements, the date of the measurements, the well identification number, and the corrective action taken. [17 CCR 95470]
89. Permittee shall conduct surface emission monitoring using either the procedures specified in section 95471 or the Los Angeles County Sanitation District monitoring procedure. Permittee shall keep records of which procedure was used. [17 CCR 95468]
90. Permittee shall keep records of delays encountered during repair of leaks or repair of positive wellhead readings. Documentation of delays shall be submitted with the annual report. [17 CCR 95468]
91. Permittee shall keep records of alternate landfill gas collection system modifications being implemented to correct an exceedance in the landfill gas surface emissions or wellhead pressure. Any alternative to installing a new well shall be documented and submitted with the annual report. [17 CCR 95468]
92. Permittee shall identify areas which are dangerous and unable to be inspected. Areas shall be clearly identified on a map of the facility. A copy of the map shall be kept onsite as well as submitted with the annual report. [17 CCR 95468]
93. Permittee shall conduct monitoring of the landfill surface within 3 inches of the surface. The facility may monitor surface emissions with the probe tip at the height of the vegetation if there is vegetation and it is impractical to monitor at 3 inches from the landfill surface. [17 CCR 95468]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

94. Permittee shall terminate surface emission testing when the measured average wind speed is over 15 mph or the instantaneous wind speed is over 30 mph. [17 CCR 95468, 17 CCR 95471]
95. Permittee shall only conduct surface emission testing when precipitation has met the following requirements. It has been 24 hours since measured precipitation of 0.01 to 0.15 inches. It has been 48 hours since measured precipitation of 0.16 to 0.24 inches. It has been 72 hours since measured precipitation of 0.25 or more inches. [17 CCR 95468]
96. Permittee shall keep records of the annual solid waste acceptance rate and the current amount of waste-in-place. [17 CCR 95470]
97. Permittee shall keep records of the nature, location, amount, and date of deposition of non-degradable waste for any landfill areas excluded from the collection system. [17 CCR 95470]
98. Permittee shall keep records of any source tests conducted pursuant to section 95464(b)(4). [17 CCR 95470]
99. Permittee shall keep records describing the mitigation measures taken to prevent the release of methane or other emissions into the atmosphere during the following activities: 1. When solid waste was brought to the surface during the installation or preparation of wells, piping, or other equipment; 2. During repairs or the temporary shutdown of gas collection system components; or, 3. When solid waste was excavated and moved. [17 CCR 95470]
100. Permittee shall keep records of any construction activities pursuant to section 95466. The records must contain the following information: 1. A description of the actions being taken, the areas of the MSW landfill that will be affected by these actions, the reason the actions are required, and any landfill gas collection system components that will be affected by these actions. 2. Construction start and finish dates, projected equipment installation dates, and projected shut down times for individual gas collection system components. 3. A description of the mitigation measures taken to minimize methane emissions and other potential air quality impacts. [17 CCR 95470]
101. Permittee shall keep records of the equipment operating parameters specified to be monitored under section 95469(b)(1) as well as records for periods of operation during which the parameter boundaries established during the most recent source test are exceeded. The records must include the following information: 1. For enclosed flares, all 3-hour periods of operation during which the average temperature difference was more than 28 degrees Celsius (or 50 degrees Fahrenheit) below the average combustion temperature during the most recent source test at which compliance with sections 95464(b)(2) was determined and a gas flow rate device which must record the flow to the control device at least every 15 minutes. [17 CCR 95470]
102. Permittee shall submit the following reports as required in section 95470(b): Closure notification, Equipment removal report and Annual report. All reports must be accompanied by a certification of truth, accuracy, and completeness signed by a responsible official. [17 CCR 95470]
103. Permittee may comply with the CARB regulation for landfill methane control measures by using approved alternative compliance options. The permittee shall obtain written District approval for the use of any alternative compliance options not approved by this permit. Changes to the approved alternate compliance options must be made and approved in writing. Documentation of approved alternative compliance options shall be available for inspection upon request. [17 CCR 95468]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-3115-3-2

EXPIRATION DATE: 07/31/2021

EQUIPMENT DESCRIPTION:

755 BHP CUMMINS MODEL QSX15-69 DIESEL-FIRED EMERGENCY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with a non-resettable hour meter with a minimum display capability of 9,999 hours, unless the District determines that a non-resettable hour meter with a different minimum display capability is appropriate in consideration of the historical use of the engine and the owner or operator's compliance history. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
6. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
7. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
8. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. Operation of this engine for all purposes combined shall not exceed 10 hours per day. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
13. Emissions from this engine shall not exceed any of the following limits: 5.7 g-NO_x/hp-hr, 0.4 g-CO/hp-hr or 0.14 g-VOC/hp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The PM₁₀ emissions rate shall not exceed 0.08 g/hp-hr based on US EPA certification using ISO 8178 test procedure. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
16. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
17. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. For units at unstaffed sites or operated remotely, records may be maintained and retained at a District-approved off-site location. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
18. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR Subpart ZZZZ] Federally Enforceable Through Title V Permit
19. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
20. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
21. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
22. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
23. The engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.