

# Bay Area Air Quality Management District

939 Ellis Street  
San Francisco, CA 94109  
(415) 771-6000

---

---

## Proposed

# MAJOR FACILITY REVIEW PERMIT

**Issued To:**  
**Shore Terminals**  
**Facility #A7034**

**Facility Address:**  
2801 Waterfront Road  
Martinez, CA 94553

**Mailing Address:**  
2801 Waterfront Road  
Martinez, CA 94553

**Responsible Official**  
Michael J. Burgett  
Vice President, Operations  
(925) 228-3227

**Facility Contact**  
Myles Butler  
Terminal Manager  
(510) 228-3227

---

---

**Type of Facility:** Marine Terminal  
**Primary SIC:** 4226  
**Product:** Receiving, Storing and Shipping  
of Petroleum products

**BAAQMD Permit Division Contact:**  
Thu H. Bui

**ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT**

---

~~Ellen Garvey~~ William C. Norton, Executive Officer/Air Pollution Control Officer      Date

**TABLE OF CONTENTS**

I. STANDARD CONDITIONS ..... 3

II. EQUIPMENT ..... 7

III. GENERALLY APPLICABLE REQUIREMENTS ..... ~~99~~

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS ..... ~~1111~~

V. SCHEDULE OF COMPLIANCE ..... ~~6162~~

VI. PERMIT CONDITIONS ..... ~~6263~~

VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS ..... ~~8285~~

VIII. TEST METHODS ..... ~~110114~~~~112~~

IX. REVISION HISTORY ..... ~~115119~~~~117~~

X. GLOSSARY ..... ~~116120~~~~118~~

XI. APPLICABLE STATE IMPLEMENTATION PLAN ..... ~~120124~~~~122~~

## I. STANDARD CONDITIONS

### A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

- BAAQMD Regulation 1 - General Provisions and Definitions  
(as amended by the District Board on ~~11/15/005/1/01~~);
- SIP Regulation 1 - General Provisions and Definitions  
(as approved by EPA through ~~9/29/986/28/99~~);
- BAAQMD Regulation 2, Rule 1 - Permits, General Requirements  
(as amended by the District Board on ~~11/15/008/1/01~~);
- SIP Regulation 2, Rule 1 - Permits, General Requirements  
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 2 - Permits, New Source Review  
(as amended by the District Board on ~~10/7/985/17/00~~);
- SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration  
(as approved by EPA through 1/26/99);
- BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking  
(as amended by the District Board on ~~10/7/985/17/00~~); and
- SIP Regulation 2, Rule 4 - Permits, Emissions Banking  
(as approved by EPA through 1/26/99).
- BAAQMD Regulation 2, Rule 6 - Permits, Major Facility Review  
(as amended by the District Board on ~~10/20/995/1/01~~).

### B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit was issued on March 12, 2001 and expires on February 28, 2006. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than August 31, 2005, and no earlier than February 28, 2005. **If a complete application for renewal has not been submitted in accordance with ~~thisese~~ deadlines, the facility may not operate after February 28, 2006.** (Regulation 2-6-307, 404.2, & 409.6; MOP Volume II, Part 3, §4.2)
2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and re-issuance, or modification; or denial of a permit renewal application. (Regulation 2-6-307; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part 3, §4.11)
4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)

## **I. Standard Conditions**

5. The filing of a request by the facility for a permit modification, revocation and re-issuance, or termination, or the filing of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
6. This permit does not convey any property rights of any sort, nor any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
8. Any records required to be maintained pursuant to this permit that the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District's Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions or the potential to emit for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)
11. The responsible official shall certify all documents submitted by the facility pursuant to the major facility review permit. The certification shall state that based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. The certifications shall be signed by a responsible official for the facility. (MOP Volume II, Part 3, §4.11)

### **C. Requirement to Pay Fees**

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

### **D. Inspection and Entry**

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment ~~which that~~ is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

### **E. Records**

1. The permit holder must provide any information, records, and reports requested or specified by the APCO. (Regulation 1-441, Regulation 2-6-409.4)

## **I. Standard Conditions**

2. Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of entry. (Regulation 2-6-501, Regulation 3; MOP Volume II, Part 3, §4.7)

### **F. Monitoring Reports**

Reports of all required monitoring must be submitted to the District at least once every six months, except where an applicable requirement specifies more frequent reporting. The first reporting period for this permit shall be March 12, 2001 to August 31, 2001. The report shall be submitted by September 30, 2001. Subsequent reports shall be for the following periods: September 1<sup>st</sup> through February 28<sup>th</sup> or 29<sup>th</sup> and March 1<sup>st</sup> through August 31<sup>st</sup> and are due on the last day of the month after the end of the reporting period. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported in writing to the District's Compliance and Enforcement Division within 10 calendar days of the discovery of the incident. Within 30 calendar days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. The reports shall be sent to the following address:

Director of Compliance and Enforcement  
Bay Area Air Quality Management District  
939 Ellis Street  
San Francisco, CA 94109  
Attn: Title V Reports

(Regulation 2-6-502, Regulation 3; MOP Volume II, Part 3, §4.7)

### **G. Compliance Certification**

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification period will be March 1<sup>st</sup> to February 28<sup>th</sup> or 29<sup>th</sup> of each year. The certification shall be submitted by March 31<sup>st</sup> of each year. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms. The certification should be directed to the District's Compliance and Enforcement Division at the address above, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

Director of the Air Division  
USEPA, Region IX  
75 Hawthorne Street  
San Francisco, CA 94105  
Attention: Air-3

## **I. Standard Conditions**

(MOP Volume II, Part 3, §4.5 and 4.15)

### **H. Emergency Provisions**

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit ~~caused by conditions beyond the permit holder's reasonable control~~ by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. ~~Any variance granted by the Hearing Board from any term or condition of this permit which lasts longer than 90 days will be subject to EPA approval.~~ (MOP Volume II, Part 3, §4.8)
3. ~~Notwithstanding the foregoing,~~ The granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement. (MOP Volume II, Part 3, §4.8)

### **I. Severability**

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

### **J. Miscellaneous Conditions**

1. The maximum capacity for each source as shown in Table II-A is the maximum allowable capacity. Exceedance of the maximum allowable capacity for any source is a violation of Regulation 2, Rule 1, Section 301. (Regulation 2-1-301)

## II. EQUIPMENT

**Table II A - Permitted Sources**

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301.

S-#	Description	Make or Type	Model	Capacity
1	Tank T-1	Fixed Roof Tank		3,360,000 gallons
2	Tank T-2	Fixed Roof Tank		3,360,000 gallons
3	Tank T-3	Fixed Roof Tank		2,310,000 gallons
4	Tank T-4	Fixed Roof Tank		2,310,000 gallons
5	Tank T-5	Fixed Roof Tank		2,310,000 gallons
6	Tank T-6	Fixed Roof Tank		2,310,000 gallons
7	Tank T-7	Fixed Roof Tank		2,310,000 gallons
8	Tank T-8	Fixed Roof Tank		840,000 gallons
9	Tank T-9	Fixed Roof Tank		420,000 gallons
10	Tank T-10	Fixed Roof Tank		126,000 gallons
11	Tank T-11 (slop)	Fixed Roof Tank		7,000 gallons
12	Tank T-12	Fixed Roof Tank		25,000 gallons
13	Tank T-13	External Floating Roof Tank		21,000,000 gallons
14	Tank T-14	External Floating Roof Tank		21,000,000 gallons
15	Tank T-15	External Floating Roof Tank		21,000,000 gallons
16	Tank T-16	External Floating Roof Tank		21,000,000 gallons
18	Tank T-34	Fixed Roof Tank		12,000 gallons
19	Tank T-35	Fixed Roof Tank		12,000 gallons
20	Tank Truck Loading Rack	Truck/Rail		12 Gasoline Fillers
21	Marine Vessel Wharf	Marine		3 Gasoline Fillers
23	Oily Water Separator – Black System	Oil Water Separator	Custom	23 gal/hr
24	Oily Water Separator – Clean System		Custom	0.5 gal/hr
27	Storage Tank T-39	Fixed Roof Tank		7,350,000 gallons
28	Storage Tank T-40	Fixed Roof Tank		7,350,000 gallons
73	Direct Fired Heater (diesel, natural gas)			25 MMBtu/hr
74	<u>Emergency Diesel Generator</u>	<u>IC Engine</u>	<u>Cummins</u> <u>210-IF</u>	<u>1.2 MMBtu/hr, 157 HP</u>

## II. Equipment

**Table II A - Permitted Sources**

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits. The capacities in this table are the maximum allowable capacities for each source, pursuant to Standard Condition I.J and Regulation 2-1-301.

S-#	Description	Make or Type	Model	Capacity
75	Emergency Diesel Generator	IC Engine	Cummins 280-IF	1.2 MMBtu/hr, 145 HP
76	Storage Tank # 11041	Internal Floating Roof		4,200,000 gallons
77	Storage Tank # 11042	Internal Floating Roof		4,200,000 gallons
78	Storage Tank # 11043	Internal Floating Roof		4,200,000 gallons

**Table II B – Abatement Devices**

A-#	Description	Source(s) Controlled	Applicable Requirement	Operating Parameters	Limit or Efficiency
A-1	Thermal Oxidizer, <u>Natural Gas, (235 MMBtu/hr)</u>	S-1 through S-12, S-18, S-19, S-20, <u>S-21</u> , S-27, S-28	BAAQMD Condition # 1253 Part III <del>D</del> , schedule D	Continuous hydrocarbon concentration monitor, continuous temperature monitor	POC = 1.44 lb/1000 barrel NOx = 9.68 lb/day plus 0.177 lb/1000 barrel; Temp. ≥ 1400°F
<del>A-2</del>	<del>Vapor Recovery</del>	<del>S-1 through S-12, S-18, S-19, S-20, S-27, S-28</del>	<del>BAAQMD Condition # 1253 Part III <del>D</del>, schedule</del>	<del>Continuous hydrocarbon concentration monitor, continuous temperature monitor</del>	<del>POC = 1.44 lb/1000 barrel NOx = 9.68 lb/day plus 0.177 lb/1000 barrel; Temp. ≥ 1400°F</del>
<del>A-41</del>	<del>Vapor Combustion Unit</del>	<del>S-1 through S-12, S-18, S-19, S-20, S-21, S-27, S-28</del>	<del>BAAQMD Condition # 1253 Part IV, section 3</del>	<del>Continuous hydrocarbon concentration monitor, continuous temperature monitor, static pressure instrument</del>	<del>POC = 1.44 lb/1000 barrel NOx = 9.68 lb/day plus 0.177 lb/1000 barrel; Temp. ≥ 1400°F</del>

### III. GENERALLY APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements would not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in Section IV, Source-Specific Applicable Requirements, of this permit.

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date.

The full language of SIP requirements is on EPA Region 9's website. The address is included at the end of this permit.

~~The full language of SIP requirements is included in Appendix A of this permit if the SIP requirement is different from the current BAAQMD requirement.~~

**NOTE:**

There are differences between the current BAAQMD rule and the version of the rule in the SIP. ~~For specific information, contact the District's Rule Development Section of the Enforcement Division.~~ All sources must comply with both versions of the rule until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

**Table III  
 Generally Applicable Requirements**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>
BAAQMD Regulation 1	General Provisions and Definitions ( <del>11/15/005</del> <u>1/01</u> )	N
SIP Regulation 1	General Provisions and Definitions ( <del>9/29/986</del> <u>28/99</u> )	Y
<u>BAAQMD Regulation 2, Rule 1</u>	<u>General Requirements (8/1/01)</u>	<u>N</u>
<u>BAAQMD 2-1-429</u>	<u>Federal Emissions Statement (6/7/95)</u>	<u>Y</u>
<u>SIP Regulation 2, Rule 1</u>	<u>General Requirements (1/26/99)</u>	<u>Y</u>
BAAQMD Regulation 4	Air Pollution Episode Plan (3/20/91)	N

### III. Generally Applicable Requirements

**Table III**  
**Generally Applicable Requirements**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>
SIP Regulation 4	Air Pollution Episode Plan (8/06/90)	Y
BAAQMD Regulation 5	Open Burning ( <del>3/6/02</del> 1/2/94)	N
<u>SIP Regulation 5</u>	<u>Open Burning (9/4/98)</u>	<u>Y</u>
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	Y
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N
BAAQMD Regulation 8, Rule 1	Organic Compounds – General Provisions (6/15/94)	Y
BAAQMD Regulation 8, Rule 3	Organic Compounds – Architectural Coatings ( <del>12/20/95</del> 1/21/01)	Y
<u>SIP Regulation 8, Rule 3</u>	<u>Organic Compounds - Architectural Coatings (2/18/98)</u>	<u>Y</u>
BAAQMD Regulation 8, Rule 18	Organic Compounds – Equipment Leaks (1/7/98)	N
SIP Regulation 8, Rule 18	Valves and Connectors at Petroleum Complexes, Chemical Plants, Bulk Plants and Bulk Terminals (3/4/92)	Y
SIP Regulation 8, Rule 25	Pump and Compressor Seals at Petroleum Refineries, Chemical Plants, Bulk Plants and Bulk Terminals (6/1/94)	Y
BAAQMD Regulation 8, Rule 33	Organic Compounds – Waste (Oil-Water) Separators (6/1/94)	Y
BAAQMD Regulation 8, Rule 49	Organic Compounds – Aerosol Paint Products (12/20/95)	N
SIP Regulation 8, Rule 49	Organic Compounds – Aerosol Paint Products (3/22/95)	Y
BAAQMD Regulation 8, Rule 51	Organic Compounds – Adhesive and Sealant Products (12/20/95)	N
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants – Asbestos Demolition, Renovation and Manufacturing (12/4/91)	Y
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (7/11/90)	Y
<u>SIP Regulation 12, Rule 4</u>	<u>Miscellaneous Standards of Performance - Sandblasting (9/2/81)</u>	<u>Y</u>
<u>California Health and Safety Code Section 44300 et seq.</u>	<u>Air Toxics “Hot Spots” Information and Assessment Act of 1987</u>	<u>N</u>
<u>40 CFR Part 61, Subpart M</u>	<u>National Emission Standards for Hazardous Air Pollutants – National Emission Standard for Asbestos (6/19/95)</u>	<u>Y</u>

#### IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s).

The dates in parentheses in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s): The date(s) of adoption or most recent amendment of the regulation by the District Board of Directors
2. Any federal requirement, including a version of a District regulation that has been approved into the SIP: The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. The full language of SIP requirements is on EPA Region 9's website. The address is included at the end of this permit. The full language of SIP requirements is included in Appendix A of this permit if the SIP requirements are different from the current BAAQMD requirements. All other text may be found in the regulations themselves.

**Table IV – A**  
**Source-specific Applicable Requirements**  
**S-1 THROUGH S-10 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 8, Rule 5</b>	<b>Organic Compounds-General Provisions (<del>1211/2715/0299</del>)</b>		
8-5-101	Description	Y	
8-5-111	Limited Exemption, Tank Removal From and Return to Service	<del>NN</del>	
8-5-112	Limited Exemption, Tanks in Operation	N	
8-5-117	Exemption, Low Vapor Pressure	<del>YN</del>	
<del>8-5-304</del> <u>301</u>	<del>Storage tanks larger than 75 cubic meter</del> <u>Storage Tanks Control Requirements</u>	<del>Y</del> <u>Y</u>	
<del>8-5-303</del>	<del>Requirements for Pressure Vacuum Valves</del>	<del>Y</del>	
<del>8-5-306</del>	<del>Requirements for Approved Emission Control System</del>	<del>Y</del>	
<del>8-5-311</del>	<del>Vapor loss control device requirements</del>	<del>Y</del>	
<del>8-5-311.3</del>	<del>Emission control system with an efficiency of at least 95% by weight</del>	<del>Y</del>	
8-5-328	Tank cleaning requirements	Y	

## IV. Source-specific Applicable Requirements

**Table IV – A**  
**Source-specific Applicable Requirements**  
**S-1 THROUGH S-10 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<u>8-5-328.1.2</u>	<u>Concentration of &lt;10,000 ppm as methane after cleaning</u>	<u>N</u>	
<del>8-5-328.2</del>	<del>An Emission Control System with an efficiency of at least 90% by weight</del>	<del>Y</del>	
<del>8-5-329</del>	<del>Ozone excess day prohibition</del>	<del>Y</del>	
<del>8-5-403</del>	<del>Inspection Requirements for Pressure Vacuum Valves</del>	<u>N</u>	
8-5-404	Certification	<del>Y</del> <u>N</u>	
<del>8-5-404.3</del>	<del>Tank degassing equipment</del>	<del>Y</del>	
8-5-501	Keep records	<del>Y</del> <u>Y</u>	
8-5-502	Tank cleaning annual source test requirement	Y	
8-5-503	Portable hydrocarbon detector	Y	
<b>SIP Regulation 8, Rule 5</b>	<b>Storage of Organic Liquids (12/2015/9399)</b>		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y	
8-5-112	Limited Exemption, Tanks in Operation	Y	
<del>8-5-117</del>	<del>Exemption, Low Vapor Pressure</del>	<u>Y</u>	
<del>8-5-304</del>	<del>Storage Tanks Larger than 75 m<sup>3</sup></del>	<u>Y</u>	
<del>8-5-311</del>	<del>Vapor loss control device requirements</del>	<u>Y</u>	
<del>8-5-311.3</del>	<del>Emission control system with an efficiency of at least 95% by weight</del>	<u>Y</u>	
<del>8-5-329</del>	<del>Ozone excess day prohibition</del>	<u>Y</u>	
<del>8-5-330</del>	<del>Viewport Installation</del>	<u>Y</u>	
<del>8-5-404</del>	<del>Certification</del>	<u>Y</u>	
<del>8-5-404.3</del>	<del>Tank degassing equipment</del>	<u>Y</u>	
<del>8-5-501</del>	<del>Keep records</del>	<u>Y</u>	
<del>8-5-503</del>	<del>Portable hydrocarbon detector</del>	<u>Y</u>	
<b>40 CFR 60</b>	<b>Standards of Performance for New Stationary Sources (12/23/71)</b>	Y	
Subpart A	General Provisions	Y	
60.4(b)	Reports to EPA and District	Y	
60.7(a)	Written notification	Y	
60.7(b)	Records	Y	
60.8	Performance Tests	Y	
60.9	Availability of Information	Y	
60.11(a)	Compliance with standards and maintenance requirements	Y	
60.11(d)	Minimizing emissions	Y	

## IV. Source-specific Applicable Requirements

**Table IV – A**  
**Source-specific Applicable Requirements**  
**S-1 THROUGH S-10 - FIXED ROOF TANKS**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
60.12	Circumvention	Y	
60.13	Reconstruction	Y	
60.19	General notification and reporting requirements	Y	
<b>NSPS Part 60 Subpart K</b>	<b>Standards of Performance for Volatile Organic Liquid Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978</b>	Y	
60.110(c)(2)	Affected tanks that are greater than or equal to 65,000 gallons	Y	
60.112(a)(1)	Vapor pressure is equal to or greater than 1.5 psia shall be equipped with a vapor recovery system, or their equivalent	Y	
60.112(a)(2)	Vapor pressure is equal to or greater than 11.1 psia shall be equipped with a vapor recovery system, or their equivalent	Y	
60.113	Monitor of operations	Y	
<b>40 CFR 63</b>	<b>National Emission Standards for Hazardous Air Pollutants for Source Categories</b>	Y	
Subpart A	General Provisions	Y	
63.4	Prohibited activities and circumvention	Y	
63.5	Construction and reconstruction	Y	
63.6	Compliance with standards and maintenance requirements	Y	
63.7	Performance testing requirements	Y	
63.8	Monitoring requirements	Y	
63.9	Notification requirements	Y	
63.10	Recordkeeping and reporting requirements	Y	
63.12	State authority and delegations	Y	
63.15	Availability of Information and confidentiality	Y	
<b>NESHAPS Part 63 Subpart R</b>	<b>National Emission Standards for Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations)</b>	Y	
63.420(a)(1)	Affected terminal	Y	
63.420(b)(1)	Affected pipeline breakout station	Y	
63.420(f)	Demonstrate compliance	Y	
63.420(g)	Most stringent control requirements	Y	
63.420(h)	Subject to the provisions of 40 CFR part 63, subpart A—General Provisions	Y	
63.420(j)	<i>Rules Stayed for Reconsideration</i>	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – A**  
**Source-specific Applicable Requirements**  
**S-1 THROUGH S-10 - FIXED ROOF TANKS**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.423	Standards: Storage vessels		
63.423(a)	Requirements	Y	
63.423(c)	December 15, 1997 deadline	Y	
63.425	Test methods and procedures	Y	
63.425(a)	Performance test on the vapor processing system	Y	
63.425(b)	Operating parameter		
63.425(b)(1)	Determine an operating parameter value	Y	
63.425(b)(2)	Determine an operating monitoring parameter value	Y	
63.425(b)(3)	Demonstrate continuous compliance	Y	
63.425(c)	Document the reasons for any change in the operating parameter	Y	
63.425(d)	Compliance with § 60.113b	Y	
63.427	Continuous monitoring	Y	
63.427(a)(3)	Continuous parameter monitoring system (CPMS), Temperature	Y	
63.427(a)(5)	Alternative parameter demonstrates continuous compliance	Y	
63.427(b)	Operate the vapor processing system	Y	
63.427(c)	Monitoring requirements in § 60.116b; 5 yr recordkeeping	Y	
63.428	Reporting and recordkeeping	Y	
63.428(a)	The initial notifications	Y	
63.428(c)(2)	Record and report simultaneously with the notification of compliance	Y	
63.428(c)(2)(i)	Determining the operating parameter value	Y	
63.428(d)	Keep records and furnish reports	Y	
63.428(e)	Work practice program recordkeeping	Y	
63.428(h)	Submit an excess emissions report to the administrator	Y	
63.428(h)(1)	Each exceedance or failure reports	Y	
63.428(h)(4)	Equipment leak	Y	
63.428(h)(4)(i)	The date on which the leak was detected	Y	
63.428(h)(4)(ii)	The date of each attempt to repair the leak	Y	
63.428(h)(4)(iii)	The reasons for the delay of repair; and	Y	
63.428(h)(4)(iv)	The date of successful repair	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – A**  
**Source-specific Applicable Requirements**  
**S-1 THROUGH S-10 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Condition # 1253</b>	<b>Permit Conditions</b>		
Part IB	Total facility organic compound emissions shall not exceed <del>65.167,146</del> tpy [Basis: Cumulative Increase]	Y	
<u>Part IID</u>	<u>Sources S-1 through S-10 shall be abated by A-1, thermal oxidizer.</u> <u>[Basis: Cumulative Increase]</u>	<u>Y</u>	
Part III <del>DD</del> , Schedule D	Organic emission shall not exceed 1.44 lb/1000 barrels for Vapor Control Equipment/Vapor Recovery System Emissions [Basis: Cumulative Increase]	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – B**  
**Source-specific Applicable Requirements**  
**S-11 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 8, Rule 5</b>	<b>Organic Compounds-General Provisions (<del>12/11/1527/9902</del>)</b>		
8-5-101	Description	Y	
8-5-111	Limited Exemption, Tank Removal From and Return to Service	N	
8-5-112	Limited Exemption, Tanks in Operation	N	
8-5-117	Exemption, Low Vapor Pressure	<del>Y</del> N	
8-5-301	<del>Storage tanks smaller than 150 cubic meter</del> <u>Storage Tanks Control Requirements</u>	<del>Y</del> Y	
8-5-302	<del>Above Ground Gasoline Storage Tanks smaller than 75 cubic meter</del> <u>Requirements for Submerged Fill Pipes</u>	Y	
<del>8-5-303</del>	<u>Requirements for Pressure Vacuum Valves</u>	Y	
8-5-328	Tank cleaning requirements	Y	
<del>8-5-328.1.2</del>	<u>Concentration of &lt;10,000 ppm as methane after cleaning</u>	N	
<del>8-5-329</del>	<del>Ozone excess day prohibition</del>	<del>Y</del>	
<del>8-5-403</del>	<u>Inspection Requirements for Pressure Vacuum Valves</u>	N	
8-5-404	Certification	Y	
<del>8-5-404.3</del>	<del>Tank degassing equipment</del>	<del>Y</del>	
8-5-501	Keep records	<del>Y</del> N	
8-5-502	Tank cleaning annual source test requirement	Y	
8-5-503	Portable hydrocarbon detector	Y	
<b>SIP Regulation 8, Rule 5</b>	<b>Storage of Organic Liquids (<del>12/2015/9399</del>)</b>		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y	
8-5-112	Limited Exemption, Tanks in Operation	Y	
<del>8-5-117</del>	<del>Exemption, Low Vapor Pressure</del>	Y	
<del>8-5-301</del>	<del>Storage Tanks smaller than 150 m<sup>3</sup></del>	Y	
<del>8-5-302</del>	<del>Above Ground Gasoline Storage Tanks smaller than 75 cubic meter</del>	Y	
<del>8-5-329</del>	<del>Ozone excess day prohibition</del>	Y	
<del>8-5-330</del>	<u>Viewport Installation</u>	Y	
<del>8-5-404</del>	<u>Certification</u>	Y	
<del>8-5-404.3</del>	<u>Tank degassing equipment</u>	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – B**  
**Source-specific Applicable Requirements**  
**S-11 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<u>8-5-501</u>	<u>Keep records</u>	<u>Y</u>	
<u>8-5-503</u>	<u>Portable hydrocarbon detector</u>	<u>Y</u>	
<b>BAAQMD Condition # 1253</b>	<b>Permit Conditions</b>		
Part IB	Total facility organic compound emissions shall not exceed <del>65.4</del> <u>67.146</u> tpy [Basis: Cumulative Increase]	Y	
<u>Part IID</u>	<u>Source S-11 shall be abated by A-1, thermal oxidizer. [Basis: Cumulative Increase]</u>	<u>Y</u>	

#### IV. Source-specific Applicable Requirements

**Table IV – C**  
**Source-specific Applicable Requirements**  
**S-12, S-18, AND S-19 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 8, Rule 5</b>	<b>Organic Compounds-General Provisions (<del>1211/1527/9902</del>)</b>		
8-5-101	Description	Y	
8-5-111	Limited Exemption, Tank Removal From and Return to Service	N	
8-5-112	Limited Exemption, Tanks in Operation	N	
8-5-117	Exemption, Low Vapor Pressure	<del>Y</del> N	
8-5- <del>304</del> <u>301</u>	<del>Storage tanks larger than 75 cubic meter</del> <u>Storage Tanks Control Requirements</u>	Y	
<del>8-5-303</del>	<del>Requirements for Pressure Vacuum Valves</del>	<del>Y</del>	
<del>8-5-306</del>	<del>Requirements for Approved Emission Control System</del>	<del>Y</del>	
<del>8-5-311</del>	<del>Vapor loss control device requirements</del>	<del>Y</del>	
<del>8-5-311.3</del>	<del>Emission control system with an efficiency of at least 95% by weight</del>	<del>Y</del>	
8-5-328	Tank cleaning requirements	Y	
<del>8-5-328.1.2</del>	<del>Concentration of &lt;10,000 ppm as methane after cleaning</del>	<del>N</del>	
<del>8-5-328.2</del>	<del>An Emission Control System with an efficiency of at least 90% by weight</del>	<del>Y</del>	
<del>8-5-329</del>	<del>Ozone excess day prohibition</del>	<del>Y</del>	
<del>8-5-403</del>	<del>Inspection Requirements for Pressure Vacuum Valves</del>	<del>N</del>	
8-5-404	Certification	<del>Y</del> N	
<del>8-5-404.3</del>	<del>Tank degassing equipment</del>	<del>Y</del>	
8-5-501	Keep records	<del>Y</del> N	
8-5-502	Tank cleaning annual source test requirement	Y	
8-5-503	Portable hydrocarbon detector	Y	
<b>SIP Regulation 8, Rule 5</b>	<b>Storage of Organic Liquids (<del>12/2015/9399</del>)</b>		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y	
8-5-112	Limited Exemption, Tanks in Operation	Y	
<del>8-5-117</del>	<del>Exemption, Low Vapor Pressure</del>	<del>Y</del>	
<del>8-5-304</del>	<del>Storage Tanks Larger than 75 m<sup>3</sup></del>	<del>Y</del>	
<del>8-5-311</del>	<del>Vapor loss control device requirements</del>	<del>Y</del>	
<del>8-5-311.3</del>	<del>Emission control system with an efficiency of at least 95% by weight</del>	<del>Y</del>	

#### IV. Source-specific Applicable Requirements

**Table IV – C**  
**Source-specific Applicable Requirements**  
**S-12, S-18, AND S-19 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<a href="#">8-5-329</a>	<a href="#">Ozone excess day prohibition</a>	<u>Y</u>	
<a href="#">8-5-330</a>	<a href="#">Viewport Installation</a>	<u>Y</u>	
<a href="#">8-5-404</a>	<a href="#">Certification</a>	<u>Y</u>	
<a href="#">8-5-404.3</a>	<a href="#">Tank degassing equipment</a>	<u>Y</u>	
<a href="#">8-5-501</a>	<a href="#">Keep records</a>	<u>Y</u>	
<a href="#">8-5-503</a>	<a href="#">Portable hydrocarbon detector</a>	<u>Y</u>	
<b>40 CFR 63</b>	<b>National Emission Standards for Hazardous Air Pollutants for Source Categories</b>	Y	
Subpart A	General Provisions	Y	
63.4	Prohibited activities and circumvention	Y	
63.5	Construction and reconstruction	Y	
63.6	Compliance with standards and maintenance requirements	Y	
63.7	Performance testing requirements	Y	
63.8	Monitoring requirements	Y	
63.9	Notification requirements	Y	
63.10	Recordkeeping and reporting requirements	Y	
63.12	State authority and delegations	Y	
63.15	Availability of Information and confidentiality	Y	
<b>NESHAPS Part 63 Subpart R</b>	<b>National Emission Standards for Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations)</b>	Y	
63.420(a)(1)	Affected terminal	Y	
63.420(b)(1)	Affected pipeline breakout station	Y	
63.420(f)	Demonstrate compliance	Y	
63.420(g)	Most stringent control requirements	Y	
63.420(h)	Subject to the provisions of 40 CFR part 63, subpart A—General Provisions	Y	
63.420(j)	<i>Rules Stayed for Reconsideration</i>	Y	
63.423	Standards: Storage vessels		
63.423(a)	Requirements	Y	
63.423(c)	December 15, 1997 deadline	Y	
63.425	Test methods and procedures	Y	
63.425(a)	Performance test on the vapor processing system	Y	
63.425(b)	Operating parameter		
63.425(b)(1)	Determine an operating parameter value	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – C**  
**Source-specific Applicable Requirements**  
**S-12, S-18, AND S-19 - FIXED ROOF TANKS**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.425(b)(2)	Determine an operating monitoring parameter value	Y	
63.425(b)(3)	Demonstrate continuous compliance	Y	
63.425(c)	Document the reasons for any change in the operating parameter	Y	
63.425(d)	Compliance with § 60.113b	Y	
63.427	Continuous monitoring	Y	
63.427(a)(3)	Continuous parameter monitoring system (CPMS), Temperature	Y	
63.427(a)(5)	Alternative parameter demonstrates continuous compliance	Y	
63.427(b)	Operate the vapor processing system	Y	
63.427(c)	Monitoring requirements in § 60.116b; 5 yr recordkeeping	Y	
63.428	Reporting and recordkeeping	Y	
63.428(a)	The initial notifications	Y	
63.428(c)(2)	Record and report simultaneously with the notification of compliance	Y	
63.428(c)(2)(i)	Determining the operating parameter value	Y	
63.428(d)	Keep records and furnish reports	Y	
63.428(e)	Work practice program recordkeeping	Y	
63.428(h)	Submit an excess emissions report to the administrator	Y	
63.428(h)(1)	Each exceedance or failure reports	Y	
63.428(h)(4)	Equipment leak	Y	
63.428(h)(4)(i)	The date on which the leak was detected	Y	
63.428(h)(4)(ii)	The date of each attempt to repair the leak	Y	
63.428(h)(4)(iii)	The reasons for the delay of repair; and	Y	
63.428(h)(4)(iv)	The date of successful repair	Y	
<b>BAAQMD Condition # 1253</b>	<b>Permit Conditions</b>		
Part IB	Total facility organic compound emissions shall not exceed <del>65.167.146</del> tpy [Basis: Cumulative Increase]	Y	
<u>Part IID</u>	<u>Sources S-12, S-18 and S-19 shall be abated by A-1, thermal oxidizer. [Basis: Cumulative Increase]</u>	<u>Y</u>	

#### IV. Source-specific Applicable Requirements

**Table IV – C**  
**Source-specific Applicable Requirements**  
**S-12, S-18, AND S-19 - FIXED ROOF TANKS**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
Part III <del>DD</del> , Schedule D	Organic emission shall not exceed 1.44 lb/1000 barrels for Vapor Control Equipment/Vapor Recovery System Emissions [Basis: Cumulative Increase]	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – D**  
**Source-specific Applicable Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 8, Rule 5</b>	<b>Organic Compounds-General Provisions (<del>1211/4527/9902</del>)</b>		
8-5-101	Description	Y	
8-5-111	Limited Exemption, Tank Removal From and Return to Service	N	
8-5-112	Limited Exemption, Tanks in Operation	N	
8-5-117	Exemption, Low Vapor Pressure	<del>Y</del>	
<del>8-5-304</del> <u>301</u>	<del>Storage tanks larger than 75 cubic meter</del> <u>Storage Tanks Control Requirements</u>	Y	
<del>8-5-303</del>	<del>Requirements for Pressure Vacuum Valves</del>	<u>Y</u>	
<del>8-5-304</del>	<del>Requirements for External Floating Roofs</del>	<u>N</u>	
<del>8-5-311</del>	<del>Vapor loss control device requirements</del>	<del>Y</del>	
<del>8-5-311.1</del>	<del>Primary and secondary seals</del>	<del>Y</del>	
8-5-320	Tank fitting requirements	Y	
<del>8-5-320.1</del>	<del>Secondary seal</del>	<del>Y</del>	
8-5-320.2	Openings in the roof	Y	
<del>8-5-320.2.1</del>	<del>Projection below liquid surface</del>	<del>Y</del>	
<del>8-5-320.2.2</del>	<del>Viewports and other openings</del>	<del>Y</del>	
8-5-320.3	<del>Pressure vacuum valves</del> <u>Gasketed Covers</u>	Y	
8-5-320.4	Solid sampling or gauging wells	Y	
8-5-320.4.1	The well shall provide a projection below the liquid surface	Y	
8-5-320.4.2	The well shall be equipped with a cover	Y	
8-5-320.4.3	The gap between the well and the roof	Y	
8-5-320.5	Slotted sampling or gauging wells	Y	
8-5-320.5.1	The well shall provide a projection below the liquid surface	Y	
8-5-320.5.2	The well requirements	<del>Y</del>	
8-5-320.5.3	The gap between the well and the roof	Y	
8-5-320.6	Emergency roof drain	Y	
8-5-321	Primary seal requirements	Y	
8-5-321.1	No holes, tears, or other openings in the primary seal fabric	Y	
8-5-321.2	The seal shall be liquid mounted except as provided in 8-5-311.2.2	Y	
8-5-321.3	Metallic shoe type seals	<del>Y</del>	
8-5-321.3.1	Geometry of shoe	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – D**  
**Source-specific Applicable Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-5-321.3.2	Gaps for welded tanks	Y	
8-5-322	Secondary seal requirements	Y	
8-5-322.1	No holes, tears, or other openings in the secondary seal	Y	
8-5-322.2	Insertion of probes	Y	
8-5-322.3	Gaps for welded tanks	Y	
8-5-328	Tank <del>cleaning</del> - <u>Degassing</u> requirements	Y	
<del>8-5-328.1</del>	<del>Liquid balancing, or</del>	<del>Y</del>	
<u>8-5-328.1.2</u>	<u>Concentration of &lt;10,000 ppm as methane after cleaning</u>	<u>N</u>	
8-5-328.2	An approved Emission Control System	Y	
<del>8-5-329</del>	<del>Ozone excess day prohibition</del>	<del>Y</del>	
8-5-401	Primary seal inspection	<del>Y</del>	
8-5-401.1	Once every 10 years for tanks subject to 8-5-322.5	<del>Y</del> <u>N</u>	
<del>8-5-401.2</del>	<del>Tank Fitting Inspection</del>	<del>Y</del> <u>N</u>	
<del>8-5-402</del>	<del>Secondary seal and fitting inspection</del>	<del>Y</del>	
<del>8-5-402.1</del>	<del>Once every 10 years for tanks subject to 8-5-322.5</del>	<del>Y</del>	
<del>8-5-403</del>	<del>Inspection Requirements for Pressure Vacuum Valves</del>	<del>Y</del> <u>N</u>	
8-5-404	Certification	<del>Y</del> <u>N</u>	
<del>8-5-404.1</del>	<del>For primary seal</del>	<del>Y</del>	
<del>8-5-404.2</del>	<del>For secondary seal</del>	<del>Y</del>	
<del>8-5-404.2.1</del>	<del>Annual basis for tanks subject to 8-5-311.1</del>	<del>Y</del>	
<del>8-5-404.3</del>	<del>For tank degassing equipment</del>	<del>Y</del>	
8-5-405	Information required	Y	
8-5-405.1	Date of inspection	Y	
8-5-405.2	Actual gap measurements	Y	
8-5-405.3	Data, supported calculation	Y	
8-5-501	Records	<del>Y</del> <u>N</u>	
8-5-502	Tank cleaning annual source test requirement	Y	
8-5-503	Portable hydrocarbon detector	Y	
<b>SIP Regulation 8, Rule 5</b>	<b>Storage of Organic Liquids (<del>112/2015/9399</del>)</b>		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y	
8-5-112	Limited Exemption, <del>Tanks in Operation</del> <u>Floating Roofs in Operation</u>	Y	
<del>8-5-117</del>	<del>Exemption, Low Vapor Pressure</del>	<del>Y</del>	

## IV. Source-specific Applicable Requirements

**Table IV – D**  
**Source-specific Applicable Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<a href="#">8-5-304</a>	<a href="#">Storage tanks larger than 75 cubic meter</a>	<u>Y</u>	
<a href="#">8-5-311</a>	<a href="#">Vapor loss control device requirements</a>	<u>Y</u>	
<a href="#">8-5-311.1</a>	<a href="#">Primary and secondary seals</a>	<u>Y</u>	
<a href="#">8-5-320</a>	<a href="#">Tank fitting requirements</a>	<u>Y</u>	
<a href="#">8-5-320.1</a>	<a href="#">Secondary seal</a>	<u>Y</u>	
<a href="#">8-5-320.2</a>	<a href="#">Openings in the roof</a>	<u>Y</u>	
<a href="#">8-5-320.2.1</a>	<a href="#">The opening</a>	<u>Y</u>	
<a href="#">8-5-320.2.2</a>	<a href="#">Viewports and other openings</a>	<u>Y</u>	
<a href="#">8-5-320.3</a>	<a href="#">Pressure vacuum valves</a>	<u>Y</u>	
<a href="#">8-5-320.4</a>	<a href="#">Solid sampling or gauging wells</a>	<u>Y</u>	
<a href="#">8-5-320.4.1</a>	<a href="#">The well shall provide a projection below the liquid surface</a>	<u>Y</u>	
<a href="#">8-5-320.4.2</a>	<a href="#">The well shall be equipped with a cover</a>	<u>Y</u>	
<a href="#">8-5-320.4.3</a>	<a href="#">The gap between the well and the roof</a>	<u>Y</u>	
<a href="#">8-5-320.5</a>	<a href="#">Slotted sampling or gauging wells</a>	<u>Y</u>	
<a href="#">8-5-320.5.1</a>	<a href="#">The well shall provide a projection below the liquid surface</a>	<u>Y</u>	
<a href="#">8-5-320.5.2</a>	<a href="#">The well requirements</a>	<u>Y</u>	
<a href="#">8-5-320.5.3</a>	<a href="#">The gap between the well and the roof</a>	<u>Y</u>	
<a href="#">8-5-320.6</a>	<a href="#">Emergency roof drain</a>	<u>Y</u>	
<a href="#">8-5-321</a>	<a href="#">Primary seal requirements</a>	<u>Y</u>	
<a href="#">8-5-321.1</a>	<a href="#">No holes, tears, or other openings in the primary seal fabric</a>	<u>Y</u>	
<a href="#">8-5-321.2</a>	<a href="#">The seal shall be liquid mounted except as provided in 8-5-311.2.2</a>	<u>Y</u>	
<a href="#">8-5-321.3</a>	<a href="#">Metallic shoe type seals</a>	<u>Y</u>	
<a href="#">8-5-321.3.1</a>	<a href="#">Geometry of shoe</a>	<u>Y</u>	
<a href="#">8-5-321.3.2</a>	<a href="#">For welded tanks</a>	<u>Y</u>	
<a href="#">8-5-329</a>	<a href="#">Ozone excess day prohibition</a>	<u>Y</u>	
<a href="#">8-5-330</a>	<a href="#">Viewport Installation</a>	<u>Y</u>	
<a href="#">8-5-401</a>	<a href="#">Primary seal inspection</a>	<u>Y</u>	
<a href="#">8-5-401.1</a>	<a href="#">Once every 10 years for tanks subject to 8-5-322.5</a>	<u>Y</u>	
<a href="#">8-5-402</a>	<a href="#">Secondary seal and fitting inspection</a>	<u>Y</u>	
<a href="#">8-5-402.1</a>	<a href="#">Once every 10 years for tanks subject to 8-5-322.5</a>	<u>Y</u>	
<a href="#">8-5-404</a>	<a href="#">Certification</a>	<u>Y</u>	
<a href="#">8-5-404.1</a>	<a href="#">For primary seal</a>	<u>Y</u>	
<a href="#">8-5-404.2</a>	<a href="#">For secondary seal</a>	<u>Y</u>	
<a href="#">8-5-404.2.1</a>	<a href="#">Annual basis for tanks subject to 8-5-311.1</a>	<u>Y</u>	

#### IV. Source-specific Applicable Requirements

**Table IV – D**  
**Source-specific Applicable Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<a href="#">8-5-404.3</a>	<a href="#">For tank degassing equipment</a>	<u>Y</u>	
<a href="#">8-5-405</a>	<a href="#">Information required</a>	<u>Y</u>	
<a href="#">8-5-405.1</a>	<a href="#">Date of inspection</a>	<u>Y</u>	
<a href="#">8-5-405.2</a>	<a href="#">Actual gap measurements</a>	<u>Y</u>	
<a href="#">8-5-405.3</a>	<a href="#">Data, supported calculation</a>	<u>Y</u>	
<a href="#">8-5-501</a>	<a href="#">Records</a>	<u>Y</u>	
<b>40 CFR 60</b>	<b>Standards of Performance for New Stationary Sources (12/23/71)</b>	Y	
Subpart A	General Provisions	Y	
60.4(b)	Reports to EPA and District	Y	
60.7(a)	Written notification	Y	
60.7(b)	Records	Y	
60.8	Performance Tests	Y	
60.9	Availability of Information	Y	
60.11(a)	Compliance with standards and maintenance requirements	Y	
60.11(d)	Minimizing emissions	Y	
60.12	Circumvention	Y	
60.13	Reconstruction	Y	
60.19	General notification and reporting requirements	Y	
<b>NSPS Part 60 Subpart K</b>	<b>Standards of Performance for Volatile Organic Liquid Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978</b>	Y	
60.110(c)(2)	Affected tanks that are greater than or equal to 65,000 gallons	Y	
60.112(a)(1)	Vapor pressure is equal to or greater than 1.5 psia shall be equipped with a vapor recovery system, or their equivalent	Y	
60.112(a)(2)	Vapor pressure is equal to or greater than 11.1 psia shall be equipped with a vapor recovery system, or their equivalent	Y	
60.113	Monitor of operations	Y	
<b>40 CFR 63</b>	<b>Standards of Performance for New Stationary Sources</b>	Y	
Subpart A	General Provisions	Y	
63.4	Prohibited activities and circumvention	Y	
63.5	Construction and reconstruction	Y	
63.6	Compliance with standards and maintenance requirements	Y	
63.7	Performance testing requirements	Y	
63.8	Monitoring requirements	Y	

## IV. Source-specific Applicable Requirements

**Table IV – D**  
**Source-specific Applicable Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.9	Notification requirements	Y	
63.10	Recordkeeping and reporting	Y	
63.12	State authority and delegations	Y	
63.15	Availability of Information and confidentiality	Y	
<b>NSPS Part 63 Subpart R</b>	<b>National Emission Standards for Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations)</b>	Y	
63.420(f)	Demonstrate compliance	Y	
63.420(g)	Most stringent control requirements	Y	
63.420(h)	Subpart A—General Provisions	Y	
63.420(j)	<i>Rules Stayed for Reconsideration</i>	Y	
63.423	Standards: Storage vessels	Y	
63.423(a)	Requirements in § 60.112b(a) (1) through (4)	Y	
63.423(b)	External floating roof storage requirements in § 60.112b(a)(2)(ii)	Y	
63.423(c)	December 15, 1997 deadline	Y	
63.425	Test methods and procedures	Y	
63.425(d)	Comply with § 60.113b	Y	
63.427	Continuous monitoring	Y	
63.427(c)	Monitoring requirements in § 60.116b; 5 yr recordkeeping	Y	
63.428	Reporting and recordkeeping	Y	
63.428(a)	The initial notification requirement	Y	
63.428(d)	Keep records and furnish reports	Y	
<b>BAAQMD Condition # 1253</b>	<b>Permit Conditions</b>		
Part IIID, Schedule A	POC emission limitation [Basis: Cumulative Increase]	Y	
Part IIID, Schedule D	Tank Standing Emission Calculations [Basis: Regulation 8-5]	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – E**  
**Source-specific Applicable Requirements**  
**S-20 – TANK TRUCK LOADING RACK**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
<b>BAAQMD Regulation 8, Rule 33</b>	<b>Organic Compounds-Gasoline bulk terminals and gasoline delivery vehicles (6/1/94)</b>		
8-33-112	Tank Gauging and inspection	Y	
8-33-113	Maintenance and repair exemption	Y	
8-33-301	Final gasoline bulk terminal limitations	Y	
8-33-302	Vapor Recovery System requirement	Y	
8-33-303	Bottom fill requirement	Y	
8-33-304	Delivery vehicle requirements		
8-33-304.1	Vapor Integrity Requirement	Y	
8-33-304.2	Vapor recovery requirement	Y	
8-33-304.4	Purging requirement	Y	
8-33-305	Equipment Maintenance	Y	
8-33-306	Operating practices	Y	
8-33-307	Loading practices	Y	
8-33-308	Vapor Diaphragm Requirements	Y	
8-33-309	Vapor Recovery System Requirements – Loading Rack	Y	
8-33-401	Equipment installation and modification	Y	
<b>40 CFR 63</b>	<b>National Emission Standards for Hazardous Air Pollutants for Source Categories</b>	Y	
Subpart A	General Provisions	Y	
63.4	Prohibited activities and circumvention	Y	
63.5	Construction and reconstruction	Y	
63.6	Compliance with standards and maintenance requirements	Y	
63.7	Performance testing requirements	Y	
63.8	Monitoring requirements	Y	
63.9	Notification requirements	Y	
63.10	Recordkeeping and reporting	Y	
63.12	State authority and delegations	Y	
<b>NESHAPS Part 63 Subpart R</b>	<b>National Emission Standards for Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations)</b>	Y	
63.420(a)(1)	Affected Terminal	Y	
63.420(b)(1)	Affected Pipeline Breakout Station	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – E**  
**Source-specific Applicable Requirements**  
**S-20 – TANK TRUCK LOADING RACK**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.420(g)	Most stringent control requirements	Y	
63.420(h)	40 CFR part 63, subpart A—General Provisions	Y	
63.420(j)	<i>Rules Stayed for Reconsideration</i>	Y	
63.422	Standards: Loading racks	Y	
63.422(a)	Comply with the requirements in § 60.502	Y	
63.422(b)	Emission Limitation ≤ 10 milligram/liter of gasoline loaded	Y	
63.422(c)	Comply with § 60.502(e)	Y	
63.422(c)(1)	The term “tank truck” as used in § 60.502(e) means “cargo tank.”	Y	
63.422(c)(2)	Vapor tightness documentation	Y	
63.422(c)(2)(i)	The gasoline cargo tank meets the applicable test requirements in § 63.425(e)	Y	
63.422(c)(2)(ii)	Gasoline cargo tank failing the test in § 63.425 (f) or (g) at the facility, the cargo tank either	Y	
63.422(c)(2)(ii)(A)	Meets the test requirements in § 63.425 (g) or (h)	Y	
63.422(c)(2)(ii)(B)	Passes the annual certification test	Y	
63.422(d)	December 15, 1997 deadline	Y	
63.425	Test methods and procedures	Y	
63.425(a)	Conduct a performance test	Y	
63.425(b)	Determine a monitored operating parameter	Y	
63.425(b)(1)	Continuously record the operating parameter	Y	
63.425(b)(2)	Determine an operating parameter value	Y	
63.425(b)(3)	Develop the value, monitoring frequency	Y	
63.425(c)	Document the reasons for any change in the operating parameter value	Y	
63.427	Continuous monitoring	Y	
63.427(a)(3)	Continuous parameter monitoring system (CPMS), Temperature	Y	
63.427(b)	The vapor processing system operation	Y	
63.428	Reporting and recordkeeping	Y	
63.428(a)	The initial notifications	Y	
63.428(b)	Keep records of the test results for each gasoline cargo tank loading	Y	
63.428(b)(1)	Annual certification testing	Y	
63.428(b)(2)	Continuous performance testing performed at any time	Y	
63.428(b)(3)	The documentation file	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – E**  
**Source-specific Applicable Requirements**  
**S-20 – TANK TRUCK LOADING RACK**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.428(b)(3) (i)	Name of test	Y	
63.428(b)(3) (ii)	Cargo tank owner's name and address	Y	
63.428(b)(3) (iii)	Cargo tank identification number	Y	
63.428(b)(3) (iv)	Test location and date	Y	
63.428(b)(3) (v)	Tester name and signature	Y	
63.428(b)(3) (vi)	Witnessing inspector, if any: Name, signature, and affiliation	Y	
63.428(b)(3) (vii)	Vapor tightness repair	Y	
63.428(b)(3) (viii)	Test results	Y	
63.428(c)	Bulk gasoline terminal requirements	Y	
63.428(c)(1)	Accessible record of the continuous monitoring data	Y	
63.428(c)(2)	Record and report simultaneously with the notification of compliance	Y	
63.428(c) (2)(i)	Determining the operating parameter value	Y	
63.428(c)(3)	Vapor processing system or monitor an operating parameter	Y	
63.428(e)	Work practice program recordkeeping		
63.428(g)	Include information	Y	
63.428(g)(1)	Vapor tightness documentation	Y	
63.428(h)	Submit an excess emissions report	Y	
63.428(h)(1)	The report shall include the monitoring data	Y	
63.428(h)(2)	Vapor tightness documentation	Y	
63.428(h)(3)	Reloading of a nonvapor-tight gasoline cargo tank	Y	
63.428(h)(4)	Equipment leak	Y	
63.428(h)(4) (I)	The date on which the leak was detected	Y	
63.428(h)(4) (ii)	The date of each attempt to repair the leak	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – E**  
**Source-specific Applicable Requirements**  
**S-20 – TANK TRUCK LOADING RACK**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.428(h)(4)(iii)	The reasons for the delay of repair	Y	
63.428(h)(4)(iv)	The date of successful repair	Y	
<b>NESHAPS Part <del>63-60</del> Subpart XX</b>	<b>National Emission Standards for Bulk Gasoline Terminals</b>	Y	
<del>6360</del> .500(a)	Loading racks at a bulk gasoline terminal applicability	Y	
<del>6360</del> .500(b)	December 17, 1980	Y	
<del>6360</del> .502	Standard for VOC emissions from bulk gasoline terminals	Y	
<del>6360</del> .502(a)	Vapor collection system requirement	Y	
<del>6360</del> .502(b)	The atmospheric emission limits	Y	
<del>6360</del> .502(c)	The vapor collection emission limits, existing	Y	
<del>6360</del> .502(d)	Prevent any VOC vapors collected at one loading rack from passing to another loading rack	Y	
<del>6360</del> .502(e)	Vapor-tight gasoline tank trucks	Y	
<del>6360</del> .502(e)(1)	The owner or operator shall obtain the vapor tightness documentation	Y	
<del>6360</del> .502(e)(2)	Tank identification number requirement	Y	
<del>6360</del> .502(e)(3)	Cross-check each tank identification number with the file of tank vapor tightness documentation	Y	
<del>6360</del> .502(e)(4)	Notification of each nonvapor-tight gasoline tank truck	Y	
<del>6360</del> .502(e)(5)	Vapor tightness documentation	Y	
<del>6360</del> .502(e)(6)	Alternate procedures	Y	
<del>6360</del> .502(f)	Vapor collection equipment	Y	
<del>6360</del> .502(g)	Training drivers in the hookup procedures and posting visible reminder signs	Y	
<del>6360</del> .502(h)	The vapor collection and liquid loading equipment	Y	
<del>6360</del> .502(i)	No pressure-vacuum at a system pressure less than 4,500 pascals	Y	
<del>6360</del> .502(j)	Inspection for organic compounds liquid or vapor leaks	Y	
<del>6360</del> .503	Test methods and procedures		
<del>6360</del> .503(a)	Methods and procedures of test methods	Y	
<del>6360</del> .503(b)	Method 21 to monitor for leakage of vapor	Y	
<del>6360</del> .503(c)	Determine compliance with the standards	Y	
<del>6360</del> .503(c)(1)	The performance test	Y	
<del>6360</del> .503(c)(2)	Performance test for intermittent operation	Y	
<del>6360</del> .503(c)(3)	The emission rate (E) of total organic compounds	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – E**  
**Source-specific Applicable Requirements**  
**S-20 – TANK TRUCK LOADING RACK**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
6360.503(c)(4)	The performance test	Y	
6360.503(c)(5)	Methods used to determine the volume (Vesi) air vapor mixture exhausted	Y	
6360.503(c)(5)(ii)	Method 2A shall be used for all other vapor processing system	Y	
6360.503(c)(6)	Method 25A or 25B shall be used for determining the total organics	Y	
6360.503(c)(7)	Determine the volume (L) of gasoline dispensed	Y	
6360.503(d)	Determine compliance with the standard	Y	
6360.503(d)(1)	A pressure measurement device	Y	
6360.503(d)(2)	Highest instantaneous pressure	Y	
6360.505	Reporting and recordkeeping	Y	
6360.505(a)	The tank truck vapor tightness documentation	Y	
6360.505(b)	The documentation file for each gasoline tank truck	Y	
6360.505(b)(1)	Gasoline Delivery Tank Pressure Test—EPA Reference Method 27	Y	
6360.505(b)(2)	Tank owner and address	Y	
6360.505(b)(3)	Tank identification number	Y	
6360.505(b)(4)	Testing location	Y	
6360.505(b)(5)	Date of test	Y	
6360.505(b)(6)	Tester name and signature	Y	
6360.505(b)(7)	Witnessing inspector, if any: Name, signature, and affiliation	Y	
6360.505(b)(8)	Test results: Actual pressure change in 5 minutes, mm of water	Y	
6360.505(c)	Inspection records	Y	
6360.505(c)(1)	Date of inspection	Y	
6360.505(c)(2)	Findings	Y	
6360.505(c)(3)	Leak determination method	Y	
6360.505(c)(4)	Corrective action	Y	
6360.505(c)(5)	Inspector name and signature	Y	
6360.505(d)	Documentation of all notifications	Y	
6360.505(f)	Records of all replacements or additions of components	Y	
6360.506	Reconstruction	Y	
6360.506(a)	Cost calculations	Y	
6360.506(b)	Fixed capital cost	Y	
<b>BAAQMD Condition # 1253</b>	<b>Permit Conditions</b>		

#### IV. Source-specific Applicable Requirements

**Table IV – E**  
**Source-specific Applicable Requirements**  
**S-20 – TANK TRUCK LOADING RACK**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<del>Part IA</del> Part IA	<del>POC, CO, NOx, SO2, PM emission limitations</del> Deleted	<del>Y</del> N	
Part IB	POC, CO, NOx, SO2, PM emission limitations [Basis: Cumulative Increase]	Y	
Part IID	Source S-20 shall be abated by A-1, thermal oxidizer. [Basis: Cumulative Increase]	Y	
Part IIIA, Section 1	Report volume of gasoline throughput at the truck rack [Basis: Cumulative Increase]	Y	
Part IIID, Schedule A	POC emission limitation [Basis: Cumulative Increase]	Y	
Part IIID, Schedule D	NOX and Organic emission limitations [Basis: Cumulative Increase]	Y	

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 8, Rule 44</b>	<b>Organic Compounds-Marine Vessel Loading Terminals (1/4/89)</b>		
8-44-110	Exemption: loading events	Y	
8-44-111	Exemption: marine vessel fueling	Y	
8-44-301.1	Limited to 5.7 gram per cubic meter (2 lbs per 1000 bbls) of organic liquid loaded, or	Y	
8-44-301.2	95% by weight from uncontrolled conditions	Y	
8-44-302	Emission control equipment	Y	
8-44-303	Operating practice	Y	
8-44-304.1	Certified leak free, gas tight and in good working vessel	Y	
8-44-304.2	Loading ceases any time gas or leaks are discovered	Y	
8-44-305	Ozone excess day prohibition	Y	
8-44-402.1	Safety/Emergency operations	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
8-44-402.2	Safety/Emergency operations	Y	
8-44-501	Record keeping	Y	
8-44-501.1	Name and location	Y	
8-44-501.2	Responsible company	Y	
8-44-501.3	Dates and times	Y	
8-44-501.4	Name, registry of the vessel loaded and legal owner	Y	
8-44-501.5	Prior cargo carried	Y	
8-44-501.6	Type, amount of liquid cargo loaded	Y	
8-44-501.7	Condition of tanks	Y	
8-44-502	Burden of proof	Y	
<b>40 CFR 63</b>	<b>National Emission Standards for Hazardous Air Pollutants for Source Categories</b>	Y	
Subpart A	General Provisions	Y	
63.4	Prohibited activities and circumvention	Y	
63.5	Construction and reconstruction	Y	
63.6	Compliance with standards and maintenance requirements	Y	
63.7	Performance testing requirements	Y	
63.8	Monitoring requirements	Y	
63.9	Notification requirements	Y	
63.10	Recordkeeping and reporting	Y	
63.12	State authority and delegations	Y	
<b>NESHAPS Part 63 Subpart Y</b>	<b>National Emission Standards for Marine Tank Vessel Loading Operations</b>	Y	
63.560(b)	Reasonable available control technology (RACT)	Y	
63.560(b)(1)	Sources with throughput of 10 million barrels or 200 million barrels	Y	
63.560(c)	General provisions applicability	Y	
63.560(d)(7)	Do not apply to ballasting operations	Y	
63.560(e)	Compliance dates		
63.560(e)(2)(i)	RACT compliance dates for sources with an initial startup date on or before September 21, 1998	Y	
63.560(e)(2)(ii)	RACT compliance dates	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.560(e)(2)(iii)	RACT compliance dates	Y	
63.560(e)(2)(v)	Extension of compliance date	Y	
63.562(a)	Emission limitations	Y	
63.562(c)(1)	RACT standards	Y	
63.562(c)(2)(i)	Vapor collection system of the terminal	Y	
63.562(c)(2)(ii)	Ship-to-shore compatibility	Y	
63.562(c)(2)(iii)	Vapor tightness of marine vessels	Y	
63.562(c)(3)	RACT standard: 98 % weight when using combustion device	Y	
63.562(c)(4)	Or 1,000 ppmv outlet VOC concentration	Y	
63.562(c)(6)	Maintenance allowance for loading berths	Y	
63.562(c)(6)(i)	Maintenance	Y	
63.562(b)(6)(ii)	Conditions beyond reasonable control	Y	
63.562(c)(6)(iii)	Hardship cannot be justified by the resulting air quality benefit	Y	
63.562(c)(6)(iv)	Curtailing marine vessel loading operations during maintenance	Y	
63.562(c)(6)(v)	Reduce emissions from other loading berths	Y	
63.562(c)(6)(vi)	Monitoring and reporting emissions from the loading berth	Y	
63.562(e)	Operation & maintenance requirements for air pollution control equipment	Y	
63.562(e)(1)	Determine compliance with design, equipment, work practice or operational emission standards	Y	
63.562(e)(2)	Develop and implement a written operation and maintenance plan	Y	
63.562(e)(2)(i)	Procedures of preventive maintenance	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.562(e)(2)(ii)	Identify, monitor and record all operating parameters	Y	
63.562(e)(2)(iii)	Inspection schedule	Y	
63.562(e)(2)(iv)	Continuous monitoring system (CMS) quality control program	Y	
63.562(e)(3)(I)	Revision of the operation and maintenance plan if does not address: Variance of the control equipment	Y	
63.562(e)(3)(ii)	Fail to provide safety and good air pollution control practices	Y	
63.562(e)(3)(iii)	Inadequate procedures for correcting a variance	Y	
63.562(e)(4)	Revise the operation maintenance plane within 45 working days after variance has occurred	Y	
63.562(e)(5)	Keep the written operation and maintenance plan on record for inspection	Y	
63.562(e)(6)	Source's standard operating procedures (SOP) manual, Occupational safety and health administration (OSHA) plan and others are satisfied	Y	
63.563	Compliance and performance testing	Y	
63.563(a)(1)(i)	Vent stream by-pass requirements for the terminal's vapor collection system	Y	
63.563(a)(1)(ii)	Repairs	Y	
63.563(a)(2)	Ship-to-shore compatibility	Y	
63.563(a)(3)	Pressure/vacuum settings for the marine vessel's vapor collection equipment	Y	
63.563(a)(4)	Vapor tightness requirements	Y	
63.563(a)(4)(i)	Pressure test documentation	Y	
63.563(a)(4)(ii)	Leak test documentation	Y	
63.563(a)(4)(iii)	Leak test performance	Y	
63.563(a)(4)(iii)(A)	No leak documentation	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.563(a)(4)(iii)(B)	Leak process	Y	
63.563(a)(4)(iv)	Negative pressure loading	Y	
63.563(b)	Compliance determination	Y	
63.563(b)(1)	Initial performance	Y	
63.563(b)(2)	Performance test exemptions	Y	
63.563(b)(2)(i)	Boilers or process heater with 44 megawatt or less comply with 63.562b(2), (3), or (4), c(3) or (4) or d(2)	Y	
63.563(b)(2)(ii)	Boilers or process heater 44 megawatt or more comply with 63.562b(2), (3), or (4), c(3) or (4) or d(2)	Y	
63.563(b)(2)(iii)	Boilers subject to 40 CFR part 266, subpart H comply with 63.562b(2), (3), or (4), c(3) or (4) or d(2)	Y	
63.563(b)(3)	Operation and maintenance inspections	Y	
63.563(b)(4)	Combustion device, except flare	Y	
63.563(b)(4)(i)	Outlet VOC concentration limit for percent combustion efficiency	Y	
63.563(b)(4)(ii)	Baseline temperature for required percent combustion efficiency	Y	
63.563(b)(10)	Emission estimation	Y	
63.563(c)	Leak detection and repair for vapor collection systems and control devices	Y	
63.563(c)(1)	Annual leak detection and repair	Y	
63.563(c)(2)	Ongoing leak detection	Y	
63.563(c)(3)	Repair within 15 days	Y	
63.564	Monitoring requirements		
63.564(a)(1)	Comply with monitoring requirement	Y	
63.564(a)(2)	Monitor equipment verification	Y	
63.564(a)(3)	Continuous operation	Y	
63.564(a)(4)	CMS comply with performance specification	Y	
63.564(a)(5)	Submit all information concerning out of control periods	Y	
63.564(b)	Vapor collection system of terminal	Y	
63.564(b)(1)	Measure and record vent stream flowrate	Y	
63.564(b)(2)	Flow indicator	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.564(b)(3)	Visual inspection	Y	
63.564(c)	Pressure/vacuum settings	Y	
63.564(d)	Loading at negative pressure	Y	
63.564(e)	Combustion device, except flare		
63.564(e)(1)	Outlet VOC concentration	Y	
63.564(e)(2)	Operating temperature determined during performance testing	Y	
63.564(e)(3)	Manufacturer’s recommended operating temperature	Y	
63.564(e)(4)	Temperature monitor	Y	
63.565(a)	Performance testing	Y	
63.565(b)	Pressure/vacuum settings of marine tank vessel’s vapor collection equipment	Y	
63.565(b)(1)	Calibrate and install a pressure measurement device	Y	
63.565(b)(2)	Connect the pressure measurement device to a pressure tap in the terminal’s vapor collection system	Y	
63.565(b)(3)	Record the pressure	Y	
63.565(c)	Vapor tightness test procedures for the marine tank vessel	Y	
63.565(c)(1)	Pressure test	Y	
63.565(c)(1)(i)	Product tank shall be pressurized with dry air or inert gas	Y	
63.565(c)(1)(ii)	Once the pressure is obtained, dry air or inert gas source shall be shut off	Y	
63.565(c)(1)(iii)	Measure the pressure	Y	
63.565(c)(1)(iv)	Compare the pressure	Y	
63.565(c)(1)(v)	Vessel is vapor tight	Y	
63.565(c)(1)(vi)	Or not vapor tight	Y	
63.565(c)(2)	Leak test	Y	
63.565(d)(1)	Testing equipment preparation and installation	Y	
63.565(d)(2)	Test Performance during last 20% of loading	Y	
63.565(d)(3)	Emission testing interval	Y	
63.565(d)(3)(i)	Readings	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.565(d)(3)(ii)	Sampling sites	Y	
63.565(d)(3)(iii)	Volume exhaust	Y	
63.565(d)(4)	Combustion devices	Y	
63.565(d)(6)	VOC mass at the inlet and outlet calculation	Y	
63.565(d)(7)	VOC mass emission rate at the inlet and outlet calculation	Y	
63.565(d)(8)	Method 25 or 25A	Y	
63.565(d)(9)	Three repeats	Y	
63.565(f)(1)	Baseline temperature from performance testing	Y	
63.565(f)(2)	Baseline temperature from manufacturer	Y	
63.565(g)	Baseline outlet VOC concentration	Y	
63.565(j)	Baseline total stream flow	Y	
63.565(k)(1)	Baseline L/V ratio from performance test	Y	
63.565(k)(2)	Baseline L/V ratio from manufacturer	Y	
63.565(l)	Emission estimation procedures	Y	
63.565(m)(1)	Alternate test procedures	Y	
63.565(m)(2)	Administrator approval	Y	
63.566(a)	Construction and reconstruction	Y	
63.566(b)(1)	Application for approval of construction or reconstruction	Y	
63.566(b)(2)	General application requirements	Y	
63.566(c)	Approval of construction or reconstruction	Y	
63.567(a)	Recordkeeping and reporting	Y	
63.567(a)(1)(i)	Submittals sent by U.S. mail	Y	
63.567(a)(1)(ii)	Submittals sent by other methods	Y	
63.567(b)	Notification requirements	Y	
63.567(b)(1)	Applicability	Y	
63.567(b)(2)	Initial notification for sources with startup before the effective date	Y	
63.567(b)(2)(i)	Name and address	Y	
63.567(b)(2)(ii)	Address of the sources	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.567(b)(2)(iii)	Identification of emission standard	Y	
63.567(b)(2)(iv)	Brief description of the nature, size, design and method	Y	
63.567(b)(2)(v)	Statement that the source is a major source	Y	
63.567(b)(3)	Initial notification for sources with startup after the effective date	Y	
63.567(b)(4)	Initial notification requirements for constructed/reconstructed sources	Y	
63.567(b)(4)(i)	Notification in writing	Y	
63.567(b)(4)(ii)	Submit a notification of the date when construction or reconstruction was commenced	Y	
63.567(b)(4)(iii)	Submit a notification of the anticipated date of startup	Y	
63.567(b)(4)(iv)	Submit a notification of the actual date of startup	Y	
63.567(b)(5)(i)	Additional initial notification requirements	Y	
63.567(b)(5)(ii)	Alternate to reporting the information	Y	
63.567(c)	Request for extension of compliance	Y	
63.567(e)(1)	Schedule for summary reports and excess emission and monitoring system performance reports	Y	
63.567(e)(2)	Request to reduce frequency of excess emissions and continuous monitoring system performance reports	Y	
63.567(e)(2)(i)	Compliance for one full year	Y	
63.567(e)(2)(ii)	Continuous compliance with all recordkeeping and monitoring requirements	Y	
63.567(e)(3)	Notify administrator in writing for the frequency of reporting of excess emissions	Y	
63.567(e)(4)	Content and submittal dates for excess emissions and monitoring system performance reports	Y	
63.567(e)(5)	Summary report	Y	
63.567(e)(6)	Summary reports	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
63.567(f)	Vapor collection system of the terminal	Y	
63.567(g)	Vent system	Y	
63.567(g)(1)	Record of flow bypassing	Y	
63.567(g)(2)	Record of car-seal maintenance	Y	
63.567(h)	Vapor-tightness documentation	Y	
63.567(l)	Vapor-tightness test documentation for marine tank vessels	Y	
63.567(i)(1)	Test title	Y	
63.567(i)(2)	Marine vessel owner and address	Y	
63.567(i)(3)	Marine vessel identification number	Y	
63.567(i)(4)	Loading time	Y	
63.567(i)(5)	Testing location	Y	
63.567(i)(6)	Date of test	Y	
63.567(i)(7)	Tester name and signature	Y	
63.567(i)(8)	Test results	Y	
63.567(i)(9)	Documentation	Y	
63.567(i)(10)	Documentation on leak repaired	Y	
63.567(j)	Emission estimation reporting and recordkeeping procedures	Y	
63.567(j)(1)	Record of all measurements, calculations	Y	
63.567(j)(2)	Records of emission estimation	Y	
63.567(j)(3)	Submit annual report of the sources' HAP control efficiency	Y	
63.567(j)(4)	Record of throughput for 5 years	Y	
63.567(k)	Leak detection and repair of vapor collection systems and control device	Y	
63.567(k)(1)	Date of inspection	Y	
63.567(k)(2)	Findings (location, nature and severity of each leak)	Y	
63.567(k)(3)	Leak determination method	Y	
63.567(k)(4)	Corrective action	Y	
63.567(k)(5)	Inspector name and signature	Y	
<b>BAAQMD Condition # 1253</b>	<b>Permit Conditions</b>		
Part IA	<del>POC, CO, NOx, SO2, PM emission limitations [Basis: Cumulative Increase] Deleted, obsolete</del>	<del>Y/N</del>	
Part IB	POC, CO, NOx, SO2, PM emission limitations [Basis: Cumulative Increase]	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
Part IIA	No tanker calling while engaging in maintenance, repair, inspection [Basis: Cumulative Increase][Basis: Recordkeeping]	Y	
Part IIB	Vapor and liquid leaks inspections for valves, pumps compressors [Basis: Regulation- 8, Rule- 18]	Y	
Part IIC	Leak check procedures and methods [Basis: NSPS]	Y	
Part IID	Source S-21 shall be abated by A-1, thermal oxidizer. [Basis: Cumulative Increase]	Y	
Part IIIA, Section 3	Reid Vapor Pressure [Basis: Cumulative Increase][Basis: Recordkeeping]	Y	
Part IIIB	Report number of vessels loaded <del>on a</del> on a quarterly basis [Basis: Cumulative Increase][Basis: Recordkeeping]	Y	
Part IIIC	Valve, pump, compressor inspection and maintenance records [Basis: RecordkeepingNSPS]	Y	
Part IIID	All records <del>required shall</del> required shall be kept for at least 5 years [Basis: RecordkeepingRegulation 2, Rule 6, Section 501]	Y	
Part IIID, Schedule A	POC emission limitation [Basis: Cumulative Increase]	Y	
Part IIID, Schedule B	NOx emission limitation [Basis: Cumulative Increase]	Y	
Part IIID, Schedule C	SO2 emission limitation [Basis: Cumulative Increase]	Y	
Part IIID, Schedule D	Fugitive emission calculations [Basis: Cumulative Increase]	Y	
Part IIID, Schedule D	Vapor control equipment/vapor recovery system emission calculation [Basis: Cumulative Increase]	Y	
Part IIID, Schedule D, Section A	Cargo loading emission calculation for uncontrolled loading [Basis: Cumulative Increase]	Y	
Part IIID, Schedule D, Section B	Cargo loading emission calculation for controlled loading [Basis: Cumulative Increase]	Y	
Part IIID, Schedule E	Sulfur- emissions [Basis: Regulation- 9, Rule- 1, Section - 303]	Y	
Part IV, Section 1	Deleted, initial startup source test requirement [Basis: Cumulative Increase]	N	

## IV. Source-specific Applicable Requirements

**Table IV – F**  
**Source-specific Applicable Requirements**  
**S-21–MARINE VESSEL LOADING WHARF**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
Part IV, Section 2	POC controlled shall be at least 95% by weight or less than or equal to 2 pounds per 1000 barrels loaded [Basis: Cumulative Increase]	Y	
Part IV, Section 3a	Install instrument to measure static pressure in marine tank vessel [Basis: Cumulative Increase]	Y	
Part IV, Section 3b	Install instrument to measure oxidizer exhaust temperature [Basis: Cumulative Increase]	Y	
Part IV, Section 3c	Install instrument to measure hydrocarbon concentration and flow rate to determine mass emission [Basis: Cumulative Increase]	Y	
Part IV, Section 4	Calculate emission caps from the emissions recorded by the continuous hydrocarbon monitor or use calculation method in Part IIID, Schedule D [Basis: Cumulative Increase]	Y	
Part IV, Section 5	Deleted, startup detail plan for monitoring equipment [Basis: Cumulative Increase]	N	
Part IV, Section 6	Marine loading shall be abated at all times by the marine vapor recovery systems [Basis: Cumulative Increase]	Y	
Part IV, Section 7	Temperature limitation [Basis: Cumulative Increase]	Y	
Part IV, Section 8	Report leak test on a quarterly basis [Basis: <del>Regulation -8, Rule -44</del> ]	Y	
Part IV, Section 9	Loading pressure shall not exceed 80% of the lowest relief valve set pressure [Basis: Cumulative Increase]	Y	
Part IV, Section 10	All maintenance record shall kept for 5 years [Basis: <del>Recordkeeping Regulation 2, Rule 1, Section 403</del> ]	Y	
Part V	Removed, Shoreside vapor recovery units, A/C expired	N	
Part VI	Removed, A/C expired	N	

#### IV. Source-specific Applicable Requirements

**Table IV – G**  
**Source-specific Applicable Requirements**  
**S-23, S-24–OILY WATER SEPARATORS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 8, Rule 8</b>	<b>Organic Compounds-Wastewater (Oil/water) Separators (6/15/94)</b>		
8-8-114	Exemption, bypassed oil-water separator or air flotation influent	Y	
8-8-301.1	Wastewater separators greater than 760 liters day and smaller than 18.9 liters per second equipped with solid, gasketed, fixed cover	Y	
8-8-303	Gauging and sampling devices	Y	
8-8-305	Oil-water separator and/or air flotation unit slop oil vessels	Y	
8-8-501	API separator or air flotation bypassed wastewater records	Y	
8-8-503	Inspection and repair records	Y	
8-8-504	Portable hydrocarbon detector	Y	
8-8-603	Inspection procedures	Y	
<b>BAAQMD Condition # 1253</b>	<b>Permit Conditions</b>		
<u>Part IB</u>	<u>POC, CO, NOx, SO2, PM emission limitations [Basis: Cumulative Increase]</u>	<u>Y</u>	
Part IIIA, Section 2	Report total volume of liquids processed on a quarterly basis [Basis: Cumulative Increase]	Y	

**Table IV – H**  
**Source-specific Applicable Requirements**  
**S-27, ~~AND~~S-28 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>BAAQMD Regulation 8, Rule 5</b>	<b>Organic Compounds-General Provisions (<del>4211/4527/9902</del>)</b>		
8-5-101	Description	Y	
8-5-111	Limited Exemption, Tank Removal From and Return to Service	N	

#### IV. Source-specific Applicable Requirements

**Table IV – H**  
**Source-specific Applicable Requirements**  
**S-27, ~~AND~~S-28 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
8-5-112	Limited Exemption, Tanks in Operation	N	
8-5-117	Exemption, Low Vapor Pressure	<del>Y</del> N	
<del>8-5-304</del> 301	<del>Storage tanks larger than 75 cubic meter</del> Storage Tanks Control Requirements	Y	
<del>8-5-303</del>	<del>Requirements for Pressure Vacuum Valves</del>	<del>Y</del>	
<del>8-5-306</del>	<del>Requirements for Approved Emission Control System</del>	<del>Y</del>	
<del>8-5-311</del>	<del>Vapor loss control device requirements</del>	<del>Y</del>	
<del>8-5-311.3</del>	<del>Emission control system with an efficiency of at least 95% by weight</del>	<del>Y</del>	
8-5-328	Tank cleaning requirements	Y	
<del>8-5-328.1.2</del>	<del>Concentration of &lt;10,000 ppm as methane after cleaning</del>	<del>N</del>	
<del>8-5-328.2</del>	<del>An Emission Control System with an efficiency of at least 90% by weight</del>	<del>Y</del>	
<del>8-5-329</del>	<del>Ozone excess day prohibition</del>	<del>Y</del>	
<del>8-5-403</del>	<del>Inspection Requirements for Pressure Vacuum Valves</del>	<del>N</del>	
8-5-404	Certification	<del>Y</del> N	
<del>8-5-404.3</del>	<del>Tank degassing equipment</del>	<del>Y</del>	
8-5-501	Keep records	<del>Y</del> N	
8-5-502	Tank cleaning annual source test requirement	Y	
8-5-503	Portable hydrocarbon detector	Y	
<b>SIP Regulation 8, Rule 5</b>	<b>Storage of Organic Liquids (<del>412/2015/9399</del>)</b>		
8-5-111	Limited Exemption, Tank Removal From and Return to Service	Y	
8-5-112	Limited Exemption, Tanks in Operation	Y	
<del>8-5-117</del>	<del>Exemption, Low Vapor Pressure</del>	<del>Y</del>	
<del>8-5-304</del>	<del>Storage Tanks Larger than 75 m<sup>3</sup></del>	<del>Y</del>	
<del>8-5-311</del>	<del>Vapor loss control device requirements</del>	<del>Y</del>	
<del>8-5-311.3</del>	<del>Emission control system with an efficiency of at least 95% by weight</del>	<del>Y</del>	
<del>8-5-329</del>	<del>Ozone excess day prohibition</del>	<del>Y</del>	
<del>8-5-330</del>	<del>Viewport Installation</del>	<del>Y</del>	
<del>8-5-404</del>	<del>Certification</del>	<del>N</del>	
<del>8-5-404.3</del>	<del>Tank degassing equipment</del>	<del>Y</del>	
<del>8-5-501</del>	<del>Keep records</del>	<del>Y</del>	
<del>8-5-503</del>	<del>Portable hydrocarbon detector</del>	<del>Y</del>	

#### IV. Source-specific Applicable Requirements

**Table IV – H**  
**Source-specific Applicable Requirements**  
**S-27, ~~AND~~S-28 - FIXED ROOF TANKS**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
<b>40 CFR 60</b>	<b>Standards of Performance for New Stationary Sources (12/23/71)</b>	Y	
Subpart A	General Provisions	Y	
60.4(b)	Reports to EPA and District	Y	
60.7(a)	Written notification	Y	
60.7(b)	Records	Y	
60.8	Performance Tests	Y	
60.9	Availability of Information	Y	
60.11(a)	Compliance with standards and maintenance requirements	Y	
60.11(d)	Minimizing emissions	Y	
60.12	Circumvention	Y	
60.13	Reconstruction	Y	
60.19	General notification and reporting requirements	Y	
<b>NSPS Part 60 Subpart Ka</b>	<b>Standards of Performance for Storage Vessels For Petroleum Liquid for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984</b>	Y	
60.110(a)(a)	Applicability and designation of affected facility	Y	
60.112(a)(a)(3)	Vapor recovery system which collects at least 95% by weight	Y	
60.113(a)(a)(2)	Testing and Procedures for vapor recovery system	Y	
60.115(a)(a)	Record period of storage and maximum true vapor pressure	Y	
60.115(a)(b)	True vapor pressure	Y	
60.115(a)(c)	Estimation of true vapor pressure	Y	
<b>40 CFR 63</b>	<b>National Emission Standards for Hazardous Air Pollutants for Source Categories</b>	Y	
Subpart A	General Provisions	Y	
63.4	Prohibited activities and circumvention	Y	
63.5	Construction and reconstruction	Y	
63.6	Compliance with standards and maintenance requirements	Y	
63.7	Performance testing requirements	Y	
63.8	Monitoring requirements	Y	
63.9	Notification requirements	Y	
63.10	Recordkeeping and reporting requirements	Y	
63.12	State authority and delegations	Y	
63.15	Availability of Information and confidentiality	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – H**  
**Source-specific Applicable Requirements**  
**S-27, ~~AND~~S-28 - FIXED ROOF TANKS**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
<b>NESHAPS Part 63 Subpart R</b>	<b>National Emission Standards for Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations)</b>	Y	
63.420(a)(1)	Affected terminal	Y	
63.420(b)(1)	Affected pipeline breakout station	Y	
63.420(f)	Demonstrate compliance	Y	
63.420(g)	Most stringent control requirements	Y	
63.420(h)	Subject to the provisions of 40 CFR part 63, subpart A—General Provisions	Y	
63.420(j)	<i>Rules Stayed for Reconsideration</i>	Y	
63.423	Standards: Storage vessels		
63.423(a)	Requirements	Y	
63.423(c)	December 15, 1997 deadline	Y	
63.425	Test methods and procedures	Y	
63.425(a)	Performance test on the vapor processing system	Y	
63.425(b)	Operating parameter		
63.425(b)(1)	Determine an operating parameter value	Y	
63.425(b)(2)	Determine an operating monitoring parameter value	Y	
63.425(b)(3)	Demonstrate continuous compliance	Y	
63.425(c)	Document the reasons for any change in the operating parameter	Y	
63.425(d)	Compliance with § 60.113b	Y	
63.427	Continuous monitoring	Y	
63.427(a)(3)	Continuous parameter monitoring system (CPMS), Temperature	Y	
63.427(a)(5)	Alternative parameter demonstrates continuous compliance	Y	
63.427(b)	Operate the vapor processing system	Y	
63.427(c)	Monitoring requirements in § 60.116b; 5 yr recordkeeping	Y	
63.428	Reporting and recordkeeping	Y	
63.428(a)	The initial notifications	Y	
63.428(c)(2)	Record and report simultaneously with the notification of compliance	Y	
63.428(c)(2)(i)	Determining the operating parameter value	Y	
63.428(d)	Keep records and furnish reports	Y	
63.428(e)	Work practice program recordkeeping	Y	
63.428(h)	Submit an excess emissions report to the administrator	Y	
63.428(h)(1)	Each exceedance or failure reports	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – H**  
**Source-specific Applicable Requirements**  
**S-27, ~~AND~~S-28 - FIXED ROOF TANKS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
63.428(h)(4)	Equipment leak	Y	
63.428(h)(4)(i)	The date on which the leak was detected	Y	
63.428(h)(4)(ii)	The date of each attempt to repair the leak	Y	
63.428(h)(4)(iii)	The reasons for the delay of repair; and	Y	
63.428(h)(4)(iv)	The date of successful repair	Y	
<b>BAAQMD Condition # 1253</b>	<b>Permit Conditions</b>		
Part IB	Total facility organic compound emissions shall not exceed <del>65.167.146</del> tpy [Basis: Cumulative Increase]	Y	
<u>Part IID</u>	<u>Sources S-27 and S-28 shall be abated by A-1, thermal oxidizer. [Basis: Cumulative Increase]</u>	<u>Y</u>	
Part IIID, Schedule D	Organic emission shall not exceed 1.44 lb/1000 barrels for Vapor Control Equipment/Vapor Recovery System Emissions [Basis: Cumulative Increase]	Y	

**Table IV-I**  
**Source-specific Applicable Requirements**  
**S-73, Direct Fired Heater**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<u>BAAQMD Regulation 6</u>	<u>Particulate Matter and Visible Emissions (9/04/98)</u>		
<u>6-310</u>	<u>Particulate Weight Limitation</u>	<u>Y</u>	
<u>6-310.3</u>	<u>Particulate Weight Limitation – Heat Transfer</u>	<u>Y</u>	
<b>BAAQMD Regulation 9, Rule 1</b>	<b>Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)</b>		

#### IV. Source-specific Applicable Requirements

**Table IV-I**  
**Source-specific Applicable Requirements**  
**S-73, Direct Fired Heater**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
9-1-301	Limitation on Ground Level Concentration	Y	
9-1-302	General Emission Limitations, or 9-1-304	Y	
9-1-304	Fuel Burning – Liquid and Solid Fuels, or 9-1-302	Y	
<b>BAAQMD Regulation 9, Rule 7</b>	<b>Inorganic Gaseous Pollutants – Nitrogen Oxides and Carbon Monoxide from Industrial, Institutional, and Commercial Boilers, Steam Generators, and Process Heaters (9/16/92)</b>		
9-7-301	Emission Limits – Gaseous Fuel	Y	
9-7-301.1	Performance Standard, NOx	Y	
9-7-301.2	Performance Standard, CO	Y	
9-7-305	Natural Gas Curtailments – Non-Gaseous Fuel	Y	
9-7-305.1	Performance Standard, NOx	Y	
9-7-305.2	Performance Standard, CO	Y	
9-7-306	Equipment Testing – Non-Gaseous Fuel	Y	
9-7-306.1	Performance Standard, NOx	Y	
9-7-306.2	Performance Standard, CO	Y	
9-7-306.3	Operating Standard, Equipment Testing	Y	
9-7-401	Compliance Schedule	Y	
9-7-403	Initial Demonstration of Compliance	Y	
9-7-501	Combination of Different Fuels	Y	
9-7-502	Modified Maximum Heat Input	Y	
9-7-503	Records	Y	
9-7-503.1	304.2 Records	Y	
9-7-503.2	Records, Curtailment	Y	
9-7-503.3	306.3 Records	Y	
9-7-503.4	403 Records and Record Retention	Y	
9-7-601	Determination of Nitrogen Oxides	Y	
9-7-602	Determination of Carbon Monoxide and Stack-Gas Oxygen	Y	
9-7-603	Compliance Determination	Y	
9-7-604	Tune-Up Procedures	N	
<b>BAAQMD Condition # 1253</b>	<b>Permit Conditions</b>		

#### IV. Source-specific Applicable Requirements

**Table IV-I**  
**Source-specific Applicable Requirements**  
**S-73, Direct Fired Heater**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
<u>Part IB</u>	<u>Total facility organic compound emissions shall not exceed 67.146 tpy [Basis: Cumulative Increase]</u>	<u>Y</u>	
Part IIID, Schedule D	POC = 0.28 lb/1000 gal of fuel oil burned NOx = 55 lb/1000 gal of fuel oil burned SO2 = 78.5 lb/1000 gal of fuel oil burned [Basis: Cumulative Increase]	Y	
<b>BAAQMD Condition # 13720</b>	<b>Permit Conditions</b>		
Part 1	Natural gas usage limitation [Basis: Cumulative Increase]	Y	
Part 2	NOx limitation [Basis: BACT]	Y	
Part 3	CO limitation [Basis: BACT]	Y	
Part 4	NOx limitation when using diesel [Basis: BACT]	Y	
Part 5	Annual source test [Basis: <u>Regulation- 9, Rule- 7</u> ]	N	
Part 6	Non-resettable natural gas flow meter [Basis: Cumulative Increase]	Y	
Part 7	Certification of <u>sulfur content in fuel oil</u> <del>from sulfur</del> [Basis: <u>Regulation 2, Rule 6, Section -6</u> 409.2]	Y	

S-□ 4 ————— This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

**Table IV – J**  
**Source-specific Applicable Requirements**  
**S-74 AND S-75 EMERGENCY DIESEL GENERATORS**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
<b>BAAQMD Regulation 6</b>	<b>Particulate Matter and Visible Emissions (12/19/90)</b>		
<u>6-303.1</u>	<u>Ringelmann No. 4-2 Limitation</u>	<u>Y</u>	
<u>6-303.1</u>	<u>Ringelmann No. 2 Limitation for standby sources of motive power</u>	<u>Y</u>	
<u>6-310.1</u>	<u>Particulate Weight Limitation</u>	<u>Y</u>	

#### IV. Source-specific Applicable Requirements

**Table IV – J**  
**Source-specific Applicable Requirements**  
**S-74 AND S-75 EMERGENCY DIESEL GENERATORS**

<u>Applicable Requirement</u>	<u>Regulation Title or Description of Requirement</u>	<u>Federally Enforceable (Y/N)</u>	<u>Future Effective Date</u>
6-401	Appearance of Emissions	<u>Y</u>	
<b><u>BAAQMD Regulation 9, Rule 1</u></b>	<b><u>Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)</u></b>		
9-1-301	Limitations on Ground Level Concentrations	<u>Y</u>	
9-1-304	Liquid and Solid Fuels	<u>Y</u>	
<b><u>BAAQMD Regulation 9, Rule 8</u></b>	<b><u>Inorganic Gaseous Pollutants – Nitrogen Oxides and Carbon Monoxide from Stationary Internal Combustion Engines (8/1/2001)</u></b>		
9-8-330	Emergency Standby Engines, Hours of Operation		
9-8-530	Emergency Standby Engines, Monitoring and Recordkeeping		
<b><u>BAAQMD Condition # 1253</u></b>	<b><u>Permit Conditions</u></b>		
<b><u>Part 1B</u></b>	<b><u>Total facility organic compound emissions shall not exceed 67.146 tpy [Basis: Cumulative Increase]</u></b>	<u>Y</u>	
<b><u>BAAQMD Condition # 19308</u></b>			
<b><u>Part 1</u></b>	<b><u>Operation limited to &lt; 100 hours per year. Fuel &amp; Sulfur certification [Regulation 9-8-330]</u></b>	<u>Y</u>	
<b><u>Part 4</u></b>	<b><u>Flow meter requirement [Regulation 9-8-530]</u></b>	<u>Y</u>	
<b><u>Part 5</u></b>	<b><u>Recordkeeping [Regulation 9-8-530]</u></b>	<u>Y</u>	

#### IV. Source-specific Applicable Requirements

**Table IV - K**  
**Source-specific Applicable Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
<b><u>BAAQMD Regulation 8, Rule 5</u></b>	<b><u>Storage of Organic Liquids (11/27/02)</u></b>		
<u>8-5-101</u>	<u>Description</u>	<u>Y</u>	
<u>8-5-111</u>	<u>Limited Exemption, Tank Removal From and Return to Service</u>	<u>N</u>	
<u>8-5-112</u>	<u>Limited Exemption, Tanks in Operation</u>	<u>N</u>	
<u>8-5-117</u>	<u>Exemption, Low Vapor Pressure</u>	<u>N</u>	
<u>8-5-301</u>	<u>Storage Tanks Control Requirements</u>	<u>Y</u>	
<u>8-5-303</u>	<u>Requirements for Pressure Vacuum Valves</u>	<u>Y</u>	
<u>8-5-305</u>	<u>Requirements for Internal Floating Roofs</u>	<u>Y</u>	
<u>8-5-305.1</u>	<u>Tank Seals installed on or before February 1, 1993</u>	<u>Y</u>	
<u>8-5-305.2</u>	<u>Tank with Seals Installed after February 1, 1993</u>	<u>Y</u>	
<u>8-5-305.3</u>	<u>3 View Ports Requirements</u>	<u>Y</u>	
<u>8-5-305.4</u>	<u>Section 8-5-320 requirements</u>	<u>Y</u>	
<u>8-5-305.5</u>	<u>The Floating Roof Must Rest on Surface of Liquid</u>	<u>N</u>	
<u>8-5-320</u>	<u>Tank fitting requirements</u>		
<u>8-5-320.2</u>	<u>Opening shall provide projection below the liquid surface</u>	<u>Y</u>	
<u>8-5-320.3.1</u>	<u>All openings shall be equipped with a gasketed cover</u>	<u>Y</u>	
<u>8-5-320.3.2</u>	<u>Inaccessible openings</u>	<u>Y</u>	
<u>8-5-320.4</u>	<u>Solid sampling or gauging wells</u>	<u>Y</u>	
<u>8-5-320.5.1</u>	<u>Well shall provide projection below the liquid surface</u>	<u>Y</u>	
<u>8-5-320.5.2</u>	<u>The well requirements</u>	<u>Y</u>	
<u>8-5-320.5.3</u>	<u>The gap between the well and the roof</u>	<u>Y</u>	
<u>8-5-320.6</u>	<u>Emergency roof drain</u>	<u>Y</u>	
<u>8-5-321</u>	<u>Primary seal requirements</u>		
<u>8-5-321.1</u>	<u>No holes, tears or other openings</u>	<u>Y</u>	
<u>8-5-321.2</u>	<u>Metallic or liquid mounted type shoes</u>	<u>Y</u>	
<u>8-5-321.3</u>	<u>Metallic shoes type seals</u>	<u>Y</u>	
<u>8-5-321.4</u>	<u>Resilient-toroid seal equipped tanks</u>	<u>Y</u>	
<u>8-5-322</u>	<u>Secondary seal requirements</u>		
<u>8-5-322.1</u>	<u>No holes, tears, or other openings in the secondary seal</u>	<u>Y</u>	
<u>8-5-322.2</u>	<u>Insertion of probes</u>	<u>Y</u>	

#### IV. Source-specific Applicable Requirements

**Table IV - K**  
**Source-specific Applicable Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
<a href="#">8-5-322.3</a>	<a href="#">No gap between tank shell and the secondary seal shall exceed 1.3 cm (1/2 in)</a>	<a href="#">Y</a>	
<a href="#">8-5-322.4</a>	<a href="#">Riveted tanks</a>	<a href="#">Y</a>	
<a href="#">8-5-322.5</a>	<a href="#">Gaps for welded tanks with seal installed after September 4, 1985</a>	<a href="#">Y</a>	
<a href="#">8-5-322.6</a>	<a href="#">Secondary seal</a>	<a href="#">Y</a>	
<a href="#">8-5-328</a>	<a href="#">Tank Degassing Requirements</a>	<a href="#">Y</a>	
<a href="#">8-5-328.1.2</a>	<a href="#">Concentration of &lt;10,000 ppm as methane after cleaning</a>	<a href="#">N</a>	
<a href="#">8-5-402</a>	<a href="#">Internal Floating Roof Inspection</a>	<a href="#">N</a>	
<a href="#">8-5-403</a>	<a href="#">Pressure Vacuum Inspection</a>	<a href="#">N</a>	
<a href="#">8-5-404</a>	<a href="#">Certification</a>	<a href="#">N</a>	
<a href="#">8-5-405</a>	<a href="#">Information required</a>	<a href="#">Y</a>	
<a href="#">8-5-501</a>	<a href="#">Records</a>	<a href="#">N</a>	
<a href="#">8-5-502</a>	<a href="#">Tank Degassing Annual Source Test Requirement</a>	<a href="#">Y</a>	
<a href="#">8-5-503</a>	<a href="#">Portable hydrocarbon detector</a>	<a href="#">Y</a>	
<b><u>SIP Regulation 8, Rule 5</u></b>	<b><u>Storage of Organic Liquids (12/15/99)</u></b>		
<a href="#">8-5-111</a>	<a href="#">Limited Exemption, Tank Removal From and Return to Service</a>	<a href="#">Y</a>	
<a href="#">8-5-112</a>	<a href="#">Limited Exemption, Tanks in Operation</a>	<a href="#">Y</a>	
<a href="#">8-5-117</a>	<a href="#">Exemption, Low Vapor Pressure</a>	<a href="#">Y</a>	
<a href="#">8-5-311</a>	<a href="#">Vapor Loss Control Device Requirements</a>	<a href="#">Y</a>	
<a href="#">8-5-329</a>	<a href="#">Ozone Excess Day Prohibition</a>	<a href="#">Y</a>	
<a href="#">8-5-330</a>	<a href="#">Viewport Installation</a>	<a href="#">Y</a>	
<a href="#">8-5-401</a>	<a href="#">Primary Seal Inspection</a>	<a href="#">Y</a>	
<a href="#">8-5-402</a>	<a href="#">Secondary Seal and Fitting Inspection</a>	<a href="#">Y</a>	
<a href="#">8-5-403</a>	<a href="#">Internal Floating Roof Tank Visual Inspection</a>	<a href="#">Y</a>	
<a href="#">8-5-404</a>	<a href="#">Certification</a>	<a href="#">Y</a>	
<a href="#">8-5-501</a>	<a href="#">Records</a>	<a href="#">Y</a>	
<b><u>40 CFR 60</u></b>	<b><u>Standards of Performance for New Stationary Sources (12/23/71)</u></b>	<a href="#">Y</a>	
<a href="#">Subpart A</a>	<a href="#">General Provisions</a>	<a href="#">Y</a>	
<a href="#">60.4(b)</a>	<a href="#">Reports to EPA and District</a>	<a href="#">Y</a>	
<a href="#">60.7(a)</a>	<a href="#">Written notification</a>	<a href="#">Y</a>	
<a href="#">60.7(b)</a>	<a href="#">Records</a>	<a href="#">Y</a>	
<a href="#">60.8</a>	<a href="#">Performance Tests</a>	<a href="#">Y</a>	

#### IV. Source-specific Applicable Requirements

**Table IV - K**  
**Source-specific Applicable Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
60.9	<u>Availability of Information</u>	<u>Y</u>	
60.11(a)	<u>Compliance with standards and maintenance requirements</u>	<u>Y</u>	
60.11(d)	<u>Minimizing emissions</u>	<u>Y</u>	
60.12	<u>Circumvention</u>	<u>Y</u>	
60.13	<u>Reconstruction</u>	<u>Y</u>	
60.19	<u>General notification and reporting requirements</u>	<u>Y</u>	
<b><u>NSPS</u></b> <b><u>40 CFR 60</u></b> <b><u>Subpart Kb</u></b>	<b><u>Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984</u></b>	<b><u>Y</u></b>	
60.110(b)(a)	<u>Tanks greater than or equal to 40 cubic meters</u>	<u>Y</u>	
60.112(b)(a) (1)	<u>Internal Floating Roof</u>	<u>Y</u>	
60.112(b)(a) (1)(i)	<u>The internal floating roof requirements</u>	<u>Y</u>	
60.112(b)(a) (1)(ii)	<u>Closure devices</u>	<u>Y</u>	
60.112(b)(a) (1)(iii)	<u>Opening</u>	<u>Y</u>	
60.112(b)(a) (1)(iv)	<u>Cover or lid</u>	<u>Y</u>	
60.112(b)(a) (1)(v)	<u>Automatic bleeder vents</u>	<u>Y</u>	
60.112(b)(a) (1)(vi)	<u>Rim space vents</u>	<u>Y</u>	
60.112(b)(a) (1)(vii)	<u>The sample well</u>	<u>Y</u>	
60.112(b)(a) (1)(viii)	<u>Flexible fabric sleeve seal or a gasketed sliding cover</u>	<u>Y</u>	
60.112(b)(a) (1)(ix)	<u>Gasketed sliding cover</u>	<u>Y</u>	
60.113(b)	<u>Testing and Procedures</u>	<u>Y</u>	
60.113(b)(a) (1)	<u>Visual inspect</u>	<u>Y</u>	

#### IV. Source-specific Applicable Requirements

**Table IV - K**  
**Source-specific Applicable Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
<u>60.113(b)(a)(2)</u>	<u>For vessels equipped with a liquid-mounted or mechanical shoe primary seal</u>	<u>Y</u>	
<u>60.113(b)(a)(4)</u>	<u>Visually inspect when emptied and degassed</u>	<u>Y</u>	
<u>60.113(b)(a)(5)</u>	<u>Notify the Administrator</u>	<u>Y</u>	
<u>60.115(b)</u>	<u>Reporting and recordkeeping requirements</u>	<u>Y</u>	
<u>60.115(b)(a)</u>	<u>Installing equipment</u>	<u>Y</u>	
<u>60.116(b)</u>	<u>Monitoring of Operation</u>	<u>Y</u>	
<u>60.116(b)(a)</u>	<u>Records required</u>	<u>Y</u>	
<u>60.116(b)(b)</u>	<u>Accessible records</u>	<u>Y</u>	
<u>60.116(b)(c)</u>	<u>Maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure</u>	<u>Y</u>	
<u>60.116(b)(d)</u>	<u>Notify the administrator within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure</u>	<u>Y</u>	
<u>60.116(b)(e)</u>	<u>Available data on the storage temperature may be used to determine the maximum true vapor pressure</u>	<u>Y</u>	
<u>60.116(b)(e)(1)</u>	<u>The maximum local monthly average ambient temperature</u>	<u>Y</u>	
<u>60.116(b)(e)(2)</u>	<u>For crude oil or refined petroleum products the vapor pressure may be obtained by the following</u>	<u>Y</u>	
<u>60.116(b)(e)(3)</u>	<u>For other liquids, the vapor pressure</u>	<u>Y</u>	
<u>60.116(b)(f)</u>	<u>Vessel storing a waste mixture of indeterminate or variable composition</u>	<u>Y</u>	
<b><u>40 CFR 63</u></b>	<b><u>National Emission Standards for Hazardous Air Pollutants for Source Categories</u></b>	<u>Y</u>	
<u>Subpart A</u>	<u>General Provisions</u>	<u>Y</u>	
<u>63.4</u>	<u>Prohibited activities and circumvention</u>	<u>Y</u>	
<u>63.5</u>	<u>Construction and reconstruction</u>	<u>Y</u>	
<u>63.6</u>	<u>Compliance with standards and maintenance requirements</u>	<u>Y</u>	
<u>63.7</u>	<u>Performance testing requirements</u>	<u>Y</u>	
<u>63.8</u>	<u>Monitoring requirements</u>	<u>Y</u>	
<u>63.9</u>	<u>Notification requirements</u>	<u>Y</u>	
<u>63.10</u>	<u>Recordkeeping and reporting</u>	<u>Y</u>	
<u>63.12</u>	<u>State authority and delegations</u>	<u>Y</u>	

#### IV. Source-specific Applicable Requirements

**Table IV - K**  
**Source-specific Applicable Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
<b><u>NSPS</u></b> <b><u>40 CFR 63</u></b> <b><u>Subpart R</u></b>	<b><u>National Emission Standards for Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations)</u></b>	<b><u>Y</u></b>	
<b><u>63.420(a)</u></b>	<b><u>Applicability</u></b>	<b><u>Y</u></b>	
<b><u>63.420(f)</u></b>	<b><u>Demonstrate compliance</u></b>	<b><u>Y</u></b>	
<b><u>63.420(g)</u></b>	<b><u>Subject to applicable provisions of 40 CFR part 60, subpart Kb</u></b>	<b><u>Y</u></b>	
<b><u>63.420(h)</u></b>	<b><u>Subject to the provisions of 40 CFR part 63, subpart A—General Provisions</u></b>	<b><u>Y</u></b>	
<b><u>63.423</u></b>	<b><u>Standards: Storage vessels</u></b>		
<b><u>63.423(a)</u></b>	<b><u>Requirements in § 60.112b(a) (1) through (4)</u></b>	<b><u>Y</u></b>	
<b><u>63.423(c)</u></b>	<b><u>December 15, 1997 compliance deadline</u></b>	<b><u>Y</u></b>	
<b><u>63.424</u></b>	<b><u>Standards: Equipment Leaks</u></b>	<b><u>Y</u></b>	
<b><u>63.425</u></b>	<b><u>Test methods and procedures</u></b>		
<b><u>63.425(d)</u></b>	<b><u>Vessel subject to the provisions of § 63.423 shall comply with § 60.113b of this chapter</u></b>	<b><u>Y</u></b>	
<b><u>63.428</u></b>	<b><u>Reporting and recordkeeping</u></b>		
<b><u>63.428(a)</u></b>	<b><u>The initial notifications</u></b>	<b><u>Y</u></b>	
<b><u>63.428(d)</u></b>	<b><u>Keep records and furnish reports</u></b>	<b><u>Y</u></b>	
<b><u>63.428(e)</u></b>	<b><u>Work Practice Program Recordkeeping</u></b>	<b><u>Y</u></b>	
<b><u>BAAQMD</u></b> <b><u>Condition #</u></b> <b><u>1253</u></b>	<b><u>Permit Conditions</u></b>		
<b><u>Part IB</u></b>	<b><u>Total facility organic compound emissions shall not exceed 67.146 tpy [Basis: Cumulative Increase]</u></b>	<b><u>Y</u></b>	
<b><u>BAAQMD</u></b> <b><u>Condition #</u></b> <b><u>20060</u></b>	<b><u>Permit Conditions</u></b>		
<b><u>Part 1</u></b>	<b><u>Gasoline or other hydrocarbon liquids yearly throughput limitation [Basis: Cumulative Increase]</u></b>	<b><u>Y</u></b>	
<b><u>Part 2</u></b>	<b><u>Gasoline or other hydrocarbon liquids daily throughput limitation [Basis: Cumulative Increase]</u></b>	<b><u>Y</u></b>	
<b><u>Part 3</u></b>	<b><u>Limitation on benzene concentration [Basis: TRMP]</u></b>	<b><u>Y</u></b>	
<b><u>Part 4</u></b>	<b><u>Valves and flanges inspection and maintenance [Basis: Regulation 8, Rule 18]</u></b>	<b><u>Y</u></b>	
<b><u>Part 5</u></b>	<b><u>Subject to all applicable requirement of Regulation 8-5 and NSPS [40 CFR 60, Subpart Kb. [Basis: Regulation 8, Rule 5, NSPS]</u></b>	<b><u>Y</u></b>	

#### IV. Source-specific Applicable Requirements

**Table IV - K**  
**Source-specific Applicable Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
<b><u>Part 6</u></b>	<b><u>Recordkeeping Requirements [Basis: Recordkeeping]</u></b>	<b><u>Y</u></b>	

**Table IV – L**  
**Source-specific Applicable Requirements**  
**A-1, THERMAL OXIDIZER**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
<b><u>BAAQMD Regulation 6</u></b>	<b><u>Particulate Matter and Visible Emissions (9/04/98)</u></b>		
<b><u>6-301</u></b>	<b><u>Ringelmann No. 1 Limitation</u></b>	<b><u>Y</u></b>	
<b><u>6-305</u></b>	<b><u>Visible Particles</u></b>	<b><u>Y</u></b>	
<b><u>6-310</u></b>	<b><u>Particulate Weight Limitation</u></b>	<b><u>Y</u></b>	
<b><u>6-401</u></b>	<b><u>Appearance of Emissions</u></b>	<b><u>Y</u></b>	
<b><u>BAAQMD Regulation 9, Rule 1</u></b>	<b><u>Inorganic Gaseous Pollutants – Sulfur Dioxide (3/15/95)</u></b>		
<b><u>9-1-301</u></b>	<b><u>Limitations on Ground Level Concentrations</u></b>	<b><u>Y</u></b>	
<b><u>9-1-302</u></b>	<b><u>General Emission Limitations</u></b>	<b><u>Y</u></b>	
<b><u>BAAQMD Condition # 1253</u></b>	<b><u>Permit Conditions</u></b>		
<b><u>Part IB</u></b>	<b><u>POC, CO, NOx, SO2, PM emission limitations [Basis: Cumulative Increase]</u></b>	<b><u>Y</u></b>	
<b><u>Part IIID, Schedule A</u></b>	<b><u>POC emission limitation [Basis: Cumulative Increase]</u></b>	<b><u>Y</u></b>	
<b><u>Part IIID, Schedule B</u></b>	<b><u>NOx emission limitation [Basis: Cumulative Increase]</u></b>	<b><u>Y</u></b>	
<b><u>Part IIID, Schedule C</u></b>	<b><u>SO2 emission limitation [Basis: Cumulative Increase]</u></b>	<b><u>Y</u></b>	
<b><u>Part IV, Section 2</u></b>	<b><u>POC controlled shall be at least 95% by weight or less than or equal to 2 pounds per 1000 barrels loaded [Basis: Cumulative Increase]</u></b>	<b><u>Y</u></b>	

#### IV. Source-specific Applicable Requirements

**Table IV – L**  
**Source-specific Applicable Requirements**  
**A-1, THERMAL OXIDIZER**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
Part IV, Section 3b	Install instrument to measure oxidizer exhaust temperature [Basis: Cumulative Increase]	<u>Y</u>	
Part IV, Section 7	Temperature limitation [Basis: Cumulative Increase]	<u>Y</u>	

**Table IV – LM**  
**Source-specific Applicable Requirements**  
**FACILITY**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
<b><u>BAAQMD Regulation 8, Rule 5</u></b>	<b><u>Storage of Organic Liquids (11/27/02)</u></b>		
8-5-328	Tank cleaning requirements	<u>N</u>	
8-5-328.1.2	An approved Emission Control system	<u>N</u>	
8-5-328.2	Degassing when ozone excesses are predicted	<u>N</u>	
8-5-404	Certification	<u>Y</u>	
8-5-404.3	For tank degassing equipment	<u>Y</u>	
8-5-502	Tank degassing annual source test requirement	<u>N</u>	
8-5-603	Determination of emissions	<u>Y</u>	
8-5-603.2	Source tests for tank cleaning equipment	<u>Y</u>	
<b><u>SIP Regulation 8, Rule 5</u></b>	<b><u>Storage of Organic Liquids (10/10/01)</u></b>		
8-5-328	Tank Cleaning Requirements	<u>Y</u> <sup>1</sup>	
8-5-328.2	An approved emission control system	<u>Y</u> <sup>1</sup>	
8-5-502	Tank cleaning annual source test requirement	<u>Y</u> <sup>1</sup>	
<b><u>BAAQMD Condition # 1253</u></b>	<b><u>Permit Conditions</u></b>		

#### IV. Source-specific Applicable Requirements

**Table IV – LM**  
**Source-specific Applicable Requirements**  
**FACILITY**

<b><u>Applicable Requirement</u></b>	<b><u>Regulation Title or Description of Requirement</u></b>	<b><u>Federally Enforceable (Y/N)</u></b>	<b><u>Future Effective Date</u></b>
Part IB	POC, CO, NOx, SO2, PM emission limitations [Basis: Cumulative Increase]	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – JNM  
 Source-specific Applicable Requirements  
 COMPONENTS**

<b>Applicable Requirement</b>	<b>Regulation Title or Description of Requirement</b>	<b>Federally Enforceable (Y/N)</b>	<b>Future Effective Date</b>
<b>BAAQMD Regulation 8, Rule 18</b>	<b>Organic Compounds-Equipment Leaks (1/7/98)</b>		
8-18-301	General	Y	
8-18-302	Valves	Y	
8-18-303	Pumps and compressors	Y	
8-18-304	Connectors	Y	
8-18-305	Pressure relief devices	Y	
8-18-306	Non-repairable equipment	Y	
8-18-307	Liquid Leaks	Y	
8-18-308	Alternate compliance	Y	
8-18-401	Inspection	Y	
8-18-402	Identification	Y	
8-18-403	Visual inspection schedule	Y	
8-18-404	Alternate inspection schedule	Y	
8-18-405	Alternate inspection reduction plan	Y	
8-18-501	Portable Hydrocarbon Detector	Y	
8-18-502	Records	Y	
<b>SIP BAAQMD Regulation 8, Rule 18</b>	<b>Organic Compounds-Valves and Connectors at Petroleum Refinery Complexes, Chemical Plants, Bulk Plants and Bulk Terminals (3/4/92)</b>		
8-18-301	Valves and Flanges	Y	
8-18-302	Valves	Y	
8-18-303	Connectors	Y	
8-18-304	Non-repairable valves	Y	
8-18-305	New or Replaced Valves	Y	
8-18-306	Repeat Leakers	Y	
8-18-307	Liquid Leak	Y	
8-18-401	Inspection	Y	
8-18-402	Identification	Y	
8-18-501	Portable Hydrocarbon Detector	Y	
8-18-502	Records	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – JNM**  
**Source-specific Applicable Requirements**  
**COMPONENTS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<b>SIP</b> <b>BAAQMD</b> <b>Regulation 8,</b> <b>Rule 25</b>	<b>Organic Compounds-Pump and Compressor Seals at Petroleum Refinery Complexes, Chemical Plants, Bulk Plants and Bulk Terminals (6/1/94)</b>		
8-25-301	Pump and compressor operating requirements	Y	
8-25-302	Pumps	Y	
8-25-303	Compressors	Y	
8-24-304	Non-repairable pumps and compressors	Y	
8-25-305	New or Replaced pumps and compressors	Y	
8-25-306	Repeat Leakers	Y	
8-25-307	Liquid Leak	Y	
8-25-401	Measurement schedule	Y	
8-25-402	Inspection plan	Y	
8-25-403	Visual inspection schedule	Y	
8-25-405	Pump and compressor identification	Y	
8-25-406	Leaking pumps and compressors	Y	
8-25-501	Portable hydrocarbon detector	Y	
8-25-503	Records	Y	
8-25-504	Burden of proof	Y	
<b>NSPS Part 63</b> <b>Subpart R</b>	<b>National Emission Standards for Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations) (12/14/94)</b>	Y	
63.424(a)	Perform monthly leak inspection of each equipment during the loading of a gasoline cargo tank	Y	
63.424(b)	Log book	Y	
63.424(c)	Record leak detection	Y	
63.424(d)	Delay repair	Y	
63.424(e)	December 15, 1997 initial compliance	Y	
63.424(f)	Alternative to compliance	Y	
63.424(g)	Measures taken	Y	
63.424(g)(1)	Minimize gasoline spills	Y	
63.424(g)(2)	Cleanup spills expeditiously	Y	
63.424(g)(3)	Cover all gasoline containers	Y	
63.424(g)(1)	Minimize gasoline sent to waste collection systems	Y	

#### IV. Source-specific Applicable Requirements

**Table IV – JNM  
 Source-specific Applicable Requirements  
 COMPONENTS**

Applicable Requirement	Regulation Title or Description of Requirement	Federally Enforceable (Y/N)	Future Effective Date
<u>BAAQMD Condition # 1253</u>	<u>Permit Conditions</u>		
<u>Part 1B</u>	<u>Total facility organic compound emissions shall not exceed 67.146 tpy [Basis: Cumulative Increase]</u>	<u>Y</u>	

## **V. SCHEDULE OF COMPLIANCE**

The permit holder shall comply with all applicable requirements cited in this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit on a timely basis.

## VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

### Condition # 1253

For S-1 THROUGH S-16, S-18, S-19, STORAGE TANKS; S-20, TANK TRUCK LOADING RACK; S-21, MARINE VESSEL WHARF; S-23, S-24, OILY WATER SEPARATORS; S-27, S-28, FIXED ROOF TANKS; S-73, DIRECT FIRED HEATER; S-75, S-77 AND S-78, INTERNAL FLOATING ROOF TANKS; AND A-1 THERMAL OXIDIZER; (EXCLUDE S-74, S-75 DIESEL IC EMERGENCY GENERATORS):

#### I. EMISSION LIMITATIONS

- A) Deleted, obsolete.
- B) Total facility emissions from all sources, including organic loading emissions, shall not exceed the following levels during any calendar year. (Revised July 1, 1991)  
[Basis: Cumulative Increase]

Organic Compounds:	<del>65.167.146</del> tons/year (Revised 4/21/2003)
Carbon Monoxide:	52.2 tons/year
Oxides of Nitrogen:	129.5 tons/year
Sulfur Dioxide:	83.5 tons/year
Particulate Matter:	25.8 tons/year

#### II. GENERAL TERMINAL AND WHARF CONDITIONS

- A) No tanker calling exclusively at the Terminal shall, while in California Coastal waters, engage in any maintenance, repair, inspection, washing, purging and gas freeing, or lightering of cargo tanks or any other operation (excepting loading and offloading, ballasting, and bunkering) that result in the escape of hydrocarbon vapor to the atmosphere, except that this does not prohibit emergency repairs. These activities shall be recorded on a District approved log and be made available to the District representative upon request. Any failure by the Permit Holder to report the activities listed above will subject them to appropriate enforcement action. Any emissions resulting from these unauthorized activities will be charged to the Permit Holder emissions cap. [Basis: Cumulative Increase]
- B) Pumps, compressors, pump manifolds and pressure relief valves shall be inspected for visible vapor or liquid leaks on a daily basis. [Basis: Regulation ~~8~~, Rule ~~18~~, Section 403]
- C) The leak check procedures, testing methods, calibration procedures, definition of a leak, repair techniques, record keeping and report requirements shall be in accordance with the Federal NSPS for equipment leaks of VOC from onshore natural gas processing plants. [Basis: Cumulative Increase NSPS]
- D) The owner/operator of the following sources shall use A-1, Thermal Oxidizer, as an

## VI. Permit Conditions

abatement -device during all of the following events:

- i. When non-exempt organic compounds (as defined in District Regulation 2, Rule 2, Section 206, and Regulation 2, Rule 1, Section 123) are being stored in or transferred to storage tanks S-1 through S-12, S-18, S-19, S-27 and S-28.
- ii. When organic liquids with a true vapor pressure of 1.5 psia or greater are being loaded at truck rack S-20; and/or
- iii. When organic liquids (as defined in District Regulation 8-44-204) are loaded at marine wharf S-21. [Basis: BACT]

## III. REPORTING REQUIREMENTS

- A) The followings shall be reported to the Director of Enforcement of the District on the quarterly basis: [Basis: Cumulative Increase]
1. The total volume of gasoline throughput at the truck rack.
  2. The total volume of liquids processed through the oil/water separators during the quarter.
  3. For each marine vessel, which called at the Terminal during the quarter, the Permit Holder shall verify the following to the satisfaction of the APCO: the Reid vapor pressure of the previous cargo and previous port of call. For all vessels that the Permit Holder claims were "gas freed" prior to entering California Coastal waters, the Permit Holder shall supply documentation of this claim that is acceptable to the APCO. [Basis: Cumulative Increase]
- B) Once the onshore vapor recovery system including vessel interconnection at the wharf is in operation, the Permit Holder shall report to the Director of Enforcement of the District within 15 days after the close of each calendar quarter on the number of vessels that have been loaded at its marine terminal. These reports shall specify the percentage of said vessels ~~which that~~ were hooked up to the Permit Holder's onshore vapor recovery system during said quarter. With respect to those vessels into which organic liquids were loaded without being hooked up to said system, these reports shall summarize the reasons given by Permit Holder's customers for their inability to secure vessels built or retrofitted to accommodate hook-up to said system. [Basis: Cumulative Increase]
- C) Records shall be kept to document compliance with the valve, pump, and compressor inspection and maintenance requirements of condition II (C) above. [Basis: Cumulative Increase~~NSPS~~]
- D) All records required to be maintained by Permit Holder under this permit shall be kept for at least 5 years and made available to a District representative upon request. [Basis: Regulation -2, Rule -6, Section -501]

## VI. Permit Conditions

### SCHEDULE A

#### ORGANIC COMPOUND EMISSION CALCULATIONS

The sum of the following emission categories shall not exceed ~~65.167.146~~ tons, per calendar year of organic compounds.

Cargo Loading Emission + Tanker Transit Emissions + Tanker Hotelling Emissions + Tanker Pumping Emission + Vapor Control Equipment Emission + Ballast Emissions + Tug Combustion Emissions + Tank Standing Losses + Fugitive Emissions + Tank Withdrawal Losses.

All calculations shall be performed in accordance with the procedures specified in Schedule D. [Basis: Cumulative Increase]

### SCHEDULE B

#### OXIDES OF NITROGEN EMISSIONS CALCULATIONS

The sum of the following emission categories shall not exceed 129.5 tons per calendar year of oxides of nitrogen.

Tug Combustion Emissions + Tanker Hotelling Emissions + Tanker Transit Emissions + Tanker Pumping Emissions + Vapor Control Equipment Combustion + Direct Fire Heater Combustion (excluding emergency diesel generators S-74 and S-75).

All calculations shall be performed in accordance with the procedures specified in Schedule D. [Basis: Cumulative Increase]

### SCHEDULE C

#### SULFUR DIOXIDE EMISSION CALCULATIONS

The sum of the following emission categories shall not exceed 83.5 tons per calendar year of sulfur dioxide.

Tug Combustion Emissions + Tanker Hotelling Emissions + Tanker Transit Emissions + Tanker Pumping Emissions + Vapor Control Equipment Combustion + Direct Fire Heater Combustion (excluding emergency diesel generators S-74 and S-75).

All calculations shall be performed in accordance with the procedures specified in



## VI. Permit Conditions

### FURNACE EMISSION CALCULATIONS

Organic Compounds	0.28 lb/1,000 gallons of fuel oil burned
NO <sub>x</sub>	55.00 lb/1,000 gallons of fuel oil burned
SO <sub>2</sub>	78.50 lb/1,000 gallons of fuel oil burned

### TANK STANDING EMISSION CALCULATIONS (Tanks 13-16 only)

Calculate using equation 4 from AP-42 p 4.3-16 (9/85)

Where:

$$L(s) = K(s) \times V_n \times P^* \times D \times M(v) \times K(c)$$

L(s) = standing losses, lb/year of organics

K(s) = seal factor 1.2 for metallic shoe primary seal; 0.2 for rim mounted secondary seal.

V = average wind speed = 13 miles per hour

N = wind speed exponent = 1.5 for metallic shoe seal

P\* = vapor pressure function

Note:

P for crude oils will be determined by monthly composite samples.

P for FCC feedstock, all gas oils and fuel oils = 0 for purpose of this calculation.

PA = atmospheric pressure = 14.7 psia

D = tank diameter = 237 feet

M(v) = molecular weight of vapor, 58 for gasoline and crude oil, 190 for No. 6 and all other products

K(c) = product factor = 0.4 for crude oil; = 1.0 for all other materials

### TANK WITHDRAWAL EMISSION CALCULATIONS

Calculate using equation 5 from AP-42 d 4-3-16 (9/85):

$$L(w) = 0.943 \text{ QCW/D}$$

where:

L(w) = withdrawal losses = lb/yr of organics

Q = throughput, bbl/year

C = shell clingage factors = 0.006

W = liquid density, lb/gal

Use:

8.2 for San Joaquin Valley Crude Oil and

7.8 for all other products if unknown

D = tank diameter = 237 feet

## VI. Permit Conditions

### CARGO LOADING EMISSION CALCULATIONS

#### A) UNCONTROLLED LOADING

##### *Crude Oil Cargos*

The three following procedures are taken from API Publication 2514A Second Edition, September 1981 and are described on pp 1-3 of that document as "Correlations for Estimating Emissions from Loading and Ballasting of Crude Oil Tankers".

1. Cargos with no vapor pressure data available:

If information on the prior cargo and compartment status during ballast voyage as well as volatility of the crude of which Permit Holder loaded is unknown, the following emission factors shall be used.

All vessels: 1.0 pounds of VOC per 1,000 gallons of liquid transferred.

2. For crude oil cargos with vapor pressure greater than 1.5 psia:

- a) When the prior cargo or arrival condition of the vessel is unknown and the volatility of the crude oil, which Permit Holder loaded is known, an arrival emission factor,  $E_a$ , of .86 lb/1,000 gallon loaded will be used. Generated emission shall be calculated as:

$$E_g = 1.84 \times (0.44 \times (TVP) - 0.42) \times M \times G / T$$

where:

$E_g$  = generated emission, lb/1,000 gallon

TVP= true vapor pressure of loaded crude oil, psia

M = molecular weight of vapor, use 58 lb/lb-mole

G = vapor growth factor, use 1.02

T = loading temperature, Rankine

Total emission shall be calculated as:

$$E_t = E_a + E_g$$

where:

$E_t$  = total loading emission, lb/1,000 gallon

$E_a$  = arrival component

$E_g$  = generated component

- b) If adequate information is available about a specific previous cargo the following calculation procedures shall be used. These procedures require a characterization of the previous cargo as either "volatile" or "non-volatile" at loading conditions. "Volatile" has been defined as having a true vapor pressure at loading conditions in excess of 1.5 psia. Any crude stream ~~which~~ that has a flash point in excess of 130F or initial boiling point excess of 302F shall be deemed to be "non-volatile" at

## VI. Permit Conditions

loading conditions. The Permit Holder shall be permitted to determine that crude oils not meeting this test are "non-volatile" by any of the three procedures described below:

- i. The ship owner or charterer may inform the Permit Holder in writing of the true vapor pressure at loading conditions, that the true vapor pressure did not exceed 1.5 psia, or of the Reid Vapor Pressure and loading temperature; or
- ii. The vessel owner, charterer or prior load terminal operator may inform the Permit Holder of the identity of the crude stream in the prior load. The crude stream may be characterized by reference to typical samples of assays of such streams along with the prior loading temperature to determine the true vapor pressure; or
- iii. The ship owner, charterer, or terminal operator for the prior load may provide assay data or samples to determine Reid Vapor Pressure. Data for loading conditions from a knowledgeable source shall be used to determine true vapor pressure at loading conditions.

Emissions from loading shall be calculated as:

$$E_t = E_a + E_g$$

where:

$E_t$  = total loading emission, lb/1,000 gallon

$E_a$  = arrival component

$E_g$  = generated component

Arrival Emission Factor, lb/1000 gallon

<u>Previous Cargo</u>	<u>Condition of Compartment</u>	<u>Arrival Emission factor</u>
Non-Volatile	Any	0.33
Volatile	Washed or Gas Freed	0.33
Volatile	Ballasted	0.46
Volatile	Uncleaned	0.86

If the prior cargo is unknown, it shall be assumed to be volatile. If the condition of the compartment is unknown, it shall be assumed to be uncleaned.

$$E_g = 1.84 \times (0.44 \times (TVP) - 0.42) \times M \times G/T$$

where:

$E_g$  = generated emission, lb/1,000 gallon

TVP= true vapor pressure of loaded crude oil, psia

M = molecular weight of vapor, use 58 lb/lb-mole

## VI. Permit Conditions

G = vapor growth factor, use 1.02  
 T = loading temperature, Rankine

- For crude oil Cargos with true vapor pressure less than 1.5 psia, emissions from loading non-volatile crude oils shall be calculated as:

$$E_t = E_a + E_g$$

where:

$E_t$  = Total loading emission, lb/1,000 gallon

$E_a$  = Arrival Emission

$E_g$  = Generated Emissions

$E_a = 12,46 \text{ SPaM/T}$

$E_g = 12,46 \text{ SPgM/T}$

Where:

S = 0.2 for ships and ocean barges 0.5 for barges

$P_a$  = True vapor pressure of prior cargo, psia = zero if tank has been water washed or gas freed = 0.75 psia if no data available.

$P_g$  = true vapor pressure of crude oil loaded, psia

M = molecular weight of vapors, use 58 lb/lb-mole

T = loading temperature, Rankine

### *Gasoline Cargos*

- If information on the vessels' prior cargo and ballast voyage treatment is unknown the following emission factors shall be used.

	Total Loading Emission lb/1,000 gallon
Gasoline - Tanker/Ocean Barges	2.6
Gasoline – Barges	3.9

Note: Ocean barges are assumed to have a capacity greater than 100,000 bbls.

- If adequate information is available, the following loading factors shall be used:

<u>Type</u> <u>of</u> <u>Vessel</u>	<u>Prior</u> <u>Cargo</u>	<u>Condition</u> <u>of</u> <u>Compartment</u>	Total Loading Emissions (lbs VOC/1,000 bbl loaded)		
			<u>minimum</u> <u>ullage</u> <u>less than</u> <u>10ft</u>	<u>minimum</u> <u>ullage</u> <u>between</u> <u>10&amp;20ft</u>	<u>minimum</u> <u>ullage</u> <u>more</u> <u>than 20ft</u>
Tanker/Ocean Barge	Volatile	Uncleaned	109.2	94.5	79.8
		Ballasted	71.4	56.7	42.0

## VI. Permit Conditions

	Cleaned (washed)	63.0	48.3	33.6
	Gas Freed	29.4	4.7	0.0
Non-Volatile	All	29.4	14.7	0.0

### Barge less than 100,000 barrels capacity

Volatile	Uncleaned	163.8	163.8	163.8
	Ballasted	84.0	84.0	84.0
	Cleaned (washed)	84.0	84.0	84.0
	Gas Freed	84.0	84.0	84.0
Non-Volatile	All	84.0	84.0	84.0

Volatile liquid is any hydrocarbon liquid with a true vapor pressure greater than 1.5 psia.

An Uncleaned compartment has had no treatment of any kind except routine heel washing.

A Ballasted compartment is an uncleaned cargo compartment that has been loaded with ballast water.

A cleaned compartment has been water washed.

A gas-freed compartment has been cleaned and airblown, such that the compartment is suitable for entry and hot work (such as welding).

### *Distillate Fuels*

1. If adequate information on the vessel's prior cargo and ballast voyage treatment is available, the following emission factors shall be used to calculate emissions from loading diesel fuel and kerosene based jet fuels:

#### Total Loading Emissions (lbs VOC/1,000 bbl loaded)

Type of Vessel	Prior Cargo	Condition of Compartment	Emission Factor
Tanker/Ocean Barge	Volatile	Uncleaned	79.8
		Ballasted	42.0
		Cleaned (washed)	33.6
		Gas Freed	0.0
	Non-Volatile	All	0.0

## VI. Permit Conditions

### Barge less than 100,000 barrels capacity

Volatile	Uncleaned	163.8
	Ballasted	84.0
	Cleaned (washed)	84.0
	Gas Freed	0.0
Non-Volatile	All	0.0

Volatile liquid is any hydrocarbon liquid with a true vapor pressure greater than 1.5 psia.

Definitions for compartment condition are the same as set forth above under gasoline cargos.

- If any of the information necessary to ascertain the prior cargo or compartment condition of the vessels being loaded is unknown, the applicable worst-case assumption from the table above shall be used.

### *Other Volatile Cargos*

Volatile organic compounds, other than gasoline or volatile crude oil, may be loaded at the Martinez Shore Oil terminal. Emissions from loading those materials shall be calculated as follows:

$$E_t = 12.47 \text{ SPM/T}$$

where:

$E_t$  = Total loading emission, lb/1,000 gallon loaded

$S$  = 0.2 for ships and ocean barges 0.5 for barges

$P$  = True vapor pressure of prior cargo, psia

$M$  = molecular weight of vapors, use 58 lb/lb-mole

$T$  = loading temperature, Rankine

For naphtha-based jet fuels,  $P$  will depend on the type of product (see AP-42, Table 4.3.2, Physical Properties of Typical Organic Liquids)

For other volatile organic liquids, Permit Holder shall obtain the data.

Volatile liquid is any hydrocarbon liquid with a true vapor pressure greater than 1.5 psia.

### *Fuel Oil and Other Non-Volatile Cargos*

## VI. Permit Conditions

Non-volatile organic materials other than non-volatile crude oils and distillate fuels may be loaded at the Permit Holder terminal.

1. If adequate information on the vessel's prior cargo and ballast voyage treatment is available, the following emission factors shall be used to calculate emissions from the loading of fuel oil and other non-volatile cargos:

Total Loading Emissions  
(lbs VOC/1000 bbl loaded)

Prior Cargo:	Crude Oil		Gasoline/ Other Volatile Organics	Diesel/ Kero Jet Fuel	Fuel Oil Other Non- Volatile Organics
	<u>Volatile</u>	<u>Non- Volatile</u>			
Condition of Compartment					
Uncleaned	30.7	11.8	79.8	0	0
Ballasted	16.4	11.8	42.0	0	0
Water Washed	11.8	11.8	33.6	0	0
Gas Freed	0	0	0	0	0

Volatile liquid is any hydrocarbon liquid with a true vapor pressure greater than 1.5 psia.

Definitions for compartment condition are the same as set forth above under gasoline cargos

2. If any of the information necessary to ascertain the prior cargo of compartment condition of the vessels being loaded is unknown, the applicable worst-case assumption from the table above shall be used.

### B) CONTROLLED LOADING

For all cargos carried on vessels for which vapor emissions during loading are controlled either by connection to the onshore vapor recovery system or by use of onboard vapor processing equipment the emissions after control shall be based on the uncontrolled emissions level modified by a factor representing reduction. Such factors shall be determined by source tests, approved by the APCO, and shall reflect operating characteristics of the actual vapor control equipment.

a + BEt

where:

a = a constant independent of the cargo loaded or uncontrolled loading emissions.

b = a constant

Et = uncontrolled level of loading emissions

## VI. Permit Conditions

### BALLASTING EMISSION CALCULATIONS

Gasoline and Gasoline Components

1.6 lb/1,000 gallons unsegregated ballast water

Unsegregated Ballast Volume M-gallons =

$42 \times 7.5 \times \text{MDWT} \times (.15 - \% \text{ segregate ballast}/100)$

MDWT = ship's displacement in thousands of dead-weight tons

### CARGO PUMPING EMISSIONS

Emissions (lbs) = factor x (volume of cargo offloaded, Mbbls)

<u>Ship Size</u>	<u>Factor lb/Mbbls</u>	
	<u>Organic</u>	<u>NOx</u>
For Steam Vessels	0.09	0.67
For Other Vessels	0.09	1.08
For Barges	0.39	1.08

SOx emissions for cargo pumping shall be calculated as shown in Schedule E.

### TRANSIT EMISSION CALCULATIONS

#### Ship Type

<u>Ship Size</u>	<u>Fuel Consumption Gal/hr</u>	<u>Total Fuel Used 9 hrs Transit</u>	<u>Part</u>	<u>Emissions During 9 hrs Transit &amp; Maneuvering</u>		
				<u>Org</u>	<u>NOx</u>	<u>CO</u>
20	210	1890	35.9	5.9	91.1	5.0
20- 29	341	3069	58.3	9.5	147.9	8.0
30- 39	394	3546	67.4	11.0	170.9	9.3
40- 49	459	4131	78.5	12.8	199.1	10.8
50- 59	630	4959	94.2	15.4	239.0	13.0
60- 79	761	5670	107.7	17.6	273.3	14.9
80- 99	840	6849	130.1	21.2	330.1	17.9
100-139	906	7560	143.6	23.4	364.4	19.8
<u>Motor</u>						
20	105	945	18.9	31.0	355.3	53.8
20- 29	236	2124	42.5	69.7	779.5	120.9
30- 39	289	2600	52	85.3	954.2	147.9

**VI. Permit Conditions**

40- 49	341	3070	61.4	100.7	1126.7	174.7
50- 59	354	3190	63.8	04.6	1170.7	181.5
60- 79	394	3546	70.9	116.3	1301.4	201.8
80- 99	405	4131	2.6	135.5	1516.1	235.1
100-139	551	4959	99.2	162.7	1819.9	282.2

SOx emissions for ship transit shall be calculated according to the procedures specified in Schedule E.

Ships calling at Bay Area Locations other than Permit Holder during the same trip shall be charged only one half of the transit emissions from the above tables.

**HOTELLING EMISSION CALCULATIONS**

Emission = factor x hours at dock

<u>Ship Size</u>	Factor lb/hr	
	<u>Organic</u>	<u>NOx</u>
less than 60 MDWT	.13	1.53
greater than 60 MDWT	.27	3.06
<u>For Motor Vessels and Others</u>		
less than 70 MDWT	.22	2.28
greater than 70 MDWT	.44	4.57
for barges, all sizes	0	0

SOx emission for hotelling shall be calculated as shown in Schedule E.

**TUG EMISSION CALCULATIONS**

For ships, Emission = factor x for all vessel calls

For barges, Emissions = factor for barges calling at other Bay Area Location  
 = factor x2, for barges calling only at the Martinez terminal

<u>Ship</u>	Factor lb/call		
	<u>Organic</u>	<u>NOx</u>	<u>SOx</u>
less than 50 MDWT	3.41	150	18.6
greater than 50 MDWT	6.81	299	37.2
<u>Barges</u>			
less than 100,000 barrels capacity	5.11	224	27.9

## VI. Permit Conditions

greater than 100,000 barrels capacity (Ocean Barges)	10.22	449	55.8
--	-------	-----	------

### SCHEDULE E

Sulfur emissions will be based on the actual sulfur content fuels burned where possible. Permit Holder shall have three alternative procedures available for establishing the sulfur content of fuels. First, Permit Holder may provide fuel of known sulfur content to the ship. Second Permit Holder may sample the ship's fuel for analysis by an outside laboratory qualified to perform Sulfur analyses on marine fuels. Third, in the absence of either of the two procedures mentioned above, assumed values below shall be used.

If Permit Holder elects to provide low sulfur fuel to a particular ship, a certified fuel analysis of the Sulfur content shall be used to establish SO<sub>2</sub> emissions. The Permit Holder terminal manager shall instruct the ship's captain or his designated to burn only that fuel while within the District waters. The amount of fuel provided shall be adequate to fuel all the ship's requirements for hotelling, pumping and transit. A sample of the fuel provided shall be retained by Permit Holder for District analysis until at least 90 days following delivery of the quarterly report including that particular ship call. Records of the quantity of fuel provided, sulfur content, and burning instructions shall be retained by Permit for at least five year following the ship call.

If Permit Holder elects to sample the fuel from a particular ship, such sample shall be gathered by the ship's personnel and delivered to permit Holder. This sample shall contain at least one-quart volume. After analysis the remaining portion of the samples shall be retained at the terminal and made available to the district for their independent analysis. All such samples shall be retained for at least 90 days following delivery of the quarterly report to the District. Samples for a calendar quarter may be combined by blending thoroughly equal parts of each sample gathered for each type of ship, that is one composite sample for steam ships and one composite sample for motor and other ships. At Permit Holder's option, each ship sample may be analyzed separately. An independent laboratory shall analyze such samples and the results of those analyses shall be used to establish sulfur emissions. Permit Holder shall report to the [Director of Enforcement of the](#) District results of all analyses performed. Any failure by Permit Holder to report the sulfur analyses will subject them to an appropriate enforcement action.

If Permit Holder neither samples the fuel from any given ship, nor provides fuel to the ship, the sulfur content of that fuel shall be assumed to be 3.34% in the case of steam ships, or 1.5% in the case of motor ships and other ships. In the event that Permit Holder samples and cause to be analyzed fuels from at least 66.67% of all ships calling at terminal in a calendar year to which fuel was not provided, the weighted average of sample results may be used in the following calendar year in lieu of the assumed sulfur values described in the preceding paragraph. In calculating the weighted average, each

## VI. Permit Conditions

analysis shall be weighted by the number of ships represented by that analysis, i.e., one if the sample was an individual ship sample or more than one if the sample was composite sample. The results of such analyses are subject to verification by the District and samples shall be available upon demand for that purpose. If Permit Holder samples and reports fewer than 66.67% of all ships to which fuel was not provided in a given calendar year, the assumptions for the following year shall be 3.34% for steam ships and 1.5% for motor and other ships. [Basis: Reg. 9-1-303]

### TRANSIT EMISSION CALCULATIONS

Emissions per call = factor x fuel sulfur index  
 (for vessels calling at other Bay Area locations)

Emissions per call = factor x fuel sulfur index x 2  
 (for vessels calling only at Terminal)

#### Factors

<u>Ship size</u>	<u>MDWT</u>	<u>Steam Vessels</u>	<u>Motor &amp; Other</u>
less than	30	244	75
	30-40	282	169
	40-50	328	207
	50-60	394	244
More than	60	451	254

### CARGO PUMPING EMISSION CALCULATIONS

Sulfur oxide emissions for offloading cargos from marine vessels to shore tanks shall be calculated as follows:

$$\text{Emissions} = \frac{\text{fuel sulfur index}}{3.34} \times \frac{315 \text{ lb SO}_2}{\text{M gal fuel}} \times \frac{32 \text{ lb S}}{64 \text{ lb SO}_2}$$

### HOTELLING EMISSION CALCULATIONS

Barges have no hotelling emissions.

Hotelling emissions will be calculated for ship as follows:

$$\text{Emissions} = \text{R-factor} \times \text{Hotelling time (hours)} \times \text{R-Fuel Sulfur Index} + \text{D-factor} \times \text{Hotelling time} \times \text{D-Fuel Sulfur Index}$$

Hotelling time = Hours from time the vessel is secure at the wharf until the time the last

## VI. Permit Conditions

line is cast off.

Factors are as follows:

<u>Ship size,MDWT</u>	<u>Steam Ships</u>		<u>Motor &amp; Other</u>	
	<u>R-Factor</u>	<u>D-Factor</u>	<u>R-Factor</u>	<u>D-Factor</u>
less than 60	6.68	0.0	6.68	3.34
60-70	13.36	0.0	6.68	3.34
Greater Than 70	13.36	0.1	13.36	6.68

## IV MARINE VESSEL LOADING VAPOR COMBUSTION UNIT (A-41)

1. Deleted, startup source test.
2. Permit Holder shall perform necessary source tests to establish a specific range of combustion zone temperatures which will ensure that the emissions of precursor organic compounds are reduced at least 95% by weight from uncontrolled conditions, or that the POC emissions do not exceed 2 lbs per 1000 barrels loaded. [Basis: Cumulative Increase]
3. Permit Holder shall install instrumentation to monitor and record the following: [Basis: Cumulative Increase]
  - a. Static pressure developed in the marine tank vessel,
  - b. Oxidizer exhaust temperature, and
  - c. Hydrocarbon concentration and flow rate to determine mass emissions, or
    - i. A concentration measurement alone if Permit Holder can demonstrate to the satisfaction of the APCO that concentration alone provides adequate assurance of compliance, or
    - ii. Any other method or device that adequately verifies compliance, with prior approval from the APCO.

The need for the hydrocarbon analyzer will be reviewed by the APCO prior to issuance of the initial permit to operate.

4. Hydrocarbon emissions charged to the annual marine and facility emission caps will be the emissions recorded by the continuous hydrocarbon monitor. If the monitor is not operating, Permit Holder shall calculate uncontrolled emissions as specified in Schedule D of the Permit Conditions established as part of application number 31329, and use a 95% (by weight) reduction factor to determine controlled emissions. The overall collection and control efficiency, as determined by source test, may be used in

## VI. Permit Conditions

- lieu of the 95% factor for determining controlled emissions. [Basis: Cumulative Increase]
5. Deleted, startup monitoring plan.
  6. Permit Holder shall not load or permit the loading of a regulated organic liquid, as defined in Regulation 8, Rule 44, Section 204, into a marine tank vessel within the District whenever the marine vapor recovery system is not fully operational, except for operations specifically exempt from Regulation 8, Rule 44. The vapor recovery system shall be maintained to be leak free, gas tight, and in good working order. For the purposes of this condition, "fully operational" shall mean the system is achieving the reductions required by Condition No. 2 above. [Basis: Cumulative Increase]
  7. The minimum incinerator temperature of A-41 shall be at least 1400°F. The vapor recovery system is not "fully operational" at any lower temperature. This minimum temperature may be adjusted by the District if source test data demonstrate that an alternate temperature is necessary for or capable of maintaining compliance with Condition No. 2 above. [Basis: Reg. 2-1-403]

The facility may conduct a source test for the purpose of lowering the minimum temperature requirement provided that the following has occurred:

- a. The facility has applied to the Permit Services Division for a change of conditions.
  - b. The Source Test Section was notified at least seven days prior to testing and the test protocol was deemed acceptable.
  - c. The results of the test demonstrate that A-41 is capable of meeting the emission factor limits imposed in Condition No. 2 for POC at the lower operating temperature. [Basis: Reg. 2-1-403]
8. A leak test shall be conducted on all vessels loading under positive pressure prior to loading more than 20% of the cargo. The leak test is not intended to impede the loading of a gas-tight tank vessel. The leak test shall include all vessel relief valves, hatch covers, gauging connections, and vapor recovery hose connections. Leak test results shall be included in the quarterly reporting already required of the Permit Holder. [Basis: Regulation -8, Rule -44]
  9. Permit Holder shall not exceed a loading pressure greater than 80% of the lowest relief valve set pressure, including vessel relief valves, while loading a controlled marine vessel. [Basis: Cumulative Increase]
  10. All maintenance records required for the vapor recovery system at this facility, which are subject to Regulation 8, Rule 44, shall be kept on site for five years and made available to the District upon request. [Basis: Recordkeeping Regulation 2, Rule 1, Section 403]

## VI. Permit Conditions

V. SHORESIDE VAPOR RECOVERY UNITS (A-42 & 43) Removed due to expired A/C.

VI. TANKAGE (S-1 & 2) Removed due to expired A/C.

### ~~COND# 9005~~

~~— For S-1 through S-16, S-18, S-19, Storage tanks; S-20, Tank Truck Loading rack; S-21, Marine Vessel Wharf; S-23, S-24, Oily Water Separators; S-27, S-28, Fixed Roof tanks.~~

- ~~1. POC emissions from A-2 and/or A-41 Afterburners shall not exceed 1.44 pounds per 1000 barrels transferred. This condition applies during all of the following events:
  - ~~a. when non-exempt organic compounds (as defined in District Regs 2-1-206 and 2-1-123) are being stored in or transferred to storage tanks S-1, S-12, S-18, S-19, S-27, S-28.~~
  - ~~b. when organic liquids with a true vapor pressure of 1.5 psia or greater are being loaded at truck rack S-20; and/or~~
  - ~~c. when organic liquids (as defined in District Reg 8-44-204) are loaded at marine wharf S-21. [Basis: BACT]~~~~
- ~~2. Storage Tanks S-1 through S-12, S-18, S-19, S-27, S-28, Truck Rack S-20, Marine Wharf S-21 shall be abated at all times of operation by either the A-1 Lean Oil Absorption System and the A-2 Afterburner or A-41 Afterburner. [Basis: Cumulative Increase]~~
- ~~3. Deleted, startup source test.~~
- ~~4. Facility emissions shall be calculated in accordance with the procedures described in Condition #1253. Total facility emissions of POC's shall not exceed 86.5 tons in any consecutive 12-month period. [Basis: Cumulative Increase]~~
- ~~5. Deleted, sources S-50 through S-72 have not been constructed, permit expired.~~
- ~~6. Deleted, sources S-50 through S-72 have not been constructed, permit expired.~~
- ~~7. Deleted, sources S-50 through S-72 have not been constructed, permit expired.~~
- ~~8. All pumps in organic liquid service at the facility shall be subject to the inspection and maintenance requirements of Regulation 8, Rule 18. This condition shall apply to pumps in both heavy and light organic liquid service. [Basis: Reg. 8-18]~~
- ~~9. Deleted, sources S-50 through S-72 have not been constructed, permit expired.~~

## VI. Permit Conditions

- ~~10. Deleted, sources S-50 through S-72 have not been constructed, permit expired.~~
- ~~\*11. The average benzene concentration in all hydrocarbon liquids stored in Storage Tanks at this facility shall not exceed 4% by weight. The owner/operator of the facility shall analyze all materials stored in these tanks for benzene concentration at least once every 6 months. These records shall be kept on file for at least 5 years after the date of entry and shall be made available to District personnel upon request. [Basis: Toxics]~~

### COND# 13720

#### S-73, DIRECT FIRED HEATER

1. Total natural gas usage at S-73 shall not exceed 90 million standard cubic feet (scf) in any consecutive 12-month period. This ~~consecutive 12-month 90 million scf gas-firing~~ limit shall be reduced by 454 scf for every gallon of diesel fuel fired during the same consecutive 12-month period. [Basis: Cumulative Increase]
2. S-73 NO<sub>x</sub> concentrations shall not exceed 20 ppmv @ 3% O<sub>2</sub> as determined using District Source Test Method 13 A or B. This condition shall become effective upon completion of the start up/commissioning period as specified in ~~condition-part~~ #5. [Basis: BACT]
3. S-73 CO concentrations shall not exceed 50 ppmv @ 3% O<sub>2</sub> as determined using District Source Test Method 6. [Basis: BACT]
4. S-73 shall be fired exclusively on natural gas except for times of force majeure ~~or~~ natural gas curtailment as defined in Regulation 9-11-208. NO<sub>x</sub> emissions from S-73 shall not exceed 60 ppmv @ 3% O<sub>2</sub> when firing on diesel as determined using District Source Test Method 13 A or B. [Basis: BACT]
5. The owner/operator shall conduct a District approved source test annually thereafter in order to determine compliance with ~~condition number~~ parts 2, 3, Regulation 9-7-301.1 and Regulation 9-7-301.2. All source testing shall be performed in accordance with the District's Manual of Procedures. The facility shall receive approval from the District's Source Test Manager for installation of test ports and source testing procedures. The results shall be delivered to the Director of Enforcement of the District no later than 30 days from the date of the source test. [Basis: Regulation -9, Rule -7]
6. The owner/operator shall use a non-resettable natural gas flow meter in order to demonstrate compliance with ~~condition-part~~ #1. Natural gas and diesel fuel usage shall be recorded in a District approved monthly log and retained for at least 5 years from the date of entry. This log shall be kept on site and made available to District staff upon request. [Basis: Record Keeping Regulation 2, Rule 1, Section 403]

## VI. Permit Conditions

7. Within 1 month of issuance of the Title V Permit, the permit holder shall analyze a sample of distillate oil in the fuel oil tank for sulfur content to ensure compliance with Regulation 9-1-304. The sample shall be analyzed using District Method 10, Determination of Sulfur in Fuel Oils. The results of the analysis shall be sent to the Director of Enforcement and ~~compliance~~ **Compliance** at the District. All subsequent shipments of fuel oil to the facility shall have a vendor certification of the sulfur content of the fuel. [Basis: Regulation 2, Rule --6, Section -409.2]

### **COND# 19308**

#### **S-74 and S-75, EMERGENCY DIESEL GENERATORS**

1. The engines for emergency generators S-74, and S-75 shall be fired exclusively on diesel fuel having a sulfur content no greater than 0.05% by weight. The sulfur content of the fuel oil shall be certified by the fuel vendor. [Basis: Cumulative Increase]  
  
“Emergency Conditions” is defined as any of the following: [Basis: Regulation 9, Rule --8, Section -231]
  - a. Loss of regular natural gas supply
  - b. Failure of regular electric power supply
  - c. Flood mitigation
  - d. Sewage overflow mitigation
  - e. Fire
  - f. Failure of a primary motor, but only for such time as needed to repair or replace the primary motor.
2. S-74 and S-75 shall only be operated to mitigate emergency conditions or for reliability-related activities. Operation for reliability-related activities shall not exceed 100 hours in any calendar year at each engine. Operation while mitigating emergency conditions is unlimited. [Basis: Regulation 9-8-330, Cumulative Increase]
3. S-74 and S-75 shall be equipped with either: [Basis: Regulation 9-8-530]
  - a. a non-resettable totalizing meter that measures and records the hours of operation for the engine  
or
  - b. a non-resettable fuel usage meter; the following factors shall be used to convert fuel usage to hours of operation:  
S-74: 8.75 gal/hr  
S-75: 8.0 gal/hr
4. The following monthly records shall be maintained in a District-approved log for at least 5 years for S-74 and S-75 and shall be made available for District inspection upon request: [Basis: Regulation 9-8-530, ~~1-441~~]
  - a. Total hours of operation for each engine

## VI. Permit Conditions

- b. Hours of operation under emergency conditions for each engine and a description of the nature of each emergency condition
- c. Fuel usage for each engine.

### COND# 20060

#### S-76, S-77 and S-78 INTERNAL FLOATING ROOF TANKS

1. The gasoline or other hydrocarbon liquids loaded into each storage tank (S-76, or S-77, or S-78) shall not exceed 105 million gallons in any consecutive 12-month period. [Basis: Cumulative Increase]
2. The gasoline or other hydrocarbon liquids loaded into each storage tank (S-76, or S-77, or S-78) shall not exceed 4.2 million gallons during any calendar day. [Basis: Cumulative Increase]
- \*3. The average benzene concentration in all hydrocarbon liquids stored in Storage Tanks S-76, S-77 and S-78 shall not exceed 1.8 % by weight. The owner/operator of sources S-76, S-77 and S-78 shall analyze all materials stored in each of these tanks for benzene concentration at least once every 6 months. Each tank shall be sampled within 30 days of start-up. If the owner/operator can demonstrate that several tanks contain hydrocarbon from a single source (shipment), then a single benzene analysis may be performed for that group of tanks. These records shall be kept on file for at least 5 years after the date of entry and shall be made available to District personnel upon request. All tests shall be performed in accordance with District approved laboratory procedures. . [Basis: TRMP]
4. All new valves and flanges associated with this project shall be subject to the inspection and maintenance criteria of District Regulation 8, Rule 18 and any future revisions to this rule. [Basis: Regulation 8, Rule 18]
5. Sources S-76, S-77 and S-78 shall meet all applicable requirements of District Regulation 8, Rule 5 and NSPS, 40 CFR 60, Subpart Kb. [Basis: Regulation 8, Rule 5, NSPS]
6. In order to demonstrate compliance with the above conditions, the owner/operator of tanks S-76, S-7, and S-78 shall maintain the following records in a District approved log. These records shall be kept on site and made available for District inspection for a period of five years from the date that the record was made. [Basis: Cumulative Increase, TRMP]
  - a. The type and VOC content of all materials stored and the dates that the materials were stored.
  - b. The total daily throughput of each material stored, summarized on a monthly and annual basis.

## VII. APPLICABLE LIMITS & COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any. The monitoring frequency indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown, either using the following codes: annual (A), quarterly (Q), monthly (M), weekly (W), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

**Table VII - A**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-1 THROUGH S-10 - FIXED ROOF TANKS**

Type of Limit	<u>Emission Limit</u> Citation of Limit	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD 8-5- <del>311.3</del> <u>3306</u>	<del>Y</del> <u>N</u>		Controlled $\geq$ 95% weight	BAAQMD Condition # 1253, part IV, Section 3b	C	Continuous Temperature Monitor
POC	BAAQMD 8-5-328. <u>1.2</u>	<del>Y</del> <u>N</u>		Tank cleaning $\geq$ 90% control, POC concentration < 10,000 ppm	<del>BAAQMD 8-5-502</del> <u>None</u>	<del>P/A</del> <u>None</u>	<del>Source Test</del> <u>None</u>
<u>POC</u>	<u>SIP</u> <u>BAAQMD</u> <u>8-5-311.3</u>	<u>Y</u>		<u>Controlled &gt; 95%</u> <u>weight</u>	<u>BAAQMD</u> <u>Condition #</u> <u>1253, part IV,</u> <u>Section 3b</u>	<u>C</u>	<u>Continuous</u> <u>Temperature</u> <u>Monitor</u>
<u>POC</u>	<u>SIP</u> <u>BAAQMD</u> <u>8-5-328.2</u>	<u>Y</u>		<u>Tank cleaning &gt; 90%</u> <u>control, POC</u> <u>concentration &lt;</u> <u>10,000 ppm</u>	<u>SIP</u> <u>BAAQMD</u> <u>8-5-502</u>	<u>P/A</u>	<u>Source Test</u>
POC	Subpart K 40 CFR 60.112(a) (1)	Y		Vapor Recovery System	Subpart K 40 CFR 60.113(d) (2)	None	None

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - A**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-1 THROUGH S-10 - FIXED ROOF TANKS**

Type of Limit	<del>Emission Limit</del> Citation of Limit	FE Y/N	Future Effective Date	<del>Emission-Limit</del>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 1253, part 1B	Y		<del>65-167.146</del> tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
POC	BAAQMD Condition # 1253, part IIID	Y		1.44 pounds/1000 barrels	BAAQMD Condition # 1253, part IV, Section 3	C	Continuous Hydrocarbon monitor

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - B**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-11 - FIXED ROOF TANKS**

Type of Limit	<del>Emission Limit</del> Citation of <del>Limit</del>	FE Y/N	Future Effective Date	<del>Emission-Limit</del>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	<u>BAAQMD 8-5-301</u>	<u>N</u>		<u>Pressure-Vacuum valve</u>	<u>BBAQMD 8-5-403</u>	<u>P/twice/yr</u>	<u>Inspection</u>
POC	<u>BAAQMD 8-5-303</u>	<u>N</u>		<u>Pressure-Vacuum valve set with 10% of maximum allowable working pressure</u>	<u>BBAQMD 8-5-403</u>	<u>P/twice/yr</u>	<u>Inspection</u>
POC	<u>SIP</u> BAAQMD 8-5-302	Y		Pressure-Vacuum valve set with 10% of maximum allowable working pressure	None	N	
POC	BAAQMD Condition # 1253, part 1B	Y		<del>65-167.146</del> tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records

**Table VII - C**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-12, S-18, AND S-19 - FIXED ROOF TANKS**

Type of Limit	<del>Emission Limit</del> Citation of <del>Limit</del>	FE Y/N	Future Effective Date	<del>Emission-Limit</del>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD 8-5- <del>311-3306</del>	<del>Y</del> <u>N</u>		Controlled $\geq$ 95% weight	BAAQMD Condition # 1253, part IV, Section 3b	C	Continuous Temperature Monitor
POC	BAAQMD 8-5-328.1.2	<del>Y</del> <u>N</u>		Tank cleaning $\geq$ 90% control, POC concentration < 10,000 ppm	<u>BAAQMD 8-5-502</u> <del>None</del>	<u>P/A</u> <del>None</del>	<u>Source Test</u> <del>None</del>

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - C**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-12, S-18, AND S-19 - FIXED ROOF TANKS**

Type of Limit	<u>Emission Limit</u> Citation of Limit	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<u>POC</u>	<u>SIP</u> <u>BAAQMD</u> <u>8-5-311.3</u>	<u>Y</u>		<u>Controlled &gt; 95% weight</u>	<u>BAAQMD</u> <u>Condition #</u> <u>1253, part IV,</u> <u>Section 3b</u>	<u>C</u>	<u>Continuous</u> <u>Temperature</u> <u>Monitor</u>
<u>POC</u>	<u>SIP</u> <u>BAAQMD</u> <u>8-5-328.2</u>	<u>Y</u>		<u>Tank cleaning &gt; 90% control, POC concentration &lt; 10,000 ppm</u>	<u>SIP</u> <u>BAAQMD</u> <u>8-5-502</u>	<u>P/A</u>	<u>Source Test</u>
POC	BAAQMD Condition # 1253, part 1B	Y		<del>65.467.146</del> tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
POC	BAAQMD Condition # 1253, part IIID	Y		1.44 pounds/1000 barrels	BAAQMD Condition # 1253, part IV, Section 3	C	Continuous Hydrocarbon monitor
NOx	BAAQMD Condition # 1253, part 1B	Y		129.5 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
NOx	BAAQMD Condition # 1253, part IIID, schedule D	Y		9.68 lb/day plus 0.1744 pounds/1000 barrels	None	None	Source test
CO	BAAQMD Condition # 1253, part 1B	Y		52.2 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
SO2	BAAQMD Condition # 1253, part 1B	Y		83.5 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - C**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-12, S-18, AND S-19 - FIXED ROOF TANKS**

Type of Limit	<u>Emission Limit Citation of Limit</u>	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<u>EPM</u>	BAAQMD Condition # 1253, part IB	Y		25.8 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records

**Table VII - D**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

Type of Limit	<u>Emission Limit Citation of Limit</u>	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<u>POC</u>	<u>BAAQMD 8-5-320.3.1</u>	<u>N</u>		<u>Gasketed cover, seal or lid with gap &lt; 0.32 cm (1/8 in)</u>	<u>BAAQMD 8-5-401.2, 8-5-404</u>	<u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>
	<u>BAAQMD 8-5-320.4.2</u>	<u>N</u>		<u>Well with cover, seal or lid with gap &lt; 0.32 cm (1/8 in)</u>	<u>BAAQMD 8-5-401.2, 8-5-404</u>	<u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>
	<u>BAAQMD 8-5-320.4.3</u>	<u>N</u>		<u>Gap between well and roof less than 1.3 cm (1/2 in)</u>	<u>BAAQMD 8-5-401.2, 8-5-404</u>	<u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>
	<u>BAAQMD 8-5-320.5.2</u>	<u>N</u>		<u>Well with cover gasket, a pole sleeve, pole wiper and internal float with gap &lt; 1.3 cm (1/2 in), or ero gap pole wiper seal</u>	<u>BAAQMD 8-5-401.2, 8-5-404</u>	<u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>
	<u>BAAQMD 8-5-320.5.3</u>	<u>N</u>		<u>Gap between well and roof less than 1.3 cm (1/2 in)</u>	<u>BAAQMD 8-5-401.2, 8-5-404</u>	<u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - D**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

Type of Limit	<u>Emission Limit Citation of Limit</u>	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
<u>POC</u>	<u>BAAQMD 8-5-321.3</u>	<u>N</u>		<u>Primary seal metallic shoe extends a minimum 61 cm (24 in) above liquid surface</u>	<u>BAAQMD 8-5-401.1, 8-5-404</u>	<u>P/twice/yr</u> <u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-321.3.1</u>	<u>N</u>		<u>Gap between shoe and tank shell is no greater than 46 cm (18 in)</u>	<u>BAAQMD 8-5-401.1, 8-5-404</u>	<u>P/twice/yr</u> <u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-321.3.2</u>	<u>N</u>		<u>Gap between tank shell and the primary seal &lt; 3.8 cm (1 1/2 in). No continuous gap &gt; 0.32 cm (1/8 in) shall exceed 10% of circumference. The cumulative length of all seal gaps exceeding 1.3 cm (1/2 in) &lt; 10% of circumference and the cumulative length of all seal gaps exceeding 0.32 cm (1/8 in) &lt; 40% of circumference</u>	<u>BAAQMD 8-5-401.1, 8-5-404</u>	<u>P/twice/yr</u> <u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-322.2</u>	<u>N</u>		<u>Secondary seal shall allow insertion up to 3.8 cm (1 1/2 in) in width</u>	<u>BAAQMD 8-5-401.1, 8-5-404</u>	<u>P/twice/yr</u> <u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-322.3</u>	<u>N</u>		<u>Gap between tank shell and the secondary seal shall not exceed 1.3 cm (1/2 in)</u>	<u>BAAQMD 8-5-401.1, 8-5-404</u>	<u>P/10 yr</u> <u>P/twice/yr</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>SIP BAAQMD 8-5-328.1.2</u>	<u>N</u>		<u>Tank cleaning &gt; 90% control, POC concentration &lt; 10,000 ppm</u>	<u>BAAQMD 8-5-502</u>	<u>P/A</u>	<u>Source Test</u>
<u>POC</u>	<u>SIP BAAQMD 8-5-320.2.2</u>	<u>Y</u>		<u>Viewports and other openings with gap ≤ 0.32 cm (1/8 in)</u>	<u>SIP BAAQMD 8-5-402</u>	<u>P/10 yr</u>	<u>Inspection</u>

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - D**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

Type of Limit	Emission Limit Citation of Limit	FE Y/N	Future Effective Date	Emission-Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	<u>SIP</u> BAAQMD 8-5-320.3	Y		PSV set within 10% of max pressure or 25.8 mmHg (0.5 psia)	<u>SIP</u> BAAQMD 8-5-402	P/10 yr	Inspection
POC	<u>SIP</u> BAAQMD 8-5-320.4.2	Y		Gap of seal or lid less than 0.32 cm (1/8 in)	<u>SIP</u> BAAQMD 8-5-402	P/10 yr	Inspection
POC	<u>SIP</u> BAAQMD 8-5-320.4.3	Y		Gap between well and roof less than 1.3 cm (1/2 in)	<u>SIP</u> BAAQMD 8-5-402	P/10 yr	Inspection
POC	<u>SIP</u> BAAQMD 8-5-320.5.2	Y	<del>6/1/00</del>	Internal float and wiper with gap $\leq$ (1/2 in)	<u>SIP</u> BAAQMD 8-5-402	P/10 yr	Inspection
POC	<u>SIP</u> BAAQMD 8-5-320.5.3	Y		Well and roof with gap $\leq$ (1/2 in)	<u>SIP</u> BAAQMD 8-5-402	P/10 yr	Inspection
POC	<u>SIP</u> BAAQMD 8-5-320.6	Y		Slotted membrane or equivalent covers at least 90% area of opening	<u>SIP</u> BAAQMD 8-5-405	P/10 yr	Inspection
POC	<u>SIP</u> BAAQMD 8-5-321.3	Y		Primary seal metallic shoe extends a minimum 61 cm (24 in) above liquid surface	<u>SIP</u> BAAQMD 8-5-401, 8-5-404	P/10 yr P/10 yr	Inspection Certification
POC	<u>SIP</u> BAAQMD 8-5-321.3.1	Y		Gap between shoe and tank shell is no greater than 46 cm (18 in)	<u>SIP</u> BAAQMD 8-5-401, 8-5-404	P/10 yr P/10 yr	Inspection Certification

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - D**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

Type of Limit	<u>Emission Limit Citation of Limit</u>	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	<u>SIP</u> BAAQMD 8-5-321.3.2	Y		Gap between tank shell and the primary seal < 3.8 cm (1 1/2 in). No continuous gap > 0.32 cm ((1/8 in) shall exceed 10% of circumference. The cumulative length of all seal gaps exceeding 1.3 cm (1/2 in) < 10% of circumference and the cumulative length of all seal gaps exceeding 0.32 cm (1/8 in) < 40% of circumference	<u>SIP</u> BAAQMD 8-5-401, 8-5-404	P/10 yr P/10 yr	Inspection Certification
POC	<u>SIP</u> BAAQMD 8-5-322.2	Y		Secondary seal shall allow insertion up to 3.8 cm (1 1/2 in) in width	<u>SIP</u> BAAQMD 8-5-402, 8-5-404	P/10 yr P/A	Inspection Certification
POC	<u>SIP</u> BAAQMD 8-5-322.3	Y		Gap between tank shell and the secondary seal shall not exceed 1.3 cm (1/2 in)	<u>SIP</u> BAAQMD 8-5-402, 8-5-404	P/10 yr P/A	Inspection Certification
POC	<u>SIP</u> BAAQMD 8-5-328.2	Y		Tank cleaning ≥ 90% control, POC concentration < 10,000 ppm	<u>SIP</u> BAAQMD 8-5-404.3, 8-5-502	P/A	Source Test
POC	Subpart K 40 CFR 60.112(a) (1)	Y		Floating Roof requirement	40 CFR 60.113(a),(b), (c)	None	Records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - D**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-13, S-14, S-15, S-16 – EXTERNAL FLOATING ROOF TANKS**

Type of Limit	Emission Limit Citation of Limit	FE Y/N	Future Effective Date	Emission-Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 1253, part 1B	Y		<del>65.167.146</del> tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records

**Table VII - E**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-20 – TANK TRUCK LOADING RACKS**

Type of Limit	Emission Limit Citation of Limit	FE Y/N	Future Effective Date	Emission-Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD 8-33-301	Y		POC Emission $\leq$ 9.6 grams per cubic meter (0.08 lb/1000gal) loaded	BAAQMD Condition # 1253, part IV, Section 3	C	Continuous Hydrocarbon monitor
POC	BAAQMD 8-33.309	Y		Tank gauge pressure < 46 cm (18 inch) of water column	N	P/E	Pressure measurement device
POC	Subpart R 40 CFR 63.422(b)	Y		TOC $\leq$ 10 milligram per liter loaded	BAAQMD Condition # 1253, part IV, Section 3	C	Continuous Hydrocarbon monitor
POC	Subpart XX 40 CFR 60.502(c)	Y		Emission < 80 milligram/liter	BAAQMD Condition # 1253, part IV, Section 3	C	Continuous Hydrocarbon monitor
POC	Subpart XX 40 CFR 60.502(h)	Y		Tank gauge pressure $\leq$ 4,500 pascals (450 mm of water)	BAAQMD Condition # 1253, part IV, Section 3	P/E	Pressure measurement device

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - E**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-20 – TANK TRUCK LOADING RACKS**

Type of Limit	<u>Emission Limit</u> Citation of Limit	FE Y/N	Future Effective Date	<del>Emission</del> -Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 1253, part 1B	Y		<del>65.467.146</del> tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
POC	BAAQMD Condition # 1253, part IIID	Y		1.44 pounds/1000 barrels	BAAQMD Condition # 1253, part IV, Section 3	C	Continuous Hydrocarbon monitor
NOx	BAAQMD Condition # 1253, part 1B	Y		129.5 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
NOx	BAAQMD Condition # 1253, part IIID, schedule D	Y		9.68 lb/day plus 0.1744 pounds/1000 barrels	None	None	
CO	BAAQMD Condition # 1253, part 1B	Y		52.2 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
SO2	BAAQMD Condition # 1253, part 1B	Y		83.5 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
<u>EPM</u>	BAAQMD Condition # 1253, part 1B	Y		25.8 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - F**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-21 – MARINE VESSEL WHARF**

Type of Limit	<del>Emission Limit</del> Citation of Limit	FE Y/N	Future Effective Date	<del>Emission-Limit</del>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD 8-44-301.1	Y		POC Emission $\leq$ 5.7 grams per cubic meter (2 lb/1000 barrel) loaded, or	BAAQMD Condition # 1253, part IV, Section 3c	C	Hydrocarbon Concentration monitor
POC	BAAQMD 8-44.301.2	Y		Controlled $\geq$ 95% weight	BAAQMD Condition # 1253, part IV, Section 3c	C	Hydrocarbon Concentration monitor
POC	Subpart Y 40 CFR 63.562(c)(2)(iii)	Y		Vapor tight	40 CFR 63.563(a)(4)	P/A	Leak test
POC	Subpart Y 40 CFR 63.562(c)(3)	Y		RACT existing source, controlled $\geq$ 98% weight by combustion device	40 CFR 63.563(b)(6)(i)(A), 63.564(a)(3)	C	Hydrocarbon Concentration monitor
POC	Subpart Y 40 CFR 63.562(c)(4)	Y		VOC $\leq$ 1000 ppmv	40 CFR 63.564(g)(1), BAAQMD Condition # 1253, part IV, Section 3c	C	Hydrocarbon Concentration monitor
POC	BAAQMD Condition # 1253, part 1B	Y		<del>65.167.146</del> tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
POC	BAAQMD Condition # 1253 part IV, section 2	Y		95% controlled efficiency or 2 lb/1000 barrels of gasoline loaded	BAAQMD Condition # 1253, part IV, Section 2	P/startup	Source test

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - F**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-21 – MARINE VESSEL WHARF**

Type of Limit	<u>Emission Limit Citation of Limit</u>	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 1253 part IV, section 7	Y		Operating temperature $\geq 1400^{\circ}\text{F}$ depend on source test result	BAAQMD Condition # 1253, part IV, Section 3c	C	Continuous temperature monitor
POC	BAAQMD Condition # 1253 part IV, section 9	Y		Loading pressure shall not exceed 80% of the lowest relief valve set pressure	None	None	Inspection
SO2	BAAQMD Regulation 9-1-303	Y		SO2 < 2000 ppm, or Sulfur < 3.34% by weight	BAAQMD Condition # 1253, part IIID, schedule F	P/Q	Analysis reports

**Table VII - G**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-23, S-24 – OILY WATER SEPARATORS**

Type of Limit	<u>Emission Limit Citation of Limit</u>	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 1253, part 1B	Y		<del>65-167.146</del> tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - H**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-27, AND S-28 - FIXED ROOF TANKS**

Type of Limit	<del>Emission Limit</del> Citation of Limit	FE Y/N	Future Effective Date	<del>Emission-Limit</del>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	<u>BAAQMD 8-5-306</u>	N		<u>Controlled &gt; 95% weight</u>	<u>BAAQMD Condition # 1253, part IV, Section 3b</u>	<u>C</u>	<u>Continuous Temperature Monitor</u>
POC	<u>BAAQMD 8-5-328.1.2</u>	N		<u>Tank cleaning &gt; 90% control, POC concentration &lt; 10,000 ppm</u>	<u>BAAQMD 8-5-502</u>	<u>P/A</u>	<u>Source Test</u>
<del>POC</del>	<del>SIP BAAQMD 8-5-311.3 BAAQMD 8-5-311.3</del>	<del>Y</del>		<del>Controlled &gt; 95% weight</del> <del>Controlled &gt; 95% weight</del>	<del>BAAQMD Condition # 1253, part IV, Section 3b BAAQMD Condition # 1253, part IV, Section 3b</del>	<del>C</del>	<del>Continuous Temperature Monitor</del> <del>Continuous Temperature Monitor</del>
<del>POC</del>	<del>SIP BAAQMD 8-5-328.2 BAAQMD 8-5-328.2</del>	<del>Y</del>		<del>Tank cleaning &gt; 90% control, POC concentration &lt; 10,000 ppm</del> <del>Tank cleaning &gt; 90% control, POC concentration &lt; 10,000 ppm</del>	<del>SIP BAAQMD 8-5-502</del>	<del>P/A</del> <del>None</del>	<del>Source Test</del> <del>None</del>
POC	Subpart Ka 40 CFR 60.112(a) (a)(3)	Y		Controlled ≥ 95%	N	N	None
POC	BAAQMD Condition # 1253, part 1B	Y		<del>65-167.146</del> tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - H**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-27, AND S-28 - FIXED ROOF TANKS**

Type of Limit	<u>Emission Limit</u> Citation of Limit	FE Y/N	Future Effective Date	<del>Emission</del> -Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Condition # 1253, part IIID	Y		1.44 pounds/1000 barrels	BAAQMD Condition # 1253, part IV, Section 3	C	Continuous Hydrocarbon monitor
NOx	BAAQMD Condition # 1253, part IB	Y		129.5 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
NOx	BAAQMD Condition # 1253, part IIID, schedule D	Y		9.68 lb/day plus 0.1744 pounds/1000 barrels	None	None	Source test
CO	BAAQMD Condition # 1253, part IB	Y		52.2 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
SO2	BAAQMD Condition # 1253, part IB	Y		83.5 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
<b>EPM</b>	BAAQMD Condition # 1253, part IB	Y		25.8 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - I**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-73 – DIRECT FIRED HEATER**

Type of Limit	<u>Emission Limit Citation of Limit</u>	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
Usage	BAAQMD Condition # 13720, part 1	Y		Natural gas < 90 M SCF/ 12 months	BAAQMD Condition # 13720, part 6	P/M	Flow meter
SO2	BAAQMD Regulation 9-1-301	Y		GLC > 0.5 ppm continuously for 3 consecutive minutes or 0.25 ppm averaged over 60 consecutive minutes or 0.05 ppm averaged over 24 hrs	None	N	
SO2	SIP BAAQMD Regulation 9-1-302	Y		≤ 300 ppm SO2, dry	None	N	
SO2	SIP BAAQMD Regulation 9-1-304	Y		≤ 0.5% by weight, fuel sulfur concentration	BAAQMD Condition # 13720, part 7	P/E	Sulfur certification or analysis
SO2	BAAQMD Condition # 1253, part IB	Y		83.5 tpy for all sources	BAAQMD Condition # 1253, part IIID	P/A	Records
SO2	BAAQMD Condition # 1253, part IIID, schedule D	Y		78.5 lb/1000 gal of fuel oil burned	BAAQMD Condition # 13720, part 7	P/E	Sulfur certification or analysis
NOx	BAAQMD Regulation 9-7-301.1	N		30 ppmv dry, @ 3% O2	None	N	

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - I**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-73 – DIRECT FIRED HEATER**

Type of Limit	Emission Limit Citation of Limit	FE Y/N	Future Effective Date	Emission-Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
NOx	BAAQMD Regulation 9-7-305.1	N		150 ppmv dry, @ 3% O2	None	N	
NOx	BAAQMD Regulation 9-7-306.1	N		150 ppmv dry, @ 3% CO2	BAAQMD Condition # 13720, part 5	P/A	Source test
NOx	BAAQMD Condition # 1253, part IB	Y		129.5 tpy for all sources	BAAQMD Condition # 1253, part IID	P/A	Records
NOx	BAAQMD Condition # 1253, part IID, schedule D	Y		55 lb/1000 gal of fuel oil burned	BAAQMD Condition # 1253, part IID	P/A	Records
NOx	BAAQMD Condition # 13720, Part 2	Y		20 ppmv @3% O2	BAAQMD Condition # 13720, part 5	P/A	Source test
NOx	BAAQMD Regulation 9-7-306.3	N		48 hours non-gaseous fuel testing	Regulation 9-7-503.3	P/M	Test records
CO	BAAQMD Regulation 9-7-301.2	N		400 ppmv dry, @ 3% CO2	BAAQMD Condition # 13720, part 5	P/A	Source test
CO	BAAQMD Regulation 9-7-305.2	N		400 ppmv dry, @ 3% CO2	None	N	
CO	BAAQMD Regulation 9-7-306.2	N		400 ppmv dry, @ 3% CO2	None	N	

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - I**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-73 – DIRECT FIRED HEATER**

Type of Limit	<u>Emission Limit Citation of Limit</u>	FE Y/N	Future Effective Date	<u>Emission-Limit</u>	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
CO	BAAQMD Regulation 9-7-306.3	N		48 hours non-gaseous fuel testing	Regulation 9-7-503.3	P/M	Test records
CO	BAAQMD Condition # 1253, part IB	Y		52.2 tpy for all sources	BAAQMD Condition # 1253, part IID	P/A	Records
CO	BAAQMD Condition # 13720, part 3	Y		50 ppmv @ 3 % O2	BAAQMD Condition # 13720, part 5	P/A	Source test
POC	BAAQMD Condition # 1253, part 1B	Y		<del>65.167.146</del> tpy for all sources	BAAQMD Condition # 1253, part IID	P/A	Records
POC	BAAQMD Condition # 1253, part IID, schedule D	Y		0.28 lb/1000 gal of fuel oil burned	BAAQMD Condition # 1253, part IID	P/A	Records
<del>FMP</del>	<u>BAAQMD 6-310.3</u>	<u>Y</u>		<u>Particulate Matter &lt; 343 mg per dscm (0.15 gr/dscf) @ 6% oxygen volume</u>	<u>None</u>	<u>N</u>	<u>N</u>
<del>EPM</del>	BAAQMD Condition # 1253, part IB	Y		25.8 tpy for all sources	BAAQMD Condition # 1253, part IID	P/A	Records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – J**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-74 AND S-75 EMERGENCY DIESEL GENERATORS**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
<u>FP</u>	<u>BAAQMD Regulation 6-303.1</u>	<u>Y</u>		<u>Ringelmann 2.0</u>	<u>BAAQMD Regulation 6-401</u>	<u>C</u>	<u>Visible Inspection</u>
<u>FP</u>	<u>BAAQMD Regulation 6-310.1</u>	<u>Y</u>		<u>0.15 gr/dscf</u>	<u>None</u>	<u>N</u>	<u>N/A</u>
<u>SO<sub>2</sub></u>	<u>BAAQMD Regulation 9-1-301</u>	<u>Y</u>		<u>Property Line Ground Level Limits: &lt; 0.5 ppm for 3 minutes and &lt; 0.25 ppm for 60 min. and &lt;0.05 ppm for 24 hours</u>	<u>None</u>	<u>N</u>	<u>N/A</u>
<u>SO<sub>2</sub></u>	<u>BAAQMD Regulation 9-1-304</u>	<u>Y</u>		<u>Fuel Sulfur Limit 0.5%</u>	<u>None</u>	<u>P/M</u>	<u>Vendor Certification</u>
<u>Operating time</u>	<u>BAAQMD Condition # 19308, Part 2</u>	<u>Y</u>		<u>100 hours per year</u>	<u>BAAQMD Condition # 19308, Part 4</u>	<u>P/D</u>	<u>Records</u>

**Table VII – K**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
<u>POC</u>	<u>BAAQMD 8-5-303.1</u>	<u>Y</u>		<u>PSV set within 10% of max pressure or 25.8 mmHg (0.5 psia)</u>	<u>BAAQMD 8-5-403 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 months interval</u>	<u>Inspection Certification</u>

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – K**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
<u>POC</u>	<u>BAAQMD 8-320.3.1</u>	<u>Y</u>		<u>Gasket cover &lt; 0.32 cm (1/8 in) gap</u>	<u>BAAQMD 8-5-402.3 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 months interval</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-320.3.2</u>	<u>Y</u>		<u>Inaccessible opening no visible gap</u>	<u>BAAQMD 8-5-402.3 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 months interval</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-320.4.2</u>	<u>Y</u>		<u>Solid sampling or gauging wells in closed position with cover, seal or lid &lt; 0.32 cm (1/8 in)</u>	<u>BAAQMD 8-5-402.3 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 months interval</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-320.4.3</u>	<u>Y</u>		<u>Solid sampling or gauging wells: Gap between well and roof shall be added to gaps measured &lt; 1.3 cm (1/2 in)</u>	<u>BAAQMD 8-5-402.3 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 months interval</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-320.5.2</u>	<u>Y</u>		<u>Slotted sampling or gauging wells in closed position with cover, seal or lid &lt; 1.3 cm (1/2 in)</u>	<u>BAAQMD 8-5-402.2 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 months interval</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-320.5.3</u>	<u>Y</u>		<u>Slotted sampling or gauging wells: Gap between well and roof shall be added to gaps measured &lt; 1.3 cm (1/2 in)</u>	<u>BAAQMD 8-5-402.2 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 months interval</u>	<u>Inspection</u> <u>Certification</u>

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – K**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
<u>POC</u>	<u>BAAQMD 8-5-320.6</u>	<u>Y</u>		<u>Emergency roof drain with slotted membrane fabric cover &gt; 90% opening area</u>	<u>BAAQMD 8-5-402 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 <del>mons</del>months interval</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-321.1</u>	<u>Y</u>		<u>No holes, tears or other openings in the primary seal fabric</u>	<u>BAAQMD 8-5-402.2 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 <del>mons</del>months interval</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-321.2</u>	<u>N</u>		<u>Primary seal metallic shoe or liquid mounted type</u>	<u>BAAQMD 8-5-402.1 &amp; 8-5-404</u>	<u>P/10 yr</u> <u>P/10 yr</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>SIP</u> <u>BAAQMD 8-5-321.2</u>	<u>Y</u>		<u>Primary seal metallic shoe</u>	<u>SIP</u> <u>BAAQMD 8-5-401.3 &amp; 8-5-404</u>	<u>P/5 yr</u> <u>P/10 yr</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-321.3</u>	<u>Y</u>		<u>Primary seal metallic shoe extends minimum 61 cm (24 in) for external floating and 18 in for internal Floating Roof tank above liquid surface</u>	<u>BAAQMD 8-5-401, 8-5-404</u>	<u>P/10 yr</u> <u>P/10 yr</u>	<u>Inspection</u> <u>Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-321.3.1</u>	<u>Y</u>		<u>Gap between shoe and tank shell is no greater than 46 cm (18 in)</u>	<u>BAAQMD 8-5-401, 8-5-404</u>	<u>P/10 yr</u> <u>P/10 yr</u>	<u>Inspection</u> <u>Certification</u>

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – K**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
<u>POC</u>	<u>BAAQMD 8-5-321.3.2</u>	<u>Y</u>		<u>For welded tanks, gap between tank shell and the primary seal &lt; 3.8 cm (1 1/2 in). No continuous gap &gt; 0.32 cm ((1/8 in) shall exceed 10% of circumference. The cumulative length of all seal gaps exceeding 1.3 cm (1/2 in) &lt; 10% of circumference and the cumulative length of all seal gaps exceeding 0.32 cm (1/8 in) &lt; 40% of circumference</u>	<u>BAAQMD 8-5-401, 8-5-404</u>	<u>P/10 yr P/10 yr</u>	<u>Inspection Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-322.1</u>	<u>Y</u>		<u>No holes, tears, or other openings</u>	<u>BAAQMD 8-5-402.2 &amp; 8-5-404</u>	<u>P/twice per year at 4 to 8 <del>mons</del>months interval</u>	<u>Inspection Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-322.2</u>	<u>Y</u>		<u>Secondary seal shall allow insertion up to 3.8 cm (1 ½ in) in width</u>	<u>BAAQMD 8-5-402, &amp; 8-5-404</u>	<u>P/10 yr P/10 yr</u>	<u>Inspection Certification</u>
<u>POC</u>	<u>BAAQMD 8-5-322.3</u>	<u>Y</u>		<u>Gap between tank shell and the secondary seal shall not exceed 1.3 cm (1/2 in)</u>	<u>BAAQMD 8-5-402, &amp; 8-5-404</u>	<u>P/10 yr P/10 yr</u>	<u>Inspection Certification</u>

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – K**  
**Applicable Limits and Compliance Monitoring Requirements**  
**S-76, S-77 AND S-78 - INTERNAL FLOATING ROOF TANKS**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
<u>POC</u>	<u>BAAQMD 8-5-328.1.1</u>	<u>N</u>		<u>Tank &gt; 75 m<sup>3</sup>, tank cleaning shall have liquid balancing with &lt; 0.5 psia</u>	<u>None</u>	<u>N</u>	<u>None</u>
<u>POC</u>	<u>BAAQMD 8-5-328.1.2</u>	<u>N</u>		<u>Tank &gt; 75 m<sup>3</sup>, Tank cleaning 90% control, POC concentration &lt; 10,000 ppm</u>	<u>BAAQMD 8-5-502</u>	<u>P/A</u>	<u>Source Test</u>
<u>POC</u>	<u>SIP BAAQMD 8-5-328.1</u>	<u>Y</u>		<u>Tank cleaning shall have liquid balancing with &lt; 0.5 psia</u>	<u>None</u>	<u>N</u>	<u>None</u>
<u>POC</u>	<u>SIP BAAQMD 8-5-328.1.2</u>	<u>Y</u>		<u>Tank cleaning 90% control, POC concentration &lt; 10,000 ppm</u>	<u>BAAQMD 8-5-404.3</u>	<u>P/A</u>	<u>Source Test</u>
<u>POC</u>	<u>Subpart Kb 40 CFR 60.113b (a)(2)</u>	<u>Y</u>		<u>No holes, tears or other openings</u>	<u>40 CFR 60.113b(a) (4)</u>	<u>P/A/ E(emptied and degassed)</u>	<u>Inspection</u>
<u>POC</u>	<u>BAAQMD Condition # 20060, part 1</u>	<u>Y</u>		<u>Gasoline or other hydrocarbon liquids throughput &lt; 105 million gal/yr for S-76, 77 and 78</u>	<u>BAAQMD Condition # 20060, part 6</u>	<u>P/M</u>	<u>Records</u>
<u>POC</u>	<u>BAAQMD Condition # 20060, part 2</u>	<u>Y</u>		<u>Gasoline or other hydrocarbon liquids throughput &lt; 4.2 million gal/day for S-76, 77 and 78</u>	<u>BAAQMD # 20060, part 6</u>	<u>P/M</u>	<u>Records</u>
<u>POC</u>	<u>BAAQMD Condition # 20060, part 4</u>	<u>Y</u>		<u>S-58 shall be abated by liquid mounted primary seal, and rim mounted secondary seal</u>	<u>BAAQMD 8-5-303</u>	<u>C</u>	<u>Install internal floating roof</u>

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - I**  
**Applicable Limits and Compliance Monitoring Requirements**  
**A-1- THERMAL OXIDIZER**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
SO <sub>2</sub>	BAAQMD Regulation 9-1-301	Y		GLC > 0.5 ppm continuously for 3 consecutive minutes or 0.25 ppm averaged over 60 consecutive minutes or 0.05 ppm averaged over 24 hrs	None	N	
SO <sub>2</sub>	SIP BAAQMD Regulation 9-1-302	Y		< 300 ppm SO <sub>2</sub> , dry	None	N	
SO <sub>2</sub>	BAAQMD Condition # 1253, part IB	Y		83.5 tpy for all sources	BAAQMD Condition # 1253, part IID	P/A	Records
NO <sub>x</sub>	BAAQMD Condition # 1253, part IB	Y		129.5 tpy for all sources	BAAQMD Condition # 1253, part IID	P/A	Records
CO	BAAQMD Condition # 1253, part IB	Y		52.2 tpy for all sources	BAAQMD Condition # 1253, part IID	P/A	Records
CO	BAAQMD Condition # 13720, part 3	Y		50 ppmv @ 3 % O <sub>2</sub>	BAAQMD Condition # 13720, part 5	P/A	Source test
POC	BAAQMD Condition # 1253, part IB	Y		67.146 tpy for all sources	BAAQMD Condition # 1253, part IID	P/A	Records
FP	BAAQMD 6-310.3	Y		Particulate Matter < 343 mg per dscm (0.15 gr/dscf)	None	N	N

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII - I**  
**Applicable Limits and Compliance Monitoring Requirements**  
**A-1- THERMAL OXIDIZER**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
FP	BAAQMD Condition # 1253, part 1B	Y		25.8 tpy for all sources	BAAQMD Condition # 1253, part 11D	P/A	Records

**Table VII - L**  
**Applicable Limits and Compliance Monitoring Requirements**  
**FACILITY**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
FP	BAAQMD Regulation 6-301	Y		Ringelmann 1 Limitation	BAAQMD Regulation 6-401	C	Visible Inspection
SO <sub>2</sub>	BAAQMD Regulation 9-1-301	Y		GLC > 0.5 ppm continuously for 3 consecutive minutes or 0.25 ppm averaged over 60 consecutive minutes or 0.05 ppm averaged over 24 hrs	None	N	Fuel Type
POC	BAAQMD Condition # 1253, part 1B	Y		67.146 tpy for all sources (except S-74 and S-75 Diesel IC Emergency Generator)	BAAQMD Condition # 1253, part 11D	P/A	Records
NO <sub>x</sub>	BAAQMD Condition # 1253, part 1B	Y		129.5 tpy for all sources (except S-74 and S-75 Diesel IC Emergency Generator)	BAAQMD Condition # 1253, part 11D	P/A	Records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – L**  
**Applicable Limits and Compliance Monitoring Requirements**  
**FACILITY**

<u>Type of Limit</u>	<u>Citation of Limit</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
<u>CO</u>	<u>BAAQMD Condition # 1253, part IB</u>	<u>Y</u>		<u>52.2 tpy for all sources (except S-74 and S-75 Diesel IC Emergency Generator)</u>	<u>BAAQMD Condition # 1253, part IIID</u>	<u>P/A</u>	<u>Records</u>
<u>SO2</u>	<u>BAAQMD Condition # 1253, part IB</u>	<u>Y</u>		<u>83.5 tpy for all sources (except S-74 and S-75 Diesel IC Emergency Generator)</u>	<u>BAAQMD Condition # 1253, part IIID</u>	<u>P/A</u>	<u>Records</u>
<u>FP</u>	<u>BAAQMD Condition # 1253, part IB</u>	<u>Y</u>		<u>25.8 tpy for all sources (except S-74 and S-75 Diesel IC Emergency Generator)</u>	<u>BAAQMD Condition # 1253, part IIID</u>	<u>P/A</u>	<u>Records</u>

**Table VII – J-M**  
**Applicable Limits and Compliance Monitoring Requirements**  
**COMPONENTS**

<u>Type of Limit</u>	<u>Emission Limit Citation</u>	<u>FE Y/N</u>	<u>Future Effective Date</u>	<u>Emission-Limit</u>	<u>Monitoring Requirement Citation</u>	<u>Monitoring Frequency (P/C/N)</u>	<u>Monitoring Type</u>
<u>POC</u>	<u>BAAQMD Regulation 8-18-301</u>	<u>Y</u>		<u>Equipment leaks <math>\leq</math> 100 ppm, except for valves, pumps, compressors, connections and pressure relief devices</u>	<u>BAAQMD Regulation 8-18-401</u>	<u>P/Q</u>	<u>Portable hydrocarbon detector, records</u>
<u>POC</u>	<u>BAAQMD Regulation 8-18-302</u>	<u>Y</u>		<u>Valves leaks <math>\leq</math> 100 ppm</u>	<u>BAAQMD Regulation 8-18-401</u>	<u>P/Q</u>	<u>Portable hydrocarbon detector, records</u>

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – J-M**  
**Applicable Limits and Compliance Monitoring Requirements**  
**COMPONENTS**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	<del>Emission</del> Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	BAAQMD Regulation 8-18-303	Y		Pump, compressor leaks $\leq$ 500 ppm	BAAQMD Regulation 8-18-401	P/Q	Portable hydrocarbon detector, records
POC	BAAQMD Regulation 8-18-304	Y		Connection leaks $\leq$ 100 ppm	BAAQMD Regulation 8-18-401	P/Q	Portable hydrocarbon detector, records
POC	BAAQMD Regulation 8-18-305	Y		Pressure relief valves $\leq$ 500 ppm	BAAQMD Regulation 8-18-401	P/Q	Portable hydrocarbon detector, records
POC	BAAQMD Regulation 8-18-306.1	Y		Non-repairable be replaced within 5 years or at next scheduled turnaround	None	N	
POC	BAAQMD Regulation 8-18-306.2	Y		Number awaiting repair $<$ 0.5% valves, 1% pressure relief valves, 1% pump and compressor	None	N	
POC	BAAQMD Regulation 8-18-306.3.2	Y		Valves $<$ 0.1 lb/day and number awaiting repair (NAR) $<$ 1.0%; Pressure relief valves $<$ 0.2 lb/day and (NAR) $<$ 5%; Pumps, compressors $<$ 0.2 lb/day and (NAR) $<$ 5%;	None	N	

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – ~~J~~M**  
**Applicable Limits and Compliance Monitoring Requirements**  
**COMPONENTS**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	<del>Emission</del> Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	SIP BAAQMD Regulation 8-18-301	Y		Until Jan. 1, 1993, valves and flanges $\leq$ 10,000 ppm, except for valves, pumps, compressors, connections and pressure relief devices	SIP BAAQMD Regulation 8-18-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-18-302	Y		Effective Jan. 1, 1993, valves $\leq$ 500 ppm; Effective Jan. 1, 1997, valves $\leq$ 100 ppm	SIP BAAQMD Regulation 8-18-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-18-303	Y		Effective Jan. 1, 1993, connectors $\leq$ 500 ppm; Effective Jan. 1, 1997, connectors $\leq$ 100 ppm	SIP BAAQMD Regulation 8-18-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-18-304	Y		Effective Jan. 1, 1993, non repairable valves $\leq$ 2%; Effective Jan. 1, 1995, non repairable valves $\leq$ 1 %; Effective Jan. 1, 1997, non repairable valves $\leq$ 0.5 %	SIP BAAQMD Regulation 8-18-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-18-305	Y		Effective Jan. 1, 1995 and until Jan. 1, 1997, valves $\leq$ 100 ppm for 4 consecutive quarters	SIP BAAQMD Regulation 8-18-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-18-306	Y		Effective Jan. 1, 1995 and until Jan. 1, 1997, repeat leakers $\leq$ 2 times in 12 months	SIP BAAQMD Regulation 8-18-401	P/Q	Portable hydrocarbon detector, records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – J-M**  
**Applicable Limits and Compliance Monitoring Requirements**  
**COMPONENTS**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	SIP BAAQMD Regulation 8-25-301	Y		Until Jan. 1, 1993, pump, compressor $\leq$ 10,000 ppm	SIP BAAQMD Regulation 8-25-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-25-302	Y		Effective Jan. 1, 1993, pumps $\leq$ 1000 ppm; Effective Jan. 1, 1997, pump $\leq$ 500 ppm	SIP BAAQMD Regulation 8-25-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-25-303	Y		Effective Jan. 1, 1993, compressors $\leq$ 1000 ppm; Effective Jan. 1, 1997, compressors $\leq$ 500 ppm	SIP BAAQMD Regulation 8-25-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-25-304.1	Y		Pumps and compressors repair or replaced within 5 years or at the next scheduled turnaround	SIP BAAQMD Regulation 8-25-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-25-304.2	Y		Effective Jan. 1, 1993, non repairable pumps and compressors $\leq$ 10%; Effective Jan. 1, 1997, non repairable pumps and compressors $\leq$ 1 %	SIP BAAQMD Regulation 8-25-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-18-305	Y		Effective Jan. 1, 1995, new replaced pumps and compressor $\leq$ 500 ppm for 4 consecutive quarters	SIP BAAQMD Regulation 8-25-401	P/Q	Portable hydrocarbon detector, records
POC	SIP BAAQMD Regulation 8-25-306	Y		Effective Jan. 1, 1993, repeat leakers $\leq$ 2 times in 12 months	SIP BAAQMD Regulation 8-25-401	P/Q	Portable hydrocarbon detector, records

## VII. Applicable Limits and Compliance Monitoring Requirements

**Table VII – ~~J~~M**  
**Applicable Limits and Compliance Monitoring Requirements**  
**COMPONENTS**

Type of Limit	Emission Limit Citation	FE Y/N	Future Effective Date	<del>Emission</del> -Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
POC	Subpart R 40 CFR 63.424(a)	Y		Vapor tight	40 CFR 63.563(a)(4)	P/A	Leak test

## VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally referenced in Section 600 of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII, Applicable Emission Limits & Compliance Monitoring Requirements, of this permit.

**Table VIII**  
**Test Methods**

<b>Applicable Requirement</b>	<b>Description of Requirement</b>	<b>Acceptable Test Methods</b>
BAAQMD Regulation 6-301	Ringelmann No. 1 Limitation	Manual of Procedures, Volume I, Evaluation of Visible Emissions
<u>BAAQMD Regulation 6-303</u>	<u>Ringelmann No. 2 Limitation</u>	<u>Manual of Procedures, Volume I, Evaluation of Visible Emissions</u>
<u>BAAQMD Regulation 6-310, 6-310.3</u>	<u>0.15 gr/dscf</u>	<u>Manual of Procedures, Volume IV, ST 15, Particulate Sampling</u>
<u>BAAQMD Regulation 8-5-301</u>	<u>True Vapor Pressure</u>	<u>Manual of Procedures, Volume III, Lab Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks, if organic compound is not listed in Table I</u>
<u>BAAQMD Regulation 8-5-303.2</u>	<u>Pressure vacuum leak concentration</u>	<u>EPA reference method 21 (40 CFR 60, Appendix A), Determination of Volatile Organic Compound Leaks</u>
<u>BAAQMD Regulation 8-5-306</u>	<u>VOC emissions</u>	<u>Manual of Procedures, Volume IV, ST-4, Bulk Gasoline Distribution Facility</u>
<u>BAAQMD Regulation 8-5-328.1.2</u>	<u>VOC emissions for tank cleaning</u>	<u>Manual of Procedures, Volume IV, ST-7, Non-Methane Organic Carbon Sampling</u>
SIP BAAQMD Regulation 8-5-304	True Vapor Pressure	Manual of Procedures, Volume III, Lab Method 28, Determination of Vapor Pressure of Organic Liquids from Storage Tanks, if organic compound is not listed in Table I

## VIII. Test Methods

**Table VIII**  
**Test Methods**

<b>Applicable Requirement</b>	<b>Description of Requirement</b>	<b>Acceptable Test Methods</b>
<u>SIP</u> BAAQMD Regulation 8-5-311.3	VOC emissions	Manual of Procedures, Volume IV, ST-34, Bulk Gasoline <del>Distribution Facilities Edwards Refrigeration Unit or Carbon Adsorption Unit</del> <u>Distributing Facilities</u>
<u>SIP</u> <u>BAAQMD</u> <u>Regulation</u> <u>8-5-320.3</u>	<u>Pressure vacuum leak concentration</u>	<u>EPA reference method 21 (40 CFR 60, Appendix A), Determination of Volatile Organic Compound Leaks</u>
<u>SIP</u> BAAQMD Regulation 8-5-328.2	VOC emissions for tank cleaning	Manual of Procedures, Volume IV, ST-7, Non-Methane Organic Carbon Sampling
<del>BAAQMD</del> <del>Regulation</del> <del>8-5-320.3</del>	<del>Pressure vacuum leak concentration</del>	<del>EPA reference method 21 (40 CFR 60, Appendix A), Determination of Volatile Organic Compound Leaks</del>
SIP BAAQMD Regulation 8-25-301, 8-25-302, 8-25-303	Leak inspection procedures	EPA reference method 21 (40 CFR 60, Appendix A), Determination of Volatile Organic Compound Leaks
BAAQMD Regulation 8-33-203	Analysis of samples	Manual of Procedures, Volume III, Method 13, Determination of the Reid Vapor Pressure of Petroleum Products
BAAQMD Regulation 8-33-301	Emission rate determination	Manual of Procedures, Volume IV, ST-3, <del>Bulk Gasoline Distribution Facility</del> 34, <del>Bulk Gasoline Distribution Facilities Edwards Refrigeration Unit or Carbon Adsorption Unit</del>
BAAQMD Regulation 8-33-305	Vapor tight – delivery vehicles	Manual of Procedures, Volume IV, ST-33, Ethanol, Integrated Sampling
BAAQMD Regulation 8-33-309	Vapor recovery system – loading racks	Manual of Procedures, Volume IV, ST-34, Bulk Gasoline Distribution Facilities Edwards Refrigeration Unit or Carbon Adsorption Unit

## VIII. Test Methods

**Table VIII**  
**Test Methods**

<b>Applicable Requirement</b>	<b>Description of Requirement</b>	<b>Acceptable Test Methods</b>
BAAQMD Regulation 8-44-301.1	Determination of emissions	Manual of Procedures, Volume IV, ST-34, Bulk Gasoline Distribution Facilities Edwards Refrigeration Unit or Carbon Adsorption Unit
BAAQMD Regulation 8-44-301.2	Efficiency and mass emission determination	Manual of Procedures, Volume IV, ST-34, Bulk Gasoline Distribution Facilities Edwards Refrigeration Unit or Carbon Adsorption Unit
BAAQMD Regulation 8-44-303	Leak test and gas tight determination	EPA reference method 21, Determination of Volatile Organic Compound Leaks
BAAQMD Regulation 9-1-301	Ground level concentration	Manual of Procedures, Volume VI, Section 1 - Ground level monitoring for hydrogen sulfide and sulfur dioxide
BAAQMD Regulation 9-1-302	General emission limitation	Manual of Procedures, Volume IV, ST-19 A or B - Sulfur dioxide continuous sampling or sulfur oxides, integrated sampling
BAAQMD Regulation 9-1-303	Emissions from ships	Manual of Procedures, Volume III, Lab 10 – Determination of Sulfur in fuel oil
<a href="#"><u>BAAQMD 9-1-304</u></a>	<a href="#"><u>Fuel Sulfur Content</u></a>	<a href="#"><u>Manual of Procedures, Volume III, Method 10, Determination of Sulfur in Fuel Oil</u></a>
BAAQMD Regulation 9-7-301	Emission Limits –Gaseous fuel	Manual of Procedures, Volume IV, ST-13 A or B –Oxides of nitrogen, continuous sampling or oxides of nitrogen, integrated sampling; Volume IV, ST-6 – Carbon monoxides, continuous sampling and ST-14 – Oxygen, continuous sampling
BAAQMD Regulation 9-7-305	Natural Gas Curtailment – Non Gaseous Fuel	Manual of Procedures, Volume IV, ST-13 A or B –Oxides of nitrogen, continuous sampling or oxides of nitrogen, integrated sampling; Volume IV, ST-6 – Carbon monoxides, continuous sampling and ST-14 – Oxygen, continuous sampling
BAAQMD Regulation 9-7-306.1	Equipment testing – Non Gaseous Fuel NOx Performance Standard	Manual of Procedures, Volume IV, ST-13A, Oxides of Nitrogen, Continuous Sampling or ST-13B, Oxides of Nitrogen, Iterated Sample and ST-14, Oxygen, Continuous Sampling
BAAQMD Regulation 9-7-306.2	Equipment testing – Non Gaseous Fuel CO Performance Standard	Manual of Procedures, Volume IV, ST-6, Carbon Monoxides Continuous Sampling and ST-14, Oxygen, Continuous Sampling

## VIII. Test Methods

**Table VIII**  
**Test Methods**

<b>Applicable Requirement</b>	<b>Description of Requirement</b>	<b>Acceptable Test Methods</b>
Subpart Kb 40 CFR 60.112(b)	Vapor Pressure	ASTM Method D2879-83
Subpart Kb 40 CFR 60.112(b)(a) (3)	Visual inspection	60 Subpart VV, 60.485(b)
Subpart XX 40 CFR 60.502(b)(c), 6-.502(h)	Monitor for leakage	EPA reference method 21, Determination of Volatile Organic Compound Leaks
Subpart XX 40 CFR 60.502(h)	Delivery tank pressure	EPA reference method 27, Determination of vapor tightness of gasoline delivery tanks using pressures vacuum test
Subpart R 40 CFR 63.422(b), or 60.112(a)(3) (ii)	Emission standard	40 CFR 60.503
Subpart R 40 CFR 63.422(c)(1), 63.422(2)	Annual certificate test for cargo tank (internal vapor valve)	Method 27, Determination of vapor tightness of gasoline delivery tanks using pressures vacuum test; and Subpart R, 63.425(e)(1), (2)
Subpart R 40 CFR 63.422(c)(1), 63.422(2)(ii)	Leak detection test	Method 21, Determination of Volatile Organic Compound Leaks; and Subpart R, 63.425(f)(1), (2)
Subpart R 40 CFR 63.422(c)(1), 63.422(2)(ii)	Nitrogen pressure decay test	Subpart R, 63.425(g)(1), (2), (3), (4), (5)
Subpart R 40 CFR 63.422(c)(1), 63.422(2)(ii)	Continues performance pressure decay test	Method 27, Determination of vapor tightness of gasoline delivery tanks using pressures vacuum test, and Subpart R, 63.425(h)

## VIII. Test Methods

**Table VIII**  
**Test Methods**

<b>Applicable Requirement</b>	<b>Description of Requirement</b>	<b>Acceptable Test Methods</b>
Subpart Y 40 CFR 63.563(a)(3)	Pressure/vacuum settings of marine tank vessel's vapor system	Subpart Y, 63.565(b)(1),(2),(3)
Subpart Y 40 CFR 63.562(b)(1) (iii)	Vapor tightness test	Subpart Y, 63.565(c)(1),(2)
Subpart Y 40 CFR 63.562(b)(2), 63.562(3), 63.562(4); and 63.562(c)(3), 63.562(4)	Combustion and recovery test	Subpart Y, 63.565(d)(1) through (10)

## IX. REVISION HISTORY

<u>Date</u>	<u>Action</u>	<u>Details</u>
<u>March 12, 2001</u>	<u>Title V Permit Issuance</u>	
<u>June , 2003</u>	<u>Minor Revision</u>	<p><u>The purpose of the revision is to correct:</u></p> <ul style="list-style-type: none"><li><u>- Table IIA - Permitted Sources to add two existing diesel emergency generators that lost their exemptions reviewed under District's Application # 4684, and three new gasoline internal floating roof tanks with 4.2 million gallons capacity each reviewed under District's Application # 5850</u></li><li><u>- Add Tables IV-J Table IV-K – Source Specific Applicable Requirements for generators and tanks</u></li><li><u>- Add Tables VII-J Table VII-K - Applicable Limits and Compliance Monitoring Requirements for generators and tanks</u></li><li><u>- Table VIII Test Methods to add the sulfur fuel test method</u></li><li><u>- Tables IV-A, B, C, D, H, and Tables VII-A, B, C, D, H that were associated with the amended Regulation 8-5 - Storage of Organic Liquids, which was adopted on 11/27/02</u></li><li><u>- Condition # 19308 was added for S-75 and S-76 Emergency Diesel Generators</u></li><li><u>- Condition # 20060 was added for S-77, S-78 and S-78 Internal Floating Roof Tanks</u></li><li><u>- Revise Condition # 1253 under Schedule A to change the total POC emissions for the whole facility from 65.1 tons per calendar year to 67.146 tons per calendar year.</u></li><li><u>- Deletion of Condition #9905 that was included in error</u></li><li><u>- Update the standards parts of the permit</u></li><li><u>- Move facility-wide requirements from source tables to "Facility" tables</u></li></ul>

## **IX.X. GLOSSARY**

### **ACT**

**Federal Clean Air Act**

### **BAAQMD**

Bay Area Air Quality Management District

### **BACT**

Best Available Control Technology

### **CAA**

The federal Clean Air Act

### **CAAQS**

California Ambient Air Quality Standards

### **CEQA**

California Environmental Quality Act

### **CFR**

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

### **CO**

Carbon Monoxide

### **Cumulative Increase**

The sum of permitted emissions from each new or modified source since a specified date pursuant to BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95). Used to determine whether threshold-based requirements are triggered.

### **District**

The Bay Area Air Quality Management District

### **EPA**

The federal Environmental Protection Agency.

### **Excluded**

Not subject to any District Regulations.

### **Federally Enforceable, FE**

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part 52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), and also including limitations and conditions contained in operating

## **IX. Glossary**

permits issued under an EPA-approved program that has been incorporated into the SIP.

### **FP**

Filterable Particulate as measured by BAAQMD Method ST-15, Particulate.

### **HAP**

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by both 40 CFR Part 63, and District Regulation 2, Rule 5.

### **Major Facility**

A facility with potential emissions of regulated air pollutants greater than or equal to 100 tons per year, greater than or equal to 10 tons per year of any single hazardous air pollutant, and/or greater than or equal to 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity as determined by the EPA administrator.

### **MFR**

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Act and implemented by District Regulation 2, Rule 6.

### **MOP**

The District's Manual of Procedures.

### **NAAQS**

National Ambient Air Quality Standards

### **NESHAPs**

National Emission Standards for Hazardous Air Pollutants. Contained in 40 CFR Part 61.

### **NMHC**

Non-methane Hydrocarbons

### **NO<sub>x</sub>**

Oxides of nitrogen.

### **NSPS**

Standards of Performance for New Stationary Sources. Federal standards for emissions from new stationary sources. Mandated by Title I, Section 111 of the Act, and implemented by both 40 CFR Part 60 and District Regulation 10.

### **NSR**

New Source Review. A federal program for pre-construction review and permitting of new and modified sources of air pollutants for which the District is classified "non-attainment". Mandated by Title I of the Clean Air Act and implemented by 40 CFR Parts 51 and 52 as well as District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

## **IX. Glossary**

### **Offset Requirement**

A New Source Review requirement to provide federally enforceable emission offsets at a specified ratio for the emissions from a new or modified source and any pre-existing cumulative increase minus any onsite contemporaneous emission reduction credits. Applies to emissions of POC, NO<sub>x</sub>, PM<sub>10</sub>, and SO<sub>2</sub>.

### **Phase II Acid Rain Facility**

A facility that generates electricity for sale through fossil-fuel combustion and by virtue of certain other characteristics (defined in Regulation 2, Rule 6) is subject to Titles IV and V of the Clean Air Act.

### **POC**

Precursor Organic Compounds

### **PM**

Total Particulate Matter

### **PM<sub>10</sub>**

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

### **PSD**

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

### **SIP**

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Air Ambient Quality Standards. Mandated by Title I of the Act.

### **SO<sub>2</sub>**

Sulfur dioxide

### **Title V**

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

### **TRMP**

**Toxic Risk Management Policy**

### **TSP**

Total Suspended Particulate

## IX. Glossary

### VOC

Volatile Organic Compounds

#### Units of Measure:

bhp	=	brake-horsepower
btu	=	British Thermal Unit
g	=	grams
gal	=	gallon
hp	=	horsepower
hr	=	hour
lb	=	pound
in	=	inches
max	=	maximum
m <sup>2</sup>	=	square meter
min	=	minute
<del>mm</del> MM	=	million
ppmv	=	parts per million, by volume
ppmw	=	parts per million, by weight
psia	=	pounds per square inch, absolute
psig	=	pounds per square inch, gauge
<u>dscf</u>	=	<u>dry standard cubic feet</u>
scfm	=	standard cubic feet per minute
yr	=	year

~~X~~X **APPLICABLE STATE IMPLEMENTATION PLAN**

The Bay Area Air Quality Management District's portion of the State Implementation Plan can be found at EPA Region 9's website. The address is:

<http://yosemite1.epa.gov/r9/r9sips.nsf/California?ReadForm&Start=1&Count=30&Expand=3.1>  
See Attachments