

FACILITY PERMIT TO OPERATE

**LAIRD COATINGS CORPORATION
15541 COMMERCE LN
HUNTINGTON BEACH, CA 92649**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By _____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	DRAFT	10/06/2015
B	RECLAIM Annual Emission Allocation	DRAFT	10/06/2015
C	Facility Plot Plan	TO BE DEVELOPED	
D	Facility Description and Equipment Specific Conditions	DRAFT	10/06/2015
E	Administrative Conditions	DRAFT	10/06/2015
F	RECLAIM Monitoring and Source Testing Requirements	DRAFT	10/06/2015
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	DRAFT	10/06/2015
H	Permit To Construct and Temporary Permit to Operate	DRAFT	10/06/2015
I	Compliance Plans & Schedules	DRAFT	10/06/2015
J	Air Toxics	DRAFT	10/06/2015
K	Title V Administration	DRAFT	10/06/2015
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	DRAFT	10/06/2015
B	Rule Emission Limits	DRAFT	10/06/2015

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR: LAIRD COATINGS CORPORATION

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION: 15541 COMMERCE LN
 HUNTINGTON BEACH, CA 92649-1601

MAILING ADDRESS: 15541 COMMERCE LN
 HUNTINGTON BEACH, CA 92649-1601

RESPONSIBLE OFFICIAL: ED LAIRD

TITLE: CEO

TELEPHONE NUMBER: (714) 894-5252

CONTACT PERSON: ED LAIRD

TITLE: PRESIDENT

TELEPHONE NUMBER: (714) 894-5252

TITLE V PERMIT ISSUED: October 14, 2010

TITLE V PERMIT EXPIRATION DATE: October 13, 2015

TITLE V	RECLAIM
YES	NOx: NO SOx: NO CYCLE: 0 ZONE: COASTAL

**FACILITY PERMIT TO OPERATE
LAIRD COATINGS CORPORATION**

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

NOT APPLICABLE

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Facility Equipment and Requirements (Section D)

This section consists of a table listing all permitted equipment at the facility, facility wide requirements, all individual Permits to Construct and Permits to Operate issued to various equipment at the facility, and Rule 219-exempt equipment subject to source-specific requirements. Each permit and Rule 219-exempt equipment will list operating conditions including periodic monitoring requirements, and applicable emission limits and requirements that the equipment is subject to. Also included is the rule origin and authority of each emission limit and permit condition.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMITTED EQUIPMENT LIST

THE FOLLOWING IS A LIST OF ALL PERMITS TO CONSTRUCT AND PERMITS TO OPERATE AT THIS FACILITY:

Application number	Permit to Operate number	Equipment description
232723	D33671	Misc Materials Blending
232724	D33672	Misc Materials Blending
232725	D33673	Misc Materials Blending
232726	D33674	Misc Materials Blending
232727	D33675	Misc Materials Blending
232730	D33664	Misc Materials Blending
232733	D33667	Misc Materials Blending
232734	D33668	Misc Materials Blending
232735	D33669	Misc Materials Blending
232736	D33670	Misc Materials Blending
337660	F43231	Storage Tank Paints
337661	F43232	Storage Tank Paints
337662	F43233	Storage Tank Paints
337664	F43234	Storage Tank Paints
337665	F43235	Storage Tank Paints
337666	F43236	Storage Tank Paints
337667	F43237	Storage Tank Paints
337668	F43238	Storage Tank Paints
337669	F43239	Storage Tank Paints
337670	F43240	Storage Tank Paints
337671	F43241	Storage Tank Paints
337672	F43242	Storage Tank Paints
339001	F48846	Paints Blending
339002	F48847	Paints Blending
339006	F48848	Paints Blending
339007	F48849	Paints Blending
339008	F48850	Solvent Reclaim Still
383709	F75770	Paints Blending
421338	F75774	Baghouse

Note: Equipment listed above that have no corresponding permits to operate number are issued permits to construct. The issuance or denial of their permits to operate is subject to engineering final review. Any other applications that are still being processed and have not been issued permits to construct or permits to operate will not be found in this title v permit.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

FACILITY WIDE CONDITION(S)

Condition(s):

1. Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - A. As dark or darker in shade as that designated No. 1 on the Ringlemann Chart, as published by the United States Bureau of Mines; or
 - B. Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.
[Rule 401]
2. The total amount of solvents that are processed in all mixers and mixing tanks at this facility shall not exceed 10,000 gallons in any one day. The operator shall keep adequate records to demonstrate compliance with this condition.
[Rule 1303(b)(2)-Offset]
3. The total amount of powders that are processed in all mixers and mixing tanks at this facility shall not exceed 10,000 gallons in any one day. The operator shall keep adequate records to demonstrate compliance with this condition.
[Rule 1303(b)(2)-Offset]
4. All records required by this permit shall be prepared in a format which is acceptable to the District, shall be retained at the facility for at least five years and shall be made available to any District representative upon request.
[Rule 109, 1303(b)(2)-Offset]
5. Safety Data Sheets for all materials used at this facility shall be kept current and made available to District personnel upon request.
[Rule 109, 1303(b)(2)-Offset]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33671
A/N 232723

Equipment Description:

Mixer #1, Serial # 27777521, 20 Horsepower, to be used with a tank of 500 gallon capacity or less.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual “Visible Emission Evaluation”, within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

- 1. Stack or emission point identification;
- 2. Description of any corrective actions taken to abate visible emissions;
- 3. Date and time visible emission was abated; and
- 4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

- 7. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33672
A/N 232724

Equipment Description:

Mixer #2, Serial # 775A-25-187, 25 Horsepower, to be used with a tank of 500 gallon capacity or less.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual “Visible Emission Evaluation”, within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

- 1. Stack or emission point identification;
- 2. Description of any corrective actions taken to abate visible emissions;
- 3. Date and time visible emission was abated; and
- 4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

- 7. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33673
A/N 232725

Equipment Description:

Mixer #3, Mooney, Serial # 9007409, 20 Horsepower, to be used with a tank of 500 gallon capacity or less.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

7. This equipment is subject to the applicable requirements of the following Rules and Regulation:
VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33674
A/N 232726

Equipment Description:

Mixer #4, Cowles, Model No. J25, Serial # LA231, 25 Horsepower, to be used with a tank of 500 gallon capacity or less.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual “Visible Emission Evaluation”, within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

- 1. Stack or emission point identification;
- 2. Description of any corrective actions taken to abate visible emissions;
- 3. Date and time visible emission was abated; and
- 4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

- 7. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33675
A/N 232727

Equipment Description:

MIXER #5, Myers, Model No. 775E-25, Serial # 639, 25 Horsepower, to be used with a tank of 500 gallon capacity or less.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual “Visible Emission Evaluation”, within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

- 1. Stack or emission point identification;
- 2. Description of any corrective actions taken to abate visible emissions;
- 3. Date and time visible emission was abated; and
- 4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

- 7. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33664
A/N 232730

Equipment Description:

Mixing Tank #1, 834 Gallon Capacity, 5'-4" Dia. x 5'-0" H., with a 7 ½ Horsepower Mixer.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual “Visible Emission Evaluation”, within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

7. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33667
A/N 232733

Equipment Description:

Mixing Tank #4, 1,250 Gallon Capacity, 4'-10" W. X 4'-10" L. X 6'-0" H., with a 25 Horsepower Mixer Driving Four Total mixers, of Which One Serves This Tank.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

7. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33668
A/N 232734

Equipment Description:

Mixing Tank #5, 1,250 Gallon Capacity, 4'-10" W. X 4'-10" L. X 6'-0" H., with a 25 Horsepower Mixer Driving Four Total Mixers, of Which One Serves This Tank.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

7. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33669
A/N 232735

Equipment Description:

Mixing Tank #6, 1,250 Gallon Capacity, 4'-10" W. X 4'-10" L. X 6'-0" H., with a 25 Horsepower Mixer Driving Four Total Mixers, of Which One Serves This Tank.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

7. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. D33670
A/N 232736

Equipment Description:

Mixing Tank #7, 1,250 Gallon Capacity, 4'-10" W. X 4'-10" L. X 6'-0" H., With a 25 Horsepower Mixer Driving Four Total Mixers, of Which One Serves This Tank.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. This equipment shall not be operated unless it is vented to an air pollution control system that is in full use and has been issued a written permit by the District when powders are used.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

4. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
5. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]
6. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

7. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F43231
A/N 337660**

Equipment Description:

Storage Tank No. 1, 2'-8" W. X 10'-1" L. X 5'-0" H., 1,000 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

VOC: Rule 109

VOC: Rule 1141.1

VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F43232
A/N 337661**

Equipment Description:

Storage Tank No. 2, 2'-8" W. X 10'-1" L. X 5'-0" H., 1,000 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

VOC: Rule 109

VOC: Rule 1141.1

VOC: RULE 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. F43233
A/N 337662

Equipment Description:

Storage Tank No. 3, 2'-8" W. X 10'-1" L. X 5'-0" H., 1,000 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

VOC: Rule 109

VOC: Rule 1141.1

VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F43234
A/N 337664**

Equipment Description:

Storage Tank No. 4, 2'-8" W. X 10'-1" L. X 5'-0" H., 1,000 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. F43235
A/N 337665

Equipment Description:

Storage Tank No. 5, 2'-8" W. X 10'-1" L. X 5'-0" H., 1,000 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

- VOC: Rule 109
- VOC: Rule 1141.1
- VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F43236
A/N 337666**

Equipment Description:

Storage Tank No. 6, 2'-8" W. X 10'-1" L. X 5'-0" H., 1,000 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

- VOC: Rule 109
- VOC: Rule 1141.1
- VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. F43237
A/N 337667

Equipment Description:

Storage Tank No. 7, 2'-8" W. X 10'-1" L. X 5'-0" H., 1,000 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

- VOC: Rule 109
- VOC: Rule 1141.1
- VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F43238
A/N 337668**

Equipment Description:

Storage Tank No. 8, 2'-8" W. X 10'-1" L. X 5'-0" H., 1,000 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

- VOC: Rule 109
- VOC: Rule 1141.1
- VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F43239
A/N 337669**

Equipment Description:

Storage Tank No. 9, 3'-10" W. X 6'-11" L. X 12'-9" H., 2,500 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

VOC: Rule 109

VOC: Rule 1141.1

VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F43240
A/N 337670**

Equipment Description:

Storage Tank No. 10, 3'-10" W. X 6'-11" L. X 12'-9" H., 2,500 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Regulations:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

VOC: Rule 109

VOC: Rule 1141.1

VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F43241
A/N 337671**

Equipment Description:

Storage Tank No. 11, 3'-10" W. X 6'-11" L. X 12'-9" H., 2,500 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

Emissions and Regulations:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:
- VOC: Rule 109
 - VOC: Rule 1141.1
 - VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F43242
A/N 337672**

Equipment Description:

Storage Tank No. 12, 3'-10" W. X 6'-11" L. X 12'-9" H., 2,500 Gallon Capacity, Fixed Roof.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. Safety Data Sheets for all raw materials used at this facility shall be kept current and be made available to District personnel upon request.
[Rule 1303(a)(1)-BACT]
6. The following facility maximum throughput limits apply:

Ethanol	35,000 gallons/year
Xylene	10,000 gallons/year
Naphtha VMP	50,000 gallons/year
Toluene	28,000 gallons/year
Clear Acrylic	45,000 gallons/year
MEK	80,000 gallons/year
Lactol Spirits	110,000 gallons/year

[Rule 1303(b)(2)-Offset]
7. This tank shall not be used for storing organic liquids having a vapor pressure of 0.5 PSI or greater under actual storage conditions unless a limit has been specified above. Solvent's that have a vapor pressure below 0.5 PSI at ambient temperature include: butyl cellosolve, mineral spirits, n-butanol, and n-butyl acetate. Acetone is exempt.
[Rule 1303(a)(1)-BACT]

Emissions and Regulations:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

VOC: Rule 109

VOC: Rule 1141.1

VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F48846
A/N 339001**

Equipment Description:

Mixing Tank #3, 2,000 Gallon Capacity, with a 60 HP Mixer.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. No more than 1,500 gallons of Volatile Organic Compounds of coating solvents shall be processed in this equipment in any one day.
[Rule 1303(b)(2)-Offset]
6. Records shall be maintained in accordance with Rule 1141.1(c) and made available for inspection by District personnel upon request.
[Rule 1303(b)(2)-Offset]

Periodic Monitoring:

7. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
8. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

9. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

10. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F48847
A/N 339002**

Equipment Description:

Mixing Tank # 4, 1,000 Gallon Capacity, with a 25 HP Mixer.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. No more than 1,500 gallons of Volatile Organic Compounds of coating solvents shall be processed in this equipment in any one day.
[Rule 1303(b)(2)-Offset]
6. Records shall be maintained in accordance with Rule 1141.1(c) and made available for inspection by District personnel upon request.
[Rule 1303(b)(2)-Offset]

Periodic Monitoring:

7. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
8. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

9. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

10. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit F48848
A/N 339006**

Equipment Description:

Mixing Tank #8, with a 25 HP Mixer, to be used with a 500 gallon capacity tank or less.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. No more than 1,500 gallons of Volatile Organic Compounds of coating solvents shall be processed in this equipment in any one day.
[Rule 1303(b)(2)-Offset]
6. Records shall be maintained in accordance with Rule 1141.1(c) and made available for inspection by District personnel upon request.
[Rule 1303(b)(2)-Offset]

Periodic Monitoring:

7. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
8. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

9. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

10. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F48849
A/N 339007**

Equipment Description:

Mixer #9, 20 H.P. Mixer, to be used with a 500 gallon capacity tank or less

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. No more than 1,500 gallons of Volatile Organic Compounds of coating solvents shall be processed in this equipment in any one day.
[Rule 1303(b)(2)-Offset]
6. Records shall be maintained in accordance with Rule 1141.1(c) and made available for inspection by District personnel upon request.
[Rule 1303(b)(2)-Offset]

Periodic Monitoring:

7. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]
8. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

9. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

10. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F48850
A/N 339008**

Equipment Description:

Solvent Reclaim Still, Disti-Kleen Incorporated, Model Disti Roto 2 Solvent Recovery System, 7'-0" W. X 14'-0" L. X 7'-0" H., 85 Gal/hour, 175 Gallon Capacity, 45.5 KW., Electric Heating, with a Water Cooled Heat Exchanger

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
4. A temperature indicator shall be installed and maintained to measure the vapor temperature at the inlet to the condenser. Heat to the Still shall be shut off automatically whenever the vapor temperature at the inlet to the condenser exceeds 550 degrees Fahrenheit.
[Rule 1303(a)(1)-BACT]
5. The condenser shall be operating at all times when the Still is in operation.
[Rule 1303(a)(1)-BACT]
6. Volatile Organic Compound materials usage shall comply with the requirements of Rule 442 (Usage of Solvents).
[Rule 442]

Periodic Monitoring:

7. In addition to the record keeping requirements in District Rule 109, the operator shall keep adequate records to demonstrate compliance with condition 3, and to verify daily usage, Volatile Organic Compound (VOC) content, and daily VOC emissions for each material used in this equipment. Such records shall be retained for a period of five years and be made available to the Executive Officer or his representative upon request.
[Rule 109; 1303(b)(2)-Offset; 3004(a)(4)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

Emissions and Requirements:

8. This equipment is subject to the applicable requirements of the following Rules and Regulations:

VOC: Rule 109

VOC: Rule 1171, See Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

Permit No. F75770
A/N 383709

Equipment Description:

Mixer #10, Serial #775A-10559, 5'-2" Dia. X 4'-4" H., 500 Gallon Capacity with One 10 HP Agitator.

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. Throughput records of organic liquids to this tank shall be maintained in accordance with Rule 1141.1 (C) and made available for inspection by District personnel upon request.
[Rule 1141.1]
4. Materials stored in this tank shall not contain any compounds identified in Rule 1401, as amended on June 1, 1990.
[Rule 1401]
5. No more than 1,500 gallons of Volatile Organic Compounds of coating solvents shall be processed in this equipment in any one day.
[Rule 1303(b)(2)-Offset]
6. This equipment shall be covered at all times except during loading and unloading.
[Rule 1303(a)(1)-BACT]
7. Materials used in this equipment shall not contain any compounds identified as carcinogenic air contaminants in Rule 1401, Table I, with an effective date of August 18, 2000 or earlier.
[Rule 1401]

Periodic Monitoring:

8. The operator shall perform semi-annual inspection of the equipment to ensure that the movable covers are closed. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. Name of the person performing the inspection of the cover.
 - B. Date, time, and result of the inspection.[Rule 3004(a)(4)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

9. The operator shall keep records, in a manner approved by the District, for the cleaning log that includes statement of the approved cleaning method.
[Rule 3004(a)(4)]

10. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one-hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- A. Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in section K of this permit; or
- B. Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB Manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in section K of this permit and the following records:

1. Stack or emission point identification;
2. Description of any corrective actions taken to abate visible emissions;
3. Date and time visible emission was abated; and
4. Visible emission observation recorded by a certified smoke reader.

[Rule 3004(a)(4)]

Emissions and Requirements:

11. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1141.1
VOC: Rule 1171, see Appendix B for emission limits
PM: Rule 405, see appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

PERMIT TO OPERATE

**Permit No. F75774
A/N 421338**

Equipment Description:

Portable Dust collecting System, consisting of:

1. Baghouse, Air King, Model M-35P with 8 Bag Filters, Each 2'-6" Dia. X 2'-0" L., Total Filter Area of 80 Sq. Ft.
2. Exhaust System with a 1 HP Motor Venting 7 Mixing Tanks and 8 Mixers

Conditions:

1. Operation of this equipment shall be conducted in compliance with all data and specifications submitted with the application under which this permit is issued unless otherwise noted below.
[Rule 204]
2. This equipment shall be properly maintained and kept in good operating condition at all times.
[Rule 204]
3. The operator shall clean the filter bag once a week.
[Rule 1303(a)(1)-BACT]
4. Dust collected in the baghouse shall be discharged only into closed containers.
[Rule 1303(a)(1)-BACT]
5. No more than one mixing tank or one mixer shall be vented to the baghouse at any one time.
[Rule 1303(a)(1)-BACT]

Periodic Monitoring:

6. The operator shall install and maintain a differential pressure gauge to accurately indicate the differential pressure across the bags. The operator shall determine and record the parameter being monitored once every week.
[Rule 3004 (a)(4)]
7. The operator shall perform an annual inspection of the equipment and filter media for leaks, broken or torn filter media and improperly installed filter media. The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - A. The name of the person performing the inspection and/or maintenance of the filter media;
 - B. The date, time and results of the inspection; and
 - C. The date, time and description of any maintenance or repairs resulting from the inspection.
[Rule 3004 (a)(4)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

8. The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in section k of this permit and the following records:

- A. Stack or emission point identification;
 - B. Description of any corrective actions taken to abate visible emissions; and
 - C. Date and time visible emission was abated.
- [RULE 3004 (a)(4)]

Emissions and Requirements:

9. This equipment is subject to the applicable requirements of the following Rules and Regulations:

Opacity:	0 percent, Rule 1155
PM:	Rule 1155
PM:	Rule 404, see appendix B for emission limits

**FACILITY PERMIT TO OPERATE
LAIRD COATINGS CORPORATION**

PERMIT TO CONSTRUCT

NONE

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

RULE 219 EQUIPMENT

Equipment Description:

Rule 219 Exempt Equipment, Coating Equipment, Portable, Architectural Coatings.

Periodic Monitoring:

The operator shall keep records, in a manner approved by the district, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records of all coatings consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coating.

For other architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coating.

[RULE 3004 (a) (4)]

Emissions and Requirements:

1. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 1113, see Appendix B for emission limits

VOC: Rule 1171, see Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

RULE 219 EQUIPMENT

Equipment Description:

Rule 219 Exempt Equipment, Hand Wiping Operations.

Emissions and Requirements:

1. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109

VOC: Rule 1171, see Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

RULE 219 EQUIPMENT

Equipment Description:

Rule 219 Exempt Equipment, Control Enclosure for Aerosol Can, Air Brush, or Hand Coating Operations, ≤ 27 Ft³ Internal Volume.

Emissions and Requirements:

1. This equipment is subject to the applicable requirements of the following Rules and Regulation:

VOC: Rule 109
VOC: Rule 1107, see Appendix B for emission limits
VOC: Rule 1136, see Appendix B for emission limits
VOC: Rule 1145, see Appendix B for emission limits
VOC: Rule 1171, see Appendix B for emission limits

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the SCAQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statutes of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION E: ADMINISTRATIVE CONDITIONS

5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to SCAQMD personnel upon request and be maintained for at least five years. [204]
7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by SCAQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]
 - d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO₂) and be averaged over 15 consecutive minutes; [407]
 - e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO₂) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION E: ADMINISTRATIVE CONDITIONS

- f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O₂) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]
8. The operator shall, when a source test is required by SCAQMD, provide a source test protocol to SCAQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by SCAQMD. The test protocol shall contain the following information: [204, 304]
 - a. Brief description of the equipment tested.
 - b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).
9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by SCAQMD rules or equipment-specific conditions. The report shall contain the following information: [204]
 - a. The results of the source test.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION E: ADMINISTRATIVE CONDITIONS

- b. Brief description of the equipment tested.
 - c. Operating conditions under which the test was performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Field and laboratory data forms, strip charts and analyses.
 - f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of SCAQMD Source Test Method 1.1 and 1.2. [217]
 11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, SCAQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, SCAQMD, 21865 Copley Drive, Diamond Bar, CA 91765-4178. [204]

**FACILITY PERMIT TO OPERATE
LAIRD COATINGS CORPORATION**

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
LAIRD COATINGS CORPORATION**

**SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR
RECLAIM SOURCES**

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
LAIRD COATINGS CORPORATION**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

See Section D of this permit for any Permit to Construct issued to this facility.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

**FACILITY PERMIT TO OPERATE
LAIRD COATINGS CORPORATION**

SECTION J: AIR TOXICS

NOT APPLICABLE

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
- (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
- (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration

9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]

10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]

12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]

13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration

14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
- (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 – Breakdown Provisions, or subdivision (i) of Rule 2004 – Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
- (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
- (A) Breakdowns shall be reported as required by Rule 430 – Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn:
Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1107	1-6-2006	Federally enforceable
RULE 1113	6-3-2011	Federally enforceable
RULE 1113	9-6-2013	Non federally enforceable
RULE 1136	6-14-1996	Federally enforceable
RULE 1141.1	11-17-2000	Federally enforceable
RULE 1145	12-4-2009	Non federally enforceable
RULE 1145	2-14-1997	Federally enforceable
RULE 1155	5-2-2014	Non federally enforceable
RULE 1171	2-1-2008	Federally enforceable
RULE 1171	5-1-2009	Non federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	12-7-1990	Non federally enforceable
RULE 1401	8-18-2000	Non federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	5-3-2013	Non federally enforceable
RULE 219	9-4-1981	Federally enforceable

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 3002	11-14-1997	Federally enforceable
RULE 3002	11-5-2010	Non federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	11-5-2010	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	11-5-2010	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	5-1-2015	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 701	6-13-1997	Federally enforceable

**FACILITY PERMIT TO OPERATE
LAIRD COATINGS CORPORATION**

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN
PERMIT PURSUANT TO RULE 219

NONE

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS								
Less Water and Less Exempt Compounds								
Effective Dates								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
General One-Component	275	275	2.3	2.3	275	275	2.3	2.3
General Multi-Component	340	340	2.8	2.8	275	275	2.3	2.3
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5
Solar-Absorbent	420	420	3.5	3.5	360	360	3.0	3.0
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0
Metallic	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

VOC LIMITS								
Less Water and Less Exempt Compounds								
Effective Dates, cont.								
Coating	Air-Dried				Baked			
	gm/l		lb/gal		gm/l		lb/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07
Extreme Performance	420	420	3.5	3.5	360	360	3.0	3.0
Prefabricated Architectural One-Component	420	275	3.5	2.3	275	275	2.3	2.3
Prefabricated Architectural Multi-Component	420	340	3.5	2.8	275	275	2.3	2.3
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0
Repair	420	420	3.5	3.5	360	360	3.0	3.0
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5
High-Performance Architectural	420	420	3.5	3.5	420	420	3.5	3.5
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5
Vacuum-Metalizing	420	420	3.5	3.5	420	420	3.5	3.5
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5
High-Temperature	420	420	3.5	3.5	420	420	3.5	3.5
Electric-Insulating Varnish	420	420	3.5	3.5	420	420	3.5	3.5
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5
Pretreatment Coatings	420	420	3.5	3.5	420	420	3.5	3.5

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

- (2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, no person shall supply, sell, offer for sale, market, manufacture, blend, repackage, apply, store at a worksite, or solicit the application of any architectural coating within the District:
 - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
 - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

TABLE OF STANDARDS 1 VOC LIMITS

**Grams of VOC Per Liter of Coating,
Less Water and Less Exempt Compounds**

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges ³		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	
Decorative Coatings		350			100
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers	340	100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters	200	100			
Reactive Penetrating Sealers		350			
Recycled Coatings		250			
Roof Coatings	250	50			
Roof Coatings, Aluminum		100			

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

Roof Primers, Bituminous	350	350		
Rust Preventative Coatings	400	100		
Stone Consolidant		450		
Sacrificial Anti-Graffiti Coatings		100		50
Shellac				
Clear		730		
Pigmented		550		
Specialty Primers	350	100		
Stains		100		

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 06-03-2011]

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Stains, Interior	250	250			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers	250	100			
Waterproofing Concrete/Masonry Sealers	400	100			
Wood Preservatives		350			

1. The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
2. The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
3. Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

TABLE OF STANDARDS 1 (cont.) VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

TABLE OF STANDARDS 2 VOC LIMITS FOR COLORANTS

Grams of VOC Per Liter of Colorant Less Water and Less Exempt Compounds

COLORANT	Limit ⁴
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 09-06-2013]

- (1) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, market, manufacture, blend, repack, apply, store at a worksite, or solid the application of any architectural coating within in the District:
 - (A) That is listed in the Table of Standards 1 and contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified; or
 - (B) That is not listed in the Table of Standards 1, and contains VOC (excluding any colorant added to tint bases) in excess of 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, until January 1, 2014, at which time the limit drops to 50 grams of VOC per liter of coating, less water, less exempt compounds (0.42 pounds per gallon).
- (2) No person within the District shall add colorant at the point of sale that is listed in the Table of Standards 2 and contains VOC in excess of the corresponding VOC limit specified in the Table of Standards 2, after the effective date specified.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 09-06-2013] TABLE OF STANDARDS 1 VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Bond Breakers		350			
Clear Wood Finishes		275			
Varnish	350	275			
Sanding Sealers	350	275			
Lacquer		275			
Concrete-Curing Compounds		100			
Concrete-Curing Compounds For Roadways and Bridges ³		350			
Concrete Surface Retarder		250			50
Driveway Sealer		100		50	
Dry-Fog Coatings		150			50
Faux Finishing Coatings					
Clear Topcoat		350		200	100
Decorative Coatings		350			
Glazes		350			
Japan		350			
Trowel Applied Coatings		350		150	50
Fire-Proofing Coatings		350			150
Flats	250	50	50		
Floor Coatings	100	50			
Form Release Compound		250			100
Graphic Arts (Sign) Coatings		500			150
Industrial Maintenance (IM) Coatings	420	100			
High Temperature IM Coatings		420			
Non-Sacrificial/Anti-Graffiti Coatings		100			
Zinc-Rich IM Primers		100			
Magnesite Cement Coatings		450			
Mastic Coatings		300			100
Metallic Pigmented Coatings	500	500			150
Multi-Color Coatings		250			
Nonflat Coatings	150	50			
Pre-Treatment Wash Primers		420			
Primers, Sealers, and Undercoaters		100			
Reactive Penetrating Sealers		350			

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 09-06-2013]

Recycled Coatings		250			
Roof Coatings		50			
Roof Coatings, Aluminum		100			
Roof Primers, Bituminous		350			
Rust Preventative Coatings	400	100			
Sacrificial Anti-Graffiti Coatings		100		50	
Shellac					
Clear		730			

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 09-06-2013]

COATING CATEGORY	Ceiling Limit ¹	Current Limit ²	Effective Date		
			7/1/08	1/1/12	1/1/14
Pigmented		550			
Specialty Primers		100			
Stains	350	100			
Stains, Interior	250	250			
Stone Consolidant		450			
Swimming Pool Coatings					
Repair		340			
Other		340			
Traffic Coatings		100			
Waterproofing Sealers		100			
Waterproofing Concrete/Masonry Sealers		100			
Wood Preservatives		350			

- 1 The specified ceiling limits are applicable to products sold under the Averaging Compliance Option.
- 2 The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.
- 3 Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

TABLE OF STANDARDS 1 (cont.) VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

TABLE OF STANDARDS 2 VOC LIMITS FOR COLORANTS

Grams of VOC Per Liter of Colorant Less Water and Less Exempt Compounds

COLORANT ADDED TO	Limit ⁴
Architectural Coatings, excluding IM Coatings	50
Solvent-Based IM	600
Waterborne IM	50

4. Effective January 1, 2014.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1136 06-14-1996]

Except as otherwise provided in Rule 1136

- (a) The operator shall not apply any coating to a wood product which has a VOC content, including any VOC-containing material added to the original coating supplied by the manufacturer, which exceeds the applicable limit specified below:

(1)

VOC LIMITS

Grams Per Liter (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

<u>COATING</u>	<u>Current Limit</u>		<u>On and After 7/1/2005</u>
	I	or	
	II		
Clear Sealers	550 (4.6) [1.39]	680 (5.7) [3.36]	275 (2.3) [0.36]
Clear Topcoat	550 (4.6) [1.37]	275 (2.3) [0.35]	275 (2.3) [0.35]
Pigmented Primers, Sealers & Undercoats	550 (4.6) [1.06]	600 (5.0) [1.08]	275 (2.3) [0.21]
Pigmented Topcoats	550 (4.6) [1.10]	275 (2.3) [0.25]	275 (2.3) [0.25]

The operator shall use coatings on a wood product that comply with either all VOC limits in column I or all VOC limits in column II. The operator that applies a primer, sealer or undercoat, but not a topcoat, to a wood product, shall be subject to column I for that wood product.

- (2) Notwithstanding the requirements of clause (a)(1), an operator that applies a topcoat and a primer, sealer or undercoat to a shutter may, until July 1, 2005, choose to comply with the VOC limits specified below for that shutter:

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1136 06-14-1996]

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

COATING

Clear Sealers	275 (2.3) [0.36]
Clear Topcoat	680 (5.7) [2.99]
Pigmented Primers, Sealers & Undercoats	275 (2.3) [0.33]
Pigmented Topcoats	600 (5.0) [1.38]

(3)

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

<u>COATING</u>	<u>Current Limit</u>	<u>On and After 7/1/2005</u>
Barrier Coat - Plastic Components	760 (6.3) [3.9]	275 (2.3) [0.28]
Composite Wood Edge Filler	550 (4.6) [1.15]	275 (2.3) [0.31]
Extreme Performance Coatings	420 (3.5) [0.51]	275 (2.3) [0.33]
Fillers	500 (4.2) [0.66]	275 (2.3) [0.18]
High-Solid Stains	550 (4.6) [1.23]	350 (2.9) [0.42]
Inks	500 (4.2) [0.96]	500 (4.2) [0.96]
Mold-Seal Coatings	750 (6.3) [4.2]	750 (6.3) [4.2]
Multi-Colored Coatings	685 (5.7) [2.6]	275 (2.3) [0.33]

VOC LIMITS

Grams Per Liter (lb/gal) of Material

<u>COATING</u>	<u>Current Limit</u>	<u>On and After 7/1/2005</u>
Low-Solids Barrier Coat - Plastic Components	760 (6.3)	120 (1.0)
Low-Solid Stains, Toners, and Washcoats	480 (4.0)	120 (1.0)

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1136 06-14-1996]

Any coating subject to this rule that meets any of the three VOC limit formats (grams per liter, lb/gal, or lbs VOC/lb of solids) is in compliance with this subparagraph.

- (4) The VOC limit for japan coatings is 700 grams per liter of coatings, less water and exempt compounds, as applied.
- (b) A person shall not use a stripper on wood products unless:
- (1) it contains less than 350 grams of VOC per liter of material; or
 - (2) the VOC composite vapor pressure is 2 mm Hg (0.04 psia) or less at 20°C (68°F).

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1145 12-04-2009]

Except as otherwise provided in Rule 1145, no person shall apply on plastics, rubber, leather, or glass any coatings which are applied with a VOC content in excess of the limits listed in the Table of Standards.

TABLE OF STANDARDS

VOC LIMITS		
LESS WATER AND LESS EXEMPT COMPOUNDS		
COATING CATEGORIES	g/L	lbs/gal
Electrical dissipating and shock free coatings	360	3.0
Extreme performance two-component coatings	420	3.5
General one-component coatings	120	1.0
General two-component coatings	120	1.0
Leather antique coatings	156	1.3
Leather color coatings	60	0.5
Leather sealer coatings	60	0.5
Leather stain coatings	216	1.8
Leather top coatings	120	1.0
Metallic coatings	420	3.5
Military specification one-component coatings	340	2.8
Military specification two-component coatings	420	3.5
Mirror backing curtain coated coatings	500	4.2
Mirror backing rolled coated coatings	312	2.6
Mold seal coatings	750	6.3
Multi-color coatings	680	5.7
Refrigerated glass door coatings	480	4.0
Optical coatings	50	0.4
Vacuum metalizing coatings	800	6.7

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1145 02-14-1997]

Except as otherwise provided in Rule 1145, the operator shall not apply on plastics, glass, or rubber any coatings which are applied with a VOC content in excess of the limits specified below:

COATING

	VOC LIMITS			
	<u>Less Water and Less Exempt</u>			
	<u>Compounds</u>			
	<u>Current</u>		<u>On and After 1-1-98</u>	
	<u>g/L</u>	<u>lbs/gal</u>	<u>g/L</u>	<u>lbs/gal</u>
General Coatings				
One-component	275	2.3	275	2.3
Two-component	420	3.5	420	3.5
Military Spec. Coating				
One-component	340	2.8	340	2.8
Two-component	420	3.5	420	3.5
Multi-Colored Coatings	685	5.7	685	5.7
Mold Seal Coatings	750	6.3	750	6.3
Vacuum Metalizing Coatings	800	6.7	800	6.7
Mirror Backing				
Curtain Coated	500	4.2	500	4.2
Roll Coated	430	3.6	430	3.6
Optical Coatings	800	6.7	800	6.7
Electric Dissipating Coatings and Shock-				
Free Coatings	800	6.7	360	3.0
Metallic Coatings	420	3.5	420	3.5

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)		

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals			
(A) Tools, Equipment, & Machinery	800 (6.7)		
(B) General Work Surfaces	600 (5.0)		
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)		
(D) Cleaning of Ink Application Equipment			
(i) General	25 (0.21)		
(ii) Flexographic Printing	25 (0.21)		
(iii) Gravure Printing			
(A) Publication	100 (0.83)		
(B) Packaging	25 (0.21)		
(iv) Lithographic (Offset) or Letter Press Printing			
(A) Roller Wash, Blanket Wash, & On-Press Components			
(I) Newsprint	100 (0.83)		

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 02-01-2008]

	CURRENT LIMITS*	EFFECTIVE 1/1/2008*	EFFECTIVE 1/1/2009
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(II) Other Substrates	500 (4.2)	100 (0.83)	
(B) Removable Press Components	25 (0.21)		
(v) Screen Printing	500 (4.2)	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)		
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)		

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)	
(B) Repair and Maintenance Cleaning		
(i) General	25 (0.21)	
(ii) Electrical Apparatus Components & Electronic Components	100 (0.83)	

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals		
(A) Tools, Equipment, & Machinery	800 (6.7)	
(B) General Work Surfaces	600 (5.0)	
(C) Cleaning of Coatings or Adhesives Application Equipment	25 (0.21)	
(D) Cleaning of Ink Application Equipment		
(i) General	25 (0.21)	
(ii) Flexographic Printing	25 (0.21)	
(iii) Gravure Printing		
(A) Publication	100 (0.83)	
(B) Packaging	25 (0.21)	
(iv) Lithographic (Offset) or Letter Press Printing		
(A) Roller Wash, Blanket Wash, & On-Press Components	100 (0.83)	

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-01-2009]

	CURRENT LIMITS*	EFFECTIVE 1/1/2010
SOLVENT CLEANING ACTIVITY (cont.)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(B) Removable Press Components	25 (0.21)	
(v) Screen Printing	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	650 (5.4)	100 (0.83)
(vii) Specialty Flexographic Printing	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)	

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
25 or less	883 or less	450	0.196	900	31780	118	0.0515
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter” Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
		Milligrams per Cubic Meter	Grains per Cubic Foot			Milligrams per Cubic Meter	Grains per Cubic Foot
Cubic meters Per Minute	Cubic feet Per Minute			Cubic meters Per Minute	Cubic feet Per Minute		
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
		Kilograms Per Hour	Pounds Per Hour			Kilograms Per Hour	Pounds Per Hour
100 or less	220 or less	0.450	0.99	9000	19840	5.308	11.7
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1.063	2.34	25000	55120	6.743	14.9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	7.296	16.1
600	1323	1.340	2.95	40000	88180	7.527	16.6

FACILITY PERMIT TO OPERATE LAIRD COATINGS CORPORATION

APPENDIX B: RULE EMISSION LIMITS [RULE 405 02-07-1986]

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour	Kilograms Per Hour	Pounds Per Hour
700	1543	1.461	3.22	45000	99210	7.738	17.1
800	1764	1.573	3.47	50000	110200	7.931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9
1250	2756	2.003	4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2.392	5.27	100000	220500	9.329	20.6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6.00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25.5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13.60	30.0