

FACILITY PERMIT TO OPERATE

**HOOD MFG INC
2621 S BIRCH ST
SANTA ANA, CA 92707**

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env.
EXECUTIVE OFFICER

By _____
Mohsen Nazemi, P.E.
Deputy Executive Officer
Engineering & Compliance

FACILITY PERMIT TO OPERATE HOOD MFG INC

TABLE OF CONTENTS

| Section | Description | Revision # | Date Issued |
|----------|---|-----------------|-------------|
| A | Facility Information | DRAFT | 07/11/2009 |
| B | RECLAIM Annual Emission Allocation | DRAFT | 07/11/2009 |
| C | Facility Plot Plan | TO BE DEVELOPED | |
| D | Facility Description and Equipment Specific Conditions | DRAFT | 07/11/2009 |
| E | Administrative Conditions | DRAFT | 07/11/2009 |
| F | RECLAIM Monitoring and Source Testing Requirements | DRAFT | 07/11/2009 |
| G | Recordkeeping and Reporting Requirements for RECLAIM Sources | DRAFT | 07/11/2009 |
| H | Permit To Construct and Temporary Permit to Operate | DRAFT | 07/11/2009 |
| I | Compliance Plans & Schedules | DRAFT | 07/11/2009 |
| J | Air Toxics | DRAFT | 07/11/2009 |
| K | Title V Administration | DRAFT | 07/11/2009 |
| Appendix | | | |
| A | NO _x and SO _x Emitting Equipment Exempt From Written Permit Pursuant to Rule 219 | DRAFT | 07/11/2009 |
| B | Rule Emission Limits | DRAFT | 07/11/2009 |

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR: HOOD MFG INC

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION: 2621 S BIRCH ST
SANTA ANA, CA 92707-3410

MAILING ADDRESS: 2621 S BIRCH ST
SANTA ANA, CA 92707-3410

RESPONSIBLE OFFICIAL: MICHAEL HOOD

TITLE: PRESIDENT

TELEPHONE NUMBER: (714) 979-7681

CONTACT PERSON: MICHAEL HOOD

TITLE: PRESIDENT

TELEPHONE NUMBER: (714) 979-7681

TITLE V PERMIT ISSUED: October 06, 2004

TITLE V PERMIT EXPIRATION DATE: October 05, 2009

| TITLE V | RECLAIM |
|---------|---|
| YES | NOx: NO SOx: NO CYCLE: 0 ZONE: COASTAL |

**FACILITY PERMIT TO OPERATE
HOOD MFG INC**

SECTION B: RECLAIM Annual Emission Allocation

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
HOOD MFG INC**

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|------------|
| Process 1 : Manufacturing Polyester Parts Line | | | | | |
| FOAM EXPANSION, POLYURETHANE FOAM DISPENSING UNIT WITH A/N: 253884 | D1 | | | VOC: (9) [RULE 1175,5-13-1994;RULE 1175,9-7-2007] | |
| TANK, PART A, POLYURETHANE FOAM | D2 | | | | |
| TANK, PART B, POLYURETHANE FOAM | D3 | | | | |
| Process 2 : Storage tanks | | | | | |
| STORAGE TANK, UNHEATED, NO.1, POLYESTER RESIN, 429 GALS; DIAMETER: 3 FT 9 IN; HEIGHT: 5 FT A/N: 03784A | D4 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; VOC: (9) [RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7- 2003 RULE 1171,2-4-2008] | H23.3 |
| STORAGE TANK, UNHEATED, NO.2, POLYESTER RESIN, 429 GALS; DIAMETER: 3 FT 9 IN; HEIGHT: 5 FT A/N: 04547A | D5 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; VOC: (9) [RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7- 2003 RULE 1171,2-4-2008] | H23.3 |
| STORAGE TANK, UNHEATED, NO.3, POLYESTER RESIN, 429 GALS; DIAMETER: 3 FT 9 IN; HEIGHT: 5 FT A/N: 04548A | D6 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; VOC: (9) [RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7- 2003 RULE 1171,2-4-2008] | H23.3 |

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|-------------------------------|
| Process 2 : Storage tanks | | | | | |
| STORAGE TANK, UNHEATED, NO.4, POLYESTER RESIN, 429 GALS; DIAMETER: 3 FT 9 IN; HEIGHT: 5 FT A/N: 04549A | D7 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; VOC: (9) [RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7- 2003 RULE 1171,2-4-2008] | H23.3 |
| STORAGE TANK, UNHEATED, NO.5, POLYESTER RESIN, 429 GALS; DIAMETER: 3 FT 9 IN; HEIGHT: 5 FT A/N: 04550A | D8 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; VOC: (9) [RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7- 2003 RULE 1171,2-4-2008] | H23.3 |
| STORAGE TANK, UNHEATED, NO.6, POLYESTER RESIN, 429 GALS; DIAMETER: 3 FT 9 IN; HEIGHT: 5 FT A/N: 04551A | D9 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; VOC: (9) [RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7- 2003 RULE 1171,2-4-2008] | H23.3 |
| Process 3 : Styrenated resin operation | | | | | |
| SPRAY COATING OPERATION, DEVILBISS, ENCLOSED, AUTOMOTIVE TYPE, 16 FT W. X 9 FT H. X 33 FT DEEP WITH 5 HP EXHAUST FAN, WITH SPRAY BOOTH A/N: 14201X | D10 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; PM: (9) [RULE 404,2-7-1986] ; VOC: (9) [RULE 1145,2-14-1997 | C6.2, D322.1, H23.2, K67.1 |

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|----------------------------|
| Process 3 : Styrenated resin operation | | | | | |
| | | | | <i>RULE 1145,12-3-2004;RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7-2003;RULE 1171,2-1-2008]</i> | |
| SPRAY COATING OPERATION, DEVILBISS, ENCLOSED, AUTOMOTIVE TYPE, 16 FT W. X 9 FT H. X 33 FT DEEP WITH 5 HP EXHAUST FAN, WITH SPRAY BOOTH A/N: 14202X | D11 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; PM: (9) [RULE 404,2-7-1986] ; VOC: (9) [RULE 1145,2-14-1997] <i>RULE 1145,12-3-2004;RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7-2003;RULE 1171,2-1-2008]</i> | C6.2, D322.1, H23.2, K67.1 |
| SPRAY COATING OPERATION, ACME, WATER WASH TYPE, WITH 5 HP EXHAUST FAN, WITH SPRAY BOOTH A/N: 14200X | D12 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; PM: (9) [RULE 404,2-7-1986] ; VOC: (9) [RULE 1145,2-14-1997] <i>RULE 1145,12-3-2004;RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7-2003;RULE 1171,2-1-2008]</i> | E448.1, K67.5 |

* (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
 (3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
 (5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
 (7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
 (9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|--------------------------------------|
| Process 3 : Styrenated resin operation | | | | | |
| ABRASIVE BLASTING, ROOM, 8 FT W. X 20 FT L. X 8 FT H., 300 LB PRESSURE POT, ALUMINA, NUTSHELL, IMPACT BEADS AND PLASTIC ABRASIVE MEDIA WITH A/N: 428970 ABRASIVE BLASTING NOZZLE, DIAMETER: 0.375 IN; 80 PSIG | D17 | C19 | | PM: (9) [RULE 1140,2-1-1980;RULE 1140,8-2-1985;RULE 405,2-7-1986] | B163.1, D323.1, E57.1, K67.4 |
| BAGHOUSE, WITH 5 CARTRIDGE FILTERS, REVERSE PULSE JET CLEANING, MICRO AIR CLEAN AIR SYSTEMS, 1250 SQ.FT. A/N: 428970 | C19 | D17 | | PM: (9) [RULE 404,2-7-1986] | D12.3, D322.2, D381.1, E102.1, K67.3 |
| Process 4 : Solvent recovery | | | | | |
| STILL, HOYT, SOLVO-SALVAGER, MODEL EP-8, 55 GALS A/N: 231699 | D13 | | | | C6.1 |
| Process 5 : R-219 EXEMPT EQUIPMENT SUBJECT TO SOURCE SPECIFIC RULES | | | | | |
| RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS | E14 | | | VOC: (9) [RULE 1113,11-8-1996;RULE 1113,7-13-2007;RULE 1171,11-7-2003;RULE 1171,2-4-2008] | K67.2 |
| RULE 219 EXEMPT EQUIPMENT, REFRIGERANT RECOVERY AND/OR RECYCLING UNITS, | E15 | | | | H23.1 |

* (1)(1A)(1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5)(5A)(5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2)(2A)(2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See Section J for NESHAP/MACT requirements
 ** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|------------|
| Process 5 : R-219 EXEMPT EQUIPMENT SUBJECT TO SOURCE SPECIFIC RULES | | | | | |
| RULE 219 EXEMPT EQUIPMENT, EXEMPT HAND WIPING OPERATIONS | E16 | | | VOC: (9) [RULE 1171,11-7-2003;RULE 1171,2-4-2008] | |
| RULE 219 EXEMPT EQUIPMENT, HAND LAY, BRUSH AND ROLL UP RESIN OPERATIONS | E20 | | | HAP: (10) [40CFR 63 Subpart WWW,4-21-2003] ; VOC: (9) [RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7- 2003 RULE 1171,2-4-2008] | H23.3 |
| RULE 219 EXEMPT EQUIPMENT, LAMINATING EQUIPMENT, LOW USE OR EMISSIONS | E21 | | | VOC: (9) [RULE 1168,10-3- 2003;RULE 1168,1-7-2005;RULE 1171,11-7-2003;RULE 1171,2-4- 2008] | H23.3 |

* (1)(1A)(1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5)(5A)(5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2)(2A)(2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See Section J for NESHAP/MACT requirements
 ** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

**FACILITY PERMIT TO OPERATE
HOOD MFG INC**

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

SECTION D: DEVICE ID INDEX

| Device Index For Section D | | | |
|-----------------------------------|---------------------------|----------------|---------------|
| Device ID | Section D Page No. | Process | System |
| D1 | 1 | 1 | 0 |
| D2 | 1 | 1 | 0 |
| D3 | 1 | 1 | 0 |
| D4 | 1 | 2 | 0 |
| D5 | 1 | 2 | 0 |
| D6 | 1 | 2 | 0 |
| D7 | 2 | 2 | 0 |
| D8 | 2 | 2 | 0 |
| D9 | 2 | 2 | 0 |
| D10 | 2 | 3 | 0 |
| D11 | 3 | 3 | 0 |
| D12 | 3 | 3 | 0 |
| D13 | 4 | 4 | 0 |
| E14 | 4 | 5 | 0 |
| E15 | 4 | 5 | 0 |
| E16 | 5 | 5 | 0 |
| D17 | 4 | 3 | 0 |
| C19 | 4 | 3 | 0 |
| E20 | 5 | 5 | 0 |
| E21 | 5 | 5 | 0 |

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[**RULE 401, 3-2-1984**; RULE 401, 11-9-2001]

F24.1 Accidental release prevention requirements of Section 112(r)(7):

a). The operator shall comply with the accidental release prevention requirements pursuant to 40 CFR Part 68 and shall submit to the Executive Officer, as a part of an annual compliance certification, a statement that certifies compliance with all of the requirements of 40 CFR Part 68, including the registration and submission of a risk management plan (RMP).

b). The operator shall submit any additional relevant information requested by the Executive Officer or designated agency.

[**40CFR 68 - Accidental Release Prevention, 5-24-1996**]

F48.1 The operator shall not use at this facility any other method to calculate the VOC emissions from the use of polyester resins and gelcoats except the method using the unified emission factors specified in Rule 1132 Attachment A.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002]

DEVICE CONDITIONS

B. Material/Fuel Type Limits

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

B163.1 The operator shall not use materials containing the following:

silica type abrasives

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D17]

C. Throughput or Operating Parameter Limits

C6.1 The operator shall use this equipment in such a manner that the temperature being monitored, as indicated below, does not exceed 100 Deg F.

This condition shall only apply to the condensate at the discharge.

To comply with this condition, the operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature at the condensate discharge.

The operator shall determine and record the parameter being monitored once every 7 days.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D13]

C6.2 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 2.5 inches water column.

To comply with this condition, the operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the exhaust filters.

The operator shall determine and record the parameter being monitored once every 7 days.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D10, D11]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D. Monitoring/Testing Requirements

D12.3 The operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the bags.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C19]

D322.1 The operator shall perform a weekly inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D10, D11]

D322.2 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C19]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D17]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D381.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a quarterly basis, at least, unless the equipment did not operate during the entire quarterly period. The routine quarterly inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C19]

E. Equipment Operation/Construction Requirements

E57.1 The operator shall vent this equipment to air pollution control equipment which has been issued a valid permit to construct or operate by the District whenever this equipment is in operation.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : D17]

E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition : C19]

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E448.1 The operator shall comply with the following requirements:

The operator shall not operate this equipment unless the water wash unit is properly maintained and in full operation with the water curtain completely covering the exhaust section of the booth. The operator shall also perform a weekly inspection of the water curtain integrity

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D12]

H. Applicable Rules

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|--------------|---------------|--------------|
| Refrigerants | District Rule | 1411 |

[RULE 1411, 3-1-1991]

[Devices subject to this condition : E15]

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 109 |
| PM | District Rule | 481 |

[RULE 109, 5-2-2003; RULE 481, 1-11-2002]

[Devices subject to this condition : D10, D11]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.3 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 109 |

[RULE 109, 5-2-2003]

[Devices subject to this condition : D4, D5, D6, D7, D8, D9, E20, E21]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

weekly record of pressure drop across the filter media

the name of the person performing the inspection and/or maintenance of the filter media

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D10, D11]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : E14]

K67.3 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the filter media

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C19]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

material safety data sheets of all materials used at this facility shall be kept current and made available to the District personnel upon request

[RULE 109, 5-2-2003; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D17]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.5 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the water wash

the date, time and results of the inspection, and

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D12]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statues of other governmental agencies. [204]
4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]
5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION E: ADMINISTRATIVE CONDITIONS

7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]
 - d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO₂) and be averaged over 15 consecutive minutes; [407]
 - e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO₂) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]
 - f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O₂) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]

8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
 - a. Brief description of the equipment tested.
 - b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream)

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION E: ADMINISTRATIVE CONDITIONS

- e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).
9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]
- a. The results of the source test.
 - b. Brief description of the equipment tested.
 - c. Operating conditions under which the test was performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream)
 - e. Field and laboratory data forms, strip charts and analyses.
 - f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]
11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

**FACILITY PERMIT TO OPERATE
HOOD MFG INC**

SECTION F: RECLAIM Monitoring and Source Testing Requirements

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
HOOD MFG INC**

SECTION G: Recordkeeping and Reporting Requirements for RECLAIM Sources

NOT APPLICABLE

**FACILITY PERMIT TO OPERATE
HOOD MFG INC**

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

NONE

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

FACILITY PERMIT TO OPERATE

HOOD MFG INC

SECTION J: AIR TOXICS **[40CFR 63 Subpart WWWW 4-21-2003]**

NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR REINFORCED PLASTIC COMPOSITES PRODUCTION.

1. The operator shall comply with all applicable requirements of 40 CFR 63, Subpart WWWW – National Emission Standards for Reinforced Plastic Composites Production and 40 CFR 63, Subpart A - General Provisions by the compliance dates that are specified in these subparts.
2. The operator shall determine the appropriate organic HAP emission factors and calculate the facility's organic HAP emissions from all reinforced plastic composites production operations pursuant to Section 63.5796, 63.5797, 63.5798, and 63.5799.
3. The operator shall comply with all applicable requirements of this subpart by the compliance dates that are specified in Section 63.5800.
4. The operator shall comply with all applicable standards specified in Section 63.5805 by using one of the options identified in Section 63.5810, 63.5820, or 63.5830 for each reinforced plastic composites production operation.
5. The operator shall comply with all applicable work practice standards and startup, shutdown, and malfunction requirements pursuant to Section 63.5835.
6. The operator shall conduct all performance tests, performance evaluations, design evaluations, capture efficiency testing, and other compliance demonstrations that are required by this subpart pursuant to Section 63.5840, 63.5845, 63.5850, 63.5855, and 63.5860.
7. For continuous lamination/casting operations, the operator shall comply with all applicable requirements of emission factor, percent reduction, and capture efficiency calculations procedures pursuant to Section 63.5865, 63.5870, 63.5875, 63.5880, 63.5885, and 63.5890.
8. The operator shall monitor and collect all required data pursuant to Section 63.5895 and demonstrate continuous compliance with all standards specified in Section 63.5805 pursuant to Section 63.5900.

FACILITY PERMIT TO OPERATE
HOOD MFG INC

SECTION J: AIR TOXICS
[40CFR 63 Subpart WWWW 4-21-2003]

9. The operator shall comply with all applicable notification requirements that are specified in Section 63.5905 of this subpart and 40 CFR 63, Subpart A.
10. The operator shall comply with all applicable reporting requirements that are specified in Section 63.5910.
11. The operator shall keep all required records pursuant to Section 63.5915 and 63.5920 of this subpart and 40 CFR 63, Subpart A to demonstrate compliance with all applicable requirements. In addition, all records including data, calculations, and any supporting documentation shall be prepared in a format which is acceptable to the AQMD.
12. Alternative plans, compliance plans, and the construction and operation of new or modified air pollution control equipment that are required by this subpart shall be approved through the AQMD permit system.

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

3. (A) Except for solid waste incineration facilities subject to standards under Section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]

(B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

Reopening for Cause

7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
 - (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

- (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
- (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

- 8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
 - (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

- 9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]
- 10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]
12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]
13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]
14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

EMERGENCY PROVISIONS

17. An emergency¹ constitutes an affirmative defense to an action brought for non-compliance with a technology-based emission limit only if:
- (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 - Breakdown Provisions, or subdivision (i) of Rule 2004 - Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 - Emergencies. [118]

¹ "Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

RECORDKEEPING PROVISIONS

19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
 - (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

22. The operator shall comply with the following requirements for prompt reporting of deviations:
 - (A) Breakdowns shall be reported as required by Rule 430 - Breakdown Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.
 - (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
 - (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
- (A) Identification of each permit term or condition that is the basis of the certification;
 - (B) The compliance status during the reporting period;
 - (C) Whether compliance was continuous or intermittent;
 - (D) The method(s) used to determine compliance over the reporting period and currently, and
 - (E) Any other facts specifically required by the Executive Officer to determine compliance.
- The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]
25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the Title V application file. [3004(a)(4)]

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations:

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

| RULE SOURCE | Adopted/Amended Date | FEDERAL Enforceability |
|------------------------|-----------------------------|-------------------------------|
| RULE 109 | 5-2-2003 | Federally enforceable |
| RULE 1113 | 11-8-1996 | Federally enforceable |
| RULE 1113 | 7-13-2007 | Non federally enforceable |
| RULE 1140 | 2-1-1980 | Federally enforceable |
| RULE 1140 | 8-2-1985 | Non federally enforceable |
| RULE 1145 | 12-3-2004 | Non federally enforceable |
| RULE 1145 | 2-14-1997 | Federally enforceable |
| RULE 1162 | 11-17-2000 | Federally enforceable |
| RULE 1162 | 7-8-2005 | Non federally enforceable |
| RULE 1168 | 1-7-2005 | Non federally enforceable |
| RULE 1168 | 10-3-2003 | Federally enforceable |
| RULE 1171 | 11-7-2003 | Federally enforceable |
| RULE 1171 | 2-1-2008 | Non federally enforceable |
| RULE 1175 | 5-13-1994 | Federally enforceable |
| RULE 1175 | 9-7-2007 | Non federally enforceable |
| RULE 118 | 12-7-1995 | Non federally enforceable |
| RULE 1303(a)(1)-BACT | 12-6-2002 | Non federally enforceable |
| RULE 1303(a)(1)-BACT | 5-10-1996 | Federally enforceable |
| RULE 1303(b)(2)-Offset | 12-6-2002 | Non federally enforceable |
| RULE 1303(b)(2)-Offset | 5-10-1996 | Federally enforceable |
| RULE 1411 | 3-1-1991 | Non federally enforceable |
| RULE 204 | 10-8-1993 | Federally enforceable |
| RULE 217 | 1-5-1990 | Federally enforceable |
| RULE 219 | 6-1-2007 | Non federally enforceable |
| RULE 219 | 9-4-1981 | Federally enforceable |
| RULE 3002 | 11-14-1997 | Federally enforceable |
| RULE 3003 | 11-14-1997 | Federally enforceable |
| RULE 3003 | 3-16-2001 | Non federally enforceable |
| RULE 3004 | 12-12-1997 | Federally enforceable |

FACILITY PERMIT TO OPERATE HOOD MFG INC

SECTION K: TITLE V Administration

| RULE SOURCE | Adopted/Amended Date | FEDERAL Enforceability |
|--|-----------------------------|-------------------------------|
| RULE 3004(a)(4)-Periodic Monitoring | 12-12-1997 | Federally enforceable |
| RULE 3005 | 11-14-1997 | Federally enforceable |
| RULE 3005 | 3-16-2001 | Non federally enforceable |
| RULE 3007 | 10-8-1993 | Federally enforceable |
| RULE 304 | 5-2-2008 | Non federally enforceable |
| RULE 401 | 11-9-2001 | Non federally enforceable |
| RULE 401 | 3-2-1984 | Federally enforceable |
| RULE 402 | 5-7-1976 | Non federally enforceable |
| RULE 404 | 2-7-1986 | Federally enforceable |
| RULE 405 | 2-7-1986 | Federally enforceable |
| RULE 408 | 5-7-1976 | Federally enforceable |
| RULE 430 | 7-12-1996 | Non federally enforceable |
| RULE 442 | 12-15-2000 | Federally enforceable |
| RULE 481 | 1-11-2002 | Federally enforceable |
| 40CFR 63 Subpart WWWW | 4-21-2003 | Federally enforceable |
| 40CFR 68 - Accidental Release Prevention | 5-24-1996 | Federally enforceable |
| RULE 701 | 6-13-1997 | Federally enforceable |

**FACILITY PERMIT TO OPERATE
HOOD MFG INC**

**APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN
PERMIT PURSUANT TO RULE 219**

NONE

FACILITY PERMIT TO OPERATE HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

| COATING | Limit* | Effective Date of Adoption | Effective 1/1/1998 | Effective 1/1/1999 | Effective 7/1/2001 | Effective 1/1/2005 | Effective 7/1/2008 |
|------------------------------------|--------|----------------------------------|-----------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| Bond Breakers | 350 | | | | | | |
| Clear Wood Finishes | | | | | | | |
| Varnish | 350 | | | | | | |
| Sanding Sealers | 350 | | | | | | |
| Lacquer | 680 | | 550 | | | 275 | |
| Concrete-Curing Compounds | 350 | | | | | | |
| Dry-Fog Coatings | 400 | | | | | | |
| Fire-proofing Exterior Coatings | 350 | 450 | | 350 | | | |
| Fire-Retardant Coatings | | | | | | | |
| Clear | 650 | | | | | | |
| Pigmented | 350 | | | | | | |
| Flats | 250 | | | | | | |
| Graphic Arts (Sign) Coatings | 500 | | | | | 100 | 50 |
| Industrial Maintenance | | | | | | | |

FACILITY PERMIT TO OPERATE HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

| | | | | | | |
|------------------------------------|-----|-----|-----|-----|-----|--|
| Primers and Topcoats | | | | | | |
| Alkyds | 420 | | | | | |
| Catalyzed Epoxy | 420 | | | | | |
| Bituminous Coatings | 420 | | | | | |
| Materials | | | | | | |
| Inorganic Polymers | 420 | | | | | |
| Vinyl Chloride Polymers | 420 | | | | | |
| Chlorinated Rubber | 420 | | | | | |
| Acrylic Polymers | 420 | | | | | |
| Urethane Polymers | 420 | | | | | |
| Silicones | 420 | | | | | |
| Unique Vehicles | 420 | | | | | |
| Japans/Faux Finishing | 350 | 700 | | 350 | | |
| Coatings | | | | | | |
| Magnesite Cement Coatings | 600 | | | 450 | | |
| Mastic Coatings | 300 | | | | | |
| Metallic Pigmented Coatings | 500 | | | | | |
| Multi-Color Coatings | 420 | | 250 | | | |
| Pigmented Lacquer | 680 | | 550 | | 275 | |
| Pre-Treatment Wash Primers | 780 | | | | | |
| Primers, Sealers, and Undercoaters | 350 | | | | | |
| Quick-Dry Enamels | 400 | | | | | |
| Roof Coatings | 300 | | | | | |
| Shellac | | | | | | |
| Clear | 730 | | | | | |
| Pigmented | 550 | | | | | |
| Stains | 350 | | | | | |
| Swimming Pool Coatings | | | | | | |
| Repair | 650 | | | | | |
| Other | 340 | | | | | |
| Traffic Coatings | 250 | | 150 | | | |
| Waterproofing Sealers | 400 | | | | | |
| Wood Preservatives | | | | | | |
| Below-Ground | 350 | | | | | |
| Other | 350 | | | | | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

**FACILITY PERMIT TO OPERATE
HOOD MFG INC**

**APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 11-8-1996]**

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

| COATING | Limit |
|--------------------|-------|
| Low-Solids Coating | 120 |

FACILITY PERMIT TO OPERATE HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 7-13-2007]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- (2) Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings, except anti-graffiti coatings, for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

FACILITY PERMIT TO OPERATE HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 7-13-2007]

TABLE OF STANDARDS VOC LIMITS

**Grams of VOC Per Liter of Coating,
 Less Water and Less Exempt Compounds**

| COATING CATEGORY | Ceiling Limit* | Current Limit | Effective Date | | | | | |
|--|----------------|---------------|----------------|--------|--------|--------|--------|--------|
| | | | 1/1/03 | 1/1/04 | 1/1/05 | 7/1/06 | 7/1/07 | 7/1/08 |
| Bond Breakers | 350 | | | | | | | |
| Clear Wood Finishes | 350 | | | | | 275 | | |
| Varnish | 350 | | | | | 275 | | |
| Sanding Sealers | 350 | | | | | 275 | | |
| Lacquer | 680 | 550 | | | 275 | | | |
| Clear Brushing Lacquer | 680 | | | | 275 | | | |
| Concrete-Curing Compounds | 350 | | | | | | 100 | |
| Concrete-Curing Compounds For Roadways and Bridges** | 350 | | | | | | | |
| Dry-Fog Coatings | 400 | | | | | | 150 | |
| Fire-Proofing Exterior Coatings | 450 | 350 | | | | | | |
| Fire-Retardant Coatings*** | | | | | | | | |
| Clear | 650 | | | | | | | |
| Pigmented | 350 | | | | | | | |
| Flats | 250 | 100 | | | | | | 50 |
| Floor Coatings | 420 | | 100 | | | 50 | | |
| Graphic Arts (Sign) Coatings | 500 | | | | | | | |
| Industrial Maintenance (IM) Coatings | 420 | | | 250 | | 100 | | |
| High Temperature IM Coatings | | | 420 | | | | | |
| Zinc-Rich IM Primers | 420 | | 340 | | | 100 | | |
| Japans/Faux Finishing Coatings | 700 | 350 | | | | | | |
| Magnesite Cement Coatings | 600 | 450 | | | | | | |
| Mastic Coatings | 300 | | | | | | | |
| Metallic Pigmented Coatings | 500 | | | | | | | |
| Multi-Color Coatings | 420 | 250 | | | | | | |
| Nonflat Coatings | 250 | | 150 | | | 50 | | |
| Nonflat High Gloss | 250 | | 150 | | | | 50 | |

FACILITY PERMIT TO OPERATE HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 7-13-2007]

| COATING CATEGORY | Ceiling Limit* | Current Limit | Effective Date | | | | | |
|--|----------------|---------------|----------------|--------|--------|--------|--------|--------|
| | | | 1/1/03 | 1/1/04 | 1/1/05 | 7/1/06 | 7/1/07 | 7/1/08 |
| Pigmented Lacquer | 680 | 550 | | | 275 | | | |
| Pre-Treatment Wash Primers | 780 | | 420 | | | | | |
| Primers, Sealers, and Undercoaters | 350 | | 200 | | | 100 | | |
| Quick-Dry Enamels | 400 | | 250 | | | 150 | 50 | |
| Quick-Dry Primers, Sealers, and Undercoaters | 350 | | 200 | | | 100 | | |
| Recycled Coatings | | | 250 | | | | | |
| Roof Coatings | 300 | | 250 | | 50 | | | |
| Roof Coatings, Aluminum | 500 | | | | 100 | | | |
| Roof Primers, Bituminous | 350 | | 350 | | | | | |
| Rust Preventative Coatings | 420 | | 400 | | | 100 | | |
| Shellac | | | | | | | | |
| Clear | 730 | | | | | | | |
| Pigmented | 550 | | | | | | | |
| Specialty Primers | 350 | | | | | 250 | 100 | |
| Stains | 350 | | 250 | | | | 100 | |
| Stains, Interior | 250 | | | | | | | |
| Swimming Pool Coatings | | | | | | | | |
| Repair | 650 | | 340 | | | | | |
| Other | 340 | | | | | | | |
| Traffic Coatings | 250 | 150 | | | | | 100 | |
| Waterproofing Sealers | 400 | | 250 | | | 100 | | |
| Waterproofing | 400 | | | | | 100 | | |
| Concrete/Masonry Sealers | | | | | | | | |
| Wood Preservatives | | | | | | | | |
| Below-Ground | 350 | | | | | | | |
| Other | 350 | | | | | | | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards.

** Does not include compounds used for curbs and gutters, sidewalks, islands, driveways and other miscellaneous concrete areas.

*** The Fire-Retardant Coating category will be eliminated on January 1, 2007 and subsumed by the coating category for which they are formulated.

FACILITY PERMIT TO OPERATE
HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1113 7-13-2007]

TABLE OF STANDARDS (cont.)
VOC LIMITS

Grams of VOC Per Liter of Material

| COATING | Limit |
|--------------------|-------|
| Low-Solids Coating | 120 |

FACILITY PERMIT TO OPERATE

HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS **[RULE 1140 2-1-1980]**

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).
- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE

HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS **[RULE 1140 8-2-1985]**

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 2 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (1)(A).

- (2) The operator shall not, if he is not complying with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines,
or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

FACILITY PERMIT TO OPERATE
HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1145 2-14-1997]

Except as otherwise provided in Rule 1145, the operator shall not apply on plastics, glass, or rubber any coatings which are applied with a VOC content in excess of the limits specified below:

| COATING | VOC LIMITS | | | |
|---|-----------------------------------|---------|---------------------|---------|
| | <u>Less Water and Less Exempt</u> | | | |
| | <u>Compounds</u> | | | |
| | Current | | On and After 1-1-98 | |
| | g/L | lbs/gal | g/L | lbs/gal |
| General Coatings | | | | |
| One-component | 275 | 2.3 | 275 | 2.3 |
| Two-component | 420 | 3.5 | 420 | 3.5 |
| Military Spec. Coating | | | | |
| One-component | 340 | 2.8 | 340 | 2.8 |
| Two-component | 420 | 3.5 | 420 | 3.5 |
| Multi-Colored Coatings | 685 | 5.7 | 685 | 5.7 |
| Mold Seal Coatings | 750 | 6.3 | 750 | 6.3 |
| Vacuum Metalizing Coatings | 800 | 6.7 | 800 | 6.7 |
| Mirror Backing | | | | |
| Curtain Coated | 500 | 4.2 | 500 | 4.2 |
| Roll Coated | 430 | 3.6 | 430 | 3.6 |
| Optical Coatings | 800 | 6.7 | 800 | 6.7 |
| Electric Dissipating Coatings and Shock-Free Coatings | 800 | 6.7 | 360 | 3.0 |
| Metallic Coatings | 420 | 3.5 | 420 | 3.5 |

FACILITY PERMIT TO OPERATE

HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1162 11-17-2000]

The operator shall not use a polyester resin material in a polyester resin operation which has a monomer content in excess of the limits specified in the Table below.

| Polyester Resin Materials | Monomer Content in Polyester Resin Materials as Applied (By Weight Percent) |
|---------------------------------|---|
| General Purpose Polyester Resin | 35 |
| Corrosion-Resistant | 48 |
| Fire Retardant | 42 |
| High Strength | 48 |
| Clear Gel Coat | 50 |
| Pigmented Gel Coat | 45 |

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1162 7-8-2005]**

The operator shall not use polyester resin material in an open molding system, which has a monomer content in excess of the limits specified in the following Table.

| Polyester Resin Materials | Monomer Percentage by Weight as Applied | |
|---------------------------|---|---|
| | Prior to 11-09-2001 | Current Limits |
| Clear Gel Coat | 50 | - |
| For Marble Resins | - | 40 |
| For Other Resins | - | 44 |
| Pigmented Gel Coat | 45 | - |
| White and Off White | - | 30 |
| Non-White | - | 37 |
| Primer | - | 28 |
| Specialty Gel Coats | - | 48 |
| General Purpose Resin | 35 | - |
| Marble Resins | - | 10 or (32 % as supplied, no fillers) 17 |
| Solid Surface Resins | - | 24 or |
| Tub/Shower Resins | - | (35 % as supplied, no fillers) |
| Lamination Resins | - | 31 or (35 % as supplied, no fillers) |
| Others | - | 35 |
| Fire Retardant Resin | 42 | 38 |
| Corrosion Resistant Resin | 48 | 48 |
| High Strength Resin | 48 | 40 |

FACILITY PERMIT TO OPERATE HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 1-7-2005]

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

| Architectural Applications | Current VOC Limit* |
|-------------------------------------|--------------------|
| Indoor Carpet Adhesives | 50 |
| Carpet Pad Adhesives | 50 |
| Outdoor Carpet Adhesives | 150 |
| Wood Flooring Adhesive | 100 |
| Rubber Floor Adhesives | 60 |
| Subfloor Adhesives | 50 |
| Ceramic Tile Adhesives | 65 |
| VCT and Asphalt Tile Adhesives | 50 |
| Dry Wall and Panel Adhesives | 50 |
| Cove Base Adhesives | 50 |
| Multipurpose Construction Adhesives | 70 |
| Structural Glazing Adhesives | 100 |
| Single Ply Roof Membrane Adhesives | 250 |

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1168 1-7-2005]**

| Specialty Applications | VOC Limits and Effective Dates** | | | |
|--|----------------------------------|--------|--------|--------|
| | Current VOC Limit* | 1-1-05 | 7-1-05 | 1-1-07 |
| PVC Welding | 510 | | | |
| CPVC Welding | 490 | | | |
| ABS Welding | 400 | | 325 | |
| Plastic Cement Welding | 350 | 250 | | |
| Adhesive Primer for Plastic | 650 | | 550 | |
| Computer Diskette Manufacturing | 350 | | | |
| Contact Adhesive | 80 | | | |
| Special Purpose Contact Adhesive | 250 | | | |
| Tire Retread | 100 | | | |
| Adhesive Primer for Traffic Marking Tape | 150 | | | |
| Structural Wood Member Adhesive | 140 | | | |
| Sheet Applied Rubber Lining Operations | 850 | | | |
| Top and Trim Adhesive | 540 | | | 250 |

** The specified limits remain in effect unless revised limits are listed in subsequent columns.

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1168 1-7-2005]**

For adhesives, adhesive bonding primers, or any other primer not regulated by the above two tables and applied to the following substrates, the following limits shall apply:

| Substrate Specific Applications | Current VOC Limit* |
|--|---------------------------|
| Metal to Metal | 30 |
| Plastic Foams | 50 |
| Porous Material (except wood) | 50 |
| Wood | 30 |
| Fiberglass | 80 |

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

| Sealants | Current VOC Limit* |
|--------------------------|---------------------------|
| Architectural | 250 |
| Marine Deck | 760 |
| Nonmembrane Roof | 300 |
| Roadway | 250 |
| Single-Ply Roof Membrane | 450 |
| Other | 420 |

FACILITY PERMIT TO OPERATE
HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1168 1-7-2005]

| Sealant Primers | Current VOC Limit* |
|------------------------|---------------------------|
| Architectural | |
| Non Porous | 250 |
| Porous | 775 |
| Modified Bituminous | 500 |
| Marine Deck | 760 |
| Other | 750 |

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1168 10-3-2003]**

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

| Architectural Applications | Current VOC Limit |
|-------------------------------------|--------------------------|
| Indoor Carpet Adhesives | 50 |
| Carpet Pad Adhesives | 50 |
| Outdoor Carpet Adhesives | 150 |
| Wood Flooring Adhesive | 100 |
| Rubber Floor Adhesives | 60 |
| Subfloor Adhesives | 50 |
| Ceramic Tile Adhesives | 65 |
| VCT and Asphalt Tile Adhesives | 50 |
| Dry Wall and Panel Adhesives | 50 |
| Cove Base Adhesives | 50 |
| Multipurpose Construction Adhesives | 70 |
| Structural Glazing Adhesives | 100 |
| Single Ply Roof Membrane Adhesives | 250 |

* For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1168 10-3-2003]**

| .Specialty Applications | VOC Limits and Effective Dates** | | | |
|--|----------------------------------|--------|--------|--------|
| | Current VOC Limit | 6-7-02 | 1-1-03 | 1-1-05 |
| PVC Welding | 510 | | | 285 |
| CPVC Welding | 490 | | | 270 |
| ABS Welding | 400 | | | |
| Plastic Cement Welding | 350 | | | 250 |
| Adhesive Primer for Plastic | 650 | | | 250 |
| Computer Diskette Manufacturing | 350 | | | |
| Contact Adhesive | 250 | | 80 | |
| Special Purpose Contact Adhesive | 250 | | | |
| Tire Retread | 100 | | | |
| Adhesive Primer for Traffic Marking Tape | 150 | | | |
| Structural Wood Member Adhesive | 140 | | | |
| Sheet Applied Rubber Lining Operations | 850 | | | |
| Top and Trim Adhesive | 250 | 540 | | 250 |

** The specified limits remain in effect unless revised limits are listed in subsequent columns.

| Substrate Specific Applications | Current VOC Limit |
|---------------------------------|-------------------|
| Metal to Metal | 30 |
| Plastic Foams | 50 |
| Porous Material (except wood) | 50 |

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1168 10-3-2003]**

| Substrate Specific Applications | Current VOC Limit |
|--|--------------------------|
| Wood | 30 |
| Fiberglass | 80 |

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

| Sealants | Current VOC Limit |
|--------------------------|--------------------------|
| Architectural | 250 |
| Marine Deck | 760 |
| Nonmembrane Roof | 300 |
| Roadway | 250 |
| Single-Ply Roof Membrane | 450 |
| Other | 420 |

| Sealant Primers | Current VOC Limit |
|------------------------|--------------------------|
| Architectural | |
| Non Porous | 250 |
| Porous | 775 |
| Modified Bituminous | 500 |
| Marine Deck | 760 |
| Other | 750 |

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 11-7-2003]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| SOLVENT CLEANING ACTIVITY | CURRENT LIMITS |
|--|------------------------|
| | VOC g/l (lb/gal) |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application | |
| (i) General | 25 (0.21) |
| (ii) Electrical Apparatus Components & Electronic Components | 500 (4.2) |
| (iii) Medical Devices & Pharmaceuticals | 800 (6.7) |
| (B) Repair and Maintenance Cleaning | |
| (i) General | 25 (0.21) |
| (ii) Electrical Apparatus Components & Electronic Components | 900 (7.5) |
| (iii) Medical Devices & Pharmaceuticals | |
| (A) Tools, Equipment, & Machinery | 800 (6.7) |
| (B) General Work Surfaces | 600 (5.0) |

FACILITY PERMIT TO OPERATE
HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-7-2003]

| SOLVENT CLEANING ACTIVITY | CURRENT LIMITS |
|---|------------------------|
| | VOC g/l (lb/gal) |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 550 (4.6) |
| (D) Cleaning of Ink Application Equipment | |
| (i) General | 25 (0.21) |
| (ii) Flexographic Printing | 25 (0.21) |
| (iii) Gravure Printing | |
| (A) Publication | 750 (6.3) |
| (B) Packaging | 25 (0.21) |
| (iv) Lithographic or Letter Press Printing | |
| (A) Roller Wash – Step 1 | 600 (5.0) |
| (B) Roller Wash-Step 2, Blanket Wash, & On-Press Components | 800 (6.7) |
| (C) Removable Press Components | 25 (0.21) |
| (v) Screen Printing | 750 (6.3) |
| (vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing) | 800 (6.7) |

FACILITY PERMIT TO OPERATE
HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 11-7-2003]

| SOLVENT CLEANING ACTIVITY | CURRENT LIMITS |
|---|------------------------|
| | VOC g/l (lb/gal) |
| (vii) Specialty Flexographic Printing | 600 (5.0) |
| (E) Cleaning of Polyester Resin Application Equipment | 25 (0.21) |

**FACILITY PERMIT TO OPERATE
 HOOD MFG INC**

**APPENDIX B: RULE EMISSION LIMITS
 [RULE 1171 2-1-2008]**

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

| | CURRENT LIMITS* | EFFECTIVE 1/1/2008* | EFFECTIVE 1/1/2009 |
|--|---------------------------------|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY | VOC g/l (lb/gal) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application | | | |
| (i) General | 25 (0.21) | | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | | |
| (iii) Medical Devices & Pharmaceuticals | 800 (6.7) | | |
| (B) Repair and Maintenance Cleaning | | | |
| (i) General | 25 (0.21) | | |
| (ii) Electrical Apparatus Components & Electronic Components | 100 (0.83) | | |

FACILITY PERMIT TO OPERATE
HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 2-1-2008]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2008* | EFFECTIVE 1/1/2009 |
|---|---------------------------------|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY (cont.) | VOC g/l (lb/gal) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (iii) Medical Devices & Pharmaceuticals | | | |
| (A) Tools, Equipment, & Machinery | 800 (6.7) | | |
| (B) General Work Surfaces | 600 (5.0) | | |
| (C) Cleaning of Coatings or Adhesives Application Equipment | 25 (0.21) | | |
| (D) Cleaning of Ink Application Equipment | | | |
| (i) General | 25 (0.21) | | |
| (ii) Flexographic Printing | 25 (0.21) | | |
| (iii) Gravure Printing | | | |
| (A) Publication | 100 (0.83) | | |
| (B) Packaging | 25 (0.21) | | |
| (iv) Lithographic (Offset) or Letter Press Printing | | | |
| (A) Roller Wash, Blanket Wash, & On-Press Components | | | |
| (I) Newsprint | 100 (0.83) | | |

FACILITY PERMIT TO OPERATE
HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 1171 2-1-2008]

| | CURRENT LIMITS* | EFFECTIVE 1/1/2008* | EFFECTIVE 1/1/2009 |
|--|---------------------------------|---------------------------------|---------------------------------|
| SOLVENT CLEANING ACTIVITY (cont.) | VOC g/l (lb/gal) | VOC g/l (lb/gal) | VOC g/l (lb/gal) |
| (II) Other Substrates | 500 (4.2) | 100 (0.83) | |
| (B) Removable Press Components | 25 (0.21) | | |
| (v) Screen Printing | 500 (4.2) | 100 (0.83) | |
| (vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing) | 650 (5.4) | 650 (5.4) | 100 (0.83) |
| (vii) Specialty Flexographic Printing | 100 (0.83) | | |
| (E) Cleaning of Polyester Resin Application Equipment | 25 (0.21) | | |

* The specified limits remain in effect unless revised limits are listed in subsequent columns.

FACILITY PERMIT TO OPERATE HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1175 5-13-1994]

Except as otherwise provided in Rule 1175

Emission Control Requirements:

- (1) Manufacturing Operations, Excluding Expandable Polystyrene (EPS) Molding Operations
 - (A) By January 1, 1994, each polyurethane operation subject to the rule shall discontinue its use of CFCs, VOCs, or methylene chloride.
 - (B) Each manufacturing operation, excluding rigid polyurethane operations shall reduce yearly emissions from its 1988 emissions baseline, based on Rule 301 emission fees filing, by 100 percent, beginning calendar year 1994.
- (2) Expandable Polystyrene (EPS) Molding Operations

The operator of an expandable polystyrene (EPS) molding operation shall demonstrate, to the satisfaction of the Executive Officer, that manufacturing emissions and post-manufacturing emissions, assuming all the blowing agent is released from the product, are less than 2.4 lbs per 100 lbs of raw material processed.
- (3) The operator of any polymeric cellular manufacturing operation, subject to the requirements of paragraph (1) or (2), shall submit a plan to the District subject to approval by the Executive Officer's designee, that will demonstrate compliance with paragraph (1) or (2).
- (4) The operator of any polymeric cellular manufacturing operation that has not achieved the requirements specified in paragraphs (1), (2), or (3) shall:
 - (A) Submit permit applications for the installation of an emission control system within four months of the date that compliance with such requirement was not achieved; and
 - (B) Within 12 months of failing to meet the requirements of paragraph (1), (2), or (3), the following provisions must be satisfied:
 - (i) An approved emission control system is installed and operating with all sources of manufacturing emissions vented only to the approved emission control system; and

FACILITY PERMIT TO OPERATE

HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS **[RULE 1175 5-13-1994]**

Emissions from the final manufact~~(i)~~ured product are vented only to the approved emission control system for at least:

- (I) 48 hours, in the case of expandable polystyrene molding operations that process more than 800,000 pounds per calendar year of raw material; or
- (II) 24 hours, in the case of all other manufacturing operations.

FACILITY PERMIT TO OPERATE

HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS **[RULE 1175 9-7-2007]**

Except as otherwise provided in Rule 1175

(c) Emission Control Requirements

- (1) Manufacturing Operations, Excluding Expandable Polystyrene (EPS) Molding Operations
 - (A) By January 1, 1994, each polyurethane operation subject to the rule shall discontinue its use of CFCs, VOCs, or methylene chloride.
 - (B) Each manufacturing operation, excluding rigid polyurethane operations shall reduce yearly emissions from its 1988 emissions baseline, based on Rule 301 emission fees filing, by 100 percent, beginning calendar year 1994.
- (2) Expandable Polystyrene (EPS) Molding Operations

The owner or operator of an expandable polystyrene (EPS) molding operation shall demonstrate, to the satisfaction of the Executive Officer, that manufacturing emissions and post-manufacturing emissions, assuming all the blowing agent is released from the product, are less than 2.4 lbs per 100 lbs of raw material processed.
- (3) The owner or operator of any polymeric cellular manufacturing operation, subject to the requirements of paragraphs (c)(1) or (c)(2), shall submit a plan to be approved by the Executive Officer, that demonstrates compliance with paragraph (c)(1) or (c)(2).
- (4) The owner or operator of any polymeric cellular manufacturing operation that has not achieved the requirements specified in paragraph (c)(1), (c)(2), or (c)(3) shall:
 - (A) Submit permit applications for the installation of an emission control system within four months of the date that compliance with such requirement was not achieved; and
 - (B) Within twelve months of failing to meet the requirements of paragraph (c)(1), (c)(2), or (c)(3), the following provisions must be satisfied:

FACILITY PERMIT TO OPERATE

HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS **[RULE 1175 9-7-2007]**

- (i) An approved emission control system is installed and operated with all sources of manufacturing emissions collected and reduced according to subparagraphs (b)(1)(A) and (b)(1)(C) ; and
- (ii) All sources of storage emissions from the final manufactured product are collected and reduced according to subparagraphs (b)(1)(B) and (b)(1)(C) for at least:
 - (I) 48 hours, in the case of expandable polystyrene molding operations that process more than 800,000 pounds per calendar year of raw material; or
 - (II) 24 hours, in the case of all other manufacturing operations; or
- (iii) Expanded polystyrene (EPS) block molding operations may, in lieu of complying with the specific control requirements of clauses (c)(4)(B)(i) and (c)(4)(B)(ii), collect and reduce, through a combination of emission control systems and operational techniques, as approved by the Executive Officer, manufacturing emissions by at least 93 percent overall by weight (the product of capture and control device efficiencies), provided, at least 60 percent of the annual EPS block throughput is manufactured with low-pentane bead and the remainder with mid-pentane bead.

FACILITY PERMIT TO OPERATE

HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 404 2-7-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a).

Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|--|--------------------------------|--|--------------------------|--|--------------------------------|---|-----------------------------|
| | | Milligrams per Cubic Meter | Grains per Cubic Foot | | | Milligrams per Cubic Meter | Grains per Cubic Foot |
| Cubic meters Per Minute | Cubic feet Per Minute | | | Cubic meters Per Minute | Cubic feet Per Minute | | |
| 25 or less | 883 or less | 450 | 0.196 | 900 | 31780 | 118 | 0.0515 |
| 30 | 1059 | 420 | .183 | 1000 | 35310 | 113 | .0493 |
| 35 | 1236 | 397 | .173 | 1100 | 38850 | 109 | .0476 |
| 40 | 1413 | 377 | .165 | 1200 | 42380 | 106 | .0463 |
| 45 | 1589 | 361 | .158 | 1300 | 45910 | 102 | .0445 |
| 50 | 1766 | 347 | .152 | 1400 | 49440 | 100 | .0437 |
| 60 | 2119 | 324 | .141 | 1500 | 52970 | 97 | .0424 |
| 70 | 2472 | 306 | .134 | 1750 | 61800 | 92 | .0402 |

FACILITY PERMIT TO OPERATE
HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 404 2-7-1986]

| Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | | Volume Discharged Calculated as Dry Gas At Standard Conditions | | Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions | |
|--|-----------------------|--|-----------------------|--|-----------------------|--|-----------------------|
| Cubic meters Per Minute | Cubic feet Per Minute | Milligrams per Cubic Meter | Grains per Cubic Foot | Cubic meters Per Minute | Cubic feet Per Minute | Milligrams per Cubic Meter | Grains per Cubic Foot |
| 80 | 2825 | 291 | .127 | 2000 | 70630 | 87 | .0380 |
| 90 | 3178 | 279 | .122 | 2250 | 79460 | 83 | .0362 |
| 100 | 3531 | 267 | .117 | 2500 | 88290 | 80 | .0349 |
| 125 | 4414 | 246 | .107 | 3000 | 105900 | 75 | .0327 |
| 150 | 5297 | 230 | .100 | 4000 | 141300 | 67 | .0293 |
| 175 | 6180 | 217 | .0947 | 5000 | 176600 | 62 | .0271 |
| 200 | 7063 | 206 | .0900 | 6000 | 211900 | 58 | .0253 |
| 250 | 8829 | 190 | .0830 | 8000 | 282500 | 52 | .0227 |
| 300 | 10590 | 177 | .0773 | 10000 | 353100 | 48 | .0210 |
| 350 | 12360 | 167 | .0730 | 15000 | 529700 | 41 | .0179 |
| 400 | 14130 | 159 | .0694 | 20000 | 706300 | 37 | .0162 |
| 450 | 15890 | 152 | .0664 | 25000 | 882900 | 34 | .0148 |
| 500 | 17660 | 146 | .0637 | 30000 | 1059000 | 32 | .0140 |
| 600 | 21190 | 137 | .0598 | 40000 | 1413000 | 28 | .0122 |
| 700 | 24720 | 129 | .0563 | 50000 | 1766000 | 26 | .0114 |
| 800 | 28250 | 123 | .0537 | 70000 or more | 2472000 or more | 23 | .0100 |

FACILITY PERMIT TO OPERATE

HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS [RULE 405 2-7-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

| Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process | | Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process | |
|----------------------------|----------------|--|--------------------|----------------------------|--------|---|--------------------|
| | | Kilograms Per Hour | Pounds Per Hour | | | Kilograms Per Hour | Pounds Per Hour |
| 100 or less | 220 or less | 0.450 | 0.99 | 9000 | 19840 | 5.308 | 11.7 |
| 150 | 331 | 0.585 | 1.29 | 10000 | 22050 | 5.440 | 12.0 |
| 200 | 441 | 0.703 | 1.55 | 12500 | 27560 | 5.732 | 12.6 |
| 250 | 551 | 0.804 | 1.77 | 15000 | 33070 | 5.982 | 13.2 |
| 300 | 661 | 0.897 | 1.98 | 17500 | 38580 | 6.202 | 13.7 |
| 350 | 772 | 0.983 | 2.17 | 20000 | 44090 | 6.399 | 14.1 |
| 400 | 882 | 1.063 | 2.34 | 25000 | 55120 | 6.743 | 14.9 |
| 450 | 992 | 1.138 | 2.51 | 30000 | 66140 | 7.037 | 15.5 |
| 500 | 1102 | 1.209 | 2.67 | 35000 | 77160 | 7.296 | 16.1 |
| 600 | 1323 | 1.340 | 2.95 | 40000 | 88180 | 7.527 | 16.6 |
| 700 | 1543 | 1.461 | 3.22 | 45000 | 99210 | 7.738 | 17.1 |
| 800 | 1764 | 1.573 | 3.47 | 50000 | 110200 | 7.931 | 17.5 |
| 900 | 1984 | 1.678 | 3.70 | 60000 | 132300 | 8.277 | 18.2 |
| 1000 | 2205 | 1.777 | 3.92 | 70000 | 154300 | 8.582 | 18.9 |

FACILITY PERMIT TO OPERATE
HOOD MFG INC

APPENDIX B: RULE EMISSION LIMITS
[RULE 405 2-7-1986]

| Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process) | | Process Weight Per Hour | | Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process) | |
|-------------------------|-----------------|---|-----------------|-------------------------|--------------------|---|-----------------|
| Kilograms Per Hour | Pounds Per Hour | Kilograms Per Hour | Pounds Per Hour | Kilograms Per Hour | Pounds Per Hour | Kilograms Per Hour | Pounds Per Hour |
| 1250 | 2756 | 2.003 | 4.42 | 80000 | 176400 | 8.854 | 19.5 |
| 1500 | 3307 | 2.206 | 4.86 | 90000 | 198400 | 9.102 | 20.1 |
| 1750 | 3858 | 2.392 | 5.27 | 100000 | 220500 | 9.329 | 20.6 |
| 2000 | 4409 | 2.563 | 5.65 | 125000 | 275600 | 9.830 | 21.7 |
| 2250 | 4960 | 2.723 | 6.00 | 150000 | 330700 | 10.26 | 22.6 |
| 2500 | 5512 | 2.874 | 6.34 | 175000 | 385800 | 10.64 | 23.5 |
| 2750 | 6063 | 3.016 | 6.65 | 200000 | 440900 | 10.97 | 24.2 |
| 3000 | 6614 | 3.151 | 6.95 | 225000 | 496000 | 11.28 | 24.9 |
| 3250 | 7165 | 3.280 | 7.23 | 250000 | 551200 | 11.56 | 25.5 |
| 3600 | 7716 | 3.404 | 7.50 | 275000 | 606300 | 11.82 | 26.1 |
| 4000 | 8818 | 3.637 | 8.02 | 300000 | 661400 | 12.07 | 26.6 |
| 4500 | 9921 | 3.855 | 8.50 | 325000 | 716500 | 12.30 | 27.1 |
| 5000 | 11020 | 4.059 | 8.95 | 350000 | 771600 | 12.51 | 27.6 |
| 6000 | 13230 | 4.434 | 9.78 | 400000 | 881800 | 12.91 | 28.5 |
| 7000 | 15430 | 4.775 | 10.5 | 450000 | 992100 | 13.27 | 29.3 |
| 8000 | 17640 | 5.089 | 11.2 | 500000 or more | 1102000 or more | 13.60 | 30.0 |