



JUL 30 2013

Mr. Robert Boston
Berry Petroleum Company
5201 Truxtun Avenue, Suite 100
Bakersfield, CA 93309

Re: Notice of Minor Title V Permit Modification
District Facility # S-1246
Project # 1133016

Dear Mr. Boston:


Enclosed is the District's analysis of your application for minor Title V permit modification for the facility identified above. You proposed a Title V minor permit modification to incorporate recently issued S-1246-296-28 into the Title V operating permit. The project increases the number of TEOR wells from 1200 to 1350 and installs additional vapor recovery compressors.

Enclosed is the engineering evaluation with the following attachments: proposed modified Title V permit, recently issued S-1246-296-28, application, and previous Title V permit. This project will be subject to a 45-day EPA commenting period prior to the District taking final action.

If you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Thank you for your cooperation in this matter.

Sincerely,



David Warner
Director of Permit Services

Enclosures

cc: Gerardo C. Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061
www.valleyair.org www.healthyairliving.com

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

TITLE V APPLICATION REVIEW

Minor Modification
Project #: S-1133016

Engineer: Richard Edgehill
Date: July 29, 2013

Facility Number: S-1246
Facility Name: Berry Petroleum Company
Mailing Address: 5201 Truxtun Avenue, Suite 300
Bakersfield, CA 93309

Contact Name: Bob Boston
Phone: (661) 616-3808
Title: Regulatory Compliance Specialist
Lead Engineer: Alan Phillips *AP SUPR A Q E*

I. PROPOSAL

JUL 29 2013

Berry Petroleum Company is proposing a Title V minor permit modification to incorporate the recently issued Authority to Construct (ATC) S-1246-296-28 into the Title V operating permit. The ATC authorized the following change:

| | |
|-------------------|--|
| ATC S-1246-296-28 | INCREASE NUMBER OF WELLS FROM 1200 TO 1350 AND INSTALL ADDITIONAL VAPOR RECOVERY COMPRESSORS |
|-------------------|--|

The purpose of this evaluation is to identify all applicable requirements, determine if the facility will comply with the applicable requirements and to provide the legal and factual basis for the proposed revisions.

II. FACILITY LOCATION

The TEOR operation authorized by ATC S-1246-296-28 is located within Berry's heavy oil production stationary source in the western Kern County fields at Sections 1, 2, 3, 11, and 12, T31S, R22E.

III. EQUIPMENT DESCRIPTION

PTO S-1246-296-37: THERMALLY ENHANCED OIL RECOVERY (TEOR)
OPERATION WELL VENT VAPOR CONTROL SYSTEM
SERVING 1350 WELLS INCLUDING GAS/LIQUID
SEPARATORS, HEAT EXCHANGERS, COMPRESSORS,

INLET SEPARATOR VESSELS, CONDENSATE PUMPS,
SULFUR SCRUBBER, VAPOR PIPING FROM TANKS
'337 AND '339 AND VAPOR PIPING TO STEAM
GENERATORS S-1246-3, '-24, '-46, '-119, '-292, '-293, '-
294, '-342, '-343, '-344, '-345, '-346, '-355, '-356, '-357, '-
358, '-359 AND/OR DOGGR APPROVED GAS DISPOSAL
WELLS (NMWSS)

IV. SCOPE OF EPA AND PUBLIC REVIEW

This change to a Title V permit is considered to be a minor modification and, as such, requires no public review.

V. APPLICABLE REQUIREMENTS

District Rule 2520, Federally Mandated Operating Permits (Adopted June 21, 2001)

VI. DESCRIPTION OF PROPOSED MODIFICATIONS

A condition match between draft PTO and current PTO S-1246-296-36 (in draft form currently being reviewed by EPA) is provided below.

S-1246-296

| Draft PTO | Current PTO | Comments |
|---------------|---------------|---|
| S-1246-296-37 | S-1246-296-36 | |
| 1-6 | 1-6 | |
| 7 | 7 | Revised DEL condition to reflect fugitive emissions from 1350 vapor controlled wells (ATC S-1246-296-29) |
| 8-54 | 8-54 | |

VII. COMPLIANCE

In accordance with Rule 2520, 3.20, these modifications:

1. Do not violate requirements of any applicable federally enforceable local or federal requirement;
2. Do not relax monitoring, reporting, or recordkeeping requirements in the permit and are not significant changes in existing monitoring permit terms or conditions;
3. Do not require or change a case-by-case determination of an emission limitation or other standard, or a source-specific determination for temporary sources of ambient impacts, or a visibility or increment analysis;
4. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include;
 - a. A federally enforceable emission cap assumed to avoid classification as a modification under any provisions of Title I of the Federal Clean Air Act; and
 - b. An alternative emissions limit approved pursuant to regulations promulgated under section 112(l)(5) of the Federal Clean Air Act; and
5. Are not Title I modifications as defined in District Rule 2520 or modifications as defined in section 111 or 112 of the Federal Clean Air Act; and
6. Do not seek to consolidate overlapping applicable requirements.

Berry Petroleum Company
Facility ID: S-1246
Project No.: S-1133016

In accordance with Rule 2520, the application meets the procedural requirements of section 11.4 by including;

1. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;
2. The source's suggested draft permit; and
3. Certification by a responsible official that the proposed modification meets the criteria for use of minor permit modification procedures and a request that such procedures be used.

VIII. ATTACHMENTS

- A. Proposed Title V PTO S-1246-296-37
- B. Authority to Construct S-1246-296-28
- C. Permit Application
- D. Previous Title V (draft) PTOs S-1246-296-36

Berry Petroleum Company
Facility ID: S-1246
Project No.: S-1133016

ATTACHMENT A

Proposed Title V PTO
S-1246-296-37

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-296-37

EXPIRATION DATE: 03/31/2016

SECTION: 02 TOWNSHIP: 31S RANGE: 22E

EQUIPMENT DESCRIPTION:

THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION WELL VENT VAPOR CONTROL SYSTEM SERVING 1350 WELLS INCLUDING GAS/LIQUID SEPARATORS, HEAT EXCHANGERS, COMPRESSORS, INLET SEPARATOR VESSELS, CONDENSATE PUMPS, SULFUR SCRUBBER, VAPOR PIPING FROM TANKS '337 AND '339 AND VAPOR PIPING TO STEAM GENERATORS S-1246-3, '-24, '-46, '-119, '-292, '-293, '-294, '-342, '-343, '-344, '-345, '-346, '-355, '-356, '-357, '-358, '-359 AND/OR DOGGR APPROVED GAS DISPOSAL WELLS (NMWSS)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. TEOR operation is authorized to operate at the following locations: Sections 1, 2, 3, 11, and 12 T31S, R22E. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Well vent vapor from this TEOR operation shall only be incinerated in approved steam generators or disposed of in DOGGR approved gas disposal wells. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Well vent vapor from this TEOR operation shall not be incinerated in approved steam generators unless it is first scrubbed in a fuel gas sulfur scrubber and sulfur compounds are reduced by a minimum of 95%. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Compliance with scrubber sulfur removal efficiency requirement shall be demonstrated by measurement of total sulfur compound concentrations at scrubber inlet and outlet. The measurement shall be conducted on grab samples taken at scrubber inlet and outlet using one of the following test methods: ASTM D3246 or double GC for H₂S and mercaptans, or equivalent test method with prior District approval. Grab samples shall be taken and analyzed upon initial use of the scrubber and, thereafter, every six months. If scrubber is not in use at six-month anniversary date, then efficiency shall be demonstrated within two weeks of returning scrubber to service. For each month in which scrubber is operated and laboratory analysis of grab samples is not required, operator shall monitor and adjust scrubber performance as needed using gas-detection tubes calibrated for existing sulfur species or other equivalent District approved sulfur detection method(s) or device(s). [District NSR Rule] Federally Enforceable Through Title V Permit
6. Well vent vapor collection and control system includes piping from sulfur scrubbers to District approved incinerating devices. Well vent vapor collection and control system includes bypass piping around sulfur scrubbers to DOGGR-approved vapor disposal well(s). [District NSR Rule] Federally Enforceable Through Title V Permit
7. Fugitive VOC emissions rate for the TEOR operation, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999) and the total number of components in gas/light liquid service, shall not exceed 584.6 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The annual inspection requirements of Section 5.8.1 through Section 5.8.5 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10 wt %) or less, as determined by the test methods in Section 6.3.5 of Rule 4401. [District Rule 4401 4.9] Federally Enforceable Through Title V Permit
10. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.8 of Rule 4401 demonstrates the existence of a component with a major liquid leak, a component with a gas leak greater than 50,000 ppmv, or an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.6.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines. [District Rule 4401 5.6.2] Federally Enforceable Through Title V Permit
12. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401 3.20] Federally Enforceable Through Title V Permit
13. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.8 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 3 of Rule 4401. [District Rule 4401 5.6.2] Federally Enforceable Through Title V Permit
14. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.6.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.9 of Rule 4401. [District Rule 4401 5.7.1] Federally Enforceable Through Title V Permit
15. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401 5.7.2] Federally Enforceable Through Title V Permit
16. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401 5.7.3] Federally Enforceable Through Title V Permit
17. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401 5.8.1] Federally Enforceable Through Title V Permit
18. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401 5.8.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. In addition to the inspections required by Section 5.8.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401 5.8.3] Federally Enforceable Through Title V Permit
20. In addition to the inspections required by Sections 5.8.1, 5.8.2 and 5.8.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.8.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401 5.8.4] Federally Enforceable Through Title V Permit
21. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401 5.8.5] Federally Enforceable Through Title V Permit
22. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401 5.8.6] Federally Enforceable Through Title V Permit
23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401 5.9.1] Federally Enforceable Through Title V Permit
24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and 5.9.2.3 of Rule 4401, or the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.2] Federally Enforceable Through Title V Permit
25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401 5.9.3] Federally Enforceable Through Title V Permit
26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 4 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401 5.9.4] Federally Enforceable Through Title V Permit
27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401 5.9.4] Federally Enforceable Through Title V Permit
28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.9.5] Federally Enforceable Through Title V Permit
29. The time of the initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.9.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401 5.9.7] Federally Enforceable Through Title V Permit
31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401 6.1.1] Federally Enforceable Through Title V Permit
32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401 6.1.3] Federally Enforceable Through Title V Permit
33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401 6.1.5] Federally Enforceable Through Title V Permit
34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401 6.1.6] Federally Enforceable Through Title V Permit
35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1.7] Federally Enforceable Through Title V Permit
36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401 6.1.8] Federally Enforceable Through Title V Permit
37. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401 6.1.11] Federally Enforceable Through Title V Permit
38. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401 6.2.1] Federally Enforceable Through Title V Permit
39. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401 6.2.2] Federally Enforceable Through Title V Permit
40. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 for a vapor control system which does not have a VOC destruction device. [District Rule 4401 6.2.3] Federally Enforceable Through Title V Permit
41. An operator seeking approval pursuant to Section 6.2.2 or Section 6.2.3 shall submit a written request and supporting information to the APCO. [District Rule 4401 6.2.4] Federally Enforceable Through Title V Permit
42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.10 of Rule 4401. [District Rule 4401 6.2.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401 6.3.1] Federally Enforceable Through Title V Permit
44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401 6.3.2] Federally Enforceable Through Title V Permit
45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401 6.3.3] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401 6.3.5] Federally Enforceable Through Title V Permit
47. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401 6.4] Federally Enforceable Through Title V Permit
48. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit
49. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
50. Collected vapors shall be disposed of in District approved incineration devices, as listed on this permit, or in Department of Oil, Gas and Geothermal Resources (DOGGR) approved vapor disposal wells. Permittee shall make documentation of DOGGR approval for injection wells readily available for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit
51. The operator shall maintain records of the fugitive component count and calculated VOC emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

52. Permittee shall maintain a written record of inlet and outlet sulfur compound measurements and recharging dates and such records shall be made readily available for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit
53. Permittee shall maintain with the permit a current listing of all steam enhanced wells with casing vents connected to the well vent collection and control system. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
54. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

ATTACHMENT B

Authority to Construct

S-1246-296-28

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1246-296-28

ISSUANCE DATE: 07/11/2012

LEGAL OWNER OR OPERATOR: BERRY PETROLEUM COMPANY
MAILING ADDRESS: 5201 TRUXTUN AVENUE SUITE 100
ATTN: EH&S MANAGER
BAKERSFIELD, CA 93309-0422

LOCATION: HEAVY OIL WESTERN STATIONARY SOURCE
KERN COUNTY, CA

SECTION: 02 TOWNSHIP: 31S RANGE: 22E

EQUIPMENT DESCRIPTION:

MODIFICATION OF THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION WELL VENT VAPOR CONTROL SYSTEM SERVING 1200 WELLS INCLUDING GAS/LIQUID SEPARATORS, HEAT EXCHANGERS, COMPRESSORS, INLET SEPARATOR VESSELS, CONDENSATE PUMPS, SULFUR SCRUBBER, VAPOR PIPING FROM TANKS '337 AND '339 AND VAPOR PIPING TO STEAM GENERATORS S-1246-3, '-24, '-46, '-119, '-292, '-293, '-342, '-343, '-344, '-345, '-346, '-355, '-356, '-357, '-358, AND '-359 AND/OR DOGGR APPROVED GAS DISPOSAL WELLS (NMWSS): INCREASE NUMBER OF WELLS FROM 1200 TO 1350 AND INSTALL ADDITIONAL VAPOR RECOVERY COMPRESSORS

CONDITIONS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. Permit to Operate S-1246-163 shall be cancelled upon implementation of this Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
3. TEOR operation is authorized to operate at the following locations: Sections 1, 2, 3, 11, and 12 T31S, R22E. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Well vent vapor from this TEOR operation shall only be incinerated in approved steam generators or disposed of in DOGGR approved gas disposal wells. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

S-1246-296-28 : Jul 18 2013 9:53AM -- EDGEHLR : Joint Inspection NOT Required

Southern Regional Office • 34946 Flyover Court • Bakersfield, CA 93308 • (661) 392-5500 • Fax (661) 392-5585

5. Well vent vapor from this TEOR operation shall not be incinerated in approved steam generators unless it is first scrubbed in a fuel gas sulfur scrubber and sulfur compounds are reduced by a minimum of 95%. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Compliance with scrubber sulfur removal efficiency requirement shall be demonstrated by measurement of total sulfur compound concentrations at scrubber inlet and outlet. The measurement shall be conducted on grab samples taken at scrubber inlet and outlet using one of the following test methods: ASTM D3246 or double GC for H₂S and mercaptans, or equivalent test method with prior District approval. Grab samples shall be taken and analyzed upon initial use of the scrubber and, thereafter, every six months. If scrubber is not in use at six-month anniversary date, then efficiency shall be demonstrated within two weeks of returning scrubber to service. For each month in which scrubber is operated and laboratory analysis of grab samples is not required, operator shall monitor and adjust scrubber performance as needed using gas-detection tubes calibrated for existing sulfur species or other equivalent District approved sulfur detection method(s) or device(s). [District Rule 2201] Federally Enforceable Through Title V Permit
7. Well vent vapor collection and control system includes piping from sulfur scrubbers to District approved incinerating devices. Well vent vapor collection and control system includes bypass piping around sulfur scrubbers to DOGGR-approved vapor disposal well(s). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Fugitive VOC emissions rate for the TEOR operation, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999) and the total number of components in gas/light liquid service, shall not exceed 584.6 lb-VOC/day. [District Rule 2201]
9. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
10. The inspection requirements of Section 5.4.1 through Section 5.4.7 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10%) or less, as determined by the test methods in Section 6.3.4 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
11. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
12. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with either of the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, or the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
13. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines, a component with a major liquid leak, or a component with a gas leak greater than 50,000 ppmv. [District Rule 4401] Federally Enforceable Through Title V Permit
14. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.4 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or a gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 2 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
15. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

16. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401] Federally Enforceable Through Title V Permit
17. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401] Federally Enforceable Through Title V Permit
18. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401] Federally Enforceable Through Title V Permit
19. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
20. In addition to the inspections required by Section 5.4.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
21. In addition to the inspections required by Sections 5.4.1, 5.4.2 and 5.4.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.4.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401] Federally Enforceable Through Title V Permit
22. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401] Federally Enforceable Through Title V Permit
23. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401] Federally Enforceable Through Title V Permit
24. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401] Federally Enforceable Through Title V Permit
25. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401] Federally Enforceable Through Title V Permit
26. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

27. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.5.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 3 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401] Federally Enforceable Through Title V Permit
28. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401] Federally Enforceable Through Title V Permit
29. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
30. The time of the initial leak detection shall be the start of the repair period specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
31. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401] Federally Enforceable Through Title V Permit
32. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401] Federally Enforceable Through Title V Permit
33. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
34. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
35. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401] Federally Enforceable Through Title V Permit
36. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
37. The results of gauge tank TVP testing conducted pursuant to Section 6.2.3 shall be submitted to the APCO within 60 days after the completion of the testing. [District Rule 4401] Federally Enforceable Through Title V Permit
38. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401] Federally Enforceable Through Title V Permit
39. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. A process system as defined in Section 3.30 of Rule 4401 is not subject to compliance source testing requirements. [District Rule 4401] Federally Enforceable Through Title V Permit
40. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection are controlled by an internal combustion engine subject to Rule 4702, a combustion device subject to Rule 4320, 4307 or 4308, a flare subject to Rule 4311. [District Rule 4401] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

41. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
42. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401] Federally Enforceable Through Title V Permit
43. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401] Federally Enforceable Through Title V Permit
44. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401] Federally Enforceable Through Title V Permit
45. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401] Federally Enforceable Through Title V Permit
46. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401] Federally Enforceable Through Title V Permit
47. Operator shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. [District Rule 4401]
48. In accordance with the approved Operator Management Plan (OMP), permittee shall meet all applicable operating, leak standards, inspection and re-inspection, leak repair, record keeping, and notification requirements of Rule 4401. [District Rule 4401]
49. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

50. Operator shall keep a list of all gauge tanks, as defined in Section 3.0 of Rule 4401. The list shall contain the size, identification number, the location of each gauge tank and specify whether the gauge tank is upstream of all front line production equipment. [District Rule 4401] Federally Enforceable Through Title V Permit
51. By January 30 of each year, an operator shall submit to the APCO for approval, in writing, an annual report indicating any changes to an existing Operator Management Plan. [District Rule 4401] Federally Enforceable Through Title V Permit
52. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4401] Federally Enforceable Through Title V Permit
53. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
54. Collected vapors shall be disposed of in District approved incineration devices, as listed on this permit, or in Department of Oil, Gas and Geothermal Resources (DOGGR) approved vapor disposal wells. Permittee shall make documentation of DOGGR approval for injection wells readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
55. The operator shall maintain records of the fugitive component count and calculated VOC emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
56. Permittee shall maintain a written record of inlet and outlet sulfur compound measurements and recharging dates and such records shall be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
57. Permittee shall maintain with the permit a current listing of all steam enhanced wells with casing vents connected to the well vent collection and control system. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
58. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070]

ATTACHMENT C

Permit Application

San Joaquin Valley Air Pollution Control District

www.valleyair.org

RECEIVED

JUL 17 2013

SJVAPCD
Southern Region

Permit Application For:

ADMINISTRATIVE AMENDMENT MINOR MODIFICATION SIGNIFICANT MODIFICATION

| | | |
|--|-------------------|--|
| 1. PERMIT TO BE ISSUED TO: Berry Petroleum Company | | |
| 2. MAILING ADDRESS: | | |
| STREET/P.O. BOX: <u>5201 Truxtun Avenue, Suite 100</u> | | |
| CITY: <u>Bakersfield</u> | STATE: <u>CA</u> | 9-DIGIT ZIP CODE: <u>93309</u> |
| 3. LOCATION WHERE THE EQUIPMENT WILL BE OPERATED: | | INSTALLATION DATE: |
| STREET: <u>Western Heavy Oil Source S-1246</u> | CITY: _____ | 2013 |
| _____ | RANGE <u>22</u> | |
| 4. GENERAL NATURE OF BUSINESS: Production of oil and gas | | |
| 5. DESCRIPTION OF EQUIPMENT OR MODIFICATION FOR WHICH APPLICATION IS MADE (include Permit #'s if known, and use additional sheets if necessary) | | |
| Include the following Authority to Construct (ATC) permits in facility Title5 Permit | | |
| S-1246-296-28 (TEOR System) –The base document for the minor modification should be draft permit S-1246-296-36. | | |
| 6. TYPE OR PRINT NAME OF APPLICANT: Bob Boston | | TITLE OF APPLICANT: Manager ES&H |
| 7. SIGNATURE OF APPLICANT:  | DATE: 07/09/13 | PHONE: ((661) 616-3808 FAX: () EMAIL: reb@bry.com |

For APCD Use Only:

| | |
|------------|--|
| DATE STAMP | FILING FEE RECEIVED: \$ _____ CHECK#: _____ DATE PAID: _____ PROJECT NO: <u>S-1133016</u> FACILITY ID: <u>S-1246</u> |
|------------|--|

JUL 17 2013

SJVAPCD
Southern Region

San Joaquin Valley Unified Air Pollution Control District

TITLE V MODIFICATION - COMPLIANCE CERTIFICATION FORM

I. TYPE OF PERMIT ACTION (Check appropriate box)

SIGNIFICANT PERMIT MODIFICATION

ADMINISTRATIVE

MINOR PERMIT MODIFICATION

AMENDMENT

| | |
|--|----------------------|
| COMPANY NAME: Berry Petroleum Company (BPC) | FACILITY ID: S- 1246 |
| 1. Type of Organization: <input checked="" type="checkbox"/> Corporation <input type="checkbox"/> Sole Ownership <input type="checkbox"/> Government <input type="checkbox"/> Partnership <input type="checkbox"/> Utility | |
| 2. Owner's Name: Berry Petroleum Company (BPC) | |
| 3. Agent to the Owner: Tim Crawford | |

II. COMPLIANCE CERTIFICATION (Read each statement carefully and initial all circles for confirmation):

- Based on information and belief formed after reasonable inquiry, the equipment identified in this application will continue to comply with the applicable federal requirement(s).
- Based on information and belief formed after reasonable inquiry, the equipment identified in this application will comply with applicable federal requirement(s) that will become effective during the permit term, on a timely basis.
- Corrected information will be provided to the District when I become aware that incorrect or incomplete information has been submitted.
- Based on information and belief formed after reasonable inquiry, information and statements in the submitted application package, including all accompanying reports, and required certifications are true accurate and complete.

I declare, under penalty of perjury under the laws of the state of California, that the forgoing is correct and true:



 Signature of Responsible Official

7-16-13

 Date

Robert E Boston

 Name of Responsible Official (please print)

Manager of ES&H

 Title of Responsible Official (please print)

ATTACHMENT D

Previous Title V PTO

S-1246-296-36

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1246-296-36

EXPIRATION DATE: 03/31/2016

SECTION: 02 TOWNSHIP: 31S RANGE: 22E

EQUIPMENT DESCRIPTION:

THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION WELL VENT VAPOR CONTROL SYSTEM SERVING 1200 WELLS INCLUDING GAS/LIQUID SEPARATORS, HEAT EXCHANGERS, COMPRESSORS, INLET SEPARATOR VESSELS, CONDENSATE PUMPS, SULFUR SCRUBBER, VAPOR PIPING FROM TANKS '337 AND '339 AND VAPOR PIPING TO STEAM GENERATORS S-1246-3, '-24, '-46, '-119, '-292, '-293, '-294, '-342, '-343, '-344, '-345, '-346, '-355, '-356, '-357, '-358, '-359 AND/OR DOGGR APPROVED GAS DISPOSAL WELLS (NMWSS)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. TEOR operation is authorized to operate at the following locations: Sections 1, 2, 3, 11, and 12 T31S, R22E. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Well vent vapor from this TEOR operation shall only be incinerated in approved steam generators or disposed of in DOGGR approved gas disposal wells. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Well vent vapor from this TEOR operation shall not be incinerated in approved steam generators unless it is first scrubbed in a fuel gas sulfur scrubber and sulfur compounds are reduced by a minimum of 95%. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Compliance with scrubber sulfur removal efficiency requirement shall be demonstrated by measurement of total sulfur compound concentrations at scrubber inlet and outlet. The measurement shall be conducted on grab samples taken at scrubber inlet and outlet using one of the following test methods: ASTM D3246 or double GC for H₂S and mercaptans, or equivalent test method with prior District approval. Grab samples shall be taken and analyzed upon initial use of the scrubber and, thereafter, every six months. If scrubber is not in use at six-month anniversary date, then efficiency shall be demonstrated within two weeks of returning scrubber to service. For each month in which scrubber is operated and laboratory analysis of grab samples is not required, operator shall monitor and adjust scrubber performance as needed using gas-detection tubes calibrated for existing sulfur species or other equivalent District approved sulfur detection method(s) or device(s). [District NSR Rule] Federally Enforceable Through Title V Permit
6. Well vent vapor collection and control system includes piping from sulfur scrubbers to District approved incinerating devices. Well vent vapor collection and control system includes bypass piping around sulfur scrubbers to DOGGR-approved vapor disposal well(s). [District NSR Rule] Federally Enforceable Through Title V Permit
7. Fugitive VOC emissions rate for the TEOR operation, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999) and the total number of components in gas/light liquid service, shall not exceed 519.5 lb-VOC/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The annual inspection requirements of Section 5.8.1 through Section 5.8.5 of Rule 4401 shall not apply to components exclusively handling gas/vapor or liquid with a VOC content of ten percent by weight (10 wt %) or less, as determined by the test methods in Section 6.3.5 of Rule 4401. [District Rule 4401 4.9] Federally Enforceable Through Title V Permit
10. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401, 5.5.1 and 5.5.2] Federally Enforceable Through Title V Permit
11. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.8 of Rule 4401 demonstrates the existence of a component with a major liquid leak, a component with a gas leak greater than 50,000 ppmv, or an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.6.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines. [District Rule 4401 5.6.2] Federally Enforceable Through Title V Permit
12. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401 3.20] Federally Enforceable Through Title V Permit
13. An operator shall be in violation of this rule if any District inspection demonstrates or if any operator inspection conducted pursuant to Section 5.8 of Rule 4401 demonstrates the existence of any combination of components with minor liquid leaks, minor gas leaks, or gas leaks greater than 10,000 ppmv up to 50,000 ppmv that totals more than number of leaks allowed by Table 3 of Rule 4401. [District Rule 4401 5.6.2] Federally Enforceable Through Title V Permit
14. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.6.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.9 of Rule 4401. [District Rule 4401 5.7.1] Federally Enforceable Through Title V Permit
15. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401 5.7.2] Federally Enforceable Through Title V Permit
16. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401 5.7.3] Federally Enforceable Through Title V Permit
17. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 of Rule 4401 at least once every year. [District Rule 4401 5.8.1] Federally Enforceable Through Title V Permit
18. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401 5.8.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. In addition to the inspections required by Section 5.8.1 of Rule 4401, an operator shall inspect for leaks all accessible operating pumps, compressors, and PRDs in service as follows: An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 4 of Rule 4401. [District Rule 4401 5.8.3] Federally Enforceable Through Title V Permit
20. In addition to the inspections required by Sections 5.8.1, 5.8.2 and 5.8.3 of Rule 4401, operator shall perform the following: initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release, re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection, inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. Except for PRDs subject to the requirements of Section 5.8.4.1 of Rule 4401, an operator shall inspect a component that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401 5.8.4] Federally Enforceable Through Title V Permit
21. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401 5.8.5] Federally Enforceable Through Title V Permit
22. District inspection in no way fulfills any of the mandatory inspection requirements that are placed upon operators and cannot be used or counted as an inspection required of an operator. [District Rule 4401 5.8.6] Federally Enforceable Through Title V Permit
23. An operator shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak and shall include the following information on the tag: date and time of leak detection, date and time of leak measurement, for a gaseous leak, the leak concentration in ppmv, for a liquid leak, whether it is a major liquid leak or a minor liquid leak, whether the component is an essential component, an unsafe-to monitor component, or a critical component. [District Rule 4401 5.9.1] Federally Enforceable Through Title V Permit
24. An operator shall keep the tag affixed to the component until an operator has met all of the following conditions: repaired or replaced the leaking component, re-inspected the component using the test method in Section 6.3.3, and 5.9.2.3 of Rule 4401, or the component is found to be in compliance with the requirements of this rule. [District Rule 4401 5.9.2] Federally Enforceable Through Title V Permit
25. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401 5.9.3] Federally Enforceable Through Title V Permit
26. Except for leaking critical components or leaking essential components subject to the requirements of Section 5.9.7 of Rule 4401, if an operator has minimized a leak but the leak still exceeds the applicable leak limits as defined in Section 3.0 of Rule 4401, an operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 4 of Rule 4401: Repair or replace the leaking component; or vent the leaking component to a VOC collection and control system as defined in Section 3.0 of Rule 4401, or remove the leaking component from operation. [District Rule 4401 5.9.4] Federally Enforceable Through Title V Permit
27. The repair period in calendar days shall not exceed 14 days for minor gas leaks, 5 days for major gas leaks less than or equal to 50,000 ppmv, 2 days for gas leak greater than 50,000 ppmv, 3 days for minor liquid leaks, 2 days for major liquid leaks. [District Rule 4401 5.9.4] Federally Enforceable Through Title V Permit
28. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.9.5] Federally Enforceable Through Title V Permit
29. The time of the initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401 5.9.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

30. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401 5.9.7] Federally Enforceable Through Title V Permit
31. The operator of any steam-enhanced crude oil production well shall maintain records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401 6.1.1] Federally Enforceable Through Title V Permit
32. An operator of any steam-enhanced crude oil production well shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401 6.1.3] Federally Enforceable Through Title V Permit
33. Operator of any steam-enhanced crude oil production well shall keep an inspection log maintained pursuant to Section 6.4 of Rule 4401. [District Rule 4401 6.1.5] Federally Enforceable Through Title V Permit
34. Records of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components, including a copy of current calibration gas certification from the vendor of said calibration gas cylinder, the date of calibration, concentration of calibration gas, instrument reading of calibration gas before adjustment, instrument reading of calibration gas after adjustment, calibration gas expiration date, and calibration gas cylinder pressure at the time of calibration shall be maintained. [District Rule 4401 6.1.6] Federally Enforceable Through Title V Permit
35. An operator shall maintain copies at the facility of the training records of the training program operated pursuant to Section 6.5 of Rule 4401. [District Rule 4401 6.1.7] Federally Enforceable Through Title V Permit
36. Operator shall keep a copy of the APCO-approved Operator Management Plan at the facility. [District Rule 4401 6.1.8] Federally Enforceable Through Title V Permit
37. An operator that discovers that a PRD has released shall record the date that the release was discovered, and the identity and location of the PRD that released. An operator shall submit such information recorded during the calendar year to the APCO no later than 60 days after the end of the calendar year. [District Rule 4401 6.1.11] Federally Enforceable Through Title V Permit
38. An operator shall source test annually all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC. Compliance testing shall be performed annually by source testers certified by ARB. Testing shall be performed during June, July, August, or September of each year if the system's control efficiency is dependent upon ambient air temperature. [District Rule 4401 6.2.1] Federally Enforceable Through Title V Permit
39. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401 6.2.2] Federally Enforceable Through Title V Permit
40. If approved by EPA, ARB, and the APCO, an operator need not comply with the annual testing requirement of Section 6.2.1 for a vapor control system which does not have a VOC destruction device. [District Rule 4401 6.2.3] Federally Enforceable Through Title V Permit
41. An operator seeking approval pursuant to Section 6.2.2 or Section 6.2.3 shall submit a written request and supporting information to the APCO. [District Rule 4401 6.2.4] Federally Enforceable Through Title V Permit
42. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.17 of Rule 4401: Conduct an initial TVP testing of the produced fluid in each gauge tank not later than June 14, 2007. Thereafter, an operator shall conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank. The TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.10 of Rule 4401. [District Rule 4401 6.2.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

43. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4401 6.3.1] Federally Enforceable Through Title V Permit
44. VOC content shall be analyzed by using the latest revision of ASTM Method E168, E169, or E260 as applicable. Analysis of halogenated exempt compounds shall be performed by using ARB Method 432. [District Rule 4401 6.3.2] Federally Enforceable Through Title V Permit
45. Leak inspection, other than audio-visual, and measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instruction, as appropriate, not more than 30 days prior to its use. The operator shall record the calibration date of the instrument. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one (1) centimeter or less from the surface of the component interface. [District Rule 4401 6.3.3] Federally Enforceable Through Title V Permit
46. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401 6.3.5] Federally Enforceable Through Title V Permit
47. Operator shall maintain an inspection log in which an operator records, at a minimum, all of the following information for each inspection performed: The total number of components inspected, total number and percentage of leaking components found by component type, location, type, and name or description of each leaking component and description of any unit where the leaking component is found, date of leak detection and the method of leak detection. For gaseous leaks, the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak. the date of repair, replacement, or removal from operation of leaking components, identify and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, methods used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier, the date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced, the inspector's name, business mailing address, and business telephone number, date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401 6.4] Federally Enforceable Through Title V Permit
48. All records of required monitoring data and support information shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4401, 6.1] Federally Enforceable Through Title V Permit
49. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
50. Collected vapors shall be disposed of in District approved incineration devices, as listed on this permit, or in Department of Oil, Gas and Geothermal Resources (DOGGR) approved vapor disposal wells. Permittee shall make documentation of DOGGR approval for injection wells readily available for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit
51. The operator shall maintain records of the fugitive component count and calculated VOC emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

52. Permittee shall maintain a written record of inlet and outlet sulfur compound measurements and recharging dates and such records shall be made readily available for District inspection upon request. [District NSR Rule] Federally Enforceable Through Title V Permit
53. Permittee shall maintain with the permit a current listing of all steam enhanced wells with casing vents connected to the well vent collection and control system. [District Rules 1070 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
54. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT