



APR 19 2016

Mr. Michael Donich
Golden State Vintners
7409 W. Central Ave
Fresno, CA 93706-9449

**Re: Notice of Preliminary Decision – Title V Permit Renewal
District Facility # C-581
Project # C-1150057**


Dear Mr. Donich:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Golden State Vintners at 7409 W. Central Ave, Fresno, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,



Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Mike Tollstrup, CARB (w/enclosures) via email
cc: Gerardo C. Rios, EPA (w/enclosures) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

**SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT**

**Title V Permit Renewal Evaluation
Golden State Vintners
C-581**

TABLE OF CONTENTS

I.	PROPOSAL	1
II.	FACILITY LOCATION	1
III.	EQUIPMENT LISTING	1
IV.	GENERAL PERMIT TEMPLATE USAGE	2
V.	SCOPE OF EPA AND PUBLIC REVIEW	2
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS	2
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE	4
VIII.	PERMIT REQUIREMENTS	5
IX.	PERMIT SHIELD	22
X.	PERMIT CONDITIONS	22
XI.	ATTACHMENTS	22

ATTACHMENT A - DRAFT RENEWED TITLE V OPERATING PERMIT
ATTACHMENT B - PREVIOUS TITLE V OPERATING PERMIT
ATTACHMENT C - DETAILED FACILITY REPORT
ATTACHMENT D - DISTRICT RULE 4702 STRINGENCY ANALYSIS
ATTACHMENT E – DISTRICT RULE 4621 STRINGENCY ANALYSIS
ATTACHMENT F – DISTRICT RULE 4622 STRINGENCY ANALYSIS

TITLE V PERMIT RENEWAL EVALUATION

Winery

Engineer: Jonah Aiyabei

Date: April 13, 2016

Facility Number: C-581
Facility Name: Golden State Vintners
Mailing Address: 7409 W. Central Ave
Fresno, CA 93706

Contact Name: Michael Donich
Phone: (559) 266-6548

Responsible Official: Michael Donich
Title: Plant Manager

Project # : C-1150057
Deemed Complete: January 28, 2015

I. PROPOSAL

Golden State Vintners was issued a Title V permit on July 31, 2010. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit has been reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the initial Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

The facility is located at 7409 W. Central Avenue in Fresno.

III. EQUIPMENT LISTING

A detailed report listing all the permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant has requested to utilize template No. SJV-UM-0-3, Facility-Wide Umbrella General Permit Template. Based on the information submitted in the Template Qualification Form, the applicant qualifies for the use of this template.

V. SCOPE OF EPA AND PUBLIC REVIEW

Certain segments of the proposed renewed operating permit are based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are included in the proposed permit and are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

The following permit conditions, including their underlying applicable requirements, originate from model general permit templates and are not subject to further EPA or public review:

Conditions 1 through 40 of the requirements for permit unit C-581-0-2.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

Rules Updated

- District Rule 2020, Exemptions (amended December 18, 2014)
- District Rule 2201, New and Modified Stationary Source Review Rule (amended April 21, 2011)
- District Rule 4621, Gasoline Transfer into Stationary Storage Containers, Delivery Vessels and Bulk Plants (amended December 19, 2013)
- District Rule 4622, Gasoline Transfer into Motor Vehicle Fuel Tanks (amended December 19, 2013)

- District Rule 4694, Wine Fermentation and Storage Tanks (adopted December 15, 2005)¹
- District Rule 4702, Internal Combustion Engines – Phase 2 (amended November 14, 2013)
- 40 CFR Part 63, Subpart ZZZZ, National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

Rules Removed

There have been no rules removed since the initial Title V permit was issued.

Rules Added

- District Rule 2410, Prevention of Significant Deterioration, (adopted June 16, 2011)

Rules Not Updated

- District Rule 1070, Inspections (December 17, 1992)
- District Rule 1081, Source Sampling (amended December 16, 1993)
- District Rule 1100, Equipment Breakdown (amended December 17, 1992)
- District Rule 1160, Emission Statements (adopted November 18, 1992)
- District Rule 2010, Permits Required (adopted December 17, 1992)
- District Rule 2031, Transfer of Permits (adopted December 17, 1992)
- District Rule 2040, Applications (adopted December 17, 1992)
- District Rule 2070, Standards for Granting Applications (adopted December 17, 1992)
- District Rule 2080, Conditional Approval (adopted December 17, 1992)
- District Rule 2520, Federally Mandated Operating Permits (amended June 21, 2001)

¹Although the rule itself has not been updated, the District's SIP submittal was amended on August 18, 2011 to exclude the fermentation requirements. The storage requirements were subsequently approved into the SIP on November 29, 2012, and have therefore become federally enforceable.

- District Rule 4201, Particulate Matter Concentration (amended December 17, 1992)
- District Rule 4701, Internal Combustion Engines – Phase 1 (amended August 21, 2003)
- 40 CFR Part 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos
- 40 CFR Part 64, Compliance Assurance Monitoring Program
- 40 CFR Part 82, Subpart F, Stratospheric Ozone

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

A. Rules Added

No rules were added.

B. Rules Updated

1. District Rule 4694, Wine Fermentation and Storage Tanks

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any winery fermenting wine and/or storing wine in bulk containers.

The rule was adopted on December 15, 2005 and submitted to EPA for approval into the State Implementation Plan (SIP). On August 18, 2011, the District approved an amended SIP submittal which excludes the fermentation provisions of the rule while maintaining the storage provisions. Therefore, the fermentation provisions are not federally enforceable. All other provisions are federally enforceable and will be discussed in Section VIII of this application

review under District Rule 4694.

The following conditions are based on this rule and are not Federally Enforceable through Title V:

C-581-0-2	Conditions 43 - 48
-----------	--------------------

2. Title 17 CCR, Section 93115 - Airborne Toxic Control Measure (ATCM) for Stationary Compression-Ignition (CI) Engines (amended May 19, 2011)

The following conditions are based on this rule and are not Federally Enforceable through Title V:

C-581-2-2	Conditions 5 and 15 through 17
-----------	--------------------------------

C. Rules Not Updated

- District Rule 4102, Nuisance (amended December 17, 1992)

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the last renewed Title V permit.

1. District Rule 2020 - Exemptions

District Rule 2020 lists equipment which is specifically exempt from obtaining permits and specifies record keeping requirements to verify such exemptions. The amendments to this rule do not have any affect on current permit requirements and will therefore not be addressed in this evaluation.

2. District Rule 2201 - New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this facility's last renewed Title V permit was issued. This Title V permit renewal does not constitute a modification per section 3.26, defined as an action including at least one of the following items:

- 1) Any change in hours of operation, production rate, or method of operation of an existing emissions unit, which would necessitate a change in permit conditions.

- 2) Any structural change or addition to an existing emissions unit which would necessitate a change in permit conditions. Routine replacement shall not be considered to be a structural change.
- 3) An increase in emissions from an emissions unit caused by a modification of the Stationary Source when the emissions unit is not subject to a daily emissions limitation.
- 4) Addition of any new emissions unit which is subject to District permitting requirements.
- 5) A change in a permit term or condition proposed by an applicant to obtain an exemption from an applicable requirement to which the source would otherwise be subject.

Since the current action does not constitute a modification, the updated requirements of this rule are not applicable at this time.

3. District Rule 2410 – Prevention of Significant Deterioration

The prevention of significant deterioration (PSD) program is a preconstruction permitting program for new major stationary sources and major modifications to existing major stationary sources located in areas classified as attainment or in areas that are unclassifiable for any criteria air pollutant. The provisions of this rule apply to any source and the owner or operator of any source subject to any requirement under Title 40 Code of Federal Regulations (40 CFR) Part 52.21 as incorporated into this rule.

The requirements of this rule cannot be triggered by the renewal of a Title V permit, since permit renewal does not involve any construction or modification of the stationary source. A detailed analysis or applicability determination is therefore not required.

4. District Rule 2520 – Federally Mandated Operating Permits

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

5. District Rule 4621 – Gasoline Transfer into Stationary Containers, Delivery Vessels and Bulk Plants

This rule applies to storage containers located at bulk plants with capacities greater than 250 gallons and less than 19,800 gallons; to other stationary

storage containers with capacities greater than 250 gallons; and to those storage containers that are not subject to the control requirements of Rule 4623 (Storage of Organic Liquids) Section 5.0. The rule also applies to gasoline delivery vessels.

The current SIP version of the rule was last amended on December 20, 2007. The current version of the rule was amended on December 19, 2013, but has not yet been approved into the SIP.

The analysis in Attachment E shows that the proposed requirements of the current non-SIP version of this rule that are applicable to the permit units at this facility are as stringent as, or more stringent than the requirements of the existing SIP version. Only some requirements in the Exemptions section (4.0) and the Bulk Plants and Loading Racks at Bulk Plants section (5.6) were less stringent in the non-SIP version of the rule. This facility does not have any permit units that are subject to sections 4.0 or 5.6. Streamlining procedures are utilized to substitute the set of requirements in the current non-SIP version of the rule for the otherwise applicable requirements in the SIP version of the rule.

Section 5.1 requires that loading equipment and vapor collection equipment shall be installed, maintained, and operated such that it is leak-free, with no excess organic liquid drainage at disconnect.

Section 3.19.2 defines a leak as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.4.3. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.

Compliance is assured with the following conditions:

C-581-1-6	Conditions 4 and 5
-----------	--------------------

Section 5.2.1 requires that no person shall transfer, or permit the transfer, of gasoline from any delivery vessel into any stationary storage container subject to the requirements of this rule unless such container is equipped with an ARB certified permanent submerged fill pipe and utilizes an ARB certified Phase I vapor recovery system that is maintained and operated according to manufacturer specifications and the applicable ARB Executive Order.

Compliance is assured with the following conditions:

C-581-1-6	Condition 1
-----------	-------------

Section 5.4.1 requires that all aboveground storage containers shall be constructed and maintained in a leak-free condition.

Compliance is assured with the following conditions:

C-581-1-6	Condition 3
-----------	-------------

Section 5.5 requires that all Phase I vapor recovery systems shall be inspected according to the frequency specified in Table 1. The person conducting the inspections shall, at a minimum, verify that the fill caps and vapor caps are not missing, damaged, or loose, that the fill cap gasket and vapor cap gaskets are not missing or damaged, that the fill adapter and vapor adapter are securely attached to the risers, that, where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing, and the dry break (poppet-valve) is not missing or damaged and that the submerged fill tube is not missing or damaged.

Compliance is assured with the following conditions:

C-581-1-6	Conditions 10 and 11
-----------	----------------------

Section 5.7.2 requires that no person shall operate, or allow the operation of a delivery vessel unless valid State of California decals which attest to the vapor integrity of the container are displayed.

Compliance is assured with the following conditions:

C-581-1-6	Condition 6
-----------	-------------

Section 6.1.4 requires that all records required to demonstrate compliance with the requirements of this rule shall be retained on the premises for a minimum of five years and made available on site during normal business hours to the APCO, ARB, or EPA, and submitted to the APCO, ARB, or EPA upon request.

Compliance is assured with the following conditions:

C-581-1-6	Conditions 25 and 26
-----------	----------------------

Section 6.2.3 requires that operators shall notify the District at least seven days prior to any performance testing.

Section 6.2.4 requires that operators shall submit all performance test results to the District within 30 days of test completion.

Compliance is assured with the following conditions:

C-581-1-6	Condition 21
-----------	--------------

Section 6.3.1 requires that installation and maintenance contractors shall be certified by the ICC for Vapor Recovery System Installation and Repair (VI) and make available onsite proof of ICC certification for VI, and have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems, or work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available onsite a current certificate from the ICC, indicating he or she has passed the VI exam and all certifications required by the applicable Executive Order.

Section 6.3.2 requires that all ICC certifications shall be renewed every 24 months by passing the appropriate exam specific to the certification being sought.

Section 6.3.3 requires that gasoline dispensing facility testers wishing to conduct vapor recovery system testing and repair at facilities located within the District, shall be in full compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification).

Compliance is assured with the following conditions:

C-581-1-6	Conditions 18 through 20
-----------	--------------------------

6. District Rule 4622 - Gasoline Transfer into Motor Vehicle Fuel Tanks

This rule applies to any gasoline storage and dispensing operation or mobile fueler from which gasoline is transferred into motor vehicle fuel tanks.

The current SIP version of the rule was last amended on December 20, 2007. The current version of the rule was amended on December 19, 2013, but has not yet been approved into the SIP.

The analysis in Attachment F shows that the proposed requirements of the current non-SIP version of this rule that are applicable to the permit units at this facility are as stringent as, or more stringent than the requirements of the existing SIP version, with the exceptions addressed below:

Section 4.0 - Exemption:

As shown in the comparison table in Appendix F, the newly amended version of the rule provides two new exemptions (mobile fuelers registered under Permit-Exempt Equipment Registration program pursuant to Section 5.11 and d E85 fuel dispensing operations) and is therefore not as stringent as the SIP version of the rule in this section. However, this facility does not have any emissions units/operations that are exempt from the rule. The additional exemptions therefore have no effects on this facility.

Section 6.4 – Testing:

As shown in the comparison table in Appendix F, the newly amended version of the rule has reduced the testing frequency for the Dynamic Back-Pressure Test (6.4.1.2) from 'once every twelve months' to 'once every five years.' The newly amended version of the rule is therefore not as stringent as the SIP version in this requirement. The requirement from the SIP version of the rule will be retained on the permit. Upon approval of the newly amended version of the rule into the SIP, the permittee may submit an application to modify the testing frequency.

For the rest of the requirements, streamlining procedures are utilized to substitute the set of requirements in the current non-SIP version of the rule for the otherwise applicable requirements in the SIP version of the rule.

Section 5.1 requires that a person shall not transfer or permit the transfer of gasoline from any stationary storage container, or from any mobile fueler with a capacity greater than 120 gallons, into a motor vehicle fuel tank with a capacity greater than 5 gallons, unless the gasoline dispensing unit used to transfer the gasoline is equipped with and has in operation an ARB certified Phase II vapor recovery system.

Section 5.1.1 requires that all ARB certified Phase II vapor recovery systems shall be maintained according to ARB certifications and the manufacturer specifications applicable to the system.

Compliance is assured with the following conditions:

C-581-1-6	Condition 1
-----------	-------------

Section 5.1.2 requires that all ARB certified Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method in Section 6.5.4.

Section 6.5.4 requires that detection of leaks shall be in accordance with EPA Test Method 21.

Section 3.17 defines a leak as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.5.4. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.

Compliance is assured with the following conditions:

C-581-1-6	Conditions 4 and 5
-----------	--------------------

Section 5.2.3 requires that "installation and maintenance contractors shall, be certified by the ICC for Vapor Recovery System Installation and Repair, renew the ICC certification for Vapor Recovery System Installation and Repair every 24 months, make available onsite proof of ICC certification, and have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems.

Section 5.2.4 requires that in lieu of complying with Sections 5.2.3.1 through 5.2.3.4, installation and maintenance contractors may work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available on site current certifications from the ICC, indicating he or she has passed the ICC Vapor Recovery System Installation and Repair exam and all other certifications required by the applicable Executive Order.

Compliance is assured with the following conditions:

C-581-1-6	Conditions 19 and 20
-----------	----------------------

Section 5.3.1 states the owner or operator of an ARB certified Phase II vapor recovery system shall conduct periodic maintenance inspections to ensure that components of the vapor recovery system are in proper operating condition.

Section 5.3.2 requires that the frequency of inspections shall be based on the operation's largest monthly gasoline throughput from the previous calendar year.

Section 5.3.4 requires that the frequency of vapor path inspections shall be based on the amount of gasoline dispensed by the operation in a calendar month.

Section 5.3.5 requires that the person conducting the inspections shall at a minimum, verify that the fueling instructions required by Section 5.5 are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs, that the following nozzle components are in place and in good condition as specified in ARB Executive Orders: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, hold open latch, that the hoses are not torn, flattened or crimped, that the vapor path of coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid and that the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit.

Compliance is assured with the following conditions:

C-581-1-6	Conditions 10 and 12
-----------	----------------------

Section 5.4.1 requires that no person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order, until: The defect has been repaired, replaced, or adjusted as necessary to correct the defect; The District has been notified, and the District has reinspected the system or authorized the system for use. Such authorization shall not include the authority to operate the equipment prior to the correction of the defective components; and all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual.

Compliance is assured with the following conditions:

C-581-1-6	Condition 7
-----------	-------------

Section 5.4.2 requires that upon identification of any major defects, the owner or operator shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired.

Section 5.4.2.1 requires that tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary.

Section 5.4.2.2 requires that in the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use.

Compliance is assured with the following conditions:

C-581-1-6	Condition 8
-----------	-------------

Section 5.4.4 requires that in the event of a separation due to a drive off, the owner or operator shall complete one of the following, unless otherwise specified in the applicable ARB Executive Order, and document the activities in accordance with Section 6.2, before placing the affected equipment back in service:

- 1) Conduct a visual inspection of the affected equipment, perform qualified repairs on any damaged components, and conduct applicable re-verification tests pursuant to Sections 6.5.1.1 and 6.5.1.4, or
- 2) Conduct a visual inspection of the affected equipment and replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified, before placing affected equipment back in service.

Compliance is assured with the following conditions:

C-581-1-6	Condition 13
-----------	--------------

Section 6.2.1 requires that operators shall retain the test result verification that each ARB certified Phase II vapor recovery system meets or exceeds the requirements of the tests specified in Section 6.5. These verifications shall be maintained for at least five years. These test results shall be dated and shall contain the names, addresses, and telephone numbers of the companies responsible for system installation and testing.

Compliance is assured with the following conditions:

C-581-1-6	Condition 22
-----------	--------------

Section 6.2.2 requires that a person who performs repairs on any ARB certified Phase I or Phase II vapor recovery system shall provide to the owner

or operator a repair log, which the owner or operator shall maintain on the premises for at least five years and which shall include all of the following:

- 1) Date and time of each repair;
- 2) The name and applicable certification numbers of the person(s) who performed the repair, and, if applicable, the name, address and phone number of the person's employer;
- 3) Description of service performed;
- 4) Each component that was repaired, serviced, or removed;
- 5) Each component that was installed as replacement, if applicable;
- 6) Receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs.

Compliance is assured with the following conditions:

C-581-1-6	Condition 23
-----------	--------------

Section 6.2.3 requires that each operator who is required to perform periodic maintenance inspections under Section 5.3 shall maintain monthly gasoline throughput records on the premises for a minimum of five years, make them available on site during normal business hours to the APCO, ARB, or EPA, and submit them to the APCO, ARB, or EPA upon request.

Compliance is assured with the following conditions:

C-581-1-6	Conditions 25 and 26
-----------	----------------------

Section 6.3.1 requires that the owner or operator of a gasoline dispensing operation shall maintain an O&M Manual in accordance with Section 6.3.

Section 6.3.2 requires that the O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request.

Section 6.3.3 requires that the O&M manual shall, at a minimum, include the following current information:

- 1) Copies of all vapor recovery performance tests,

- 2) All applicable ARB Executive Orders, Approval Letters, and District Permits,
- 3) Manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer,
- 4) System and/or component testing requirements, including test schedules and passing criteria for each of the standard tests listed in Section 6.0. The owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements, and
- 5) Additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components.

Section 6.3.4 requires that owners or operators of gasoline dispensing operations shall document the periodic maintenance inspection program in the O&M manual.

Compliance is assured with the following conditions:

C-581-1-6	Conditions 9, 17 and 24
-----------	-------------------------

The current SIP version of the rule, section 6.4.1.2 requires that operators conduct and pass a Dynamic Back-Pressure Test of the ARB certified Phase II vapor recovery system at least once every twelve months except for those aboveground storage tanks that have integral dispensers (non-remote), unless otherwise required under ARB Executive Order.

The newly amended version of the rule (December 19, 2013), section 6.4.1.2 requires that operators conduct and pass a Dynamic Back-Pressure Test of the ARB certified Phase II vapor recovery system at least once every five years except for those aboveground storage tanks that have integral dispensers (non-remote), unless otherwise required under ARB Executive Order.

Since the proposed amendment is less stringent than the existing SIP requirement, it cannot be implemented through the Title V permit at this point. The testing frequency stipulated in the SIP version of the rule will be retained on the permit. Upon approval of the amended version of the rule into the SIP, the permittee may submit an application to modify the testing frequency.

Compliance is assured with the following conditions:

C-581-1-6	Condition 16
-----------	--------------

Section 6.4.4 requires that persons responsible for conducting the tests specified in Section 6.5 shall be in full compliance with all provisions of Rule 1177 (Gasoline Dispensing Facility Tester Certification).

Compliance is assured with the following conditions:

C-581-1-6	Condition 18
-----------	--------------

7. District Rule 4694 – Wine Fermentation and Storage Tanks

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any winery fermenting wine and/or storing wine in bulk containers.

As previously discussed, on August 18, 2011 the District approved an amended SIP submittal which excludes the fermentation provisions of District Rule 4694 while maintaining the storage provisions. Therefore, only the storage provisions are federally enforceable and will be discussed below.

Section 5.2 states that owners or operators of any wine storage tank having an internal volume equal to or greater than 5,000 gallons shall comply with the following requirements when storing wine:

- 5.2.1 The tank shall be equipped and operated with a pressure-vacuum relief valve meeting all of the following requirements:
- The pressure-vacuum relief valve shall operate within 10% of the maximum allowable working pressure of the tank,
 - The pressure-vacuum relief valve shall operate in accordance with the manufacturer's instructions, and
 - The pressure-vacuum relief valve shall be permanently labeled with the operating pressure settings.
 - The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21.

5.2.2 The temperature of the stored wine shall be maintained at or below 75° F.

- Temperature of the stored wine shall be determined and recorded at least once per week.
- For each batch of wine, operators shall achieve the storage temperature of 75° F or less within 60 days after completing fermentation.

Storage tanks C-581-4 through -6 have an internal volume less than 5,000 gallons and are therefore not subject to these requirements.

Compliance is assured with the following conditions:

C-581-7 through -111	Conditions 1 through 3
----------------------	------------------------

Section 6.4 states that commencing January 1, 2007, the following records shall be maintained, retained on-site for a minimum of five years, and made available to the APCO upon request:

6.4.2 For each storage tank, operators shall record the following information on a weekly basis:

- Total gallons of wine contained in the tank, and
- Maximum temperature of the stored wine.

Compliance is assured with the following conditions:

C-581-4 through -111	Conditions 15 and 19
----------------------	----------------------

8. District Rule 4702 – Internal Combustion Engines

The purpose of this rule is to limit the emissions of nitrogen oxides (NOx), carbon monoxide (CO), volatile organic compounds (VOC), and sulfur oxides (SOx) from internal combustion engines.

This rule applies to any internal combustion engine rated at 25 brake horsepower or greater.

The current SIP version of the rule was last amended on January 18, 2007. The current version of the rule was amended on November 14, 2013, but has not yet been approved into the SIP.

The analysis in Attachment D shows that the proposed requirements of the current non-SIP version of this rule are as stringent as, or more stringent than

the requirements of the existing SIP version. Streamlining procedures are utilized to substitute the set of requirements in the current non-SIP version of the rule for the otherwise applicable requirements in the SIP version of the rule.

Pursuant to Section 4.3, except for the requirements of Section 6.2.3, the requirements of this rule shall not apply to an internal combustion engine that meets the following conditions:

- 1) The engine is operated exclusively to preserve or protect property, human life, or public health during a disaster or state of emergency, such as a fire or flood, and
- 2) Except for operations associated with Section 4.3.1.1, the engine is limited to operate no more than 100 hours per calendar year as determined by an operational nonresettable elapsed operating time meter, for periodic maintenance, periodic readiness testing, and readiness testing during and after repair work of the engine, and
- 3) The engine is operated with a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.

Section 6.2.3 requires that an owner claiming an exemption under Section 4.2 or Section 4.3 shall maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and submitted to the APCO upon request and at the end of each calendar year in a manner and form approved by the APCO. The records shall include, but are not limited to, the following:

- Total hours of operation,
- The type of fuel used,
- The purpose for operating the engine,
- For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and
- Other support documentation necessary to demonstrate claim to the exemption.

Compliance is assured with the following conditions:

C-581-2-2	Conditions 2, 4, 6, 14 and 18
-----------	-------------------------------

9. 40 CFR 63 Subpart ZZZZ – National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

Emergency engines are subject to this subpart if they are operated at a major or area source of Hazardous Air Pollutant (HAP) emissions. A major source of HAP emissions is a facility that has the potential to emit any single HAP at a rate of 10 tons/year or greater or any combinations of HAPs at a rate of 25 tons/year or greater. An area source of HAPs is a facility is not a major source of HAPs.

Pursuant to section 63.6603(a), the owner or operator of an existing (constructed prior to June 12, 2006) stationary reciprocating internal combustion engine (RICE) located at an area source of HAP emissions, must comply with the requirements in Table 2d to this subpart. Pursuant to Table 2d row 4, the following requirements are applicable to emergency stationary CI RICE:

- Change oil and filter every 500 hours of operation or annually, whichever comes first
- Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first, and replace as necessary
- Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary

Pursuant to Section 63.6625(e)(3), the owner or operator of an emergency stationary RICE must operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop their own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.

Pursuant to Section 63.6625(f), the owner or operator of an existing emergency stationary RICE located at an area source of HAP emissions must install a non-resettable hour meter if one is not already installed.

Pursuant to Section 63.6625(h), the owner or operator must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes.

Pursuant to Section 63.6625(i), the owner or operator of an existing emergency stationary RICE located at an area source of HAP emissions may have the option of utilizing an oil analysis program in order to extend the

specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.

Pursuant to Section 63.6640(a), the owner or operator of an existing emergency stationary RICE located at an area source of HAP emissions may demonstrate on-going compliance with the requirements of this subpart by operating and maintaining the stationary RICE according to the manufacturer's emission-related operation and maintenance instructions; or developing and following their own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions (Table 6 row 9).

Pursuant to Section 63.6640(f): 1) There is no time limit on the use of emergency stationary RICE in emergency situations; and 2) An emergency stationary RICE may be operated for maintenance checks and readiness testing, emergency demand response, and other non-emergency situations up to a maximum of 100 hours per calendar year.

Pursuant to Section 63.6655(a)(2), the owner or operator must maintain records the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment.

Pursuant to Section 63.6655(a)(4), the owner or operator must maintain records of all required maintenance performed on the air pollution control and monitoring equipment.

Pursuant to Section 63.6655(a)(5), the owner or operator must maintain records of actions taken during periods of malfunction to minimize emissions,

including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.

Pursuant to Section 63.6660, the owner or operator must maintain records in a form suitable and readily available for expeditious review, and readily accessible in hard copy or electronic form for at least 5 years.

Compliance is assured with the following conditions:

C-581-2-2	Conditions 1, 4, 6 through 14 and 18
-----------	--------------------------------------

10.40 CFR Part 64 – Compliance Assurance Monitoring

40 CFR Part 64 requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

- 1) The unit must have an emission limit for the pollutant;
- 2) The unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
- 3) The unit must have a pre-control potential to emit of greater than the major source thresholds.

a. C-581-1-6: Gasoline Dispensing Operation

This permit unit does not have any emissions limits or add-on controls for any pollutant that would cause the unit to be subject to this requirement. CAM is therefore not required.

b. C-581-2-2: 130 bhp Cummins Diesel-Fired Emergency IC Engine Powering a Fire Water Pump

This permit unit does not have any emissions limits or add-on controls for any pollutant that would cause the unit to be subject to this requirement. CAM is therefore not required.

c. C-581-4-3, -5-3, -6-3, 7-3, -8-3, -9-4, -10-3, -11-3, -12-3, -13-3, -14-3, -15-3, -16-3, -17-3, -18-3, -19-3, -20-3, -21-3, -22-3, -23-3, -24-3, -25-3, -26-3, -27-3, -28-3, -29-3, -30-3, -31-3, -32-3, -33-3, -34-3, -35-3, -36-3, -37-3, -38-3, -39-3, -40-3, -41-3, -42-3, -43-3, -44-3, -45-3, -46-3, -47-3, -48-3, -49-3, -50-3, -51-3, -52-3, -53-3, -54-3, -55-3, -56-3, -57-3, -58-3, -59-3, -60-3, -61-3, -62-3, -63-3, -64-3, -65-3, -66-3, -67-3, -68-3, -69-3, -70-3, -71-3, -72-3, -73-3, -74-3, -75-3, -76-3, -77-3, -78-3, -79-3, -80-3, -81-3, -82-3, -83-3, -84-3, -85-3, -86-3, -87-3, -88-3, -89-3,

-90-3, -91-3, -92-3, -93-3, -94-3, -95-3, -96-3, -97-3, -98-3, -99-3, -100-3, -101-3, -102-3, -103-3, -104-3, -105-3, -106-3, -107-3, -108-3, -109-3, -110-3, and -111-3: Wine Fermentation/Storage Tanks

These permit units do not have any emissions limits or add-on controls for any pollutant that would cause the units to be subject to this requirement. CAM is therefore not required.

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

By using the model general permit template listed in Section IV of this evaluation, the applicant has requested that a permit shield be issued for requirements addressed in the template. The basis for each permit shield is discussed in the Permit Shield section of each template.

B. Requirements not Addressed by Model General Permit Templates

The applicant is not requesting any new permit shields within this Title V renewal project. In addition, the applicant is not requesting any changes to the existing permit shields already included in their Title V operating permit. Therefore, all of the existing permit shields will be maintained on the revised permit for this renewal project.

X. PERMIT CONDITIONS

The draft renewed Title V operating permit is included as Attachment A.

XI. ATTACHMENTS

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Detailed Facility Report
- D. District Rule 4702 Stringency Analysis
- E. District Rule 4621 Stringency Analysis
- F. District Rule 4622 Stringency Analysis

ATTACHMENT A

Draft Renewed Title V Operating Permit

San Joaquin Valley Air Pollution Control District

FACILITY: C-581-0-2

EXPIRATION DATE: 07/31/2015

FACILITY-WIDE REQUIREMENTS

1. {2285} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {2286} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {2287} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {2289} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
6. {2290} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {2291} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {2292} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {2293} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: GOLDEN STATE VINTNERS
Location: 7409 W CENTRAL AVE, FRESNO, CA 93706
C-581-0-2: Dec 1 2015 2:56PM - AIYABEU

10. {2294} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {2295} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {2296} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {2297} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {2298} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {2299} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {2300} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {2301} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {2302} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {2303} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {2304} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {2305} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (2/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {2310} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {2311} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {2312} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/04) or Rule 8011 (8/19/04). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
35. {2319} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. {2320} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {2321} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {2322} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. {2323} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (12/17/09); 8021 (8/19/04); 8031 (8/19/04); 8041 (8/19/04); 8051 (8/19/04); 8061 (8/19/04); and 8071 (9/16/04). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin on August 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
44. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]
45. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2007, and every three years thereafter on or before July 1. [District Rule 4694]
46. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]
47. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than March 1, 2008, and every year thereafter on or before March 1. [District Rule 4694]
48. Operators using District Obtained Emission Reductions (DOER) shall submit payment of DOER and administrative fees to the District no later than March 1, of the first year in the applicable compliance period. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-1-6

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 15,000 GALLON SPLIT (5,000 GALLON GASOLINE/10,000 GALLON DIESEL) FIREGUARD ABOVEGROUND STORAGE TANK SERVED BY TWO-POINT PHASE I VAPOR RECOVERY SYSTEM (G-70-162), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY INTEGRATED HIRT VCS 200 PHASE II VAPOR RECOVERY SYSTEM (G-70-139)

PERMIT UNIT REQUIREMENTS

1. The Phase I and Phase II vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
4. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
5. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
7. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
9. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
11. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the fueling instructions required by this permit are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs; 2) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 3) the hoses are not torn, flattened or crimped; 4) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 5) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
13. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit
14. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District NSR Rule] Federally Enforceable Through Title V Permit
15. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

16. The permittee shall perform and pass a Dynamic Back Pressure Test using ARB TP-201.4 at least once every 12 months. [District Rule 4622] Federally Enforceable Through Title V Permit
17. The permittee shall perform the "Minimum Maintenance Requirements" for the Hirt VCS-200 from CARB Executive Order G-70-139, and shall record all maintenance activities in a maintenance log. [District Rule 4622] Federally Enforceable Through Title V Permit
18. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
19. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
22. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
23. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
24. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
26. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-2-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

130 HP CUMMINS MODEL #6BTA59F2 DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE WATER PUMP

PERMIT UNIT REQUIREMENTS

1. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
2. This engine shall be used exclusively for fire fighting purposes. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702; 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [17 CCR 93115]
6. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4701 and 4702; 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
8. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The permittee must maintain records of all required maintenance performed on the air pollution control and monitoring equipment. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions, including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
16. If this engine is located on the grounds of a K-12 school, or if this engine is located within 500 feet of the property boundary of a K-12 school, the engine shall not be operated for non-emergency purposes, including maintenance and testing, between 7:30 a.m. and 3:30 p.m. on days when school is in session. [17 CCR 93115]
17. If this engine is located on the grounds of a K-12 school, the engine shall not be operated for non-emergency purposes, including maintenance and testing, whenever there is a school sponsored activity. [17 CCR 93115]
18. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701 and 4702; 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-4-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

4,029 GALLON (POSTED 4,028 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0002 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-5-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

3,438 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0004 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-6-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

3,438 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0005 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201, and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-7-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

8,151 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0008 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-8-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

22,413 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0021 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-9-4

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

20,243 GALLON STAINLESS STEEL WINE FERMENTATION/STORAGE AND DISTILLED SPIRITS STORAGE TANK F0022 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method-21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
13. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
14. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
16. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-10-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

20,243 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0023 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-11-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

20,243 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0024 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-12-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

20,243 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0025 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-13-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P1 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
6. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-14-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P2 WITH
PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
6. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-15-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P3 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
6. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-16-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P4 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
6. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-17-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0181 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-18-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0182 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-19-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0183 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-20-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0184 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-21-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1001 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-22-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1002 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-23-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1003 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-24-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1004 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-25-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1005 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-26-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1006 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-27-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1011 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-28-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1012 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-29-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1013 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-30-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1014 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-31-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1015 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-32-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1016 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-33-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1017 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-34-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1018 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-35-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1022 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-36-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1023 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-37-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1024 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-38-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1025 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-39-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1026 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-40-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1027 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-41-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1028 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-42-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1029 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-43-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

200,326 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1991 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-44-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

200,487 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1992 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-45-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

200,487 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1993 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-46-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

200,487 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1994 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-47-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2001 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-48-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2002 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-49-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2003 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-50-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2004 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-51-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2010 WITH PRESSURE/VACUUM VALVE AND INSULATION

DRAFT

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-52-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2011 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-53-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2012 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-54-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2020 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-55-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2021 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-56-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2022 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-57-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3001 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-58-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3002 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-59-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3003 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-60-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3004 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-61-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3005 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-62-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3006 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-63-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3007 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-64-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3008 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-65-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3009 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-66-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3010 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-67-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3011 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-68-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3012 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-69-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3013 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-70-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3014 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-71-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3015 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-72-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3016 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-73-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3017 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-74-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3018 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-75-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3019 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-76-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3020 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-77-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3021 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-78-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3022 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-79-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3023 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-80-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3024 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-81-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3026 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-82-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3027 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-83-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3028 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-84-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3029 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-85-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3030 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-86-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3031 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-87-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3032 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-88-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3034 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-89-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3035 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-90-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3036 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-91-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3037 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-92-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3038 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-93-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3039 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-94-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3040 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-95-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3042 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-96-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3043 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-97-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3044 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-98-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3045 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-99-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3046 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-100-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9801 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-101-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9802 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-102-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9803 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-103-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9804 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-104-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9805 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-105-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9806 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-106-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9807 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-107-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9808 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-108-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9809 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-109-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9810 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-110-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9811 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-111-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9812 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

Golden State Vintners

C-581

C-1150057

ATTACHMENT B

Previous Title V Operating Permit



Permit to Operate

FACILITY: C-581

EXPIRATION DATE: 07/31/2015

LEGAL OWNER OR OPERATOR: GOLDEN STATE VINTNERS
MAILING ADDRESS: 7409 W CENTRAL AVE
FRESNO, CA 93706

FACILITY LOCATION: 7409 W CENTRAL AVE
FRESNO, CA 93706

FACILITY DESCRIPTION: WINERY

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

Arnaud Marjollet
Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: C-581-0-1

EXPIRATION DATE: 07/31/2015

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: GOLDEN STATE VINTNERS
Location: 7409 W CENTRAL AVE, FRESNO, CA 93706
C-581-0-1: Dec 1 2015 3:56PM - AIYABEU

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (2/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials for architectural coatings subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/04) or Rule 8011 (8/19/04). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/04) or Rule 8011 (8/19/04). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (12/17/09); 8021 (8/19/04); 8031 (8/19/04); 8041 (8/19/04); 8051 (8/19/04); 8061 (8/19/04); and 8071 (9/16/04). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. On July 31, 2010, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]
44. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]
45. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2007, and every three years thereafter on or before July 1. [District Rule 4694]
46. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]
47. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than March 1, 2008, and every year thereafter on or before March 1. [District Rule 4694]
48. Operators using District Obtained Emission Reductions (DOER) shall submit payment of DOER and administrative fees to the District no later than March 1, of the first year in the applicable compliance period. [District Rule 4694]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-1-4

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 15,000 GALLON SPLIT (5,000 GALLON GASOLINE/10,000 GALLON DIESEL) FIREGUARD ABOVEGROUND STORAGE TANK SERVED BY TWO-POINT PHASE I VAPOR RECOVERY SYSTEM (G-70-162), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY INTEGRATED HIRT VCS 200 PHASE II VAPOR RECOVERY SYSTEM (G-70-139)

PERMIT UNIT REQUIREMENTS

1. The Phase I and Phase II vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
4. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
5. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
7. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
9. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
11. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the fueling instructions required by this permit are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs; 2) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 3) the hoses are not torn, flattened or crimped; 4) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 5) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
13. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit
14. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District NSR Rule] Federally Enforceable Through Title V Permit
15. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

16. The permittee shall perform and pass a Dynamic Back Pressure Test using ARB TP-201.4 at least once every 5 years. [District Rule 4622]
17. The permittee shall perform the "Minimum Maintenance Requirements" for the Hirt VCS-200 from CARB Executive Order G-70-139, and shall record all maintenance activities in a maintenance log. [District Rule 4622] Federally Enforceable Through Title V Permit
18. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
19. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
22. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
23. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
24. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
26. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-2-1

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

130 HP CUMMINS MODEL #6BTA59F2 DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE WATER PUMP

PERMIT UNIT REQUIREMENTS

1. This engine shall be used exclusively for fire fighting purposes. [District Rule 4701] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [17 CCR 93115]
5. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4701 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
8. If this engine is located on the grounds of a K-12 school, or if this engine is located within 500 feet of the property boundary of a K-12 school, the engine shall not be operated for non-emergency purposes, including maintenance and testing, between 7:30 a.m. and 3:30 p.m. on days when school is in session. [17 CCR 93115]
9. If this engine is located on the grounds of a K-12 school, the engine shall not be operated for non-emergency purposes, including maintenance and testing, whenever there is a school sponsored activity. [17 CCR 93115]
10. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-4-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

4,029 GALLON (POSTED 4,028 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0002 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-5-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

3,438 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0004 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-6-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

3,438 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0005 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-7-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

8,151 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0008 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-8-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

22,413 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0021 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-9-3

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

20,243 GALLON STAINLESS STEEL WINE FERMENTATION/STORAGE AND DISTILLED SPIRITS STORAGE TANK F0022 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
13. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
14. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
16. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-10-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

20,243 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0023 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-11-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

20,243 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0024 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-12-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

20,243 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0025 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-13-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P1 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule2201] Federally Enforceable Through Title V Permit
3. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule2201] Federally Enforceable Through Title V Permit
4. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
6. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-14-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P2 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
6. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-15-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P3 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
4. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
6. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-16-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P4 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule2201] Federally Enforceable Through Title V Permit
3. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule2201] Federally Enforceable Through Title V Permit
4. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
6. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
7. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-17-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0181 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-18-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0182 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-19-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0183 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-20-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0184 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-21-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1001 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-22-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1002 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-23-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1003 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-24-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1004 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-25-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1005 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-26-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1006 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-27-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1011 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-28-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1012 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-29-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1013 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-30-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1014 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-31-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1015 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-32-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1016 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-33-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1017 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-34-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1018 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-35-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1022 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-36-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1023 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-37-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1024 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent; $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-38-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1025 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-39-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1026 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-40-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1027 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-41-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1028 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-42-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1029 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-43-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

200,326 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1991 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-44-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

200,487 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1992 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-45-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

200,487 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1993 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-46-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

200,487 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F1994 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-47-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2001 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-48-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2002 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-49-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2003 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-50-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2004 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-51-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F2010 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-52-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F2011 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-53-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F2012 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-54-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F2020 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-55-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F2021 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-56-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F2022 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-57-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3001 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-58-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3002 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-59-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3003 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-60-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3004 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-61-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3005 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-62-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3006 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-63-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3007 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-64-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3008 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-65-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3009 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-66-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3010 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-67-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3011 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-68-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3012 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-69-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3013 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-70-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3014 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-71-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3015 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-72-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3016 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-73-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3017 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-74-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3018 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-75-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3019 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-76-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3020 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-77-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3021 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-78-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3022 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-79-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3023 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-80-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3024 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-81-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3026 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-82-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3027 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-83-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3028 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-84-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3029 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-85-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3030 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-86-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3031 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-87-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3032 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-88-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3034 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-89-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3035 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-90-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3036 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-91-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3037 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-92-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3038 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-93-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3039 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-94-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3040 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-95-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3042 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-96-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3043 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-97-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3044 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-98-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3045 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-99-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE
FERMENTATION/STORAGE TANK F3046 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-100-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9801 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-101-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9802 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-102-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9803 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-103-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9804 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-104-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9805 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-105-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9806 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-106-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9807 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-107-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9808 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-108-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9809 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-109-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9810 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-110-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9811 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-581-111-2

EXPIRATION DATE: 07/31/2015

EQUIPMENT DESCRIPTION:

98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9812 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The daily VOC emissions rate for wine fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage and the tank capacity is greater than or equal to 200,000 gallons, the daily tank throughput shall not exceed the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage and the tank capacity is less than 200,000 gallons, the daily tank throughput shall not exceed twice the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 435,581 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: GOLDEN STATE VINTNERS

Location: 7409 W CENTRAL AVE, FRESNO, CA 93706

C-581-111-2 : Dec 1 2015 3:57PM -- AIYABEIJ

10. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Combined annual VOC emissions from all wine storage operations shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The annual VOC wine storage emission factor (EF) for each wine transfer shall be selected from the following emission factors based on the ethanol content of the wine transferred: For wine with ethanol content less than or equal to 14 volume percent: $EF = 0.150 \text{ lb-VOC}/1000 \text{ gallons}$; For wine with ethanol content greater than 14 volume percent, $EF = 0.248 \text{ lb-VOC}/1000 \text{ gallons}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
17. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
18. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Golden State Vintners

C-581

C-1150057

ATTACHMENT C

Detailed Facility Report

Detailed Facility Report
For Facility=581 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

GOLDEN STATE VINTNERS 7409 W CENTRAL AVE FRESNO, CA 93706	FAC # STATUS: TELEPHONE:	C 581 A 2092666548	TYPE: TOXIC ID:	TitleV	EXPIRE ON: AREA: INSP. DATE:	07/31/2015 6 / 310 03/16
--	---	---	----------------------------------	---------------	---	---

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-581-1-4	1 nozzle	3020-11 A	1	36.00	36.00	A	GASOLINE DISPENSING OPERATION WITH ONE 15,000 GALLON SPLIT (5,000 GALLON GASOLINE/10,000 GALLON DIESEL) FIREGUARD ABOVEGROUND STORAGE TANK SERVED BY TWO-POINT PHASE I VAPOR RECOVERY SYSTEM (G-70-162), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY INTEGRATED HIRT VCS 200 PHASE II VAPOR RECOVERY SYSTEM (G-70-139)
C-581-2-1	130 bhp IC engine	3020-10 B	1	123.00	123.00	A	130 HP CUMMINS MODEL #6BTA59F2 DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE WATER PUMP
C-581-4-2	4,029 gallon tank	3020-05 A	1	79.00	79.00	A	4,029 GALLON (POSTED 4,028 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0002 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-5-2	3,438 gallon tank	3020-05 A	1	79.00	79.00	A	3,438 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0004 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-6-2	3,438 Gallon Tank	3020-05 A	1	79.00	79.00	A	3,438 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0005 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-7-2	8,151 gallon tank	3020-05 B	1	98.00	98.00	A	8,151 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0008 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-8-2	22,413 gallon tank	3020-05 C	1	142.00	142.00	A	22,413 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0021 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-9-3	20,243 gallon tank	3020-05 C	1	142.00	142.00	A	20,243 GALLON STAINLESS STEEL WINE FERMENTATION/STORAGE AND DISTILLED SPIRITS STORAGE TANK F0022 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-10-2	20,243 gallon tank	3020-05 C	1	142.00	142.00	A	20,243 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0023 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-11-2	20,243 gallon tank	3020-05 C	1	142.00	142.00	A	20,243 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0024 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-12-2	20,243 gallon tank	3020-05 C	1	142.00	142.00	A	20,243 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0025 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-13-2	13,000 gallon tank	3020-05 B	1	98.00	98.00	A	13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P1 WITH PRESSURE/VACUUM VALVE
C-581-14-2	13,000 gallon tank	3020-05 B	1	98.00	98.00	A	13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P2 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=581 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-581-15-2	13,000 gallon tank	3020-05 B	1	98.00	98.00	A	13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P3 WITH PRESSURE/VACUUM VALVE
C-581-16-2	13,000 gallon tank	3020-05 B	1	98.00	98.00	A	13,000 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION TANK F00P4 WITH PRESSURE/VACUUM VALVE
C-581-17-2	18,890 gallon tank	3020-05 B	1	98.00	98.00	A	18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0181 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-18-2	18,890 gallon tank	3020-05 B	1	98.00	98.00	A	18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0182 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-19-2	18,890 gallon tank	3020-05 B	1	98.00	98.00	A	18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0183 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-20-2	18,890 gallon tank	3020-05 B	1	98.00	98.00	A	18,890 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F0184 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-21-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1001 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-22-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1002 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-23-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1003 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-24-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1004 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-25-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1005 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-26-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1006 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-27-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1011 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-28-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1012 WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=581 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-581-29-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1013 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-30-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1014 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-31-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1015 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-32-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1016 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-33-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1017 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-34-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1018 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-35-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1022 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-36-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1023 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-37-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1024 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-38-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1025 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-39-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1026 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-40-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1027 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-41-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1028 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-42-2	105,690 gallon tank	3020-05 E	1	258.00	258.00	A	105,690 GALLON (POSTED 106,241 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1029 WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=581 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-581-43-2	200,326 gallon tank	3020-05 E	1	258.00	258.00	A	200,326 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1991 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-44-2	200,487 gallon tank	3020-05 E	1	258.00	258.00	A	200,487 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1992 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-45-2	200,487 gallon tank	3020-05 E	1	258.00	258.00	A	200,487 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1993 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-46-2	200,487 gallon tank	3020-05 E	1	258.00	258.00	A	200,487 GALLON (POSTED 200,486 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F1994 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-47-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2001 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-48-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2002 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-49-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2003 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-50-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2004 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-51-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2010 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-52-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2011 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-53-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2012 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-54-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2020 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-55-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2021 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-56-2	216,191 gallon tank	3020-05 E	1	258.00	258.00	A	216,191 GALLON (POSTED 216,879 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F2022 WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=581 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-581-57-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3001 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-58-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3002 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-59-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3003 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-60-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3004 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-61-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3005 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-62-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3006 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-63-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3007 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-64-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3008 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-65-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3009 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-66-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3010 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-67-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3011 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-68-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3012 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-69-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3013 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-70-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3014 WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=581 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-581-71-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3015 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-72-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3016 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-73-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3017 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-74-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3018 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-75-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3019 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-76-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3020 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-77-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3021 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-78-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3022 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-79-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3023 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-80-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3024 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-81-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3026 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-82-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3027 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-83-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3028 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-84-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3029 WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=581 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-581-85-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3030 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-86-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3031 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-87-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3032 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-88-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3034 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-89-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3035 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-90-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3036 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-91-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3037 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-92-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3038 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-93-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3039 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-94-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3040 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-95-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3042 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-96-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3043 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-97-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3044 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-98-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3045 WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report
For Facility=581 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-581-99-2	348,949 gallon tank	3020-05 E	1	258.00	258.00	A	348,949 GALLON (POSTED 348,928 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F3046 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-100-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9801 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-101-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9802 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-102-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9803 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-103-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9804 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-104-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9805 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-105-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9806 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-106-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9807 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-107-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9808 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-108-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9809 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-109-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9810 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-110-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9811 WITH PRESSURE/VACUUM VALVE AND INSULATION
C-581-111-2	98,001 gallon tank	3020-05 D	1	194.00	194.00	A	98,001 GALLON (POSTED 98,000 GALLON) STAINLESS STEEL RED AND WHITE WINE FERMENTATION/STORAGE TANK F9812 WITH PRESSURE/VACUUM VALVE AND INSULATION

Number of Facilities Reported: 1

ATTACHMENT D

District Rule 4702 Stringency Analysis

Comparison of the Non-SIP version (amended November 14, 2013) of District Rule 4702 (Internal Combustion Engines) with the SIP approved version (amended January 18, 2007) of District Rule 4702 (Internal Combustion Engines)

Section	SIP Version of Rule 4702 (Amended January 18, 2007)	Non-SIP Version of Rule 4702 (Amended November 14, 2013)	Conclusion
1.0 Purpose	1.0 The purpose of this rule is to limit the emissions of nitrogen oxides (NOx), carbon monoxide (CO), and volatile organic compounds (VOC) from internal combustion engines.	1.0 The purpose of this rule is to limit the emissions of nitrogen oxides (NOx), carbon monoxide (CO), volatile organic compounds (VOC), and sulfur oxides (SOx) from internal combustion engines.	There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.
2.0 Applicability	2.0 This rule applies to any internal combustion engine with a rated brake horsepower greater than 50 horsepower.	2.0 This rule applies to any internal combustion engine rated at 25 brake horsepower or greater.	The SIP version does not apply to engines rated between 25 and 50 bhp. Therefore, the Non-SIP Version of the rule is more stringent.
4.0 Exemptions	<p>4.1 The requirements of this rule shall not apply to the following engines:</p> <p>4.1.1 An engine used to propel implements of husbandry, as that term is defined in Section 36000 of the California Vehicle Code, as that section existed on January 1, 2003.</p> <p>4.1.2 An engine used exclusively to power a wind machine.</p> <p>4.1.3 A de-rated spark-ignited engine not used in agricultural operations, provided the de-rating occurred before June 1, 2004.</p> <p>4.1.4 A de-rated spark-ignited engine used in agricultural operations or a de-rated compression-ignited engine, provided the de-rating occurred before June 1, 2005.</p> <p>4.1.5 An engine used exclusively to power Mobile Agricultural Equipment.</p> <p>4.2 Except for the requirements of Section 5.7 and Section 6.2.3, the requirements of this rule shall not apply to:</p> <p>4.2.1 An emergency standby engine as defined in Section 3.0 of this rule, and provided that it is operated with a nonresettable elapsed operating time meter. In lieu of a nonresettable time meter, the owner of an emergency engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.</p> <p>4.2.2 An internal combustion engine that is operated no more than 200 hours per</p>	<p>4.1 The requirements of this rule shall not apply to the following engines:</p> <p>4.1.1 An engine used to propel implements of husbandry, as that term is defined in Section 36000 of the California Vehicle Code, as that section existed on January 1, 2003.</p> <p>4.1.2 An engine used exclusively to power a wind machine.</p> <p>4.1.3 A de-rated spark-ignited engine not used in agricultural operations, provided the de-rating occurred before June 1, 2004.</p> <p>4.1.4 A de-rated spark-ignited engine used in agricultural operations or a de-rated compression-ignited engine, provided the de-rating occurred before June 1, 2005.</p> <p>4.1.5 An engine used exclusively to power Mobile Agricultural Equipment.</p> <p>4.1.6 An internal combustion engine registered as a portable emissions unit under the Statewide Portable Equipment Registration Program pursuant to California Code of Regulations Title 13, Division 3, Chapter 9, Article 5, Sections 2450-2465.</p> <p>4.1.7 An internal combustion engine registered as a portable emissions unit under Rule 2280 (Portable Equipment Registration).</p> <p>4.2 Except for the requirements of Sections 5.9 and 6.2.3, the requirements of this rule shall not apply to an emergency standby engine or a low-use engine, provided that the engine is operated with an operating nonresettable elapsed time meter.</p> <p>4.2.1 In lieu of operating a nonresettable elapsed time meter, the operator may</p>	The non-SIP version of this rule includes several operations that are not required to meet the requirements of this rule. These operations were added to clarify what operations are subject to this rule. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.

calendar year as determined by an operational nonresettable elapsed operating time meter and provided the engine is not used to perform any of the functions specified in Section 4.2.2.1 through Section 4.2.2.3 below. In lieu of a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.

- 4.2.2.1 To generate electrical power that is either fed into the electrical utility power grid or used to reduce electrical power purchased by a stationary source,
 - 4.2.2.2 To generate mechanical power that is used to reduce electrical power purchased by a stationary source, or
 - 4.2.2.3 In a distributed generation application.
- 4.3 Except for the administrative requirements of Section 6.2.3, the requirements of this rule shall not apply to:
- 4.3.1 An internal combustion engine that meets the following conditions:
 - 4.3.1.1 The engine is operated exclusively to preserve or protect property, human life, or public health during a disaster or state of emergency, such as a fire or flood, and
 - 4.3.1.2 Except for operations associated with Section 4.3.1.1, the engine is limited to operate no more than 100 hours per calendar year as determined by an operational nonresettable elapsed operating time meter, for periodic maintenance, periodic readiness testing, and readiness testing during and after repair work of the engine, and
 - 4.3.1.3 The engine is operated with a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.
 - 4.3.2 An internal combustion engine registered as a portable emissions unit under Rule 2280 (Portable Equipment

use an alternative device, method, or technique, in determining operating time, provided that the alternative is approved by the APCO and EPA and is allowed by the Permit-to-Operate or Permit-Exempt Equipment Registration. The operator must demonstrate that the alternative device, method, or technique is equivalent to using a nonresettable elapsed time meter.

- 4.2.2 The operator shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions.
- 4.3 Except for the administrative requirements of Section 6.2.3, the requirements of this rule shall not apply to the following:
- 4.3.1 An internal combustion engine that meets the following conditions:
 - 4.3.1.1 The engine is operated exclusively to preserve or protect property, human life, or public health during a disaster or state of emergency, such as a fire or flood; and
 - 4.3.1.2 Except for operations associated with Section 4.3.1.1, the engine is limited to operate no more than 100 hours per calendar year as determined by an operational nonresettable elapsed time meter, for periodic maintenance, periodic readiness testing, and readiness testing during and after repair work of the engine; and
 - 4.3.1.3 The engine is operated with an operational nonresettable elapsed time meter. In lieu of installing a nonresettable elapsed time meter, the operator of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and EPA. The operator of the engine shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions.
 - 4.3.2 Military Tactical Equipment and engines used to retract military aircraft arresting gear cables.
- 4.4 For existing facilities, a replacement unit installed for the sole purpose of complying with the requirements of this rule shall be considered to be an emission control technique and shall be exempt from the Best Available Control Technology (BACT) and offsets requirements of District Rule 2201 (New and Modified Stationary Source Review Rule) provided that all other requirements of Rule 2201 are met.
- 4.5 Except for the requirements of Section 5.1,

	<p>Registration) or the Statewide Portable Equipment Registration Program pursuant to Sections 2450-2465, Article 5, Title 13, California Code of Regulations.</p> <p>4.3.3 Military Tactical Equipment and engines used to retract military aircraft arresting gear cables.</p> <p>4.4. A replacement engine installed for the sole purpose of complying with the requirements of this rule shall be exempt from the Best Available Control Technology (BACT) and Offsets requirements of District Rule 2201 (New and Modified Stationary Source Review Rule) provided that all of the following conditions are met:</p> <p>4.4.1 The replacement engine is of equal or lesser horsepower rating of the engine being replaced,</p> <p>4.4.2 The replacement engine is subject to the same operational parameters (e.g. hours of operation, fuel use limitations, etc.) as the engine being replaced,</p> <p>4.4.3 The replacement engine performs the same function as the engine being replaced, and</p> <p>4.4.4 The emissions of the replacement engine are no greater than the emissions of the engine being replaced.</p>	<p>the requirements of this rule shall not apply to stationary engines rated at least 25 Brake Horsepower, up to, and including 50 Brake Horsepower.</p>	
<p>5.0 Requirements</p>	<p>Note: Section 5.0 requirements refer to Tables 1 through 4, which list the emission limits/standards for various categories of IC engines subject to this rule. These Tables are included at the end of this Stringency Comparison for each version of the rule.</p> <p>N/A</p>	<p>5.1 Stationary Engines Rated at Least 25 Brake Horsepower, Up To, and Including 50 Brake Horsepower and Used in Non-Agricultural Operations (Non-AO)</p> <p>5.1.1 On and after July 1, 2012, no person shall sell or offer for sale any non-AO spark-ignited engine or any non-AO compression-ignited engine unless the engine meets the applicable requirements and emission limits specified in 40 Code of Federal Regulation (CFR) 60 Subpart IIII (Standards of Performance for Stationary Compression Ignition Internal Combustion Engines) and 40 CFR 60 Subpart JJJJ (Standards of Performance for Stationary Spark Ignition Internal Combustion Engines) for the year in which the ownership of the engine changes.</p> <p>5.1.2 By January 1, 2013, the operator shall submit a one-time report that includes the number of engines at the stationary source, and the following information for each engine:</p> <p>5.1.2.1 Location of each engine, 5.1.2.2 Engine manufacturer, 5.1.2.3 Model designation and engine</p>	<p>The SIP version does not apply to engines rated between 25 and 50 bhp. Therefore, the Non-SIP Version of the rule is more stringent.</p>

		<p>serial number,</p> <p>5.1.2.4 Rated brake horsepower,</p> <p>5.1.2.5 Type of fuel and type of ignition,</p> <p>5.1.2.6 Combustion type: rich-burn, lean-burn, or compression ignition,</p> <p>5.1.2.7 Purpose, and intended use, of the engine,</p> <p>5.1.2.8 Typical daily operating schedule, and</p> <p>5.1.2.9 Fuel consumption (cubic feet for gas or gallons for liquid fuel) for the previous one-year period.</p>	
	<p>5.1 Engine Emission Limits/Standards</p> <p>5.1.1 Spark-Ignited Internal Combustion Engine Emission Limits/Standards - The owner of a spark-ignited internal combustion engine shall not operate it in such a manner that results in emissions exceeding the limits in Table 1 below for the appropriate engine type according to the compliance schedules listed in Section 7.0 or according to the compliance dates specified in Table 1 below. A spark-ignited engine shall comply with the applicable emission limits pursuant to Section 5.1 or Section 8.0.</p>	<p>5.2 Engines Rated at Greater than 50 Brake Horsepower (>50 bhp)</p> <p>5.2.1 Spark Ignited Engines Used in non-AO - Table 1 Emission Limits/Standards</p> <p>The operator of a spark-ignited internal combustion engine rated at >50 bhp that is used exclusively in non-AO shall not operate it in such a manner that results in emissions exceeding the limits in Table 1 for the appropriate engine type until such time that the engine has demonstrated compliance with Table 2 emission limits pursuant to the compliance deadlines in Section 7.5. In lieu of complying with Table 1 emission limits, the operator of a spark-ignited engine shall comply with the applicable emission limits pursuant to Section 8.0.</p> <p>5.2.2 Spark-Ignited Engines Used in non-AO - Table 2 Emission Limits/Standards</p> <p>On and after the compliance schedule specified in Section 7.5, the operator of a spark-ignited engine > 50 bhp that is used in non-AO shall comply with all the applicable requirements of the rule and one of the following, on an engine-by-engine basis:</p> <p>5.2.2.1 On and after the compliance schedule specified in Section 7.5, the operator of a spark-ignited engine that is used exclusively in non-AO shall comply with Sections 5.2.2.1.1 through 5.2.2.1.3 on an engine-by-engine basis:</p> <p>5.2.2.1.1 NOx, CO, and VOC emission limits pursuant to Table 2;</p> <p>5.2.2.1.2 SOx control requirements of Section 5.7, pursuant to the deadlines specified in Section 7.5; and</p> <p>5.2.2.1.3 Monitoring requirements of Section 5.10, pursuant to the deadlines specified in Section 7.5.</p> <p>5.2.2.2 In lieu of complying with the NOx emission limit requirement of Section 5.2.2.1.1, an operator may pay an annual fee to the District, as specified in Section 5.6, pursuant to Section 7.6.</p>	<p>The requirements of Table 1 of both versions of the rule are identical. Table 2 from the non-SIP version found at the end of this document has emissions requirements that are more stringent than the requirements of Table 1 in both versions of the Rule. The standards of the non-SIP version are at least as stringent as the SIP version. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.</p>

		<p>5.2.2.2.1 Engines in the fee payment program shall have actual emissions not greater than the applicable limits in Table 1 during the entire time the engine is part of the fee payment program.</p> <p>5.2.2.2.2 Compliance with Section 5.7 and 5.10, pursuant to the deadlines specified in Section 7.5, is also required as part of the fee payment option.</p> <p>5.2.2.3 In lieu of complying with the NO_x, CO, and VOC limits of Table 2 on an engine-by-engine basis, an operator may elect to implement an alternative emission control plan pursuant to Section 8.0. An operator electing this option shall not be eligible to participate in the fee payment option outlined in Section 5.2.2.2 and Section 5.6.</p> <p>5.2.3 Spark-Ignited Engines Used Exclusively in Agricultural Operations (AO)</p> <p>5.2.3.1 The operator of a spark-ignited internal combustion engine rated at >50 bhp that is used exclusively in AO shall not operate it in such a manner that results in emissions exceeding the limits in Table 3 for the appropriate engine type on an engine-by-engine basis.</p> <p>5.2.3.2 In lieu of complying with the NO_x, CO, and VOC limits of Table 3 on an engine-by-engine basis, an operator may elect to implement an alternative emission control plan pursuant to Section 8.0.</p> <p>5.2.3.3 An operator of an AO spark-ignited engine that is subject to the applicable requirements of Table 3 shall not replace such engine with an engine that emits more emissions of NO_x, VOC, and CO, on a ppmv basis, (corrected to 15% oxygen on a dry basis) than the engine being replaced.</p>	
--	--	--	--

	<p>5.1.2 Compression-Ignited Internal Combustion Engine Emission Limits/Standards and Compliance Schedules – The owner of a compression-ignited internal combustion engine shall repower, replace or control the engine to comply with the applicable limits/standards and compliance dates in Table 2 below. The annual hours of operation shall be determined on a calendar year basis. A compression-ignited engine shall comply with the applicable emission limits/standards pursuant to Section 5.1.2 or Section 8.0.</p> <p>5.1.3 On and after June 1, 2006, the owner of an AO rich-burn spark-ignited engine, AO lean-burn spark-ignited engine, or AO compression-ignited engine that is subject to the requirements of Section 5.1 shall not replace such engine with a rich-burn spark-ignited, lean-burn spark-ignited, or compression-ignited engine, respectively, that emits more emissions of NOx, VOC, and CO, on a ppmv basis, (corrected to 15% oxygen on a dry basis) than the engine being replaced.</p> <p>5.1.4 The owner of a non-certified compression-ignited engine, in place on June 1, 2006, shall comply with the Emission Limit/Standard and Compliance Date in Table 2 based on the non-certified compression-ignited engine that was in place on June 1, 2006, unless the owner meets one of the following conditions:</p> <p>5.1.4.1 Replaces the non-certified compression-ignited engine with a non-modified Tier 3 or a non-modified Tier 4 engine after June 1, 2006,</p> <p>5.1.4.2 Controls the non-certified compression-ignited engine after June 1, 2006, to emit emissions less than, or equal to, 80 ppm NOx, 2,000 ppm CO, and 750 ppm VOC, (corrected to 15% oxygen on a dry basis), or</p> <p>5.1.4.3 Replaces the non-certified compression-ignited engine after June 1, 2006, with an engine or other source with emissions less than, or equal to, 80 ppm NOx, 2,000 ppm CO, and 750 ppm VOC (corrected to 15% oxygen on a dry basis).</p>	<p>5.2.4 Certified Compression-Ignited Engines (AO and non-AO)</p> <p>The operator of a certified compression-ignited engine rated >50 bhp shall comply with the following requirements:</p> <p>5.2.4.1 Repower, replace, or control the engine's emissions to comply with the applicable limits/standards in Table 4 on an engine-by-engine basis by the compliance dates as specified in Table 4.</p> <p>5.2.4.2 The annual hours of operation shall be determined on a calendar year basis.</p> <p>5.2.4.3 In lieu of complying with the NOx, CO, and VOC limits of Table 4 on an engine-by-engine basis, an operator may elect to implement an alternative emission control plan pursuant to Section 8.0.</p> <p>5.2.4.4 An operator of an AO compression-ignited engine that is subject to the applicable requirements of Table 4 shall not replace such engine with an engine that emits more emissions of NOx, VOC, and CO, on a ppmv basis, (corrected to 15% oxygen on a dry basis) than the engine being replaced.</p> <p>5.2.5 Non-Certified Compression-Ignited Engines (AO and Non-AO) The operator of a non-certified compression-ignited engine, in place on or before June 1, 2006, shall comply with the Emission Limit/Standard and Compliance Date in Table 4 based on the non-certified compression ignited engine that was in place on June 1, 2006, unless the operator meets one of the following conditions:</p> <p>5.2.5.1 Replace the non-certified compression-ignited engine with a nonmodified Tier 3 or a non-modified Tier 4 engine after June 1, 2006;</p> <p>5.2.5.2 Control the non-certified compression-ignited engine after June 1, 2006, to emit emissions less than, or equal to, 80 ppmv NOx, 2,000 ppmv CO, and 750 ppmv VOC (corrected to 15% oxygen on a dry basis); or</p> <p>5.2.5.3 Replace the non-certified compression-ignited engine after June 1, 2006, with an engine or other source with emissions less than, or equal to, 80 ppmv NOx, 2,000 ppmv CO, and 750 ppmv VOC (corrected to 15% oxygen on a dry basis).</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
--	--	--	--

	<p>5.2 All continuous emission monitoring systems (CEMS) emissions measurements shall be averaged over a period of 15 consecutive minutes. Any 15-consecutive-minute block average CEMS measurement exceeding the applicable emission limits of this rule shall constitute a violation of this rule.</p> <p>5.3 Percent emission reductions, if used to comply with the NO_x emission limits of Section 5.1, shall be calculated as follows:</p> <p>5.3.1 For engines with external control devices that are not operated in combination with a second emission control device or technique, percent reduction shall be calculated using emission samples taken at the inlet and outlet of the control device.</p> <p>5.3.2 For engines without external control devices and for engines with an external control device in combination with a second emission control device or technique, percent reduction shall be based on source test results for the uncontrolled engine and the engine after the control device or technique has been employed. In this situation, the engine's typical operating parameters, loading, and duty cycle shall be documented and repeated at each successive post-control source test to ensure that the engine is meeting the percent reduction limit. When representative source sampling prior to the application of an emissions control technology or technique is not available, the APCO may approve the use of a manufacturer's uncontrolled emissions information or source sampling from a similar, uncontrolled engine.</p> <p>5.4 The owner of an internal combustion engine that uses percent emission reduction to comply with the NO_x emission limits of Section 5.1 shall provide an accessible inlet and outlet on the external control device or the engine as appropriate for taking emission samples and as approved by the APCO.</p>	<p>5.3 All continuous emission monitoring systems (CEMS) emissions measurements shall be averaged over a period of 15 consecutive minutes. Any 15-consecutive-minute block average CEMS measurement exceeding the applicable emission limits of this rule shall constitute a violation of this rule.</p> <p>5.4 Percent emission reductions, if used to comply with the NO_x emission limits of Section 5.2, shall be calculated as follows:</p> <p>5.4.1 For engines with external control devices that are not operated in combination with a second emission control device or technique, percent reduction shall be calculated using emission samples taken at the inlet and outlet of the control device.</p> <p>5.4.2 For engines without external control devices and for engines with an external control device in combination with a second emission control device or technique, percent reduction shall be based on source test results for the uncontrolled engine and the engine after the control device or technique has been employed. In this situation, the engine's typical operating parameters, loading, and duty cycle shall be documented and repeated at each successive post-control source test to ensure that the engine is meeting the percent reduction limit. When representative source sampling prior to the application of an emissions control technology or technique is not available, the APCO may approve the use of a manufacturer's uncontrolled emissions information or source sampling from a similar, uncontrolled engine.</p> <p>5.5 The operator of an internal combustion engine that uses percent emission reduction to comply with the NO_x emission limits of Section 5.2 shall provide an accessible inlet and outlet on the external control device or the engine as appropriate for taking emission samples and as approved by the APCO.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
<p>N/A</p>		<p>5.6 Payment of an Annual Fee In Lieu of Complying with a NO_x Emission Limit</p> <p>The operator of a non-AO spark-ignited engine who elects to comply under Section 5.2.2.2 shall comply with the requirements of Sections 5.6 by the schedule specified in Section 7.6 and all other applicable provisions of this rule.</p> <p>5.6.1 An operator shall pay a total annual fee to the District based on the total NO_x emissions from those engines that will be subject to Section 5.2.2.2. The annual fee shall be calculated in the following manner:</p> <p>5.6.1.1 The operator shall calculate the total emissions for all engines operating at a stationary source that will comply with Section 5.2.2.2. The total NO_x emissions</p>	<p>The annual fee option applies to units subject to Table 2.</p>

		<p>shall be calculated in accordance with Section 5.6.1.3.</p> <p>5.6.1.2 The total annual fee shall be calculated in accordance with Section 5.6.1.4. These calculations include only the units that have been identified to comply with Section 5.2.2.2.</p> <p>5.6.1.3 Total Emissions (TE) Calculation</p> $E(\text{engine}) = A \times B \times C \times D \times 2.147 \times 10^{-16}$ <p>Where:</p> <p>E (engine) = Annual NO_x emissions for each unit, in tons/year.</p> <p>A = NO_x emission limit for the Permit-to-Operate, in ppmvd corrected to 15% oxygen.</p> <p>B = Annual fuel use (ft³/year)</p> <p>C = Fuel higher heating value (Btu/ft³) – for natural gas use 1,000 Btu/ft³</p> <p>D = Fuel F-Factor at 60oF (Dscf/MMBtu) – for natural gas use 8,579 Dscf/MMBtu</p> $TE = \Sigma E(\text{engine})$ <p>Where:</p> <p>ΣE(engine) = Sum of all NO_x emissions from all units in the annual fee program, in tons per year.</p> <p>5.6.1.4 Total Annual Fee Calculation</p> $\text{Total Annual Fee} = (TE \times FR) + \text{Administrative Fee}$ <p>Where:</p> <p>TE = Total Emissions, in tons per year, as calculated in Section 5.6.1.3.</p> <p>FR (Fee Rate) = the cost of NO_x reductions, in dollars per ton, as established by District Rule 9510. Under no circumstances shall the cost per ton of NO_x reductions exceed the cost effectiveness threshold for the Carl Moyer Cost Effectiveness, as established by the applicable state law.</p> $\text{Administrative Fee} = 4\% \times (TE \times FR)$	
--	--	--	--

<p>5.5 California Reformulated Gasoline shall be used as the fuel for all gasoline-fired, spark-ignited internal combustion engines.</p>	<p>5.7 Sulfur Oxides (SOx) Emission Control Requirements</p> <p>On and after the compliance schedule specified in Section 7.5, operators of non-AO spark-ignited engines and non-AO compression-ignited engines shall comply with one of the following requirements:</p> <p>5.7.1 Operate the engine exclusively on PUC-quality natural gas, commercial propane, butane, or liquefied petroleum gas, or a combination of such gases; or</p> <p>5.7.2 Limit gaseous fuel sulfur content to no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet; or</p> <p>5.7.3 Use California Reformulated Gasoline for gasoline-fired spark-ignited engines; or</p> <p>5.7.4 Use California Reformulated Diesel for compression-ignited engines; or</p> <p>5.7.5 Operate the engine on liquid fuel that contains no more than 15 ppm sulfur, as determined by the test method specified in Section 6.4.6; or</p> <p>5.7.6 Install and properly operate an emission control system that reduces SO2 emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6.</p>	<p>The non-SIP version of this rule contains SOx emissions control requirements not found in the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
<p>5.6 Monitoring Requirements A</p> <p>The owner of a non-AO spark-ignited engine subject to the requirements of Section 5.1 or any engine subject to the requirements of Section 8.0 shall comply with the following requirements:</p> <p>5.6.1 For each engine with a rated brake horsepower of 1,000 hp or greater and which is allowed by Permit-to-Operate or Permit-Exempt Equipment Registration condition to operate more than 2,000 hours per calendar year, or with an external emission control device, either install, operate, and maintain continuous monitoring equipment for NOx, CO, and oxygen, as identified in Rule 1080 (Stack Monitoring), or install, operate, and maintain APCO-approved alternate monitoring. The monitoring system may be a continuous emissions monitoring system (CEMS), a parametric emissions monitoring system (PEMS), or an alternative monitoring system approved by the APCO. APCO-approved alternate monitoring shall consist of one or more of the following:</p> <p>5.6.1.1 Periodic NOx and CO emission concentrations,</p> <p>5.6.1.2 Engine exhaust oxygen concentration,</p> <p>5.6.1.3 Air-to-fuel ratio,</p> <p>5.6.1.4 Flow rate of reducing agents added to engine exhaust,</p> <p>5.6.1.5 Catalyst inlet and exhaust temperature,</p>	<p>5.8 Monitoring Requirements: Non-AO Spark-Ignited Engines and Engines in an AEC (Section 8.0)</p> <p>The operator of a non-AO spark-ignited engine subject to the requirements of Section 5.2 or any engine subject to the requirements of Section 8.0 shall comply with the following requirements:</p> <p>5.8.1 For each engine with a rated brake horsepower of 1,000 bhp or greater and which is allowed by Permit-to-Operate or Permit-Exempt Equipment Registration condition to operate more than 2,000 hours per calendar year, or with an external emission control device, either install, operate, and maintain continuous monitoring equipment for NOx, CO, and oxygen, as identified in Rule 1080 (Stack Monitoring), or install, operate, and maintain APCO approved alternate monitoring. The monitoring system may be a continuous emissions monitoring system (CEMS), a parametric emissions monitoring system (PEMS), or an alternative monitoring system approved by the APCO. APCO-approved alternate monitoring shall consist of one or more of the following:</p> <p>5.8.1.1 Periodic NOx and CO emission concentrations,</p> <p>5.8.1.2 Engine exhaust oxygen concentration,</p> <p>5.8.1.3 Air-to-fuel ratio,</p> <p>5.8.1.4 Flow rate of reducing agents added to engine exhaust,</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

	<p>5.6.1.6 Catalyst inlet and exhaust oxygen concentration, 5.6.1.7 Other operational characteristics.</p> <p>5.6.2 For each engine not subject to Section 5.6.1, monitor operational characteristics recommended by the engine manufacturer or emission control system supplier, and approved by the APCO.</p> <p>5.6.3 For each engine with an alternative monitoring system, submit to, and receive approval from the APCO, adequate verification of the alternative monitoring system's acceptability. This would include data demonstrating the system's accuracy under typical operating conditions for the specific application and any other information or data deemed necessary in assessing the acceptability of the alternative monitoring system.</p> <p>5.6.4 For each engine with an APCO approved CEMS, operate the CEMS in compliance with the requirements of 40 Code of Federal Regulations (CFR) Part 51, 40 CFR Parts 60.7 and 60.13 (except subsection h), 40 CFR Appendix B (Performance Specifications), 40 CFR Appendix F (Quality Assurance Procedures), and applicable provisions of Rule 1080 (Stack Monitoring).</p> <p>5.6.5 For each engine, have the data gathering and retrieval capabilities of an installed monitoring system described in Section 5.6 approved by the APCO.</p> <p>5.6.6 For each engine, install and operate a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and is allowed by Permit-to-Operate or Permit-Exempt Equipment Registration condition. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.</p> <p>5.6.7 For each engine, implement the Inspection and Monitoring (I&M) plan, if any, submitted to and approved by the APCO pursuant to Section 6.5.</p> <p>5.6.8 For each engine, collect data through the I&M plan in a form approved by the APCO.</p> <p>5.6.9 For each engine use a portable NOx analyzer to take NOx emission readings to verify compliance with the emission requirements of Section 5.1 or Section 8.0 during each calendar quarter in which a source test is not performed and the engine is operated. All emission readings shall be taken with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt</p>	<p>5.8.1.5 Catalyst inlet and exhaust temperature, 5.8.1.6 Catalyst inlet and exhaust oxygen concentration, or 5.8.1.7 Other operational characteristics.</p> <p>5.8.2 For each engine not subject to Section 5.8.1, monitor operational characteristics recommended by the engine manufacturer or emission control system supplier, and approved by the APCO.</p> <p>5.8.3 For each engine with an alternative monitoring system, submit to, and receive approval from the APCO, adequate verification of the alternative monitoring system's acceptability. This would include data demonstrating the system's accuracy under typical operating conditions for the specific application and any other information or data deemed necessary in assessing the acceptability of the alternative monitoring system.</p> <p>5.8.4 For each engine with an APCO approved CEMS, operate the CEMS in compliance with the requirements of 40 Code of Federal Regulations (CFR) Part 51, 40 CFR Parts 60.7 and 60.13 (except subsection h), 40 CFR Appendix B (Performance Specifications), 40 CFR Appendix F (Quality Assurance Procedures), and applicable provisions of Rule 1080 (Stack Monitoring).</p> <p>5.8.5 For each engine, have the data gathering and retrieval capabilities of an installed monitoring system described in Section 5.8 approved by the APCO.</p> <p>5.8.6 For each engine, install and operate a nonresettable elapsed time meter.</p> <p>5.8.6.1 In lieu of installing a nonresettable elapsed time meter, the operator may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and EPA and is allowed by a Permit-to- Operate or Permit-Exempt Equipment Registration condition.</p> <p>5.8.6.2 The operator shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions.</p> <p>5.8.7 For each engine, implement the Inspection and Monitoring (I&M) plan, if any, submitted to and approved by the APCO pursuant to Section 6.5.</p> <p>5.8.8 For each engine, collect data through the I&M plan in a form approved by the APCO.</p> <p>5.8.9 For each engine, use a portable NOx analyzer to take NOx emission readings to verify compliance with the emission requirements of Section 5.2 or Section 8.0 during each calendar quarter in which a</p>	
--	--	---	--

	<p>Equipment Registration. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. All NOx emissions readings shall be reported to the APCO in a manner approved by the APCO. NOx emission readings taken pursuant to this section shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15 consecutive-minute period.</p> <p>5.6.10 The APCO shall not approve an alternative monitoring system unless it is documented that continued operation within ranges of specified emissions-related performance indicators or operational characteristics provides a reasonable assurance of compliance with applicable emission limits. The operator shall source test over the proposed range of surrogate operating parameters to demonstrate compliance with the applicable emission standards.</p> <p>5.6.11 For each engine subject to Section 8.0, install and operate a nonresettable fuel meter. In lieu of installing a nonresettable fuel meter, the owner may use an alternative device, method, or technique in determining daily fuel consumption provided that the alternative is approved by the APCO. The owner shall properly maintain, operate, and calibrate the required fuel meter in accordance with the manufacturer's instructions.</p>	<p>source test is not performed and the engine is operated.</p> <p>5.8.9.1 If an engine is operated less than 120 calendar days per calendar year, take one NOx emission reading during the calendar year in which a source test is not performed and the engine is operated.</p> <p>5.8.9.2 All emission readings shall be taken with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration.</p> <p>5.8.9.3 The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO.</p> <p>5.8.9.4 All NOx emissions readings shall be reported to the APCO in a manner approved by the APCO.</p> <p>5.8.9.5 NOx emission readings taken pursuant to this section shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15 consecutive minute period.</p> <p>5.8.10 The APCO shall not approve an alternative monitoring system unless it is documented that continued operation within ranges of specified emissions related performance indicators or operational characteristics provides a reasonable assurance of compliance with applicable emission limits. The operator shall source test over the proposed range of surrogate operating parameters to demonstrate compliance with the applicable emission standards.</p> <p>5.8.11 For each engine subject to Section 8.0, install and operate a nonresettable fuel meter.</p> <p>5.8.11.1 In lieu of installing a nonresettable fuel meter, the operator may use an alternative device, method, or technique in determining daily fuel consumption provided that the alternative is approved by the APCO and EPA.</p> <p>5.8.11.2 The operator shall properly maintain, operate, and calibrate the required fuel meter in accordance with the manufacturer's instructions.</p>	
	<p>5.7 Monitoring Requirements B</p> <p>5.7.1 The owner of any of the following engines shall comply with the requirements specified</p>	<p>5.9 Monitoring Requirements: All Other Engines</p> <p>5.9.1 The operator of any of the following engines shall comply with the requirements</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the</p>

	<p>in Section 5.7.2 through Section 5.7.5 below:</p> <p>5.7.1.1 An AO spark-ignited engine subject to the requirements of Section 5.1,</p> <p>5.7.1.2 A compression-ignited engine subject to the requirements of Section 5.1, or</p> <p>5.7.1.3 An engine subject to Section 4.2.</p> <p>5.7.2 Properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier.</p> <p>5.7.3 Monitor the operational characteristics of each engine as recommended by the engine manufacturer or emission control system supplier.</p> <p>5.7.4 Install and operate a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and is allowed by Permit-to-Operate or Permit-Exempt Equipment Registration condition. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.</p> <p>5.7.5 The owner of an AO spark-ignited engine that has been retro-fitted with a NOx exhaust control that has not been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements, or a compression-ignited engine that has been retro-fitted with a NOx exhaust control shall comply with the following:</p> <p>5.7.5.1 Use a portable NOx analyzer to take NOx emission readings to demonstrate compliance with the emission requirements of Section 5.1.</p> <p>5.7.5.2 The owner of a compression-ignited engine that is subject to the limits/standards of Section 5.1.2 Table 2 Category 1.d shall use a portable NOx analyzer to take NOx emission readings at least once every six months that the engine is operated.</p> <p>5.7.5.3 The owner of any other engine that has been retro-fitted with a NOx exhaust control shall use a portable NOx analyzer to take NOx emission readings at least once every 24 months that the engine is operated.</p> <p>5.7.5.4 All emission readings shall be taken with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration.</p>	<p>specified in Section 5.9.2 through Section 5.9.5 below:</p> <p>5.9.1.1 An AO spark-ignited engine subject to the requirements of Section 5.2;</p> <p>5.9.1.2 A compression-ignited engine subject to the requirements of Section 5.2; or</p> <p>5.9.1.3 An engine subject to Section 4.2.</p> <p>5.9.2 Properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier.</p> <p>5.9.3 Monitor the operational characteristics of each engine as recommended by the engine manufacturer or emission control system supplier.</p> <p>5.9.4 Install and operate a nonresettable elapsed time meter.</p> <p>5.9.4.1 In lieu of installing a nonresettable elapsed time meter, the operator may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and EPA and is allowed by a Permit-to- Operate or Permit-Exempt Equipment Registration condition.</p> <p>5.9.4.2 The operator shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions.</p> <p>5.9.5 The operator of an AO spark-ignited engine that has been retro-fitted with a NOx exhaust control that has not been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements, or a compression ignited engine that has been retro-fitted with a NOx exhaust control shall comply with the following:</p> <p>5.9.5.1 Use a portable NOx analyzer to take NOx emission readings to demonstrate compliance with the emission requirements of Section 5.2.</p> <p>5.9.5.2 The operator of a compression-ignited engine that is subject to the limits/standards of Section 5.2 Table 4 Category 1.d shall use a portable NOx analyzer to take NOx emission readings at least once every six (6) months that the engine is operated.</p> <p>5.9.5.3 The operator of any other engine that has been retro-fitted with a NOx exhaust control shall use a portable NOx analyzer to take NOx emission readings at least once every 24 months that the engine is operated.</p> <p>5.9.5.4 All emission readings shall be taken with the engine operating either at</p>	<p>rule is as stringent as the SIP version of the rule.</p>
--	--	--	---

	<p>5.7.5.5 The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO.</p> <p>5.7.5.6 All NOx emissions readings shall be reported to the APCO in a manner approved by the APCO.</p> <p>5.7.5.7 NOx emission readings taken pursuant to this section shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15 consecutive-minute period.</p>	<p>conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration.</p> <p>5.9.5.5 The portable NOx analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO.</p> <p>5.9.5.6 All NOx emissions readings shall be reported to the APCO in a manner approved by the APCO.</p> <p>5.9.5.7 NOx emission readings taken pursuant to this section shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15 consecutive minute period.</p>	
		<p>5.10 SOx Emissions Monitoring Requirements On and after the compliance schedule specified in Section 7.5, an operator of a non-AO engine shall comply with the following requirements:</p> <p>5.10.1 An operator of an engine complying with Sections 5.7.2 or 5.7.5 shall perform an annual sulfur fuel analysis in accordance with the test methods in Section 6.4. The operator shall keep the records of the fuel analysis and shall provide it to the District upon request,</p> <p>5.10.2 An operator of an engine complying with Section 5.7.6 by installing and operating a control device with at least 95% by weight SOx reduction efficiency shall submit for approval by the APCO the proposed the key system operating parameters and frequency of the monitoring and recording not later than July 1, 2013, and</p> <p>5.10.3 An operator of an engine complying with Section 5.7.6 shall perform an annual source test unless a more frequent sampling and reporting period is included in the Permit-to-Operate. Source tests shall be performed in accordance with the test methods in Section 6.4.</p>	<p>The non-SIP approved version contains SO_x emissions monitoring requirements not required in the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

	<p>5.8 Permit-Exempt Equipment Registration Requirements</p> <p>The owner of an engine used exclusively in agricultural operations shall register such engine pursuant to Rule 2250 (Permit-Exempt Equipment Registration), except for an engine that meets any one of the following conditions:</p> <p>5.8.1 The engine is required to have a Permit-to-Operate pursuant to California Health and Safety Code Section 42301.16, or</p> <p>5.8.2 The engine is not required to comply with Section 5.1 of this rule.</p>	<p>5.11 Permit-Exempt Equipment Registration Requirements</p> <p>The operator of an engine used exclusively in agricultural operations shall register such engine pursuant to Rule 2250 (Permit-Exempt Equipment Registration), except for an engine that meets any one of the following conditions:</p> <p>5.11.1 The engine is required to have a Permit-to-Operate pursuant to California Health and Safety Code Section 42301.16; or</p> <p>5.11.2 The engine is not required to comply with Section 5.2 of this rule.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
<p>6.0 Administrative Requirements</p>	<p>6.1 Emission Control Plan</p> <p>The owner of an engine subject to the requirements of Section 5.1 or Section 8.0, except for an engine specified in Section 6.1.1, of this rule shall submit to the APCO an APCO-approvable emission control plan of all actions to be taken to satisfy the emission requirements of Section 5.1 and the compliance schedules of Section 7.0.</p> <p>6.1.1 The requirement to submit an emission control plan shall not apply to an engine specified below:</p> <p>6.1.1.1 A certified compression-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0,</p> <p>6.1.1.2 A certified spark-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0,</p> <p>6.1.1.3 An AO spark-ignited engine that has not been retro-fitted with a catalytic emission control device and is not subject to the requirements of Section 8.0,</p> <p>6.1.1.4 An engine subject to Section 4.2, or</p> <p>6.1.1.5 An engine subject to Section 4.3.</p> <p>6.1.1.6 An engine with an operating exhaust control system that has been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements.</p> <p>6.1.2 Such emission control plan shall contain the following information, as applicable for each engine:</p> <p>6.1.2.1 Permit-to-Operate number, Authority-to-Construct number, or Permit-Exempt Equipment Registration number</p> <p>6.1.2.2 Engine manufacturer</p> <p>6.1.2.3 Model designation and engine serial</p>	<p>6.1 Emission Control Plan</p> <p>The operator of an engine subject to the requirements of Section 5.2 of this rule shall submit to the APCO an APCO-approvable emission control plan of all actions to be taken to satisfy the emission requirements of Section 5.2 and the compliance schedules of Section 7.0. If there is no change to the previously-approved emission control plan, the operator shall submit a letter to the District indicating that the previously approved plan is still valid.</p> <p>6.1.1 The requirement to submit an emission control plan shall apply to the following engines:</p> <p>6.1.1.1 Engines that have been retrofitted with an exhaust control device, except those certified per Section 9.0;</p> <p>6.1.1.2 Engines subject to Section 8.0;</p> <p>6.1.1.3 An AO spark-ignited engine that is subject to the requirements of Section 8.0;</p> <p>6.1.1.4 An AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0.</p> <p>6.1.2 Such emission control plan shall contain the following information, as applicable for each engine:</p> <p>6.1.2.1 Permit-to-Operate number, Authority-to-Construct number, or Permit-Exempt Equipment Registration number,</p> <p>6.1.2.2 Engine manufacturer,</p> <p>6.1.2.3 Model designation and engine serial number,</p> <p>6.1.2.4 Rated brake horsepower,</p> <p>6.1.2.5 Type of fuel and type of ignition,</p> <p>6.1.2.6 Combustion type: rich-burn or lean-</p>	<p>The non-SIP approved version of this rule includes what engine categories are subject to this section. The SIP approved version has a list of what engines are exempt from this section. However, there is no change in the actual engine categories that are required to meet these section requirements. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

<p>number</p> <p>6.1.2.4 Rated brake horsepower</p> <p>6.1.2.5 Type of fuel and type of ignition</p> <p>6.1.2.6 Combustion type: rich-burn or lean-burn</p> <p>6.1.2.7 Total hours of operation in the previous one-year period, including typical daily operating schedule</p> <p>6.1.2.8 Fuel consumption (cubic feet for gas or gallons for liquid) for the previous one-year period</p> <p>6.1.2.9 Stack modifications to facilitate continuous in-stack monitoring and to facilitate source testing</p> <p>6.1.2.10 Type of control to be applied, including in-stack monitoring specifications</p> <p>6.1.2.11 Applicable emission limits</p> <p>6.1.2.12 Documentation showing existing emissions of NOx, VOC, and CO, and</p> <p>6.1.2.13 Date that the engine will be in full compliance with Rule 4702.</p> <p>6.1.3 The emission control plan shall identify the type of emission control device or technique to be applied to each engine and a construction/removal schedule, or shall provide support documentation sufficient to demonstrate that the engine is in compliance with the emission requirements of this rule.</p> <p>6.1.4 For an engine being permanently removed from service, the emission control plan shall include a letter of intent pursuant to Section 7.2.</p>	<p>burn,</p> <p>6.1.2.7 Total hours of operation in the previous one-year period, including typical daily operating schedule,</p> <p>6.1.2.8 Fuel consumption (cubic feet for gas or gallons for liquid) for the previous one-year period,</p> <p>6.1.2.9 Stack modifications to facilitate continuous in-stack monitoring and to facilitate source testing,</p> <p>6.1.2.10 Type of control to be applied, including in-stack monitoring specifications,</p> <p>6.1.2.11 Applicable emission limits,</p> <p>6.1.2.12 Documentation showing existing emissions of NOx, VOC, and CO, and</p> <p>6.1.2.13 Date that the engine will be in full compliance with this rule.</p> <p>6.1.3 The emission control plan shall identify the type of emission control device or technique to be applied to each engine and a construction/removal schedule, or shall provide support documentation sufficient to demonstrate that the engine is in compliance with the emission requirements of this rule.</p> <p>6.1.4 For an engine being permanently removed from service, the emission control plan shall include a letter of intent pursuant to Section 7.2.</p>	
<p>6.2 Recordkeeping</p> <p>6.2.1 Except for engines subject to Section 4.0, the owner of an engine subject to the requirements of Section 5.1 of this rule shall maintain an engine operating log to demonstrate compliance with this rule. This information shall be retained for a period of at least five years, shall be readily available, and be made available to the APCO upon request. The engine operating log shall include, on a monthly basis, the following information:</p> <p>6.2.1.1 Total hours of operation,</p> <p>6.2.1.2 Type of fuel used,</p> <p>6.2.1.3 Maintenance or modifications performed,</p> <p>6.2.1.4 Monitoring data,</p> <p>6.2.1.5 Compliance source test results, and</p>	<p>6.2 Recordkeeping</p> <p>6.2.1 The operator of an engine subject to the requirements of Section 5.2 of this rule shall maintain an engine operating log to demonstrate compliance with this rule. This information shall be retained for a period of at least five years, shall be readily available, and be made available to the APCO upon request. The engine operating log shall include, on a monthly basis, the following information:</p> <p>6.2.1.1 Total hours of operation,</p> <p>6.2.1.2 Type of fuel used,</p> <p>6.2.1.3 Maintenance or modifications performed,</p> <p>6.2.1.4 Monitoring data,</p> <p>6.2.1.5 Compliance source test results, and</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

<p>6.2.1.6 Any other information necessary to demonstrate compliance with this rule.</p> <p>6.2.1.7 For an engine subject to Section 8.0, the quantity (cubic feet of gas or gallons of liquid) of fuel used on a daily basis.</p>	<p>6.2.2 The data collected pursuant to the requirements of Section 5.6 and Section 5.7 shall be maintained for at least five years, shall be readily available, and made available to the APCO upon request.</p> <p>6.2.3 An owner claiming an exemption under Section 4.2 or Section 4.3 shall maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and provided to the APCO upon request. The records shall include, but are not limited to, the following:</p> <p>6.2.3.1 Total hours of operation,</p> <p>6.2.3.2 The type of fuel used,</p> <p>6.2.3.3 The purpose for operating the engine,</p> <p>6.2.3.4 For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and</p> <p>6.2.3.5 Other support documentation necessary to demonstrate claim to the exemption.</p>	<p>6.2.1.6 Any other information necessary to demonstrate compliance with this rule.</p> <p>6.2.1.7 For an engine subject to Section 8.0, the quantity (cubic feet of gas or gallons of liquid) of fuel used on a daily basis.</p> <p>6.2.2 The data collected pursuant to the requirements of Section 5.8 and Section 5.9 shall be maintained for at least five years, shall be readily available, and made available to the APCO upon request.</p> <p>6.2.3 An operator claiming an exemption under Section 4.2 or Section 4.3 shall maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and provided to the APCO upon request. The records shall include, but are not limited to, the following:</p> <p>6.2.3.1 Total hours of operation,</p> <p>6.2.3.2 The type of fuel used,</p> <p>6.2.3.3 The purpose for operating the engine,</p> <p>6.2.3.4 For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and</p> <p>6.2.3.5 Other support documentation necessary to demonstrate claim to the exemption.</p>	
<p>6.3 Compliance Testing</p> <p>The owner of an engine subject to the requirements of Section 5.1 or the requirements of Section 8.0, shall comply with the following requirements, except for an engine specified in Section 6.3.1:</p> <p>6.3.1 The requirements of Section 6.3.2 through Section 6.3.4 shall not apply to any of the following engines:</p> <p>6.3.1.1 A certified compression-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0.</p> <p>6.3.1.2 A certified spark-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0.</p> <p>6.3.1.3 An AO spark-ignited engine that has not been retro-fitted with a catalytic emission control device and is not subject to the requirements of Section 8.0.</p> <p>6.3.1.4 An engine subject to Section 4.2.</p> <p>6.3.1.5 An engine subject to Section 4.3.</p> <p>6.3.1.6 An engine with an operating exhaust</p>	<p>6.3 Compliance Testing</p> <p>The operator of an engine subject to the requirements of Section 5.2 or the requirements of Section 8.0 shall comply with the following requirements:</p> <p>6.3.1 The requirements of Section 6.3.2 through Section 6.3.4 shall apply to the following engines:</p> <p>6.3.1.1 Engines that have been retrofitted with an exhaust control device, except those certified per Section 9.0;</p> <p>6.3.1.2 Engines subject to Section 8.0;</p> <p>6.3.1.3 An AO spark-ignited engine that is subject to the requirements of Section 8.0;</p> <p>6.3.1.4 An AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0.</p> <p>6.3.2 Demonstrate compliance with applicable limits, ppmv or percent reduction, in accordance with the test methods in Section 6.4, as specified below:</p> <p>6.3.2.1 By the applicable date specified in</p>	<p>6.3 Compliance Testing</p> <p>The operator of an engine subject to the requirements of Section 5.2 or the requirements of Section 8.0 shall comply with the following requirements:</p> <p>6.3.1 The requirements of Section 6.3.2 through Section 6.3.4 shall apply to the following engines:</p> <p>6.3.1.1 Engines that have been retrofitted with an exhaust control device, except those certified per Section 9.0;</p> <p>6.3.1.2 Engines subject to Section 8.0;</p> <p>6.3.1.3 An AO spark-ignited engine that is subject to the requirements of Section 8.0;</p> <p>6.3.1.4 An AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0.</p> <p>6.3.2 Demonstrate compliance with applicable limits, ppmv or percent reduction, in accordance with the test methods in Section 6.4, as specified below:</p> <p>6.3.2.1 By the applicable date specified in</p>	<p>The non-SIP approved version of this rule includes what engine categories are subject to this section. The SIP approved version has a list of what engines are exempt from this section. However, there is no change in the actual engine categories that are required to meet this section requirements. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

control system that has been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements.

6.3.2 Demonstrate compliance with applicable limits, ppmv or percent reduction, in accordance with the test methods in Section 6.4, as specified below:

6.3.2.1 By the applicable date specified in Section 5.1.1, Section 5.1.2, Section 7.3, Section 7.4, Section 7.5, or Section 7.6 and at least once every 24 months thereafter, except for an engine subject to Section 6.3.2.2.

6.3.2.2 By the applicable date specified in Section 5.1.1, Section 5.1.2, Section 7.3, Section 7.4, Section 7.5, or Section 7.6 and at least once every 60 months thereafter, for an AO spark-ignited engine that has been retro-fitted with a catalytic emission control device and is not subject to the requirements of Section 8.0.

6.3.2.3 A portable NOx analyzer may be used to show initial compliance with the applicable limits/standards in Section 5.1 for AO spark-ignited engines, provided the criteria specified in Sections 6.3.2.3.1 to 6.3.2.3.5 are met, and a source test is conducted in accordance with Section 6.3.2 within 12 months from the required compliance date.

6.3.2.3.1 A minimum of 15 minutes of runtime must be measured with data recorded at a minimum of 15, evenly spaced time intervals. Compliance is to be determined with the arithmetic average of the oxygen-corrected data.

6.3.2.3.2 The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Analyzer calibration records shall be made available at the District's request.

6.3.2.3.3 The analyzer shall be checked with EPA protocol span gas at the beginning and end of each test day. The results of these checks shall be recorded and copies submitted to the District with each engine test. If the analyzer exhibits more than a 10% deviation from the span check, the instrument must be re-calibrated. Any analysis performed prior to an end-of-day span check failure shall be void.

6.3.2.3.4. The test results of each engine, including span check results, shall be submitted to the District within 30 days of the test date. Test results shall clearly identify the engine tested including owner, location, permit or

Section 5.2, and at least once every 24 months thereafter, except for an engine subject to Section

6.3.2.2 By the applicable date specified in Section 5.2 and at least once every 60 months thereafter, for an AO spark-ignited engine that has been retro-fitted with a catalytic emission control device.

6.3.2.3 A portable NOx analyzer may be used to show initial compliance with the applicable limits/standards in Section 5.2 for AO spark ignited engines, provided the criteria specified in Sections 6.3.2.3.1 to 6.3.2.3.5 are met, and a source test is conducted in accordance with Section 6.3.2 within 12 months from the required compliance date.

6.3.2.3.1 A minimum of 15 minutes of runtime must be measured with data recorded at a minimum of 15, evenly spaced time intervals. Compliance is to be determined with the arithmetic average of the oxygen corrected data;

6.3.2.3.2 The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Analyzer calibration records shall be made available at the District's request;

6.3.2.3.3 The analyzer shall be checked with EPA protocol span gas at the beginning and end of each test day. The results of these checks shall be recorded and copies submitted to the District with each engine test. If the analyzer exhibits more than a 10% deviation from the span check, the instrument must be recalibrated. Any analysis performed prior to an end-of-day span check failure shall be void;

6.3.2.3.4 The test results of each engine, including span check results, shall be submitted to the District within 30 days of the test date. Test results shall clearly identify the engine tested including operator, location, permit or registration number, manufacturer, model, and serial number; and

6.3.2.3.5 The analyzer utilized for each check shall be clearly identified in the material submitted with the test results. Identification shall include manufacturer and serial number of the analyzer used, and the last calibration date.

6.3.3 Conduct emissions source testing with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration. For emissions source testing performed pursuant to Section 6.3.2 for the

registration number, manufacturer, model, and serial number.

6.3.2.3.5. The analyzer utilized for each check shall be clearly identified in the material submitted with the test results. Identification shall include manufacturer and serial number of the analyzer used, and the last calibration date.

6.3.3 Conduct emissions source testing with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration. For emissions source testing performed pursuant to Section 6.3.2 for the purpose of determining compliance with an applicable standard or numerical limitation, the arithmetic average of three (3) 30-consecutive-minute test runs shall apply. If two (2) of three (3) runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC shall be reported as methane. VOC, NO_x, and CO concentrations shall be reported in ppmv, corrected to 15 percent oxygen. For engines that comply with a percent reduction limit in Table 1, the percent reduction of NO_x emissions shall also be reported.

6.3.4 In addition to other information, the source test protocol shall describe which critical parameters will be measured and how the appropriate range for these parameters shall be established. The range for these parameters shall be incorporated into the I&M plan.

6.3.5 Engines that are limited by Permit-to-Operate or Permit-Exempt Equipment Registration condition to be fueled exclusively with PUC quality natural gas shall not be subject to the reoccurring source test requirements of Section 6.3.2 for VOC emissions.

purpose of determining compliance with an applicable standard or numerical limitation, the arithmetic average of three (3) 30-consecutive-minute test runs shall apply. If two (2) of three (3) runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC shall be reported as methane. VOC, NO_x, and CO concentrations shall be reported in ppmv, corrected to 15 percent oxygen. For engines that comply with a percent reduction limit, the percent reduction of NO_x emissions shall also be reported.

6.3.4 In addition to other information, the source test protocol shall describe which critical parameters will be measured and how the appropriate range for these parameters shall be established. The range for these parameters shall be incorporated into the I&M plan.

6.3.5 Engines that are limited by Permit-to-Operate or Permit-Exempt Equipment Registration condition to be fueled exclusively with PUC quality natural gas shall not be subject to the reoccurring source test requirements of Section 6.3.2 for VOC emissions.

6.3.6 Representative Testing

For spark-ignited engines, in lieu of compliance with the applicable requirements of Section 6.3.2, compliance with the applicable emission limits in Section 5.1 shall be demonstrated by submittal of annual emission test results, within 30 days of the test date, to the District, from a unit or units that represents a specified group of units, provided all of the following requirements are satisfied:

6.3.6.1 The units are located at the same stationary source;

6.3.6.2 The units were produced by the same manufacturer, have the same model number or other manufacturer's designation in common, and have the same rated capacity and operating specifications;

6.3.6 Representative Testing

For spark-ignited engines, in lieu of compliance with the applicable requirements of Section 6.3.2, compliance with the applicable emission limits in Section 5.2 shall be demonstrated by submittal of annual emission test results, within 30 days of the test date, to the District, from a unit or units that represents a specified group of units, provided all of the following requirements are satisfied:

6.3.6.1 The units are located at the same stationary source;

6.3.6.2 The units were produced by the same manufacturer, have the same model number or other manufacturer's designation in common, and have the same rated

There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.

	<p>6.3.6.3 The units are operated and maintained in a similar manner; and</p> <p>6.3.6.4 At least 20% of the total number of units are tested during each annual test cycle.</p> <p>6.3.6.5 The District, based on documentation submitted by the stationary source:</p> <p>6.3.6.5.1 Determines that the margin of compliance for the identical units tested is significant and can be maintained on an on-going basis; or</p> <p>6.3.6.5.2 Determines based on a review of sufficient emissions data that, though the margin of compliance is not substantial, other factors allow for the determination that the variability of emissions for identical tested units is low enough for confidence that the untested unit will be in compliance. These factors may include, but are not limited to, the following:</p> <p>6.3.6.5.2.1 Historical records at the tested unit</p> <p>6.3.6.5.2.2 Fuel characteristics yielding low variability and therefore assurance that emissions will be constant and below allowable levels;</p> <p>6.3.6.5.2.3 Statistical analysis of a robust emissions data set demonstrates sufficiently low variability to convey assurance that the margin of compliance, though small, is reliable.</p> <p>6.3.6.6 Should any of the representative units exceed the required emission limits, or if the District notifies the operator that the criteria in Sections 6.3.6.1 through 6.3.6.5 have not been fulfilled, each of the units in the group shall individually demonstrate compliance by emissions testing. Failure to complete emissions testing within 90 days of the failed test shall result in the untested units being in violation of this rule. After compliance with the requirements of Section 6.3.6.6 has been demonstrated, subsequent source testing shall be performed pursuant to Sections 6.3.2 or 6.3.6.</p>	<p>capacity and operating specifications;</p> <p>6.3.6.3 The units are operated and maintained in a similar manner; and</p> <p>6.3.6.4 At least 20% of the total number of units are tested during each annual test cycle.</p> <p>6.3.6.5 The District, based on documentation submitted by the stationary source:</p> <p>6.3.6.5.1 Determines that the margin of compliance for the identical units tested is significant and can be maintained on an on-going basis; or</p> <p>6.3.6.5.2 Determines based on a review of sufficient emissions data that, though the margin of compliance is not substantial, other factors allow for the determination that the variability of emissions for identical tested units is low enough for confidence that the untested unit will be in compliance. These factors may include, but are not limited to, the following:</p> <p>6.3.6.5.2.1 Historical records at the tested unit showing consistent invariant load;</p> <p>6.3.6.5.2.2 Fuel characteristics yielding low variability and therefore assurance that emissions will be constant and below allowable levels;</p> <p>6.3.6.5.2.3 Statistical analysis of a robust emissions data set demonstrating sufficiently low variability to convey assurance that the margin of compliance, though small, is reliable.</p> <p>6.3.6.6 Should any of the representative units exceed the required emission limits, or if the District notifies the operator that the criteria in Sections 6.3.6.1 through 6.3.6.5 have not been fulfilled, each of the units in the group shall individually demonstrate compliance by emissions testing. Failure to complete emissions testing within 90 days of the failed test shall result in the untested units being in violation of this rule. After compliance with the requirements of this section has been demonstrated, subsequent source testing shall be performed pursuant to Sections 6.3.2 or 6.3.6.</p>	
	<p>6.4 Test Methods</p> <p>Compliance with the requirements of Section 5.0 shall be determined, as required, in accordance with the following test procedures or any other method approved by EPA and the APCO:</p> <p>6.4.1 Oxides of nitrogen - EPA Method 7E, or ARB Method 100.</p> <p>6.4.2 Carbon monoxide - EPA Method 10, or ARB Method 100.</p>	<p>6.4 Test Methods</p> <p>Compliance with the requirements of Section 5.2 shall be determined, as required, in accordance with the following test procedures or any other method approved by EPA and the APCO:</p> <p>6.4.1 Oxides of nitrogen - EPA Method 7E, or ARB Method 100.</p> <p>6.4.2 Carbon monoxide - EPA Method 10, or ARB Method 100.</p>	<p>The Non-SIP approved version of this rule added SO_x test methods to the SIP approved version of this rule. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

	<p>6.4.3 Stack gas oxygen - EPA Method 3 or 3A, or ARB Method 100.</p> <p>6.4.4 Volatile organic compounds - EPA Method 25A or 25B, or ARB Method 100.</p> <p>6.4.5 Operating horsepower determination - any method approved by EPA and the APCO.</p>	<p>6.4.3 Stack gas oxygen - EPA Method 3 or 3A, or ARB Method 100.</p> <p>6.4.4 Volatile organic compounds - EPA Method 25A or 25B, or ARB Method 100. Methane and ethane, which are exempt compounds, shall be excluded from the result of the test.</p> <p>6.4.5 Operating horsepower determination - any method approved by EPA and the APCO.</p> <p>6.4.6 SOx Test Methods</p> <p>6.4.6.1 Oxides of sulfur – EPA Method 6C, EPA Method 8, or ARB Method 100.</p> <p>6.4.6.2 Determination of total sulfur as hydrogen sulfide (H₂S) content – EPA Method 11 or EPA Method 15, as appropriate.</p> <p>6.4.6.3 Sulfur content of liquid fuel – American Society for Testing and Materials (ASTM) D 6920-03 or ASTM D 5453-99.</p> <p>6.4.6.4 The SOx emission control system efficiency shall be determined using the following:</p> <p>% Control Efficiency = [(CSO₂, inlet – CSO₂, outlet) / CSO₂, inlet] X 100</p> <p>Where:</p> <p>CSO₂, inlet = concentration of SOx (expressed as SO₂) at the inlet side of the SOx emission control system, in lb/Dscf</p> <p>CSO₂, outlet = concentration of SOx (expressed as SO₂) at the outlet side of the SOx emission control system, in lb/Dscf</p> <p>6.4.7 The Higher Heating Value (hhv) of the fuel shall be determined by one of the following test methods:</p> <p>6.4.7.1 ASTM D 240-02 or ASTM D 3282-88 for liquid hydrocarbon fuels.</p> <p>6.4.7.2 ASTM D 1826-94 or ASTM 1945-96 in conjunction with ASTM D 3588-89 for gaseous fuel.</p>	
--	---	---	--

	<p>6.5 Inspection and Monitoring (I&M) Plan</p> <p>The owner of an engine that is subject to the requirements of Section 5.1 or the requirements of Section 8.0, except for an engine specified in Section 6.5.1, shall submit to the APCO for approval, an I&M plan that specifies all actions to be taken to satisfy the following requirements and the requirements of Section 5.6. The actions to be identified in the I&M plan shall include, but are not limited to, the information specified below:</p> <p>6.5.1 The requirements of Section 6.5.2 through Section 6.5.9 shall not apply to any of the following engines:</p> <p>6.5.1.1 A certified compression-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0.</p> <p>6.5.1.2 A certified spark-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0.</p> <p>6.5.1.3 An AO spark-ignited engine that has not been retro-fitted with a catalytic emission control device and is not subject to the requirements of Section 8.0.</p> <p>6.5.1.4 An engine subject to Section 4.2.</p> <p>6.5.1.5 An engine subject to Section 4.3.</p> <p>6.5.1.6 An engine with an operating exhaust control system that has been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements.</p> <p>6.5.2 Procedures requiring the owner or operator to establish ranges for control equipment parameters, engine operating parameters, and engine exhaust oxygen concentrations that source testing has shown result in pollutant concentrations within the rule limits.</p> <p>6.5.3 Procedures for monthly inspections as approved by the APCO. The applicable control equipment parameters and engine operating parameters will be inspected and monitored monthly in conformance with a regular inspection schedule listed in the I&M plan.</p> <p>6.5.4 Procedures for the corrective actions on the noncompliant parameter(s) that the owner or operator will take when an engine is found to be operating outside the acceptable range for control equipment parameters, engine operating parameters, and engine exhaust NO_x, CO, VOC, or oxygen concentrations.</p> <p>6.5.5 Procedures for the owner or operator to notify the APCO when an engine is found to be operating outside the acceptable range for control equipment parameters, engine operating parameters, and engine exhaust</p>	<p>6.5 Inspection and Monitoring (I&M) Plan</p> <p>The operator of an engine that is subject to the requirements of Section 5.2 or the requirements of Section 8.0 shall submit to the APCO for approval, an I&M plan that specifies all actions to be taken to satisfy the following requirements and the requirements of Section 5.8. The actions to be identified in the I&M plan shall include, but are not limited to, the information specified below. If there is no change to the previously approved I&M plan, the operator shall submit a letter to the District indicating that previously approved plan is still valid.</p> <p>6.5.1 The requirements of Section 6.5.2 through Section 6.5.9 shall apply to the following engines:</p> <p>6.5.1.1 Engines that have been retrofitted with an exhaust control device, except those certified per Section 9.0;</p> <p>6.5.1.2 Engines subject to Section 8.0;</p> <p>6.5.1.3 An AO spark-ignited engine that is subject to the requirements of Section 8.0.</p> <p>6.5.1.4 An AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0.</p> <p>6.5.2 Procedures requiring the operator to establish ranges for control equipment parameters, engine operating parameters, and engine exhaust oxygen concentrations that source testing has shown result in pollutant concentrations within the rule limits.</p> <p>6.5.3 Procedures for monthly inspections as approved by the APCO. The applicable control equipment parameters and engine operating parameters will be inspected and monitored monthly in conformance with a regular inspection schedule listed in the I&M plan.</p> <p>6.5.4 Procedures for the corrective actions on the noncompliant parameter(s) that the operator will take when an engine is found to be operating outside the acceptable range for control equipment parameters, engine operating parameters, and engine exhaust NO_x, CO, VOC, or oxygen concentrations.</p> <p>6.5.5 Procedures for the operator to notify the APCO when an engine is found to be operating outside the acceptable range for control equipment parameters, engine operating parameters, and engine exhaust NO_x, CO, VOC, or oxygen concentrations.</p> <p>6.5.6 Procedures for preventive and corrective maintenance performed for the purpose of maintaining an engine in proper operating</p>	<p>The non-SIP approved version of this rule includes what engine categories are subject to this section. The SIP approved version has a list of what engines are exempt from this section. However, there is no change in the actual engine categories that are required to meet these section requirements. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
--	--	---	---

	<p>NOx, CO, VOC, or oxygen concentrations.</p> <p>6.5.6 Procedures for preventive and corrective maintenance performed for the purpose of maintaining an engine in proper operating condition.</p> <p>6.5.7 Procedures and a schedule for using a portable NOx analyzer to take NOx emission readings pursuant to Section 5.6.9.</p> <p>6.5.8 Procedures for collecting and recording required data and other information in a form approved by the APCO including, but not limited to, data collected through the I&M plan and the monitoring systems described in Sections 5.6.1 and 5.6.2. Data collected through the I&M plan shall have retrieval capabilities as approved by the APCO.</p> <p>6.5.9 Procedures for revising the I&M plan. The I&M plan shall be updated to reflect any change in operation. The I&M plan shall be updated prior to any planned change in operation. An engine owner that changes significant I&M plan elements must notify the District no later than seven days after the change and must submit an updated I&M plan to the APCO no later than 14 days after the change for approval. The date and time of the change to the I&M plan shall be recorded in the engine operating log. For new engines and modifications to existing engines, the I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit-to-Operate or Permit-Exempt Equipment Registration. The owner of an engine may request a change to the I&M plan at any time.</p>	<p>condition.</p> <p>6.5.7 Procedures and a schedule for using a portable NOx analyzer to take NOx emission readings pursuant to Section 5.8.9.</p> <p>6.5.8 Procedures for collecting and recording required data and other information in a form approved by the APCO including, but not limited to, data collected through the I&M plan and the monitoring systems described in Sections 5.8.1 and 5.8.2. Data collected through the I&M plan shall have retrieval capabilities as approved by the APCO.</p> <p>6.5.9 Procedures for revising the I&M plan. The I&M plan shall be updated to reflect any change in operation. The I&M plan shall be updated prior to any planned change in operation. An engine operator that changes significant I&M plan elements must notify the District no later than seven days after the change and must submit an updated I&M plan to the APCO no later than 14 days after the change for approval. The date and time of the change to the I&M plan shall be recorded in the engine operating log. For new engines and modifications to existing engines, the I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit-to-Operate or Permit-Exempt Equipment Registration. The operator of an engine may request a change to the I&M plan at any time.</p>	
<p>7.0 Compliance Schedules</p>	<p>7.1 Loss of Exemption</p> <p>The owner of an engine which becomes subject to the emission limits/standards of this rule through loss of exemption shall not operate the subject engine, except as required for obtaining a new or modified Permit-to-Operate or Permit-Exempt Equipment Registration for the engine, until the owner demonstrates that the subject engine is in full compliance with the requirements of this rule.</p>	<p>7.1 Loss of Exemption</p> <p>The operator of an engine which becomes subject to the emission limits/standards of this rule through loss of exemption shall not operate the subject engine, except as required for obtaining a new or modified Permit-to-Operate or Permit-Exempt Equipment Registration for the engine, until the operator demonstrates that the subject engine is in full compliance with the requirements of this rule.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
	<p>7.2 Permanent Removal of an Engine</p> <p>The owner of an engine who elects to permanently remove the engine from service shall comply with all of the following conditions:</p> <p>7.2.1 Comply with all applicable requirements of this rule until the engine is permanently removed from service;</p> <p>7.2.2 Submit a letter to the APCO no later than 14 days before the engine is permanently removed from service, stating the intent to</p>	<p>7.2 Permanent Removal of an Engine</p> <p>The operator of an engine who elects to permanently remove the engine from service shall comply with all of the following conditions:</p> <p>7.2.1 Comply with all applicable requirements of this rule until the engine is permanently removed from service;</p> <p>7.2.2 Submit a letter to the APCO no later than 14 days before the engine is permanently</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

	<p>permanently remove the engine from service. The engine removal letter can be submitted with the emission control plan, if any; and</p> <p>7.2.3 Permanently remove the engine from service and officially surrender the Permit-to-Operate or Permit-Exempt Equipment Registration, if any, to the APCO no later than 30 days after the engine is permanently removed from service.</p>	<p>removed from service, stating the intent to permanently remove the engine from service. The engine removal letter can be submitted with the emission control plan, if any; and</p> <p>7.2.3 Permanently remove the engine from service and officially surrender the Permit-to-Operate or Permit-Exempt Equipment Registration, if any, to the APCO no later than 30 days after the engine is permanently removed from</p>	
	<p>7.3 Compliance Schedule for an AO Compression-Ignited Engine</p> <p>7.3.1 Compliance Schedule - Submission of Emission Control Plan, I&M Plan, Permit-Exempt Equipment Registration Application and Authority-to-Construct for an AO Compression-Ignited Engine</p> <p>7.3.1.1 The owner of an engine that is subject to Section 4.2 or Section 4.3 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) no later than January 1, 2006.</p> <p>7.3.1.2 The owner of an engine that is subject to Section 5.1 and that is required to submit an Authority-to-Construct application in order to comply with the requirements of Rule 4702, shall submit the Authority-to-Construct application, and any required Emission Control Plan or I&M Plan, no later than six months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702.</p> <p>7.3.1.3 The owner of an engine that is subject to Section 5.1 and that is required to submit a Permit-Exempt Equipment Registration application in order to comply with the requirements of Rule 4702, shall submit the Permit-Exempt Equipment Registration application, and any required Emission Control Plan or I&M Plan, no later than three months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702.</p> <p>7.3.2 Compliance Schedule - Monitoring and Recordkeeping for an AO Compression-Ignited Engine Subject to Section 5.1 and Section 5.7</p> <p>On and after June 1, 2006, the owner of an engine that is subject to Section 5.1 and Section 5.7 of Rule 4702 shall be in compliance with the requirements of Section 5.7, Section 6.2.1.1, and Section 6.2.1.2.</p> <p>7.3.3 Compliance Schedule - General for an AO Compression-Ignited Engine</p>	<p>7.3 AO Compression-Ignited Engine</p> <p>7.3.1 The operator of an AO compression-ignited engine that is subject to Section 5.2 and that is required to submit an Authority-to-Construct application in order to comply with the requirements of this rule, shall submit the Authority-to-Construct application, and any required Emission Control Plan or I&M Plan, no later than six months before the engine is required to be in compliance with the requirements of Section 5.2.</p> <p>7.3.2 The operator of an AO compression-ignited engine that is subject to Section 5.2 and that is required to submit a Permit-Exempt Equipment Registration application in order to comply with the requirements of Rule 4702, shall submit the Permit-Exempt Equipment Registration application, and any required Emission Control Plan or I&M Plan, no later than three months before the engine is required to be in compliance with the requirements of Section 5.2.</p> <p>7.3.3 Unless otherwise specified, the operator of an engine that is subject to the requirements of Section 5.2 of Rule 4702 shall be in full compliance with Rule 4702 by the indicated dates in Table 4.</p>	<p>The Non-SIP approved version of this rule only includes current requirements from the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

<p>7.3.3.1 On and after January 1, 2006, unless otherwise specified, the owner of an engine that is subject to the requirements of Section 4.2 or Section 4.3 of Rule 4702 shall be in full compliance with Rule 4702.</p> <p>7.3.3.2 Unless otherwise specified, the owner of an engine that is subject to the requirements of Section 5.1 of Rule 4702 shall be in full compliance with Rule 4702 by the indicated dates pursuant to Section 5.1.2.</p>		
<p>7.4 Compliance Schedule for an AO Spark-Ignited Engine</p> <p>7.4.1 Compliance Schedule - Submission of Emission Control Plan, I&M Plan, Permit-Exempt Equipment Registration Application and Authority-to-Construct for an AO Spark-Ignited Engine</p> <p>7.4.1.1 The owner of an engine that is subject to Section 4.2 or Section 4.3 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) no later than January 1, 2006.</p> <p>7.4.1.2 The owner of an engine that is subject to Section 5.1 and that is required to submit an Authority-to-Construct application in order to comply with the requirements of Rule 4702, shall submit the Authority-to-Construct application, and any required Emission Control Plan or I&M Plan, by June 1, 2006, or six months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702, whichever is later.</p> <p>7.4.1.3 The owner of an engine that is subject to Section 5.1 and that is required to submit a Permit-Exempt Equipment Registration application in order to comply with the requirements of Rule 4702, shall submit the Permit-Exempt Equipment Registration application, and any required Emission Control Plan or I&M Plan by January 1, 2007, or three months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702, whichever is later.</p> <p>7.4.2 Compliance Schedule - Monitoring and Recordkeeping for an AO Spark-Ignited Engine Subject to Section 5.1 and Section 5.7</p> <p>On and after June 1, 2006, the owner of an engine that is subject to Section 5.1 and Section 5.7 of Rule 4702 shall be in compliance with the requirements of Section 5.7.3 through Section</p>		<p>AO spark-ignited engines were required to be in full compliance with this rule by 1/1/10. The requirements from this section of the rule are obsolete and not required on the Non-SIP approved version of the rule. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

	<p>5.7.5, Section 6.2.1.1, and Section 6.2.1.2.</p> <p>7.4.3 Compliance Schedule - General for an AO Spark-Ignited Engine</p> <p>7.4.3.1 On and after June 1, 2006, unless otherwise specified, the owner of an engine that is subject to the requirements of Section 4.2 or Section 4.3 of Rule 4702 shall be in full compliance with Rule 4702.</p> <p>7.4.3.2 Unless otherwise specified, the owner of an engine that is subject to the requirements of Section 5.1 of Rule 4702 shall be in full compliance with Rule 4702 by the indicated dates pursuant to Section 5.1.1.</p>		
	<p>7.5 Compliance Schedule for a Non-AO Compression-Ignited Engine</p> <p>7.5.1 Compliance Schedule - Submission of Emission Control Plan, I&M Plan, and Authority-to-Construct for a Non-AO Compression-Ignited Engine</p> <p>7.5.1.1 The owner of an engine that is subject to Section 4.2 or Section 4.3 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) no later than June 1, 2006.</p> <p>7.5.1.2 The owner of an engine that is subject to Section 5.1 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) by June 1, 2006 or six months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702, whichever is later.</p> <p>7.5.2 Compliance Schedule - General for a Non-AO Compression-Ignited Engine</p> <p>7.5.2.1 On and after June 1, 2006, unless otherwise specified, the owner of an engine that is subject to the requirements of Section 4.1, Section 4.2, or Section 4.3 of Rule 4702 shall be in full compliance with Rule 4702.</p> <p>7.5.2.2 Unless otherwise specified, the owner of an engine that is subject to the requirements of Section 5.1 of Rule 4702 shall be in full compliance with Rule 4702 by the indicated dates pursuant to Section 5.1.2.</p> <p>7.5.2.3 The owner of an engine that is subject to the requirements of Section 4.0 or Section 5.0 of Rule 4701 (Internal Combustion Engines – Phase 1) shall no longer be subject to the requirements of Rule 4701 pursuant to the following requirements:</p> <p>7.5.2.3.1 For an engine that is subject to the requirements of Section 4.1, Section 4.2, or</p>	<p>7.4 Non-AO Compression-Ignited Engine</p> <p>7.4.1 The operator of a non-AO compression-ignited engine that is subject to Section 5.2 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with rule requirements, shall submit such document(s) no later than six months before the engine is required to be in compliance with the requirements of Section 5.2.</p> <p>7.4.2 Unless otherwise specified, the operator of an engine that is subject to the requirements of Section 5.2 shall be in full compliance with Rule 4702 by the indicated dates in Table 4.</p>	<p>The Non-SIP approved version of this rule only includes current requirements from the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

<p>Section 4.3 of Rule 4702, the requirements of Rule 4701 shall not apply effective on the date that such engine is required to be in full compliance with Rule 4702, or</p> <p>7.5.2.3.2 For an engine that is subject to the requirements of Section 5.1 of Rule 4702, the requirements of Rule 4701 shall not apply effective on the date that such engine is required to be in full compliance with Rule 4702.</p>		
<p>7.6 Compliance Schedule for a Non-AO Spark-Ignited Engine</p> <p>7.6.1 Compliance Schedule - Submission of Emission Control Plan, I&M Plan, and Authority-to-Construct for a Non-AO Spark-Ignited Engine</p> <p>Effective on and after June 16, 2005, the owner of an engine that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) no later than six months before the engine is required to be in full compliance with Rule 4702.</p> <p>7.6.2 Compliance Schedule – Emission Limits for a Non-AO Spark-Ignited Engine</p> <p>The owner of a non-AO spark-ignited engine subject to the requirements of Rule 4702 shall not operate the engine unless the owner demonstrates and maintains the engine in compliance with the applicable requirements of Rule 4702 by the indicated dates below.</p> <p>Compliance Schedule 1 – Non-AO Spark-Ignited Engine</p> <p>For the purposes of Section 7.6, the total number of non-AO spark-ignited engines at a stationary source on a specified date includes those non-AO spark-ignited engines subject to Rule 4702 pursuant to Section 2.0 and excludes any engines exempt from Rule 4702 pursuant to Section 4.1 on the specified date.</p> <p>7.6.3 Compliance Schedule - General for a Non-AO Spark-Ignited Engine</p> <p>7.6.3.1 On and after January 1, 2006, unless otherwise specified, the owner of an engine that is subject to the requirements of Section 4.1 of Rule 4702 shall be in full compliance with Rule 4702.</p>	<p>Note: This section refers to Table 5. Table 5 can be found as an attachment to this document.</p> <hr/> <p>7.5 Non-AO Spark-Ignited Engine</p> <p>7.5.1 An operator with non-AO spark-ignited engines at a stationary source subject to Table 2 or Section 8.0 emission limits, SOx control requirements of Section 5.7, and the SOx monitoring requirements of Section 5.10 shall comply with the schedule specified in Table 5.</p> <p>7.5.2 As shown in Table 5, the column labeled:</p> <p>7.5.2.1 "Emission Control Plan" identifies the date by which the operator shall submit an emission control plan pursuant to the applicable provisions of Section 6.1. The emission control plan shall identify all the Non-AO spark-ignited engines subject to Table 2 emission limits, SOx control and monitoring requirements. The emission control plan shall identify all the steps to be taken to comply with this rule. If there is no change to the previously approved emission control plan, the operator does not need to submit a new emission control plan. However, the operator shall submit a letter to the District indicating that previously approved plan is still valid.</p> <p>7.5.2.2 "Authority to Construct and Inspection and Maintenance Plan" identifies the date by which the operator shall submit an Authority to Construct (if needed) and an Inspection and Monitoring Plan as specified in the applicable provisions of Section 6.5 for each engine subject to Table 2 emission limits, SOx control and monitoring requirements. If there is no change to the previously approved I&M plan, the operator does not need to submit a new I&M Plan. However, the operator shall submit a letter to the District indicating that previously approved I&M plan is still valid.</p> <p>7.5.2.3 "Full Compliance" identifies the date by which the operator shall demonstrate that each unit is in compliance with Table 2</p>	<p>The Non-SIP approved version of this rule only includes current requirements from the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

	<p>7.6.3.2 Unless otherwise specified, the owner of an engine subject to the requirements of Rule 4702 shall be in full compliance with Rule 4702 by the applicable compliance date pursuant to Section 7.6.2.</p> <p>7.6.3.3 The owner of an engine that is subject to the requirements of Rule 4701 shall no longer be subject to the requirements of Rule 4701 pursuant to the following requirements:</p> <p>7.6.3.3.1 For an engine that is subject to the requirements of Section 4.1 of Rule 4702, the requirements of Rule 4701 shall not apply effective on and after January 1, 2006, or</p> <p>7.6.3.3.2 For an engine that is subject to the requirements of Section 4.2, Section 4.3, or Section 5.1 of Rule 4702, the requirements of Rule 4701 shall not apply effective on the date that such engine is required to be in full compliance with Rule 4702.</p>	<p>emission limits, SOx control and monitoring requirements.</p>	
		<p>7.6 Operator of Non-AO Spark-Ignited Engine Who Elects to Pay Fees</p> <p>In lieu of complying with Table 2 NOx emission limits, the operator of a non-AO spark-ignited engine who elects to pay annual fees under Section 5.2.2.2 and Section 5.6 shall comply with the following requirements:</p> <p>7.6.1 By the date specified in Table 5, submit an Emission Control Plan which includes the following information:</p> <p>7.6.1.1 Number of engines at a stationary source that will comply under Section 5.2.2.2,</p> <p>7.6.1.2 Location of each engine,</p> <p>7.6.1.3 Engine manufacturer, model designation, engine serial number, and Permit-to-Operate number, and</p> <p>7.6.1.4 Each engine's rated brake horsepower, fuel type, and type of ignition.</p> <p>7.6.2 The total annual fees shall be paid to the District in the following manner:</p> <p>7.6.2.1 Payment shall be paid no later than June 30 of each year, for the emissions of the previous calendar year,</p> <p>7.6.2.2 The first payment is due to the District no later than June 30 of the year in which full compliance is required for the specified percent of engines at a stationary as specified in Table 5 that the operator has opted to pay the annual fees,</p>	<p>This section was added to address a new unit category. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

		<p>7.6.2.3 Should June 30 fall on a day when the District is closed, the payment shall be made by the next District working day after June 30, and</p> <p>7.6.2.4 Payments shall continue annually until the engine either is permanently removed from use in the San Joaquin Valley Air Basin and the Permit-to-Operate is surrendered or the operator demonstrates compliance with the applicable Table 2 emission limits.</p> <p>7.6.2.5 The emissions fee for units that operate for less than the full calendar year before demonstrating compliance under Section 5.2, shall be based on the actual fuel used during the portion of the calendar year prior to demonstrating compliance or removing the unit from operation within the San Joaquin Valley Air Basin.</p>	
<p>8.0 Alternative Emission Control Plan (AECF)</p>	<p>An owner may comply with the NOx emission requirements of Section 5.1 for a group of engines by meeting the requirements below. An owner that is subject to the requirements below shall also comply with all the applicable requirements of Sections 5.0, 6.0, and 7.0. An engine that is not subject to Section 5.1 is not eligible for inclusion in an AECF.</p> <p>8.1 During any 7 (seven) consecutive calendar day period, the owner shall operate all engines in the AECF to achieve an actual aggregate NOx emission level that is not greater than 90 percent of the NOx emissions that would be obtained by controlling the engines to comply individually with the NOx limits in Section 5.1. The owner shall operate engines in the AECF such that</p> $AE_{Actual} \leq 0.90 (AE_{Limit})$ <p>and shall notify the APCO within 24 hours of a violation of this section.</p> <p>8.1.1 The actual aggregate NOx emissions (AE_{Actual}) is the sum of the actual NOx emissions, over a 7 (seven) consecutive calendar day period, from all engines in the AECF which were actually operated during that period. AE_{Actual} shall be calculated as follows:</p> $AE_{Actual} = \sum_i (EF_i)(F_i)(k_i)$ <p>where:</p> <p>i identifies each engine in the AECF.</p> <p>EF_i is the NOx emission factor of the engine established pursuant to Section 8.2 and approved by the APCO.</p> <p>F_i is the actual total fuel used by the engine</p>	<p>An operator may comply with the NOx emission requirements of Section 5.2 for a group of engines by meeting the requirements below. An operator that is subject to the requirements below shall also comply with all the applicable requirements of Sections 5.0, 6.0, and 7.0. Only engines subject to Section 5.2 are eligible for inclusion in an AECF.</p> <p>8.1 During any seven (7) consecutive calendar day period, the operator shall operate all engines in the AECF to achieve an actual aggregate NOx emission level that is not greater than 90 percent of the NOx emissions that would be obtained by controlling the engines to comply individually with the NOx limits in Section 5.2. The operator shall operate engines in the AECF such that</p> $AE_{Actual} \leq 0.90 (AE_{Limit})$ <p>and shall notify the APCO within 24 hours of any violation of this section.</p> <p>8.1.1 The actual aggregate NOx emissions (AE_{Actual}) is the sum of the actual NOx emissions, over a seven (7) consecutive calendar day period, from all engines in the AECF which were actually operated during that period. AE_{Actual} shall be calculated as follows:</p> $AE_{Actual} = \sum_i (EF_i)(F_i)(k_i)$ <p>where:</p> <p>i identifies each engine in the AECF.</p> <p>EF_i is the NOx emission factor of the engine established pursuant to Section 8.2 and approved by the APCO.</p> <p>F_i is the actual total fuel used by the engine</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

during the 7 (seven) consecutive calendar day period.

k_i is a constant used to convert an engine's fuel use and NOx emission factor to the amount of NOx emitted. k_i is dependent on the engine and the pollutant emitted. Calculation of k_i shall be accomplished using 40 CFR Part 60, Appendix A, Method 19, or an equivalent method approved by EPA, ARB and the APCO.

8.1.2 The estimated aggregate NOx emissions limit (AE_{Limit}) is the sum of the NOx emissions, over a 7 (seven) consecutive calendar day period, for the same engines in the AECF which were actually operated during the same period as considered in Section 8.1.1, calculated with the NOx limits of Section 5.1 and the actual fuel usage during that 7 (seven) consecutive calendar day period. AE_{Limit} shall be calculated as follows:

$$AE_{Limit} = \sum_i (EL_i)(F_i)(k_i)$$

where:

i identifies each engine in the AECF.

EL_i is the NOx emission limit from Section 5.1 for each engine.

F_i is the actual total fuel used by the engine during the 7 (seven) consecutive calendar day period.

k_i is a constant used to convert an engine's fuel use and NOx emission limit to the amount of NOx emitted. k_i is dependent on the engine and the pollutant emitted. Calculation of k_i shall be accomplished using 40 CFR Part 60, Appendix A, Method 19, or an equivalent method approved by EPA, ARB and the APCO.

8.1.3 Only engines in the AECF which were operated during the 7 (seven) consecutive calendar day period shall be included in the calculations of AE_{Limit} and AE_{Actual} .

8.1.4 The owner shall, at least one time each day the AECF is used, calculate and record the actual aggregate NOx emissions (AE_{Actual}) and the aggregate NOx emission limit (AE_{Limit}) for the preceding 7 (seven) consecutive calendar day period.

8.2 The owner shall establish a NOx emission factor limit for each engine. The established NOx emission factor of an engine shall be no less than the NOx emission factor of the engine from the most recent source test conducted pursuant to Section 6.3 and approved by the APCO. The owner shall not operate an AECF engine in such a manner that NOx emissions exceed the established NOx emission factor of the engine.

during the 7 (seven) consecutive calendar day period.

k_i is a constant used to convert an engine's fuel use and NOx emission factor to the amount of NOx emitted. k_i is dependent on the engine and the pollutant emitted. Calculation of k_i shall be accomplished using 40 CFR Part 60, Appendix A, Method 19, or an equivalent method approved by EPA, ARB and the APCO.

8.1.2 The estimated aggregate NOx emissions limit (AE_{Limit}) is the sum of the NOx emissions, over a seven (7) consecutive calendar day period, for the same engines in the AECF which were actually operated during the same period as considered in Section 8.1.1, calculated with the NOx limits of Section 5.2 and the actual fuel usage during that seven (7) consecutive calendar day period. AE_{Limit} shall be calculated as follows:

$$AE_{Limit} = \sum_i (EL_i)(F_i)(k_i)$$

where:

i = identifies each engine in the AECF.

EL_i = the NOx emission limit from Section 5.2 for each engine.

F_i = the actual total fuel used by the engine during the seven (7) consecutive calendar day period.

k_i = a constant used to convert an engine's fuel use and NOx emission limit to the amount of NOx emitted. k_i is dependent on the engine and the pollutant emitted. Calculation of k_i shall be accomplished using 40 CFR Part 60, Appendix A, Method 19, or an equivalent method approved by EPA, ARB and the APCO.

8.1.3 Only engines in the AECF which were operated during the seven (7) consecutive calendar day period shall be included in the calculations of AE_{Limit} and AE_{Actual} .

8.1.4 The operator shall, at least one time each day the AECF is used, calculate and record the actual aggregate NOx emissions (AE_{Actual}) and the aggregate NOx emission limit (AE_{Limit}) for the preceding seven (7) consecutive calendar day period.

8.2 The operator shall establish a NOx emission factor limit for each engine. The established NOx emission factor of an engine shall be no less than the NOx emission factor of the engine from the most recent source test conducted pursuant to Section 6.3 and approved by the APCO. The operator shall not operate an AECF engine in such a manner that NOx emissions exceed the established NOx emission factor of the engine.

There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.

<p>8.3 The owner shall submit the AECP to the APCO at least 18 months before compliance with the emission limits in Section 5.1 is required. The AECP shall:</p> <p>8.3.1 Not be implemented prior to APCO approval.</p> <p>8.3.2 Be enforceable on a daily basis by the District.</p> <p>8.3.3 Contain any information necessary to determine eligibility of the engines for alternative emission control, including, but not limited to:</p> <p>8.3.3.1 A list of engines subject to the AECP. All engines in an AECP shall be under the operational control of a single owner and shall be located at a single stationary source.</p> <p>8.3.3.2 The NOx emission factor established by the engine owner for each engine pursuant to Section 8.2.</p> <p>8.3.3.3 The estimated aggregate NOx emissions calculated according to Section 8.1.2.</p> <p>8.3.4 Present the methodology for determining equivalency of actual NOx emissions under the proposed AECP as compared to the estimated NOx emissions allowed by this rule.</p> <p>8.3.5 Detail the method of recording and verifying daily compliance with the AECP.</p> <p>8.3.6 Demonstrate to the satisfaction of the APCO that the difference between the NOx emission limits of this rule and any lower actual NOx emissions will not be used to increase emissions from the same or another source.</p> <p>8.3.7 Demonstrate that the engines subject to the requirements of Section 5.1 are in compliance with or on an approved schedule for compliance with all applicable District rules.</p>	<p>8.3 The operator shall submit the AECP to the APCO at least 18 months before compliance with the emission limits in section 5.2 is required. The AECP shall:</p> <p>8.3.1 Not be implemented prior to APCO approval.</p> <p>8.3.2 Be enforceable on a daily basis by the District.</p> <p>8.3.3 Contain any information necessary to determine eligibility of the engines for alternative emission control, including, but not limited to:</p> <p>8.3.3.1 A list of engines subject to the AECP. All engines in an AECP shall be under the operational control of a single operator and shall be located at a single stationary source,</p> <p>8.3.3.2 The NOx emission factor established by the engine operator for each engine pursuant to Section 8.2, and</p> <p>8.3.3.3 The estimated aggregate NOx emissions calculated according to Section 8.1.2.</p> <p>8.3.4 Present the methodology for determining equivalency of actual NOx emissions under the proposed AECP as compared to the estimated NOx emissions allowed by this rule.</p> <p>8.3.5 Detail the method of recording and verifying daily compliance with the AECP.</p> <p>8.3.6 Demonstrate to the satisfaction of the APCO that the difference between the NOx emission limits of this rule and any lower actual NOx emissions will not be used to increase emissions from the same or another source.</p> <p>8.3.7 Demonstrate that the engines subject to the requirements of Section 5.2 are in compliance with or on an approved schedule for compliance with all applicable District rules.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
<p>8.4 The owner shall submit an updated or modified AECP for approval by the APCO prior to any of the following:</p> <p>8.4.1 Modification of the engine(s) which would require an Authority-to-Construct.</p> <p>8.4.2 When new or amended rules are adopted which regulate the emissions from the engines.</p> <p>8.4.3 When the NOx emission factor established by the engine owner for an engine pursuant to Section 8.2 is modified.</p>	<p>8.4 The operator shall submit an updated or modified AECP for approval by the APCO prior to any of the following:</p> <p>8.4.1 Modification of the engine(s) which would require an Authority-to-Construct;</p> <p>8.4.2 When new or amended rules are adopted which regulate the emissions from the engines; or</p> <p>8.4.3 When the NOx emission factor established by the engine operator for an engine pursuant to Section 8.2 is modified.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

	<p>8.5 In addition to the records kept pursuant to Section 6.2, the owner shall maintain records, on a daily basis, of the parameters needed to demonstrate compliance with the applicable NOx emission limits when operating under the AECF. These records shall be retained for at least five years, shall be readily available, and be made available to the APCO upon request. The records shall include, but are not limited to, the following for each engine unless otherwise indicated:</p> <p>8.5.1 Total hours of operation.</p> <p>8.5.2 Type and quantity (cubic feet of gas or gallons of liquid) of fuel used.</p> <p>8.5.3 The actual NOx emissions limits to be included in the calculation of AE_{Actual} pursuant to Section 8.1.1.</p> <p>8.5.4 The actual aggregate NOx emissions (AE_{Actual}) for all the engines in the AECF calculated pursuant to Section 8.1.1.</p> <p>8.5.5 The estimated NOx emissions limits to be included in the calculation of AE_{Limit} pursuant to Section 8.1.2.</p> <p>8.5.6 The estimated aggregate NOx emissions (AE_{Limit}) for all the engines in the AECF calculated pursuant to Section 8.1.2.</p> <p>8.5.7 The comparison of the actual aggregate NOx emissions (AE_{Actual}) for all the engines in the AECF and 90 percent of the estimated aggregate NOx emissions (AE_{Limit}) for all the engines in the AECF to demonstrate compliance with Section 8.1.</p> <p>8.5.8 Any other parameters needed to demonstrate daily compliance with the applicable NOx emission limits when operating under the AECF.</p>	<p>8.5 In addition to the records kept pursuant to Section 6.2, the operator shall maintain records, on a daily basis, of the parameters needed to demonstrate compliance with the applicable NOx emission limits when operating under the AECF. These records shall be retained for at least five years, shall be readily available, and be made available to the APCO upon request. The records shall include, but are not limited to, the following for each engine unless otherwise indicated:</p> <p>8.5.1 Total hours of operation,</p> <p>8.5.2 Type and quantity (cubic feet of gas or gallons of liquid) of fuel used,</p> <p>8.5.3 The actual NOx emissions limits to be included in the calculation of AE_{Actual} pursuant to Section 8.1.1,</p> <p>8.5.4 The actual aggregate NOx emissions (AE_{Actual}) for all the engines in the AECF calculated pursuant to Section 8.1.1,</p> <p>8.5.5 The estimated NOx emissions limits to be included in the calculation of AE_{Limit} pursuant to Section 8.1.2,</p> <p>8.5.6 The estimated aggregate NOx emissions (AE_{Limit}) for all the engines in the AECF calculated pursuant to Section 8.1.2,</p> <p>8.5.7 The comparison of the actual aggregate NOx emissions (AE_{Actual}) for all the engines in the AECF and 90 percent of the estimated aggregate NOx emissions (AE_{Limit}) for all the engines in the AECF to demonstrate compliance with Section 8.1, and</p> <p>8.5.8 Any other parameters needed to demonstrate daily compliance with the applicable NOx emission limits when operating under the AECF.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
	<p>8.6 For the purpose of determining the quantity of spark-ignited engines in compliance pursuant to Section 7.6, a spark-ignited engine in an AECF shall not be considered to be in compliance until all spark-ignited engines in the AECF that have been designated to meet more stringent NOx emission factors pursuant to Section 8.2 are in compliance with the rule.</p>	<p>8.6 For the purpose of determining the quantity of spark-ignited engines in compliance pursuant to Section 7.5, a spark-ignited engine in an AECF shall not be considered to be in compliance until all spark-ignited engines in the AECF that have been designated to meet more stringent NOx emission factors pursuant to Section 8.2 are in compliance with the rule.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

<p>9.0 Exhaust Control System Certification Requirements</p>	<p>9.1 To be considered for APCO certification, the manufacturer or operator shall comply with all of the following requirements:</p> <p>9.1.1 Certification shall be based upon the emission source testing results of a specific exhaust control system.</p> <p>9.1.2A source testing protocol shall be submitted in accordance with the provisions of Rule 1081 (Source Sampling) for approval by the APCO prior to conducting the source test. The source testing protocol approved by the APCO shall be strictly adhered to during certification source testing.</p> <p>9.1.3 Source testing shall be conducted over the range of operating parameters for which the unit(s) will be operated.</p> <p>9.1.4 The source testing results shall demonstrate compliance with the emission limits of this rule for each model of exhaust control system(s) to be certified.</p> <p>9.1.5 The source testing procedure and reports shall be prepared by an ARB- approved independent testing laboratory, and shall contain all the elements identified in the APCO-approved source testing protocol.</p> <p>9.1.6 Source testing shall be conducted no more than 90 days prior to the date of submission of request for certification by the APCO.</p> <p>9.1.7 Any additional supporting information required by the APCO to address other performance parameters.</p>	<p>9.1 To be considered for APCO certification, the manufacturer or operator shall comply with all of the following requirements:</p> <p>9.1.1 Certification shall be based upon the emission source testing results of a specific exhaust control system,</p> <p>9.1.2 A source testing protocol shall be submitted in accordance with the provisions of Rule 1081 (Source Sampling) for approval by the APCO prior to conducting the source test. The source testing protocol approved by the APCO shall be strictly adhered to during certification source testing,</p> <p>9.1.3 Source testing shall be conducted over the range of operating parameters for which the unit(s) will be operated,</p> <p>9.1.4 The source testing results shall demonstrate compliance with the emission limits of this rule for each model of exhaust control system(s) to be certified,</p> <p>9.1.5 The source testing procedure and reports shall be prepared by an ARB approved independent testing laboratory, and shall contain all the elements identified in the APCO-approved source testing protocol,</p> <p>9.1.6 Source testing shall be conducted no more than 90 days prior to the date of submission of request for certification by the APCO, and</p> <p>9.1.7 Any additional supporting information required by the APCO to address other performance parameters.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
	<p>9.2 The manufacturer or operator requesting certification shall submit to the APCO the following information:</p> <p>9.2.1 Copies of the source testing results conducted pursuant to the requirements of Section 9.1, and other pertinent technical data to demonstrate compliance with the emission limits of this rule.</p> <p>9.2.2 The applicant shall sign and date the statement attesting to the accuracy of all information in the statement.</p> <p>9.2.3 Name and address of the exhaust control system manufacturer or operator, brand name of the exhaust control unit, model number, and description of model of system(s) being certified.</p>	<p>9.2 The manufacturer or operator requesting certification shall submit to the APCO the following information:</p> <p>9.2.1 Copies of the source testing results conducted pursuant to the requirements of Section 9.1, and other pertinent technical data to demonstrate compliance with the emission limits of this rule,</p> <p>9.2.2 The applicant shall sign and date the statement attesting to the accuracy of all information in the statement, and</p> <p>9.2.3 Name and address of the exhaust control system manufacturer or operator, brand name of the exhaust control unit, model number, and description of model of system(s) being certified.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

	<p>9.3 The APCO will only approve an application for certification to the extent that the requirements of Sections 9.1 through 9.2 are met and the source testing results demonstrate that the emission limits of this rule are met.</p>	<p>9.3 The APCO will only approve an application for certification to the extent that the requirements of Sections 9.1 through 9.2 are met and the source testing results demonstrate that the emission limits of this rule are met.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
	<p>9.4 The APCO-approved certification is valid only for the range of operating parameters and conditions for which certification is issued.</p>	<p>9.4 The APCO-approved certification is valid only for the range of operating parameters and conditions for which certification is issued.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>
	<p>9.5 The APCO shall publish a list of certified exhaust control systems after the certification process is completed.</p>	<p>9.5 The APCO shall publish a list of certified exhaust control systems after the certification process is completed.</p>	<p>There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.</p>

District Rule 4702 was amended (11/14/2013). As analyzed, each amended section of the non-SIP version of the rule is at least as stringent as, or more stringent than the corresponding section of the SIP version of the rule. Therefore, it is concluded that overall the non-SIP version of the rule is more stringent than the SIP version of the rule

SIP APPROVED VERSION OF DISTRICT RULE 4702

Table 1 Emission Limits/Standards for a Spark-Ignited Internal Combustion Engine and Emission Limits/Standards and Compliance Schedule for a Spark-Ignited Engine Used Exclusively in Agricultural Operations (corrected to 15% oxygen on a dry basis)

Engine Type	NOx	CO	VOC
1. Rich-Burn			
a. Waste gas fueled	50 ppmv or 90% reduction	2000 ppmv	250 ppmv
b. Cyclic loaded, field gas fueled	50 ppmv	2000 ppmv	250 ppmv
c. All other engines	25 ppmv or 96% reduction	2000 ppmv	250 ppmv
2. Lean-Burn			
a. Two stroke, gaseous fueled, less than 100 horsepower	75 ppmv or 85% reduction	2000 ppmv	750 ppmv
b. All other engines	65 ppmv or 90% reduction	2000 ppmv	750 ppmv
3. Rich-Burn Engine Used Exclusively in Agricultural Operations			
a. Comply by 1/1/2009, or if owner has an agreement to electrify, comply by 1/1/2010	90 ppmv or 80% reduction	2000 ppmv	250 ppmv
4. Lean-Burn Engine Used Exclusively in Agricultural Operations			
a. Comply by 1/1/2009 or if owner has an agreement to electrify comply by 1/1/2010	150 ppmv or 70% reduction	2000 ppmv	750 ppmv
5. Certified Spark-Ignited Engine Used Exclusively in AO and installed on or before June 16, 2005			
a. Comply by 6/1/2006	Meet Certified Spark-Ignited Engine Standard of HC+NOx < 0.6 g/bhp-hr		

SIP APPROVED VERSION OF DISTRICT RULE 4702

Table 2 Emission Limits/Standards and Compliance Schedule for a Compression-Ignited Internal Combustion Engine (corrected to 15% oxygen on a dry basis)

Engine Type	Emission Limit/ Standard	Compliance Date
1. Non-Certified Compression-Ignited Engine		
a. Greater than 50 bhp but not more than 500 bhp	EPA Tier 3 or Tier 4	1/1/2010
b. Greater than 500 bhp but not more than 750 bhp and less than 1000 annual operating hours	EPA Tier 3	1/1/2010
c. Greater than 750 bhp and less than 1000 annual operating hours	EPA Tier 4	7/1/2011
d. Greater than 500 bhp and greater than or equal to 1000 annual operating hours	80 ppm NOx, 2,000 ppm CO, 750 ppm VOC	1/1/2008 or, if owner has an agreement to electrify, comply by 1/1/2010
2. Certified Compression-Ignited Engine		
a. EPA Certified Tier 1 or Tier 2 Engine	EPA Tier 4	1/1/2015 or 12 years after installation date, whichever is later
b. EPA Certified Tier 3 or Tier 4 Engine	Meet Certified Compression-Ignited Engine Standard in effect at time of installation	At time of installation

SIP APPROVED VERSION OF DISTRICT RULE 4702

Compliance Schedule 1 – Non-AO Spark-Ignited Engine

Quantity of Non-AO Spark-Ignited Engines to be in Compliance at a Stationary Source	Compliance Date
a. 25% or more of the total number of non-AO spark-ignited engines at a stationary source on June 1, 2005	6/1/05
b. 62.5% or more of the total number of non-AO spark-ignited engines at a stationary source on June 1, 2006	6/1/06
c. 100% of the total number of non-AO spark-ignited engines at a stationary source on June 1, 2007	6/1/07

NON-SIP APPROVED VERSION OF DISTRICT RULE 4702

Table 1 Emission Limits/Standards for a Spark-Ignited Internal Combustion Engine rated at >50 bhp Used Exclusively in Non-AO (All ppmv limits are corrected to 15% oxygen on a dry basis.).			
Engine Type	NOx	CO	VOC
1. Rich-Burn			
a. Waste gas fueled	50 ppmv or 90% reduction	2000 ppmv	250 ppmv
b. Cyclic loaded, field gas fueled	50 ppmv	2000 ppmv	250 ppmv
c. All other engines	25 ppmv or 96% reduction	2000 ppmv	250 ppmv
2. Lean-Burn			
a. Two stroke, gaseous fueled, less than 100 horsepower	75 ppmv or 85% reduction	2000 ppmv	750 ppmv
b. All other engines	65 ppmv or 90% reduction	2000 ppmv	750 ppmv

Table 2 Emission Limits for a Spark-Ignited Internal Combustion Engine Rated at >50 bhp Used Exclusively in Non-AO (All ppmv limits are corrected to 15% oxygen on a dry basis). Emission Limits are effective according to the compliance schedule specified in Section 7.5.			
Engine Type	NOx (ppmv)	CO (ppmv)	VOC (ppmv)
1. Rich-Burn			
a. Waste Gas Fueled	50	2000	250
b. Cyclic Loaded, Field Gas Fueled	50	2000	250
c. Limited Use	25	2000	250
d. Rich-Burn Engine, not listed above	11	2000	250
2. Lean-Burn Engines			
a. Two-Stroke, Gaseous Fueled, >50 bhp and < 100 bhp	75	2000	750
b. Limited Use	65	2000	750
c. Lean-Burn Engine used for gas compression	65 ppmv or 93% reduction	2000	750
d. Waste Gas Fueled	65 ppmv or 90% reduction	2000	750
e. Lean-Burn Engine, not listed above	11	2000	750

NON-SIP APPROVED VERSION OF DISTRICT RULE 4702

Table 3 Emission Limits/Standards and Compliance Schedule for a Spark-Ignited Internal Combustion Engine >50 bhp Used Exclusively in AO (All ppmv limits are corrected to 15% oxygen on a dry basis).			
Engine Type	NO _x Limit	CO Limit	VOC Limit
1. Rich-Burn	90 ppmv or 80% reduction	2000 ppmv	250 ppmv
2. Lean-Burn	150 ppmv or 70% reduction	2000 ppmv	750 ppmv
3. Certified and installed on or before June 16, 2005	Meet a Certified Spark-Ignited Engine Standard of HC + NO _x < 0.6 g/bhp-hr		

Table 4 Emission Limits/Standards and Compliance Schedule for Compression-Ignited Internal Combustion Engine (corrected to 15% oxygen on a dry basis)		
Engine Type	Emission Limit/Standard	Compliance Date
1. Non-Certified Compression-Ignited Engine Installed on or before June 1, 2006		
a. Greater than 50 bhp but not more than 500 bhp	EPA Tier 3 or Tier 4	1/1/2010
b. Greater than 500 bhp but not more than 750 bhp and less than 1000 annual operating hours	EPA Tier 3	1/1/2010
c. Greater than 750 bhp and less than 1000 annual operating hours	EPA Tier 4	7/1/2011
d. Greater than 500 bhp and greater than or equal to 1000 annual operating hours	80 ppmv NO _x , 2,000 ppmv CO, 750 ppmv VOC	1/1/2008 or, if owner has an agreement to electrify, comply by 1/1/2010
2. Certified Compression-Ignited Engine		
a. EPA Certified Tier 1 or Tier 2 Engine	EPA Tier 4	1/1/2015 or 12 years after installation date, but not later than 6/1/2018
b. EPA Certified Tier 3 or Tier 4 Engine	Meet Certified Compression-Ignited Engine Standard in effect at time of installation	At time of installation

NON-SIP APPROVED VERSION OF DISTRICT RULE 4702

Table 5 Compliance Schedule for Non-AO Spark-Ignited Engines Subject to Table 2 Emission Limits, and SOx Control and Monitoring Requirements			
Engines to be in Compliance at a Stationary Source	Emission Control Plan	Authority to Construct and Inspection and Monitoring Plan	Full Compliance
Operator with a single engine at a stationary source			
Single Engine	1/1/12	1/1/13	1/1/14
Operator with at least two engines, but less than 12 engines at a stationary source			
33% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/13	1/1/14
66% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/14	1/1/15
100% of the engines subject to Table 2 emission limits	7/1/12	1/1/15	1/1/16
Operator with at least 12 engines at a stationary source			
25% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/13	1/1/14
50% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/14	1/1/15
75% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/15	1/1/16
100% of the engines subject to Table 2 emission limits	7/1/12	1/1/16	1/1/17

ATTACHMENT E

District Rule 4621 Stringency Analysis

District Rule 4621 Stringency Analysis

Section	SIP Version (Amended December 20, 2007)	Non-SIP Version (Amended December 19, 2013)	Conclusion
1.0 Purpose	The purpose of this rule is to limit VOC emissions from stationary storage containers, delivery vessels, and bulk plants and to provide the administrative requirements for determining compliance with this rule.	The purpose of this rule is to limit VOC emissions from stationary storage containers, delivery vessels, and bulk plants and to provide the administrative requirements for determining compliance with this rule.	There are no changes in the requirements of this section.
2.0 Applicability	This rule applies to storage containers located at bulk plants with capacities greater than 250 gallons and less than 19,800 gallons; to other stationary storage containers with capacities greater than 250 gallons; and to those storage containers that are not subject to the control requirements of Rule 4623 (Storage of Organic Liquids) Section 5.0. The rule also applies to gasoline delivery vessels.	This rule applies to storage containers located at bulk plants with capacities greater than 250 gallons and less than 19,800 gallons; to other stationary storage containers with capacities greater than 250 gallons; and to those storage containers that are not subject to the control requirements of Rule 4623 (Storage of Organic Liquids) Section 5.0. The rule also applies to gasoline delivery vessels.	There are no changes in the requirements of this section.
3.0 Definitions (emissions-related sections only)	<p>3.7 Bulk Plant: any loading rack and associated unloading racks, storage containers and vapor recovery system(s) used to load less than 20,000 gallons of gasoline in any one day, to delivery vessels.</p> <p>3.10 Delivery Vessel: any cargo container having a volumetric capacity in excess of 120 gallons that is used for the transportation of gasoline or aviation gasoline. This term includes pumps, meters, valves, fittings, pipings, and other appurtenances attached to a gasoline storage container on a vehicle and used in connection with the gasoline/aviation gasoline being transported. Containers used exclusively for aviation gasoline in agricultural operations, with an annual throughput of 1,000 gallons or less, will not be considered delivery vessels for the purpose of this rule.</p> <p>3.13 Excess Organic Liquid Drainage: more than 10 milliliters liquid drainage which is not contained by an ARB certified spill container. Such liquid drainage for disconnect operations shall be determined by computing the average drainage from three consecutive disconnects at any one loading arm.</p> <p>3.19 Leak: one of the following – 3.19.1 For delivery vessels, the dripping of VOC-containing liquid at a rate of more than three drops per minute, or a reading of greater than 100 percent of the lower explosive limit (21,000 ppm measured as equivalent propane) when measured in accordance with the test method in Section 6.4.3. 3.19.2 For all other operations, the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.4.3. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak, provided such activities are</p>	<p>3.7 Bulk Plant: any loading rack and associated unloading racks, storage containers and vapor recovery system(s) used to load less than 20,000 gallons of gasoline in any one day, to delivery vessels.</p> <p>3.10 Delivery Vessel: any cargo container having a volumetric capacity in excess of 120 gallons that is used for the transportation of gasoline or aviation gasoline. This term includes pumps, meters, valves, fittings, piping, and other appurtenances attached to a gasoline storage container on a vehicle and used in connection with the gasoline/aviation gasoline being transported. Containers used exclusively for aviation gasoline in agricultural operations, with an annual throughput of 1,000 gallons or less, will not be considered delivery vessels for the purpose of this rule.</p> <p>3.13 Excess Organic Liquid Drainage: more than 10 milliliters liquid drainage which is not contained by an ARB certified spill container. Such liquid drainage for disconnect operations shall be determined by computing the average drainage from three consecutive disconnects at any one loading arm.</p> <p>3.19 Leak: one of the following – 3.19.1 For delivery vessels, the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or a reading of greater than 100 percent of the lower explosive limit (21,000 ppm measured as equivalent propane) when measured in accordance with the test method in Section 6.4.3. 3.19.2 For all other operations, the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.4.2. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak, provided such activities are done as expeditiously as</p>	There are no changes in any significant emissions related definitions.

	<p>done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.</p> <p>3.32 Switch Loading: the transfer of diesel fuel into a delivery vessel or storage container with a capacity over 250 gallons which previously contained gasoline</p>	<p>possible and with minimal spillage of material and VOC emissions to the atmosphere.</p> <p>3.32 Switch Loading: the transfer of diesel fuel into a delivery vessel or storage container with a capacity over 250 gallons which previously contained gasoline.</p>	
4.0 Exemptions	<p>The requirements of Section 5.2.1 and 5.2.2 do not apply to the following operations:</p> <p>4.1 The transfer of gasoline into any stationary storage container with a capacity of 550 gallons or less used primarily for the fueling of implements of husbandry, if such container is equipped with a permanent submerged fill pipe.</p> <p>4.2 The transfer of gasoline into any stationary storage container having a capacity of 2,000 gallons or less which was installed prior to July 1, 1975, if such container is equipped with a permanent submerged fill pipe, and provided no major modification is made on the container.</p> <p>4.3 The transfer of gasoline into any stationary storage container in existence prior to July 1, 1975, which is equipped with an offset fill pipe if such container is equipped with a permanent submerged fill pipe, and provided no major modification is made on the container.</p> <p>4.4 Mobile fuelers used exclusively for fueling emergency motor vehicles while on location at an emergency.</p>	<p>Except for the provisions of Section 6.1.1, the requirements of this rule shall not apply to the following operations:</p> <p>4.1 The transfer of gasoline into any stationary storage container with a capacity of 550 gallons or less used primarily for the fueling of implements of husbandry, if such container is equipped with a permanent submerged fill pipe.</p> <p>4.2 The transfer of gasoline into any stationary storage container having a capacity of 2,000 gallons or less which was installed prior to July 1, 1975, if such container is equipped with a permanent submerged fill pipe, and provided no major modification is made on the container.</p> <p>4.3 The transfer of gasoline into any stationary storage container in existence prior to July 1, 1975, which is equipped with an offset fill pipe if such container is equipped with a permanent submerged fill pipe, and provided no major modification is made on the container.</p> <p>4.4 Mobile fuelers used exclusively for fueling emergency motor vehicles while on location at an emergency.</p>	<p>The SIP version of the rule provides exemption from only two subsections of the rule, whereas the newly amended version provides exemption from the entire rule (other than recordkeeping to demonstrate exemption status). The newly amended version of the rule is therefore not as stringent as the SIP version in this section.</p>
5.0 Requirements	<p>5.1 Loading equipment and vapor collection equipment shall be installed, maintained, and operated such that it is leak-free, with no excess organic liquid drainage at disconnect.</p>	<p>5.1 Loading equipment and vapor collection equipment shall be installed, maintained, and operated such that it is leak-free, with no excess organic liquid drainage at disconnect.</p>	<p>There are no changes in the requirements of this section.</p>
	<p>5.2 Gasoline Storage and Loading</p> <p>5.2.1 In addition to the requirements of Section 5.1 no person shall transfer or permit the transfer of gasoline from any delivery vessel into any stationary storage container subject to requirements of this rule unless:</p> <p>5.2.1.1 Such container, except those used for aviation gasoline, is equipped with an ARB certified permanent submerged fill pipe and utilizes an ARB certified Phase I vapor recovery system that is maintained and operated according to manufacturer specifications and the applicable ARB Executive Order; or</p> <p>5.2.1.2 Containers used for aviation gasoline are equipped with a permanent submerged fill pipe and a Phase I vapor recovery system is certified (or was previously certified) to meet a minimum volumetric control of 95%.</p> <p>5.2.2 Any vent pipe on a stationary gasoline storage container shall be equipped with a pressure-vacuum relief valve in accordance with the requirements set forth in Sections 5.3 and 5.4, as applicable.</p> <p>5.2.3 Vent pipes may be manifolded, as per the applicable ARB Executive Order, to a single pressure-vacuum relief valve. The pressure-vacuum relief valve shall be properly</p>	<p>5.2 Gasoline Storage and Loading</p> <p>5.2.1 In addition to the requirements of Section 5.1 no person shall transfer or permit the transfer of gasoline from any delivery vessel into any stationary storage container subject to requirements of this rule unless:</p> <p>5.2.1.1 Such container, except those used for aviation gasoline, is equipped with an ARB certified permanent submerged fill pipe and utilizes an ARB certified Phase I vapor recovery system that is maintained and operated according to manufacturer specifications and the applicable ARB Executive Order; or</p> <p>5.2.1.2 Containers used for aviation gasoline are equipped with a permanent submerged fill pipe and a Phase I vapor recovery system that is certified (or was previously certified) to meet a minimum volumetric control of 95%.</p> <p>5.2.2 Any vent pipe on a stationary gasoline storage container shall be equipped with a pressure-vacuum relief valve in accordance with the requirements set forth in Sections 5.3 and 5.4, as applicable.</p> <p>5.2.3 Vent pipes may be manifolded, as per the applicable ARB Executive Order, to a single pressure-vacuum relief valve. The pressure-vacuum relief valve shall be properly</p>	<p>There are no changes in the requirements of this section.</p>

	<p>installed and maintained according to manufacturer specifications and the applicable Executive Order.</p> <p>5.2.4 Operators shall have all underground storage container installations and all underground piping configurations inspected by the APCO prior to backfilling. The operator shall notify the District by telephone or other District-approved method and obtain a confirmation number at least three business days prior to the backfilling.</p>	<p>installed and maintained according to manufacturer specifications and the applicable ARB Executive Order.</p> <p>5.2.4 Operators shall have all underground storage container installations and all underground piping configurations inspected by the APCO prior to backfilling. The operator shall notify the District by telephone or other District-approved method and obtain a confirmation number at least three business days prior to the backfilling.</p>	
	<p>5.3 Underground Storage Containers</p> <p>5.3.1 Unless otherwise specified in the applicable ARB Executive Order, for an underground storage container that contains gasoline and is located at a bulk plant, the container shall be equipped with an ARB certified pressurevacuum relief valve set at 3.0±0.5 inches water column pressure relief and 8.0±2.0 inches water column vacuum relief.</p> <p>5.3.2 Unless otherwise specified in the applicable ARB Executive Order, for an underground storage container that contains aviation gasoline and is located at a bulk plant, the container shall be equipped with a pressurevacuum relief valve set at 3.0±0.5 inches water column pressure relief and 8.0±2.0 inches water column vacuum relief.</p> <p>5.3.3 For an underground storage container that contains gasoline and is not located at a bulk plant, the container shall be equipped with an ARB certified Phase I vapor recovery system that is certified to have a minimum volumetric control efficiency of 98%.</p> <p>5.3.4 For an underground storage container that contains aviation gasoline and is not located at a bulk plant, the container shall be equipped with a permanent submerged fill pipe and a Phase I vapor recovery system that is certified (or was previously certified) to meet a minimum volumetric control of 95%.</p> <p>5.3.5 Operators of underground storage containers not located at bulk plants shall conduct and pass the applicable performance tests specified in Sections 6.4.5 through 6.4.8 to determine compliance at least once every 36 months, (no more than 30 days before or after the required performance test date) unless otherwise required under ARB Executive Order or Rule 4622 (Gasoline Transfer into Motor Vehicle Fuel Tanks).</p>	<p>5.3 Underground Storage Containers</p> <p>5.3.1 Unless otherwise specified in the applicable ARB Executive Order, for an underground storage container that contains gasoline and is located at a bulk plant, the container shall be equipped with an ARB certified pressure-vacuum relief valve set at 3.0±0.5 inches water column pressure relief and 8.0±2.0 inches water column vacuum relief.</p> <p>5.3.2 Unless otherwise specified in the applicable ARB Executive Order, for an underground storage container that contains aviation gasoline and is located at a bulk plant, the container shall be equipped with a pressurevacuum relief valve set at 3.0±0.5 inches water column pressure relief and 8.0±2.0 inches water column vacuum relief.</p> <p>5.3.3 For an underground storage container that contains gasoline and is not located at a bulk plant, the container shall be equipped with an ARB certified Phase I vapor recovery system that is certified to have a minimum volumetric control efficiency of 98%.</p> <p>5.3.4 For an underground storage container that contains aviation gasoline and is not located at a bulk plant, the container shall be equipped with a permanent submerged fill pipe and a Phase I vapor recovery system that is certified (or was previously certified) to meet a minimum volumetric control of 95%.</p> <p>5.3.5 Operators of underground storage containers not located at bulk plants shall conduct and pass the applicable performance tests specified in Sections 6.4.4 through 6.4.7 to determine compliance at least once every 36 months, (no more than 30 days before or after the required performance test date) unless otherwise required under ARB Executive Order or Rule 4622 (Gasoline Transfer into Motor Vehicle Fuel Tanks).</p>	<p>There are no changes in the requirements of this section.</p>
	<p>5.4 Aboveground Storage Containers</p> <p>5.4.1 All aboveground storage containers shall be constructed and maintained in a leak-free condition.</p> <p>5.4.2 Until December 31, 2008, all aboveground storage containers that contain gasoline shall be equipped with pressure relief valves set at eight (8) ounces per square inch, unless:</p> <p>5.4.2.1 Otherwise specified in the applicable ARB Executive Order, or</p> <p>5.4.2.2 Such setting will exceed the vessel's maximum pressure rating.</p> <p>5.4.3 On and after January 1, 2009, all aboveground storage containers that contain gasoline shall be equipped with an ARB certified pressure vacuum relief valve set 3.0±0.5 inches water column pressure relief and 8.0±2.0</p>	<p>5.4 Aboveground Storage Containers</p> <p>5.4.1 All aboveground storage containers shall be constructed and maintained in a leak-free condition.</p> <p>5.4.2 All aboveground storage containers that contain gasoline shall be equipped with an ARB certified pressure vacuum relief valve set 3.0±0.5 inches water column pressure relief and 8.0±2.0 inches water column vacuum relief, unless:</p> <p>5.4.2.1 Otherwise specified in the applicable ARB Executive Order, or</p> <p>5.4.2.2 Such setting will exceed the vessel's maximum pressure rating.</p> <p>5.4.3 All aboveground storage containers that contain aviation gasoline shall be equipped with pressure relief valves set at eight (8) ounces per square inch, unless:</p>	<p>There are no changes in the requirements of this section.</p>

	<p>inches water column vacuum relief, unless:</p> <p>5.4.2.1 Otherwise specified in the applicable ARB Executive Order, or</p> <p>5.4.2.2 Such setting will exceed the vessel's maximum pressure rating.</p> <p>5.4.4 All aboveground storage containers that contain aviation gasoline shall be equipped with pressure relief valves set at eight (8) ounces per square inch, unless:</p> <p>5.4.4.1 Otherwise specified in the applicable ARB Executive Order or</p> <p>5.4.4.2 Such setting will exceed the vessel's maximum pressure rating.</p> <p>5.4.5 On and after June 20, 2008, operators of an aboveground storage container not located at a bulk plant shall conduct and pass the performance test specified in Sections 6.4.9 to determine compliance at least once every 36 months, (no more than 30 days before or after the required performance test date) unless otherwise required under ARB Executive Order.</p>	<p>5.4.3.1 Otherwise specified in the applicable ARB Executive Order or</p> <p>5.4.3.2 Such setting will exceed the vessel's maximum pressure rating.</p> <p>5.4.4 Operators of an aboveground storage container not located at a bulk plant shall conduct and pass the performance test specified in Section 6.4.8 to determine compliance at least once every 36 months, (no more than 30 days before or after the required performance test date) unless otherwise required under ARB Executive Order.</p>	
	<p>5.5 All Phase I vapor recovery systems shall be inspected according to the frequency specified in Table 1. The person conducting the inspections shall, at a minimum, verify the following:</p> <p>5.5.1 That the fill caps and vapor caps are not missing, damaged, or loose;</p> <p>5.5.2 That the fill cap gasket and vapor cap gaskets are not missing or damaged;</p> <p>5.5.3 That the fill adapter and vapor adapter are securely attached to the risers;</p> <p>5.5.4 That, where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing, and the dry break (poppet-valve) is not missing or damaged; and</p> <p>5.5.5 That the submerged fill tube is not missing or damaged.</p> <p><u>Table 1 – Schedule of Maintenance Inspection – Inspection Frequency based on gasoline dispensed during largest monthly throughput of previous year</u></p> <p><u>Retail:</u> Less than 25,000 gal – 1 day/week 25,000 gal or more – 5 days/week</p> <p><u>Non-Retail/Other:</u> Less than 2,500 gal – 1 day/month 2,500 to less than 25,000 gal – 1 day/week More than 25,000 gal - 5 days/week</p>	<p>5.5 All Phase I vapor recovery systems shall be inspected according to the frequency specified in Table 1. The person conducting the inspections shall, at a minimum, verify the following:</p> <p>5.5.1 That the fill caps and vapor caps are not missing, damaged, or loose;</p> <p>5.5.2 That the fill cap gasket and vapor cap gaskets are not missing or damaged;</p> <p>5.5.3 That the fill adapter and vapor adapter are securely attached to the risers;</p> <p>5.5.4 That, where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing, and the dry break (poppet-valve) is not missing or damaged; and</p> <p>5.5.5 That the submerged fill tube is not missing or damaged.</p> <p><u>Table 1 – Schedule of Maintenance Inspection – Inspection Frequency based on gasoline dispensed during largest monthly throughput of previous year</u></p> <p><u>Retail:</u> Less than 25,000 gal – 1 day/week 25,000 gal or more – 5 days/week</p> <p><u>Non-Retail/Other:</u> Less than 2,500 gal – 1 day/month 2,500 to less than 25,000 gal – 1 day/week More than 25,000 gal - 5 days/week</p>	<p>There are no changes in the requirements of this section.</p>
	<p>5.6 Bulk Plants and Loading Racks at Bulk Plants</p> <p>5.6.1 All bulk plants shall be equipped with an ARB certified vapor recovery system for loading operations (loading rack).</p> <p>5.6.2 The loading rack vapor recovery system shall not create a back pressure in excess of the pressure limits of the delivery vessel certification leak test (18 inches water column).</p> <p>5.6.3 Operators shall store or dispose of gasoline in closed, non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty.</p> <p>5.6.4 Bulk Plant Leak Inspections</p> <p>5.6.4.1 All bulk plants shall be constructed and maintained in a leak-free condition.</p> <p>5.6.4.2 All bulk plants shall be inspected for leaks at least once in every six-month period (from four to eight months apart) in accordance</p>	<p>5.6 Bulk Plants and Loading Racks at Bulk Plants</p> <p>5.6.1 All bulk plants shall meet one of the following requirements:</p> <p>5.6.1.1 Bulk plants not involved with aviation gasoline loading shall be equipped with an ARB certified vapor recovery system for loading operations (loading rack).</p> <p>5.6.1.2 Bulk plants involved with aviation gasoline loading shall be equipped with a vapor recovery system that meets a minimum volumetric control of 90% when measured in accordance with the test method specified in Section 6.4.9.</p> <p>5.6.2 The loading rack vapor recovery system shall not create a back pressure in excess of the pressure limits of the delivery vessel certification leak test (18 inches water column).</p> <p>5.6.3 Operators shall store or dispose of gasoline in closed, non-leaking containers. The containers shall remain closed at all times</p>	<p>In this section, the newly amended version of the rule is not as stringent as the SIP version since it does not require ARB certified vapor recovery systems for bulk plants involved with aviation gasoline loading.</p>

	<p>with the test procedure specified in Section 6.4.3.</p> <p>5.6.4.3 All loading racks located at bulk plants shall be inspected for leaks during product transfer at the frequency required in Section 5.6.5.2.</p> <p>5.6.4.4 If any storage container, storage container component, or loading rack component is found to leak during an inspection, the inspection frequency shall be changed to quarterly until the unit has successfully passed five consecutive quarterly inspections. Thereafter, the quarterly inspection may revert to the applicable inspection frequency specified in Section 5.6.4.2.</p> <p><u>5.6.5 Bulk Plant Leak Repair</u></p> <p>5.6.5.1 Upon detection of a leaking component, the operator shall affix to that component a weatherproof readily visible tag with the date and time of leak detection, the date and time of leak measurement, and for gas leaks, the leak concentration in ppmv.</p> <p>5.6.5.2 The tag shall remain affixed to the component until all the conditions specified in Sections 5.6.5.3 and 5.6.5.4 have been met.</p> <p>5.6.5.3 All leaking components shall be repaired or replaced within seven (7) business days after the leak is detected. If the component cannot be repaired within seven days, the operator must remove the leaking component(s) from VOC service.</p> <p>5.6.5.4 Upon returning a leaking component to service, the following conditions must be met.</p> <p>5.6.5.4.1 The component must be re-inspected using the test method specified in Section 6.4.3; and</p> <p>5.6.5.4.2 The component must be found to be in compliance with the requirements of this rule.</p>	<p>except when depositing or removing the contents of the containers or when the container is empty.</p> <p><u>5.6.4 Bulk Plant Leak Inspections</u></p> <p>5.6.4.1 All bulk plants shall be constructed and maintained in a leakfree condition.</p> <p>5.6.4.2 All bulk plants shall be inspected for leaks at least once in every six-month period (from four to eight months apart) in accordance with the test procedure specified in Section 6.4.2.</p> <p>5.6.4.3 All loading racks located at bulk plants shall be inspected for leaks during product transfer at the frequency required in Section 5.6.4.2.</p> <p>5.6.4.4 If any storage container, storage container component, or loading rack component is found to leak during an inspection, the inspection frequency shall be changed to quarterly until the unit has successfully passed five consecutive quarterly inspections. Thereafter, the quarterly inspection may revert to the applicable inspection frequency specified in Section 5.6.4.2.</p> <p><u>5.6.5 Bulk Plant Leak Repair</u></p> <p>5.6.5.1 Upon detection of a leaking component, the operator shall affix to that component a weatherproof readily visible tag with the date and time of leak detection, the date and time of leak measurement, and for gas leaks, the leak concentration in ppmv.</p> <p>5.6.5.2 The tag shall remain affixed to the component until all the conditions specified in Sections 5.6.5.3 and 5.6.5.4 have been met.</p> <p>5.6.5.3 All leaking components shall be repaired or replaced within seven (7) business days after the leak is detected. If the component cannot be repaired within seven (7) business days, the operator must remove the leaking component(s) from VOC service.</p> <p>5.6.5.4 Upon returning a leaking component to service, the following conditions must be met.</p> <p>5.6.5.4.1 The component must be re-inspected using the test method specified in Section 6.4.2; and</p> <p>5.6.5.4.2 The component must be found to be in compliance with the requirements of this rule.</p>	
	<p>5.7 Delivery Vessels</p> <p>5.7.1 All delivery vessels shall have an ARB certified vapor recovery system for cargo containers. Cargo container vapor recovery systems shall be maintained and tested in accordance with manufacturer specifications and any applicable ARB Executive Orders.</p> <p>5.7.2 No person shall operate, or allow the operation of a delivery vessel unless valid State of California decals which attest to the vapor integrity of the container are displayed.</p> <p>5.7.3 No person shall store gasoline in, otherwise use, or operate any gasoline delivery vessel unless such vessel is designed and maintained to be leakfree. Any delivery vessel into which gasoline vapors have been transferred shall be filled only at loading racks that are equipped with an ARB certified vapor recovery system.</p> <p>5.7.4 The hatch on a delivery vessel shall be equipped with a leak-free cover and the hatch</p>	<p>5.7 Delivery Vessels</p> <p>5.7.1 All delivery vessels shall have an ARB certified vapor recovery system for cargo containers. Cargo container vapor recovery systems shall be maintained and tested in accordance with manufacturer specifications and any applicable ARB Executive Orders.</p> <p>5.7.2 No person shall operate, or allow the operation of a delivery vessel unless valid State of California decals which attest to the vapor integrity of the container are displayed.</p> <p>5.7.3 No person shall store gasoline in, otherwise use, or operate any gasoline delivery vessel unless such vessel is designed and maintained to be leakfree. Any delivery vessel into which gasoline vapors have been transferred shall be filled only from loading racks or other delivery vessels that are equipped with an ARB certified vapor recovery system.</p> <p>5.7.4 The hatch on a delivery vessel shall be</p>	<p>There are no significant changes in the requirements of this section.</p>

	<p>shall not be opened for visual inspection unless at least three minutes have elapsed since loading or unloading has stopped. The dome hatch, once opened, shall not be held open longer than three minutes, except as directed by local, state, or federal agencies having jurisdiction.</p> <p>5.7.5 Gasoline vapors shall not be purged into the atmosphere. This includes relieving container pressure by manually "popping" the poppet valve on the truck-mounted vapor return line.</p> <p>5.7.6 Switch loading shall not be conducted unless such transfer is made using a permanently installed ARB certified vapor recovery system.</p> <p>5.7.7 During loading of the delivery vessel, the truck-mounted vapor return line shall be connected to a vapor recovery system that meets the requirements of this rule for the vapor recovery systems.</p>	<p>equipped with a leak-free cover and the hatch shall not be opened for visual inspection unless at least three minutes have elapsed since loading or unloading has stopped. The dome hatch, once opened, shall not be held open longer than three minutes, except as directed by local, state, or federal agencies having jurisdiction.</p> <p>5.7.5 Gasoline vapors shall not be purged into the atmosphere. This includes relieving container pressure by manually "popping" the poppet valve on the truck-mounted vapor return line.</p> <p>5.7.6 Switch loading shall not be conducted unless such transfer is made using a permanently installed ARB certified vapor recovery system.</p> <p>5.7.7 During loading of the delivery vessel, the truck-mounted vapor return line shall be connected to a vapor recovery system that meets the requirements of this rule for the vapor recovery systems.</p>	
<p>6.0 Administrative Requirements</p>	<p>6.1 Recordkeeping</p> <p>6.1.1 All data necessary to demonstrate qualifications for the exemptions allowed in this rule shall be maintained on the premise at all times and shall be submitted for District, ARB, or EPA review upon request. Such records shall include exemption status and volume delivered to each stationary storage container serviced.</p> <p>6.1.2 Bulk Plants and Loading Racks: A record of all inspections and all actions conducted on any part of the storage container or loading racks shall be maintained in chronological order showing date of inspection, description and location of any equipment replaced, and a description of the problem which required repair.</p> <p>6.1.3 Effective December 20, 2007, all bulk plants shall maintain daily gasoline throughput records.</p> <p>6.1.4 All records required to demonstrate compliance with the requirements of this rule shall be retained on the premises for a minimum of five years and made available on site during normal business hours to the APCO, ARB, or EPA, and submitted to the APCO, ARB, or EPA upon request.</p>	<p>6.1 Recordkeeping</p> <p>6.1.1 All data necessary to demonstrate qualifications for the exemptions allowed in this rule shall be maintained on the premises at all times and shall be submitted for District, ARB, or EPA review upon request. Such records shall include exemption status and volume delivered to each stationary storage container serviced.</p> <p>6.1.2 Bulk Plants and Loading Racks: A record of all inspections and all actions conducted on any part of the storage container or loading racks shall be maintained in chronological order showing date of inspection, description and location of any equipment replaced, and a description of the problem which required repair.</p> <p>6.1.3 All bulk plants shall maintain daily gasoline throughput records.</p> <p>6.1.4 All records required to demonstrate compliance with the requirements of this rule shall be retained on the premises for a minimum of five (5) years and made available on site during normal business hours to the APCO, ARB, or EPA, and submitted to the APCO, ARB, or EPA upon request.</p>	<p>There are no changes in the requirements of this section.</p>
	<p>6.2 Testing Requirements</p> <p>6.2.1 Operators shall conduct all performance tests required by ARB Executive Order and facility installation and operations manual as per the frequency outline therein or as designated by the APCO.</p> <p>6.2.2 Each ARB certified Phase I vapor recovery system shall be performance tested within 60 days of completion of installation or modification.</p> <p>6.2.3 Operators shall notify the District at least seven days prior to any performance testing.</p> <p>6.2.4 Operators shall submit all performance test results to the District within 30 days of test completion.</p>	<p>6.2 Testing Requirements</p> <p>6.2.1 Operators shall conduct all performance tests required by ARB Executive Order and facility installation and operations manual as per the frequency outline therein or as designated by the APCO.</p> <p>6.2.2 Each ARB certified Phase I vapor recovery system shall be performance tested within 60 days of completion of installation or modification.</p> <p>6.2.3 Bulk plants involved with aviation gasoline loading subject to Section 5.6.1.2 shall be performance tested within 60 days of completion of installation or modification.</p> <p>6.2.4 Operators shall notify the District at least seven (7) days prior to any performance testing.</p> <p>6.2.5 Operators shall submit all performance test results to the District within 30 days of test completion.</p>	<p>There are no significant changes in the requirements of this section.</p>

	<p>6.3 Certification Requirements</p> <p>6.3.1 Installation and maintenance contractors shall:</p> <p>6.3.1.1 On and after June 20, 2008, be certified by the ICC for Vapor Recovery System Installation and Repair (VI) and make available onsite proof of ICC certification for VI, and</p> <p>6.3.1.2 Have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems, or</p> <p>6.3.1.3 Work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available onsite a current certificate from the ICC, indicating he or she has passed the VI exam and all certifications required by the applicable Executive Order.</p> <p>6.3.2 All ICC certifications shall be renewed every 24 months by passing the appropriate exam specific to the certification being sought.</p> <p>6.3.3 Effective on and after March 21, 2008, Gasoline Dispensing Facility Testers wishing to conduct vapor recovery system testing and repair at facilities located within the District, shall be in full compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification).</p>	<p>6.3 Certification Requirements</p> <p>6.3.1 Installation and maintenance contractors shall:</p> <p>6.3.1.1 Be certified by the ICC for Vapor Recovery System Installation and Repair (VI) and make available onsite proof of ICC certification for VI, and</p> <p>6.3.1.2 Have and make available on site proof of any and all certifications required by the applicable ARB Executive Order and installation and operation manual in order to install or maintain specific systems, or</p> <p>6.3.1.3 Work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available onsite a current certificate from the ICC, indicating he or she has passed the VI exam and all certifications required by the applicable ARB Executive Order.</p> <p>6.3.2 All ICC certifications shall be renewed every 24 months by passing the appropriate exam specific to the certification being sought.</p> <p>6.3.3 Gasoline Dispensing Facility Testers wishing to conduct vapor recovery system testing and repair at facilities located within the District, shall be in full compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification).</p>	<p>There are no changes in the requirements of this section.</p>
--	---	---	--

ATTACHMENT F

District Rule 4622 Stringency Analysis

District Rule 4622 Stringency Analysis

Section	SIP Version (Amended December 20, 2007)	Non-SIP Version (Amended December 19, 2013)	Conclusion
1.0 Purpose	The purpose of this rule is to limit emissions of gasoline vapors from the transfer of gasoline into motor vehicle fuel tanks.	The purpose of this rule is to limit emissions of gasoline vapors from the transfer of gasoline into motor vehicle fuel tanks.	There are no changes in the requirements of this section.
2.0 Applicability	This rule applies to any gasoline storage and dispensing operation or mobile fueler from which gasoline is transferred into motor vehicle fuel tanks, except as provided in Section 4.0.	This rule applies to any gasoline storage and dispensing operation or mobile fueler from which gasoline is transferred into motor vehicle fuel tanks, except as provided in Section 4.0.	There are no changes in the requirements of this section.
3.0 Definitions (emissions-related sections only)	<p>3.17 Leak: the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.5.4. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.</p> <p>3.18 Major Defect: any defect that meets the criteria of California Code of Regulations, Title 17, Division III, Chapter 1, Subchapter 8, Article 1, Section 94006 and is listed on ARB's Vapor Recovery Equipment Defects (VRED) list or is specified within the Executive Order certifying the vapor recovery system, as applicable.</p> <p>3.19 Major Modification: the addition, replacement, or removal of fifty percent or more of the buried vapor piping, or the replacement of dispensers. The replacement of a dispenser is not a major modification when the replacement is occasioned by end user damage to a dispenser.</p> <p>3.21 Motor Vehicle: a vehicle that is self propelled.</p> <p>3.23 Portable Hydrocarbon Detection Instrument: a hand-held hydrocarbon analyzer that meets the criteria specified in US EPA Method 21, 40 CFR Part 60. The instrument shall be calibrated with methane.</p> <p>3.24 Phase II Vapor Recovery System: a vapor recovery system that controls vapors during the transfer of gasoline from the gasoline dispensing operation to the vehicle and storage of gasoline at the gasoline dispensing operation.</p> <p>3.26 Topping Off: to attempt to dispense gasoline to a motor vehicle fuel tank after a vapor recovery dispensing nozzle has shut off automatically. The filling of a vehicle tank which can be filled only after the seal between the fill pipe and the nozzle is broken, due to the nature and configuration of the fill pipe which causes premature shut-off of the dispensing nozzle, shall not be considered topping off.</p>	<p>3.20 Leak: the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.5.4. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.</p> <p>3.22 Major Defect: any defect that meets the criteria of California Code of Regulations, Title 17, Division III, Chapter 1, Subchapter 8, Article 1, Section 94006 and is listed on ARB's Vapor Recovery Equipment Defects (VRED) list or is specified within the ARB's Executive Order certifying the vapor recovery system, as applicable.</p> <p>3.23 Major Modification: the addition, replacement, or removal of fifty percent or more of the buried vapor piping, or the replacement of dispensers. The replacement of a dispenser is not a major modification when the replacement is occasioned by end user damage to a dispenser.</p> <p>3.25 Motor Vehicle: a vehicle that is self propelled.</p> <p>3.28 Portable Hydrocarbon Detection Instrument: a hand-held hydrocarbon analyzer that meets the criteria specified in US EPA Method 21, 40 CFR Part 60. The instrument shall be calibrated with methane.</p> <p>3.27 Phase II Vapor Recovery System: a vapor recovery system that controls vapors during the transfer of gasoline from the gasoline dispensing operation to the vehicle and storage of gasoline at the gasoline dispensing operation.</p> <p>3.30 Topping Off: to attempt to dispense gasoline to a motor vehicle fuel tank after a vapor recovery dispensing nozzle has shut off automatically. The filling of a vehicle tank which can be filled only after the seal between the fill pipe and the nozzle is broken, due to the nature and configuration of the fill pipe which causes premature shut-off of the dispensing nozzle, shall not be considered topping off.</p>	There are no changes in any significant emissions related definitions.

	<p>3.27 Vehicle: a device by which any person or property may be propelled, moved, or drawn upon a highway, excepting a device moved exclusively by human power or used exclusively upon stationary rails or tracks.</p> <p>3.28 Vehicle Fleet: a group of vehicles operated under the control of a single owner/operator.</p>	<p>3.31 Vehicle: a device by which any person or property may be propelled, moved, or drawn upon a highway, excepting a device moved exclusively by human power or used exclusively upon stationary rails or tracks.</p> <p>3.32 Vehicle Fleet: a group of vehicles operated under the control of a single owner/operator.</p>	
4.0 Exemptions	<p>4.1 Except for the provisions of Section 6.1.1 and 6.1.2, requirements of this rule shall not apply to the transfer of gasoline into motor vehicle fuel tanks from any existing storage container, as defined in Section 3.10, with an aggregate dispensing operation throughput of:</p> <p>4.1.1 less than or equal to 24,000 gallons per calendar year; and</p> <p>4.1.2 less than or equal to 10,000 gallons in any consecutive 30-day period.</p> <p>4.1.3 Any facility which exceeds the throughput limitations under Section 4.1.1 or 4.1.2 shall be subject to all provisions of this rule on and after the date the throughput limitations were exceeded and shall be in compliance according to the schedule in Section 7.1.</p> <p>4.2 The requirements of this rule shall not apply to gasoline storage containers that are exempt pursuant to Section 4.0 of Rule 4621 (Gasoline Transfer into Stationary Storage Containers, Delivery Vessels, and Bulk Plants).</p> <p>4.3 Except for Section 6.1.3 and 7.5, the requirements of this rule shall not apply to vehicle fleets where 100 percent of the vehicles are equipped with onboard refueling vapor recovery (ORVR) systems. To qualify for this exemption, the operator must also own the gasoline dispensing operation that services the vehicle fleet.</p> <p>4.4 The requirements of this rule shall not apply to a mobile fueler that exclusively fuels aircraft.</p>	<p>4.1 Except for the provisions of Section 6.1.1 and 6.1.2, requirements of this rule shall not apply to the transfer of gasoline into motor vehicle fuel tanks from any existing storage container, as defined in Section 3.11, with an aggregate dispensing operation throughput of:</p> <p>4.1.1 less than or equal to 24,000 gallons per calendar year; and</p> <p>4.1.2 less than or equal to 10,000 gallons in any consecutive 30-day period.</p> <p>4.1.3 Any facility which exceeds the throughput limitations under Section 4.1.1 or 4.1.2 shall be subject to all provisions of this rule on and after the date the throughput limitations were exceeded and shall be in compliance according to the schedule in Section 7.1.</p> <p>4.2 The requirements of this rule shall not apply to gasoline storage containers that are exempt pursuant to Section 4.0 of Rule 4621 (Gasoline Transfer into Stationary Storage Containers, Delivery Vessels, and Bulk Plants).</p> <p>4.3 Except for Section 6.1.3 and 7.2, the requirements of this rule shall not apply to vehicle fleets where 100 percent of the vehicles are equipped with onboard refueling vapor recovery (ORVR) systems. To qualify for this exemption, the operator must also own the gasoline dispensing operation that services the vehicle fleet.</p> <p>4.4 The requirements of this rule shall not apply to a mobile fueler that exclusively fuels aircraft.</p> <p>4.5 The requirements of Section 6.4.1 shall not apply to mobile fuelers registered under Permit-Exempt Equipment Registration program pursuant to Section 5.11.</p> <p>4.6 The requirements of this rule shall not apply to E85 fuel dispensing operations.</p>	<p>The newly amended version of the rule provides two additional exemptions that did not exist in the SIP version of the rule. The newly amended version of the rule is therefore not as stringent as the SIP version in this section.</p>
5.0 Requirements	<p>5.1 A person shall not transfer or permit the transfer of gasoline from any stationary storage container, or from any mobile fueler with a capacity greater than 120 gallons, into a motor vehicle fuel tank with a capacity greater than 5 gallons, unless the gasoline dispensing unit used to transfer the gasoline is equipped with and has in operation an ARB certified Phase II vapor recovery system.</p> <p>5.1.1 All ARB certified Phase II vapor recovery systems shall be maintained according to ARB certifications and the manufacturer specifications applicable to the system.</p> <p>5.1.2 All ARB certified Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method in Section 6.5.4.</p>	<p>5.1 A person shall not transfer or permit the transfer of gasoline from any stationary storage container, or from any mobile fueler with a capacity greater than 120 gallons, into a motor vehicle fuel tank with a capacity greater than 5 gallons, unless the gasoline dispensing unit used to transfer the gasoline is equipped with and has in operation an ARB certified Phase II vapor recovery system.</p> <p>5.1.1 All ARB certified Phase II vapor recovery systems shall be maintained according to ARB certifications and the manufacturer specifications applicable to the system.</p> <p>5.1.2 All ARB certified Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method in Section 6.5.4.</p>	<p>There are no changes in the requirements of this section.</p>

	<p>5.2 Installation</p> <p>5.2.1 Any gasoline dispensing system subject to this rule shall comply with the provisions of this rule at the time of installation.</p> <p>5.2.2 Operators shall have all underground storage container installations and all underground piping configurations inspected by the APCO prior to backfilling. The operator shall notify the District by telephone or other District-approved method and obtain a confirmation number at least three business days prior to the backfilling.</p> <p>5.2.3 Installation and maintenance contractors shall comply with the following requirements on and after June 20, 2008:</p> <p>5.2.3.1 Be certified by the ICC for Vapor Recovery System Installation and Repair; and</p> <p>5.2.3.2 Renew the ICC certification for Vapor Recovery System Installation and Repair every 24 months.</p> <p>5.2.3.3 Make available onsite proof of ICC certification, and</p> <p>5.2.3.4 Have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems.</p> <p>5.2.4 In lieu of complying with Sections 5.2.3.1 through 5.2.3.4, installation and maintenance contractors may work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available on site current certifications from the ICC, indicating the individual has passed the ICC Vapor Recovery System Installation and Repair exam and all other certifications required by the applicable Executive Order.</p> <p>5.2.5 Notwithstanding any provisions of this rule, any gasoline dispensing operation which has installed and obtained a permit to operate an ARB certified Phase II vapor recovery system shall continue to use such system and shall maintain the system and all of its components in good repair in order that such system can continue to comply with the certification recovery efficiency.</p> <p>5.2.6 Any ARB certified Phase II vapor recovery system that has been installed shall not be removed regardless of the amount of gasoline dispensed or how the gasoline is delivered to the operation.</p> <p>5.2.6.1 This requirement shall not include those operations that are exempt or become exempt per Section 4.3.</p> <p>5.2.6.2 This requirement shall not preclude the installation of a new ARB certified Phase II vapor recovery system.</p>	<p>5.2 Installation</p> <p>5.2.1 Any gasoline dispensing system subject to this rule shall comply with the provisions of this rule at the time of installation.</p> <p>5.2.2 Operators shall have all underground storage container installations and all underground piping configurations inspected by the APCO prior to backfilling. The operator shall notify the District by telephone or other District-approved method and obtain a confirmation number at least three business days prior to the backfilling.</p> <p>5.2.3 Installation and maintenance contractors shall comply with the following requirements:</p> <p>5.2.3.1 Be certified by the ICC for Vapor Recovery System Installation and Repair; and</p> <p>5.2.3.2 Renew the ICC certification for Vapor Recovery System Installation and Repair every 24 months.</p> <p>5.2.3.3 Make available onsite proof of ICC certification, and</p> <p>5.2.3.4 Have and make available on site proof of any and all certifications required by the applicable ARB Executive Order and installation and operation manual in order to install or maintain specific systems.</p> <p>5.2.4 In lieu of complying with Sections 5.2.3.1 through 5.2.3.4, installation and maintenance contractors may work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available on site current certifications from the ICC, indicating the individual has passed the ICC Vapor Recovery System Installation and Repair exam and all other certifications required by the applicable ARB Executive Order.</p> <p>5.2.5 Notwithstanding any provisions of this rule, any gasoline dispensing operation which has installed and obtained a permit to operate an ARB certified Phase II vapor recovery system shall continue to use such system and shall maintain the system and all of its components in good repair in order that such system can continue to comply with the certification recovery efficiency.</p> <p>5.2.6 Any ARB certified Phase II vapor recovery system that has been installed shall not be removed regardless of the amount of gasoline dispensed or how the gasoline is delivered to the operation.</p> <p>5.2.6.1 This requirement shall not include those operations that are exempt or become exempt per Section 4.3.</p> <p>5.2.6.2 This requirement shall not preclude the installation of a new ARB certified Phase II vapor recovery system.</p>	<p>There are no changes in the requirements of this section.</p>
	<p>5.3 Inspections</p> <p>5.3.1 The owner or operator of an ARB certified Phase II vapor recovery system shall conduct periodic maintenance inspections to ensure that components of the vapor recovery system are in proper operating condition.</p>	<p>5.3 Inspections</p> <p>5.3.1 The owner or operator of an ARB certified Phase II vapor recovery system shall conduct periodic maintenance inspections to ensure that components of the vapor recovery system are in proper operating condition.</p>	<p>There are no changes in the requirements of this section.</p>

	<p>5.3.2 The frequency of inspections shall be based on the operation's largest monthly gasoline throughput from the previous calendar year as indicated in Table 1.</p> <p><u>Table 1 – Schedule of Maintenance Inspection – Inspection Frequency based on gasoline dispensed during largest monthly throughput of previous year</u></p> <p><u>Retail:</u> Less than 25,000 gal – 1 day/week 25,000 gal or more – 5 days/week</p> <p><u>Non-Retail/Other:</u> Less than 2,500 gal – 1 day/month 2,500 to less than 25,000 gal – 1 day/week More than 25,000 gal - 5 days/week</p> <p>5.3.3 Until June 20, 2008, except for gasoline dispensing operations identified in Table 1 Category B.1, the vapor path shall be inspected at least once per week. Until June 20, 2008, for facilities identified in Table 1 Category B.1, the vapor path shall be inspected at least once per calendar month.</p> <p>5.3.4 On and after June 20, 2008, the frequency of vapor path inspections shall be based on the amount of gasoline dispensed by the operation in a calendar month as indicated in Table 1.</p> <p>5.3.5 The person conducting the inspections shall at a minimum, verify the following during inspections:</p> <p>5.3.5.1 That the fueling instructions required by Section 5.5 are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs.</p> <p>5.3.5.2 That the following nozzle components are in place and in good condition as specified in ARB Executive Orders: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, hold open latch.</p> <p>5.3.5.3 That the hoses are not torn, flattened or crimped.</p> <p>5.3.5.4 That the vapor path of coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid.</p> <p>5.3.5.4.1 The amount of liquid in the vapor path shall be determined by lowering the gasoline dispensing nozzle into a container, opening the vapor check valve, and allowing the hose to drain until such time that no more liquid drains from the nozzle.</p> <p>5.3.5.4.2 The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker.</p> <p>5.3.5.5 That the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit.</p>	<p>5.3.2 The frequency of inspections shall be based on the operation's largest monthly gasoline throughput from the previous calendar year as indicated in Table 1.</p> <p><u>Table 1 – Schedule of Maintenance Inspection – Inspection Frequency based on gasoline dispensed during largest monthly throughput of previous year</u></p> <p><u>Retail:</u> Less than 25,000 gal – 1 day/week 25,000 gal or more – 5 days/week</p> <p><u>Non-Retail/Other:</u> Less than 2,500 gal – 1 day/month 2,500 to less than 25,000 gal – 1 day/week More than 25,000 gal - 5 days/week</p> <p>5.3.3 The frequency of vapor path inspections shall be based on the amount of gasoline dispensed by the operation in a calendar month as indicated in Table 1.</p> <p>5.3.4 The person conducting the inspections shall at a minimum, verify the following during inspections:</p> <p>5.3.4.1 That the fueling instructions required by Section 5.5 are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs.</p> <p>5.3.4.2 That the following nozzle components are in place and in good condition as specified in ARB Executive Orders: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, hold open latch.</p> <p>5.3.4.3 That the hoses are not torn, flattened or crimped.</p> <p>5.3.4.4 That the vapor path of coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid, or as required by the applicable ARB Executive Order.</p> <p>5.3.4.4.1 The amount of liquid in the vapor path shall be determined by lowering the gasoline dispensing nozzle into a container, opening the vapor check valve, and allowing the hose to drain until such time that no more liquid drains from the nozzle.</p> <p>5.3.4.4.2 The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker.</p> <p>5.3.4.5 That the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit.</p>	
	<p>5.4 Maintenance and Repair</p> <p>5.4.1 No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order, until:</p> <p>5.4.1.1 The defect has been repaired, replaced, or adjusted as necessary to correct the defect;</p>	<p>5.4 Maintenance and Repair</p> <p>5.4.1 No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect until:</p> <p>5.4.1.1 The defect has been repaired, replaced, or adjusted as necessary to correct the defect;</p> <p>5.4.1.2 The District has been notified, and the District has reinspected the system or</p>	<p>There are no changes in the requirements of this section.</p>

	<p>5.4.1.2 The District has been notified, and the District has reinspected the system or authorized the system for use. Such authorization shall not include the authority to operate the equipment prior to the correction of the defective components; and</p> <p>5.4.1.3 All major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual.</p> <p>5.4.2 Upon identification of any major defect, the owner or operator shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired.</p> <p>5.4.2.1 Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary.</p> <p>5.4.2.2 In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use.</p> <p>5.4.3 Breakaway valves, hoses, and nozzles shall be ARB certified.</p> <p>5.4.4 In the event of a separation due to a drive off, the owner or operator shall complete one of the following, unless otherwise specified in the applicable ARB Executive Order, and document the activities in accordance with Section 6.2, before placing the affected equipment back in service:</p> <p>5.4.4.1 Conduct a visual inspection of the affected equipment, perform qualified repairs on any damaged components, and conduct applicable reverification tests pursuant to Sections 6.5.1.1 and 6.5.1.4, or</p> <p>5.4.4.2 Conduct a visual inspection of the affected equipment and replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified, before placing affected equipment back in service.</p>	<p>authorized the system for use. Such authorization shall not include the authority to operate the equipment prior to the correction of the defective components; and</p> <p>5.4.1.3 All major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual.</p> <p>5.4.2 Upon identification of any major defect, the owner or operator shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired.</p> <p>5.4.2.1 Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary.</p> <p>5.4.2.2 In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use.</p> <p>5.4.3 Breakaway valves, hoses, and nozzles shall be ARB certified.</p> <p>5.4.4 In the event of a separation due to a drive off, the owner or operator shall complete one of the following, unless otherwise specified in the applicable ARB Executive Order, and document the activities in accordance with Section 6.2, before placing the affected equipment back in service:</p> <p>5.4.4.1 Conduct a visual inspection of the affected equipment, perform qualified repairs on any damaged components, and conduct applicable reverification tests pursuant to Sections 6.5.1.1 and 6.5.1.4, or</p> <p>5.4.4.2 Conduct a visual inspection of the affected equipment and replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified, before placing affected equipment back in service.</p>	
	<p>5.5 No owner or operator of a retail gasoline outlet shall operate or allow the operation of an ARB certified Phase II vapor recovery system unless operating instructions for the system:</p> <p>5.5.1 Are posted, noticeable, and readable from any place from which gasoline may be dispensed from the operation,</p> <p>5.5.2 Describe clearly how to fuel vehicles correctly using the station's dispensing nozzles,</p> <p>5.5.3 Include a warning that topping off may result in spillage or recirculation of gasoline and is prohibited, and</p> <p>5.5.4 Display prominently the District's or the ARBs toll-free telephone number, or both, and the information that such number or numbers can be used to register complaints regarding the operation of the vapor recovery</p>	<p>5.5 No owner or operator of a retail gasoline outlet shall operate or allow the operation of an ARB certified Phase II vapor recovery system unless operating instructions for the system:</p> <p>5.5.1 Are posted, noticeable, and readable from any place from which gasoline may be dispensed from the operation,</p> <p>5.5.2 Describe clearly how to fuel vehicles correctly using the station's dispensing nozzles,</p> <p>5.5.3 Include a warning that topping off may result in spillage or recirculation of gasoline and is prohibited, and</p> <p>5.5.4 Display prominently the District's or the ARBs toll-free telephone number, or both, and the information that such number or numbers can be used to register complaints regarding the operation of the vapor recovery</p>	<p>There are no changes in the requirements of this section.</p>

5.6 No person shall top off a motor vehicle fuel tank.	5.6 No person shall top off a motor vehicle fuel tank.	There are no changes in the requirements of this section.
<p>5.7 Each retail gasoline outlet shall utilize hold-open latches on all gasoline dispensing nozzles.</p> <p>5.7.1 Any gasoline dispensing nozzle which is installed, repaired, or replaced shall be equipped with a hold-open latch.</p> <p>5.7.2 The hold-open latch shall be installed on the gasoline dispensing nozzle by the original manufacturer of the nozzle, or if retrofitted, shall be installed using components and procedures approved by the nozzle manufacturer.</p>	<p>5.7 Each retail gasoline outlet shall utilize hold-open latches on all gasoline dispensing nozzles.</p> <p>5.7.1 Any gasoline dispensing nozzle which is installed, repaired, or replaced shall be equipped with a hold-open latch.</p> <p>5.7.2 The hold-open latch shall be installed on the gasoline dispensing nozzle by the original manufacturer of the nozzle, or if retrofitted, shall be installed using components and procedures approved by the nozzle manufacturer.</p>	There are no changes in the requirements of this section.
5.8 The requirements of Section 5.7 shall not apply to operations where the use of holdopen latches is prohibited by law or the local fire control authority.	5.8 The requirements of Section 5.7 shall not apply to operations where the use of holdopen latches is prohibited by law or the local fire control authority.	There are no changes in the requirements of this section.
5.9 No owner or operator shall tamper with, or permit tampering with, the system in a manner that would impair the operation or effectiveness of the system.	5.9 No owner or operator shall tamper with, or permit tampering with, the system in a manner that would impair the operation or effectiveness of the system.	There are no changes in the requirements of this section.
5.10 All liquid removal devices required by ARB Executive Order shall be maintained to achieve a minimum liquid removal rate of five milliliters per gallon. This standard shall apply at dispensing rates exceeding five gallons per minute, unless a higher removal rate is specified in the applicable Executive Order.	5.10 All liquid removal devices required by ARB Executive Order shall be maintained to achieve a minimum liquid removal rate of five milliliters per gallon. This standard shall apply at dispensing rates exceeding five gallons per minute, unless a higher removal rate is specified in the applicable Executive Order.	There are no changes in the requirements of this section.
<p>5.11 Mobile Fueler Registration Requirements On and after December 20, 2008, the owner of a mobile fueler shall register such mobile fueler pursuant to Rule 2250 (Permit-Exempt Equipment Registration), except for a mobile fueler that is not required to comply with Section 5.1 of this rule.</p>	<p>5.11 Mobile Fueler Registration Requirements The owner of a mobile fueler shall register such mobile fueler pursuant to Rule 2250 (Permit-Exempt Equipment Registration), except for a mobile fueler that is not required to comply with Section 5.1 of this rule.</p>	There are no changes in the requirements of this section.
	<p>5.12 Liquid Condensate Traps Liquid condensate traps shall be used, if necessary, to keep the vapor return piping clear of any liquid blockage from the remote dispenser to the aboveground storage tank or when it is not possible to achieve the necessary slope from the dispenser to the underground storage tank.</p> <p>5.12.1 Liquid condensate traps shall be used only when the minimum slope requirements of 1/8 inches per foot of run cannot be met due to the topography.</p> <p>5.12.2 When liquid condensate traps are installed on gasoline dispensing systems equipped with an ARB certified Phase II enhanced vapor recovery system, they shall meet the following requirements:</p> <ul style="list-style-type: none"> 5.12.2.1 Maintained vapor tight; 5.12.2.2 Accessible for inspection upon request; 5.12.2.3 Capable of automatic evacuation of liquid; and 5.12.2.4 Equipped with an alarm system in case of failure of the evacuation system. 	This is a new section. Since it addresses a requirement on which the rule was previously silent, its overall effect is to make the rule more stringent.
	<p>5.13 In-Station Diagnostics (ISD) System 5.13.1 The owner or operator shall not clear, or allow any other individual to clear, any ISD warning or failure alarms prior to taking</p>	This is a new section. Since it addresses requirements for

		<p>appropriate action. The appropriate action shall be in accordance with the IOM manual for the Phase II vapor recovery system or an ARB Enforcement Advisory.</p> <p>5.13.2 In the event of an ISD failure alarm and subsequent automatic shutdown of gasoline dispensing, the owner or operator shall not re-enable or allow the re-enabling of the affected fueling point(s) unless all troubleshooting, repairs and tests specified in the applicable ARB Executive Order and IOM for the Phase II vapor recovery system, have been successfully completed or are in the process of being completed and documented.</p> <p>5.13.3 The owner or operator shall keep records of all alarms detected by the ISD system. The records shall include the following:</p> <ul style="list-style-type: none"> 5.13.3.1 The alarm date; 5.13.3.2 The nature of the alarm; 5.13.3.3 Type of test and test date to verify the validity of ISD alarm; 5.13.3.4 Maintenance or repair date to correct the cause of the alarm; 5.13.3.5 Maintenance or repair performed to correct the cause of the alarm; and 5.13.3.6 Affiliation, telephone number, name and Certified Technician Identification Number of individual conducting maintenance or test. 	<p>components/ systems that were previously not in use, it has no overall bearing on the stringency of the rule.</p>
<p>6.0 Administrative Requirements</p>	<p>6.1 Recordkeeping and Reporting for Exempt Operations:</p> <p>6.1.1 Gasoline dispensing operations that are exempt under Section 4.1 shall maintain gasoline throughput records which will allow the gasoline throughput for any 30-day period to be continuously determined. These records shall be maintained on the premises as long as exempt status is claimed.</p> <p>6.1.2 Any gasoline dispensing operation previously exempt under Section 4.1 whose gasoline throughput exceeds the exemption levels in Sections 4.1.1 and 4.1.2 shall notify the District within 30 days of the date of exceeding the exemption levels.</p> <p>6.1.3 An operator claiming exemption under Section 4.3 shall keep a record of the make, model, model year, and vehicle identification number of all vehicles refueled at the gasoline dispensing operation. These records shall be maintained on the premises for at least five calendar years.</p>	<p>6.1 Recordkeeping and Reporting for Exempt Operations:</p> <p>6.1.1 Gasoline dispensing operations that are exempt under Section 4.1 shall maintain gasoline throughput records which will allow the gasoline throughput for any 30-day period to be continuously determined. These records shall be maintained on the premises as long as exempt status is claimed.</p> <p>6.1.2 Any gasoline dispensing operation previously exempt under Section 4.1 whose gasoline throughput exceeds the exemption levels in Sections 4.1.1 and 4.1.2 shall notify the District within 30 days of the date of exceeding the exemption levels.</p> <p>6.1.3 An operator claiming exemption under Section 4.3 shall keep a record of the make, model, model year, and vehicle identification number of all vehicles refueled at the gasoline dispensing operation. These records shall be maintained on the premises for at least five calendar years.</p>	<p>There are no changes in the requirements of this section.</p>
	<p>6.2 Recordkeeping and Reporting for Non-exempt Operations</p> <p>6.2.1 Operators shall retain the test result verification that each ARB certified Phase II vapor recovery system meets or exceeds the requirements of the tests specified in Section 6.5. These verifications shall be maintained for at least five years. These test results shall be dated and shall contain the names, addresses, and telephone numbers of the companies responsible for system installation and testing.</p> <p>6.2.2 A person who performs repairs on any ARB</p>	<p>6.2 Recordkeeping and Reporting for Non-exempt Operations</p> <p>6.2.1 Operators shall retain the test result verification that each ARB certified Phase II vapor recovery system meets or exceeds the requirements of the tests specified in Section 6.5. These verifications shall be maintained for at least five years. These test results shall be dated and shall contain the names, addresses, and telephone numbers of the companies responsible for system installation and testing.</p> <p>6.2.2 A person who performs repairs on any ARB</p>	<p>There are no changes in the requirements of this section.</p>

	<p>certified Phase I or Phase II vapor recovery system shall provide to the owner or operator a repair log, which the owner or operator shall maintain on the premises for at least five years and which shall include all of the following:</p> <ul style="list-style-type: none"> 6.2.2.1 Date and time of each repair; 6.2.2.2 The name and applicable certification numbers of the person(s) who performed the repair, and, if applicable, the name, address and phone number of the person's employer; 6.2.2.3 Description of service performed; 6.2.2.4 Each component that was repaired, serviced, or removed; 6.2.2.5 Each component that was installed as replacement, if applicable; 6.2.2.6 Receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. <p>6.2.3 Each operator who is required to perform periodic maintenance inspections under Section 5.3 shall maintain monthly gasoline throughput records on the premises for a minimum of five years, make them available on site during normal business hours to the APCO, ARB, or EPA, and submit them to the APCO, ARB, or EPA upon request.</p>	<p>certified Phase I or Phase II vapor recovery system shall provide to the owner or operator a repair log, which the owner or operator shall maintain on the premises for at least five years and which shall include all of the following:</p> <ul style="list-style-type: none"> 6.2.2.1 Date and time of each repair; 6.2.2.2 The name and applicable certification numbers of the person(s) who performed the repair, and, if applicable, the name, address and phone number of the person's employer; 6.2.2.3 Description of service performed; 6.2.2.4 Each component that was repaired, serviced, or removed; 6.2.2.5 Each component that was installed as replacement, if applicable; 6.2.2.6 Receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. <p>6.2.3 Each operator who is required to perform periodic maintenance inspections under Section 5.3 shall maintain monthly gasoline throughput records on the premises for a minimum of five years, make them available on site during normal business hours to the APCO, ARB, or EPA, and submit them to the APCO, ARB, or EPA upon request.</p>	
	<p>6.3 Recordkeeping Requirements for the Operations & Maintenance Manual (O&M Manual)</p> <p>6.3.1 The owner or operator of a gasoline dispensing operation shall maintain an O&M Manual in accordance with Section 6.3.</p> <p>6.3.2 The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request.</p> <p>6.3.3 The O&M manual shall, at a minimum, include the following current information:</p> <ul style="list-style-type: none"> 6.3.3.1 Copies of all vapor recovery performance tests, 6.3.3.2 All applicable ARB Executive Orders, Approval Letters, and District Permits, 6.3.3.3 Manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer, 6.3.3.4 System and/or component testing requirements, including test schedules and passing criteria for each of the standard tests listed in Section 6.0. The owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements, and 6.3.3.5 Additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. <p>6.3.4 Owners or operators of gasoline dispensing</p>	<p>6.3 Recordkeeping Requirements for the Operations & Maintenance Manual (O&M Manual)</p> <p>6.3.1 The owner or operator of a gasoline dispensing operation shall maintain an O&M Manual in accordance with Section 6.3.</p> <p>6.3.2 The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request.</p> <p>6.3.3 The O&M manual shall, at a minimum, include the following current information:</p> <ul style="list-style-type: none"> 6.3.3.1 Copies of all vapor recovery performance tests, 6.3.3.2 All applicable ARB Executive Orders, Approval Letters, and District Permits, 6.3.3.3 Manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB certification procedures, and any additional instruction provided by the manufacturer, 6.3.3.4 System and/or component testing requirements, including test schedules and passing criteria for each of the standard tests listed in Section 6.0. The owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements, and 6.3.3.5 Additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. <p>6.3.4 Owners or operators of gasoline dispensing operations shall document the periodic</p>	<p>There are no changes in the requirements of this section.</p>

	<p>operations shall document the periodic maintenance inspection program in the O&M manual.</p>	<p>maintenance inspection program in the O&M manual.</p>	
	<p>6.4 Testing Requirements</p> <p>6.4.1 Operators shall comply with the ARB certified Phase II vapor recovery system performance tests specified in Sections 6.4.1.1 through 6.4.1.4 and shall conduct all applicable performance tests at start up and thereafter (no more than 30 days before or after the required compliance testing date) as required by ARB Executive Order and installation and operation manuals.</p> <p>6.4.1.1 Conduct and pass a Static Leak Test of the ARB certified Phase II vapor recovery system at least once every twelve months.</p> <p>6.4.1.2 Conduct and pass a Dynamic Back-Pressure Test of the ARB certified Phase II vapor recovery system at least once every twelve months except for those aboveground storage tanks that have integral dispensers (non-remote), unless otherwise required under ARB Executive Order.</p> <p>6.4.1.3 For ARB certified Phase II vapor recovery systems with bellowsless nozzles, conduct and pass, as applicable, an Air-to-Liquid Volume Ratio Test or a Vapor-to-Liquid Ratio Test at least once every six months.</p> <p>6.4.1.4 For ARB certified Phase II vapor recovery systems with a liquid removal device required by ARB Executive Orders, conduct and pass a Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid. The amount of liquid in the vapor path shall be determined in accordance with the procedure specified in Section 5.3.5.4.</p> <p>6.4.2 The person responsible for conducting the tests specified in Section 6.4 shall use calibrated equipment meeting the calibration range and calibration intervals specified by the manufacturer, ARB Executive Order, or ARB test procedure.</p> <p>6.4.3 Until March 20, 2008 persons responsible for conducting the tests specified in Section 6.5 shall have completed a District-approved training program or the District's orientation class for testing and any subsequent required refresher class.</p> <p>6.4.4 Effective on and after March 21, 2008, persons responsible for conducting the tests specified in Section 6.5 shall be in full compliance with all provisions of Rule 1177 (Gasoline Dispensing Facility Tester Certification).</p> <p>6.4.5 Each gasoline dispensing operation shall notify the District at least seven days prior to any performance testing.</p> <p>6.4.6 Each ARB certified Phase II vapor recovery system shall be tested within 60 days of completion of installation or modification.</p>	<p>6.4 Testing Requirements</p> <p>6.4.1 Operators shall comply with the ARB certified Phase II vapor recovery system performance tests specified in Sections 6.4.1.1 through 6.4.1.4 and shall conduct all applicable performance tests at start up and thereafter (no more than 30 days before or after the required compliance testing date) as required by ARB Executive Order and installation and operation manuals.</p> <p>6.4.1.1 Conduct and pass a Static Leak Test of the ARB certified Phase II vapor recovery system at least once every twelve months.</p> <p>6.4.1.2 Conduct and pass a Dynamic Back-Pressure Test of the ARB certified Phase II vapor recovery system at least once every five years except for those aboveground storage tanks that have integral dispensers (non-remote), unless otherwise required under ARB Executive Order.</p> <p>6.4.1.3 For ARB certified Phase II vapor recovery systems with bellowsless nozzles, conduct and pass, as applicable, an Air-to-Liquid Volume Ratio Test or a Vapor-to-Liquid Ratio Test at least once every six months.</p> <p>6.4.1.4 For ARB certified Phase II vapor recovery systems with a liquid removal device required by ARB Executive Orders, conduct and pass a Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid. The amount of liquid in the vapor path shall be determined in accordance with the procedure specified in Section 5.3.4.4.</p> <p>6.4.2 The person responsible for conducting the tests specified in Section 6.4 shall use calibrated equipment meeting the calibration range and calibration intervals specified by the manufacturer, ARB Executive Order, or ARB test procedure.</p> <p>6.4.3 Persons responsible for conducting the tests specified in Section 6.5 shall be in full compliance with all provisions of Rule 1177 (Gasoline Dispensing Facility Tester Certification).</p> <p>6.4.4 Each gasoline dispensing operation shall notify the District at least seven days prior to any performance testing.</p> <p>6.4.5 Each ARB certified Phase II vapor recovery system shall be tested within 60 days of completion of installation or modification.</p>	<p>The newly amended version of the rule has reduced the testing frequency for the Dynamic Back-Pressure Test from 'once every twelve months' to 'once every five years.'</p> <p>The newly amended version of the rule is therefore not as stringent as the SIP version in this section.</p>