



APR 15 2011

Matt Towers
O'Neill Beverage Co.
8418 S. Lac Jac Avenue
Parlier, CA 93648-9708

**Re: Notice of Significant Title V Permit Modification
District Facility # C-629
Project # C-1110535**

Dear Mr. Towers:

Enclosed for you to review is the District's analysis of an application for significant Title V permit modification for the facility identified above. O'Neill Beverage Co. is proposing a Title V significant permit modification to incorporate the recently issued Authorities to Construct C-629-333-0, 1, & 2 through '-378-0, -1, & -2, '-381-0, -1, & -2 and '-382-0, -1, & -2 into the Title V operating permit (see enclosures). O'Neill Beverages proposes to incorporate these new units into the Title V permit.

Enclosed are the current Title V permit, recently issued Authorities to Construct C-629-333-0, 1, & 2 through '-378-0, -1, & -2, '-381-0, -1, & -2 and '-382-0, -1, & -2, proposed modified Title V permit, engineering evaluation, and application. The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period that begins on the date you receive this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

Enclosures

c: Dennis Roberts, Permit Services

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



APR 15 2011

Gerardo C. Rios, Chief
Permits Office
Air Division
U.S. EPA - Region IX
75 Hawthorne St.
San Francisco, CA 94105

**Re: Notice of Significant Title V Permit Modification
District Facility # C-629
Project # C-1110535**

Dear Mr. Rios:

Enclosed for you to review is the District's analysis of an application for significant Title V permit modification for the facility identified above. O'Neill Beverage Co. is proposing a Title V significant permit modification to incorporate the recently issued Authorities to Construct C-629-333-0, 1, & 2 through '-378-0, -1, & -2, '-381-0, -1, & -2 and '-382-0, -1, & -2 into the Title V operating permit (see enclosures). O'Neill Beverages proposes to incorporate these new units into the Title V permit.

Enclosed are the current Title V permit, recently issued Authorities to Construct C-629-333-0, 1, & 2 through '-378-0, -1, & -2, '-381-0, -1, & -2 and '-382-0, -1, & -2, proposed modified Title V permit, engineering evaluation, and application. The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 45-day comment period that begins on the date you receive this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

Enclosures

c: Dennis Roberts, Permit Services

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-8000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



APR 15 2011

Mike Tollstrup, Chief
Project Assessment Branch
Air Resources Board
P O Box 2815
Sacramento, CA 95812-2815

**Re: Notice of Significant Title V Permit Modification
District Facility # C-629
Project # C-1110535**

Dear Mr. Tollstrup:

Enclosed for you to review is the District's analysis of an application for significant Title V permit modification for the facility identified above. O'Neill Beverage Co. is proposing a Title V significant permit modification to incorporate the recently issued Authorities to Construct C-629-333-0, 1, & 2 through '-378-0, -1, & -2, '-381-0, -1, & -2 and '-382-0, -1, & -2 into the Title V operating permit (see enclosures). O'Neill Beverages proposes to incorporate these new units into the Title V permit.

Enclosed are the current Title V permit, recently issued Authorities to Construct C-629-333-0, 1, & 2 through '-378-0, -1, & -2, '-381-0, -1, & -2 and '-382-0, -1, & -2, proposed modified Title V permit, engineering evaluation, and application. The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period that begins on the date you receive this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

Enclosures

c: Dennis Roberts, Permit Services

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

Fresno Bee

**NOTICE OF PRELIMINARY DECISION
FOR THE PROPOSED MODIFICATION OF
FEDERALLY MANDATED OPERATING PERMIT**

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District solicits public comment on the proposed modification of the Federally Mandated Operating Permit to O'Neill Beverage Co. for its Winery located at 8418 S. Lac Jac Avenue in Parlier, California. O'Neill Beverages proposes to incorporate new wine tanks into the Title V permit.

The District's analysis of the legal and factual basis for this proposed action, project #C-1110535, is available for public inspection at http://www.valleyair.org/notices/public_notices_idx.htm and the District office at the address below. This will be the public's only opportunity to comment on the specific conditions of the modification. If requested by the public, the District will hold a public hearing regarding issuance of this modification. For additional information, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900. Written comments on the proposed initial permit must be submitted within 30 days of the publication date of this notice to DAVID WARNER, DIRECTOR OF PERMIT SERVICES, SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 1990 E. GETTYSBURG AVE, FRESNO, CALIFORNIA 93726-0244.

Engineering Evaluation

TITLE V APPLICATION REVIEW

Significant Modification
Project #: C-1110535

Engineer: Dennis Roberts
Date: March 17, 2011

Facility Number: C-629
Facility Name: O'Neill Beverages Co, LLC
Mailing Address: 8418 S. Lac Jac Avenue
Parlier, CA 93648-9708

Contact Name: Matt Towers
Phone: (559) 638-3544

Responsible Official: Matt Towers
Title: Chief Operating Officer

I. PROPOSAL

O'Neill Beverages Co. LLC is proposing a Title V significant permit modification to incorporate 144 Authorities to Construct (listed in Attachment A) into the Title V operating permit. The ATCs encompass several proposed modifications to the existing winery tank permits plus the installation of new winery tanks. The details are stated in Section VI of this document.

The purpose of this evaluation is to identify all applicable requirements, determine if the facility will comply with the applicable requirements and to provide the legal and factual basis for the proposed revisions.

II. FACILITY LOCATION

8418 S. Lac Jac Avenue in Parlier, California

III. EQUIPMENT DESCRIPTION

See Attachment B for a listing of all permits and equipment.

IV. SCOPE OF EPA AND PUBLIC REVIEW

This change to a Title V permit is considered to be a significant modification because the applicant did not originally apply for a Certificate of Conformity (COC) with the original New Source Review (NSR) Authorities to Construct (ATCs). As such, this project requires public review.

V. APPLICABLE REQUIREMENTS

District Rule 2520, Federally Mandated Operating Permits (Adopted June 21, 2001)

VI. DESCRIPTION OF PROPOSED MODIFICATIONS

O'Neill Beverages proposes incorporation of various ATC's, previously issued from five different District projects, into the Title V permit. A description of the proposed modifications is described below under the respective originating District project numbers:

District Project C-1092457

- Install sixteen (16) new wine storage tanks (ATC's '-333-0 through '-348-0)

District Project C-1094900

- Install sixteen (34) new wine storage tanks (ATC's '-349-0 through '-378-0, '-381-0 and '-382-0)

District Project C-1100281

- Increase the maximum ethanol content of the wine stored in each of the tanks to 23.9%, by volume and establish a maximum combined annual VOC emission limit for all wine storage tanks (ATC's C-629-333-1 through '-378-1, '-381-1 and '-382-1).
- Increase the maximum allowable daily wine storage throughput (ATC's C-629-339-1 through '-342-1, '-365-1 and '-366-1).

District Project C-1101398

- Designate the wine storage tanks as red fermenters and include them in the facility-wide specific limiting condition for fermentation operations (ATC's '-333-2 through '-378-2, '-381-2 and '-382-2).

C-629-333-3 through '-378-3, '-381-3 and '-382-3:

- Conditions 4-20 of the Authorities to Construct '-333-2 through '-378-2, '-381-2 and '-382-2 appear as conditions 1-14 and 16-18 of the new Permits to Operate.
- Condition 15 was added to the permits to ensure compliance with the record keeping requirements of Rule 4694.
- Condition 1 and 2 from the original ATCs '-333-0 through '-378-0, '-381-0 and '-382-0 were deleted since they have been satisfied by the facility's submittal of an ERC withdrawal application as required by these conditions.
- Condition 1 of ATCs '-333-1 through '-378-1, '-381-1 and '-382-1 and condition 2 of ATCs '-333-2 through '-378-2, '-381-2 and '-382-2 were deleted since ATCs '-0, '-1 and '-2 are being converted concurrently by this project.
- Condition 1 from ATCs '-333-2 through '-378-2, '-381-2 and '-382-2 have been deleted since they were satisfied by the applicant's submittal of the application for this Title V permitting action.

VII. COMPLIANCE

District Rule 2520, Section 6.0 describes the source's ability to make changes including significant permit modification. This modification does not meet the minor permit modification criteria pursuant to Section 3.20 described as follows.

1. Do not violate requirements of any applicable federally enforceable local or federal requirement;
2. Do not relax monitoring, reporting, or recordkeeping requirements in the permit and are not significant changes in existing monitoring permit terms or conditions;
3. Do not require or change a case-by-case determination of an emission limitation or other standard, or a source-specific determination for temporary sources of ambient impacts, or a visibility or increment analysis;
4. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include;
 - a. A federally enforceable emission cap assumed to avoid classification as a modification under any provisions of Title I of the Federal Clean Air Act; and

- b. An alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Federal Clean Air Act; and
5. Are not Title I modifications as defined in District Rule 2520 or modifications as defined in section 111 or 112 of the Federal Clean Air Act; and
6. Do not seek to consolidate overlapping applicable requirements.

In accordance with Rule 2520, the application meets the procedural requirements of Section 11.3 by including;

1. The identification of the source, the name and address of the permit holder, the activities and emissions change involved in the permit action;
2. The name and address of the District, the name and telephone number of District staff to contact for additional information;
3. The availability, upon request, of a statement that sets forth the legal and factual basis for the proposed permit conditions;
4. The location where the public may inspect the complete application, the District analysis, the proposed permit, and all relevant supporting materials;
5. A statement that the public may submit written comments regarding the proposed decision within at least 30 days from the date of publication and a brief description of commenting procedures, and
1. A statement that members of the public may request the APCO or his designee to preside over a public hearing for the purpose of receiving oral public comment, if a hearing has not already been scheduled. The APCO shall provide notice of any public hearing scheduled to address the proposed decision at least 30 days prior to such hearing;

VIII. ATTACHMENTS

- A. List of ATCs for Incorporation into the Title V Permit
- B. List of Permits and Equipment
- C. Emissions Increases

ATTACHMENT A

List of ATCs for Incorporation into the Title V
Permit

**ATCs for Title V Implementation
District Project C-1110535**

C-629- 333 -0,-1,-2	C-629- 375 -0,-1,-2
C-629- 334 -0,-1,-2	C-629- 376 -0,-1,-2
C-629- 335 -0,-1,-2	C-629- 377 -0,-1,-2
C-629- 336 -0,-1,-2	C-629- 378 -0,-1,-2
C-629- 337 -0,-1,-2	C-629- 381 -0,-1,-2
C-629- 338 -0,-1,-2	C-629- 382 -0,-1,-2
C-629- 339 -0,-1,-2	
C-629- 340 -0,-1,-2	
C-629- 341 -0,-1,-2	
C-629- 342 -0,-1,-2	
C-629- 343 -0,-1,-2	
C-629- 344 -0,-1,-2	
C-629- 345 -0,-1,-2	
C-629- 346 -0,-1,-2	
C-629- 347 -0,-1,-2	
C-629- 348 -0,-1,-2	
C-629- 349 -0,-1,-2	
C-629- 350 -0,-1,-2	
C-629- 351 -0,-1,-2	
C-629- 352 -0,-1,-2	
C-629- 353 -0,-1,-2	
C-629- 354 -0,-1,-2	
C-629- 355 -0,-1,-2	
C-629- 356 -0,-1,-2	
C-629- 357 -0,-1,-2	
C-629- 358 -0,-1,-2	
C-629- 359 -0,-1,-2	
C-629- 360 -0,-1,-2	
C-629- 361 -0,-1,-2	
C-629- 362 -0,-1,-2	
C-629- 363 -0,-1,-2	
C-629- 364 -0,-1,-2	
C-629- 365 -0,-1,-2	
C-629- 366 -0,-1,-2	
C-629- 367 -0,-1,-2	
C-629- 368 -0,-1,-2	
C-629- 369 -0,-1,-2	
C-629- 370 -0,-1,-2	
C-629- 371 -0,-1,-2	
C-629- 372 -0,-1,-2	
C-629- 373 -0,-1,-2	
C-629- 374 -0,-1,-2	

ATTACHMENT B

List of Permits and Equipment

Equipment Description

Permit.	Equipment
C-629- 333 -3	6,500 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0290) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING
C-629- 334 -3	6,500 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0291) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING
C-629- 335 -3	6,500 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0292) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING
C-629- 336 -3	6,500 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0293) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING
C-629- 337 -3	6,500 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0294) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING
C-629- 338 -3	6,500 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0295) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING
C-629- 339 -3	196,000 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0622) WITH PRESSURE/VACUUM VALVE AND INSULATION
C-629- 340 -3	196,000 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0623) WITH PRESSURE/VACUUM VALVE AND INSULATION
C-629- 341 -3	196,000 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0624) WITH PRESSURE/VACUUM VALVE AND INSULATION
C-629- 342 -3	196,000 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK #R0625) WITH PRESSURE/VACUUM VALVE AND INSULATION
C-629- 343 -3	86,780 GALLON STEEL RED AND WHITE WINE FERMENTATION/STORAGE STORAGE TANK (TANK#R2035) WITH PRESSURE/VACUUM VALVE AND INSULATION

- C-629- 344 -3 86,780 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK#R2036) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 345 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2037) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 346 -3 86,780 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2038) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 347 -3 86,780 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2039) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 348 -3 86,780 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2040) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 349 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R3030) WITH
PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING
- C-629- 350 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R3031) WITH
PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING
- C-629- 351 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R3032) WITH
PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING
- C-629- 352 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R3033) WITH
PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING
- C-629- 353 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R3034) WITH
PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING
- C-629- 354 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R3035) WITH
PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING
- C-629- 355 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK TANK (TANK #R3036)
WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING

- C-629- 356 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R3037) WITH
PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING
- C-629- 357 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R3038) WITH
PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING
- C-629- 358 -3 13,300 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R3039) WITH
PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE
CONTROLLED BUILDING
- C-629- 359 -3 45,226 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2006) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 360 -3 45,226 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2007) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 361 -3 45,226 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2008) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 362 -3 45,226 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2009) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 363 -3 45,226 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2010) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 364 -3 45,226 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2011) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 365 -3 120,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2021) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 366 -3 120,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2022) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 367 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2041) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 368 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2042) WITH
PRESSURE/VACUUM VALVE AND INSULATION

- C-629- 369 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2043) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 370 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2044) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 371 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2045) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 372 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2046) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 373 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2047) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 374 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2048) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 375 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2049) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 376 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2050) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 377 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2051) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 378 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2052) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 381 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2055) WITH
PRESSURE/VACUUM VALVE AND INSULATION
- C-629- 382 -3 87,000 GALLON STEEL RED AND WHITE WINE
FERMENTATION/STORAGE STORAGE TANK (TANK #R2056) WITH
PRESSURE/VACUUM VALVE AND INSULATION

ATTACHMENT C

Emissions Increases

	SSIPE (lb/yr)				
	NOx	VOC	CO	SOx	PM10
C-629-333-3 through '-378-3, '-381-3, '-382-3	0	8,794	0	0	0
TOTAL	0	8,794	0	0	0

Application

Revised app. received 10/1/10
D. Roberts

San Joaquin Valley Air Pollution Control District

www.valleyair.org

Permit Application For:

ADMINISTRATIVE AMENDMENT MINOR MODIFICATION SIGNIFICANT MODIFICATION

1. PERMIT TO BE ISSUED TO: <u>O'Neill Beverages Co LLC</u>	
2. MAILING ADDRESS: STREET/P.O. BOX: <u>8418 S. Lac Jac Ave</u> CITY: <u>Parlier</u> STATE: <u>CA</u> ZIP CODE: <u>93648-9708</u>	
3. LOCATION WHERE THE EQUIPMENT WILL BE OPERATED: STREET: <u>8418 S. Lac Jac Ave</u> CITY: <u>Parlier</u> 1/4 SECTION _____ TOWNSHIP _____ RANGE _____	INSTALLATION DATE:
4. GENERAL NATURE OF BUSINESS: <u>Wine and Beverage Alcohol Production and Storage</u>	
5. DESCRIPTION OF EQUIPMENT OR MODIFICATION FOR WHICH APPLICATION IS MADE (include Permit #'s if known, and use additional sheets if necessary) <u>Bringing into SERVICE 350 tanks for wine fermentation and storage Permits numbers:</u> <u>Twenty one tanks C-629-11 to C-629-31</u> <u>Six tanks C-629-40 to C-629-45</u> <u>Two Hundred twenty nine tanks C-629-52 to C-629-281</u> <u>Ninety two tanks C-629-284 to C-629-378</u> <u>Two tanks C-629-381 to C-629-382</u>	
6. TYPE OR PRINT NAME OF APPLICANT: <u>Matt Towers</u>	TITLE OF APPLICANT: <u>G.M</u>
7. SIGNATURE OF APPLICANT: <u>Tom Vitali (for Matt)</u>	DATE: <u>10/1/2010</u> PHONE: <u>(559) 638-3544</u> FAX: <u>(559) 638-7148</u> EMAIL:

For APCD Use Only:

DATE STAMP	FILING FEE RECEIVED: \$ _____ CHECK#: _____
	DATE PAID: _____
	PROJECT NO: _____ FACILITY ID: _____

San Joaquin Valley Unified Air Pollution Control District

TITLE V MODIFICATION - COMPLIANCE CERTIFICATION FORM

I. TYPE OF PERMIT ACTION (Check appropriate box)


- SIGNIFICANT PERMIT MODIFICATION ADMINISTRATIVE
 MINOR PERMIT MODIFICATION AMENDMENT

COMPANY NAME: <u>O'Neill BEVERAGES CO, LLC</u>	FACILITY ID: <u>C-629</u>
1. Type of Organization: <input type="checkbox"/> Corporation <input type="checkbox"/> Sole Ownership <input type="checkbox"/> Government <input checked="" type="checkbox"/> Partnership <input type="checkbox"/> Utility	
2. Owner's Name: <u>Jeff O'Neill</u>	
3. Agent to the Owner: <u>Matthew Towers</u>	

II. COMPLIANCE CERTIFICATION (Read each statement carefully and initial all circles for confirmation):

- Based on information and belief formed after reasonable inquiry, the equipment identified in this application will continue to comply with the applicable federal requirement(s).
- Based on information and belief formed after reasonable inquiry, the equipment identified in this application will comply with applicable federal requirement(s) that will become effective during the permit term, on a timely basis.
- Corrected information will be provided to the District when I become aware that incorrect or incomplete information has been submitted.
- Based on information and belief formed after reasonable inquiry, information and statements in the submitted application package, including all accompanying reports, and required certifications are true accurate and complete.

I declare, under penalty of perjury under the laws of the state of California, that the foregoing is correct and true:



 Signature of Responsible Official

9-29-2010

 Date

Matthew S. Towers

 Name of Responsible Official (please print)

Chief Operating Officer

 Title of Responsible Official (please print)

**Recently Issued ATC(s)
Authorities to Construct '-333-0 through '-378-0, '-381-0 and '-382-0
(District Projects C-1092457 and C-1094900)**



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-333-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0290) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3.5 lb, 2nd quarter - 3.5 lb, 3rd quarter - 3.5 lb, and fourth quarter - 3.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-333-0 - Nov 5 2009 11:15AM - ROBERTSD - Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-8061

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 31,000 gallons in any one day. [District Rule 2201]
9. Combined storage throughput of permits C-629-333 through C-629-338 shall not exceed 402,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-333 through '-338 shall be kept. [District Rule 2201]



San Joaquin Valley AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-334-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0291) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3.5 lb, 2nd quarter - 3.5 lb, 3rd quarter - 3.5 lb, and fourth quarter - 3.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-334-0: Nov 5 2009 11:15AM - ROBERTSD - Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-6061

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 31,000 gallons in any one day. [District Rule 2201]
9. Combined storage throughput of permits C-629-333 through C-629-338 shall not exceed 402,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-333 through '338 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-335-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
 6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0292) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3.5 lb, 2nd quarter - 3.5 lb, 3rd quarter - 3.5 lb, and fourth quarter - 3.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Sayed Sadredin, Executive Director / APCO

David Warner

DAVID WARNER, Director of Permit Services

C-629-335-0 : Nov 5 2009 11:15AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 31,000 gallons in any one day. [District Rule 2201]
9. Combined storage throughput of permits C-629-333 through C-629-338 shall not exceed 402,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-333 through C-629-338 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-336-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0293) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3.5 lb, 2nd quarter - 3.5 lb, 3rd quarter - 3.5 lb, and fourth quarter - 3.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-336-0: Nov 5 2009 11:15AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 31,000 gallons in any one day. [District Rule 2201]
9. Combined storage throughput of permits C-629-333 through C-629-338 shall not exceed 402,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-333 through '-338 shall be kept. [District Rule 2201]



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-337-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0294) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3.5 lb, 2nd quarter - 3.5 lb, 3rd quarter - 3.5 lb, and fourth quarter - 3.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-337-0, Nov 5 2009 11:16AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 31,000 gallons in any one day. [District Rule 2201]
9. Combined storage throughput of permits C-629-333 through C-629-338 shall not exceed 402,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-333 through '-338 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-338-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0295) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 3.5 lb, 2nd quarter - 3.5 lb, 3rd quarter - 3.5 lb, and fourth quarter - 3.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-338-0: Nov 5 2009 11:16AM - ROBERTSD - Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 31,000 gallons in any one day. [District Rule 2201]
9. Combined storage throughput of permits C-629-333 through C-629-338 shall not exceed 402,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-333 through '-338 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-339-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
 196,000 GALLON STEEL WINE STORAGE TANK (TANK #R0622) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 40.5 lb, 2nd quarter - 40.5 lb, 3rd quarter - 40.5 lb, and fourth quarter - 40.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Matt Warner

DAVID WARNER, Director of Permit Services
C-629-339-0: Nov 5 2009 11:16AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 196,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-339 through C-629-342 shall not exceed 3,136,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-339 through '342 shall be kept. [District Rule 2201]



San Joaquin Valley AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-340-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
196,000 GALLON STEEL WINE STORAGE TANK (TANK #R0623) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 40.5 lb, 2nd quarter - 40.5 lb, 3rd quarter - 40.5 lb, and fourth quarter - 40.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-340-0: Nov 5 2009 11:16AM - ROBERTSD : Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-6061

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 196,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-339 through C-629-342 shall not exceed 3,136,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-339 through C-629-342 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-341-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
 196,000 GALLON STEEL WINE STORAGE TANK (TANK #R0624) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 40.5 lb, 2nd quarter - 40.5 lb, 3rd quarter - 40.5 lb, and fourth quarter - 40.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Kuant for

DAVID WARNER, Director of Permit Services
C-629-341-0 Nov 5 2009 11:18AM - ROBERTSD Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 196,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-339 through C-629-342 shall not exceed 3,136,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-339 through '342 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-342-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
 196,000 GALLON STEEL WINE STORAGE TANK (TANK #R0625) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 40.5 lb, 2nd quarter - 40.5 lb, 3rd quarter - 40.5 lb, and fourth quarter - 40.5 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Keast for

DAVID WARNER, Director of Permit Services
C-629-342-0 - Nov 5 2009 11:15AM - ROBERTSD - Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 196,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-339 through C-629-342 shall not exceed 3,136,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-339 through '342 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-343-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK#R2035) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 18.0 lb, 2nd quarter - 18.0 lb, 3rd quarter - 18.0 lb, and fourth quarter - 18.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Keast for

DAVID WARNER, Director of Permit Services
C-629-343-0 : Nov 5 2009 11:16AM -- ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-343 through C-629-348 shall not exceed 2,100,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-343 through '348 shall be kept. [District Rule 2201]



San Joaquin Valley AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-344-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

87,000 GALLON STEEL WINE STORAGE TANK (TANK#R2036) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 18.0 lb, 2nd quarter - 18.0 lb, 3rd quarter - 18.0 lb, and fourth quarter - 18.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-344-0 - Nov 5 2009 11:16AM - ROBERTSD - Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-6061

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-343 through C-629-348 shall not exceed 2,100,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-343 through C-348 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-345-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
 87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2037) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 18.0 lb, 2nd quarter - 18.0 lb, 3rd quarter - 18.0 lb, and fourth quarter - 18.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Kiant for

DAVID WARNER, Director of Permit Services
C-629-345-0 : Nov 5 2009 11:10AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-343 through C-629-348 shall not exceed 2,100,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-343 through '-348 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-346-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2038) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 18.0 lb, 2nd quarter - 18.0 lb, 3rd quarter - 18.0 lb, and fourth quarter - 18.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Keast for

DAVID WARNER, Director of Permit Services

C-629-346-0: Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-343 through C-629-348 shall not exceed 2,100,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-343 through '348 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-347-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2039) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 18.0 lb, 2nd quarter - 18.0 lb, 3rd quarter - 18.0 lb, and fourth quarter - 18.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martha Kiant for

DAVID WARNER, Director of Permit Services

C-629-347-0: Nov 5 2009 11:16AM -- ROBERTSO : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-343 through C-629-348 shall not exceed 2,100,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-343 through '348 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-348-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2040) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 18.0 lb, 2nd quarter - 18.0 lb, 3rd quarter - 18.0 lb, and fourth quarter - 18.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number C-1026-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Sayed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-348-0, Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-343 through C-629-348 shall not exceed 2,100,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-343 through '-348 shall be kept. [District Rule 2201]

D-2

Authorities to Construct '-349-0 through '-378-0,
'-381-0 and '-382-0
(District ATC Project C-1094900)



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-349-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3030) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Keast for

DAVID WARNER, Director of Permit Services
C-629-349-0 : Nov 5 2009 11:17AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-349 through C-629-358 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-350-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3031) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Mark Krast Jr

DAVID WARNER, Director of Permit Services

C-629-350-0; Nov 5 2009 11:17AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-349 through C-629-358 shall be kept. [District Rule 2201]



San Joaquin Valley AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-351-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3032) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-351-0 : Nov 5 2009 11:17AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-349 through C-629-358 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-352-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3033) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martha Kiant for

DAVID WARNER, Director of Permit Services
C-629-352-0 Nov 5 2009 11:17AM - ROBERTSD - Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-333 through '-338 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-353-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
 13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3034) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Sayed Sadredin, Executive Director / APCO

David Warner

DAVID WARNER, Director of Permit Services

C-629-353-0 : Nov 5 2009 11:17AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-349 through C-629-358 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-354-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3035) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-354-0 : Nov 5 2009 11:17AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-349 through C-629-358 shall be kept. [District Rule 2201]



San Joaquin Valley AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-355-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3036) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-355-0 - Nov 5 2009 11:17AM - ROBERTSD Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-349 through C-629-358 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-356-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3037) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-356-0 : Nov 5 2009 11:17AM -- ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-349 through C-629-358 shall be kept. [District Rule 2201]



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-357-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3038) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-357-0; Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-6061

Printed on recycled paper

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-349 through C-629-358 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-358-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
 13,300 GALLON STEEL WINE STORAGE TANK (TANK #R3039) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 6.8 lb, 2nd quarter - 6.8 lb, 3rd quarter - 6.8 lb, and fourth quarter - 6.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Kent for

DAVID WARNER, Director of Permit Services

C-629-358-0 : Nov 5 2009 11:16AM - ROBERT6D : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 66,500 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-349 through C-629-358 shall not exceed 1,325,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-349 through C-629-358 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-359-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
45,500 GALLON STEEL WINE STORAGE TANK (TANK #R2006) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 19.8 lb, 2nd quarter - 19.8 lb, 3rd quarter - 19.8 lb, and fourth quarter - 19.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-359-0 Nov 5 2009 11:18AM - ROBERTSD Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 135,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-359 through C-629-366 shall not exceed 3,075,600 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-359 through '-366 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-360-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
 45,500 GALLON STEEL WINE STORAGE TANK (TANK #R2007) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 19.8 lb, 2nd quarter - 19.8 lb, 3rd quarter - 19.8 lb, and fourth quarter - 19.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Krest for

DAVID WARNER, Director of Permit Services
C-629-360-0 Nov 5 2009 11:18AM - ROBERTSD Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 135,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-359 through C-629-366 shall not exceed 3,075,600 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-359 through '-366 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-361-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
45,500 GALLON STEEL WINE STORAGE TANK (TANK #R2008) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 19.8 lb, 2nd quarter - 19.8 lb, 3rd quarter - 19.8 lb, and fourth quarter - 19.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-361-0: Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 135,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-359 through C-629-366 shall not exceed 3,075,600 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-359 through '366 shall be kept. [District Rule 2201]



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-362-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
45,500 GALLON STEEL WINE STORAGE TANK (TANK #R2009) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 19.8 lb, 2nd quarter - 19.8 lb, 3rd quarter - 19.8 lb, and fourth quarter - 19.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-362-0 : Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 135,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-359 through C-629-366 shall not exceed 3,075,600 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-359 through '366 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-363-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
45,500 GALLON STEEL WINE STORAGE TANK (TANK #R2010) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 19.8 lb, 2nd quarter - 19.8 lb, 3rd quarter - 19.8 lb, and fourth quarter - 19.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-363-0 - Nov 5 2009 11:18AM - ROBERTSD - Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 135,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-359 through C-629-366 shall not exceed 3,075,600 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-359 through '-366 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-364-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
45,500 GALLON STEEL WINE STORAGE TANK (TANK #R2011) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 19.8 lb, 2nd quarter - 19.8 lb, 3rd quarter - 19.8 lb, and fourth quarter - 19.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-364-0; Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 135,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-359 through C-629-366 shall not exceed 3,075,600 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-359 through '-366 shall be kept. [District Rule 2201]



San Joaquin Valley AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-365-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
120,000 GALLON STEEL WINE STORAGE TANK (TANK #R2021) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 19.8 lb, 2nd quarter - 19.8 lb, 3rd quarter - 19.8 lb, and fourth quarter - 19.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-365-0 : Nov 5 2009 11:18AM -- ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 240,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-359 through C-629-366 shall not exceed 3,075,600 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-359 through '366 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-366-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
45,500 GALLON STEEL WINE STORAGE TANK (TANK #R2022) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 19.8 lb, 2nd quarter - 19.8 lb, 3rd quarter - 19.8 lb, and fourth quarter - 19.8 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martha Keast for

DAVID WARNER, Director of Permit Services
C-629-366-0 : Nov 5 2009 11:18AM -- ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 240,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-359 through C-629-366 shall not exceed 3,075,600 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-359 through '-366 shall be kept. [District Rule 2201]



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-367-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2041) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-367-0: Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-8061

Printed on recycled paper

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-368-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2042) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-368-0 : Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-369-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2043) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-369-0 : Nov 5 2009 11:16AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



San Joaquin Valley AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-370-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2044) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Sayed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-370-0 : Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

Central Regional Office • 1990 E. Gettysburg Ave. • Fresno, CA 93726 • (559) 230-5900 • Fax (559) 230-6061

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-371-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2045) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Klant for

DAVID WARNER, Director of Permit Services
C-629-371-0; Nov 5 2009 11:18AM - ROBERTSD - Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-372-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2046) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martin Keast for

DAVID WARNER, Director of Permit Services

C-629-372-0: Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-373-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2047) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-373-0: Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-374-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2048) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-374-0 : Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-375-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2049) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-375-0: Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-376-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2050) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-376-0 : Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-377-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2051) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services
C-629-377-0 : Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-378-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2052) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-378-0: Nov 5 2009 11:19AM - ROBERTSD - Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-379-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2053) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-379-0: Nov 5 2009 11:19AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-380-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2054) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Martha Keast for

DAVID WARNER, Director of Permit Services
C-629-380-0 : Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-381-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2055) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

David Warner

DAVID WARNER, Director of Permit Services

C-629-381-0: Nov 5 2009 11:19AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-382-0

ISSUANCE DATE: 11/05/2009

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2056) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. Prior to operating equipment under this Authority to Construct, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 27.0 lb, 2nd quarter - 27.0 lb, 3rd quarter - 27.0 lb, and fourth quarter - 27.0 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
2. ERC Certificate Number S-3259-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of this Authority to Construct. [District Rule 2201]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
5. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DAVID WARNER, Director of Permit Services

C-629-382-0: Nov 5 2009 11:18AM - ROBERTSD : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
7. The ethanol content of wine stored in this tank shall not exceed 14.5 percent by volume. [District Rule 2201]
8. Tank throughput shall not exceed 261,000 gallons in any one day. [District Rule 2201]
9. The combined storage throughput of permits C-629-367 through C-629-382 shall not exceed 8,352,000 gallons per year. [District Rule 2201]
10. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
11. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]
13. Records of the combined annual storage throughput for permit units C-629-367 through C-629-382 shall be kept. [District Rule 2201]

**Recently Issued ATC(s)
Authorities to Construct '-333-1 through '-378-1, '-381-1 and '-382-1
(District Project C-1100281)**



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-333-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0290) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING; INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-333-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
7. The maximum wine storage throughput in this tank shall not exceed 31,000 gallons per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Sayed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services
C-629-333-1: 03/30/2010 8:04AM - BROWND: Joint Inspection NOT Required

8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-334-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0291) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING: INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-334-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
7. The maximum wine storage throughput in this tank shall not exceed 31,000 gallons per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services
C-629-334-1: Rev 30 2010 6 04AM - BROWNED : Joint Inspection NOT Required

8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



San Joaquin Valley AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-335-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0292) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING: INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-335-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
7. The maximum wine storage throughput in this tank shall not exceed 31,000 gallons per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services

C-629-335-1: Iss. 03/30/2010 & 04/01/10 - BROWND : Joint Inspection NOT Required

8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-336-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0293) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING; INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-336-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
7. The maximum wine storage throughput in this tank shall not exceed 31,000 gallons per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services
C-629-336-1 : MAR 30 2010 8:04AM - BROWN : Joint Inspection NOT Required

8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-337-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0294) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING: INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-337-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
7. The maximum wine storage throughput in this tank shall not exceed 31,000 gallons per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services
C-629-337-1 : MAR 30 2010 9:04AM - BROWNED : Joint Inspection NOT Required

8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-338-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 6,500 GALLON STEEL WINE STORAGE TANK (TANK #R0295) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING: INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-338-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
7. The maximum wine storage throughput in this tank shall not exceed 31,000 gallons per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Sayed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services
C-629-338-1: 03/30/2010 8:00AM - BROWND - Joint Inspection NOT Required

8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-339-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 196,000 GALLON STEEL WINE STORAGE TANK (TANK #R0622) WITH PRESSURE/VACUUM VALVE AND INSULATION: INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; INCREASE DAILY WINE STORAGE THROUGHPUT LIMIT TO 392,000 GALLONS; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-339-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services
C-629-339-1, MAR 20 2010 8 04AM - BROWN : Joint Inspection NOT Required

7. The maximum wine storage throughput in this tank shall not exceed 392,000 gallons per day. [District Rule 2201]
8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-340-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 196,000 GALLON STEEL WINE STORAGE TANK (TANK #R0623) WITH PRESSURE/VACUUM VALVE AND INSULATION: INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; INCREASE DAILY WINE STORAGE THROUGHPUT LIMIT TO 392,000 GALLONS; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-340-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services

C-629-340-1: Mar 30 2010 6:04AM - BROWND : Joint Inspection NOT Required

7. The maximum wine storage throughput in this tank shall not exceed 392,000 gallons per day. [District Rule 2201]
8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-341-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 196,000 GALLON STEEL WINE STORAGE TANK (TANK #R0624) WITH PRESSURE/VACUUM VALVE AND INSULATION; INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; INCREASE DAILY WINE STORAGE THROUGHPUT LIMIT TO 392,000 GALLONS; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-341-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services

C-629-341-1: Mar 30 2010 8:04AM - BROWNED - Joint Inspection NOT Required

7. The maximum wine storage throughput in this tank shall not exceed 392,000 gallons per day. [District Rule 2201]
8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-342-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 196,000 GALLON STEEL WINE STORAGE TANK (TANK #R0625) WITH PRESSURE/VACUUM VALVE AND INSULATION: INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; INCREASE DAILY WINE STORAGE THROUGHPUT LIMIT TO 392,000 GALLONS; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-342-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Sayed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services
C-629-342-1: Mar 30 2010 8 04AM - BROWNED - Joint Inspection NOT Required

7. The maximum wine storage throughput in this tank shall not exceed 392,000 gallons per day. [District Rule 2201]
8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-343-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 87,000 GALLON STEEL WINE STORAGE TANK (TANK#R2035) WITH PRESSURE/VACUUM VALVE AND INSULATION: CORRECT TANK SIZE TO 86,780 GALLONS; INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382

CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-343-0. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
7. The maximum wine storage throughput in this tank shall not exceed 261,000 gallons per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services
C-629-343-1 Mar 30 2010 8:04AM - BROWND - Joint Inspection NOT Required

8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



San Joaquin Valley AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-344-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 87,000 GALLON STEEL WINE STORAGE TANK (TANK#R2036) WITH PRESSURE/VACUUM VALVE AND INSULATION; CORRECT TANK SIZE TO 86,780 GALLONS; INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382


CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-344-1. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
7. The maximum wine storage throughput in this tank shall not exceed 261,000 gallons per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5960 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


DAVID WARNER, Director of Permit Services

C-629-344-1; Mar 30 2010 9:04AM - BROWNED : Joint Inspection NOT Required

8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

AUTHORITY TO CONSTRUCT

PERMIT NO: C-629-345-1

ISSUANCE DATE: 03/30/2010

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
 PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
 PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2037) WITH PRESSURE/VACUUM VALVE AND INSULATION; CORRECT TANK SIZE TO 86,780 GALLONS; INCREASE MAXIMUM ETHANOL CONTENT OF WINE STORED TO 23.9%; AND ADD A COMBINED ANNUAL VOC EMISSIONS LIMIT OF 8,991 LB/YEAR FROM ALL WINE STORAGE OPERATIONS UNDER PERMITS C-629-289 THROUGH C-629-382


CONDITIONS

1. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-345-1. [District Rule 2201]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
4. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
6. The ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
7. The maximum wine storage throughput in this tank shall not exceed 261,000 gallons per day. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-6950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO


 DAVID WARNER, Director of Permit Services
C-629-345-1: Issued 03/30/10 8:05AM - BROWNED - Joint Inspection NOT Required

8. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
9. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
10. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
11. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
12. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
13. The permittee shall maintain records of the combined annual VOC emissions for permit units C-629-289 through C-629-382 and those records shall be updated at least once per month. [District Rule 2201]
14. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694]