

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-400-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

87,000 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R2069) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-629-400-0 : Jul 16 2010 12:31PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 261,000 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-401-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

87,000 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R2070) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-401-0 : Jul 16 2010 12:31PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 261,000 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 oF, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-402-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3040) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-629-402-0 : Jul 16 2010 12:31PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-403-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3041) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-629-403-0: Jul 18 2010 12:31PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-404-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3042) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-629-404-0; Jul 18 2010 12:31PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-629-405-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3043) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-629-405-0 : Jul 19 2010 12:31PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-406-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3044) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-629-406-0 : Jul 16 2010 12:31PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-407-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3045) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-629-407-0 : Jul 16 2010 12:31PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-408-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3046) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-408-0 : Jul 18 2010 12:32PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-409-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3047) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-629-409-0 : Jul 16 2010 12:32PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-410-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3048) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-629-410-0: Jul 16 2010 12:32PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-411-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3049) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DRAFT

DAVID WARNER, Director of Permit Services

C-629-411-0: Jul 16 2010 12:32PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-412-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3050) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-629-412-0: Jul 18 2010 12:32PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-413-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3051) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-629-413-0: Jul 16 2010 12:32PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-414-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3052) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-414-0 : Jul 16 2010 12:32PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-415-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3053) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-629-415-0 : Jul 16 2010 12:32PM -- FUKUOAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-416-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3054) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-629-416-0 : Jul 16 2010 12:32PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-417-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3055) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services
C-629-417-0 : Jul 18 2010 12:32PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-418-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3056) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-418-0 : Jul 16 2010 12:33PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT

PERMIT NO: C-629-419-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3057) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-419-0 : Jul 16 2010 12:33PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-420-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3058) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-629-420-0 : Jul 16 2010 12:33PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-421-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3059) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-629-421-0 : Jul 16 2010 12:33PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-422-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3060) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-629-422-0; Jul 16 2010 12:33PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-423-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3061) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DRAFT

DAVID WARNER, Director of Permit Services
C-629-423-0 : Jul 16 2010 12:33PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-424-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3062) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST** NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-629-424-0 : Jul 16 2010 12:33PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-425-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC

MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3063) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-629-425-0 : Jul 16 2010 12:33PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-426-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:
13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3064) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-426-0: Jul 16 2010 12:33PM - FUKUDAD : Joint Inspection NOT Required

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-368-2

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

MODIFICATION OF 87,000 GALLON STEEL WINE STORAGE TANK (TANK #R2042) WITH PRESSURE/VACUUM VALVE AND INSULATION: ADD THE ABILITY TO USE TANK FOR WINE FERMENTATION AND INCLUDE IN THE EXISTING FACILITY-WIDE FERMENTATION VOC SLC

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. This Authority to Construct (ATC) shall be implemented prior to, or concurrently with, the modification and startup of the equipment authorized by ATC C-629-368-1. [District Rule 2201]
3. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. Combined annual VOC emissions from all wine storage operations under permit units C-629-289 through C-629-382 shall not exceed 8,991 pounds per year. [District Rule 2201]
5. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]
6. Combined annual VOC emissions from wine storage operations under permit units C-629-289 through C-629-382 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
7. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services

C-629-368-2 : Jul 16 2010 12:27PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-427-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3065) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-427-0 : Jul 16 2010 12:33PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-428-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3066) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-428-0 : Jul 16 2010 12:34PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-429-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3067) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-429-0 : Jul 16 2010 12:34PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-430-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3068) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU **MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT.** This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director APCO

DAVID WARNER, Director of Permit Services
C-629-430-0 : Jul 16 2010 12:34PM -- FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

ISSUANCE DATE: DRAFT
DRAFT

PERMIT NO: C-629-431-0

LEGAL OWNER OR OPERATOR: O'NEILL BEVERAGES CO LLC
MAILING ADDRESS: 8418 S LAC JAC AVE
PARLIER, CA 93648-9708

LOCATION: 8418 S LAC JAC AVE
PARLIER, CA 93648

EQUIPMENT DESCRIPTION:

13,300 GALLON STEEL RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK (TANK #R3069) WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

CONDITIONS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. Prior to operating any piece of equipment authorized by Authority to Construct permits C-625-383-0 through -431-0, permittee shall surrender VOC emission reduction credits for the following quantity of emissions: 1st quarter - 1,250 lb, 2nd quarter - 1,250 lb, 3rd quarter - 1,250 lb, and fourth quarter - 1,250 lb. Offsets shall be provided at the applicable offset ratio specified in Table 4-2 of Rule 2201 (as amended 9/21/06). [District Rule 2201]
4. ERC Certificate Number S-3384-1 (or a certificate split from this certificate) shall be used to supply the required offsets, unless a revised offsetting proposal is received and approved by the District, upon which this Authority to Construct shall be reissued, administratively specifying the new offsetting proposal. Original public noticing requirements, if any, shall be duplicated prior to reissuance of these Authority to Construct permits. [District Rule 2201]
5. Combined annual VOC emissions from all wine storage operations under permit units C-629-383 through C-629-431 shall not exceed 5,000 pounds per year. [District Rule 2201]
6. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: $EF = 1.705259 * P^{1.090407}$; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. [District Rule 2201]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (559) 230-5950 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director, APCO

DAVID WARNER, Director of Permit Services

C-629-431-0: Jul 16 2010 12:34PM - FUKUDAD : Joint Inspection NOT Required

7. Combined annual VOC emissions from wine storage operations under permit units C-629-383 through C-629-431 shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]
8. The VOC emissions rate for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
9. Total annual VOC emissions from all wine fermentation operations at this facility shall not exceed 410,502 lb per year. [District Rule 2201]
10. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production-gal) x (6.2 lb-VOC/1000 gal) + (Total Annual White Wine Production-gal) x (2.5 lb-VOC/1000 gal). [District Rule 2201]
11. Ethanol content of wine stored in this tank shall not exceed 23.9 percent by volume. [District Rule 2201]
12. The maximum wine storage throughput in this tank shall not exceed 66,500 gallons per day. [District Rule 2201]
13. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
14. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]
15. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
16. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 F, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 4694]
17. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
18. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rule 4694]
19. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
20. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694]

DRAFT