

EXHIBIT 25

**Cleveland Trencher
Regulated Waste Removal**

**20100 St. Clair Ave.
Euclid, OH.**

ITEMS TO BE REMOVED

Task #1: Containerized Materials

- A) A number of containers (including 2 or 3 small above ground storage tanks) have been identified for removal. These containers were found to contain the following materials: oil; oily water; grease; non-hazardous solid grease; sodium hydroxide; paint/thinners pumpable; and paint/thinners solid. Some of this material will be considered hazardous waste under RCRA, based on its characteristics and/or composition.
- a. Field observations and subsequent verification will be used to characterize and classify listed containers and complete appropriate TSD facility profiles. Information used for characterization includes generator knowledge, obvious odors, obvious labels, visual inspection of color and texture, pH, MSDS sheets, and previous analysis (if any). Additional analysis (as necessary) to complete a full characterization will be completed prior to the commencement of work.
 - b. Completed profiles will be presented to the owner for review and signature. Signed profiles will be submitted to TSD's for disposal approvals.
 - c. Each container will be evaluated for structural integrity. If any container is not in DOT shippable condition, the container will be repaired (replace lid, ring, bung/s), consolidated, over packed or repackaged.
 - d. All containers will be collected in a staging area in preparation for transportation off-site. Similar materials, especially oils, may be bulked together into the same drum to facilitate shipping. Empty containers from this process will be labeled in preparation for shipment to a drum recycler.
 - e. Each container will be properly labeled/marked as required.
 - f. Appropriate shipping papers, manifest, LDR's will be prepared for each container.
 - g. Containers will be loaded to licensed transportation vehicles and transported to TSD's for final disposal.

h. At the completion of the project, client will have copies of all relevant paperwork related to transportation and disposal.

i. Client will have the option to inspect the site and approve prior to contractor's demobilization.

Task #2: Electrical Transformers

Several pole-mounted electrical transformers have been identified on-site. These transformers have been identified as non- TSCA. These will be sent to a transformer recycler for appropriate handling. The recycler will verify the PCB levels prior to processing the transformers.

Safety Precautions

1) PPE will include hard-hat, work boots, gloves, and safety glasses. If drums must be opened for any reason, personnel will wear air-purifying respirators with combination cartridges. White Tyvek suits will also be employed as necessary, especially if waste must be pumped or poured from one container to another.

2) Any hand tools and non-disposable PPE that may come in direct contact with hazardous waste will be washed, if necessary, with a mild detergent and water then rinsed with clean water. All wash/rinse waters along with any clothes, brushes, and/or paper produces used for cleaning/drying will be collected in appropriate containers for disposal.

3) All used disposable PPE will be collected as discarded into appropriate containers.



5500 Old Brecksville Road • Independence, Ohio 44131
(216) 642-6040 • fax (216) 642-6041

Cleveland Trencher

ASBESTOS ABATEMENT & CLEANUP

EUCLID, OHIO

HEALTH & SAFETY SUBMITTALS

Submitted
June 30, 2011

HEALTH & SAFETY PLAN

Table of contents

Site Specific Work Plan	Section 1
Emergency Plan and Phone List	Section 2
Transportation and Disposal	Section 3
Supervisor Qualifications	Section 4
Worker Qualifications	Section 5
Respiratory Protection Program	Section 6
Asbestos Abatement Program	Section 7
License, Worker's Compensation, Insurance	Section 8
Product Data and Material Safety Data Sheets.	Section 9
Project Notifications	Section 10
Clearance Sampling Plan	Section 11

Section 1

Site Specific Work Plan



5500 Old Brecksville Road • Independence, Ohio 44131
(216) 642-6040 • fax (216) 642-6041

Cleveland Trencher

Asbestos Abatement and Cleanup

Eucclid, OH

Scope of Work (Asbestos) The project involves removal and disposal of asbestos-containing pipe insulation, hanging roof materials, debris piles, and decontamination of interior building structures, and exterior concrete slabs, located throughout the project site.

Worker Training, Personnel Protection & Safety All personnel working on this project will be as certified as an asbestos worker (including equipment operator) and/or an asbestos supervisors by the Ohio Department of Health and will have received the mandatory associated EPA training for each classification. Each worker shall also have 40-hour Hazardous Waste Operations Training (HAZWOPER). Each worker and supervisor is current in the required medical surveillance program. Each individual employee will be fit tested to ensure a proper fit of his or her respirator. Records of training, medical surveillance, and fit testing shall be kept on site and made available for inspection throughout the project.

All Precision Environmental personnel will be issued hard hats, work boots, and safety glasses to be worn at all times during the project. All personnel shall wear Tyvek suits, and, depending on the initial exposure assessments, half-mask respirators equipped with HEPA filters. All employees shall dispose of coveralls in dirty room, and shower and clean respirator prior to exiting the work area.

Ground Fault Circuit Interrupters (GFCI's) will be used according to 29 CFR 1926.404(b)(1)(ii).

In accordance with OSHA 29 CFR 1926.59, Hazard Communication, Precision Environmental Co. shall have on site a list of Hazardous chemicals to be used on site, a corresponding MSDS (Material Safety Data Sheet) for each chemical, and a copy of Precision Environmental's Written Hazard Communication Program.

Permits & Notifications Copies of all permits and notifications shall be forwarded to the owner's representative prior to commencing work.

Air Monitoring Precision shall collect all required OSHA personal air samples on 25% of the work force during asbestos abatement operations. A complete record of all personal air monitoring and results will be furnished to the owner's representative. Written reports of all air monitoring tests shall be posted at the job site or a central location on a regular basis.

****Note perimeter air sampling plan to follow in separate document**

Work Area Preparation & Removal Procedures All work area preparation and removal procedures described herein shall be supervised by a Competent Person. HEPA vacuums shall be utilized for all work procedures to collect small particles/debris resulting from asbestos removal and/or decontamination operations. Prior to commencing all asbestos removal work, Precision Environmental Co. shall post asbestos warning signs and danger tape as required by OSHA's Asbestos Standard for the Construction Industry, 29 CFR 1926.1101.

All asbestos-containing pipe insulation, to be removed per the specification's scope shall be removed using wet methods, and glovebag or wrap and cut methods. Pipe insulation shall be accessed with either aerial boom lifts or scissers lifts using appropriate personal fall protection.

All asbestos-containing debris piles, hanging roof materials, and building decontamination to be removed per the specification's scope shall be removed using wet methods. Debris piles including one inch of soil underneath (where debris is on soil) shall be removed with skid steer loaders. Non-porous surfaces i.e. concrete shall be washed and left on site. Hanging roof material shall be accessed with either aerial boom lifts or scissers lifts using appropriate personal fall protection. All concrete surfaces shall be cleaned, washed, and cleared to no visible remaining gross debris.

***Note - North end office building shall have all windows and doors sealed with polyethylene sheeting from the inside and the entrance boarded up.*

Disposal All asbestos containing waste materials shall be double bagged in 6-mil asbestos bags, or double wrapped in 6-mil poly sheeting, or placed in double lined dumpsters, shall bear asbestos labeling, generator information and shall be transported by and to an EPA approved asbestos landfill. Waste shipment records shall be maintained and copies shall be submitted upon removal of asbestos waste from the project site, and after arrival at the landfill. All DOT regulations shall be strictly adhered to.

Decontamination Zones/Center

The objective of decontamination procedures is to minimize the risk of exposure to hazard substances by limiting the spread of contamination from the work area. Decontamination will be accomplished in accordance with 29 CFR 1910.120 and 29 CFR 1926.1101. The work area will be divided into 3 controlled zones. The zones will be known as the Exclusion Zone (contaminated zone), Contamination Reduction Zone or CRZ (decontamination zone), and the Support Zone (clean zone).

Exclusion (Hot) Zone (Asbestos work areas)

The exclusion zone is the work area where actual abatement operations are taking place. The perimeter of the exclusion zone shall be demarcated. Access restricted to only those personnel who have received certified training and are wearing the proper level of protection. Entry and exit in the exclusion zone must be made through the CRZ.

Contamination Reduction (Warm) Zone (decon trailer north end inside fence)

The purpose of the Contamination Reduction Zone (CRZ) is to limit the spread of contaminated material from the exclusion zone to the support zone. All equipment and PPE will be decontaminated in this area prior to entry into the support zone. This is effectively accomplished by the decontamination shower.

In compliance with 29 CFR 1926.1101 a three-chambered personnel decontamination center shall be constructed at the entrance/exit of the work areas or a decon trailer provided. The personnel decontamination center shall consist of a clean room, shower and equipment room of sufficient size to accommodate the work crew as well as load-out activities.

Support (Cold) Zone (North end outside fence)

The support zone is the clean area outside the exclusion zone and the CRZ. No materials, tools, PPE, or personnel are permitted to enter this area without first passing through the CRZ.


Equipment Decontamination


Skid steer loaders, asbestos dumpsters, and other equipment that cannot be decontaminated through the personnel decontamination center shall be decontaminated prior to exiting or being removed from the work zones. This shall be done by rinsing the equipment over bermed polyethylene sheeting. All rinse water shall be collected and filtered prior to disposal.

Utilities

Upon mobilization to the project site, Precision shall establish necessary utilities needed for performance of the work. Water shall be obtained from adjacent hydrant(s) or utilization of water tanks. All necessary electrical service shall be obtained utilizing portable generators.

Cleveland Trencher
20100 St. Clair
Euclid, Ohio





Activity ID	Activity Description	Orig Dur	Days
1000	Mobilization	2	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28
1010	Establish Support Zone / Demarcation	2	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28
1020	Secure / Critical Office Building	2	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28
1030	Remove Pipe Insulation	2	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28
1040	Remove Debris Piles	11	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28
1050	Final Clean Structures / Slabs	7	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28
1060	Final Clearance Sampling	3	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28
1070	De-Mobilization	2	1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28

Printed 13JUL11 09:15

© Primavera Systems, Inc.

FCRF

Sheet 1 of 3

Prepared By:

Precision Environmental Co.



Section 2

Emergency Plan and Phone List

Precision Environmental Company

Emergency Response Procedures

Cleveland Trencher

Euclid, Ohio

Purpose

Dealing effectively with any type of emergency situation requires prompt notification, coordinated mobilization, quick implementation of specific duties and assignments, and the optimum use of job site and community emergency response resources. During the course of asbestos abatement and cleanup at Cleveland Trencher, there may also arise situations or emergencies, which may require modification or breach of the work area.

I. Fire

- A. The Euclid Fire Department must be notified immediately in the event of a fire by dialing 911. This policy holds true regardless of the size of the fire or the ease with which it may be extinguished. A second call to the fire department telling them the fire has been extinguished is far better than notification after the fire is out of control.
- B. Emergency exits shall be established and clearly marked with duct tape, arrows or other effective designations to permit easy location from anywhere within work area. They shall be secured to prevent access from uncontaminated areas and still permit emergency exiting. These exits shall be properly sealed with polyethylene sheeting, which can be cut to permit egress if needed. These exits may be the worker decontamination enclosure, the waste pass-out airlock and/or other alternative exits satisfactory to fire official.
- C. Steps to take in a fire emergency:
 1. Any person discovering a fire should quickly and carefully remove anyone who is injured or in immediate danger. This person must be careful not to risk injury to himself as it is most important that he remain conscious and able to report the fire.
 2. The nearest telephone or radio should be used to report the fire. The individual reporting the fire shall provide the following information: that there is a fire; what is on fire; the specific location of the fire; and the name, telephone number and location of the person reporting the fire.

3. Extinguishment of the fire should be attempted only if there is portable fire fighting equipment available and the fire is in its incipient, that is, initial or beginning state and can be safely controlled or extinguished with this equipment. If the size of the fire presents an immediate danger to life or health, evacuation, not fire fighting, should be the primary objective.
4. Fire extinguishers will be located at designated areas on each floor of the building. In the event of a fire, emergency exits shall be used or breached.
5. Evacuation: When evacuation is deemed necessary, there should be no hesitation in requiring personnel to immediately vacate the area. *Emergency exits and other means of egress from each area shall be noted prior to the start of the job and communicated to all employees.* An assembly area shall be designated and all personnel required to report there immediately for a roll call to assure that all are present and accounted for. Once out of the building, no one will be allowed to re-enter until the emergency is declared over.

II. Employee Injury

- A. Should an incident occur which results in an injury to an employee, an immediate assessment of the severity should be made.
- B. No attempts at rescue or first aid should be made until the scene has been surveyed and it is determined that it is safe to enter the area. Particular attention should be given to the possibility of electrical shock, asphyxiating or oxygen deficient atmospheres, overhead hazards, and fall hazards.
- C. Designated first aid personnel shall be summoned to the scene. If it is necessary to call an ambulance the person placing the call should be prepared to provide such information as: the location of the accident, type of accident (fall from elevation, heart attack, etc.), the condition of the injured, and where to enter site.
- D. An individual shall be directed to meet the ambulance at a previously designated location.
- E. The area shall be kept clear of all-unnecessary personnel and equipment that could hinder the emergency response effort.
- F. The site entrance shall be secured to prevent any unauthorized entrance by those not directly involved in the emergency response effort.

- G. In case of an injury requiring emergency treatment, the treatment shall not be delayed for decontamination purposes. Breach of containment at emergency exits shall be done if necessary. Emergency personnel will be advised of containment conditions.

III. Emergency Phone Numbers

Emergency phone numbers shall be posted at a pre-determined location. Numbers will also be posted at the Precision Field Office.

IV. Power Failure

In the event of a power failure, all work shall be halted, workers shall exit containments and containments shall be sealed until such time that power can be restored.

Cleveland Trencher

Euclid, Ohio

Emergency Phone Numbers

<u>Emergency Assistance</u>	<u>Phone #</u>
FIRE & EMS:	911
POLICE	911
HOSPITALS: Concentra Medical Center 5500 S. Marginal Road Cleveland, Ohio 44103	(216) 426-9020

(When calling Emergency Services, advise dispatcher if employee was working in containment)

Precision Environmental Contacts - 5500 Old Brecksville Road, Independence, Ohio (216) 642-6040

	<u>Mobile</u>	<u>Other</u>
Kenny Yates — Supervisor	(216) 214-2562	
Emory Wolf - Superintendent	(216) 214-2474	
Marc Garland — Safety Director	(216) 214-5173	(440) 209-0194
John Savage - Vice President	(216) 214-0401	

Additional Emergency Phone Numbers:

Chemtrec	(800) 424-9300
TSCA Hotline	(800) 424-9065
	(202) 544-1404
ATSDR			Day	.	.	(404) 329-2888
			Night	.	.	(404) 566-7777
ATF (Explosives)	(800) 424-9555
National Response Center	(800) 424-8802
Pesticide Information Service	(800) 845-7633
EPA Emergency Response Team	(201) 321-6660
RCRA Hotline	(800) 424-9346
CMA Chemical Referral Center	(800) 262-8200
National Poison Control	(800) 942-5969
U. S. DOT			Days Only	.	.	(202) 366-0656

Section 3

Transportation and Disposal

2011

OhioEPA

2011

Construction and Demolition Debris Facility License

License Expires December 31, 2011

Facility: Minerva Enterprises (CID:54288) 9000 Minerva Rd Waynesburg, OH 44688

This license has been issued in accordance with the requirements of state law, is subject to revocation or suspension for cause, and is not transferable without the consent of the Board of Health or the Director of the Ohio Environmental Protection Agency.
--

Licensing Authority: Stark Co - CDDL

Conditions of Licensure

The Licensee hereunder, its agents, employees, and all others in active concert with said licensee, including the facility owner and operator, shall be subject to and shall comply with the following conditions of this license:

1. All applicable requirements of Ohio Revised Code Chapters 3714, 3734, 6111, and 3704.
2. All applicable requirements of Ohio Administrative Code Chapters 3745-37 and 3745-400.
3. Plans, other authorizing documents and administrative and judicial orders applicable to this facility and as approved by the Ohio Environmental Protection Agency and/or the licensing authority.
4. By applying for and accepting this license, the licensee specifically consents in advance and agrees to allow the Director, the Health District, or an authorized representative, to enter upon the licensee's premises at any reasonable time during the construction and/or operation of the facility for the purpose of inspecting, conducting tests, collecting samples, or examining records or reports pertaining to construction, modification, installation, or operation of the facility. The licensee hereby acknowledges and agrees that any and all rights of access granted herein shall not be deemed to be unreasonable or unlawful under Ohio Revised Code Sec. 3714.08.

The licensee, its agents, employees, and all others in active concert with said licensee shall maintain and operate the construction and demolition debris facility to which the license pertains in a sanitary manner so as not to create a nuisance, create a fire hazard, cause or contribute to water pollution, or create a health hazard. This license shall not be construed to constitute a defense to any civil or criminal action brought by the State of Ohio or any duly authorized representative thereof to enforce the provisions of Chapters 3714, 3734, 3767, 6111, or 3704, of the Ohio Revised Code, or the regulations issued thereunder.

Issuance of this license does not relieve the licensee of the duty to comply with all applicable federal, state, and local laws, regulations and ordinances.

If Checked, Additional Conditions Apply to This License (See Back, or Attachment)



Health Commissioner

December 29, 2010

Date Issued



CERTIFICATE OF LIABILITY INSURANCE

OP ID: P
 DATE (MM/DD/YYYY)
 01/11/11

THIS CERTIFICATE IS ISSUED AS A MATTER OF INFORMATION ONLY AND CONFERS NO RIGHTS UPON THE CERTIFICATE HOLDER. THIS CERTIFICATE DOES NOT AFFIRMATIVELY OR NEGATIVELY AMEND, EXTEND OR ALTER THE COVERAGE AFFORDED BY THE POLICIES BELOW. THIS CERTIFICATE OF INSURANCE DOES NOT CONSTITUTE A CONTRACT BETWEEN THE ISSUING INSURER(S), AUTHORIZED REPRESENTATIVE OR PRODUCER, AND THE CERTIFICATE HOLDER.

IMPORTANT: If the certificate holder is an **ADDITIONAL INSURED**, the policy(ies) must be endorsed. If **SUBROGATION IS WAIVED**, subject to the terms and conditions of the policy, certain policies may require an endorsement. A statement on this certificate does not confer rights to the certificate holder in lieu of such endorsement(s).

PRODUCER The Fedeli Group P.O. Box 318003 5005 Rockside Road Independence, OH 44131-8003 Rob Snyder, CPGU	216-328-8080 216-328-8081	CONTACT NAME: Pat Gowan PHONE (A/C No. Ext): 216-643-2749 E-MAIL ADDRESS: pgowan@thefedeligroup.com PRODUCER CUSTOMER ID#: MINER-3	FAX (A/C No.): 216-328-8081
	INSURER(S) AFFORDING COVERAGE		NAIC#
INSURED Minerva Enterprises, LLC 9090 Minerva Road Waynesburg, OH 44688	INSURER A: Zurich American Insurance Co.		16535
	INSURER B: Steadfast Insurance Company		26387
	INSURER C:		
	INSURER D:		
	INSURER E:		

COVERAGES **CERTIFICATE NUMBER:** **REVISION NUMBER:**

THIS IS TO CERTIFY THAT THE POLICIES OF INSURANCE LISTED BELOW HAVE BEEN ISSUED TO THE INSURED NAMED ABOVE FOR THE POLICY PERIOD INDICATED. NOTWITHSTANDING ANY REQUIREMENT, TERM OR CONDITION OF ANY CONTRACT OR OTHER DOCUMENT WITH RESPECT TO WHICH THIS CERTIFICATE MAY BE ISSUED OR MAY PERTAIN, THE INSURANCE AFFORDED BY THE POLICIES DESCRIBED HEREIN IS SUBJECT TO ALL THE TERMS, EXCLUSIONS AND CONDITIONS OF SUCH POLICIES. LIMITS SHOWN MAY HAVE BEEN REDUCED BY PAID CLAIMS.


INSR LTR	TYPE OF INSURANCE	ADDL SUBR INSR W/O	POLICY NUMBER	POLICY EFF. (MM/DD/YYYY)	POLICY EXP. (MM/DD/YYYY)	LIMITS
A	GENERAL LIABILITY <input checked="" type="checkbox"/> COMMERCIAL GENERAL LIABILITY CLAIMS-MADE <input checked="" type="checkbox"/> OCCUR includes: <input checked="" type="checkbox"/> X,C,U GENL. AGGREGATE LIMIT APPLIES PER: <input type="checkbox"/> POLICY <input checked="" type="checkbox"/> PRO-JECT <input type="checkbox"/> LOG		GLO903222004	01/10/11	01/10/12	EACH OCCURRENCE \$ 1,000,000 DAMAGE TO RENTED PREMISES (Ea occurrence) \$ 50,000 MED EXP (any one person) \$ 5,000 PERSONAL & ADV INJURY \$ 1,000,000 GENERAL AGGREGATE \$ 2,000,000 PRODUCTS - COMP/OP AGG \$ 1,000,000
	AUTOMOBILE LIABILITY <input checked="" type="checkbox"/> ANY AUTO <input type="checkbox"/> ALL OWNED AUTOS <input type="checkbox"/> SCHEDULED AUTOS <input checked="" type="checkbox"/> HIRED AUTOS <input checked="" type="checkbox"/> NON-OWNED AUTOS		BAP903222104	01/10/11	01/10/12	COMBINED SINGLE LIMIT (Ea accident) \$ 1,000,000 BODILY INJURY (Per person) \$ BODILY INJURY (Per accident) \$ PROPERTY DAMAGE (Per accident) \$
A	<input checked="" type="checkbox"/> UMBRELLA LIAB <input checked="" type="checkbox"/> OCCUR <input type="checkbox"/> EXCESS LIAB CLAIMS-MADE DEDUCTIBLE <input checked="" type="checkbox"/> RETENTION \$ 10,000		SEO903222204	01/10/11	01/10/12	EACH OCCURRENCE \$ 5,000,000 AGGREGATE \$ 5,000,000
A	WORKERS COMPENSATION AND EMPLOYERS LIABILITY ANY PROPRIETOR/PARTNER/EXECUTIVE OFFICER/MEMBER EXCLUDED? (Mandatory in NH) If yes, describe under DESCRIPTION OF OPERATIONS below	Y/N <input type="checkbox"/> N/A	GLO903222004 OHIO STOP-GAP LIABILITY	01/10/11	01/10/12	<input checked="" type="checkbox"/> WC STATUTORY LIMITS <input type="checkbox"/> OTHER E.L. EACH ACCIDENT \$ 1,000,000 E.L. DISEASE - EA EMPLOYEE \$ 1,000,000 E.L. DISEASE - POLICY LIMIT \$ 1,000,000
B	Legal Pollution Liability		PLC903322704 INCL ASBESTOS/LEAD OPS	01/10/11	01/10/12	Limit: \$ 5,000,000 Deductible: 25,000

DESCRIPTION OF OPERATIONS / LOCATIONS / VEHICLES (Attach ACORD 101, Additional Remarks Schedule, if more space is required)

CERTIFICATE HOLDER: Precision Environmental Co Attn: Jill Keppler 5500 Old Brecksville Road Independence, OH 44131	PREC-12	CANCELLATION SHOULD ANY OF THE ABOVE DESCRIBED POLICIES BE CANCELLED BEFORE THE EXPIRATION DATE THEREOF, NOTICE WILL BE DELIVERED IN ACCORDANCE WITH THE POLICY PROVISIONS. AUTHORIZED REPRESENTATIVE <i>Pat Gowan</i>
---	----------------	--

© 1988-2009 ACORD CORPORATION. All rights reserved.

Health Commissioner:
William J. Frantz, M.P.H.
Medical Director:
Grant A. Mason, Jr., M.D.
President Board of Health:
James Recchio, Jr.



**STARK COUNTY
HEALTH DEPARTMENT**

Board Members:
Leo Meris, M.D.
Cary Feller
Philly Francis
Karen Galtland
Candy Holmes
Daphne Feltman
Terence Seeburger

RESOLUTION #9-2010

A RESOLUTION TO ADD REQUIREMENTS OR AGENDA TO THE CONSTRUCTION AND DEMOLITION DEBRIS FACILITY LICENSES OF NAMED FACILITIES FOR THE 2011 LICENSING YEAR.

WHEREAS, 3745-37-03(D) of the Ohio Administrative Code provides that, *"The licensing authority of a construction and demolition debris facility may impose such special terms and conditions as are appropriate or necessary to ensure that the facility will comply with Chapter 3714. of the Revised Code and Chapter 3745-400 of the Administrative Code, and to protect public health and safety and the environment."*

WHEREAS, 3714.06 of the Ohio Revised Code provides that, *"Any such license may be issued with such terms and conditions as the board or the director, as appropriate, finds necessary to ensure that the facility will comply with this chapter and the rules adopted under it and to protect the public health and safety and the environment."*

WHEREAS, facility license reviews that were conducted by the Environmental Division of the Stark County Health Department during November, 2010 indicated that the following conditions and terms are necessary to insure compliance and/or to protect public health and safety and the environment for each facility as specified.

BE IT THEREFORE RESOLVED THAT, the Stark County Board of Health attaches these terms and conditions to the Construction and Demolition Debris Facility Licenses as:

Minerva Enterprises LLC

1. Surface Water Analysis

Analyze all sedimentation ponds for those constituents listed below every 6 months (2 times a year) and submit the results to the Stark County Health Department.

pH	Specific Conductance	Turbidity
Temperature	Total Dissolved Solids (TDS)	Nitrate-Nitrite
Phosphorous, Total	Biological Oxygen Demand	Nitrogen-as Ammonia
Chlorides	Chemical Oxygen Demand	Sulfates
Total Organic Carbon	Depth/Pond Level	Flow Rate

Metals (Arsenic, Barium, Cadmium, Calcium, Chromium, Copper, Iron, Lead, Magnesium, Manganese, Mercury, Nickel, Potassium, Selenium, Silver, Sodium, Zinc)

3951 Convenience Circle, N.W. • Canton, Ohio 44718-2660 • (330) 493-9904 • Fax (330) 493-9920
www.starkhealth.org

This agency is an equal provider of services and an equal opportunity employer - Civil Rights Act of 1964

2. Topographical Map

By September 30, 2011, Minerva Enterprises LLC., shall submit a current topographical drawing showing the approved limits of waste placement with a contour interval no greater than two feet.

Stark C&D Landfill

1. Surface Water Analysis

Analyze all sedimentation ponds for those constituents listed below every 6 months (2 times a year) and submit the results to the Stark County Health Department.

pH	Specific Conductance	Turbidity
Temperature	Total Dissolved Solids (TDS)	Nitrate-Nitrite
Phosphorous, Total	Biological Oxygen Demand	Nitrogen as Ammonia
Chlorides	Chemical Oxygen Demand	Sulfates
Total Organic Carbon	Depth/Pond Level	Flow Rate

Metals (Arsenic, Barium, Cadmium, Calcium, Chromium, Copper, Iron, Lead, Magnesium, Manganese, Mercury, Nickel, Potassium, Selenium, Silver, Sodium, Zinc)

2. Topographical Map

By September 30, 2011, Stark C&D Landfill, shall submit a current topographical drawing showing the approved limits of waste placement with a contour interval no greater than two feet.

BE IT FURTHER RESOLVED, that the Board of Health, of the Stark County Combined General Health District, adopts this measure to be effective on and after Wednesday, December 8, 2010.

ADOPTED: December 8, 2010
By a majority of the members
of the Board of Health of the
Stark County Combined General
Health District

**STARK COUNTY COMBINED
BOARD OF HEALTH**




PRESIDENT



SECRETARY

Health Commissioner:
William J. Franks, M.P.H.
Medical Director:
Maureen Ahmann, D.O.
President-Board of Health:
James Recchio, Jr.



STARK COUNTY HEALTH DEPARTMENT

Board Members:
P.S. Murthy, M.D.
Cary Feller
Philip Francis
Karen Hiltbrand
Connie Holmes
Daphne Fetteamat
Terrence Seeburger

December 29, 2010

Steve Chandler
Minerva Enterprises, LLC
P.O. Box 709
Waynesburg, OH 44688

Dear Mr. Chandler:

On September 30, 2010, this office received an application for a 2011 Construction and Demolition Debris Facility License. Upon review, the application is complete. Therefore, your 2011 Construction and Demolition Debris Facility License is granted. This license is effective for the current approved active licensed disposal area only. The license is subject to special terms and conditions as stated in the enclosed copy of Stark County Board of Health Resolution #9-2010.

A motion to attach these special terms and conditions was passed by a majority of the members of the Board of Health of the Stark County Combined General Health District, and are effective on and after December 8, 2010. These special terms and conditions are hereby attached as provided by 3745-37-03(D) of the Ohio Administrative Code and 3714.06 of the Ohio Revised Code.

This action is final and may be appealed to the Environmental Board of Review pursuant to sections 3714.10 of the Ohio Revised Code. Issuance of this license does not relieve the licensee of the duty to comply with all applicable federal, state, and local laws, regulations, and ordinances.

Feel free to contact Kirk Norris at (330) 493-9904, ext. 214 if you have any questions.

Sincerely,

William Franks, MPH
Health Commissioner

W/ enclosure

3951 Convenience Circle, N.W. ● Canton, Ohio 44718-2660 ● (330) 493-9904 ● Fax (330) 493-9920
www.starkhealth.org

This agency is an equal provider of services and an equal opportunity employer - Civil Rights Act of 1964

The following Contains Minerva Enterprises, LLC's (Minerva) Asbestos Disposal Permit as part of Minerva's Air Permits Group.

For Asbestos Disposal Permit Verification Purposes Only, the Primary 3 Pages of The Asbestos Permit are attached below. [Pages 17,18 & 19 of the 25 page permit]

Should you desire Minerva Enterprises, LLC's entire Air Permits Including Asbestos Please email me at: stevechandler40@aol.com.

Minerva's Asbestos Permit is referred to as F001-Asbestos Disposal



**State of Ohio Environmental Protection Agency
Division of Air Pollution Control**

FINAL

**Air Pollution Permit-to-Install and Operate
for
Minerva Enterprises, LLC**

Facility ID: 1576001700
Permit Number: P0104984
Permit Type: OAC Chapter 3745-31 Modification
Issued: 1/5/2010
Effective: 1/5/2010
Expiration: 1/5/2020

Taken From Page 19 of 25 Below Outlines Minerva's:

Asbestos Material Acceptance Permit Description

- f. The facility can accept for disposal any regulated asbestos-containing material as defined in the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Asbestos, 40 CFR Part 61, Subpart M, Section 141 and OAC rule 3745-20, or any subsequent revisions to either rule. Regulated asbestos-containing material is defined to include:
- i. friable asbestos material;
 - ii. Category I nonfriable asbestos-containing material that has become friable;
 - iii. Category I nonfriable asbestos-containing material that will be or has been subjected to sanding, grinding, cutting, or abrading; or
 - iv. Category II nonfriable asbestos-containing material that has a high probability of becoming or has become crumbled, pulverized, or reduced to powder by the forces expected to act on the material in the course of demolition or renovation operations regulated by this subpart.

Exact Copy of Page 17 of 25 Below Outlines Minerva's: Annual Permit Limit & Begins Asbestos Specific F003 Asbestos Disposal Permit



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit to Install and Operate
Permit Number: F0104964
Facility ID: 1576001700
Effective Date: 1/5/2010

3. F003, Asbestos Disposal

Operations, Property and/or Equipment Description:

Construction and Demolition Waste Landfill Approved to Accept NESHAP-regulated Asbestos-containing Waste Materials

a) This permit document constitutes a permit to install issued in accordance with ORC 3704.03(F) and a permit to operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit to install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit to operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) **Applicable Emissions Limitations and/or Control Requirements**

(1) The specific operations(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	40 CFR 61.154(a) and (e) and OAC rule 3745-20-06 This PTIO supercedes PTI 15-1292 Modification NESHAP 40 FCR Part 61, Subpart M	Permittee shall not create any visible emissions
b.	The permittee has agreed to limit the volume of material accepted.	A maximum of 1,000,000 tons per year of C & D material containing RACM may be accepted.



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate
Permit Number: P0104984
Facility ID: 1576001700
Effective Date: 1/5/2010

(2) Additional Terms and Conditions

- a. The landfill, approved to accept asbestos-containing waste materials shall maintain the following work practice standards.
 - b. There shall be no visible emissions from asbestos-containing waste materials during on-site transportation, transfer, unloading, deposition, compacting operations, or from any inactive asbestos waste disposal sites.
 - c. Deposition and burial operations shall be conducted in a careful manner that prevents asbestos-containing waste materials from being broken up or dispersed before the materials are buried.
 - d. The permittee shall inspect each load of asbestos-containing material delivered to the facility. The inspection shall consist of a visual examination to ensure that each shipment of asbestos-containing waste materials is received in intact, leak-tight containers labeled with appropriate hazard warning labels, the name of the waste generator, and the location of waste generation. The inspection also shall determine whether the waste shipment records accompany the consignment and accurately describe the waste material and quantity.
 - i. If on the basis of the inspection, the waste material is found to be improperly received, the load shall be disposed of in accordance with the procedures in the "Asbestos Spill Contingency Plan," and the discrepancy shall be noted on the waste shipment record.
- [40 CFR 61.154(a) and (e)] and [OAC rule 3745-20-06]
- e. The permittee shall develop, implement, and maintain an "Asbestos Disposal Operating Procedure and Spill Contingency Plan" consisting of:
 - i. authorized personnel training;
 - ii. inspection and disposal operating procedures;
 - iii. non-conforming load response procedures;
 - iv. inventory and maintenance procedures for safety and emissions control equipment;
 - v. record keeping procedures; and
 - vi. emergency notification procedures.

Authorized personnel shall be knowledgeable in the procedures, and the Plan shall be available for inspection at this facility at all times. Emissions control equipment shall be available for wetting and containing asbestos in



State of Ohio Environmental Protection Agency
Division of Air Pollution Control

Final Permit-to-Install and Operate
Permit Number: F0104984
Facility ID: 1576001700
Effective Date: 1/5/2010

the event of a release or non-conforming load disposal. All equipment required to implement the "Asbestos Disposal Operating Procedure and Spill Contingency Plan" shall be maintained in accordance with good engineering practices to ensure that the equipment is in a ready-to-use condition and in an appropriate location for use.

[OAC rule 3745-20-06, in part] and/or [OAC rule 3745-31-05(A)(3)]

f. The facility can accept for disposal any regulated asbestos-containing material as defined in the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Asbestos, 40 CFR Part 61, Subpart M, Section 141 and OAC rule 3745-20, or any subsequent revisions to either rule. Regulated asbestos-containing material is defined to include:

- i. friable asbestos material;
- ii. Category I nonfriable asbestos-containing material that has become friable;
- iii. Category I nonfriable asbestos-containing material that will be or has been subjected to sanding, grinding, cutting, or abrading; or
- iv. Category II nonfriable asbestos-containing material that has a high probability of becoming or has become crumbled, pulverized, or reduced to powder by the forces expected to act on the material in the course of demolition or renovation operations regulated by this subpart.

g. The permittee shall ensure that any Category I and/or Category II nonfriable asbestos-containing waste material received does not become friable during processing at the landfill. If any asbestos material arrives at the landfill and meets the description of a regulated asbestos-containing material as described in (a) through (d) above, the landfill shall:

- i. cause or permit no visible emissions to the outside air from the asbestos-containing waste materials during on-site transportation, transfer, deposition, or compacting operations;
- ii. assure that deposition and burial operations are conducted in a manner which prevents handling by equipment or persons that causes asbestos-containing waste materials to be broken up or dispersed before the materials are buried;
- iii. cover the asbestos-containing waste material with at least twelve inches of nonasbestos-containing material, as soon as practicable after deposition, but no later than at the end of the operating day; and

Section 4

Supervisor Qualifications

Precision Environmental Company
Precision ProCat

Respirator Assignment and Fit Test

A successful respirator fit test has been completed by the individual named below using the respirator fit test procedure mandated in 29 CFR, 1910.134 Appendix A.

Name: Kenny Yates SS Number (last 4 digits): XXX-XX-4117 Date: 6-19-11

Address (street, city, state, zip): 2235a Harms Rd, Richmond Hts, Ohio 44143

Respirator Model	Size	Pass	Fail
<input checked="" type="checkbox"/> M600 5500/700 Half Usec	S <input type="checkbox"/> M <input type="checkbox"/> L <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> M Powerflow Full Face PAPR	S <input type="checkbox"/> M <input type="checkbox"/> L <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Other	S <input type="checkbox"/> M <input type="checkbox"/> L <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Annual Respiratory Protection Training completed per 29 CFR 1910.134: Yes No

Normal respiratory condition: Yes No

Type of Fit Test: Qualitative Quantitative

Type of Qualitative Test: Isobutyl alcohol Banana oil Sucralose

I hereby certify that the above named employee has been properly fit tested per the referenced and attached procedures.

Signature: [Signature]
Fit Tester Name:

Signature: [Signature]
Employee Name:



PRECISION ENVIRONMENTAL COMPANY
PRECISION PROCAT
RESPIRATOR QUALIFICATION

Patient Name: Kenny Yates

SS# (last 4): XXX-XX-4117

This office certifies that the above named individual has been evaluated and completed the medical surveillance program provided by Precision Environmental and Precision ProCat. The medical surveillance program meets or exceeds the requirements of 29 CFR 1910.126, 29 CFR 1910.134 and 29 CFR 1926.1161.

The healthcare provider for this surveillance examination is:

Concordia Medical Center
4800 Blunkhoy Industrial Parkway
Cleveland, Ohio 44109

The above named patient has been examined in accordance with the above requirements and has been found to be:

- Qualified for respirator use without restrictions
 Not qualified for respirator use

Signature: [Signature]
Physician Signature

Date: 6/19/11
Date (print clearly or type)

Signature: [Signature]
Physician Name



Asbestos Contractor Supervisor Refresher

Certificate
This is to certify
Kenny Yates
XXX-XX-4117



I have attended and successfully completed the Asbestos Hazard Emergency Response Act mandatory training for the Asbestos Contractor Supervisor Refresher and has passed an examination in that course with a minimum score of 70% or better. Training was in accordance with 40 CFR, Part 763 (A) (EX-2). The above student received the requisite training for asbestos accreditation under Title II of the Toxic Substances Control Act, State of Indiana requirements under 326 IAC 1-6.2, Chapter 3701-34 Ohio Administrative Code, and the Illinois Department of Public Health (IDPH) under section 955.120 of Title 22. IDPH recognition based on student request.

Training Manager	Expiration Date	Date(s) of Course	Examination Date	Course Location
<u>[Signature]</u>	<u>2/19/12</u>	<u>2/19/11</u>	<u>2/19/11</u>	<u>Independence, OH</u>

TST
11158 Lakeland Blvd.
Cleveland, OH 44135
1-866-666-3438

11 TSI 38777 csc

CONCORDIA MEDICAL CENTER
MEDICAL EXAMINER'S CERTIFICATE

Name: Kenny Yates

SSN: XXX-XX-4117

DOB: 08/31/1949

Signature: [Signature]
Physician Name: Retired

Date: 6/19/11

State of Ohio
Department of Health
Division of Quality Assurance - Asbestos Program

Asbestos Hazard Abatement Specialist

Kenneth A Yates
Precision Environmental Company
5500 Old Brecksville Road
Independence OH 44131



Certification Number: AS2553
Expiration Date: 03/05/2012

DOB: 08/31/1949
Certification Card is

This certification is issued pursuant to Chapter 3712 of the

STATE OF NEW YORK - DEPARTMENT OF LABOR
ASBESTOS CERTIFICATE



KENNETH A YATES
CLASS EXPIRES
03/05/12



CERT# 09-11704
DMV# 774229691

MUST BE CARRIED ON ASBESTOS PROJECTS

CERTIFICATE OF ACHIEVEMENT



Construction Industry Service Program of Greater Cleveland

honors

Ken Yates

for achievement in completing

OSHA 30-HOUR FOR CONSTRUCTION

AUGUST 4, 11, 18, 2006

John B. Poraga
JOHN B. PORAGA
ADMINISTRATOR

Darlene Fossli
DARLENE FOSSLIM
OSHA
CONSTRUCTION TEAM LEADER

Wayne J. Greasap
WAYNE J. GREASAP
DIRECTOR OF SAFETY EDUCATION

Stephaniel Johnson
STEPHANIEL JOHNSON
ASSISTANT DIRECTOR OF
SAFETY EDUCATION

HAZARDOUS MATERIALS TECHNICIAN

This certificate of completion is awarded to

Kenny Yates

For completion of eight hours of Hazardous Material
Technician refresher training according to 29 CFR 1910.120
Precision Environmental



PRECISION Environmental Company
5722 School Road - Independence, Ohio 44131 - (216) 941-6940

Certifies that

KENNETH A. YATES
818 Weybridge Avenue, Cleveland, Ohio 44118

Successfully completed the construction

LEAD HAZARD AWARENESS

Conducted in accordance with 29 CFR 1926.62

Course Date: March 14, 1996
Certificate Number: 02148612

HAZARDOUS WASTE WORKER REFRESHER TRAINING COURSE

NAME:	Kenneth Yates		
OSHA:	XX-XX-4117		
DATE COMPLETED INITIAL COURSE:	2/10/06	REFRESHER COMPLETION DATE:	3/10/07
NEXT REFRESHER TRAINING DUE WITHIN ONE YEAR OF THE REFRESHER COMPLETION DATE:	3/10/08		
CERTIFICATE #:	277504117HWR0307		

COMPLIES WITH OSHA REGULATION 29 CFR 1910.120



LABORERS-AGG EDUCATION AND TRAINING FUND

37 Deerfield Road
P.O. Box 37
Pomfret Center, CT 06259
(860) 974-0800

University of Cincinnati

Occupational Health & Safety Continuing Education Program
Co-Sponsored by *Training Services International*

Kenny Yates

Precision Environmental
818 Weybridge Ave
Independence, OH 44131

The Successful Candidate Completed the
Lead Safety for Renovation, Repair and Painting Initial Training Course

Stephaniel Johnson
Program Director

R-17845-10-02513

Certificate Number: 682010

Issue Date: 6/15/10

Language: English

10 TSI 35602 ERF

American Heart Association
Learn and Live

Heartsaver® First Aid

Kenny Yates

For each certificate the sponsor and recipient must complete the sponsor and recipient registration in accordance with the provisions of the AHA Instructor Registration Manual.

APRIL 2010

APRIL 2012

Training Center: AHAID 216-337-9435

TO ADDRESS CERTIFICATES: Health, Compliance, Care, ACLS & CPR

Instructor: CRAIG DUNNING & CORNELL JENNIFER

Holdings: 6/15/10

If in the center of the module NOT completed. This card contains unique security features to protect against forgery.

Section 5

Worker Qualifications

Worker documentation shall be submitted when work crew is known.

Section 6

Respiratory Protection Program

1.0 PURPOSE

To provide guidance, in compliance with 29 CFR 1910.134, 29 CFR 1926.1101(h)(2), and 29 CFR 1926.62(f)(1), in the selection and proper use of respirators for protection from respiratory hazards during the course of working with known and unknown hazardous materials. These materials may include but are not limited to asbestos, lead, mold, and other respiratory hazards.

2.0 APPLICATION

This procedure applies to the Precision Environmental Company and Precision ProCUT facilities and jobsites when employees are determined to require the use of respiratory protection.

Compliance with local laws and regulations is mandatory. Where the customer's procedures are more protective than OSHA or local requirements, Precision Environmental will comply with the more protective requirements.

3.0 RESPONSIBILITY

The Safety Director is the designated Respiratory Protection Program Administrator and is solely responsible for all facets of the program and has full authority to make necessary decisions to ensure the success of this program. The Program Administrator will develop and maintain written detailed instructions covering each of the basic elements in this program, and is the sole person authorized to amend these instructions. This company has expressly authorized the Program Administrator to halt any operation of the company where there is danger of serious personal injury.

Project Managers and Supervisors shall be responsible for implementation of the Respiratory Protection Program on projects. This includes ensuring that proper selection of respirators, fit testing, training, and maintenance has been conducted for employees on all projects.

4.0 DEFINITIONS

4.1 Air-Purifying Respirators are respirators which can purify the air, but do not supply air. They must never be used in oxygen-deficient atmospheres. They include:

- Gas and Vapor Respirators (Chemical Cartridge Respirators)
- Particulate Respirators (Mechanical Filter Respirators)

- Powered Air-Purifying Respirators (PAPR)
 - Combination Gas, Vapor, and Particulate Respirators
- 4.2 Air-Supplying Respirators are respirators which provide a supply of breathable air different from the workplace air. They include:
- Self-Contained Breathing Apparatus (SCBA)
 - Supplied-Air Respirators (SAR)
 - Combination Self-Contained and Air-Supplying Respirators
- 4.3 Chemical Cartridge Respirators - See Gas and Vapor Respirators.
- 4.4 Combination Gas, Vapor, and Particulate Respirators filter out gases, vapors, and particulates by passing the contaminated air through a cartridge or canister containing both a particulate filter and a gas/vapor absorbing device.
- 4.5 Combination Self-Contained and Air-Supplying Respirators are respirators usually used in atmospheres that are immediately dangerous to life or health. The auxiliary cylinder permits escape if the regular air-line supply is cut off.
- 4.6 Filtering Facepiece (dust mask) means a negative pressure particulate respirator with a filter as an integral part of the facepiece or with the entire facepiece composed of the filtering medium.
- 4.7 Gas And Vapor Respirators (also known as chemical cartridge respirators) are respirators which remove gases and/or vapors by passing the contaminated air through cartridges containing charcoal or other special material that traps these contaminants. Cartridges must be matched to the contaminants. These cartridges are used to protect against contaminants that have adequate warning properties of smell or irritation. This allows the wearer to judge when a cartridge is no longer usable. Some cartridges are dated as well, and should not be used after the expiration date.
- 4.8 Immediately Dangerous to Life and Health (IDLH) is a term used to describe a very hazardous atmosphere where employee exposure can:
- Cause serious injury or death within a short time.
 - Cause serious delayed (chronic) effects.
- 4.9 Negative Pressure Respirator is a respirator in which the pressure inside the face piece is lower than the outside pressure. (This means that all negative-pressure respirators must have a tight fitting face piece with a good seal between the respirator and the face. If the fit is poor and a leak occurs, the outside

contaminated air at the higher pressure will leak into the face piece at the lower pressure.) Since leaks would be occurring around the seal rather than through the air-purifying elements of the respirator, contaminated air would enter the worker's breathing zone.

- 4.10 Particulate Respirators (also known as mechanical filter respirators) are respirators which depending upon the design of the filters, can filter out dust, fog, fume, mist, spray, or smoke by passing the contaminated air through a pad or filter. Filters should be changed at frequent intervals, when they become clogged, or when it becomes difficult to breathe through them.
- 4.11 Positive Pressure Respirator is a respirator in which the pressure inside the respirator face piece is greater than the pressure outside the face piece or the atmospheric pressure. Theoretically, a leak would be outward and exposure to the contaminant is less likely to occur.
- 4.12 Powered Air-Purifying Respirators use a blower to draw contaminated air through an element that removes the contaminant and to supply purified air to a face piece, helmet, or hood. The purifying element may be either a filter, a cartridge, or a combination of the two.
- 4.13 Qualitative Fit Test is a pass/fail fit test that relies on the wearer's sensory response to detect the challenge agent.
- 4.14 Quantitative Fit Test is a fit test that uses an instrument to measure the challenge agent inside and outside the respirator.
- 4.15 Respiratory Hazards occur when a toxic or harmful material is present in the atmosphere at a concentration that is high enough to impair body function. Some respirators protect against air contaminants while others protect against both air contaminants and oxygen deficiency.
- 4.16 Self-Contained Breathing Apparatus (SCBA) are respirators which provide a transportable supply of breathable air, and afford complete respiratory protection against toxic gases and oxygen deficiency.
- 4.17 Supplied-Air Respirators (SAR) provide air through an air line or air hose. The air may be supplied from a compressor or through a large diameter tubing with its inlet placed in uncontaminated air.

5.0 PROCEDURES

5.1 General Requirements

5.1.1 The program administrator shall assure that an effective respiratory protection program is implemented by:

- Conducting PPE Hazard Assessment to determine the workplace risks and hazards to which employees may be exposed (for Precision's PPE Hazard Assessment see Appendix 6);
- Developing a written standard operating procedure covering the training, selection, use and maintenance of respirators;
- Providing the correct respirators for the specific hazards;
- Maintaining surveillance of work area conditions and degree of employee exposure or stress;
- Conducting a regular inspection and evaluation to determine the continued effectiveness of the program.

5.1.2 Respirators are to be used only where engineering control of respiratory hazards is not feasible, while engineering controls are being installed, or in emergencies.

5.1.3 When effective engineering controls are not feasible, employees that are exposed to the effects of inhaling hazardous dust, gases, mist, vapors and fumes must be provided with respiratory protection devices.

5.1.4 Respirators shall only be used by those employees who have been properly fitted and trained in the proper use, care, storage and maintenance of the respirators.

5.1.5 Respirators shall be assigned to individual workers for their exclusive use.

5.1.6 Respirators shall not be worn when conditions prevent a good face seal. Such conditions may be a growth of beard, side burns, a skull cap that projects under the face piece, or temple pieces on glasses. Also the absence of one or both dentures can seriously affect the fit of a face piece.

5.1.7 All employees who are required to wear a respirator for personal protection through the course of their normal job requirements, shall be clean shaven at the beginning of the day. No beards or long side burns that

reach the seal of the respirator shall be allowed. Mustaches are permissible as long as they do not reach the seal of the respirator.

5.1.8 Contact lenses shall not be worn under self-contained breathing apparatus (SCBA) or supplied air respirators (SAR).

5.1.9 All employees who require corrective prescription lenses and are required to wear a full-face respirator (Air Purifying, Supplied Air or SCBA) shall be provided a pair of prescription eyeglass inserts.

5.2 Respirator Selection

5.2.1 Respirators shall be selected on the basis of hazards to which the worker is exposed.

5.2.2 Only NIOSH certified respirators shall be selected and used.

5.2.3 Respirator parts which are not certified for use together must NEVER be interchanged.

5.2.4 Respirator parts manufactured by a different respirator supplier must NEVER be interchanged.

5.3 Medical Qualifications

5.3.1 Employees required to wear respiratory protection shall be examined annually by a physician to ensure that they are physically able to wear respirators while working.

5.3.2 The physician conducting the exam shall determine what health and physical conditions are pertinent and shall certify the employee's ability to use a respirator in compliance with the requirements of 29 CFR 1910.120, 29 CFR 1910.134 and 29 CFR 1926.1101..

5.4 Training

5.4.1. Respirator training shall include:

- The contaminants to be encountered, their toxic properties and the probable concentration to be expected.
- The reasons for using the respirator and the protection to be provided.

- Description of the respiratory protective device. This shall include the capabilities and limitations of the respirator, the parts of the respirator, and instructions on checking for proper fit and operating condition.
- Actual process of putting the respirator on and adjusting for proper fit.
- Wearing the respirator for a period of time in normal air to become familiar with its use.
- Instruction on the proper maintenance and storage of the respirator.
- Fit testing.
- Respirator training records shall be maintained in the employee training record file.

5.5 Fit Testing

- 5.5.1. Qualitative fit testing procedures (Appendix 2) shall be performed initially on all employees required to wear respirators and repeated at least annually (or at appropriate intervals when there is a significant change in the wearer's physical status).
- 5.5.2. Any employee who is not clean-shaven or who has any other facial features which intrude into the respirator sealing surface, shall not be fit tested and shall not be allowed to wear a respirator.
- 5.5.3. All records related to respirator fit testing shall be maintained in the employee's file and in the Precision employee database.
- 5.5.4. To assure proper protection, the facepiece fit shall be checked by the wearer each time the respirator is worn. Test procedures shall include simple field tests (negative and positive fit test).

5.6 Respirator Inspection, Maintenance and Storage

- 5.6.1 Employees using respirators must guard against damage to the respirators and immediately replace any defective respirator or respirator parts.
- 5.6.2. Respirators shall be properly maintained per the procedures in Appendix 3 to assure proper performance and maximum employee protection. This maintenance program shall include:

- Periodic inspection of all respirators. Respirators shall be inspected routinely by the user and immediately before each use.
- Regular cleaning and sanitizing of respirators. (All equipment shall be cleaned and sanitized on a daily basis when used.)
- Inspection of respirator component parts when they are cleaned and replacement of defective parts.

5.6.3. Respirators shall be cleaned after each use and stored in a convenient and sanitary location. Storage containers for clean respirators, in the form of plastic bags or covered boxes, shall be provided.

5.6.4. Respirators shall be stored to protect them from dust, sunlight, heat, extreme cold, excessive moisture, and damaging chemicals. Unprotected respirators can sustain damaged parts or face piece distortion that make them ineffective.

5.6.5. Respirators for emergency use, self-contained breathing apparatus (SCBA), and supplied air respirator systems (SAR) shall be thoroughly inspected at least once a month and after each use.

Irritant Smoke Fit Test Protocol
(attach to back of fit test form)

The following test exercises are to be performed for an accepted fit test. Each test exercise shall be performed for one minute. The respirator shall not be adjusted once the fit test exercises begin. Any adjustment voids the test, and the fit test must be repeated. The test subject shall perform exercises, in the test environment, in the following manner:

- (1) Normal breathing. In a normal standing position, without talking, the subject shall breathe normally.
- (2) Deep breathing. In a normal standing position, the subject shall breathe slowly and deeply, taking caution so as not to hyperventilate.
- (3) Turning head side to side. Standing in place, the subject shall slowly turn his/her head from side to side between the extreme positions on each side. The head shall be held at each extreme momentarily so the subject can inhale at each side.
- (4) Moving head up and down. Standing in place, the subject shall slowly move his/her head up and down. The subject shall be instructed to inhale in the up position (i.e., when looking toward the ceiling).
- (5) Talking. The subject shall talk out loud slowly and loud enough so as to be heard clearly by the test conductor. The subject can read from a prepared text such as the Rainbow Passage, count backward from 100, or recite a memorized poem or song. *Note: Rainbow Passage cannot be performed during an irritant smoke fit test since eyes must remain closed.*

Rainbow Passage

When the sunlight strikes raindrops in the air, they act like a prism and form a rainbow. The rainbow is a division of white light into many beautiful colors. These take the shape of a long round arch, with its path high above, and its two ends apparently beyond the horizon. There is, according to legend, a boiling pot of gold at one end. People look, but no one ever finds it. When a man looks for something beyond reach, his friends say he is looking for the pot of gold at the end of the rainbow.

- (6) Bending over. The test subject shall bend at the waist as if he/she were to touch his/her toes.
- (7) Normal breathing. Same as exercise (1).

Irritant Smoke (Stannic Chloride) Protocol

- (1) The respirator to be tested shall be equipped with high efficiency particulate air (HEPA) or P100 series filter(s).
- (2) Only stannic chloride smoke tubes shall be used for this protocol.
- (3) No form of test enclosure or hood for the test subject shall be used.
- (4) The smoke can be irritating to the eyes, lungs, and nasal passages. The test conductor shall take precautions to minimize the test subject's exposure to irritant smoke. Sensitivity varies, and certain individuals may respond to a greater degree to irritant smoke.
- (5) The fit test shall be performed in an area with adequate ventilation to prevent exposure of the person conducting the fit test or the build-up of irritant smoke in the general atmosphere.
- (6) The person being fit tested shall don the respirator without assistance, and perform the required user seal check(s).
- (7) The test subject shall be instructed to keep his/her eyes closed.
- (8) The test operator shall direct the stream of irritant smoke from the smoke tube toward the face seal area of the test subject, using the low flow pump or the squeeze bulb. The test operator shall begin at least 12 inches from the facepiece and move the smoke stream around the whole perimeter of the mask. The operator shall gradually make two more passes around the perimeter of the mask, moving to within six inches of the respirator.
- (9) If the person being tested has not had an involuntary response and/or detected the irritant smoke, proceed with the test exercises.
- (10) Exercises, 1 through 7 listed above, shall be performed by the test subject while the respirator seal is being continually challenged by the smoke, directed around the perimeter of the respirator at a distance of six inches.
- (11) If the person being fit tested reports detecting the irritant smoke at any time, the test is failed. The person being retested must repeat the entire fit test procedure. If the irritant smoke is not detected then the fit test is passed.

APPENDIX 2

Precision Environmental's Accepted Fit Test Protocols (OSHA 1910.134 Appendix A)

A. Fit Testing Procedures – General Requirements

Precision's Supervisors or designated medical provider shall conduct fit testing using the following procedures.

1. The test subject shall be allowed to pick the most acceptable respirator from a sufficient number of respirator models and sizes so that the respirator is acceptable to, and correctly fits, the user.
2. Prior to the selection process, the test subject shall be shown how to put on a respirator, how it should be positioned on the face, how to set strap tension and how to determine an acceptable fit. A mirror shall be available to assist the subject in evaluating the fit and positioning of the respirator. This instruction may not constitute the subject's formal training on respirator use, because it is only a review.
3. The test subject shall be informed that he/she is being asked to select the respirator that provides the most acceptable fit. Each respirator represents a different size and shape, and if fitted and used properly, will provide adequate protection.
4. The test subject shall be instructed to hold each chosen facepiece up to the face and eliminate those that obviously do not give an acceptable fit.
5. The more acceptable facepieces are noted in case the one selected proves unacceptable; the most comfortable mask is donned and worn at least five minutes to assess comfort. Assistance in assessing comfort can be given by discussing the points in the following item A.6. If the test subject is not familiar with using a particular respirator, the test subject shall be directed to don the mask several times and to adjust the straps each time to become adept at setting proper tension on the straps.
6. Assessment of comfort shall include a review of the following points with the test subject and allowing the test subject adequate time to determine the comfort of the respirator:
 - (a) Position of the mask on the nose
 - (b) Room for eye protection
 - (c) Room to talk
 - (d) Position of mask on face and cheeks
7. The following criteria shall be used to help determine the adequacy of the respirator fit:
 - (a) Chin properly placed;

- (b) Adequate strap tension, not overly tightened;
 - (c) Fit across nose bridge;
 - (d) Respirator of proper size to span distance from nose to chin;
 - (e) Tendency of respirator to slip;
 - (f) Self-observation in mirror to evaluate fit and respirator position.
8. The test subject shall conduct a user seal check, either the negative and positive pressure seal checks described in Appendix 4 of this section or those recommended by the respirator manufacturer which provide equivalent protection to the procedures in Appendix 4. Before conducting the negative and positive pressure checks, the subject shall be told to seat the mask on the face by moving the head from side-to-side and up and down slowly while taking in a few slow deep breaths. Another facepiece shall be selected and retested if the test subject fails the user seal check tests.
 9. The test shall not be conducted if there is any hair growth between the skin and the facepiece sealing surface, such as stubble beard growth, beard, mustache or sideburns which cross the respirator sealing surface. Any type of apparel which interferes with a satisfactory fit shall be altered or removed.
 10. If a test subject exhibits difficulty in breathing during the tests, she or he shall be referred to a physician or other licensed health care professional, as appropriate, to determine whether the test subject can wear a respirator while performing her or his duties.
 11. If the employee finds the fit of the respirator unacceptable, the test subject shall be given the opportunity to select a different respirator and to be retested.
 12. Exercise regimen. Prior to the commencement of the fit test, the test subject shall be given a description of the fit test and the test subject's responsibilities during the test procedure. The description of the process shall include a description of the test exercises that the subject will be performing. The respirator to be tested shall be worn for at least 5 minutes before the start of the fit test.
 13. The fit test shall be performed while the test subject is wearing any applicable safety equipment that may be worn during actual respirator use, which could interfere with respirator fit.
 14. Test Exercises.
 - (a) The following test exercises are to be performed for Precision's accepted fit test protocols as prescribed in this appendix. The test subject shall perform exercises, in the test environment, in the following manner:
 - (1) Normal breathing. In a normal standing position, without talking, the subject shall breathe normally.

- (2) Deep breathing. In a normal standing position, the subject shall breathe slowly and deeply, taking caution so as not to hyperventilate.
- (3) Turning head side to side. Standing in place, the subject shall slowly turn his/her head from side to side between the extreme positions on each side. The head shall be held at each extreme momentarily so the subject can inhale at each side.
- (4) Moving head up and down. Standing in place, the subject shall slowly move his/her head up and down. The subject shall be instructed to inhale in the up position (i.e., when looking toward the ceiling).
- (5) Talking. The subject shall talk out loud slowly and loud enough so as to be heard clearly by the test conductor. The subject can read from a prepared text such as the Rainbow Passage, count backward from 100, or recite a memorized poem or song.

Rainbow Passage

When the sunlight strikes raindrops in the air, they act like a prism and form a rainbow. The rainbow is a division of white light into many beautiful colors. These take the shape of a long round arch, with its path high above, and its two ends apparently beyond the horizon. There is, according to legend, a boiling pot of gold at one end. People look, but no one ever finds it. When a man looks for something beyond reach, his friends say he is looking for the pot of gold at the end of the rainbow.

- (6) Bending over. The test subject shall bend at the waist as if he/she were to touch his/her toes.
 - (7) Normal breathing. Same as exercise (1).
- (b) Each test exercise shall be performed for one minute. The test subject shall be questioned by the test conductor regarding the comfort of the respirator upon completion of the protocol. If it has become unacceptable, another model of respirator shall be tried. The respirator shall not be adjusted once the fit test exercises begin. Any adjustment voids the test, and the fit test must be repeated.

B. Qualitative Fit Test (QLFT) Protocols

1. General

- (a) The Program Administrator when administering QLFT shall be able to prepare test solutions, calibrate equipment and perform tests properly, recognize invalid tests, and ensure that test equipment is in proper working order.
- (b) The Program Administrator shall ensure that QLFT equipment is kept clean and well maintained so as to operate within the parameters for which it was designed.

2. Irritant Smoke (Stannic Chloride) Protocol

This qualitative fit test uses a person's response to the irritating chemicals released in the "smoke" produced by a stannic chloride ventilation smoke tube to detect leakage into the respirator.

(a) General Requirements and Precautions

- (1) The respirator to be tested shall be equipped with high efficiency particulate air (HEPA) or P100-series filter(s).
- (2) Only stannic chloride smoke tubes shall be used for this protocol.
- (3) No form of test enclosure or hood for the test subject shall be used.
- (4) The smoke can be irritating to the eyes, lungs, and nasal passages. The test conductor shall take precautions to minimize the test subject's exposure to irritant smoke. Sensitivity varies, and certain individuals may respond to a greater degree to irritant smoke. Care shall be taken when performing the sensitivity screening checks that determine whether the test subject can detect irritant smoke to use only the minimum amount of smoke necessary to elicit a response from the test subject.
- (5) The fit test shall be performed in an area with adequate ventilation to prevent exposure of the person conducting the fit test or the build-up of irritant smoke in the general atmosphere.

(b) Sensitivity Screening Check

The person to be tested must demonstrate his or her ability to detect a weak concentration of the irritant smoke.

- (1) The test operator shall break both ends of a ventilation smoke tube containing stannic chloride, and attach one end of the smoke tube to an aspirator squeeze bulb.
- (2) The test operator shall advise the test subject that the smoke can be irritating to the eyes, lungs, and nasal passages and instruct the subject to keep his/her eyes closed while the test is performed.
- (3) The test subject shall be allowed to smell a weak concentration of the irritant smoke before the respirator is donned to become familiar with its irritating properties and to determine if he/she can detect the irritating properties of the smoke. The test operator shall carefully direct a small amount of the irritant smoke in the test subject's direction to determine that he/she can detect it.

(c) Irritant Smoke Fit Test Procedure

- (1) The person being fit tested shall don the respirator without assistance, and perform the required user seal check(s).
- (2) The test subject shall be instructed to keep his/her eyes closed.

- (3) The test operator shall direct the stream of irritant smoke from the smoke tube toward the face seal area of the test subject, using the low flow pump or the squeeze bulb. The test operator shall begin at least 12 inches from the facepiece and move the smoke stream around the whole perimeter of the mask. The operator shall gradually make two more passes around the perimeter of the mask, moving to within six inches of the respirator.
- (4) If the person being tested has not had an involuntary response and/or detected the irritant smoke, proceed with the test exercises.
- (5) The exercises identified in section I.A. 14. of this appendix shall be performed by the test subject while the respirator seal is being continually challenged by the smoke, directed around the perimeter of the respirator at a distance of six inches.
- (6) If the person being fit tested reports detecting the irritant smoke at any time, the test is failed. The person being retested must repeat the entire sensitivity check and fit test procedure.
- (7) Each test subject passing the irritant smoke test without evidence of a response (involuntary cough, irritation) shall be given a second sensitivity screening check, with the smoke from the same smoke tube used during the fit test, once the respirator has been removed, to determine whether he/she still reacts to the smoke. Failure to evoke a response shall void the fit test.
- (8) If a response is produced during this second sensitivity check, then the fit test is passed.

APPENDIX 3

Precision Environmental Respirator Cleaning Procedures (OSHA 1910.13 Appendix B-2)

These procedures are provided for employee use when cleaning respirators. They are general in nature, and the employee as an alternative may use the cleaning recommendations provided by the manufacturer of the respirators used by their employees, provided such procedures are as effective as those listed here. Equivalent effectiveness simply means that the procedures used must accomplish the objectives set forth in this Appendix, i.e., must ensure that the respirator is properly cleaned and disinfected in a manner that prevents damage to the respirator and does not cause harm to the user.

I. Procedures for Cleaning Respirators

- A. Remove filters, cartridges, or canisters. Disassemble facepieces by removing speaking diaphragms, demand and pressure-demand valve assemblies, hoses, or any components recommended by the manufacturer. Discard or repair any defective parts.
- B. Wash components in warm (110 deg. F maximum) water with a mild detergent or with a cleaner recommended by the manufacturer. A stiff bristle (not wire) brush may be used to facilitate the removal of dirt.
- C. Rinse components thoroughly in clean, warm (110 deg. F maximum), preferably running water. Drain.
- D. When the cleaner used does not contain a disinfecting agent, respirator components should be immersed for two minutes in one of the following:
 1. Hypochlorite solution (50 ppm of chlorine) made by adding approximately one milliliter of laundry bleach to one liter of water at (110 deg. F); or,
 2. Aqueous solution of iodine (50 ppm iodine) made by adding approximately 0.8 milliliters of tincture of iodine (6-8 grams ammonium and/or potassium iodide/100 cc of 45% alcohol) to one liter of water at (110 deg. F); or,
 3. Other commercially available cleansers of equivalent disinfectant quality when used as directed, if their use is recommended or approved by the respirator manufacturer.
- E. Rinse components thoroughly in clean, warm (110 deg. F maximum), preferably running water. Drain. The importance of thorough rinsing cannot be overemphasized. Detergents or disinfectants that dry on facepieces may result in dermatitis. In addition,

some disinfectants may cause deterioration of rubber or corrosion of metal parts if not completely removed.

- F. Components should be hand-dried with a clean lint-free cloth or air-dried.
- G. Reassemble facepiece, replacing filters, cartridges, and canisters where necessary.
- H. Test the respirator to ensure that all components work properly.

APPENDIX 4

Precision Environmental User Seal Check Procedures (OSHA 1910.134 Appendix B-1)

The individual who uses a tight-fitting respirator is to perform a user seal check to ensure that an adequate seal is achieved each time the respirator is put on. Either the positive and negative pressure checks listed in this appendix, or the respirator manufacturer's recommended user seal check method shall be used. User seal checks are not substitutes for qualitative or quantitative fit tests.

I. Facepiece Positive and/or Negative Pressure Checks

- A. Positive pressure check. Close off the exhalation valve and exhale gently into the facepiece. The face fit is considered satisfactory if a slight positive pressure can be built up inside the facepiece without any evidence of outward leakage of air at the seal. For most respirators this method of leak testing requires the wearer to first remove the exhalation valve cover before closing off the exhalation valve and then carefully replacing it after the test.
- B. Negative pressure check. Close off the inlet opening of the canister or cartridge(s) by covering with the palm of the hand(s) or by replacing the filter seal(s), inhale gently so that the facepiece collapses slightly, and hold the breath for ten seconds. The design of the inlet opening of some cartridges cannot be effectively covered with the palm of the hand. The test can be performed by covering the inlet opening of the cartridge with a thin latex or nitrile glove. If the facepiece remains in its slightly collapsed condition and no inward leakage of air is detected, the tightness of the respirator is considered satisfactory.

II. Manufacturer's Recommended User Seal Check Procedures

The respirator manufacturer's recommended procedures for performing a user seal check may be used instead of the positive and/or negative pressure check procedures provided that the employer demonstrates that the manufacturer's procedures are equally effective.

APPENDIX 5

Precision Environmental Voluntary Use Procedure (OSHA 1910.134 Appendix D)

Information for Employees Using Respirators When Not Required Under the Standard

Respirators are an effective method of protection against designated hazards when properly selected and worn. Respirator use is encouraged, even when exposures are below the exposure limit, to provide an additional level of comfort and protection for workers. However, if a respirator is used improperly or not kept clean, the respirator itself can become a hazard to the worker. Sometimes, workers may wear respirators to avoid exposures to hazards, even if the amount of hazardous substance does not exceed the limits set by OSHA standards. If your employer provides respirators for your voluntary use, or if you provide your own respirator, you need to take certain precautions to be sure that the respirator itself does not present a hazard.

You should do the following:

1. Read and heed all instructions provided by the manufacturer on use, maintenance, cleaning and care, and warnings regarding the respirators limitations.
2. Choose respirators certified for use to protect against the contaminant of concern. NIOSH, the National Institute for Occupational Safety and Health of the U.S. Department of Health and Human Services, certifies respirators. A label or statement of certification should appear on the respirator or respirator packaging. It will tell you what the respirator is designed for and how much it will protect you.
3. Do not wear your respirator into atmospheres containing contaminants for which your respirator is not designed to protect against. For example, a respirator designed to filter dust particles will not protect you against gases, vapors, or very small solid particles of fumes or smoke.
4. Keep track of your respirator so that you do not mistakenly use someone else's respirator.

APPENDIX 6

Precision Environmental's Respirator Hazard Assessment

The nature of Precision's work in the field is quite varied and can include the following potential exposures:

Asbestos - The potential for exposure exceeding the PEL are considered to be minimal with proper engineering protocols. Precision, however, requires its supervisors to perform personal air monitoring and all employees to wear proper respiratory protection during during all asbestos abatement and removal projects. Negative exposure assessments are maintained on file.

Lead - The potential for exposure exceeding the PEL are considered to be minimal with proper engineering protocols. Precision, however, requires its supervisors to perform personal air monitoring and all employees to wear proper respiratory protection during during all lead based paint abatement and removal projects. Negative exposure assessments are maintained on file.

Silica - The potential for exposure exceeding the PEL are considered to be minimal with proper engineering protocols. Negative exposure assessments are maintained on file.

Mold - There are no established PELs for microbial mitigation and exposures are considered to be minimal with proper engineering protocols. Precision, however, requires its supervisors and employees to wear proper respiratory protection during all microbial mitigation projects.

Unique situations or projects such as potential exposure to acutely toxic or carcinogenic materials or work activities in confined or poorly ventilated locations as determined by the Project Managers or Program Administrator will be evaluated and monitored on a case by case basis. These situations or projects are not the norm but may require respirators with greater protection factors.

Section 7

Asbestos Abatement Program

1.0 PURPOSE

To establish basic safe work practices and procedures for the abatement of asbestos containing materials (ACM) at all asbestos abatement jobsites where work is performed by Precision Environmental Company or Precision ProCUT employees.

2.0 APPLICATION

This procedure shall be followed on all Precision Environmental Company jobsites where asbestos abatement is performed by Precision Environmental or Precision ProCUT.

Compliance with local laws and regulations is mandatory. Where the customer's procedures are more protective than OSHA or local requirements, Precision Environmental will comply with the more protective requirements.

3.0 RESPONSIBILITY

The company Safety Director is solely responsible for all facets of this program and has full authority to make necessary decisions to ensure the success of this program. The Safety Director will develop written detailed instructions covering each of the basic elements in this program, and is the sole person authorized to amend these instructions. This company has authorized the Safety Director to halt any operation of the company where there is danger of serious personal injury.

4.0 DEFINITIONS

Amended Water Water containing a wetting agent or surfactant.

Asbestos The term asbestos includes chrysotile, amosite, crocidolite, tremolite, anthophyllite, and actinolite.

Asbestos Control Area An area where asbestos removal operations are performed which is isolated by physical boundaries to prevent the spread of asbestos dust, fibers, or debris.

Area Monitoring Sampling of asbestos fiber concentrations within the asbestos control area which is representative of the airborne concentrations of asbestos fibers, which may reach the breathing zone (12" of the nose/mouth).

Abatement Procedures to control fiber release from spray or trowel applied asbestos containing building materials. Includes removal only.

Airlock A system for permitting entrance or exit without permitting air movement between a contaminated area and an uncontaminated area, typically consisting of two curtained doorways at least 6 feet apart.

Air Monitoring The process of measuring the fiber content of a specific volume of air in a stated period of time. (Includes personnel and area monitoring).

Asbestos Containing Materials (ACM) Includes any existing construction material within the facility which contains > 1% asbestos.

Asbestos Workers Any workers involved in the disturbance or removal of existing asbestos materials.

Authorized Visitor The building owner, the building owner's representative or a representative of any regulatory or other agency having jurisdiction over the project.

Barrier Polyethylene sheeting which is used to separate contaminated work areas from uncontaminated areas by applying the sheeting to walls, floors and other structures.

Class I Asbestos Work Work activities involving the removal of Thermal System Insulation (TSI) and surfacing Asbestos Containing Material (ACM) and Presumed Asbestos Containing Material (PACM).

Class II Asbestos Work Work activities involving the removal of ACM, which is not thermal system insulation, or surfacing material. Includes but is not limited to, the removal of asbestos containing wallboard, floor tile and sheeting, roofing and siding shingles, and construction mastics.

Class III Asbestos Work Repair and maintenance operations, where "ACM", including thermal system insulation and surfacing material, is likely to be disturbed.

Class IV Asbestos Work Maintenance and custodial activities during which employees contact ACM and PACM and activities to clean up waste and debris containing ACM and PACM.

Clean Room An uncontaminated area or room, which is part of the worker decontamination enclosure system, which provisions for storage of workers' street clothes and protection equipment.

Competent Person One who is capable of identifying existing asbestos hazards in the work place and selecting the appropriate control strategy for asbestos exposure and who has the authority to take prompt corrective measures to eliminate them. For Class I and Class II work, one who is specially trained in a training course which meets EPA's requirements, and for Class III and IV work, one who is trained in accordance with EPA requirements for maintenance and custodial staff.

Contaminated Material Shall mean an area of material containing asbestos or coated with asbestos.

Disposal The transportation and final disposal of asbestos containing materials to an approved disposal site, in accordance with the Federal, State and Local Regulations.

Decontamination System A series of connected rooms, with curtained doorways between any two adjacent rooms, for the decontamination of workers or of materials and equipment. A

decontamination enclosure system always contains at least one airlock.

Encapsulant A liquid sealant material which is applied to asbestos containing material or asbestos contaminated material to limit the possible release of asbestos fibers into the ambient air. The encapsulant may be a penetrating type or a bridging type. The penetrating type moves into the asbestos material and bind the fibers together, while a bridging type covers over the surface of the asbestos and encloses the fibers.

Encapsulation All specified procedures necessary to coat asbestos-containing or asbestos-contaminated materials with an encapsulant to control the possible release of asbestos fibers into the ambient air.

Equipment Room A contaminated area or room, which is part of the worker decontamination enclosure system, with provision for storage of contaminated clothing and equipment.

Holding Area A chamber between the washroom and an uncontaminated area in the equipment decontamination enclosure system. The holding area comprises an airlock.

HEPA Filter Equipment High efficiency particulate air filtered vacuuming equipment with a filter system capable of collecting and retaining asbestos fibers. Filters shall be of 99.97 percent efficiency for retaining fibers of 0.3 microns in diameter or larger.

HEPA Filter A high efficiency particulate air (HEPA) filter capable of trapping and retaining 99.97% of asbestos particles greater than 0.3 microns in diameter.

Initial Exposure Assessment Initial monitoring performed at the initiation of each asbestos job to accurately determine the airborne concentrations of asbestos to which employees may be exposed.

Isolation Shall mean the act of partitioning off or sealing an area containing asbestos from the adjacent environment.

Medical Examinations Before exposure to airborne asbestos fibers, provide workers with a comprehensive medical examination as required by 29 CFR 1926.1101 and 1910.134. The same medical examination shall be given on an annual basis to employees engaged in an occupation involving asbestos fibers and within 30 calendar days before or after the termination of employment in such occupation.

Negative Air Machine A filtration system which utilizes a series of air filters in combination with an exhaust fan to reduce the level of airborne asbestos in a work area. The final filter in a negative air filtration unit should be a HEPA filter with an efficiency of no less than 99.97% of particles greater than 0.3 microns in diameter.

Negative Initial Exposure Assessment Demonstration by the employer that initial exposure assessments indicate that employee exposure during an operation is expected to be consistently below the PELs.

Permissible Exposure Limit (PEL) The permitted employee exposure level based on an 8 hour time-weighted average (TWA). The PEL for asbestos is 0.1 fiber per cubic centimeter of air TWA (8).

Personal Monitoring Sampling of asbestos fiber concentrations within the breathing zone of an employee.

Regulated or Control Areas A controlled area where all Class I, II and III asbestos work or other asbestos operations, which can or may exceed the PEL, must be performed. Regulated areas must be demarcated and have access limited to authorized persons only.

Removal Shall mean the dismantling and disposal of existing materials, components, equipment, and utilities. Removed items shall be handled, prepared for storage, transported to storage areas, and disposed of as specified.

Shower Room A room between the clean room and the equipment room in the worker decontamination enclosure system, with hot and cold or warm running water and suitably arranged for complete showering during decontamination. The shower room comprises an airlock between contaminated and clean areas. Portable showers shall be used at all locations unless noted otherwise specified.

Time Weighted Average The TWA is an 8-hour time weighted average airborne concentration of particles per volume of air. The Permissible Exposure Limit is 0.1 fiber/cubic centimeter as an 8-hour TWA as set forth in 29 CFR 1926.1101.

Wet Cleaning The process of eliminating asbestos contamination from building surfaces and objects by using cloths, mops, or other cleaning tools which have been dampened with water, and by contaminated waste.

Work Area Asbestos Removal Work Area, area in which asbestos removal will be done. The area which is designated for the containment of the asbestos material.

5:0 PROCEDURES

5.1 Pre-Job

5.1.1 Asbestos abatement projects mandate a very thorough and consistent tracking system from the time of award to the project completion.

5.1.2 Notifications to the Ohio Department of Health, Local Air Quality District, and Ohio Environmental Protection Agency must first be generated. The local fire department may need to be informed of a change in the fire protection system, if applicable, and the local police and emergency medical services may also need to be informed of the project. All notifications should be sent certified mail in order to assure they were received. Asbestos abatement conducted outside the State of Ohio shall comply with all applicable local and state notifications.

- 5.1.3 The estimator and project manager shall review specifications, drawings and the conditions at the job site for "hazards" or unusual conditions that may exist. An Initial Exposure Assessment should be also be utilized to evaluate potential asbestos exposure.
- 5.1.4 Various projects may require additional paperwork including shop drawings, work area plans, schedules, storage area plans, fire and safety evaluation plan, worker's health and safety training programs including respiratory protection, and temporary electrical or temporary HVAC system control. All of these requirements will be addressed by Precision Environmental, as needed for the project.
- 5.1.5 Copies of Supervisor and worker qualifications, certifications, training and medical reports showing the employee's ability to perform the assignment and wear respiratory protection shall be available on site and/or furnished to the owner's representative.
- 5.1.6 During mobilization all projects shall have emergency telephone numbers and location of emergency services posted. As required by OSHA, personnel trained in First Aid shall be available on the jobsite. All MSDS data sheets shall be available from the Supervisor per requirements of the OSHA's Hazard Communications requirements.
- 5.1.7 Exposure Assessments
- **Initial** At the start of any work operations, an Initial Exposure Assessment must be performed. The purpose of an initial exposure assessment is to determine expected exposures that may be encountered during asbestos operations. The assessment must be performed by a competent person. An initial assessment will take into consideration monitoring results and all observations and information that may indicate employee exposure. Prior to conducting the initial assessment, and until it is documented that employees are not exposed at or above the PEL, or a negative exposure assessment has been made, it will be presumed that workers will be exposed above the TWA. Copies of initial exposure assessments shall be submitted to the owner's representative and maintained at the project location as required.
 - **Negative** Employee exposure may also be demonstrated to be below the PEL by a Negative Exposure Assessment. Monitoring data from projects within twelve months of the current project may be used. The projects must closely resemble the processes, types of material, control methods, work practices, and environmental conditions existing on the current project. Personnel training and experience must also be similar. The data must show that there is a high degree of certainty that employee exposures will not exceed the TWA and excursion limit.

5.2 Full Containment ACM Removal

During any removal of friable asbestos containing material (ACM), it is imperative the proper methods and procedures are selected. Under normal conditions, some non-friable materials containing asbestos would not be considered hazardous; however, this material will release airborne concentrations of asbestos fibers during demolition and removal and therefore shall be handled in accordance with removal and disposal procedures as specified herein. The removal of friable ACM requires specialized techniques to isolate the work area from the outer environment. One of the most commonly used techniques to abate these areas is the **Full Containment** method.

Work Area Preparation

- 5.2.1 The first step in full containment procedures involve the isolation of the project area. Precision Environmental shall post caution signs meeting the specifications of OSHA 29 CFR 1926.1101 at locations and approaches to a location where airborne concentrations of asbestos may exceed ambient background levels. Signs will be posted at a distance sufficiently far enough away from the work area to permit the employee/public to read the sign and take the necessary protective measures to avoid exposure. Additional signs may be posted as necessary following construction of work area enclosure barriers. Warning signs shall bear the following information:

**DANGER
ASBESTOS
CANCER AND LUNG DISEASE HAZARD
AUTHORIZED PERSONNEL ONLY
RESPIRATORS AND PROTECTIVE CLOTHING
REQUIRED IN THIS AREA**

- 5.2.2 Labels will be affixed to all containers containing asbestos including waste containers. Labels will be used in accordance with OSHA's Hazard Communication Standard and will contain the following information:

**DANGER
CONTAINS ASBESTOS FIBERS
AVOID CREATING DUST
CANCER AND LUNG DISEASE HAZARD**

Precision Environmental will notify all employers of employees who will be performing work within or adjacent to areas of asbestos abatement operations of the presence, location and quantity of ACM or PACM. Notification shall be in writing or personal communication.

- 5.2.3 Precision Environmental shall shut down and lockout electrical power to all work areas. Temporary power and lighting shall be installed in compliance with all applicable electrical code requirements and OSHA requirements for temporary electrical systems.

- 5.2.4 Precision Environmental shall shut down and lockout all heating, ventilation and air conditioning systems (HVAC) components that are in supply or pass through the work area. (Note: Interiors of existing duct work may require decontamination). Seal all intake and exhaust vents in the area with tape and 6-mil polyethylene. Also seal any seams in system components that pass through the work area. Removal all HVAC system filters and place in labeled 6 mil polyethylene bags for staging and eventual disposal as asbestos contaminated waste.
- 5.2.5 Precision Environmental shall provide sanitary facilities for abatement personnel outside of the enclosed work area and maintain them in a clean and sanitary condition throughout the project.
- 5.2.6 Precision Environmental shall preclean all moveable objects within the work area using a HEPA filtered vacuum and/or wet cleaning methods as appropriate. After cleaning, these objects shall be removed from the work area and carefully stored in an uncontaminated location. Drapes, upholstered furniture and other fabric items shall be cleaned as asbestos contaminated items utilizing HEPA vacuum techniques.
- 5.2.7 Precision Environmental shall preclean all fixed objects in the work area using HEPA filtered vacuums and/or wet cleaning techniques as appropriate. Careful attention must be paid to machinery behind grills or gratings where access may be difficult but contamination significant. Attention shall be paid to all wall, floor and ceiling penetrations behind fixed items. After precleaning fixed objects will be enclosed in a double layer of 4 mil polyethylene sheeting and seal securely in place with tape. Control panels, gauges, etc. in work area may require owner access during abatement. These shall be designated and enclosures constructed with access flaps sealed with waterproof tape.
- 5.2.8 Precision Environmental shall seal off all windows, doorways, elevator openings, corridor entrances, drains, ducts, grills, grates, diffuses, skylights and any other openings between the work area and uncontaminated areas outside of the work area with 4 mil polyethylene sheeting and tape.
- 5.2.9 Precision Environmental shall cover floors with two layers of 6-mil (minimum) sheeting. Additional layer(s) of sheeting shall be utilized as drop cloth(s) to aid in the cleanup of bulk materials. The layers of drop cloth plastic shall be installed so that they can be removed independently from the first two layers installed.
- 5.2.10 Plastic shall be sized to minimize seams. If the floor area necessitates seams, those on successive layers of sheeting shall be staggered to reduce the potential for water to penetrate to the flooring material. A distance of at least six feet between seams is sufficient. No seams will be located at any wall/floor joints. Floor sheeting shall extend at least 12" up the sidewalls of the work area.

- 5.2.11 Sheeting shall be installed in a fashion so as to prevent slips between successive layers of material. (Vinyl sheeting may be used for improved traction on floors) Where stairs or ramps are covered with plastic, 3/4" exterior grade plywood treads securely held in place will be provided.
- 5.2.12 All walls in the work area will be covered with polyethylene sheeting. Walls that are non-porous and will not be damaged by water, surfactant, encapsulant do not necessarily need protection. They can be decontaminated using HEPA vacuums and wet cleaning techniques. Walls with mortar joints (e.g. tile) are considered porous. In addition, openings through these walls to uncontaminated areas of the building must be sealed as described previously. Walls shall be covered with two layers of 4-mil polyethylene sheeting. Wall sheeting shall overlap floor sheeting by at least 12 inches beyond the wall/floor joint to provide a better seal against water damage and for negative pressure. Wall sheeting shall be secured adequately to prevent it from falling away from walls. This will require additional support/attachment when negative pressure ventilation is utilized. The inner most layer of polyethylene (farthest from the building surface) shall be installed as a "drop cloth". It shall be installed such that it can be removed independently from the outer most layer of polyethylene in conjunction with the layer of floor drop cloth.

Decontamination Center

- 5.2.13 Worker decontamination enclosure systems shall be provided at all locations where workers will enter or exit the work area. One system at a single location is preferred, these systems may consist of existing rooms outside of the work area, if layout is appropriate, that can be enclosed in plastic sheeting and are accessible from the work area. When this situation does not exist enclosure systems may be constructed out of metal, wood or plastic support as appropriate.
- 5.2.14 The worker decontamination enclosure system shall consist of at least a clean room, a shower room and an equipment room each separate from each other and from the work area by air locks. Entry to and exit from all airlock and decontamination enclosure system chambers shall be through curtained doorways consisting of two sheets of overlapping polyethylene sheeting. One sheet shall be secured at the top and left side, the other sheet at the top and right side. Both sets shall have weights attached to the bottom to insure that they hang straight and maintain a seal over the doorway when not in use.
- 5.2.15 Access between any rooms in the decontamination enclosure system shall be through an airlock with at least three feet separating each curtained doorway. Pathways into (from clean to contaminated) and out from (contaminated to clean) the work area shall be clearly designated.
- 5.2.16 The clean room shall be sized to adequately accommodate the work crew. Benches shall be provided as well as hooks for hanging up street clothes. Clean work clothes, clean disposable clothing, replacement filters for respirators, towels and other necessary items will be provided in adequate supply at the clean room. A

location for posting shall also be provided in this area. Lighting, heat and electricity shall be provided as necessary for comfort.

- 5.2.17 The shower room shall contain one or more showers as necessary to adequately accommodate workers. Each showerhead shall be supplied with hot and cold water adjustable at the tap. The shower enclosure will be constructed to ensure against leakage of any kind. Shower water will be drained, collected and filtered through a system with at least 0.5 - 1.0 micron particle size collection capability.
- 5.2.18 The equipment room shall be used for storage of equipment and tools at the end of a shift after they have been decontaminated using a HEPA filtered vacuum and/or wet cleaning techniques as appropriate. Replacement filters (in sealed containers until used) for HEPA vacuums and negative pressure ventilation equipment. Extra tools, containers of surfactant and other materials and equipment that may be required during the abatement may also be stored here as needed. A dry lined drum with a labeled 6-mil polyethylene bag for collection of disposable clothing shall be stored in this room. Contaminated footwear (e.g. rubber boots, other reusable footwear) shall be stored in this area for reuse the following workday.

Work Area

- 5.2.19 Emergency exits shall be established and clearly marked with duct tape, arrows or other effective designations to permit easy location from anywhere within the work area. They shall be secured to prevent access from uncontaminated areas and still permit emergency exiting. These exits shall be properly sealed with polyethylene sheeting, which can be cut to permit egress if needed. These exits may be the worker decontamination enclosure, the waste pass-out airlock and/or other alternative exits satisfactory to fire officials.
- 5.2.20 The contaminated work area shall be separated from uncontaminated, occupied areas of the building by the construction of airtight barriers. Walls shall be constructed of wood or metal framing to support barriers in all openings larger than 4' x 8'. A sheeting material (plywood, drywall) of at least 3/8" thickness shall be applied to work side of barrier. Cover both sides of partition with a double layer of 6-mil polyethylene sheeting with staggered joints and seal in place. Caulk edges of partition at floor, ceiling, walls and fixtures to form an airtight seal.
- 5.2.21 Following completion of the construction of all polyethylene barriers and decontamination system enclosures, allow overnight settling to insure that barriers will remain intact and secured to walls and fixtures before beginning actual abatement activities.
- 5.2.22 All polyethylene barriers inside the work place, in the worker decontamination enclosure system, in the waste container pass-out airlock and at partitions constructed to isolate the work area from occupied areas shall be inspected at least twice daily, prior to the start of each day's abatement activities and following the completion of the day's abatement activities. Smoke tubes shall be used to test the effectiveness of the barrier system as required.

- 5.2.23 At any time during the abatement activities after barriers have been erected, if visible material is observed outside of the work area or if damage occurs to barriers, work shall immediately stop, repairs be made to barriers, and debris/residue cleaned up using appropriate HEPA vacuuming and wet mopping procedures.
- 5.2.24 If air samples collected outside of the work area during abatement activities indicate airborne fiber concentrations greater than 0.01 f/cc or pre-measured background levels (whichever is lower) work shall immediately stop for inspection and repair of barriers. Cleanup of surfaces outside of the work area using HEPA vacuums or wet cleaning techniques may be necessary.
- 5.2.25 Precision Environmental Company shall install and initiate operation of negative pressure ventilation equipment as needed to provide one air change in the work area every 15 minutes. Openings made in the enclosure system to accommodate these units shall be made airtight with tape and/or caulking as needed. If more than one unit is installed, they should be turned on one at a time, checking the integrity of wall barriers for secure attachment and need for additional reinforcement. Insure that adequate power supply is available to satisfy the requirements of the ventilating units. Negative pressure ventilation units shall be exhausted to the outside of the building. They shall not be exhausted into occupied areas of the building. Twelve-inch extension ducting shall be used to reach from the work area to the outside when required. Careful installation, air monitoring and daily inspections shall be done to insure that the ducting does not release fibers into uncontaminated building areas.

ACM Removal Procedure

- 5.2.26 Wet all asbestos containing material with an amended water solution using equipment capable of providing a fine spray mist; in order to reduce airborne fiber concentrations when the material is disturbed. Do not allow excessive water to accumulate in the work area. Maintain a high humidity in the work area by misting or spraying to assist in fiber settling and reduce airborne concentrations. Wetting procedures are not equally effective on all types of asbestos containing materials but shall none-the-less be used in all cases.
- 5.2.27 Saturated asbestos containing material shall be removed in manageable sections. Removed material will be containerized before moving to a new location for continuance of work. Surrounding areas shall be periodically sprayed and maintained in a wet condition until visible material is cleaned up.
- 5.2.28 Material removed from building structures or components shall not be dropped or thrown to the floor. Material should be removed as intact sections or components whenever possible and carefully lowered to the floor. If this cannot be done for materials greater than 50 feet above the floor, a dust-tight chute shall be constructed to transport the material to containers on the floor or the material may be containerized at elevated levels (e.g. on scaffolds) and carefully lowered to the

ground by mechanical means.

- 5.2.29 For materials between 15 and 50 feet above the ground they may be containerized at elevated levels or dropped onto inclined chutes or scaffolding for subsequent collection and containerization.
- 5.2.30 Containers shall be sealed when full. Bags shall not be overfilled. ACM shall be adequately wet before sealing containers. They should be securely sealed to prevent accidental opening and leakage by tying tops of bags in an overhead bow or by taping in gooseneck fashion. (Bags may be placed in drums for staging and transportation to the landfill. Bags shall be decontaminated on exterior surfaces by wet cleaning and HEPA vacuuming before being placed in clean drums and sealed with locking ring tops).
- 5.2.31 Large components removed intact may be wrapped in 2 layers of 6-mil polyethylene sheeting secured with tape for transport to the landfill. Asbestos containing waste with sharp-edged components (e.g. nails, screws, metal lathe, tin sheeting) will tear polyethylene bags and sheeting and shall be placed into drums for disposal.
- 5.2.32 After completion of all stripping work, surfaces from which asbestos containing materials have been removed shall be wet brushed and sponged or cleaned by some equivalent method to remove all visible residue.
- 5.2.33 Special circumstances (e.g. live electrical equipment) may prohibit the adequate use of wet methods to reduce fiber concentrations. For these situations dry removal may be required and requiring special permits from the relevant agencies.

Clean-up Procedures

- 5.2.34 Remove and containerize all visible accumulations of asbestos containing material and asbestos contaminated debris utilizing rubber dustpans and rubber squeegees to move material around. Special care shall be taken to minimize damage to floor sheeting. Remove "drop cloth" layer of polyethylene sheeting from walls and floor.
- 5.2.35 After removal of "drop cloth" layer of polyethylene the following will be in place: (1) two layers of polyethylene sheeting on the floor, (2) one layer of polyethylene sheeting on walls, and polyethylene layers(s) over equipment and wall or ceiling penetrations, and temporary barriers separating the work area from non-work areas.
- 5.2.36 All surfaces in the work area shall be cleaned using cloths, mops and sponges as appropriate. Excess water and gross wet debris shall be collected with a wet-dry shop vacuum. The vacuum shall be decontaminated prior to removal from the work area.
- 5.2.37 At this time, a thin coat of an encapsulating agent shall be applied to all surfaces in the work area to seal in non-visible residue including structural members, building

components, plastic sheeting on walls and floors, and coverings of non-removable items. If insulation or acoustical materials are to be reapplied to the abated area, be certain that the encapsulant selected will permit good adhesion to the substrate. Negative air machines may be temporarily turned off while spraying encapsulant, but must be turned on immediately at completion of spray operations.

- 5.2.38 After encapsulant has dried, the two layers of polyethylene sheeting should be removed from the floor and one layer from the walls. There should remain the following in place: polyethylene layer(s) over equipment, wall and ceiling penetrations, temporary barriers separating work area from non-work areas, decontamination units, and negative pressure ventilation units.
- 5.2.39 Tools and equipment should be HEPA vacuumed, wet cleaned and removed from the work area during the cleaning phase when they will no longer be needed to perform scheduled tasks. Scaffolds, ladders and temporary lighting shall remain in the work area to facilitate final visual inspection.
- 5.2.40 Inspect the work area for visible residue. If any accumulation of residue is observed, it will be assumed to be asbestos and the cleaning cycle repeated. Visual inspection shall not be performed until all surfaces are dry.
- 5.2.41 Following the satisfactory completion of aggressive clearance air monitoring, the remaining barriers may be removed and properly disposed of. A final visual inspection by the Precision and/or owner's representative shall insure that no contamination remains in the work area.

5.3 Glovebag Procedures

The start of each project requires a project layout and quality control format. The designated work area is secured by means of asbestos warning tape and signs. The information provided by the warning signs shall clearly acknowledge the health and safety hazards to potential entrants arriving at the project site. The existing (HVAC) servicing the project area shall be isolated or shutdown. Polyethylene sheeting shall be placed on the floor beneath the work area.

When these phases are completed the project may proceed. The following will serve as a guideline for glovebag abatement projects:

- 5.3.1 Mix the surfactant with water in a sprayer type mechanism as per manufacturer's directions.
- 5.3.2 Have each employee put on an approved HEPA cartridge respirator and check the face-fit.
- 5.3.3 Have each employee put on a disposable full-body suit, remembering the hood goes over the respirator straps.
- 5.3.4 Check the pipe where the work will be performed. If it is damaged (broken

lagging, hanging, etc.), wrap the entire length of the pipe in polyethylene plastic and "candy stripe" it with duct tape. A common error when doing glovebag work is forgetting that loose pipe lagging several feet or even several yards away from the glovebag work may be jarred loose by the activity. This is one of the common causes of high airborne fiber concentrations during glovebag work. The other problem is failure to clean up debris on the floor and other surfaces which has accumulated and contains asbestos.

- 5.3.5 Slit the top of the glovebag open (if necessary) and cut down the sides to accommodate the size of the pipe (about two inches longer than the pipe diameter).
- 5.3.6 Place the necessary tools into the pouch located inside the glovebag. This will usually include the bone saw, utility knife, rags, scrub brush and wire cutters.
- 5.3.7 Place one strip of duct tape along the edge of the open top slit of the glovebag for reinforcement.
- 5.3.8 Place the glovebag around the section of pipe to be worked on and staple the top together through the reinforcing duct tape. Staple at intervals of approximately one inch. Next, fold the stapled top flap back and tape it down with a strip of duct tape. This should provide an adequate seal along the top. Next, duct tape the ends of the glovebag to the pipe itself, previously covered with plastic or duct tape.
- 5.3.9 Insert the wand from the water sprayer through the sleeve. Using duct tape, tape and seal sleeve tightly around the wand to prevent air leakage.
- 5.3.10 One person places his hands into the long-sleeved gloves while the second person directs the water spray at the work.
- 5.3.11 Once the ends are cut, the section of insulation should be slit from end to end using the utility knife. The cut should be made along the bottom of the pipe and water continuously supplied. Again, care should be taken when using the knife not to puncture the bag. Some insulation may have wires to be clipped as well.
- 5.3.12 Spray all tools with water inside the bag and place back into pouch.
- 5.3.13 The insulation can now be lifted off the pipe and gently placed in the bottom of the bag.
- 5.3.14 Using the scrub brush, rags and water, scrub and wipe down the exposed pipe inside the glovebag.
- 5.3.15 Remove the water wand from the water sleeve and attach the small nozzle from the HEPA filtered vacuum. Turn on the vacuum only briefly to collapse the bag.
- 5.3.16 Remove the vacuum nozzle and twist the water sleeve closed and seal with duct tape.

- 5.3.17 From outside the bag, pull the tool pouch away from the bag and twist it to separate it from the bag. Place duct tape over the twisted portion and then cut the tool bag from the glovebag without cleaning. Alternatively, the tool pouch with the tools can be placed in a bucket of water, opened underwater, and the tools cleaned and dried without releasing asbestos into the air.
- 5.3.18 With the removed insulation in the bottom of the bag, twist the bag several times and tape it to keep the material in the bottom during removal of the glovebag from the pipe.
- 5.3.19 Remove the tape and open the top of the glovebag and fold it down into the disposal bag.
- 5.3.20 Remove the disposable suits and place these into the bag with the waste.
- 5.3.21 Twist the top of the bag closed, fold this over, and seal with duct tape. Label the bag with a warning label.
- 5.4 Removal of Resilient Floor Tile and Floor Tile Mastic

Floor Tile

- 5.4.1 Place critical barriers over all openings to the regulated area.
- 5.4.2 Tiles in areas exposed to heavy foot traffic will usually adhere the tightest. Therefore, select those areas exposed to the least amount of foot traffic for starting removal.
- 5.4.3 Individual tiles should be removed as a complete unit in as large a piece as possible. Water with "wetting agent" (dishwashing detergent or commercially prepared surfactant) may be used to soak tiles loose.
- 5.4.4 Continue loosening by prying tiles with a long-handled scraper and apply a mist of water as work progresses.
- 5.4.5 Removed materials should be placed in a heavy duty (6 mil) plastic bag for proper disposal.
- 5.4.6 HEPA vacuums shall be used to clean floors after abatement

Mastic

- 5.4.7 Place critical barriers over all openings to the regulated area and polyethylene sheeting 3 feet up all walls adjacent to mastic removal.
- 5.4.8 Apply mastic remover with the sprayer on a section of the mastic to be removed. Apply enough product so that during agitation you are working with material that has the consistency of motor oil.

- 5.4.9 Using the floor squeegee, push the liquefied mastic from one section to the next as removal progresses. Add additional mastic remover as needed to maintain the consistency of motor oil.
- 5.4.10 Soaking of the mastic should not be necessary. Follow the manufacturer's instructions as indicated. Immediate agitation with the course bristle broom will accelerate the removal of the mastic.
- 5.4.11 Using the absorbent, pick up the liquefied mastic and dispose of in accordance with Federal, State, County and Local regulations.
- 5.4.12 Mop and rinse all abated surfaces with 110°F water and deodorizing detergent.
- 5.5 Disposal Procedures
- 5.5.1 As the work progresses, to prevent exceeding available storage capacity on site, sealed and labeled containers of asbestos containing waste shall be removed and transported to the prearranged disposal location.
- 5.5.2 Disposal must occur at an authorized site in accordance with Federal, State and Local regulations.
- 5.5.3 All dump receipts, trip tickets, transportation manifests or other documentation of disposal shall be delivered to the building owner for his records. The manifest shall include the names and addresses of the building owner, Precision Environmental Company, job location, disposal site, the estimated quantity of the asbestos waste and the type of containers used. The form should be signed by the owner, Precision Environmental, and disposal site operator, as the possession of the material changes hands.
- 5.5.4 Once drums, bags and wrapped components have been removed from the work area, they shall be loaded into an enclosed truck for transportation. The enclosed cargo area of the truck shall be free from debris and lined with 6 mil polyethylene sheeting to prevent contamination from leaking or spilled containers. Floor sheeting shall be installed first and extended up the sidewalls. Wall sheeting shall be overlapped and taped into place.
- 5.5.5 Drums shall be placed on level surfaces in the cargo area and packed tightly together to prevent shifting and tipping. Large structural components shall be secured to prevent shifting of bags.
- 5.5.6 Personnel loading asbestos containing waste shall be protected by disposable clothing, including head, body and foot protection and at a minimum, half-face piece, air-purifying, dual cartridge respirators equipped with HEPA filters.

- 5.5.7 Bags, Drums and components shall be inspected as they are off-loaded at the disposal site. Waste containers shall be placed on the ground at the disposal site; not pushed or thrown out of trucks.
- 5.5.8 Personnel off-loading containers at the disposal site shall wear protective equipment consisting of disposable clothing; including head, body and foot protection and at minimum, half-face piece, air-purifying, dual cartridge respirators equipped with HEPA filters.
- 5.5.9 Following the removal of all containerized waste, the truck cargo area shall be decontaminated using HEPA vacuums, and/or wet methods to meet the "no visible residue" criteria. Polyethylene sheeting shall be removed and discarded along with contaminated cleaning materials and protective clothing, in bags or drums at the disposal site.

Section 8

License, Worker's Compensation, Insurance

STATE OF OHIO
DEPARTMENT OF HEALTH

ASBESTOS HAZARD ABATEMENT CONTRACTOR LICENSE

Be it known that **Precision Environmental Company** is hereby licensed, having qualified as required by law in accordance with rules adopted by the Public Health Council relative to Asbestos Contractors.

In Witness whereof, I have subscribed my name and affixed the seal of the Department of Health State of Ohio on **February 07, 2011** in the city of Columbus.


License number: **AC1154**

Effective Until: **February 26, 2012**

In witness thereof _____



Karen F. Hughes
Acting Director
Ohio Department of Health



Ohio

Bureau of Workers' Compensation

30 W. Spring St.
Columbus, OH 43215

Certificate of Premium Payment

This certifies the employer listed below has paid into the Ohio State Insurance Fund as required by law. Therefore, the employer is entitled to the rights and benefits of the fund for the period specified. For more information, call 1-800-OHIOBWC.

This certificate must be conspicuously posted.


Policy No. and Employer

Period Specified Below

947659

01/01/2011 Thru 08/31/2011

PRECISION ENVIRONMENTAL COMPANY
5500 OLD BRECKSVILLE RD
INDEPENDENCE, OH 44131-1508



ohiobwc.com

Stephen Bucher
Administrator/CEO

You can reproduce this certificate as needed.

Ohio Bureau of Workers' Compensation

Required Posting

Effective Oct. 13, 2004, Section 4123.54 of the Ohio Revised Code requires notice of rebuttable presumption. Rebuttable presumption means an employee may dispute or prove untrue the presumption (or belief) that alcohol or a controlled substance not prescribed by the employee's physician is the proximate cause (main reason) of the work-related injury.

The burden of proof is on the employee to prove the presence of alcohol or a controlled substance was not the proximate cause of the work-related injury. An employee who tests positive or refuses to submit to chemical testing may be disqualified for compensation and benefits under the Workers' Compensation Act.

Ohio

Bureau of Workers' Compensation

You must post this language with the certificate of premium payment.



CERTIFICATE OF LIABILITY INSURANCE

OP ID: J5

DATE (MM/DD/YYYY)

02/15/11

THIS CERTIFICATE IS ISSUED AS A MATTER OF INFORMATION ONLY AND CONFERS NO RIGHTS UPON THE CERTIFICATE HOLDER. THIS CERTIFICATE DOES NOT AFFIRMATIVELY OR NEGATIVELY AMEND, EXTEND OR ALTER THE COVERAGE AFFORDED BY THE POLICIES BELOW. THIS CERTIFICATE OF INSURANCE DOES NOT CONSTITUTE A CONTRACT BETWEEN THE ISSUING INSURER(S), AUTHORIZED REPRESENTATIVE OR PRODUCER, AND THE CERTIFICATE HOLDER.

IMPORTANT: If the certificate holder is an ADDITIONAL INSURED, the policy(ies) must be endorsed. If SUBROGATION IS WAIVED, subject to the terms and conditions of this policy, certain policies may require an endorsement. A statement on this certificate does not confer rights to the certificate holder in favor of such endorsement(s).

PRODUCER The Fedall Group P.O. Box 318003 5005 Rockside Road Independence, OH 44131-8003 Umberto P. Fedall	216-328-8080 216-328-8081	CONTACT NAME: PHONE (AC, No, Ext): FAX (AC, No): E-MAIL: ADDRESS: PRODUCER CUSTOMER ID#: PREC19
INSURED Precision Environmental Company The Precision Company 5500 Old Brecksville Road Independence, OH 44131	INSURER(S) AFFORDING COVERAGE	
	INSURER A: Zurich American Ins. Co.	16535
	INSURER B: Steadfast Insurance Company	26387
	INSURER C:	
	INSURER D:	
	INSURER E:	
	INSURER F:	

COVERAGES **CERTIFICATE NUMBER:** **REVISION NUMBER:**

THIS IS TO CERTIFY THAT THE POLICIES OF INSURANCE LISTED BELOW HAVE BEEN ISSUED TO THE INSURED NAMED ABOVE FOR THE POLICY PERIOD INDICATED. NOTWITHSTANDING ANY REQUIREMENT, TERM OR CONDITION OF ANY CONTRACT OR OTHER DOCUMENT WITH RESPECT TO WHICH THIS CERTIFICATE MAY BE ISSUED OR MAY PERTAIN, THE INSURANCE AFFORDED BY THE POLICIES DESCRIBED HEREIN IS SUBJECT TO ALL THE TERMS, EXCLUSIONS AND CONDITIONS OF SUCH POLICIES. LIMITS SHOWN MAY HAVE BEEN REDUCED BY PAID CLAIMS.

INSR. LIST	TYPE OF INSURANCE	ADDITIONAL INSURER	POLICY NUMBER	POLICY EFF. DATE (MM/DD/YYYY)	POLICY EXPI. DATE (MM/DD/YYYY)	LIMITS
A	<input checked="" type="checkbox"/> GENERAL LIABILITY <input checked="" type="checkbox"/> COMMERCIAL GENERAL LIABILITY <input type="checkbox"/> CLAIMS-MADE <input checked="" type="checkbox"/> OCCUR <input checked="" type="checkbox"/> Underground GEN'L AGGREGATE LIMIT APPLIES PER: <input type="checkbox"/> POLICY <input checked="" type="checkbox"/> PRO-PORT <input type="checkbox"/> LOC	X	GLO902564207	02/17/11	02/17/12	EACH OCCURRENCE \$ 1,000,000 DAMAGE TO RENTED PREMISES (Ea. occurrence) \$ 100,000 MED EXP (Any one person) \$ 10,000 PERSONAL & ADV INJURY \$ 1,000,000 GENERAL AGGREGATE \$ 1,000,000 PRODUCTS - COMP/OP AGG. \$ 1,000,000
	AUTOMOBILE LIABILITY <input type="checkbox"/> ANY AUTO <input type="checkbox"/> ALL OWNED AUTOS <input type="checkbox"/> SCHEDULED AUTOS <input type="checkbox"/> HIRED AUTOS <input type="checkbox"/> NON-OWNED AUTOS					COMBINED SINGLE LIMIT (Ea. accident) \$ BODILY INJURY (Per person) \$ BODILY INJURY (Per accident) \$ PROPERTY DAMAGE (Per accident) \$ \$ \$
B	<input checked="" type="checkbox"/> UMBRELLA LIAB <input checked="" type="checkbox"/> OCCUR <input type="checkbox"/> EXCESS LIAB <input type="checkbox"/> CLAIMS-MADE <input checked="" type="checkbox"/> DEDUCTIBLE <input checked="" type="checkbox"/> RETENTION \$ 10,000	X	SEO902564707	02/17/11	02/17/12	EACH OCCURRENCE \$ 14,000,000 AGGREGATE \$ 14,000,000 \$ \$
A	WORKERS COMPENSATION AND EMPLOYERS' LIABILITY <input type="checkbox"/> ANY PROPRIETOR/PARTNER/EXECUTIVE/OFFICER/MEMBER EXCLUDED? (Mandatory in NH) <input type="checkbox"/> Y/N <input type="checkbox"/> N/A If yes, describe under DESCRIPTION OF OPERATIONS below		GLO902564207 OHIO STOP GAP LIABILITY	02/17/11	02/17/12	<input checked="" type="checkbox"/> WC STATUTORY LIMITS <input type="checkbox"/> OTHER EL EACH ACCIDENT \$ 1,000,000 EL DISEASE - EA EMPLOYEE \$ 1,000,000 EL DISEASE - POLICY LIMIT \$ 1,000,000
A	<input checked="" type="checkbox"/> Contractual P&OH <input checked="" type="checkbox"/> Pollution Liab.		PEC654939401 INCL ASBESTOS & LEAD	02/17/11	02/17/12	Ea. Claim \$ 15,000,000 All Claims \$ 15,000,000

DESCRIPTION OF OPERATIONS / LOCATIONS / VEHICLES (Attach ACORD 101, Additional Remarks Schedule, if more space is required)
 Additional insured to be included, if necessary, per written contract

CERTIFICATE HOLDER	CANCELLATION
0000000	SHOULD ANY OF THE ABOVE DESCRIBED POLICIES BE CANCELLED BEFORE THE EXPIRATION DATE THEREOF, NOTICE WILL BE DELIVERED IN ACCORDANCE WITH THE POLICY PROVISIONS.
To Whom This May Concern	AUTHORIZED REPRESENTATIVE
	<i>Pat Cowan</i>

© 1988-2009 ACORD CORPORATION. All rights reserved.



CERTIFICATE OF LIABILITY INSURANCE

DATE (MM/DD/YYYY)
2/17/2011

THIS CERTIFICATE IS ISSUED AS A MATTER OF INFORMATION ONLY AND CONFERS NO RIGHTS UPON THE CERTIFICATE HOLDER. THIS CERTIFICATE DOES NOT AFFIRMATIVELY OR NEGATIVELY AMEND, EXTEND OR ALTER THE COVERAGE AFFORDED BY THE POLICIES BELOW. THIS CERTIFICATE OF INSURANCE DOES NOT CONSTITUTE A CONTRACT BETWEEN THE ISSUING INSURER(S), AUTHORIZED REPRESENTATIVE OR PRODUCER, AND THE CERTIFICATE HOLDER.

IMPORTANT: If the certificate holder is an ADDITIONAL INSURED, the policy(ies) must be endorsed. If SUBROGATION IS WAIVED, subject to the terms and conditions of the policy, certain policies may require an endorsement. A statement on this certificate does not confer rights to the certificate holder in lieu of such endorsements.

PRODUCER The Everts Tremaine Flicker Company 1100 Chester Ave. #300 Cleveland OH 44115 INSURED Precision Environmental Company The Precision Company 5500 Old Bracksville Road Independence OH 44131	CONTACT NAME: Diana Pahlner PHONE: (216) 621-7183 FAX: (216) 621-4759 ADDRESS: PRODUCER: 06000089 CUSTOMER: INSURER(S) AFFORDING COVERAGE: NAIC#: 14621 INSURER A: Motorists Mutual INSURER B: INSURER C: INSURER D: INSURER E:
--	--

COVERAGES	CERTIFICATE NUMBER: 2010 Precision Cert	REVISION NUMBER:
------------------	--	-------------------------

THIS IS TO CERTIFY THAT THE POLICIES OF INSURANCE LISTED BELOW HAVE BEEN ISSUED TO THE INSURED NAMED ABOVE FOR THE POLICY PERIOD INDICATED. NOTWITHSTANDING ANY REQUIREMENT, TERM OR CONDITION OF ANY CONTRACT OR OTHER DOCUMENT WITH RESPECT TO WHICH THIS CERTIFICATE MAY BE ISSUED OR MAY PERTAIN, THE INSURANCE AFFORDED BY THE POLICIES DESCRIBED HEREIN IS SUBJECT TO ALL THE TERMS, EXCLUSIONS AND CONDITIONS OF SUCH POLICIES. LIMITS SHOWN MAY HAVE BEEN REDUCED BY PAID CLAIMS.

INSR LTR	TYPE OF INSURANCE	ADJ. SUBR. INSR. RVD.	POLICY NUMBER	POLICY EFF. (MM/DD/YYYY)	POLICY EXP. (MM/DD/YYYY)	LIMITS
	GENERAL LIABILITY <input type="checkbox"/> COMMERCIAL GENERAL LIABILITY <input type="checkbox"/> CLAIMS-MADE <input type="checkbox"/> OCCUR <input type="checkbox"/> GENT. AGGREGATE LIMIT APPLIES PER: <input type="checkbox"/> POLICY <input type="checkbox"/> PER. <input type="checkbox"/> LOC					EACH OCCURRENCE \$ DAMAGE TO RENTED PREMISES (Per occurrence) \$ MED EXP. (Any one person) \$ PERSONAL & ADV INJURY \$ GENERAL AGGREGATE \$ PRODUCTS - COMP/OP AGG \$ \$
A	AUTOMOBILE LIABILITY <input checked="" type="checkbox"/> ANY AUTO <input type="checkbox"/> ALL OWNED AUTOS <input type="checkbox"/> SCHEDULED AUTOS <input type="checkbox"/> HIRED AUTOS <input type="checkbox"/> NON-OWNED AUTOS		3323289000	2/17/2011	2/17/2012	COMBINED SINGLE LIMIT (Per accident) \$ 1,000,000 BODILY INJURY (Per person) \$ BODILY INJURY (Per accident) \$ PROPERTY DAMAGE (Per accident) \$ Rental reimbursement 30 days \$ 30 Medical payments \$ 1,000
	<input type="checkbox"/> UMBRELLA LIAB <input type="checkbox"/> OCCUR <input type="checkbox"/> EXCESS LIAB <input type="checkbox"/> CLAIMS-MADE <input type="checkbox"/> DEDUCTIBLE <input type="checkbox"/> RETENTION \$					EACH OCCURRENCE \$ AGGREGATE \$ \$ \$
	WORKERS COMPENSATION AND EMPLOYERS' LIABILITY ANY PROPRIETOR/PARTNER/EXECUTIVE OFFICER/MEMBER EXCLUDED? (Mandatory in NY) <input type="checkbox"/> Y/N N/A If Yes, describe under DESCRIPTION OF OPERATIONS below					<input type="checkbox"/> WC STATE-TORY LIMITS <input type="checkbox"/> BOTH PER EL EACH ACCIDENT \$ EL DISEASE - EA EMPLOYEE \$ EL DISEASE - POLICY LIMIT \$

DESCRIPTION OF OPERATIONS / LOCATIONS / VEHICLES (Attach ACORD 107, Additional Remarks Schedule, if more space is required)
 Additional Insured to be included if necessary, per written contract

CERTIFICATE HOLDER To Whom This May Concern	CANCELLATION SHOULD ANY OF THE ABOVE DESCRIBED POLICIES BE CANCELLED BEFORE THE EXPIRATION DATE THEREOF, NOTICE WILL BE DELIVERED IN ACCORDANCE WITH THE POLICY PROVISIONS.
	AUTHORIZED REPRESENTATIVE J. Brickenden/DCF

Section 9

Product Data and Material Safety Data Sheets

PRODUCT DATA

PENEWET®

DESCRIPTION

Product No.: 6450 clear

Penewet is an ready-to-use, colorless wetting agent/surfactant solution incorporating advanced concepts in surface chemistry. It provides powerful wetting, penetrating and coalescing of asbestos containing materials (ACM) to permit handling and removal of these materials under damp, dust-free conditions. Penewet is a nonflammable water based nontoxic liquid which will not corrode aluminum components of spray equipment.

PROPERTIES

- Solids by Weight: 10 +/-2%
- Volatile: Water
- Average particle size: 0.2 microns
- Viscosity @ 77°F: 50-55 Krebs Units
- Weight per gallon @ 77°F: 8.8 lbs.
- Ionic nature: Non-ionic
- Flammability: Non-flammable
- Phosphate free?: Yes
- Surface tension: 31 dynes/cm.
- Coverage: 500 sq.ft./gal.
- Shelf Life: @ 77°F, 36 months minimum, (in original factory sealed containers).
- Odor: Applied indoors, virtually odorless.
- Packaged: 5, and 55 gallon containers

APPLICATION INFORMATION

SURFACTANT/WETTING AGENT: Penewet is a ready-to-use formulation. Sealing microscopic residual fibers after asbestos removal is mandatory on every project. Prior to post-removal air monitoring, apply one coat to all exposed surfaces prior to post removal air monitoring.

PULLDOWN BY MISTING: Pulldown by misting the contaminated air is an effective technique prior to post removal air monitoring. To pull down free-floating asbestos fibers effectively, stand in the center of the room and hold the spray gun as close to the ceiling as possible. A mist should be sprayed parallel to the ceiling in every direction or in a circle. Apply one coat to the polyethylene walls and floor.

(Over)



FIBERLOCK TECHNOLOGIES, INC.

150 Dascomb Road
Andover, MA 01830 U.S.A.
Toll Free: (800) 342-3755
Tel.: (978) 623-9987 Fax: (978) 475-6205
www.fiberlock.com

APPLICATION PROCEDURES FOR PENEWET ASBESTOS WETTING COMPOUND

PREPARATION

Prior to application, stir thoroughly to achieve a uniform consistency. Penewet is pre-mixed, water addition is not necessary.

APPLICATION EQUIPMENT

Professional models of all brands of spray equipment can be used to successfully apply Penewet. Use the settings below when applying Penewet:

Pressure: 2500-2700 psi
Hose length: 100 feet
Hose diameter: 1/4 inch
Tip size: .015 - .027 (orifice size)
Fan size: 12 inches

CLEAN UP

Tools and drippings should be cleaned with soap and water before coating dries.

SHIPPING AND STORAGE INFORMATION

Shelf Life: 3 years in sealed containers

Storage Temperature: Keep from freezing. Store in a dry place at temperatures between 40°F - 100°F

Flash Point: None.

**KEEP OUT OF REACH OF CHILDREN
FOR PROFESSIONAL USE ONLY
KEEP FROM FREEZING**

Cautions: Approved respirators must be used to prevent inhalation of asbestos fibers that may be present in the air. Protective clothing should be worn. Tools and drippage should be cleaned immediately with clean, soapy water before the coating dries. Careful consideration should be given to all Environmental Protection Agency (EPA), OSHA and state regulations in effect at the time of application of Penewet. The EPA, through the Office of Pesticides and Toxic Substances, has issued reports headed "Guidance for Controlling Friable Asbestos Containing Materials in Buildings," EPA 560/S 45-024, June 1985, and "Managing Asbestos in Place, A Building Owner's Guide to Operations and Maintenance Programs for Asbestos Containing Materials," 201-2003, July 1990, containing the proper data, cautions, and procedures for asbestos control. Copies are available from the Environmental Assistance Division, TS-799, TSCA Assistance Information Service, U.S. EPA, 401 M Street SW, Washington, DC 20460, (202) 554-1404.

Keep from freezing. Do not store at temperatures above 100°F.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Fibertek Technologies, Inc., nor our agents shall be responsible for the use or results of use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of Penewet for each specific project and for the health and safety of personnel working in the area.

MATERIAL SAFETY DATA SHEET

(Essentially similar to OSHA form 174, Sept. 1985 - For Compliance with OSHA's Hazard Communication Standard, 29CFR 1910.1200)

Section I - Product Identity:

Penewet® (6450)

Manufacturer's Name:
Fiberlock Technologies, Inc.
150 Dascomb Road
Andover, MA 01810

Date of Preparation: September 15, 2002
Information Telephone Number: (978) 623-9987
Emergency Telephone Numbers:
Weekdays: (978) 623-9987
After hours, weekends & holidays: (978) 887-5926, or
"CHEM-TEL" Emergency Contact Number: (800) 255-3924

Section II - Hazardous Ingredients/Identity Information

HAZARDOUS COMPONENT	COMMON NAME(S)	%	CAS NO.	OSHA PEL	OR	ACGIH TLV
---------------------	----------------	---	---------	----------	----	-----------

None per the limits for reporting set forth in 29CFR 1910.1200

Section III - Physical/Chemical Characteristics

Boiling Points of Major Constituent (Water)	212°F	Specific Gravity (H ₂ O=1) Wgt./gal.	1.01
Vapor Pressure (mm Hg) @ 68°F	ND	Melting Point Water (Ice)	32°F
Vapor Density (AIR=1) Heavier Lighter	ND	Evaporation Rate (Butyl Acetate=1)	Slower
Solubility in Water	Complete	Appearance: Odor:	Clear solution Odorless

Section IV - Fire and Explosion Hazard Data (Nonflammable)

Flash Point: None	Flammable Limits: LEL: N/A UEL: N/A	DOT Hazard Class: Not Regulated	Marking: "Keep From Freezing"
----------------------	--	------------------------------------	----------------------------------

Special Firefighting Properties: N/A Unusual Fire Explosion: N/A

Section V - Reactivity Data

Hazardous Polymerization: Won't occur Stability: Stable Incompatibility: N/A
Hazardous Decomposition: N/A Conditions to Avoid: N/A

Section VI - Health Hazard Data; Toxicity Data

Route(s) of Entry: None for skin, inhalation and ingestion.
Carcinogenicity NTP: No IARC Monographs: No OSHA Regulated: No Signs/Symptoms: N/A
Health Hazards (Acute and Chronic): N/A Medical Conditions: N/A

EMERGENCY AND FIRST AID PROCEDURES: Eyes: Flush with water. Skin: Wash with soap/water. Remove contaminated clothing.
Ingestion: Induce vomiting. Seek immediate medical attention. Inhalation: Remove to fresh air.

SUPPLEMENTAL INFORMATION

To comply with New Jersey DOH Right-To-Know labeling law (N.J.A.C. 8:59 - 5.1 & 5.2)

CAS. No.:
7732-18-5
68431-39-5
64-02-8
Not Avail.*
Not Avail.*
Contents partially unknown

CHEMICAL INGREDIENTS:
Water
Alcohol ethoxylate
Tetrasodium EDTA
Alkoxylated linear alcohol
Hydroxyethyl cellulose

HMIS HAZARD RATING			
Health 1	Flammability 0	Reactivity 0	Personal Protection A
HAZARD INDEX: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe			
PERSONAL PROTECTION CODE			
A= Safety Classes			

Section VII: Precautions for Safe Handling and Use

IN CASE MATERIAL IS RELEASED OR SPILLED: Flush area with water. Mop up and hold for disposal.

WASTE DISPOSAL METHOD: Any method in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container sealed when not in use. Do not store at elevated temperatures.

OTHER PRECAUTIONS: Eye protection recommended.

Ventilation: N/A

Section VIII: Control Measures

RESPIRATORY PROTECTION: None needed

PROTECTIVE GLOVES: N/A

EYE PROTECTION: Use safety eyewear including side shields, face shields, or chemical splash goggles (ANSI Z-87.1 or approved equivalent).

OTHER PROTECTIVE EQUIPMENT: N/A

WORK HYGIENIC: N/A

PRODUCT DATA

FIBERSET™ PM

DESCRIPTION

Product No.: 7470 white, 7475 clear, 7480 blue

Fiberset PM is a pre-mixed "lockdown" sealing treatment for microscopic residual fibers present after removal of asbestos containing material (ACM). Fiberset PM is a ready-to-use, class "A" fire rated coating that provides a flexible barrier over residual fibers to insure final air clearance. Fiberset PM and Fiberset PT are the only UL® classified (#R13770) lockdowns accepted for fluted, cellular and corrugated deck assemblies. Fiberset PM is compatible with most leading brands of replacement fireproofing and flooring adhesives. Fiberset PM can also be used to penetrate asbestos contaminated soil in crawl spaces. Fiberset PM is a water based nontoxic coating which employs advanced 100% acrylic resin technology to extend the life expectancy of airless spray equipment.

UL Classification: ASTM E-119

UL Category: Encapsulant Materials



PROPERTIES

- Volatile: Water
- Average particle size: 0.2 microns
- Viscosity @ 77°F: 55-60 Krebs Units
- Weight per gallon @ 77°F: 8.5 lbs.
- Film Hardness: Excellent
- Film Flexibility: Excellent
- Impact Resistance: Excellent
- Water resistance of dry film: Excellent
- Bond Strength to concrete/steel: Excellent
- Coverage: not less than 500 sq. ft./gal. (as specified by UL)
- Flash point: Tag Closed Cup, Non-combustible water based product.
- Dry Time: 1 - 2 hours
- Shelf Life: @ 77°F, 36 months minimum, (in original factory sealed containers).
- Odor: virtually odorless.
- Finish: slight gloss
- Packaged: 5, and 55 gallon containers

APPLICATION INFORMATION

LOCKDOWN: Sealing microscopic residual fibers after asbestos removal is mandatory on every project. Prior to post-removal air monitoring, apply one coat to all exposed surfaces. Fiberset PM has been accepted as part of a UL Classified Fireproofing System for use with Retro-Guard® manufactured by W.R. Grace & Co., Conn.

PULLDOWN BY MISTING: Pulldown by misting the contaminated air is an effective technique prior to post removal air monitoring. To pull down free-floating asbestos fibers effectively, stand in the center of the room and hold the spray gun as close to the ceiling as possible. A mist should be sprayed parallel to the ceiling in every direction or in a circle. Apply one coat to the polyethylene walls and floor.

(Over)



FIBERLOCK TECHNOLOGIES, INC.

150 Dascomb Road
Andover, MA 01810 U.S.A.
Toll Free: (800) 342-3755
Tel.: (978) 623-9987 Fax: (978) 475-6205
www.fiberlock.com

APPLICATION PROCEDURES FOR FIBERSET PM

PREPARATION

Prior to application, stir thoroughly to achieve a uniform consistency. Fiberset PM is pre-mixed, water addition is not necessary.

APPLICATION EQUIPMENT

Professional models of all brands of spray equipment can be used to successfully apply Fiberset PM. Use the settings below when applying Fiberset PM:

Pressure: 2500-2700 psi
Hose length: 100 feet
Hose diameter: 1/4 inch
Tip size: .015 - .025 (orifice size)
Fan size: 12 inches

CLEAN UP

Tools and drippings should be cleaned with soap and water before coating dries.

SHIPPING AND STORAGE INFORMATION

Shelf Life: 3 years in sealed containers

Storage Temperature: Keep from freezing. Store in a dry place at temperatures between 40°F - 100°F

Flash Point: None.

Note: Fiberset PM is part of a UL Classified Fireproofing System for use with Classified types RG and RG1 cementitious mixtures manufactured by Zonolite Construction Products Division W.R. Grace & Co., Conn.

**KEEP OUT OF REACH OF CHILDREN
FOR PROFESSIONAL USE ONLY
KEEP FROM FREEZING**

Cautions: Approved respirators must be used to prevent inhalation of asbestos fibers that may be present in the air. Protective clothing should be worn. Tools and drippings should be cleaned immediately with clean, soapy water before the coating dries. Careful consideration should be given to all Environmental Protection Agency (EPA), OSHA and state regulations in effect at the time of application of Fiberset PM. The EPA, through the Office of Pesticides and Toxic Substances has issued reports headed "Guidance for Controlling Friable Asbestos-Containing Materials in Buildings," EPA 560/S 85-024, June 1985, and "Managing Asbestos in Place, A Building Owner's Guide to Operations and Maintenance Programs for Asbestos Containing Materials," 201-2003, July 1990, containing the proper data, cautions, and procedures for asbestos control. Copies are available from the Environmental Assistance Division, TS-799, TSCA Assistance Information Service, U.S. EPA, 401 M Street SW, Washington, DC 20460, (202) 554-1404.

Keep from freezing. Do not store at temperatures above 100°F.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Fiberset Technologies, Inc., nor our agents shall be responsible for the use or results of use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of Fiberset PM for each specific project and for the health and safety of personnel working in the area.

MATERIAL SAFETY DATA SHEET

(Essentially similar to OSHA form 174, Sept. 1985 - For Compliance with OSHA's Hazard Communication Standard, 29CFR 1910.1200)

Section I - Product Identity:

Fiberset FT® (6470,6475) Fiberset PM (7470,7475, 7480)

Manufacturer's Name:
Fiberlock Technologies, Inc.
150 Dascomb Road
Andover, MA 01810

Date of Preparation: September 15, 2002
Information Telephone Number: (978) 623-9987
Emergency Telephone Numbers
Weekdays: (978) 623-9987
After hours, weekends & holidays: (978) 887-5926, or
"CHEM-TEL" Emergency Contact Number: (800) 255-3924

Section II - Hazardous Ingredients/Identify Information*

HAZARDOUS COMPONENT	COMMON NAME(S)	%	CAS. NO.	OSHA OR PEL	ACGIH TLV
Titanium dioxide	(same)	<2.0	13463-67-7		ACGIH TWA 10 mg/m³

Section III - Physical/Chemical Characteristics [See reference note(s) No. 1, 2 on Reverse]

Boiling Points of Major Constituent (Water)	212°F	Specific Gravity (H ₂ O=1) Wgt./gal.	8.5
Vapor Pressure (mm Hg) @ 68°F	17	Melting Point Water (Ice)	32°F
Vapor Density (AIR=1) Heavier Lighter	X	Evaporation Rate (Butyl Acetate=1)	Slower
Solubility in Water	Total	Appearance: liquid Odor: slight odor	Maximum VOC's 100 g/l (0.9 lbs/gal)

Section IV - Fire and Explosion Hazard Data (Nonflammable)

Flash Point: Noncombustible	Flammable Limits: LEL: N/A (UEL: N/A)	DOT Hazard Class: Not Regulated	Marking: "Keep From Freezing"
--------------------------------	--	------------------------------------	----------------------------------

Section V - Reactivity Data

Hazardous Polymerization: Will not occur.
Stability: Stable
Incompatibility: Avoid contact with: Strong oxidizing agents (e.g., nitric acid, permanganates), etc.
Hazardous Decomposition Products: Some carbon monoxide.

Section VI - Health Hazard Data, Toxicity Data

Route(s) of Entry: N/A
Carcinogenicity?: No
Health Hazards (Acute and Chronic): N/A

EFFECTS OF OVEREXPOSURE: Inhalation: Vapors or spray mists may be slightly irritating to eye, nose, throat, and mucous membranes of respiratory tract producing symptoms of headache, nausea in poorly ventilated areas. Skin Contact: Prolonged or repeated contact with coating may cause slight skin irritation. Eye Contact: Direct contact; inconsequential eye irritation.

EMERGENCY AND FIRST AID PROCEDURES: Inhalation: Remove to fresh air. Eye and Skin Contact: Immediately flush eyes with plenty of water for at least 15 minutes and consult physician; wash skin thoroughly with soap and water. If drenched, remove and wash clothing before reuse. Ingestion: If swallowed, call a physician immediately. If victim is conscious, give 2 glasses of water. Never give anything to an unconscious person. Treat symptomatically.

TOXICITY INFORMATION: The effects of overexposure shown in Section VI are based on acute toxicity profiles for a number of special emulsions that are compositionally similar to this product. Typical values are: Rat, oral LD 50 > 5.0 g/kg; Rabbit, dermal LD 50 > 5.0 g/kg; Rabbit, skin irritation: practically non-irritating -72 hour Mean Irritation Score = 0 to 2; Rabbit, eye irritation: inconsequentially irritating.

SUPPLEMENTAL INFORMATION

To comply with New Jersey DOH Right-To-Know labeling law (N.J.A.C. 8:59 - 5.1 & 5.2)

CAS. No.:
7732-18-5
13463-67-7
57-55-6
Not Avail.*
Not Avail.*

CHEMICAL INGREDIENTS:
Water
Titanium dioxide (#6470 & 7470 only)
Propylene glycol
Proprietary defoamer
Acrylic resin solids

*Contents partially unknown

HMIS HAZARD RATING			
Health 1	Flammability 0	Physical Hazard 0	Personal Protection A
HAZARD INDEX 0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious, 4 = Severe			
PERSONAL PROTECTION CODE			
A = Safety Glasses			

Section VII: Precautions for Safe Handling and Use

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep unnecessary people away. Floor may be slippery; use care to avoid falling. Dike and contain material with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills and runoff out of municipal sewers and open bodies of water.

WASTE DISPOSAL METHOD: The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should then be sealed and properly labeled with waste designation and landfill or incinerated according to current local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Maximum storage temperature 100°F. Keep closure tight and container upright to prevent leakage. Precautionary Labeling: "Keep from Freezing".

OTHER PRECAUTIONS: Do not get in eyes. Avoid skin contact. Prevent prolonged or repeated breathing of vapors or spray mists. Do not handle until the manufacturer's safety precautions and label instructions have been read and understood. Avoid breathing sanding dust.

Section VIII: Control Measures

RESPIRATORY PROTECTION: None required if good ventilation is maintained. Wear respirator (MSHA/NIOSH-approved or equivalent) suitable for concentrations and types of air contaminants encountered. Use approved chemical/mechanical filters designed to remove particulates in open and restricted ventilation areas. Use MSHA/NIOSH-approved airline type respirators or hood in confined areas.

VENTILATION: Sufficient ventilation, in pattern and volume, should be provided to keep the air contaminant concentration below applicable exposure limits. All application areas should be ventilated in accordance with OSHA regulation 29CFR Part 1910.94.

PROTECTIVE GLOVES: Impervious gloves should be worn if prolonged skin contact is likely. Use neoprene or rubber gloves to prevent prolonged skin contact.

EYE PROTECTION: Use safety eyewear including side shields, face shields, or chemical splash goggles (ANSI Z-87.1 or approved equivalent).

OTHER PROTECTIVE EQUIPMENT: Use disposable or impervious clothing if work clothing contamination is likely. Use protective cream if prolonged skin contact is likely.

HYGIENIC PRACTICES: Wash hands before eating, smoking, or using the washroom. Food or beverages should not be consumed anywhere this product is being applied.

References:

1. Sax, N.I., "Dangerous Properties of Industrial Materials", 8th ed., Van Nostrand Reinhold Company, Inc., NY, 1992.
2. American Conference of Governmental Industrial Hygienists, "TLV's and Biological Exposure Indices" for the current year (published annually).
3. U.S. Code of Federal Regulations (CFR) U.S. Dept. of Labor, No. 29, Parts 1900 to 1910.1200. OSHA Communications Standard 29 CFR 1910.1200.
4. Sax, N.I., R.J. "Hazardous Chemicals Desk Reference", Van Nostrand Reinhold Co., Inc., NY, 1987.
5. Fire Protection Guide to Hazardous Materials, 12th edition, National Fire Protection Association, Quincy, MA, 1997.
6. Title III List of Lists, U.S. Environmental Protection Agency publication EPA 560/4-90-011, January 1990.



MATERIAL SAFETY DATA SHEET – Spray Rite 8 oz. Spray Adhesive

GLT Products
6810 Cochran Road
Solon, OH 44139

Date Prepared: 06/05/06
Emergency Phone: Chem-Tel 800/255-3924
Information Phone: 440/914-1122

Section 1 – Product Identification

Name:

Spray Rite 8 oz. Spray Adhesive

Section 2 – Hazardous Ingredients

Ingredient	CAS No.	OSHA PEL	TWA TEV	STEL	SARA 313	WT % (Optional)
Acetone	67-64-1	750	750	1000		20 – 30
Propane	74-98-6	1000	1000	Asphyxiant		20 – 30
Hexane	110-54-3	50	50		X	15 – 20
Isobutane	75-28-5	N/A	800	N/A		5 – 15

Section 3 – Health Hazard Information:

Effects of Overexposure:

Inhalation: Can cause irritation to the nose and throat. High concentrations may cause headaches, dizziness, nausea and confusion.

Eye: May cause eye irritation.

Skin: May cause transient skin irritation.

Ingestion: May cause gastrointestinal irritation.

Other: Reports have associated prolonged and repeated occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Section 4 – First Aid Procedures

Swallowing: If swallowed, do not induce vomiting. Call poison control center, hospital emergency room or physician immediately.

Inhalation: Remove to fresh air immediately. If breathing has stopped, give artificial respiration. Keep warm and quiet. Get medical attention.

MATERIAL SAFETY DATA SHEET – Spray Rite 8 oz. Spray Adhesive

Eye: Flush with large amounts of water, lifting upper and lower lids occasionally. Continue for at least 15 minutes. Get medical attention.

Skin: Remove contaminated clothing. Wash affected area with soap and water. Get medical attention if irritation persists.

Section 5 – Physical Data

Boiling Point	-40°F to 160°F
Vapor Pressure PSIG @ 70°F	70 approx.
Vapor Density	2.5
Appearance and Odor:	Clear light amber solution
Specific Gravity:	0.6
Melting Point:	N/A
% Volatile:	80%

Section 6 – Fire and Explosion Data

Flash Point and Method:	-40°F TCC	Flammable Limits: 1.8 LEL 12.0 UEL
Unusual Fire and Explosion Hazards:		Aerosol cans may rupture when heated.
Extinguishing Media:		Use water fog, dry chemical, foam or carbon dioxide.
Special Fire Fighting Procedures:		Heating of contents above 130°F may cause cans to burst.

Section 7 – Reactivity Data

Stability:	Stable
Conditions to Avoid:	Storing in high temperatures or exposing to open flames.
Incompatibility (Conditions to avoid):	None
Hazardous Decomposition Products:	Carbon Monoxide and Carbon Dioxide.
Hazardous Polymerization:	None

Section 8 – Spill or Leak Information

MATERIAL SAFETY DATA SHEET – Spray Rite 8 oz. Spray Adhesive

Steps to be taken in case material is released or spilled: Eliminate all sources of ignition. Permit only properly protected workers in the area with skin/eye protection and self contained breathing gear. Absorb small spills with inert absorbent material. Contact state, local, and federal agencies to ensure compliance with current regulations.

Waste disposal method: Waste must be disposed of according to local, state and federal regulations.

Section 9 – Personal Protection Information

Respirator Protection: If the LTV's listed in Section 2 are exceeded, use a properly fitted NIOSH/MSHA approved respirator.

Ventilation: Local and mechanical ventilation are recommended to keep any hazardous ingredients listed in Section 2 below the lowest exposure limit.

Hand Protection: Resistant plastic or rubber recommended.

Eye Protection: Wear safety chemical splash goggles.

Other Protective Equipment: Not likely to be needed.

Section 10 – Special Precautions


Precautions To Be Taken In Handling and Storage: Store cans in a cool, dry and well ventilated area away from all ignition sources. Prolonged exposure of cans to elevated temperatures may cause cans to rupture or burst.

Section 11 – Disclaimer


The information presented in this MSDS represents the most accurate known presentation of this product. However, due to the many and diverse variables in its end use, it is the end users responsibility to determine the suitability of this information for the adoption of the safety precautions as may be necessary.

Half Masks

7700 AND 5500 SERIES HALF MASKS



7700 Series




The North 7700 half-mask is the industry standard for comfort, fit and reliability. For over 25 years the North 7700 has proven itself, protecting workers in some of the harshest environments. Why settle for a copy when you can have the original?

The North 5500 is the economical choice for the occasional user, contractors or as a "visitor's mask". The North 5500 has many of the same features as the 7700 mask, but made with an elastomeric material.

Cartridges and filters sold separately. Refer to pages 14 and 15 for a complete listing.


FEATURE	FUNCTION	BENEFIT
GENERAL		
Can be adapted to PAPR or Supplied Air	• Flexible for multiple work environments	• No need to inventory, train workers and fit test them on several respirators
Only 9 replacement parts – and all parts are replaceable	• Quick and easy to strip down and clean • Less inventory	• Cost savings in maintenance
Both the 7700 & 5500 are latex free:	• No latex allergens	• Safe for your workers with allergies
Low "dead-air" space	• Less exhaled breath is re-breathed	• Increased worker productivity
Strategic placement of exhalation valve	• More breath is exhaled out of the mask faster	• Workers feel cooler, more comfortable
FACESEAL		
Variable thickness in sealing area	• Nose area is flexible enough to conform to the bridge of the nose, but not too thin to collapse • Built up chin area supports the mask, maintains fit even while the wearer is talking • Sides are medium thickness to maintain a seal without pressure points.	• Superior comfort without sacrificing fit
Wide, contoured sealing area	• Improved fit for more facial types	• More people will fit in a medium, so you have less inventory of alternate sizes
Overlapping sizes	• Fits a wider range of facial types	• Get the best fit possible for each of your workers
HEAD STRAP		
Expanded angle on cradle suspension is fixed into position	• More secure fit that will not slip • Workers can not wear it incorrectly	• Ideal for workers in active jobs • Less training on proper donning
Headstraps have dual elasticity Top straps have less stretch Bottom straps provide more stretch	• Holds the respirator in place • No constraints as worker turns head side to side	• More secure fit • More comfortable, will not pinch • Will not pull on the mask and jeopardize the seal
'Parking' feature	• Mask is still handy and at the ready when not worn	• Workers can get back to work quickly after a break
MASK MATERIAL		
7700 is 100% silicone – no filters	• No chance of latex allergens • More durable, greater chemical resistance • More comfortable than other masks	• Worry free for you and your workers • Like new after other masks have quit • Increased user acceptance
5500 is elastomeric with a silicone blend	• Economical • Softer than other elastomeric masks • No chance of latex allergens	• Ideal for occasional use or for sub-contractors • More comfortable and better fit than other economy masks



All North Half Masks can be adapted to PAPR or Supplied Air.

PART NO.	DESCRIPTION	PACKAGING
770030S, M, L	Silicone half mask. Sizes: small, medium and large.	Each
550030S, M, L	Elastomeric half mask. Sizes: small, medium and large.	Each

5500 CONVENIENCE PACKS



5580P100

North has taken the most popular combinations of half mask, cartridges and filters and put them all together in one "convenient package" – the North 5500 Series Convenience Packs. Convenience Packs are ideal as a "visitor" respirator you can hand out to your sub-contractors, plant guests and other occasional users of respirators.

Not available in Canada

FEATURE	FUNCTION	BENEFIT
Half mask, cartridges and/or filters in one package	• Complete and convenient.	• No worry that something is missing • You do not need to bundle your own respirator handout.
All parts are replaceable Cartridges and filters are replaceable	• Priced as a disposable, but can be reused if you choose	• Flexibility for your worksite and sub-contractors.

Each respirator contains one mask, one set of cartridges and/or filters, and one set of filter holders if a prefilter is included. Refer to pages 14 and 15 for replacement cartridges and filters, and descriptions of these air-purifying elements (cartridges and filters).

PART NO.	DESCRIPTION	PACKAGING
<i>Common applications: Exposure to dust, mists and fumes, including asbestos and lead, and atmospheres that contain oil based aerosols.</i>		
5580P100S, M, L	Half mask respirator complete with P100 filters. Sizes: small, medium and large.	Each
<i>Common applications: Most paint and pesticide applications: Exposure to organic vapors such as MEK and isocyanates, plus particulates such as dusts, mists and fumes.</i>		
5501N95S, M, L	Half mask respirator complete with organic vapor cartridges and N95 prefilters. Sizes: small, medium and large.	Each
5501R95S, M, L	Half mask respirator complete with organic vapor cartridges and R95 prefilters. Sizes: small, medium and large.	Each
<i>Common applications: Exposure to organic vapors such as MEK and isocyanates. Will not protect against particulates such as dusts, mists and fumes.</i>		
5501S, M, L	Half mask respirator complete with organic vapor cartridges. Sizes: small, medium and large.	Each
<i>Common applications: Exposure to organic vapors such as MEK and isocyanates plus acid gases such as chlorine, sulfur dioxide, and hydrogen fluoride. Will not protect against particulates such as dusts, mists and fumes.</i>		
5503S, M, L	Half mask respirator complete with organic vapor /acid gas cartridges. Sizes: small, medium and large.	Each
<i>Common applications: Exposure to vapors and/or gases plus particulates such as dusts, mists and fumes including asbestos and lead, and atmospheres that contain oil based aerosols. The Defender™ also offers protection from formaldehyde.</i>		
5581P100S, M, L	Half mask respirator complete with organic vapor cartridge/P100 filter. Sizes: small, medium and large.	Each
5583P100S, M, L	Half mask respirator complete with organic vapor /acid gas cartridges/ P100 filters. Sizes: small, medium and large.	Each
558CP100S, M, L	Half mask respirator complete with Defender™ multi-contaminant cartridges/P100 filters. Sizes: small, medium and large.	Each

Cartridges/Filters for Air-Purifying Respirators



North offers a complete line of cartridges and filters for the North 5500, 7700, 5400 and 7600 Series facepieces. All cartridges and filters listed below are interchangeable with any of these masks. Filters for limited use respirators, canisters for gas masks, and PAPR cartridges are listed in this catalog with those products.

NORTH ESLIFE™ PROGRAM FOR CARTRIDGE CHANGE SCHEDULES

OSHA's Standard for Respiratory Protection, 29 CFR 1910.134, requires Employers to implement a change schedule for all vapor and gas cartridges when there isn't an end-of-service life indicator on the cartridge. This schedule must be site specific and take into consideration worksite humidity, worker breathing rate as well as contaminant concentrations.

The North esLife Program is designed to help you with your cartridge change schedule, providing information on a cartridge's life based on your worksite parameters. Visit the North web site www.northsafety.com to learn more and try the North esLife Program.

PART NO.	DESCRIPTION	PROTECTION FROM	PACKAGING
GAS AND VAPOR CARTRIDGES			
75SC	Defender™ Multi-Purpose	Organic vapors, ammonia, methylamine, formaldehyde and acid gases (chlorine, hydrogen chloride, sulfur dioxide, hydrogen sulfide [escape], hydrogen fluoride and chlorine dioxide)	Pair
N75001	Organic Vapor	Organic vapors	Pair
N75002	Acid Gas Cartridge	Acid gases (chlorine, hydrogen chloride, sulfur dioxide, hydrogen sulfide [escape], hydrogen fluoride and chlorine dioxide) and formaldehyde	Pair
N75003	Organic Vapor & Acid Gas	Organic vapors and acid gases (chlorine, hydrogen chloride, sulfur dioxide, hydrogen sulfide [escape], hydrogen fluoride and chlorine dioxide)	Pair
N75004	Ammonia & Methylamine	Ammonia and methylamine	Pair
N750052	Mercury Vapor Cartridge with ESLI	Mercury vapor and chlorine with End-of-Service Life Indicator (ESLI) for mercury	Pair
COMBINATION GAS AND VAPOR CARTRIDGES WITH P100 PARTICULATE FILTERS			
75SCP100	Defender™ Multi-Purpose with P100	Organic vapors, ammonia, methylamine, formaldehyde and acid gases (chlorine, hydrogen chloride, sulfur dioxide, hydrogen sulfide [escape], hydrogen fluoride and chlorine dioxide); and 99.97% filter efficiency for all particulates	Pair
7581P100	Organic Vapor with P100	Organic vapors; and 99.97% filter efficiency for all particulates	Pair
7582P100	Acid Gas with P100	Acid gases (chlorine, hydrogen chloride, sulfur dioxide, hydrogen sulfide [escape], hydrogen fluoride and chlorine dioxide) and formaldehyde; and 99.97% filter efficiency for all particulates	Pair
7583P100	Organic Vapor & Acid Gas with P100	Organic vapors and acid gases (chlorine, hydrogen chloride, sulfur dioxide, hydrogen sulfide [escape], hydrogen fluoride and chlorine dioxide); and 99.97% filter efficiency for all particulates	Pair
7584P100	Ammonia & Methylamine with P100	Ammonia and methylamine; and 99.97% filter efficiency for all particulates	Pair
75852P100	Mercury Vapor with ESLI and P100	Mercury vapor and chlorine with End-of-Service Life Indicator (ESLI) for mercury; and 99.97% filter efficiency for all particulates	Pair

Cartridges/Filters for Air-Purifying Respirators



PART NO.	DESCRIPTION	PROTECTION FROM	PACKAGING
PARTICULATE FILTERS			
7580P100	P100	99.97% filter efficiency for all particulates	Pair
75FFP100	Pancake, Low profile P100 filter for use under welding helmets	99.97% filter efficiency for all particulates	Pair
75FFP100NL	Pancake with odor relief, Low profile P100 filter for use under welding helmets	99.97% filter efficiency for all particulates; plus relief from odors caused by nuisance levels of organic vapors, acid gases and ozone	Pair
7506N95	N95 Prefilter	95% filter efficiency for non-oil based aerosol particulates	10 per Pack
7506R95	R95 Prefilter	95% filter efficiency for all particulates. Restricted to 8 hours service life if used in atmospheres containing oil-based aerosols	10 per Pack
7506N99	N99 Prefilter	99% filter efficiency for non-oil based aerosol particulates	10 per Pack
PARTICULATE FILTER ASSEMBLIES			
7536FP100	Stack Pack Pancake with Adapter	99.97% filter efficiency for all particulates. Includes one pair of N750035 adapter to attach the Pancake to North cartridges. May not be used with the Defender cartridges.	5 Pair filters & 1 Pair adapter
7531N95	N95 Filter Assembly	95% filter efficiency for non-oil based aerosol particulates. Includes 7506N95 prefilters, N750027 filter covers and N750015 filter retainers for use on half mask or full facepiece when cartridges are not used.	1 Pair
7537R95	R95 Filter Assembly	95% filter efficiency for all particulates. Restricted to 8 hours service life if used in atmospheres containing oil-based aerosols. Includes 7506R95 prefilters, N750027 filter covers and N750015 filter retainers for use on half mask or full facepiece when cartridges are not used.	1 Pair

FILTER EFFICIENCIES

The National Institute of Occupational Safety and Health (NIOSH) classifies filters in two ways, type and efficiency. Using these classifications there are nine possible filter groups. The most commonly used are N95 as the most economical, and P100 providing the highest possible protection. The classifications are defined on the right.

Type	Efficiency
N Not for use in atmospheres that contain oil based aerosols.	95 95% minimum filter efficiency in removing particulates.
R Restricted to eight hours of service life if used in atmospheres that contain oil based aerosols.	99 99% minimum filter efficiency in removing particulates.
P Oil Proof. May be used without restrictions in atmospheres that contain oil based aerosols.	100 99.97% minimum filter efficiency in removing particulates.

PART NO.	DESCRIPTION	PROTECTION FROM	PACKAGING
ACCESSORIES			
N750035	Pancake Adapter	Allows user to stack the Pancake on a North cartridge, converting the Pancake to a P100 prefilter. May not be used with the Defender.	Each
N750015	Filter Holder	Holds prefilters onto North half and full facepieces. Must be used with N750027 Filter cover.	Each
N750027	Seal Check / Filter Cover	Snaps on top of prefilters to hold them in place on North cartridges or on N750015 filter holder	Each
N750029	Shower Cap	For use with 7580P100. Deflects moisture during a "Decon" shower	Each



DuPont™ Tyvek®

The best balance of protection, durability and comfort

With Tyvek® you don't have to compromise. That's because Tyvek® delivers the best balance of protection, durability and comfort. Made using a proprietary manufacturing process, Tyvek® features an inherent barrier. So, unlike other protective apparel fabrics, which have either a film or coating that can be easily scratched or worn away, Tyvek® provides barrier through the entire fabric. As a result, your protection is not compromised unless the fabric has been completely torn—which isn't easy to do because of the strength and durability of Tyvek®. Make sure you're getting Tyvek®. Ask for it by name.

Barrier Protection You Can Trust, Durability That Isn't Easily Compromised

- Tyvek® is the industry standard for dry particulate barriers. Microscopic particles as small as 0.5 microns can't pass through Tyvek®—even after it's been abraded.
- Tyvek® is an inherent barrier—not easily scratched or worn away.

Comfort You'd Never Expect

Standing still, your body radiates heat and moisture vapor. So, it's no surprise that working in protective apparel that can't breathe escalates the problem dramatically and can affect productivity. It's called heat stress. And, it can seriously compromise your safety, especially in hazardous environments.

- Tyvek® lets air and moisture vapor pass through.
- Tyvek® is anti-static treated.
- Tyvek® breathes. Breathability is a key factor in reducing heat stress.
- Tyvek® is six times more breathable than microporous film garment materials.
- Tyvek® SoftWear™ is even more comfortable and four times as breathable as traditional Tyvek®.
- Tyvek® SoftWear™ has a dramatically softer feel.

Proven Performance and Quality

At DuPont Personal Protection, our goal is to combine scientific innovation with material, garment and manufacturing knowledge to create protective apparel that helps the people who wear PPE perform at their best. Both DuPont manufacturing facilities are certified to ISO 9001:1994.

Garment Styles To Meet Your Needs

- Tyvek® is available in a wide variety of garment styles, such as coveralls, labcoats, smocks and aprons.
- Tyvek® SoftWear™ is available in four coverall styles.

Wide Range of Applications

- General Maintenance Operations
- Construction & Agricultural
- Lead & Asbestos Abatement
- Environmental Clean-up
- Modesty Garments (Hospitals & Police)
- Environments where cross-contamination is an issue
- Spray Painting
- Food Processing
- Mold Remediation
- Abrasive Blasting
- Forensics



The miracles of science®

DuPont™ Tyvek®

The best balance of protection, durability and comfort

With Tyvek® you don't have to compromise. That's because Tyvek® delivers the best balance of protection, durability and comfort. Made using a proprietary manufacturing process, Tyvek® features an inherent barrier. So, unlike other protective apparel fabrics, which have either a film or coating that can be easily scratched or worn away, Tyvek® provides barrier through the entire fabric. As a result, your protection is not compromised unless the fabric has been completely torn—which isn't easy to do because of the strength and durability of Tyvek®. Make sure you're getting Tyvek®. Ask for it by name.

Barrier Protection You Can Trust, Durability That Isn't Easily Compromised

- Tyvek® is the industry standard for dry particulate barriers. Microscopic particles as small as 0.5 microns can't pass through Tyvek®—even after it's been abraded.
- Tyvek® is an inherent barrier—not easily scratched or worn away.

Comfort You'd Never Expect

Standing still, your body radiates heat and moisture vapor. So, it's no surprise that working in protective apparel that can't breathe escalates the problem dramatically and can affect productivity. It's called heat stress. And, it can seriously compromise your safety, especially in hazardous environments.

- Tyvek® lets air and moisture vapor pass through.
- Tyvek® is anti-static treated.
- Tyvek® breathes. Breathability is a key factor in reducing heat stress.
- Tyvek® is six times more breathable than microporous film garment materials.
- Tyvek® SoftWear™ is even more comfortable and four times as breathable as traditional Tyvek®.
- Tyvek® SoftWear™ has a dramatically softer feel.

Proven Performance and Quality

At DuPont Personal Protection, our goal is to combine scientific innovation with material, garment and manufacturing knowledge to create protective apparel that helps the people who wear PPE perform at their best. Both DuPont manufacturing facilities are certified to ISO 9001:1994.

Garment Styles To Meet Your Needs

- Tyvek® is available in a wide variety of garment styles, such as coveralls, labcoats, smocks and aprons.
- Tyvek® SoftWear™ is available in four coverall styles.

Wide Range of Applications

- General Maintenance Operations
- Construction & Agricultural
- Lead & Asbestos Abatement
- Environmental Clean-up
- Modesty Garments (Hospitals & Police)
- Environments where cross contamination is an issue
- Spray Painting
- Food Processing
- Mold Remediation
- Abrasive Blasting
- Forensics



The miracles of science®

Tyvek® and Tyvek® SoftWear™

Physical Properties

PROPERTY	UNITS	TYVEK®	TYVEK® SOFTWEAR™
Basis Weight	oz/yd ²	1.2	1.2
Thickness	mils	5.8	6.0
Tongue Tear, MD	lbf	2.2	2.2
Tongue Tear, CD	lbf	2.3	2.2
Strip Tensile, MD	lbf	7.9	7.9
Strip Tensile, CD	lbf	8.7	8.1
Mullen Burst	psi	50	55
Porosity	Mm ³ /min/Atm H ₂ O	3.0	18.6
Static--Log R	log ohms	<9.8	<9.8
Flammability	16 CFR 1610	Class 1	Class 1

INDEX OF CODES:
 <= less than

These results are measured using the latest ASTM test methods. Results will vary due to the changes in test methods. A true test of performance is to use.

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information.

It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions at their own discretion and risk.

Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded or punctured, and user should discontinue use of garment to avoid potential exposure to chemical. **SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE AND ASSUME NO LIABILITY WHATSOEVER IN CONNECTION WITH ANY USE OF THIS INFORMATION.**

This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of DuPont or others covering any material or its use.

WARNINGS:

- 1) Tyvek® is not flame-resistant and should not be used around heat, flame, sparks or in potentially flammable or explosive environments.
- 2) Garments made of Tyvek® should have slip-resistant or antislip materials on the outer surface of hoods, shoe covers or other garment surfaces in conditions where slipping could occur.

For more information:

Visit our website at:
www.PersonalProtection.DuPont.com

DuPont Personal Protection
Fax-On-Demand Service at 1-800-558-9329

DuPont manufactures a complete line of garments for personal protection.
 For more information, call **1-800-931-3456**

DuPont Personal Protection





Tychem®

CHEMICAL PROTECTIVE CLOTHING

[← Back to Apparel Selector](#)

Tychem® SL

Lightweight protection of Tyvek® laminated with a chemical-resistant Saranex

Tychem® SL delivers effective protection against a range of chemical environments. Tychem® SL, utilizing Saranex® 23-P film laminated to Tyvek® brand protective material, is a lightweight, comfortable garment specifically designed for easy wear. Tychem® SL is ideal for chemical mixing, remediation, emergency medical response, paint spraying, and radioactive environments.

Tychem® SL is used in a variety of industries, including environmental clean-up operations, waste management, industrial plants, cleanroom applications, hazardous material response teams and other emergency services. General garment construction/wear guidelines should be followed according to the specific application.¹

Visibility

When workers wear high-visibility colors it improves how well they can be recognized and distinguished from the background. Obviously, safety is enhanced when workers can be clearly see co-workers. The Tychem® SL standard white color provides the highest level of visibility in low and dim light; however, it may have low contrast. White garments provide high contrast visibility in wooded areas and low contrast against snow. In a laboratory study, Tychem® SL received high overall ratings for visibility for dim light and bright light. Contrast was low against bright, light colored backgrounds, but very high against dark and outdoor backgrounds.²

Durability

Tychem® SL is rugged and durable even in cold temperatures. Tychem® SL offers little change in stiffness when exposed to extreme cold temperatures (-65°C to 20°C or -85°F to 68°F) measured per ASTM D747.

Permeation

Tychem® SL is the only fabric laminated with Saranex® DuPont provides permeation data and technical support provides permeation data and detailed information on how to perform against chemical classes in a variety of forms. Choose Fax-On-Demand, website, CD-ROM or our eye printed Permeation Guide³ for DuPont Tychem® Protec

Nuclear Environments

A study was conducted by Southwest Research Institute on fabrics in potentially radioactive environments. The study of the fabrics' ability to resist water vapor and tritium gas penetration showed Tychem® SL was 150% more resistant to tritium gas penetration than other fabrics. The study states, "when it is desired to penetrate of tritium, data suggest that the wearer may work three hours in Tychem® SL, as opposed to only half an hour in other fabrics".

Permeation Data for ASTM Recommended List of Chemicals for Evaluating Protective Clothing Materials (ASTM F1001)

CHEMICAL NAME	PHYSICAL PHASE	AVERAGE NORMALIZED BREAKTHROUGH TIME (minutes)	AVERAGE PERMEATION RATE (µg/cm ² /minute)
Acetone	L	> 24	1.6
Acetonitrile	L	12	2.8
Ammonia	G	32	0.15
1,3-Butadiene	G	> 480	< 0.02
Carbon disulfide	L	immed.	>50
Chlorine gas	G	> 480	< 0.01
Dichloromethane	L	immed.	>50
Diethylamine	L	12	>50
N,N-	L	112	0.85

INDEX OF CODES

Dimethylformamide			
Ethyl acetate	L	14	0.54
Ethylene oxide	G	immed.	8.4
n-Hexane	L	146	0.48
Hydrogen chloride	G	> 480	< 0.1
Methanol	L	>480	<0.001
Methyl chloride	G	> 480	< 0.006
Nitrobenzene	L	102	2.3
Sodium hydroxide, 50%	L	> 480	< 0.1
Sulfuric acid (conc.)	L	> 480	< 0.1
1,1,2,2-Tetrachloroethylene	L	immed.	5.7
Tetrahydrofuran	L	immed.	>50
Toluene	L	immed.	25

> = greater than
 < = less than
 L = liquid, G = gas
 immed. = immediate (<10 minutes)
 Numbers reported are averages of samples tested by ASTM F739 test method. Sample results do vary and therefore averages for these results are reported.

CHEMICAL NAME	PHYSICAL PHASE	CAS #	AVERAGE NORMALIZED BREAKTHROUGH TIME (minutes)	CHEMICAL NAME	PHYSICAL PHASE	CAS #	AVERAGE NORMALIZED BREAKTHROUGH TIME (minutes)
Acetone	L	64-19-7	>480	Methanol	L	67-56-1	>480
Acetic anhydride	L	108-24-7	>480	Methyl bromide	G	74-83-9	>480
Acrylic acid	L	79-10-7	>480	Methyl chloride	G	74-87-3	>480
Acrylonitrile	L	107-13-1	>480	Methyl ethyl ketoxime	L	96-29-7	>480
Ammonia	L	7664-41-7	>480	Methyl t-butyl ether	L	1634-04-4	>480
Ammonium hydroxide, 28%-30%	L	1336-21-6	>480	n-Methyl-2-pyrrolidone	L	872-50-4	>480
Benzene	L	71-43-2	74	4,4'-Methylene bis (o-chloroaniline), sat. sol. in methanol	L	101-14-4	>480
Benzo[a]pyrene	S	50-32-8	>480	Mineral oil	L	8012-95-1	>480
Black liquor	L	123465-36-1	>480	Mineral spirits	L	64475-85-0	>480
Chemideize 727 ND	L	mixture	>480	Nicotine	L	54-11-5	450
Chlorine, 20 ppm	G	7782-50-5	>480	Nitric acid, 70%	L	7697-37-2	>480
Chloroacetone	L	78-95-5	480	Nitrogen dioxide	G	10102-44-0	>480
Chromic acid, 60%	L	1333-82-0	>480	Oilum, 40% free SO ₃	L	8014-95-7	>480
o-Cresol	L	95-48-7	>480	PCB	L	11097-69-1	>480
Crude oil	L	8002-05-9	>480	PCB 1%, Mineral spirits 99%	L	11097-69-1	>480
1,1-Dichlorotetrafluoroethane	L	374-07-2	>480	PCB 50%, Mineral oil 50%	L	11097-69-1	>480
Diethylaniline crude	L	91-66-7	>480				
Diethyl-m-toluidine crude	L	91-67-8	>480				
Ethylene glycol	L	107-21-1	>480				
Formalin (Formaldehyde)	L	50-00-0	>480				

37%)				PCB 50%,			
Formic acid	L	64-18-6	>480	Trichlorobenzene	L	11097-69-1	>480
Fuel oil	L	mixture	>480	50%			
Gluteraldehyde, 5% aqueous solution	L	1-11-30-8	>480	PCB gas condensate	L	10097-69-1	401
Green liquor	L	68131-30-6	>480	Phenol, 85%	L	108-95-2	>480
Hexamethyldisilazane	L	999-97-3	>480	Phenyl ethyl alcohol	L	98-85-1	>480
Hydrazine	L	302-01-2	>480	Phosphoric acid, 85%	L	7665-38-2	>480
Hydrochloric acid, 37%	L	7647-01-0	>480	Potassium acetate, sat. sol. in water	L	127-08-2	>480
Hydrofluoric acid, 48%	L	7664-39-3	>480	Sodium hydroxide, 50%	L	1310-73-2	>480
Iodine	S	7553-56-2	>480	Sodium hypochlorite, 17%	L	7681-52-9	>480
Mercuric chloride, sat sol. in water	L	7487-94-7	>480	Sodium hypochlorite, 5.25%	L	7681-52-9	>480
Mercury	L	7439-97-6	>480	Sulfur dioxide	G	7446-09-5	>480
Methanesulfonic acid	L	75-75-2	>480	Sulfuric acid	L	7664-93-9	>480
				1,1,1,2-Tetrafluoroethane	L	811-97-2	>480
				Toluene-2,4-diisocyanate	L	584-84-9	>480
				Triethylamine	L	121-44-8	>480
				White liquor	L	68131-33-9	>480

> = greater than, L = liquid, G = gas, S = solid

Physical Properties of Tychem® SL		Chemical Warfare Agents			
		AGENT	TIME	CUMULATIVE PERMEATION	P
Basis Weight (ASTM D3776-90)	3.6 oz/yd ²	HD, Sulfur Mustard	3 hours	<0.1 µg/cm ²	
Thickness (ASTM D1777-75)	13 mils	L, Lewisite	6 hours	<0.1 µg/cm ²	
Mullen Burst (ASTM D3786-87)	73 psi	GB, Sarin	6 hours	<0.00012 µg/cm ²	
Breaking Strength Grab (md/cd) (ASTM D5034-90)	47/50 lbs	VX	12 hours	<0.00012 µg/cm ²	
Tearing Strength Trapezoid (md/cd) (ASTM D1117-80)	9/8 lbs	Applied at 10g/m ² in 1µL drops at 22°C, 50%			
				< = less than	

◀ Back to Apparel Selector

For more information:

For specific permeation data and breakthrough times for other chemicals:

DuPont Protective Apparel

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DUPONT MAKES NO GUARANTEE OF RESULTS AND ASSUMES NO OBLIGATION OR LIABILITY WHATSOEVER IN CONNECTION WITH THIS INFORMATION.

It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein

Fax-On-Demand Service
at 1-800-558-5907

Visit our website at
www.TyvekProtectiveApprl.com

DuPont manufactures a complete line of chemical protective fabrics made of Tychem® and fabric made of Tyvek® for dry particulate protection. For more information, call 1-877-797-5907.

WARNINGS:

1) Tychem® BR is not flame-resistant and should not be used around heat, flame, sparks, or potentially flammable or explosive environments.

2) Garments made of Tychem® BR should have slip-resistant or antislip materials on the outer surface of boots, shoe covers or other garment surfaces in conditions where slipping could occur.

reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk.

Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact the garment manufacturer for specific data. If fabric becomes torn, abraded or punctured, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, expressed or implied, including, without limitation, no warranties of merchantability or fitness for a particular use and assume no liability whatsoever in connection with any use of this information.

This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of DuPont or others covering any material or



[Home](#)

[Air Filtration Equipment](#)

[Indoor Air Quality](#)

[Stages of Filtration](#)

[Equipment Options](#)

[Water Filtration](#)

[Floor Tile Equipment](#)

[Request A Brochure](#)


Water Filtration

Portable Shower #9105

The ORIGINAL COLLAPSIBLE telescoping decontamination shower is easily set up by two men in a matter of seconds.

Features:

- * MADE IN U.S.A.
 - * Lightweight aluminum construction
 - * 100 Micron drain filter
 - * Removable curtain
 - * Two (2) Handles for E-Z Handling
- Dimensions: (Open) 31" X 30" X 83"
Dimensions: (Closed) 31" X 31" X 48"
Weight: 100 lbs.



#9115 Two Stage Pump and
#9105 Collapsed Shower

[CLICK HERE FOR THE PARTS LIST](#)

Two Stage Pump #9115


Features:

- * MADE IN U.S.A.
- * Enclosed aluminum container
- * Galvanized plumbing
- * 5 Micron and 50 Micron filtration
- * 12 Gallons per minute
- * Weight: 36 lbs.
- * 1/2 H.P. Motor

[CLICK HERE FOR THE PARTS LIST](#)

Entry/Exit Frame Model #9108

Decontamination frames are 32" wide which can be used to form "tunnels" from one contaminated area to another. They can also form a passageway from a decontamination trailer to a work area, or can be used with the Aero-Porta Shower for airlock chambers.



**Aerospace America, Inc. ~ 900 Harry Truman Pkwy. ~ Bay City, MI 48706
1-800-237-6414 ~ 989-684-2121 ~ Fax: 989-684-4486**

HEPA Vacuums

PULLEMAN-HOFF




Asbestos
Abatement

Lead
Removal

Hazardous Mold
Remediation



If you're doing professional abatement work, you need a continuous duty heavy grade vacuum. You need one that does the job right the first time, every time. Pullman-Holt understands your needs and has developed a line of HEPA vacs that are up to whatever challenge you can put them to. From backpack style vacs to huge drum canister vacs, there's something for every type of operation. We know that, as a busy professional, you don't have time to shop for a new vacuum every time your old one breaks down, not to mention the financial considerations. That's why we've designed all Pullman-Holt HEPA vacs with quality and long service-life in mind. And, we proudly stand behind our products with a warranty that's unsurpassed in the safety/environmental industry. So, take a few minutes now to look over this brochure and select the models that will best suit your needs. Once you place your order and receive your Pullman-Holt vac(s), you won't have to think about your vacuum equipment any more. It'll just be there, ready to go when you are. Now that's peace of mind!



**MODEL
102ASB DA
(B160446)**




Our super heavy-duty drum style HEPA vac, model 102, sits atop a steel drum to create the ultimate in vacuum recovery capacity. This unit features an unsurpassed 55 gallons of wet recovery capacity and a whopping 7.2 bushels of dry capacity. When the job seems daunting, the 102 Drum model fits the bill. *Drum not included.*

- ¥2HP, 2 stage by-pass motor, 11.1 AMPS, 105 waterlift, 110 CFM
- ¥ Louvered head diffuses exhaust air to prevent excessive air disturbance.
- ¥ Complete tool kit; 10 hose, floor brush, metal wand, floor squeegee and round brush
- ¥ 25 foot power cord
- ¥ Vacuum motor warranty 3 years


SURVIVORS SERIES

The 102ASB-12P, is one of our most popular HEPA vacs and a true work-horse for heavy-duty service in professional abatement work. Its 2HP, two-stage, long-life motor provides superior vacuum recovery for everything from dry, light particulates to wet, heavy debris. The standard 102 model features a heavy duty poly tank, and is equipped with a high-efficiency drop-in HEPA filter individually certified to have minimum efficiency of 99.99% at 3 microns (based on 1EST-RP-CC007 particle count test method). For further filtration, a polyester prefilter is located on the bottom of the HEPA filter and is held firmly in place with Velcro fasteners. Additionally, a dacron filter bag (dacron material sheds dust to maintain vacuum efficiency) covers the entire spacer sleeve and HEPA filter for three-stage filtration. In addition our paper bag provides an extra filtering area and is used in trapping and holding the bulk of any recovered material and can be easily disposed (for dry use only).

- ¥ 2 HP, 2 stage by-pass motor, 11.1 AMPS, 105 waterlift, 110 CFM
- ¥ Louvered head diffuses exhaust air to prevent excessive air disturbance.
- ¥ Uses an air seal gasket between the motorhead and the tanks for a positive lock fit
- ¥ Complete tool kit; 10' hose, floor brush, metal wand, floor squeegee and round brush
- ¥ Vacmobile handle and cart w/8 rear wheels and 2.5 front casters for easy transport
- ¥ 25 foot power cord
- ¥ Vacuum motor warranty 3 years




**MODEL
102ASB-12P
(B160421)**



- Wet/Dry Tool Kit: (B160056)**
- ¥5 two-piece metal wand (B521007)
 - ¥10 x 1.5 crushproof hose (B000311)
 - ¥ 14 floor brush tool (B527095)
 - ¥ 14 ABS floor squeegee (B527094)
 - ¥ Round dusting brush (B000394)

HEPA filter system

- hepa filter (B160009)
- spacer sleeve (B700306)
- prefilter (B700047)
- dacron filter bag (B000517)
- disposable paper bag (B524253)



THE BEST INVESTMENT YOU CAN MAKE IS IN YOUR OWN PROTECTION.

**MODEL
86ASB54C
(B160419)**



The 86ASB dry and wet/dry, is a compact steel vac that's small and light enough to be easy to carry or transport, yet rugged enough to handle the toughest jobs. It's designed to work in tight areas and is available in dry or wet/dry (5-gal. wet recovery capacity) versions. The 86 is powered by an efficient 1HP motor that delivers a respectable 96cfm. This is a high-efficiency unit featuring a drop-in style HEPA filter individually certified to have a minimum efficiency of 99.97% at .3 microns (based on IEST-RP-CC007 particle count test method). For full three-stage filtration, Pullman-Holt includes a dacron filter bag that covers the entire spacer sleeve and HEPA filter. (Dacron material sheds dust to maintain maximum vacuum efficiency.) And, the model 86ASB includes the same high quality tool kit included with our 102ASB series: 10' x 1.5" crushproof hose; 5-foot two-piece metal wand; 14-inch ABS floor brush tool; 14-inch floor squeegee tool (not included with 86ASB5D4C); and a round dusting brush. For ease of use and portability, the 86ASB includes a 25-foot power cord.





**MODEL
86ASB5D4C
(B160420)**

HEPA filter system

hepa filter (B526520)	spacer sleeve (B700344)	disposable paper bag (B700408)
prefilter (B527302)	dacron filter bag (B000517)	

**MODEL 30ASB
(B160000)**



HEPA filter system

hepa filter
(B700000)
disposable paper bag
(B160007)

When it comes to lightweight, portable backpack-style vacs, the model 30ASB by Pullman-Holt is the preferred vac. Its 1HP motor delivers an impressive 101cfm. The model 30ASB is ideal for use in elevated or hard-to-reach areas. It makes quick work of sampling or glove bag work. And we've thought of everything when it comes to building power and efficiency right into this model. An air seal gasket between the motor-head and tanks forms a positive lock fit. As with many of our other HEPA vacs, the 30 includes a high-efficiency, drop-in style HEPA filter that is individually certified to have a minimum efficiency of 99.97% at .3 microns (based on IEST-RP-CC007 particle count test method). The model 30 would not be complete, without its; 10' x 1.5" crushproof hose and round dusting brush. And a 50-foot power cord allows maximum range without relocating the plug to another power source. Consider the model 30ASB for your portable vacuum needs.

Dry Tool Kit (B160423)

¥ 10 x 1.5 crushproof hose (B000311)
¥ Round dusting brush (B000394)



BDX II ABATEMENT AIR SAMPLER

*Introducing The BDX II,
the newest member of Sensidyne's
Gilian Line. A low cost, high
performance personal air sampling
pump for the lead and asbestos
abatement industry.*

- 0.5-3.0 LPM
- Anti-tamper control covers
- Internal components sealed from dust, fibers and moisture
- Easy calibration
- Portable
- Built-in electronic flow control adjustment
- Rechargeable battery pack
- UL approved



800.451.9444

For the first time, the precision of Sensidyne's Gilian line is combined with the durability and economical pricing of BDX products in the BDX II. Designed for lead and asbestos monitoring, its compact, lightweight design is rugged and completely reliable, making it ideal for field applications.

The BDX II accurately monitors for asbestos using the NIOSH Method 7400 or the OSHA reference sampling method. It will also monitor for lead using NIOSH Methods 7082, 7105 or 7300.

FEATURES

Rugged and dependable construction will withstand the toughest industrial environments.

This pump is made to outlast and outperform larger and more costly pumps.

The built-in rotameter monitors flow rates over the entire flow range of 0.5 - 3.0 LPM.

The electronic flow control adjustment enables parts to last longer.

The rechargeable NiCad battery provides approximately 10 hours of reliable operation on a single charge and easily detaches from the pump body for recharging and/or quick field change.

Sealed flow adjustment and on/off switch protects the pump from moisture, dust and fibers.

STARTER KIT

A specially designed Starter Kit is available for the BDXZ and includes the pump and accessories, everything needed for accurate and reliable sampling.

Part #801863-120 Starter Kit

SPECIFICATIONS

General Specifications

Controls	Power Switch, Flow Control
Flow Indicator	Built-in rotameter, range 500-5000 cc/min, with 500 cc/div @ $\pm 20\%$ Full Scale accuracy
Additional features	See-through external filter housing, with filter monitoring lens; built-in belt clip
Dimensions	3.6" (W) x 3.9" (H) x 2.0" (D) (90 mm (W) x 100 mm (H) x 51 mm (D))
Weight	21 oz (595 g)
Power Supply	
Battery Pack	4.8 volt, 1.8 amp hour, sealed
Battery Type	Rechargeable nickel-cadmium
Battery Charge Time	14 - 16 hours
Expected Battery Life*	300-500 charge-recharge cycles or 2.5 years (<20 hours weekly use) 1.5-2.5 years (20-39 hours weekly use) 1-1.5 years (40-60 hours weekly use)

*Inactivity for extended periods may shorten nickel-cadmium battery life. Battery life estimates are based on proper battery maintenance.

OPERATING SPECIFICATIONS

Operating Range	500-3000 cc/min (0.5-3.0 LPM)
Flow Control	$\pm 5\%$ of set point over an 8-hour period, when operating at 2.0 LPM.
Operating Duration (Full Charge)	10 hours at 2.0 LPM with an inlet pressure of up to 20 inches of water at 21°C (70°F)
Operating Temperature	-20°C to 45°C (-4°F to 113°F)
Storage Temperature	-40°C to 45°C (-40°F to 113°F)
Charging Temperature	5°C to 45°C (41°F to 113°F)



Sensidyne manufactures, supplies, and services gas detection systems and air sampling pumps that are characterized by their ease of use, accuracy, economical cost and durability.

Copyright 2001 © Sensidyne, Inc.



Grayling

6072


AVAIL Standard
Glovebag System for
Long and Short Pipe Runs



DANGER
This material is highly flammable and may ignite. Handle with care.


OT18

WILSON




QT18

Large pipe diameters from 14" to 18" are no problem for this QT18 model. Two sets of glovesleeves let the worker easily reach and remove pipe insulation. This bag is a direct replacement of the 6584 style glovebag.



QT30

This super-sized AVAIL model handles pipe diameters from 18" to 30" and directly replaces the 72120. Ideal for larger pipes, valves and fittings where more work area is required. Three sets of glovesleeves let workers remove insulation on large diameter pipe.




The **QuickTwist 1-2-3** debris chamber makes it easy for workers to securely and safely separate debris laden bags from pipe. The new design incorporates a narrower and taller waste area so that less bunching is required to twist close the glovebag. After waste is funneled into the chamber, the worker easily twists it closed at the top and tapes the neck to prevent escape of dangerous fibers.



Grayling AVAIL brand glovebags enjoy the industry reputation of being the highest performing, easiest to use, and safest method to remove asbestos insulation from pipe. It is no wonder that more professionals choose AVAIL than any other brand. AVAIL glovebags have been used to remove over 50 million linear feet of pipe insulation.


The AVAIL QuickTwist model incorporates all the safety and labor saving features of other AVAIL glovebags, plus a new debris chamber design that makes it safer and easier for workers to twist off the waste area. The QuickTwist design has two distinct work zones, the removal area and the debris chamber. This two-stage design makes it safer and easier for workers to remove and securely separate debris-laden bags from pipe. The QuickTwist incorporates a larger work area with a narrower and taller debris chamber so that less bunching is required to twist close the glovebag. The increased work area gives the worker greater freedom inside the glovebag to access difficult pipe insulation. Each debris chamber is tall enough to handle intact sections of pipe insulation, less breakage of debris means lower fiber counts. After waste is funneled into the chamber, the worker easily twists it closed at the top and tapes the neck to prevent escape of dangerous fibers. The QuickTwist debris chamber is more puncture and tear resistant than any glovebag ever made. Made from PHD, a specially engineered polymer that incorporates all the strength and durability of low and high-density polyethylene.

All AVAIL bags come packaged in a convenient dispensing box that protects the unused bags from damage due to handling. The bags are on a roll and can be cut off and used in sections of 1, 2, 3 or more. 6 mil is standard construction.



QT10


The most popular and versatile glovebag in the collection, the QT10 fits pipe diameters up to 10". It handles 40% more insulation than a 4460 style glovebag. This bag directly replaces the 4460 through 6060 style glovebags.



QT14


When larger diameters of pipe are encountered, the QT14 is a workhorse. It safely encloses pipe diameters from 10" to 14". A perfect replacement for the 6072 style glovebag.






6072EXT & 6072

The Avail workhorse for larger pipe diameters from 10" to 14". Chambers measure 60"x72" with one glovesleeve set, port set, quick attach collars and 6-mil construction.



6684-2EXT & 6684-2

This Avail bag eliminates awkward bag twisting to reach around the pipe diameter with two sets of glovesleeves. Ideal for pipe diameters 14" to 18". Each chamber measures 66"x84" and has a port set, quick attach collars and 6-mil construction.



72120-2



This super sized AVAIL model handles pipe diameters from 18" to 30". Ideal for larger pipes, valves and fittings where more work area is required. Two sets of glovesleeves let workers easily remove insulation on large diameter pipes. Measures 72"x120" with a port set and 6-mil construction.



Grayling AVAIL brand glovebags enjoy the industry reputation of being the highest performing, easiest to use, and safest method to remove asbestos insulation from pipe. It is no wonder that more professionals choose AVAIL than any other brand. AVAIL glovebags have been used to remove over 50 million linear feet of pipe insulation.

All AVAIL bags come packaged in a convenient dispensing box that protects the unused bags from damage due to handling. The bags are on a roll and can be cut off and used in sections of 1, 2, 3 or more. 6 mil is standard construction.

Extended-run glovebags dramatically increase productivity and safety by eliminating multiple bag set-up labor and reducing jobsite fiber counts. The extended-run design is more efficient because it encloses a larger work area per bag and allows workers to remove more insulation than when used as a single bag.



4460EXT & 4460

The basic economy Avail glovebag encloses pipe diameters up to 8". Each chamber measures 44"x60" with one arm set per chamber; 6-mil construction. Available in the popular Extended-run design on a roll or as pre-cut single bags.

5460EXT & 5460

This full featured Avail glovebag sets the industry standard for efficiency on pipe diameters up to 10". Available in the popular Extended-run design on a roll or as pre-cut single bags. Each chamber measures 54"x60" with one arm set, and ports per chamber, 6-mil construction.



6684-2



ONCE



Graying

Not all applications are long runs of horizontal pipe. These Special Application AVAIL glovebags make your workers more productive on difficult vertical pipe, small valves and large vessels.

The AVAIL M6 is the perfect bag for small maintenance and repair operations where the work is on small pipe, valves and gaskets. The M6 has pre-cut openings, collars and fiberguard glovesleeves like the other AVAIL models.

AVAIL glovebags for vertical applications improve worker productivity by design features which assist in the removal of debris. Debris weight and bulk is directed away from the work area by the debris chamber. Awkward twisting and turning of the bag is eliminated due to the work area being separated from the debris area. Installation is quick, safe and secure with fitted collars and pre-cut bag openings.

M6

AVAIL Special Application Glovebag System

op
durapax

DISP
Bags
for asbestos
abatement

DANGER

CONTAINS ASBESTOS FIBERS
AVOID CREATING DUST
SEAL AND DISCARD PROPERLY
DO NOT BREATHE AIRBORNE FIBERS




Grayline™

1-800-222-2222

d. TM
durapax

Disposal Bags for asbestos abatement

Grayling Industries' Durapax is a full line of industrial strength disposal bags for asbestos and other waste. Available in a variety of sizes, thickness, colors and printing. Bags are packaged on a roll and perforated for dispensing ease. In flat or gusset form, depending on bag size. Durapax disposal bags are extruded from resins that have exceptional strength, tear and puncture resistance for the most demanding waste disposal applications.



durapax
disposal bags are available
standard in clear, yellow and
black, with and without
printing, in sizes from 30"x40"
to 60"x72".
Other sizes, gauges, printing
and color combinations are
available as special order,
please contact your authorized
Grayling distributor for more
information.



Available in these stock sizes-

Description	Size	Part Number	Count	Weight
Clear/Printed	30" X 40"	02213040	100	30
Clear/Unprinted	30" X 40"	02203040	100	30
Clear/Printed	30" X 40" X 6mil	022130406	75	36
Clear/Printed	33" X 50"	02213350	100	41
Clear/Unprinted	33" X 50"	02203350	100	41
Clear/Printed	33" X 50" X 6mil	022133506	75	49
Clear/Unprinted	33" X 50" X 6mil	022033506	75	49
Clear/Printed	38" X 63"	02213863	75	45
Clear/Unprinted	38" X 63"	02203863	75	45
Clear/Printed	38" X 63" X 6mil	022138636	50	48
Clear/Unprinted	38" X 63" X 6mil	022038636	50	48
Clear/Printed	60" X 72"	02216072	50	58
Black/Printed	30" X 40"	02113040	100	30
Black/Unprinted	30" X 40"	02103040	100	30
Black/Printed	30" X 40" X 6mil	021130406	75	36
Black/Printed	33" X 50"	02113350	100	41
Black/Printed	33" X 50" X 6mil	021133506	75	50
Black/Printed	36" X 60"	02113660	75	41
Black/Unprinted	36" X 60"	02103660	75	41
Black/Printed	36" X 60" X 6mil	021136606	50	43
Black/Unprinted	36" X 60" X 6mil	021036606	50	43
Yellow/Printed	33" X 50" X 6mil	023133506	75	50

Other sizes, case quantities and mil gauges are available. 150 case minimum order quantity for special order bags.

**FOR YOUR LOCAL DISTRIBUTOR
CALL 800-635-1551**



Grayling Industries, Inc.
1000 Branch Drive

Section 10

Project Notifications

ODH and OEPA Notifications shall be submitted prior job startup.

Section 11

Clearance Sampling Plan