

### UNITED STATES ENVIRONMENTAL PROTECTION AGENCY REGION III 1650 Arch Street Philadelphia, Pennsylvania 19103

#### UNDERGROUND INJECTION CONTROL PERMIT NUMBER <u>PAS2D020BCLE</u> AUTHORIZATION TO OPERATE A CLASS IID INJECTION WELL

In compliance with provisions of the Safe Drinking Water Act, as amended, (42 U.S.C. §§ 300f-300j-11, commonly known as the SDWA), the Resource Conservation and Recovery Act (42 U.S.C. –§§ 6901-6991i, commonly known as RCRA) and attendant regulations promulgated by the U. S. Environmental Protection Agency under Title 40 of the Code of Federal Regulations,

#### Windfall Oil and Gas 305 Chan Road Falls Creek, PA 15840

is authorized by this permit to construct a Class II-D injection well, the Zelman #1, and inject fluids produced in association with oil and gas production into the Huntersville Chert/Oriskany formation in accordance with the conditions set forth herein. The injection well is located in Brady Township, Clearfield County, PA. The coordinates for this injection well are: Latitude 41° 04' 55.0" and Longitude -78° 44' 48.95".

All references to Title 40 of the Code of Federal Regulations are to all regulations that are in effect on the date that this permit is effective.

This permit shall become effective on \_\_\_\_\_, 2020.

This permit and its authorization to inject shall remain in effect until midnight on

, 2030.

Catherine A. Libertz, Director Water Division

Printed on 100% recycled/recyclable paper with 100% post-consumer fiber and process chlorine free. Customer Service Hotline: 1-800-438-2474

## PART I

## A. Effect of Permit

Windfall Oil and Gas Inc. ("the Permitee") is allowed to engage in underground injection in accordance with the conditions of this permit. The underground injection activity, otherwise authorized by this permit, shall not allow the movement of fluid containing any contaminant into underground sources of drinking water (USDW), if the presence of that contaminant may cause a violation of any primary drinking water regulation under 40 C.F.R. Part 141 or may otherwise adversely affect the health of persons. Any underground injection activity not authorized by this permit or otherwise authorized by rule is prohibited. Issuance of this permit does not convey property rights or mineral rights of any sort or any exclusive privilege; nor does it authorize any injury to persons or property, any invasion of other private rights, or any infringement of State or local law or regulations. Compliance with terms of this permit does not constitute a defense to any action brought under Part C and the imminent and substantial endangerment provisions in Part D of the Safe Drinking Water Act (SDWA) or any other common or statutory law for any breach of any other applicable legal duty.

## B. Permit Actions

This permit can be modified, revoked and reissued or terminated for cause as specified in 40 C.F.R. §§ 144.12, 144.39 and 144.40. Also, the permit is subject to minor modifications as specified in 40 C.F.R. § 144.41. The filing of a request for a permit modification, revocation and reissuance, or termination, or the notification of planned changes, or anticipated noncompliance on the part of the permittee shall not stay the applicability or enforceability of any permit condition.

## C. Severability

The provisions of this permit are severable, and if any provision of this permit or the permittee's application, dated April 2020 is held invalid, the remainder of this permit shall not be affected thereby.

## D. General Requirements

1. <u>Duty to Comply.</u> The permittee shall comply with all applicable UIC Program regulations and conditions of this permit, except to the extent and for the duration such noncompliance is authorized by an emergency permit issued under 40 C.F.R. § 144.34. Any permit noncompliance constitutes a violation of the SDWA and is grounds for enforcement action, permit termination, revocation and reissuance, modification, or for denial of a permit renewal application.

2. <u>Need to Halt or Reduce Activity Not a Defense.</u> It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

3. <u>Duty to Mitigate.</u> The permittee shall take all reasonable steps to minimize or correct any adverse impact on the environment resulting from noncompliance with this permit.

4. <u>Proper Operation and Maintenance.</u> The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control and related appurtenances which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance include effective performance, adequate funding, adequate operator staffing and training, adequate security at the facility to prevent unauthorized access and operation of the well and adequate laboratory and process controls, including appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facility or similar systems only when necessary to achieve compliance with the conditions of this permit.

5. <u>Duty to Provide Information</u>. The permittee shall furnish to the Director of the Water Division ("Director"), within a time specified by the Director, any information which the Director may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The permittee shall also furnish to the Director, upon request, copies of records required to be kept by this permit. If the permittee becomes aware of any incomplete or incorrect information in the Permit Application or subsequent reports, the permittee shall promptly submit information addressing these deficiencies.

6. <u>Inspection and Entry.</u> The permittee shall allow the Director, or an authorized representative, upon the presentation of credentials and other documents as may be required by law to:

a. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;

b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;

c. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and

d. Sample or monitor any substances or parameters at any location, at reasonable times, for the purposes of assuring permit compliance or as otherwise authorized by SDWA.

7. <u>Penalties</u>. Any person who violates a permit requirement is subject to civil penalties, fines and other enforcement actions under the SDWA and may be subject to the same such actions pursuant to RCRA. Any person who willfully violates permit conditions is subject to criminal prosecution.

8. <u>Transfer of Permits.</u> This permit is not transferable to any person except after notice is sent on EPA Form 7520 and approval is given by the Director and the requirements of 40 C.F.R. § 144.38 are satisfied. The Director may require modification or revocation of the permit to change the name of the permittee and incorporate such other requirements as may be necessary under the SDWA.

9. <u>Signatory Requirements.</u>

a. All reports required by this permit and other information requested by the Director shall be signed as follows:

(1) for a corporation, by a responsible corporate officer of at least the level of vice-president;

(2) for a partnership or sole proprietorship, by a general partner or the proprietor, respectively; or

(3) for a Municipality, State, Federal, or other public agency by either a principal executive or a ranking elected official.

b. A duly authorized representative of the official designated in paragraph a. above may also sign only if:

(1) the authorization is made in writing by a person described in paragraph a. above;

- (2) the authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as the position of plant manager, operator of a well or a well field, superintendent, or a position of equivalent responsibility. A duly authorized representative may thus be either a named individual or any individual occupying a named position; and
- (3) the written authorization is submitted to the Director.

c. If an authorization under paragraph b. of this section is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of paragraph b. of this section

must be submitted to the Director prior to or together with any reports, information or applications to be signed by an authorized representative.

d. Any person signing a document under paragraph a. or b. of this section shall make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person(s) who manage the system, or those persons directly responsible for gathering the information, the information submitted is to the best of my knowledge and belief, true accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

## 10. <u>Confidentiality of Information.</u>

a. In accordance with 40 C.F.R. Parts 2 (Public Information) and § 144.5, any information submitted to the Director pursuant to these permits may be claimed as confidential by the submitter. Any such claim must be asserted at the time of submission by stamping the words "confidential business information" on each page containing such information. If no claim is made at the time of submission, EPA may make the information available to the public without further notice. If a claim is asserted, the information will be treated in accordance with the procedures in 40 C.F.R. Part 2.

b. Claims of confidentiality for the following information will be denied:

(1) The name and address of any permit applicant or permittee.

(2) Information which deals with the existence, absence, or level of contaminants in drinking water.

11. <u>Reapplication</u>. If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee must submit a complete application for a new permit at least 180 days before this permit expires.

12. <u>State Laws.</u> Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any applicable State law or regulation.

## PART II

### A. General

Copies of all reports and notifications required by this permit shall be signed and certified in accordance with the requirements of Section D(9) of Part I of this permit and shall be submitted to the Director at the following address:

Source Water & UIC Section (3WD22) Drinking Water & Source Water Protection Branch U. S. Environmental Protection Agency Region 3 1650 Arch Street Philadelphia, Pennsylvania 19103

### B. Record Retention

1. The permittee shall retain records of all monitoring and other information required by this permit, including the following (if applicable), for a period of at least five years from the date of the sample, measurement, report or application, unless such records are required to be retained for a longer period of time under paragraph B.2 below. This period may be extended by request of the Director at any time.

a. All data required to complete the Permit Application form for this permit and any supplemental information submitted under 40 C.F.R. § 144.31.

b. Calibrations and maintenance records and all original strip chart recordings for continuous monitoring instrumentation.

c. Copies of all reports required by this permit.

2. The permittee shall retain records concerning the nature and composition of all injected fluids, as listed in Part II, paragraphs C.3. and C.4. of this permit, until three years after the completion of any plugging and abandonment procedures. After three years from the completion of plugging and abandonment, the permittee shall continue to retain these records unless the permittee delivers the records to the Director or obtains written approval from the Director to discard the records.

3. Records of monitoring information shall include:

- a. The date, exact place, and the time of sampling or measurements;
- b. The individual(s) who performed the sampling or measurements;
- c. A precise description of both sampling methodology and the handling (custody) of samples;

- d. The date(s) analyses were performed;
- e. The individual(s) who performed the analyses;
- f. The analytical techniques or methods used; and
- g. The results of such analyses.

4. Monitoring the nature of injected fluids shall comply with applicable analytical methods cited in Part II, paragraph C.1., below.

5. All environmental measurements required by the permit, including, but not limited to, measurements of pressure, temperature, mechanical integrity (as applicable) and chemical analyses shall be done in accordance with EPA guidance on quality assurance.

### C. Monitoring Requirements

1. Samples and measurements taken for the purpose of monitoring shall be representative of the monitored activity. The method used to obtain a representative sample of the fluid to be analyzed and the procedure for analysis of the sample shall be in accordance with test procedures approved under 40 C.F.R. § 136.3 unless otherwise approved by the Director. The permittee shall identify the types of tests and methods used to generate the monitoring data.

2. Injection pressure, annular pressure, flow rate and cumulative volume shall be observed and recorded continuously beginning on the date on which the well commences operation and concluding when the well is plugged and abandoned. The well shall be equipped with an automatic shut-off device which would be activated in the event of a mechanical integrity failure.

3. The permittee shall sample, analyze and record the nature of the injected fluid for the parameters listed below at the initiation of the injection operation and every year thereafter, or whenever the operator observes or anticipates a change in the injection fluid (see condition C.4. below).

-pH	-Manganese
-Specific Gravity	-Total Dissolved Solids
-Barium	-Hydrogen Sulfide
-Specific Conductance	-Sodium
-Iron	-Alkalinity
-Magnesium	-Hardness
-Chloride	-Total Organic Carbon (TOC)
-Dissolved Oxygen	

4. Samples of injected fluid shall be collected and analyzed from initial loads received from each disposal customer and each type of source (e.g., from different geologic

formations, geographic regions, etc). Minimum analyses of the fluid will include specific gravity, total dissolved solids, ph, and TOC. Any analysis of specific gravity greater than 1.26 and any analysis of TOC greater than 250 mg/l shall be reported to the Director within twenty-four (24) hours of the results.

5. The permittee shall maintain a record of every load of fluid received. The record shall include the hauler's name, the operator's name and the location from where the load was obtained, the volume of the load and whether the load of fluid delivered was a split load. If the load was a split load, each operator's name and location shall be listed and, if possible, the volumes of fluid received from each operator documented.

6. A demonstration of mechanical integrity in accordance with 40 C.F.R. § 146.8 shall, after the initial demonstration, be made at least once every two years. Subsequent two-year demonstrations shall be conducted no more than 30 days prior to the anniversary date of the previous test. In addition to the above requirement, a mechanical integrity test demonstration shall be conducted whenever protective casing or tubing is removed from the well, the packer is reseated, or a well failure is evident. The permittee may continue operation only if the permittee has successfully demonstrated to the Director the mechanical integrity of the permitted well. The permittee shall cease injection operations if a loss of mechanical integrity becomes evident or if mechanical integrity cannot be demonstrated. Any such test shall be conducted in keeping with the notification requirements of Permit Condition D.11. of Part II of this permit.

7. After the initial demonstration of mechanical integrity, a pressure fall-off test shall be run to better characterize the injection reservoir. The pressure fall-off test shall be run to determine the reservoir's geologic characteristics, obtain a bottom-hole pressure and determine the type of flow conditions exhibited by the well during operation. If the results of the pressure fall-off testing determine that the geologic values used to calculate the permitted maximum injection pressure and the injection well's projected zone of endangering influence are significantly different, recalculation of these conditions will occur and the conditions in the permit will be changed accordingly. Subsequent annual pressure fall-off testing shall be conducted no more than 30 days prior to the anniversary date of the previous test.

D. Reporting and Notification Requirements.

1. <u>Report on Permit Review.</u> Within 30 days of receipt of this permit, the permittee shall report to the Director that the permittee has read and is personally familiar with all terms and conditions of this permit.

2. <u>Commencing Injection</u>. The operator of an injection well may not commence injection until construction or well rework is complete and all of the following conditions have been satisfied:

a. The permittee has submitted the results of the pressure fall-off testing, including the determination of bottom-hole pressure and whether any linear flow exists, has

demonstrated to EPA that the injection well has mechanical integrity in accordance with 40 C.F.R. § 146.8 and the permittee has received written notice from the Director that the results of the testing and the mechanical integrity demonstration are satisfactory;

b. The permittee has submitted notice of completion of construction (EPA Form 7520-18) to the Director; and

c.(1) The Director has inspected or otherwise reviewed the new injection well and finds it is in compliance with the conditions of the permit; or

c.(2) The permittee has not received notice from the Director of his or her intent to inspect or otherwise review the new injection well within 13 days of the date of the notice in paragraph (a) of this permit condition, in which case, prior inspection or review is waived and the permittee may commence injection.

## 3. <u>Twenty-four Hour Reporting.</u>

a. The permittee shall report to the Director any noncompliance which may endanger health or the environment. Such report shall be provided orally to the Senior Permit Specialist of the Source Water & UIC Section (currently, Kevin Rowsey, 215-814-5463) or to the Senior Field Inspector for the Source Water & UIC Section (currently, David Rectenwald, 814-827-1952) within 24 hours from the time the permittee becomes aware of the circumstances. The following shall be included as information which must be reported orally within 24 hours:

(1) Any monitoring or other information which indicates that any contaminant may cause an endangerment to an underground source of drinking water.

(2) Any noncompliance with a permit condition, or malfunction of the injection system which may cause fluid migration into or between underground sources of drinking water, or failure of mechanical integrity test demonstrations.

b. A written submission shall also be provided within five days of the time the permittee becomes aware of the circumstances. The written submission shall contain a description of the noncompliance and its cause; the period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.

4. <u>Anticipated Noncompliance.</u> The permittee shall give advance notice to the Director of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.

5. <u>Other Noncompliance</u>. The permittee shall report all other instances of noncompliance in writing within ten (10) days of the time the permittee becomes aware of the circumstances. The reports shall contain the information listed in Permit Condition D.3., of Part II of this permit.

6. <u>Planned Changes.</u> The permittee shall give notice to the Director as soon as possible of any planned physical alterations or additions to the permitted facility.

7. <u>Conversion</u>. The permittee shall notify the Director thirty days prior to the conversion of the well to an operating status other than an injection well.

8. <u>Annual Report.</u> The permittee shall submit an Annual Report to the Director summarizing the results of the monitoring and testing required by Permit Condition C within Part II of this permit. This report shall include monthly monitoring records of injected fluids, the results of any mechanical integrity testing and pressure fall-off testing, and any major changes in characteristics or sources of injected fluids. The permittee shall complete and submit this information with its Annual Report EPA Form 7520-11 (Annual Disposal/Injection Well Monitoring Report). The Annual Report shall be submitted not later than January 31st of each year, summarizing the activity of the calendar year ending the previous December 31st.

9. <u>Plugging and Abandonment Reports and Notifications.</u>

a. The permittee shall notify the Director 45 days before the plugging and abandonment of the well. The Director may allow a shorter notice period upon written request.

b. Revisions to the Plugging and Abandonment Plan must be submitted to the Director no less than 45 days prior to plugging and abandonment on EPA Plugging and Abandonment Form 7520-19. The Director must approve the revisions prior to the start of plugging operations.

c. Within 60 days after plugging the well, the permittee shall submit a report to the Director which shall consist of either:

(1) A statement that the well was plugged in accordance with the plan previously submitted to and approved by the Director; or

(2) Where actual plugging differed from the plan previously submitted, an updated version of the plan, on the form supplied by the Director, specifying the different procedures used.

The report shall be certified as accurate by the person who performed the plugging operation.

10. <u>Compliance Schedules.</u> Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 30 days following each schedule date.

11. <u>Mechanical Integrity Tests.</u> The permittee shall notify the Director of his or her intent to conduct a mechanical integrity test at least 30 days prior to such a demonstration.

12. <u>Cessation of Injection Activity.</u> After a cessation of injection for two years the owner or operator shall plug and abandon the well in accordance with the Plugging and Abandonment Plan unless he:

a. Provides notice to the Director; and

b. Describes actions or procedures, satisfactory to the Director, which the permittee will take to ensure that the well will not endanger USDWs during the period of temporary abandonment. These actions and procedures shall include compliance with the technical requirements applicable to an active injection well unless waived in writing by the Director.

E. Mechanical Integrity Standards

1. <u>Standards.</u> The permittee shall have and maintain the mechanical integrity of the permitted injection well pursuant to 40 C.F.R. § 146.8.

2. <u>Request from Director.</u> The Director may, by written notice, require the permittee to demonstrate mechanical integrity at any time.

## PART III

A. Construction Requirements

1. Notwithstanding any other provision of this permit, the injection well shall inject only into formations which are separated from any underground source of drinking water by a confining zone that is free of known open faults or fractures within the Area of Review.

2. <u>Casing and Cementing.</u> The permittee shall case and cement the well to prevent the movement of fluids into or between underground sources of drinking water. The casing and cement used in the construction of the well shall be designed for the life expectancy of the well. Two ground water protective strings of casing shall be installed, one from the surface to a depth of approximately 170 feet and the other from the surface to a depth of 375 feet. Both of these casing strings will be cemented back to the surface. Surface casing shall also be installed to protect the lowermost underground source of drinking water. The surface casing shall be installed from the surface to a depth of approximately 1000 feet and cemented back to the

surface. The injection zone shall be isolated by the placement of long string casing to total depth, approximately 7300 feet, and cemented back to approximately 5000 feet below land surface. Injection shall occur through a tubing string and packer installed inside the long string casing and set above the injection zone.

3. Logs and Tests. The logs and tests listed below shall be conducted during the drilling and construction of the well or, in the event that the well is being converted to an injection well, obtain and submit the logs and tests from the well's original construction. A descriptive report interpreting the results (which specifically relate to (1) the lowermost underground source of drinking water and the confining zone adjacent to it and (2) the injection zone and adjacent formations) shall be prepared by a knowledgeable log analyst and submitted to the Director. At a minimum, such logs and or tests shall include the following:

- A cement bond log and variable density log or a cement evaluation log which documents the cemented portion of the long string casing.
- Drilling records or a log which documents the location of the surface casing.
- Records documenting the cementing of the ground water protective strings of casing and the surface casing.
- Gamma Ray logs which document the geologic formations in the wellbore.

4. <u>Mechanical Integrity</u>. Injection operations are prohibited until the permittee demonstrates that the well covered by this permit has mechanical integrity in accordance with 40 C.F.R. § 146.8 and the permittee has received notice from the Director that such a demonstration is satisfactory in accordance with the provisions of Condition D.2. found in Part II of this permit.

5. <u>Corrective Action.</u> If necessary, corrective action, in the form of plugging and abandoning wells within the one-quarter mile area of review, which could provide conduits for fluid migration into USDWs, will be completed prior to the authorization of injection. If an abandoned well is discovered within the one-quarter mile area of review after injection commences, the permittee shall notify the Director upon discovery, and within five (5), days submit to the Director for approval a plan for corrective action and implement the approved plan.

B. Operating Requirements

1. <u>Injection Formation.</u> Injection shall be limited to the Huntersville Chert/Oriskany Formation in the subsurface interval between approximately 7300 feet and 7387 feet.

2. <u>Injection Fluid</u>. The permittee shall not inject any hazardous substances, as defined by 40 C.F.R. 261, or any other fluid, other than the fluids produced solely in association with oil and gas production operations.

3. <u>Injection Volume Limitation.</u> Injection volume shall not exceed 30,000 barrels per month.

4. <u>Injection Pressure Limitation</u>. Injection pressure shall not exceed a surface injection pressure maximum of 2443 psi and a bottom hole pressure maximum of 6425 psi. These pressure calculations are based on the specific gravity of the injection fluid not exceeding 1.26 and a formation depth of 7306 feet. If the specific gravity of the injection fluid should exceed 1.26 or the top of the formation's injection depth is greater than 7306 feet, then the surface injection pressure must be revised downward so that the bottom-hole maximum injection pressure does not exceed 6425 psi. Injection at a pressure which initiates new fractures or propagates existing fractures in the confining zone adjacent to underground sources of drinking water or causes the movement of injection or formation fluids into an underground source of drinking water is prohibited.

5. Injection between the outermost casing protecting underground sources of drinking water and the well bore is prohibited, as is injection into any USDW.

C. Plugging and Abandonment

1. The permittee shall plug and abandon the well in accordance with the approved plugging and abandonment plan, EPA Form 7520-19, provided as Attachment 1 in the permit.

2. Plugging and abandonment shall be conducted in such a manner that movement of fluids will not be allowed into or between underground sources of drinking water.

D. Financial Responsibility

The permittee shall maintain financial responsibility and resources to close, plug and abandon the underground injection well in accordance with 40 C.F.R. Section 144.52(a)(7) in the amount of at least \$30,000. If the circumstances regarding the acceptability of the Letter of Credit and Standby Trust Agreement submitted to EPA to demonstrate financial responsibility should change, the permittee shall provide advance notification to the Director, and the Director may seek an alternative financial demonstration from the permittee.

The permittee shall not substitute an alternative demonstration of financial responsibility for that which the Director has approved, unless the permittee has previously submitted evidence of that alternative demonstration to the Director and the Director notifies him or her that the alternative demonstration of financial responsibility is acceptable. The Director may require the permittee to submit a revised demonstration of Financial Responsibility if the Director has reason to believe that the original demonstration is no longer adequate to cover the costs of plugging and abandonment.

## ATTACHMENT 1

## PLUGGING & ABANDONMENT PLAN

			OND I	No. 2040-0042	Approval Explica	\$ 4/30/2022
		United Sta	ates Environmental Prote	ection Agency		
<b>\$EPA</b>	WELL REWO	ORK RECORD	, PLUGGING A	ND ABA	NDONMEN	T PLAN,
			ND ABANDON	NMENT A	FFIDAVIT	
lame and Address Windfall Oil and	, Phone Number and/or Email of F	Permittee	an anna an Anna a' casta stat	i e fan i eine de fan i ferster en de je		in an internet and a state of the
	d, Falls Creek PA 15840					
814-771-9686						
mhoov16@veri	izon.net					
	Ny mandrid Name and Anna and A	and a second	و المراجع		an a	a na far san shi na mara na mar
Permit or EPA ID	and the second	API Number	a se a companya a serie	Contraction of the second second second	/ell Name	
PAS2D020BCI		37-033-27255-00	)-00	Frank	k & Susan Zelma	n
State	al et andre et al andre en al antiste andre en al andre en andre et al andre et al andre et al andre et al andr	and the second	County		erences and some bade and the state of the state	and a second reaction of the second se
PA	n an	a dala a se angla ang katalan ang katalan katalan se ang katalan katalan se ang	Clearfield	$\mathbf{r} = \mathbf{r} = \left( \mathbf{r} \right) = \left( \mathbf{r} \right) = \left( \mathbf{r} \right)^{1/2} \left( \mathbf{r} \right)^{1/2$	tation), in particul state of addition programming on	and an an address of the second state of the state of the second s
Locate well in two	o directions from nearest lines o	f quarter section and d	rilling unit Latitu	de 41.08194	14	
Surface Location				An one report of reserve		ana Sala
1/4 of	1/4 of Section	Township R	ange	de -78.7469	31	-
(managed by proceeding)	and instant of the solution of the	and a second	and a second sec			
Lotte a prospine o sea arrange of an in	rom (N/S) Line of quar	ter section				
ft. f	rom (E/W) Line of quar	ter section.				
Well Class	Timing of Action (pick one)				Type of Action (	pick one)
Class I	V Notice Prior to Work				Well Rewor	k
V Class II	Date Expected to Comm	ence			in the second	
					Plugging ar	nd Abandonment
Class III	3					
C BY BUT	Report After Work				Conversion	to a Non-Injection Well
Class III Class V	Report After Work Date Work Ended		1		Conversion	to a Non-Injection Well
A State of the second s	See 11414				Conversion	to a Non-Injection Well
Class V	See 11414	t to be performed, or th	at was performed. Use ad	ditional pages	-tower al	-
Class V	Date Work Ended		-	to month the many spectrum term in a comparison	-tower al	-
Class V	Date Work Ended		at was performed. Use ad Or Zelman Injectio	to month the many spectrum term in a comparison	- Lance L	-
Class V Provide a narrativ	Date Work Ended	P&A plan f	-	to month the many spectrum term in a comparison	- Lance L	-
Class V Provide a narrativ	Date Work Ended	P&A plan f	or Zelman Injectio	to month the many spectrum term in a comparison	- Lance L	
Class V Provide a narrativ Provide Sp	Date Work Ended we description of the work planned all packer and re-run tub pot plug #1: 176 sx class	P&A plan f	or Zelman Injectio	to month the many spectrum term in a comparison	- Lance L	
Class V Provide a narrativ Provide Sp Sta	Date Work Ended we description of the work planned all packer and re-run tub pot plug #1: 176 sx class and back tubing	P&A plan f ing string to TD A cement from 7	or Zelman Injectio	to month the many spectrum term in a comparison	- Lance L	
Class V Provide a narrativ Pu Sp Sta Cu	Date Work Ended we description of the work planned all packer and re-run tub pot plug #1: 176 sx class and back tubing at 4 ½ casing at 5000' and	P&A plan f ing string to TD A cement from 7	or Zelman Injectio	to month the many spectrum term in a comparison	- Lance L	
Class V Provide a narrativ Pu Sp Sta Cu La	Date Work Ended we description of the work planned all packer and re-run tub pot plug #1: 176 sx class and back tubing at 4 ½ casing at 5000' and y down 4 ½ casing	P&A plan f ing string to TD A cement from 7 d gel hole	or Zelman Injectio 388-5000'	n Well	as necessary. See in	astructions.
Class V Provide a narrativ Pu Sp Sta Cu La Ru	Date Work Ended we description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing at 4 ½ casing at 5000' and y down 4 ½ casing an tubing 3300' and spot	P&A plan f ing string to TD A cement from 7 d gel hole the following ce	or Zelman Injectio 388-5000'	n Well	as necessary. See in	astructions.
Class V Provide a narrativ Pu Sp Sta Cu La Ru Plu	Date Work Ended we description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing it 4 ½ casing at 5000' and y down 4 ½ casing in tubing 3300' and spot ug #2: 29 sx of cement f	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200'	or Zelman Injectio 388-5000'	n Well	as necessary. See in	astructions.
Class V Provide a narrativ Pu Sp Sta Cu La Ru Plu Plu	Date Work Ended we description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing ut 4 ½ casing at 5000' and y down 4 ½ casing un tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900	or Zelman Injectio 388-5000'	n Well	as necessary. See in	astructions.
Class V Provide a narrativ Pu Sp Sta Cu La Ru Plu Plu Plu	Date Work Ended we description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing it 4 ½ casing at 5000' and y down 4 ½ casing in tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900 rom 2600-2500	or Zelman Injectio 388-5000'	n Well	as necessary. See in	astructions.
Class V Provide a narrativ Sp Sta Cu La Ru Plu Plu Plu Plu	Date Work Ended we description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing ut 4 ½ casing at 5000' and y down 4 ½ casing un tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900 rom 2600-2500 rom 1050-950	or Zelman Injectio 388-5000'	n Well	as necessary. See in	astructions.
Class V Provide a narrativ Sp Sta Cu La Ru Plu Plu Plu Plu	Date Work Ended We description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing it 4 ½ casing at 5000' and y down 4 ½ casing in tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr ug #5: 60 sx of cement fr	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900 rom 2600-2500 rom 1050-950	or Zelman Injectio 388-5000'	n Well	as necessary. See in	astructions.
Class V Provide a narrativ Sp Sta Cu La Ru Plu Plu Plu Plu	Date Work Ended We description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing it 4 ½ casing at 5000' and y down 4 ½ casing in tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr ug #5: 60 sx of cement fr	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900 rom 2600-2500 rom 1050-950	or Zelman Injectio 388-5000'	n Well	as necessary. See in	astructions.
Class V Provide a narrativ Sp Sta Cu La Ru Plu Plu Plu Plu	Date Work Ended We description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing it 4 ½ casing at 5000' and y down 4 ½ casing in tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr ug #5: 60 sx of cement fr	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900 rom 2600-2500 rom 1050-950 -surface	or Zelman Injectio 388-5000' ment plugs with 6	n Well	as necessary. See in	astructions.
Class V Provide a narrativ Pu Sp Sta Cu La Ru Plu Plu Plu Ba	Date Work Ended we description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing it 4 ½ casing at 5000' and y down 4 ½ casing in tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr ug #5: 60 sx of cement fr il 8 5/8 casing from 950	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900 rom 2600-2500 rom 1050-950 -surface	or Zelman Injectio 388-5000' ment plugs with 6	n Well % gel plugs	as necessary. See in	n cement plug
Class V Provide a narrativ Pu Sp Sta Cu La Ru Plu Plu Ba	Date Work Ended We description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing it 4 ½ casing at 5000' and y down 4 ½ casing in tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr ug #5: 60 sx of cement fr	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900 rom 2600-2500 rom 1050-950 -surface Ce personally examined a	or Zelman Injectio 388-5000' ment plugs with 6 ment plugs with 6	n Well % gel plugs	as necessary. See in s between each	n cement plug
Class V Provide a narrativ Pu Sp Sta Cu La Ru Plu Plu Ba	Date Work Ended we description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing ut 4 ½ casing at 5000' and y down 4 ½ casing un tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr ug #5: 60 sx of cement fr til 8 5/8 casing from 950-	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 300-2900 rom 2600-2500 rom 1050-950 -surface Ce personally examined a of those individuals in	or Zelman Injectio 388-5000' ment plugs with 6 rtification nd am famillar with the I	n Well % gel plugs	as necessary. See in s between each	n cement plug
Class V Provide a narrativ Pu Sp Sta Cu La Ru Plu Plu Plu Ba	Date Work Ended we description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing it 4 ½ casing at 5000' and y down 4 ½ casing in tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr il 8 5/8 casing from 950- der the penalty of law that I have ts and that, based on my inquiry n is true, accurate, and complete. of fine and imprisonment. (Ref.	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900 rom 2600-2500 rom 1050-950 -surface Ce personally examined a of those individuals im I am aware that there 40 CFR § 144.32)	or Zelman Injectio 388-5000' ment plugs with 6 rtification nd am famillar with the I mediately responsible for are significant penalties	n Well % gel plugs	as necessary. See in s between each	ment and all eve that the including the
Class V Provide a narrativ Pu Sp Sta Cu La Ru Plu Plu Plu Ba	Date Work Ended We description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing It 4 ½ casing at 5000' and y down 4 ½ casing In tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr il 8 5/8 casing from 950- der the penalty of law that I have ts and that, based on my inquiry n is true, accurate, and complete of fine and imprisonment. (Ref. al Title ( <i>Please type or print</i> )	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 300-2900 rom 2600-2500 rom 1050-950 -surface Ce personally examined a of those individuals in	or Zelman Injectio 388-5000' ment plugs with 6 rtification nd am famillar with the I mediately responsible for are significant penalties	n Well % gel plugs	as necessary. See in s between each	ment and all eve that the including the Date Signed
Class V Provide a narrativ Pu Sp Sta Cu La Ru Plu Plu Plu Ba	Date Work Ended we description of the work planned all packer and re-run tub bot plug #1: 176 sx class and back tubing it 4 ½ casing at 5000' and y down 4 ½ casing in tubing 3300' and spot ug #2: 29 sx of cement fr ug #3: 29 sx of cement fr ug #4: 29 sx of cement fr il 8 5/8 casing from 950- der the penalty of law that I have ts and that, based on my inquiry n is true, accurate, and complete. of fine and imprisonment. (Ref.	P&A plan f ing string to TD A cement from 7 d gel hole the following ce rom 3300-3200' rom 3000-2900 rom 2600-2500 rom 1050-950 -surface Ce personally examined a of those individuals im I am aware that there 40 CFR § 144.32)	or Zelman Injectio 388-5000' ment plugs with 6 rtification nd am famillar with the I mediately responsible for are significant penalties	n Well % gel plugs	as necessary. See in s between each	n cement plug

#### 3/5/2020 Zelman#1 Injection Well

# ZELMAN POST PLUG & ABANDONMENT SCHEMATIC

Elevation 1697'

