

217/782-2113

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT - REVISED

PERMITTEE

Hamilton Sundstrand
Attn: Larry Carlson
4747 Harrison Avenue
P.O. Box 7002
Rockford, Illinois 61125-7002

Application No.: 73110059

I.D. No.: 201030AEV

Applicant's Designation:

Date Received: December 11, 1998

Subject: FESOP

Date Issued: January 7, 1999

Expiration Date: March 26, 2001

Location: 4747 Harrison Avenue, Rockford

This permit is hereby granted to the above-designated Permittee to OPERATE emission source(s) and/or air pollution control equipment consisting of External Combustion Group A emission units (Plant 6 and Plant 8 boilers, water heaters, air heaters, super heaters and large and small afterburners); External Combustion Group B emission units (Plant 3, Plant 9 and Plant 19 boilers, water heaters and space heaters); six Waukesha internal combustion engines, a monopropellant engine test stand with a large afterburner from Combustion Group A, orbiter/booster test stands with small afterburners from Combustion Group A, an aircraft starter/APU testing unit, a diesel fired emergency generator, a natural gas fired emergency generator, an emergency fire pump and a propane-fired steam cleaner; also Plant 6 surface coating operations (paint spray booths and associated equipment) and cleaning operations (vapor degreasing, cold cleaning, etc.); and miscellaneous operations (air stripper, storage tanks, welding, packaging foam and cooling towers) pursuant to the above-referenced application. This Permit is subject to standard conditions attached hereto and the following special condition(s):

- 1a. This federally enforceable state operating permit is issued to limit the emissions of air pollutants from the source to less than major source thresholds (i.e., 100 tons/year for nitrogen oxides, 100 tons/year for carbon monoxide, 100 tons/year for VOM, 25 tons/year for combined HAPs and 10 tons/year for an individual HAP). As a result the source is excluded from the requirements to obtain a Clean Air Act Permit Program permit. The maximum emissions of this source, as limited by the conditions of this permit, are described in Attachment A.
- b. Prior to issuance, a draft of this permit has undergone a public notice and comment period.
- c. This permit supersedes all operating permits issued for this location.

2a. Emissions and operation of external combustion units shall not exceed the following limits:

i.

<u>Item of Equipment</u>	Total Fuel		E M I S S I O N S			
	Heat Content*		NO _x		CO	
	(mmBtu/Mo)	(mmBtu/Yr)	(Lb/Mo)	(T/Yr)	(Lb/Mo)	(T/Yr)

External Combustion						
Group A	21,600	86,600	3,100	6.2	800	1.6

* Dual fuel capacity assuming 1000 Btu/scf for natural gas and 140,000 Btu/gal for fuel oil

Total fuel Heat Content = 1000 x Quantity of Natural Gas consumed (scf/mo) + 140000 x Quantity of Fuel Oil consumed (gal/mo)

The Emissions of NO_x and CO are based on Standard AP-42 emission factors for natural gas and fuel oil combustion.

ii.

<u>Item of Equipment</u>	Natural Gas Usage		E M I S S I O N S			
			NO _x		CO	
	(mmscf/Mo)	(mmscf/Yr)	(Lb/Mo)	(T/Yr)	(Lb/Mo)	(T/Yr)

External Combustion						
Group B	5.4	21.5	540	1.1	108	0.2

Emissions of NO_x are based on the standard AP-42 emission factor of 100 lb/mmcf.

iii.

<u>Item of Equipment</u>	Jet Fuel Usage		E M I S S I O N S			
			NO _x		CO	
	(Gal/Mo)	(Gal/Yr)	(Lb/1000 Gal)	(T/Yr)	(Lb/1000 Gal)	(T/Yr)

Aircraft						
Starter/						
APU Testing	450	1,750	28	0.03	413	0.36

iv.

<u>Item of Equipment</u>	Horsepower Rating (Hp)	Hours of Operation (Hr/Yr)	E M I S S I O N S			
			NO _x		CO	
			(gr/Hp-Hr)	(T/Yr)	(gr/Hp-Hr)	(T/Yr)

Waukesha I.C.E.s	1,470 (ea.)	5,263	10	85.2	10	85.2
Emergency Generator	305	75	14.0	0.4	3.03	0.1
Emergency Fire Pump	115	75	14.0	0.2	3.03	0.1
Emergency Generator	400	50	19.5	0.6	0.9	0.2

v.	<u>Item of Equipment</u>	Hours of Operation <u>(Hr/Yr)</u>	E M I S S I O N S			
			NO _x <u>(Lb/Hr)(T/Yr)</u>		CO <u>(Lb/Hr)(T/Yr)</u>	
	Monopropellant Engine Test Stand - Mode 1	25	115.5	1.5	0.9	0.1
	Monopropellant Engine Test Stand - Mode 2	25	N/A	N/A	67.1	0.9
	Orbiter/Booster Test Stands (Sea Level)	40	10.1	0.2	----	---

vi.	<u>Item of Equipment</u>	Hours of Operation <u>(Hr/Yr)</u>	LPG Usage <u>(Gal/Hr)</u>	E M I S S I O N S			
				NO _x <u>(Lb/1000 Gal)(T/Yr)</u>		CO <u>(Lb/1000 Gal)(T/Yr)</u>	
	Propane Fired Steam Cleaner	75	4.6	14	0.1	1.9	0.1

b. Compliance with annual limits shall be determined from a running total of the data for the current month and the previous 11 months of data.

3a. i. Emissions and operation of coating and cleaning shall not exceed the following limits:

<u>Process</u>	<u>Material</u>	Usage Rate		Maximum	VOM	
		<u>(Gal/Mo)</u>	<u>(Gal/Yr)</u>	VOM Content*	Emissions	
				<u>(Lb/Gal)</u>	<u>(Lb/Mo)</u>	<u>(T/Yr)</u>
Surface Coating Operations	Paints & Thinner	175	1,750	7.00	1,225	6.1
Cleanup	MEK & Methanol	180	1,760	6.71	1,208	5.9
Cold Cleaning**	Cleaning Solvent	5,000	50,000	6.67	3,335	16.7
IPA Vapor Degreasing	Isopropanol	550	5,500	6.59	3,625	18.1
Vapor Degreasing/ Cold Cleaning	1-Bomopropane	342	4,104	11.25	3,848	23.1
Vapor Degreasing	Cyclohexane	100	1,200	6.50	650	3.9

* Minus water and exempt compounds

** Emissions assumed to be 10% of solvent used (based on in-house data)

ii. Emissions of VOM from miscellaneous activities (i.e., the gasoline, waste oil, fuel oil and JP-4), storage tanks, welding and packaging foam shall not exceed: 2.0 tons/year.

b. Compliance with annual limits shall be determined from a running total of the current month and the previous 11 months of data.

4. The emissions of Hazardous Air Pollutants (HAPs) as listed in Section 112(b) of the Clean Air Act shall not equal or exceed 10 tons per year of any single HAP or 25 tons per year of any combination of such HAPs, or such lesser quantity as USEPA may establish in rule which would require the Permittee to obtain a CAAPP permit from the Illinois EPA. As a result of this condition, this permit is issued based on the emissions of any HAP from this source not triggering the requirement to obtain a CAAPP permit from the Agency.
- 5a. The Permittee shall maintain monthly records of the following:
 - i. Usage rates of natural gas and distillate fuel oil for External Combustion Group A (mmscf/mo and gal/mo).
 - ii. Total combined heat content of both natural gas and fuel oil, calculated using the usage rates in (i) and the heat contents of natural gas (1000 Btu/scf) and fuel oil (140,000 Btu/gal).
 - iii. Usage rate of natural gas for External Combustion Group B (mmscf/mo).
 - iv. Jet Fuel usage for the Aircraft Starter/APU Testing (gal/mo).
 - v. Hours of operation for the Monopropellant Engine Test Stand the Orbiter/Booster Test stands, the emergency pumps/generators and the steam cleaner (hours/mo).
 - vi. Usage rates and VOM content of all paints and thinners, (gal/mo and lb VOM/gal).
- b. The Permittee shall maintain monthly records of the following items for the degreasers:
 - i. Solvent usage (U) in gallons/month and gallons/year.
 - ii. Virgin solvent added to the degreasers (V) in gallons/month and gallons/year, as determined by daily addition log sheets.
 - iii. Waste solvent removed from the degreasers (W) in gallons/month and gallons/year.
 - iv. Analysis sheet(s) showing test results and any calculations used to determine percent concentration of solvent in waste (P) for each month or each year.
 - v. Emissions of VOM and HAPs in tons/month.
 - vi. Emissions of VOM and HAPs in tons/yr (i.e., running 12 month total).
- c. The Permittee shall maintain records of the sulfur content of each fuel oil shipment for boiler operation.

6. All records and logs required by this permit shall be retained at a readily accessible location at the source for at least three years from the date of entry and shall be made available for inspection and copying by the Illinois EPA or USEPA upon request. Any records retained in an electronic format (e.g., computer) shall be capable of being retrieved and printed on paper during normal source office hours so as to be able to respond to an Illinois EPA or USEPA request for records during the course of a source inspection.
7. If there is an exceedance of the requirements of this permit as determined by the records required by this permit, the Permittee shall submit a report to the Illinois EPA's Compliance Section in Springfield, Illinois within 30 days after the exceedance. The report shall include the emissions released in accordance with the recordkeeping requirements, a copy of the relevant records, and a description of the exceedance or violation and efforts to reduce emissions and future occurrences.
8. All reports, notifications, etc., required by this permit shall be sent to:

 Illinois EPA
 Bureau of Air
 Compliance Section (#40)
 P.O. Box 19276
 Springfield, Illinois 62794-9276

 and

 Illinois Environmental Protection Agency
 Division of Air Pollution Control - Regional Office
 5415 North University
 Peoria, Illinois 61614
- 9a. The afterburner combustion chamber shall be preheated to the manufacturer's recommended temperature but not lower than 1525°F, before the testing process is begun; this temperature shall be maintained during the testing process.
- b. The afterburner shall be equipped with a continuous temperature indicator and strip chart recorder or disk storage for the afterburner combustion chamber temperature. The Permittee shall retain all records of equipment operation and strip charts or disk storage for at least one year. These records shall be available for inspection by the Agency.
- 10a. This permit is issued based on the plant meeting the exemption requirements of 35 Ill. Adm. Code Part 215, Subpart F, i.e., actual VOM emissions of the plant as addressed by this permit are 25 tons/year or less, in the absence of air pollution control equipment.

- b. i. If the annual emissions of VOM exceed 25 tons in a calendar year, the Permittee's coating operations are subject to the emission limitations of Part 215, Subpart F, e.g., the VOM content of extreme performance coatings applied to miscellaneous metal parts and products shall not exceed 3.5 lb/gallon.
 - ii. By March 1 following a calendar year in which plant VOM emissions exceed 25 tons, the Permittee shall submit a report addressing compliance with Part 215, Subpart F, including a listing of coatings at the plant subject to Subpart F, the typical usage of each coating and the VOM content as applied.
 - c. This permit is issued based on the cold cleaning and vapor degreasers meeting the specific operating requirements of 35 Ill. Adm. Code, Part E, Sections 215.181, 215.182 and 215.183.
11. The Permittee shall submit the following additional information with the Annual Emission Report, due May 1st of each year: type of fuel and fuel usage rates and paint/thinner/solvent usage for the prior calendar year. If there have been no exceedances during the prior calendar year, the Annual Emission Report shall include a statement to that effect.
12. This permit is being issued based on the "patch test" process meeting the exemption requirements specified in 35 Ill. Adm. Code 215.181(b). As a result, the emissions from the "patch test" process shall not exceed 800 pounds in any calendar month.

It should be noted that this permit has been revised to incorporate construction permit 98050017, which consists of a modification to a vapor degreaser.

If you have any questions on this, please call Jason Schnepf at 217/782-2113.

Donald E. Sutton, P.E.
Manager, Permit Section
Division of Air Pollution Control

DES:JMS:jar

cc: Region 2

Attachment A

This attachment provides a summary of the maximum emissions from this facility operating in compliance with the requirements of this federally enforceable permit. In preparing this summary, the Agency used the annual operating scenario which results in maximum emissions from such a plant. This facility utilizes natural gas, fuel oil, coatings, etc. so as not to exceed specified emission thresholds. The resulting maximum emissions are well below the levels, e.g., 100 tons/year for NO_x, CO and VOM at which this source would be considered a major source for purposes of the Clean Air Act Permit Program. Actual emissions from this source will be less than predicted in this summary to the extent that less material is handled and control measures are more effective than required in this permit.

1a. Emissions and operation of external combustion units shall not exceed the following limits:

i.		Total Fuel		E M I S S I O N S			
		Heat Content*		NO _x		CO	
	<u>Item of Equipment</u>	<u>(mmBtu/Mo)</u>	<u>(mmBtu/Yr)</u>	<u>(Lb/Mo)</u>	<u>(T/Yr)</u>	<u>(Lb/Mo)</u>	<u>(T/Yr)</u>
	External Combustion						
	Group A	21,600	86,600	3,100	6.2	800	1.6

* Dual fuel capacity assuming 1000 Btu/scf for natural gas and 140,000 Btu/gal for fuel oil

Total fuel Heat Content = 1000 x Quantity of Natural Gas consumed (scf/mo) + 140000 x Quantity of Fuel Oil consumed (gal/mo)

The Emissions of NO_x and CO are based on Standard AP-42 emission factors for natural gas and fuel oil combustion.

ii.		Natural Gas Usage		E M I S S I O N S			
				NO _x		CO	
	<u>Item of Equipment</u>	<u>(mmscf/Mo)</u>	<u>(mmscf/Yr)</u>	<u>(Lb/Mo)</u>	<u>(T/Yr)</u>	<u>(Lb/Mo)</u>	<u>(T/Yr)</u>
	External Combustion						
	Group B	5.4	21.5	540	1.1	108	0.2

Emissions of NO_x are based on the standard AP-42 emission factor of 100 lb/mmcf.

iii.		Jet Fuel Usage		E M I S S I O N S			
				NO _x		CO	
	<u>Item of Equipment</u>	<u>(Gal/Mo)</u>	<u>(Gal/Yr)</u>	<u>(Lb/1000 Gal)</u>	<u>(T/Yr)</u>	<u>(Lb/1000 Gal)</u>	<u>(T/Yr)</u>
	Aircraft						
	Starter/ APU Testing	450	1,750	28	0.03	413	0.36

iv.

<u>Item of Equipment</u>	Horsepower	Hours of	E M I S S I O N S			
	Rating	Operation	NO _x		CO	
	(Hp)	(Hr/Yr)	(gr/Hp-Hr)	(T/Yr)	(gr/Hp-Hr)	(T/Yr)
Waukesha I.C.E.s	1,470 (ea.)	5,263	10	85.2	10	85.2
Emergency Generator	305	75	14.0	0.4	3.03	0.1
Emergency Fire Pump	115	75	14.0	0.2	3.03	0.1
Emergency Generator	400	50	19.5	0.6	0.9	0.2

v.

<u>Item of Equipment</u>	Hours of	E M I S S I O N S			
	Operation	NO _x		CO	
	(Hr/Yr)	(Lb/Hr)	(T/Yr)	(Lb/Hr)	(T/Yr)
Monopropellant Engine Test Stand - Mode 1	25	115.5	1.5	0.9	0.1
Monopropellant Engine Test Stand - Mode 2	25	N/A	N/A	67.1	0.9
Orbiter/Booster Test Stands (Sea Level)	40	10.1	0.2	----	---

vi.

<u>Item of Equipment</u>	Hours of	LPG Usage	E M I S S I O N S			
	Operation		NO _x		CO	
	(Hr/Yr)	(Gal/Hr)	(Lb/1000 Gal)	(T/Yr)	(Lb/1000 Gal)	(T/Yr)
Propane Fired Steam Cleaner	75	4.6	14	0.1	1.9	0.1

b. Emissions and operation of coating and cleaning shall not exceed the following limits:

<u>Process</u>	<u>Material</u>	Usage Rate	Maximum		VOM		
			(Gal/Mo)	(Gal/Yr)	VOM Content*	Emissions	
			(Gal/Mo)	(Gal/Yr)	(Lb/Gal)	(Lb/Mo)	(T/Yr)
Surface Coating Operations	Paints & Thinner	175	1,750	7.00	1,225	6.1	
Cleanup	MEK & Methanol	180	1,760	6.71	1,208	5.9	
Cold Cleaning**	Cleaning Solvent	5,000	50,000	6.67	3,335	16.7	
IPA Vapor							
Degreasing	Isopropanol	550	5,500	6.59	3,625	18.1	
Vapor Degreasing/							
Cold Cleaning	1-Bomopropane	342	4,104	11.25	3,848	23.1	
Vapor Degreasing	Cyclohexane	100	1,200	6.50	650	3.9	

* Minus water and exempt compounds
 ** Emissions assumed to be 10% of solvent used (based on in-house data)

c. Emissions of VOM from miscellaneous activities (i.e., the gasoline, waste oil, fuel oil and JP-4), storage tanks, welding, cooling towers, stripping towers and packaging foam shall not exceed: 3.0 tons/year.

- d. i. Emissions of HAPs shall not exceed a combined total of 25 tons/year, or 10 tons/year for any individual HAP (see l.b. for MEK).

DES:JMS:jar

217/782-2113

October 15, 1999

Hamilton Sundstrand
Attn: Larry Carlson
4747 Harrison Avenue
P.O. Box 7002
Rockford, Illinois 61125-7002

I.D. No.: 201030AEV

Dear Mr. Carlson:

Enclosed is a revised permit letter which reflects only a change of ownership. Please note that if you have changed or intend to change this operation it will be necessary to apply for revision of your air pollution permit(s).

If you have any questions or require any assistance concerning these matters, contact Karen Luparell at 217/782-2113.

Very truly yours,

Donald E. Sutton, P.E.
Manager, Permit Section
Division of Air Pollution Control

DES:KJL:73110059:jar

Enclosure

cc: Region 2
I.D. File
Permit File