

217/782-2113

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT - NSPS SOURCE -- RENEWAL

PERMITTEE

Duraco, Inc.  
Attn: William Vasa  
7400 West Industrial Drive  
Forest Park, Illinois 60130

Application No.: 03120015

I.D. No.: 031090ACF

Applicant's Designation:

Date Received: January 7, 2009

Subject: Pressure Sensitive Tape Coaters

Date Issued:

Expiration Date:

Location: 7400 West Industrial Drive, Forest Park, Cook County, 60130

Permit is hereby granted to the above-designated Permittee to OPERATE emission unit(s) and/or air pollution control equipment consisting of two (2) pressure sensitive tape coater/laminators controlled by a permanent total enclosure and catalytic oxidizer, foam tape cutting/slitting, equipment solvent wipe cleaning and mold release operations, and two (2) ozone surface treatment generators as described in the above-referenced application. This Permit is subject to standard conditions attached hereto and the following special condition(s):

- 1a. This federally enforceable state operating permit is issued:
  - i. To limit the emissions of air pollutants from the source to less than major source thresholds (i.e., 100 tons/yr for Volatile Organic Material (VOM) and 10 tons/year for any single Hazardous Air Pollutant (HAP) and 25 tons/year for any combination of such HAPs). As a result, the source is excluded from the requirements to obtain a Clean Air Act Permit Program (CAAPP) permit. The maximum emissions of this source, as limited by the conditions of this permit are described in Attachment A.
  - ii. To limit the potential emissions of VOM from the source to less than 25 tons/year. As a result, the source is excluded from the requirement of 35 Ill. Adm. Code Part 205, Emission Reduction Market System. The maximum emissions of this source, as limited by the conditions of this permit, are described in Attachment A.
- b. Prior to issuance, a draft of this permit has undergone a public notice and comment period.
- c. This permit supersedes all operating permit(s) issued for this location.

- 2a. The two coating/laminating lines are subject to New Source Performance Standards (NSPS) for Pressure Sensitive Tape and Label Surface Coating Operations, 40 CFR 60, Subparts A and RR. The Illinois EPA is administering the NSPS in Illinois on behalf of the United States EPA under a delegation agreement.
- b. Pursuant to 40 CFR 60.442(a), on and after the date on which the performance test required by 40 CFR 60.8 has been completed each owner or operator subject to 40 CFR 60 Subpart RR shall:
  - ii. Cause the discharge into the atmosphere from an affected facility not more than 0.20 kg VOC/kg of coating solids applied as calculated on a weighted average basis for one calendar month; or
  - ii. Demonstrate for each coating affected line:
    - A. A 90 percent overall VOC emission reduction as calculated over a calendar month; or
    - B. The percent overall VOC emission reduction specified in 40 CFR 60.443(b) as calculated over a calendar month.
- 3a. The two coating/laminating lines are subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Flexible Polyurethane Foam Production and Fabrication Area Sources, 40 CFR 63 Subparts A and OOOOOO. The Illinois EPA is administering the NESHAP in Illinois on behalf of the United States EPA under a delegation agreement.
- b. Pursuant to 40 CFR 63.11416(e), if you own or operate a new or existing flexible polyurethane foam fabrication affected source, you must not use any adhesive containing methylene chloride in a flexible polyurethane foam fabrication process.
- 4a. Pursuant to 35 Ill. Adm. Code 212.123(a), no person shall cause or allow the emission of smoke or other particulate matter, with an opacity greater than 30 percent, into the atmosphere from any emission unit other than those emission units subject to 35 Ill. Adm. Code 212.122.
- b. Pursuant to 35 Ill. Adm. Code 212.123(b), the emission of smoke or other particulate matter from any such emission unit may have an opacity greater than 30 percent but not greater than 60 percent for a period or periods aggregating 8 minutes in any 60 minute period provided that such opaque emissions permitted during any 60 minute period shall occur from only one such emission unit located within a 305 m (1000 ft) radius from the center point of any other such emission unit owned or operated by such person, and provided further that such opaque emissions permitted from each such emission unit shall be limited to 3 times in any 24 hour period.

- c. Pursuant to 35 Ill. Adm. Code 212.321(a), no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period from any new process emission unit which, either alone or in combination with the emission of particulate matter from all other similar process emission units for which construction or modification commenced on or after April 14, 1972, at a source or premises, exceeds the allowable emission rates specified in 35 Ill. Adm. Code 212.321(c).
- 5. Pursuant to 35 Ill. Adm. Code 214.301, no person shall cause or allow the emission of sulfur dioxide into the atmosphere from any process emission source to exceed 2000 ppm.
- 6a. Pursuant to 35 Ill. Adm. Code 218.187(a)(1), on and after April 1, 2011 except as provided in 35 Ill. Adm. Code 218.187(a)(2), the requirements of 35 Ill. Adm. Code 218.187 shall apply to all cleaning operations which use organic materials at sources that emit a total of 6.8 kg/day (15 lbs/day) or more of VOM from cleaning operations at the source, in the absence of air pollution control equipment. For purposes of 35 Ill. Adm. Code 218.187, "cleaning operation" means the process of cleaning products, product components, tools, equipment, or general work areas during production, repair, maintenance, or servicing, including but not limited to spray gun cleaning, spray booth cleaning, large and small manufactured components cleaning, parts cleaning, equipment cleaning, line cleaning, floor cleaning, and tank cleaning, at sources with emission units;
- b. Pursuant to 35 Ill. Adm. Code 218.187(b), no owner or operator of a source subject to 35 Ill. Adm. Code 218.187 shall perform any cleaning operation subject to 35 Ill. Adm. Code 218.187 unless the owner or operator meets the requirements in 35 Ill. Adm. Code 218.187(b)(1), (b)(2), or (b)(3):
  - i. The VOM content of the as-used cleaning solutions (minus water and any compounds that are specifically exempted from the definitions of VOM) does not exceed the following emissions limitations:

	kg/l	lb/gal
All other cleaning operations not subject to a specific limitation in 35 Ill. Adm. Code 218.187(b)(1)(A) through (b)(1)(C)	0.050	0.42
  - ii. The composite vapor pressure of each as-used cleaning solution used does not exceed 8.0 mmHg measured at 20°C (68°F);
- c. Pursuant to 35 Ill. Adm. Code 218.204(c), except as provided in 35 Ill. Adm. Code 218.205, 218.207, 218.208, 218.212, 218.215 and 218.216, no owner or operator of a coating line shall apply at any time any coating in which VOM content exceeds following emission limitations for Paper Coating. The following emission limitations are expressed in units of VOM per volume of coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied at each coating applicator, except where noted. Compounds which are

specifically exempted from the definition of VOM should be treated as water for the purpose of calculating the "less water" part of the coating composition. Compliance with 35 Ill. Adm. Code 218 Subpart F must be demonstrated through the applicable coating analysis test methods and procedures specified in 35 Ill. Adm. Code 218.105(a) and the recordkeeping and reporting requirements specified in 35 Ill. Adm. Code 218.211(c) except where noted. (Note: The equation presented in 35 Ill. Adm. Code 218.206 shall be used to calculate emission limitations for determining compliance by add on controls, credits for transfer efficiency, emissions trades and cross line averaging.) The emission limitations are as follows:

- i. Prior to May 1, 2011:
 

	kg/l	lb/gal
	0.28	(2.3)
  
- ii. On and after May 1, 2011:
 

	kg VOM/kg (lb VOM/lb)	kg VOM/kg (lb VOM/lb)
	solids applied	coatings applied
A. Pressure sensitive tape and label surface coatings	0.20	(0.067)
B. All other paper coatings	0.40	(0.08)
  
- d. Pursuant to 35 Ill. Adm. Code 218.207(a), any owner or operator of a coating line subject to 35 Ill. Adm. Code 218.204 may comply with 35 Ill. Adm. Code 218.207, rather than with 35 Ill. Adm. Code 218.204, if a capture system and control device are operated at all times the coating line is in operation and the owner or operator demonstrates compliance with 35 Ill. Adm. Code 218.207(c), (d), (e), (f), (g), (h), (i), (j), (k), (l), or (m) (depending upon the source category) through the applicable coating analysis and capture system and control device efficiency test methods and procedures specified in 35 Ill. Adm. Code 218.105 and the recordkeeping and reporting requirements specified in 35 Ill. Adm. Code 218.211(e); and the control device is equipped with the applicable monitoring equipment specified in 35 Ill. Adm. Code 218.105(d) and the monitoring equipment is installed, calibrated, operated and maintained according to vendor specifications at all times the control device is in use. A capture system and control device, which does not demonstrate compliance with 35 Ill. Adm. Code 218.207(c), (d), (e), (f), (g), (h), (i), (j), (k), (l), or (m) may be used as an alternative to compliance with 35 Ill. Adm. Code 218.204 t only if the alternative is approved by the Illinois EPA and approved by the USEPA as a SIP revision.
  
- e. Pursuant to 35 Ill. Adm. Code 218.207(b)(1), the coating line is equipped with a capture system and control device that provides 81 percent reduction in the overall emissions of VOM from the coating line and the control device has a 90 percent efficiency.

- f. Pursuant to 35 Ill. Adm. Code 218.207(1), on and after May 1, 2011, no owner or operator of a paper coating line, metal furniture coating line, or large appliance coating line that is equipped with a capture system and control device shall operate the subject coating line unless either:
  - i. The capture system and control device provide at least 90 percent reduction in the overall emissions of VOM from the coating line; or
  - ii. The owner or operator complies with the applicable limitation set forth in 35 Ill. Adm. Code 218.204 by utilizing a combination of low-VOM coatings and a capture system and control device.
- g. Pursuant to 35 Ill. Adm. Code 218.301, no person shall cause or allow the discharge of more than 3.6 kg/hour (8 lbs/hour) of organic material into the atmosphere from any emission unit, except as provided in 35 Ill. Adm. Code 218.302, 218.303, or 218.304 and the following exception: If no odor nuisance exists the limitation of 35 Ill. Adm. Code 218 Subpart G shall apply only to photochemically reactive material.
- 7a. This permit is issued based on the pressure sensitive tape coaters at this source not being subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Paper and Other Web Coating, 40 CFR 63 Subpart JJJJ. This is a result of the federally enforceable production and operating limitations, which restrict the potential to emit to less than 10 tons/year for any individual Hazardous Air Pollutant (HAP), and 25 tons/year of any combination of such HAPs.
- b. This permit is issued based on this source not being subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for Paint Stripping And Miscellaneous Surface Coating Operations At Area Sources, 40 CFR 63 Subpart HHHHHH because the source does not perform spray application of coatings containing compounds of chromium (Cr), lead (Pb), manganese (Mn), nickel (Ni), or cadmium (Cd), collectively referred to as the target HAP to any part or product made of metal or plastic, or combinations of metal and plastic that are not motor vehicles or mobile equipment.
- 8. Pursuant to 35 Ill. Adm. Code 212.314, 35 Ill. Adm. Code 212.301 shall not apply and spraying pursuant to 35 Ill. Adm. Code 212.304 through 212.310 and 35 Ill. Adm. Code 212.312 shall not be required when the wind speed is greater than 40.2 km/hr (25 mph). Determination of wind speed for the purposes of this rule shall be by a one-hour average or hourly recorded value at the nearest official station of the U.S. Weather Bureau or by wind speed instruments operated on the site. In cases where the duration of operations subject to this rule is less than one hour, wind speed may be averaged over the duration of the operations on the basis of on-site wind speed instrument measurements.

- 9a. This permit is issued based on the pressure sensitive tape coater/laminators not being subject to 35 Ill. Adm. Code 218.187 (Other Industrial Solvent Cleaning Operations). Pursuant to 35 Ill. Adm. Code 218.187(a) (2) (B) (viii), notwithstanding 35 Ill. Adm. Code 218.187(a) (1), cleaning operations for emission units within the paper, film, and foil coating source category shall be exempt from the requirements of 35 Ill. Adm. Code 218.187(b), (c), (d), (f), and (g).
  - b. Pursuant to 35 Ill. Adm. Code 218.209, no owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.204 is required to meet the limitations of 35 Ill. Adm. Code 218 Subpart G (35 Ill. Adm. Code 218.301 or 218.302), after the date by which the coating line is required to meet 35 Ill. Adm. Code 218.204.
  - c. This permit is issued based on the use of mold release agent not being subject to 35 Ill. Adm. Code 218 Subpart TT (Other Emission Units). Pursuant to 35 Ill. Adm. Code 218.980(b) (1) (A), a source is subject to 35 Ill. Adm. Code 218 Subpart TT if it has the potential to emit 22.7 Mg (25 tons) or more of VOM per year, in aggregate, from emission units, other than furnaces at glass container manufacturing sources and VOM leaks from components, that are not regulated by 35 Ill. Adm. Code 218 Subparts B, E, F, H, Q, R, S, T, (excluding 35 Ill. Adm. Code 218.486), V, X, Y, Z, or BB.
10. Pursuant to 40 CFR 60.11(d), at all times, including periods of startup, shutdown, and malfunction, owners and operators shall, to the extent practicable, maintain and operate any affected facility including associated air pollution control equipment, in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Illinois EPA or USEPA which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source.
- 11a. Pursuant to 35 Ill. Adm. Code 212.306, all normal traffic pattern access areas surrounding storage piles specified in 35 Ill. Adm. Code 212.304 and all normal traffic pattern roads and parking facilities which are located on mining or manufacturing property shall be paved or treated with water, oils or chemical dust suppressants. All paved areas shall be cleaned on a regular basis. All areas treated with water, oils or chemical dust suppressants shall have the treatment applied on a regular basis, as needed, in accordance with the operating program required by 35 Ill. Adm. Code 212.309, 212.310 and 212.312.
  - b. Pursuant to 35 Ill. Adm. Code 212.309(a), the emission units described in 35 Ill. Adm. Code 212.304 through 212.308 and 35 Ill. Adm. Code 212.316 shall be operated under the provisions of an operating program, consistent with the requirements set forth in 35 Ill. Adm. Code 212.310 and 212.312, and prepared by the owner or operator and submitted to the Illinois EPA for its review. Such operating program shall be designed to significantly reduce fugitive particulate matter emissions.

- c. Pursuant to 35 Ill. Adm. Code 212.310, as a minimum the operating program shall include the following:
  - i. The name and address of the source;
  - ii. The name and address of the owner or operator responsible for execution of the operating program;
  - iii. A map or diagram of the source showing approximate locations of storage piles, conveyor loading operations, normal traffic pattern access areas surrounding storage piles and all normal traffic patterns within the source;
  - iv. Location of unloading and transporting operations with pollution control equipment;
  - v. A detailed description of the best management practices utilized to achieve compliance with 35 Ill. Adm. Code 212 Subpart K, including an engineering specification of particulate collection equipment, application systems for water, oil, chemicals and dust suppressants utilized and equivalent methods utilized;
  - vi. Estimated frequency of application of dust suppressants by location of materials; and
  - vii. Such other information as may be necessary to facilitate the Illinois EPA's review of the operating program.
- d. Pursuant to 35 Ill. Adm. Code 212.312, the operating program shall be amended from time to time by the owner or operator so that the operating program is current. Such amendments shall be consistent with 35 Ill. Adm. Code 212 Subpart K and shall be submitted to the Illinois EPA for its review.
- 12a. Pursuant to 35 Ill. Adm. Code 218.187(c), the owner or operator of a subject source shall demonstrate compliance with 35 Ill. Adm. Code 218.187 by using the applicable test methods and procedures specified in 35 Ill. Adm. Code 218.187(g) and by complying with the recordkeeping and reporting requirements specified in 35 Ill. Adm. Code 218.187(e).
- b. Pursuant to 35 Ill. Adm. Code 218.187(d), the owner or operator of a source subject to the requirements of 35 Ill. Adm. Code 218.187 shall comply with the following for each subject cleaning operation:
  - i. Cover open containers and properly cover and store applicators used to apply cleaning solvents;
  - ii. Minimize air circulation around the cleaning operation;
  - iii. Dispose of all used cleaning solutions, cleaning towels, and applicators used to apply cleaning solvents in closed containers;
  - iv. Utilize equipment practices that minimize emissions.

- c. Pursuant to 35 Ill. Adm. Code 218.210(g), no owner or operator of a coating line subject to the emission limitations in 35 Ill. Adm. Code 218.204(c)(2), (g)(2), or (h)(2) shall operate that coating line on or after a date consistent with 35 Ill. Adm. Code 218.106(e), unless the owner or operator has complied with, and continues to comply with, 35 Ill. Adm. Code 218.204(c)(2), (g)(2), or (h)(2), as applicable, or the alternative control options in 35 Ill. Adm. Code 218.205 or 218.207, and all applicable requirements in 35 Ill. Adm. Code 218.211 and 218.218.
- d. Pursuant to 35 Ill. Adm. Code 218.218(a), on and after May 1, 2011, every owner or operator of a source subject to the requirements of 35 Ill. Adm. Code 218.204(c) shall:
  - i. Store all VOM-containing cleaning materials in closed containers;
  - ii. Ensure that mixing and storage containers used for VOM-containing materials are kept closed at all times except when depositing or removing those materials;
  - iii. Minimize spills of VOM-containing cleaning materials;
  - iv. Convey VOM-containing cleaning materials from one location to another in closed containers or pipes; and
  - v. Minimize VOM emissions from the cleaning of storage, mixing, and conveying equipment.
- 13a. In the event that the operation of this source results in an odor nuisance, the Permittee shall take appropriate and necessary actions to minimize odors, including but not limited to, changes in raw material or installation of controls, in order to eliminate the nuisance.
- b. The Permittee shall, in accordance with the manufacturer(s) and/or vendor(s) recommendations, perform periodic maintenance on the catalytic oxidizer such that the catalytic oxidizer is kept in proper working condition and not cause a violation of the Illinois Environmental Protection Act or regulations promulgated therein.
- c. The catalytic oxidizer's combustion chamber shall be preheated to at least the manufacturer's recommended temperature but no less than the temperature at which compliance was demonstrated in the most recent compliance test, or 760°F in the absence of a compliance test. This temperature shall be maintained during operation.
- d. The catalytic oxidizer shall only be operated with natural gas as the fuel. The use of any other fuel in the catalytic oxidizer requires that the Permittee first obtain a construction permit from the Illinois EPA and then perform stack testing to verify compliance with all applicable requirements.

- e. The coating of plastic spray application of coatings to a plastic and/or metal substrate on a part or product shall only be performed with coatings not containing compounds of chromium (Cr), lead (Pb), manganese (Mn), nickel (Ni), or cadmium (Cd). The use of coatings containing compounds of chromium (Cr), lead (Pb), manganese (Mn), nickel (Ni), or cadmium (Cd) requires that the Permittee first obtain a construction permit from the Illinois EPA and then verify compliance with all applicable requirements.
- 14a. The VOM emissions from the two coater/laminators shall not exceed 2.44 tons/mo and 19.5 tons/yr. This limit is based on the maximum coating and solvent usage, the VOM content of the coatings and solvents used, and the control efficiency of the catalytic oxidizer. The VOM emissions shall be determined from the following equation:

$$E = \sum (S_i \times C_i) \times (1 - CE),$$

Where:

E = VOM emissions (ton);

S<sub>i</sub> = individual coating and solvent usage (ton);

C<sub>i</sub> = VOM content of the each individual coating and solvent (wt. fraction);

CE = overall efficiency of the capture and control device (fraction) demonstrated during the most recent stack test. CE = 0 when control device is not used.

- b. VOM usage and emissions from equipment wipe cleaning and use of mold release agent shall not exceed 0.63 ton/mo and 5.0 ton/yr. This limit is based on the maximum materials usage and their maximum VOM content.
- c. Emission of ozone from two ozone generators shall not exceed 3.20 lb/hour and 14.00 tons/year. These limits are based on the manufacturer's specification and year round operations.
- d. Operation of and emissions from the combustion of natural gas in the catalytic oxidizer shall not exceed the following limits:

<u>Pollutant</u>	<u>Emission Factor</u>	<u>Emissions</u>	
	<u>(lbs/mmscf)</u>	<u>(lb/hour)</u>	<u>(Tons/Yr)</u>
Carbon Monoxide (CO)	84.0	0.50	2.21
Nitrogen Oxides (NO <sub>x</sub> )	100.0	0.60	2.63
Particulate Matter (PM)	7.6	0.05	0.20
Sulfur Dioxide (SO <sub>2</sub> )	0.6	0.01	0.02
Volatile Organic Material (VOM)	5.5	0.03	0.14

These limits are based on the maximum firing rate (6.0 mmBtu/hour), a heat content of 1,000 Btu/scf for natural gas, 8760 hours/year of operation, and standard emission factors (Tables 1.4-1 and 1.4-2, AP-42, Fifth Edition, Volume I, Supplement D, July 1998).

- e. The emissions of Hazardous Air Pollutants (HAPs) as listed in Section 112(b) of the Clean Air Act from this source shall not exceed 0.9 tons/month and 9.0 tons/year of any single HAP and 2.25 tons/month and 22.5 tons/year of any combination of such HAPs. As a result of this condition, this permit is issued based on the emissions of any HAP from this source not triggering the requirement to obtain a CAAPP permit from the Illinois EPA and the NESHAP for Paper and Other Web Coating, 40 CFR 63 Subpart JJJJ.
  - f. Compliance with the annual limits of this permit shall be determined on a monthly basis from the sum of the data for the current month plus the preceding 11 months (running 12 month total).
- 15a. Pursuant to 40 CFR 60.8(a), at such other times as may be required by the Illinois EPA or USEPA under section 114 of the Clean Air Act, the owner or operator of such facility shall conduct performance test(s) and furnish the Illinois EPA or USEPA a written report of the results of such performance test(s).
- b. Pursuant to 40 CFR 60.8(b), performance tests shall be conducted and data reduced in accordance with the test methods and procedures contained in each applicable subpart of 40 CFR Part 60 unless the Illinois EPA or USEPA:
    - i. Specifies or approves, in specific cases, the use of a reference method with minor changes in methodology;
    - ii. Approves the use of an equivalent method;
    - iii. Approves the use of an alternative method the results of which he has determined to be adequate for indicating whether a specific source is in compliance;
    - iv. Waives the requirement for performance tests because the owner or operator of a source has demonstrated by other means to the Illinois EPA's or USEPA's satisfaction that the affected facility is in compliance with the standard; or
    - v. Approves shorter sampling times and smaller sample volumes when necessitated by process variables or other factors. Nothing in this paragraph shall be construed to abrogate the Illinois EPA's or USEPA's authority to require testing under section 114 of the Clean Air Act.
  - c. Pursuant to 40 CFR 60.8(c), performance tests shall be conducted under such conditions as the Illinois EPA or USEPA shall specify to the plant operator based on representative performance of the affected facility. The owner or operator shall make available to the Illinois EPA or USEPA such records as may be necessary to determine the conditions of the performance tests. Operations during periods of startup, shutdown, and malfunction shall not constitute representative conditions for the purpose of a performance test nor shall emissions in excess of the level of the applicable emission limit during periods of startup,

shutdown, and malfunction be considered a violation of the applicable emission limit unless otherwise specified in the applicable standard.

- d. Pursuant to 40 CFR 60.8(d), the owner or operator of an affected facility shall provide the Illinois EPA or USEPA at least 30 days prior notice of any performance test, except as specified under other subparts, to afford the Illinois EPA or USEPA the opportunity to have an observer present. If after 30 days notice for an initially scheduled performance test, there is a delay (due to operational problems, etc.) in conducting the scheduled performance test, the owner or operator of an affected facility shall notify the Illinois EPA or USEPA as soon as possible of any delay in the original test date, either by providing at least 7 days prior notice of the rescheduled date of the performance test, or by arranging a rescheduled date with the Illinois EPA or USEPA by mutual agreement.
- e. Pursuant to 40 CFR 60.8(e), the owner or operator of an affected facility shall provide, or cause to be provided, performance testing facilities as follows:
  - i. Sampling ports adequate for test methods applicable to such facility. This includes:
    - A. Constructing the air pollution control system such that volumetric flow rates and pollutant emission rates can be accurately determined by applicable test 1 methods and procedures; and
    - B. Providing a stack or duct free of cyclonic flow during performance tests, as demonstrated by applicable test methods and procedures.
  - ii. Safe sampling platform(s).
  - iii. Safe access to sampling platform(s).
  - iv. Utilities for sampling and testing equipment.
- f. Pursuant to 40 CFR 60.8(f), unless otherwise specified in the applicable subpart of 40 CFR Part 60, each performance test shall consist of three separate runs using the applicable test method. Each run shall be conducted for the time and under the conditions specified in the applicable standard under 40 CFR Part 60. For the purpose of determining compliance with an applicable standard under 40 CFR Part 60, the arithmetic means of results of the three runs shall apply. In the event that a sample is accidentally lost or conditions occur in which one of the three runs must be discontinued because of forced shutdown, failure of an irreplaceable portion of the sample train, extreme meteorological conditions, or other circumstances, beyond the owner or operator's control, compliance may, upon the Illinois EPA's or USEPA's approval, be determined using the arithmetic mean of the results of the two other runs.

16a. Pursuant to 40 CFR 60.443(a), to determine compliance with 40 CFR 60.442 the owner or operator of the affected facility shall calculate a weighted average of the mass of solvent used per mass of coating solids applied for a one calendar month period according to the following procedures:

- i. Determine the weight fraction of organics and the weight fraction of solids of each coating applied by using Reference Method 24 or by the coating manufacturer's formulation data.
- ii. Compute the weighted average by the following equation:

$$G = \frac{\sum_{i=1}^n W_{oi} M_{ci}}{\sum_{i=1}^n W_{si} M_{ci}}$$

iii. For each affected facility where the value of G is less than or equal to 0.20 kg VOC per kg of coating solids applied, the affected facility is in compliance with 40 CFR 60.442(a)(1).

b. Pursuant to 40 CFR 60.443(b), to determine compliance with 40 CFR 60.442(a)(2), the owner or operator shall calculate the required overall VOC emission reduction according to the following equation:

$$R_q = \frac{G - 0.20}{G} \times 100$$

If  $R_q$  is less than or equal to 90 percent, then the required overall VOC emission reduction is  $R_q$ . If  $R_q$  is greater than 90 percent, then the required overall VOC emission reduction is 90 percent.

c. Pursuant to 40 CFR 60.444(c), the performance test for affected facilities controlled by a solvent destruction device shall be conducted as follows:

- i. The performance of the solvent destruction device shall be determined by averaging the results of three test runs as specified in 40 CFR 60.8(f).
- ii. Determine for each affected facility prior to each test run the weighted average mass of VOC per mass of coating solids applied being used at the facility. The weighted average shall be determined as specified in 40 CFR 60.443(a). In this application the quantities of  $W_{oi}$ ,  $W_{si}$ , and  $M_{ci}$  shall be determined for the time period of each test run and not a calendar month as specified in 40 CFR 60.441.
- iii. Calculate the required percent overall VOC emission reduction as specified in 40 CFR 60.443(b).
- iv. Determine the percent overall VOC emission reduction of the solvent destruction device by the following equation and procedures:

$$R = \frac{\sum_{i=1}^n Q_{bi} C_{bi} - \sum_j^m Q_{aj} C_{aj}}{\sum_{i=1}^n Q_{bi} C_{bi} + \sum_{k=1}^p Q_{fk} C_{fk}} \times 100$$

- A. The owner or operator of the affected facility shall construct the overall VOC emission reduction system so that all volumetric flow rates and total VOC emissions can be accurately determined by the applicable test methods and procedures specified in 40 CFR 60.446(b).
  - B. The owner or operator of an affected facility shall construct a temporary total enclosure around the coating line applicator and flashoff area during the performance test for the purpose of capturing fugitive VOC emissions. If a permanent total enclosure exists in the affected facility prior to the performance test and the Illinois EPA or USEPA is satisfied that the enclosure is totally capturing fugitive VOC emissions, then no additional total enclosure will be required for the performance test.
  - C. For each affected facility where the value of R is greater than or equal to the value of  $R_q$  calculated in 40 CFR 60.443(b), compliance with 40 CFR 60.442(a)(2) is demonstrated.
- d. Pursuant to 40 CFR 60.446(b), Method 25 shall be used to determine the VOC concentration, in parts per million by volume, of each effluent gas stream entering and exiting the solvent destruction device or its equivalent, and each effluent gas stream emitted directly to the atmosphere. Methods 1, 2, 3, and 4 shall be used to determine the sampling location, volumetric flowrate, molecular weight, and moisture of all sampled gas streams. For Method 25, the sampling time for each of three runs must be at least 1 hour. The minimum sampling volume must be 0.003 dscm except that shorter sampling times or smaller volumes, when necessitated by process variables or other factors, may be approved by the Illinois EPA or USEPA.
- 17a. Pursuant to 35 Ill. Adm. Code 201.282, every emission source or air pollution control equipment shall be subject to the following testing requirements for the purpose of determining the nature and quantities of specified air contaminant emissions and for the purpose of determining ground level and ambient air concentrations of such air contaminants:
- i. Testing by Owner or Operator. The Illinois EPA may require the owner or operator of the emission source or air pollution control equipment to conduct such tests in accordance with procedures adopted by the Illinois EPA, at such reasonable times as may be specified by the Illinois EPA and at the expense of the owner or operator of the emission source or air pollution control equipment. The Illinois EPA may adopt procedures detailing methods of testing and formats for reporting results of testing. Such procedures and revisions thereto, shall not become effective

until filed with the Secretary of State, as required by the APA Act. All such tests shall be made by or under the direction of a person qualified by training and/or experience in the field of air pollution testing. The Illinois EPA shall have the right to observe all aspects of such tests.

- ii. Testing by the Illinois EPA. The Illinois EPA shall have the right to conduct such tests at any time at its own expense. Upon request of the Illinois EPA, the owner or operator of the emission source or air pollution control equipment shall provide, without charge to the Illinois EPA, necessary holes in stacks or ducts and other safe and proper testing facilities, including scaffolding, but excluding instruments and sensing devices, as may be necessary.
- b. Testing required by Conditions 18 and 19 shall be performed upon a written request from the Illinois EPA by a qualified independent testing service.
- 18. Pursuant to 35 Ill. Adm. Code 212.110(c), upon a written notification by the Illinois EPA, the owner or operator of a particulate matter emission unit subject to 35 Ill. Adm. Code Part 212 shall conduct the applicable testing for particulate matter emissions, opacity, or visible emissions at such person's own expense, to demonstrate compliance. Such test results shall be submitted to the Illinois EPA within thirty (30) days after conducting the test unless an alternative time for submittal is agreed to by the Illinois EPA.
- 19a. Pursuant to 35 Ill. Adm. Code 218.187(g)(1), testing to demonstrate compliance with the requirements of 35 Ill. Adm. Code 218.187 shall be conducted by the owner or operator within 90 days after a request by the Illinois EPA, or as otherwise specified in 35 Ill. Adm. Code 218.187. Such testing shall be conducted at the expense of the owner or operator and the owner or operator shall notify the Illinois EPA in writing 30 days in advance of conducting the testing to allow the Illinois EPA to be present during the testing;
- b. Pursuant to 35 Ill. Adm. Code 218.187(g)(2), testing to demonstrate compliance with the VOM content limitations in 35 Ill. Adm. Code 218.187(b)(1), and to determine the VOM content of cleaning solvents and cleaning solutions, shall be conducted as follows:
  - i. The applicable test methods and procedures specified in 35 Ill. Adm. Code 218.105(a) shall be used, provided, however, Method 24 shall be used to demonstrate compliance; or
  - ii. The manufacturer's specifications for VOM content for cleaning solvents may be used if such manufacturer's specifications are based on results of tests of the VOM content conducted in accordance with methods specified in 35 Ill. Adm. Code 218.105(a), however, Method 24 shall be used to determine compliance;

- c. Pursuant to 35 Ill. Adm. Code 218.187(g) (3), testing to determine the VOM composite partial vapor pressure of cleaning solvents, cleaning solvent concentrates, and as-used cleaning solutions shall be conducted in accordance with the applicable methods and procedures specified in 35 Ill. Adm. Code 218.110;
  - d. Pursuant to 35 Ill. Adm. Code 218.211(a), the VOM content of each coating and the efficiency of each capture system and control device shall be determined by the applicable test methods and procedures specified in 35 Ill. Adm. Code 218.105 to establish the records required under 35 Ill. Adm. Code 218.211.
- 20a. Pursuant to 40 CFR 60.445(f), the owner or operator of an affected facility controlled by a catalytic incineration solvent destruction device shall install, calibrate, maintain, and operate a monitoring device which continuously indicates and records the gas temperature both upstream and downstream of the catalyst bed.
- b. Pursuant to 40 CFR 60.445(g), the owner or operator of an affected facility controlled by a solvent destruction device which uses a hood or enclosure to capture fugitive VOC emissions shall install, calibrate, maintain, and operate a monitoring device which continuously indicates that the hood or enclosure is operating. No continuous monitor shall be required if the owner or operator can demonstrate that the hood or enclosure system is interlocked with the affected facility's oven recirculation air system.
- 21a. Pursuant to 35 Ill. Adm. Code 218.105(d) (2) (A) (ii), an owner or operator that uses an afterburner or carbon adsorber to comply with any Section of 35 Ill. Adm. Code Part 218 shall use Illinois EPA and USEPA approved continuous monitoring equipment which is installed, calibrated, maintained, and operated according to vendor specifications at all times the control device is in use except as provided in 35 Ill. Adm. Code 218.105(d) (3). The continuous monitoring equipment must monitor for each afterburner which has a catalyst bed, commonly known as a catalytic afterburner, the temperature rise across each catalytic afterburner bed or VOM concentration of exhaust.
- b. Pursuant to 35 Ill. Adm. Code 218.105(d) (2) (B), an owner or operator must install, calibrate, operate and maintain, in accordance with manufacturer's specifications, a continuous recorder on the temperature monitoring device, such as a strip chart, recorder or computer, having an accuracy of  $\pm 1$  percent of the temperature measured in degrees Celsius or  $\pm 0.5^\circ$  C, whichever is greater.
22. Pursuant to 40 CFR 60.7(f), any owner or operator subject to the provisions of 40 CFR Part 60 shall maintain a file of all measurements, including continuous monitoring system, monitoring device, and performance testing measurements; all continuous monitoring system performance evaluations; all continuous monitoring system or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; and all other information required by 40 CFR Part 60 recorded in a permanent form suitable for inspection. The file

shall be retained for at least two years following the date of such measurements, maintenance, reports, and records.

- 23a. Pursuant to 40 CFR 60.445(a), the owner or operator of an affected facility subject to 40 CFR 60 Subpart RR shall maintain a calendar month record of all coatings used and the results of the reference test method specified in 40 CFR 60.446(a) or the manufacturer's formulation data used for determining the VOC content of those coatings.
- b. Pursuant to 40 CFR 60.445(h), records of the measurements required in 40 CFR 60.443 and 60.445 must be retained for at least two years following the date of the measurements.
24. Pursuant to 40 CFR 63.11416(f), you may demonstrate compliance with the requirements in 40 CFR 63.11416(b) (2) and (c) through (e) using adhesive usage records, Material Safety Data Sheets, and engineering calculations.
25. Pursuant to 40 CFR 63.10(b) (3), if an owner or operator determines that his or her stationary source that emits (or has the potential to emit, without considering controls) one or more hazardous air pollutants regulated by any standard established pursuant to section 112(d) or (f) of the Clean Air Act, and that stationary source is in the source category regulated by the relevant standard, but that source is not subject to the relevant standard (or other requirement established under 40 CFR Part 63) because of limitations on the source's potential to emit or an exclusion, the owner or operator must keep a record of the applicability determination on site at the source for a period of 5 years after the determination, or until the source changes its operations to become an affected source, whichever comes first. The record of the applicability determination must be signed by the person making the determination and include an analysis (or other information) that demonstrates why the owner or operator believes the source is unaffected (e.g., because the source is an area source). The analysis (or other information) must be sufficiently detailed to allow the USEPA and/or Illinois EPA to make a finding about the source's applicability status with regard to the relevant standard or other requirement. If relevant, the analysis must be performed in accordance with requirements established in relevant subparts of 40 CFR Part 63 for this purpose for particular categories of stationary sources. If relevant, the analysis should be performed in accordance with USEPA guidance materials published to assist sources in making applicability determinations under Section 112 of the Clean Air Act, if any. The requirements to determine applicability of a standard under 40 CFR 63.1(b) (3) and to record the results of that determination under 40 CFR 63.10(b) (3) shall not by themselves create an obligation for the owner or operator to obtain a Title V permit.
26. Pursuant to 35 Ill. Adm. Code 212.110(e), the owner or operator of an emission unit subject to 35 Ill. Adm. Code Part 212 shall retain records of all tests which are performed. These records shall be retained for at least three (3) years after the date a test is performed.

27a. Pursuant to 35 Ill. Adm. Code 218.187(e) (3), all sources complying with 35 Ill. Adm. Code 218.187 pursuant to the requirements of 35 Ill. Adm. Code 218.187(b) (1) shall collect and record the following information for each cleaning solution used:

- i. For each cleaning solution which is prepared at the source with automatic equipment:
  - A. The name and identification of each cleaning solution;
  - B. The VOM content of each cleaning solvent in the cleaning solution;
  - C. Each change to the setting of the automatic equipment, with date, time, description of changes in the cleaning solution constituents (e.g., cleaning solvents), and a description of changes to the proportion of cleaning solvent and water (or other non-VOM);
  - D. The proportion of each cleaning solvent and water (or other non-VOM) used to prepare the as-used cleaning solution;
  - E. The VOM content of the as-used cleaning solution with supporting calculations; and
  - F. A calibration log for the automatic equipment, detailing periodic checks;
- ii. For each batch of cleaning solution which is not prepared at the source with automatic equipment:
  - A. The name and identification of each cleaning solution;
  - B. Date, time of preparation, and each subsequent modification of the batch;
  - C. The VOM content of each cleaning solvent in the cleaning solution;
  - D. The total amount of each cleaning solvent and water (or other non-VOM) used to prepare the as-used cleaning solution; and
  - E. The VOM content of the as-used cleaning solution, with supporting calculations. For cleaning solutions that are not prepared at the site but are used as purchased, the manufacturer's specifications for VOM content may be used if such manufacturer's specifications are based on results of tests of the VOM content conducted in accordance with methods specified in 35 Ill. Adm. Code 218.105(a);

- b. Pursuant to 35 Ill. Adm. Code 218.187(e) (4), all sources complying with 35 Ill. Adm. Code 218.187 pursuant to the requirements of 35 Ill. Adm. Code 218.187(b) (2) shall collect and record the following information for each cleaning solution used:
  - i. The name and identification of each cleaning solution;
  - ii. Date, time of preparation, and each subsequent modification of the batch;
  - iii. The molecular weight, density, and VOM composite partial vapor pressure of each cleaning solvent, as determined in accordance with the applicable methods and procedures specified in 35 Ill. Adm. Code 218.110;
  - iv. The total amount of each cleaning solvent used to prepare the as-used cleaning solution; and
  - v. The VOM composite partial vapor pressure of each as-used cleaning solution, as determined in accordance with the applicable methods and procedures specified in 35 Ill. Adm. Code 218.110;
- c. Pursuant to 35 Ill. Adm. Code 218.187(e) (7), all records required by 35 Ill. Adm. Code 218.187(e) shall be retained by the source for at least three years and shall be made available to the Illinois EPA upon request.
- d. Pursuant to 35 Ill. Adm. Code 218.211(c) (2), any owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.204 other than 35 Ill. Adm. Code 218.204(a) (2) or (a) (3) and complying by means of 35 Ill. Adm. Code 218.204 shall collect and record all of the following information for each coating line and maintain the information at the source for a period of three years:
  - i. The name and identification number of each coating as applied on each coating line.
  - ii. The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.
- e. Pursuant to 35 Ill. Adm. Code 218.211(e) (2), any owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.207 and complying by means of 35 Ill. Adm. Code 218.207(c), (d), (e), (f), (g) or (h) shall collect and record all of the following information each day for each coating line and maintain the information at the source for a period of three years:
  - i. The weight of VOM per volume of coating solids as applied each day on each coating line, if complying pursuant to 35 Ill. Adm. Code 218.207(b) (2).
  - ii. Control device monitoring data.

- iii. A log of operating time for the capture system, control device, monitoring equipment and the associated coating line.
- 28a. The Permittee shall maintain records of the following items so as to demonstrate compliance with the conditions of this permit:
- i. Records addressing use of good operating practices for the pollution control equipment covered under this permit:
    - A. Records for periodic inspection of the catalytic oxidizer with date, individual performing the inspection, and nature of inspection; and
    - B. Records for prompt repair of defects, with identification and description of defect, effect on emissions, date identified, date repaired, and nature of repair.
  - ii. Names and amounts of coatings and solvents used (ton/mo and ton/yr);
  - iii. VOM and HAP content of coatings and solvents used (wt. %);
  - iv. Operating hours of the catalytic oxidizer (hours/month and hours/year); and
  - v. Monthly and annual emissions of CO, NO<sub>x</sub>, PM, ozone, SO<sub>2</sub>, VOM and HAPs from the source with supporting calculations (ton/mo and ton/yr).
- b. All records and logs required by this permit shall be retained at a readily accessible location at the source for at least five (5) years from the date of entry and shall be made available for inspection and copying by the Illinois EPA or USEPA upon request. Any records retained in an electronic format (e.g., computer storage device) shall be capable of being retrieved and printed on paper during normal source office hours so as to be able to respond to the Illinois EPA or USEPA request for records during the course of a source inspection.
- 29a. Pursuant to 40 CFR 60.447(b), following the initial performance test, the owner or operator of each affected facility shall submit quarterly reports to the Administrator of exceedances of the VOC emission limits specified in 40 CFR 60.442. If no such exceedances occur during a particular quarter, a report stating this shall be submitted to the Illinois EPA or USEPA semiannually.
- b. Pursuant to 40 CFR 60.447(c), the owner or operator of each affected facility shall also submit reports at the frequency specified in 40 CFR 60.7(c) when the incinerator temperature drops as defined under 40 CFR 60.443(e). If no such periods occur, the owner or operator shall state this in the report.

30. Pursuant to 35 Ill. Adm. Code 212.110(d), a person planning to conduct testing for particulate matter emissions to demonstrate compliance shall give written notice to the Illinois EPA of that intent. Such notification shall be given at least thirty (30) days prior to the initiation of the test unless a shorter period is agreed to by the Illinois EPA. Such notification shall state the specific test methods from 35 Ill. Adm. Code 212.110 that will be used.
- 31a. Pursuant to 35 Ill. Adm. Code 218.187(e)(2), all sources subject to the requirements of 35 Ill. Adm. Code 218.187 shall:
  - i. By April 1, 2011, or upon initial start-up of the source, whichever is later, submit a certification to the Illinois EPA that includes:
    - A. A declaration that all subject cleaning operations are in compliance with the requirements of 35 Ill. Adm. Code 218.187;
    - B. Identification of each subject cleaning operation and each VOM-containing cleaning solution used as of the date of certification in such operation;
    - C. If complying with the emissions control system requirement, what type of emissions control system will be used;
    - D. Initial documentation that each subject cleaning operation will comply with the applicable limitation, including copies of manufacture's specifications, test results (if any), formulation data, and calculations;
    - E. Identification of the methods that will be used to demonstrate continuing compliance with the applicable limitations;
    - F. A description of the practices and procedures that the source will follow to ensure compliance with the limitations in 35 Ill. Adm. Code 218.187(d); and
    - G. A description of each cleaning operation exempt pursuant to 35 Ill. Adm. Code 218.187(a)(2), if any, and a listing of the emission unit(s) on which the exempt cleaning operation is performed;
  - ii. At least 30 calendar days before changing the method of compliance between 35 Ill. Adm. Code 218.187(b)(1), (b)(2), and 35 Ill. Adm. Code 218.187(b)(3), notify the Illinois EPA in writing of such change. Such notification shall include a demonstration of compliance with the newly applicable subsection;
- b. Pursuant to 35 Ill. Adm. Code 218.211(c)(3), any owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.204 of and complying by means of 35 Ill. Adm. Code 218.204 shall notify the Illinois EPA in the following instances:

- i. Any record showing violation of 35 Ill. Adm. Code 218.204 shall be reported by sending a copy of such record to the Illinois EPA within 30 days following the occurrence of the violation.
  - ii. At least 30 calendar days before changing the method of compliance from 35 Ill. Adm. Code 218.204 to 35 Ill. Adm. Code 218.205 or 35 Ill. Adm. Code 218.207, the owner or operator shall comply with all requirements of 35 Ill. Adm. Code 218.211(d) (1) or (e) (1), respectively. Upon changing the method of compliance from 35 Ill. Adm. Code 218.204 to 35 Ill. Adm. Code 218.205 or 35 Ill. Adm. Code 218.207, the owner or operator shall comply with all requirements of 35 Ill. Adm. Code 218.211(d) or (e), respectively.
- c. Pursuant to 35 Ill. Adm. Code 218.211(e) (3), any owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.207 and complying by means of 35 Ill. Adm. Code 218.207(c), (d), (e), (f), (g) or (h) shall notify the Illinois EPA in the following instances:
- i. Any record showing violation of 35 Ill. Adm. Code 218.207 shall be reported by sending a copy of such record to the Illinois EPA within 30 days following the occurrence of the violation.
  - ii. At least 30 calendar days before changing the method of compliance with 35 Ill. Adm. Code 218 Subpart F from 35 Ill. Adm. Code 218.207 to 35 Ill. Adm. Code 218.204 or 35 Ill. Adm. Code 218.205, the owner or operator shall comply with all requirements of 35 Ill. Adm. Code 218.207(c) (1) or (d) (1), respectively. Upon changing the method of compliance with 35 Ill. Adm. Code 218 Subpart F from 35 Ill. Adm. Code 218.207 to 35 Ill. Adm. Code 218.204 or 35 Ill. Adm. Code 218.205, the owner or operator shall comply with all requirements of 35 Ill. Adm. Code 218.207(c) or (d), respectively.
- d. Pursuant to 35 Ill. Adm. Code 218.990, upon request by the Illinois EPA, the owner or operator of an emission unit which is exempt from the requirements of 35 Ill. Adm. Code 218 Subparts PP, QQ, RR, TT or 35 Ill. Adm. Code 218.208(b) shall submit records to the Illinois EPA within 30 calendar days from the date of the request that document that the emission unit is exempt from those requirements.
- 32a. If there is an exceedance of or a deviation from the requirements of this permit as determined by the records required by this permit, the Permittee shall submit a report to the Illinois EPA's Compliance Section in Springfield, Illinois within 30 days after the exceedance or deviation. The report shall include the emissions released in accordance with the recordkeeping requirements, a copy of the relevant records, and a description of the exceedance or deviation and efforts to reduce emissions and future occurrences.

b. Two (2) copies of required reports and notifications shall be sent to:

Illinois Environmental Protection Agency  
Division of Air Pollution Control  
Compliance Section (#40)  
P.O. Box 19276  
Springfield, Illinois 62794-9276

and one (1) copy shall be sent to the Illinois EPA's regional office at the following address unless otherwise indicated:

Illinois Environmental Protection Agency  
Division of Air Pollution Control  
9511 West Harrison  
Des Plaines, Illinois 60016

It should be noted that this permit has been revised to modify emission limits for the coating, mold release application and solvent cleaning operations.

If you have any questions on this, please call Valeriy Brodsky at 217/782-2113.

Edwin C. Bakowski, P.E.  
Manager, Permit Section  
Division of Air Pollution Control

Date Signed: \_\_\_\_\_

ECB:VJB:

cc: Illinois EPA, FOS Region 1  
Lotus Notes

Attachment A - Emission Summary

This attachment provides a summary of the maximum emissions from the pressure sensitive tape manufacturing coating plant operating in compliance with the requirements of this federally enforceable permit. In preparing this summary, the Illinois EPA used the annual operating scenario which results in maximum emissions from such a plant. The resulting maximum emissions are below the levels (e.g., 100 tons/year of volatile organic material, 10 tons/year any single HAP, and 25 tons/year of any combination of such HAPs) at which this source would be considered a major source for purposes of the Clean Air Act Permit Program. Actual emissions from this source will be less than predicted in this summary to the extent that less material is handled, less volatile organic material and hazardous air pollutants are used and control measures are more effective than required in this permit.

<u>Emission Unit</u>	E M I S S I O N S (Tons/Year)							Single <u>HAP</u>	Combined <u>HAPs</u>
	<u>CO</u>	<u>NO<sub>x</sub></u>	<u>Ozone</u>	<u>PM</u>	<u>SO<sub>2</sub></u>	<u>VOM</u>			
Two Coater/ Laminators						19.5			
Wipe Cleaning & Mold Release						5.0			
Two Ozone Generators			14.00						
Fuel Combustion	<u>2.21</u>	<u>2.63</u>	<u>--</u>	<u>0.20</u>	<u>0.02</u>	<u>0.14</u>	<u>--</u>	<u>--</u>	
Totals	2.21	2.63	14.00	0.20	0.02	24.64	9.0	22.5	

VJB: