

217/782-2113

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT

PERMITTEE

ITT Corporation, Residential and Commercial Water Division  
Attn: John Fogel  
8200 North Austin Avenue  
Morton Grove, Illinois 60053

Application No.: 96030036

I.D. No.: 031195ABT

Applicant's Designation:

Date Received: June 28, 2007

Subject: Industrial Pumps

Date Issued: March 21, 2008

Expiration Date: March 21, 2013

Location: 8200 North Austin Avenue, Morton Grove, Cook County, 60053

This permit is hereby granted to the above-designated Permittee to OPERATE emission unit(s) and/or air pollution control equipment consisting of eight paint spray booths (PB1 - PB7 and PB11), Kewanee natural gas-fired 3043-300 hp boiler (10.0 mmBtu/hour), wastewater evaporator, two cold cleaning degreasers and natural gas-fired combustion equipment pursuant to the above-referenced application. This Permit is subject to standard conditions attached hereto and the following special condition(s):

- 1a. This federally enforceable state operating permit is issued:
  - i. This federally enforceable state operating permit (FESOP) is issued to limit the emissions of air pollutants from the source to less than major source thresholds (i.e., 100 tons/year for volatile organic material (VOM), 10 tons/year for a single hazardous air pollutant (HAP) and 25 tons/year for totaled HAPs). As a result, the source is excluded from the requirements to obtain a Clean Air Act Permit Program (CAAPP) permit. The maximum emissions of this source, as limited by the conditions of this permit are described in Attachment A.
  - ii. To limit the potential emissions of VOM from the source to less than 25 tons/year. As a result, the source is excluded from the requirement of 35 Ill. Adm. Code Part 205, Emission Reduction Market System. The maximum emissions of this source, as limited by the conditions of this permit, are described in Attachment A.
  - iii. This permit is issued based upon the source not being subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Coating of Miscellaneous Metal Parts and Products, 40 CFR 63, Subpart Mmmm. This is consequence of the federally enforceable production and operating limitations, which restrict a potential to emit to less than 10 tons/year for any individual Hazardous Air Pollutant (HAP), and 25 tons/year of any combination of such HAPs.

- b. Prior to issuance, a draft of this permit has undergone a public notice and comment period.
- c. This permit supersedes all operating permits issued for this location.
- 2a. No person shall cause or allow the emission of smoke or other particulate matter, with an opacity greater than 30 percent, into the atmosphere from any emission unit other than those emission units subject to the requirements of 35 Ill. Adm. Code 212.122, pursuant to 35 Ill. Adm. Code 212.123(a), except as allowed by 35 Ill. Adm. Code 212.123(b) and 212.124.
- b. No person shall cause or allow any visible emissions of fugitive particulate matter from any process, including any material handling or storage activity beyond the property line of the emission source unless the wind speed is greater than 40.2 kilometers per hour (25 miles per hour), pursuant to 35 Ill. Adm. Code 212.301 and 212.314.
- c. Pursuant to 35 Ill. Adm. Code 212.306, all normal traffic pattern access areas surrounding storage piles specified in 35 Ill. Adm. Code 212.304 and all normal traffic pattern roads and parking facilities which are located on mining or manufacturing property shall be paved or treated with water, oils or chemical dust suppressants. All areas treated shall be cleaned on a regular basis. All areas treated with water, oils or chemical dust suppressants shall have the treatment applied on a regular basis, as needed, in accordance with the operating program required by 35 Ill. Adm. Code 212.309, 212.310 and 212.312.
- d. Pursuant to 35 Ill. Adm. Code 212.307, All unloading and transporting operations of materials collected by pollution control equipment shall be enclosed or shall utilize spraying, palletizing, screw conveying or other equivalent methods.
- e. Pursuant to 35 Ill. Adm. Code 212.309(a), the emission units described in 35 Ill. Adm. Code 212.304 through 212.308 shall be operated under the provisions of an operating program, consistent with the requirements set forth in 35 Ill. Adm. Code 212.310 and 212.312, and prepared by the owner or operator and submitted to the Illinois EPA for its review. Such operating program shall be designed to significantly reduce fugitive particulate matter emissions.
- f. Pursuant to 35 Ill. Adm. Code 212.310, as a minimum the operating program shall include the following:
  - i. The name and address of the source;
  - ii. The name and address of the owner or operator responsible for execution of the operating program;
  - iii. A map or diagram of the source showing approximate locations of storage piles, conveyor loading operations, normal traffic

pattern access areas surrounding storage piles and all normal traffic patterns within the source;

- iv. Location of unloading and transporting operations with pollution control equipment;
  - v. A detailed description of the best management practices utilized to achieve compliance with 35 Ill. Adm. Code 212 Subpart K, including an engineering specification of particulate collection equipment, application systems for water, oil, chemicals and dust suppressants utilized and equivalent methods utilized;
  - vi. Estimated frequency of application of dust suppressants by location of materials; and
  - vii. Such other information as may be necessary to facilitate the Illinois EPA's review of the operating program.
- g. Pursuant to 35 Ill. Adm. Code 212.321(a), no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period from any new process emission unit which, either alone or in combination with the emission of particulate matter from all other similar process emission units for which construction or modification commenced on or after April 14, 1972, at a source or premises, exceeds the allowable emission rates specified in subsection (c) of 35 Ill. Adm. Code 212.321.
3. Pursuant to 35 Ill. Adm. Code 214.301, no person shall cause or allow the emission of sulfur dioxide into the atmosphere from any process emission source to excess 2000 ppm.
4. No person shall cause or allow the emission of carbon monoxide (CO) into the atmosphere from any fuel combustion emission source with actual heat input greater than 2.9 MW (10 mmBtu/hr) to exceed 200 ppm, corrected to 50 percent excess air, pursuant to 35 Ill. Adm. Code 216.121.
- 5a. Pursuant to 35 Ill. Adm. Code 218.182(a), no person shall operate a cold cleaning degreaser unless:
- i. Waste solvent is stored in covered containers only and not disposed of in such a manner that more than 20% of the waste solvent (by weight) is allowed to evaporate into the atmosphere;
  - ii. The cover of the degreaser is closed when parts are not being handled; and
  - iii. Parts are drained until dripping ceases.
- b. Pursuant to 35 Ill. Adm. Code 218.182(b), no person shall operate a cold cleaning degreaser unless:

- i. The degreaser is equipped with a cover which is closed whenever parts are not being handled in the cleaner. The cover shall be designed to be easily operated with one hand or with the mechanical assistance of springs, counter-weights or a powered system if:
    - A. The solvent vapor pressure is greater than 2 kPa (15 mmHg or 0.3 psi) measured at 38°C (100°F);
    - B. The solvent is agitated; or
    - C. The solvent is heated above ambient room temperature.
  - ii. The degreaser is equipped with a device for draining cleaned parts. The drainage device shall be constructed so that parts are enclosed under the cover while draining unless:
    - A. The solvent vapor pressure is less than 4.3 kPa (32 mmHg or 0.6 psi) measured at 38°C (100°F); or
    - B. An internal drainage device cannot be fitted into the cleaning system, in which case the drainage device may be external.
  - iii. The degreaser is equipped with one of the following control devices if the vapor pressure of the solvent is greater than 4.3 kPa (32 mmHg or 0.6 psi) measured at 38°C (100°F) or if the solvent is heated above 50°C (120°F) or its boiling point:
    - A. A freeboard height of 7/10 of the inside width of the tank or 91 cm (36 in), whichever is less; or
    - B. Any other equipment or system of equivalent emission control as approved by the Illinois EPA and further processed consistent with 35 Ill. Adm. Code 218.108. Such a system may include a water cover, refrigerated chiller or carbon adsorber.
  - iv. A permanent conspicuous label summarizing the operating procedure is affixed to the degreaser; and
  - v. If a solvent spray is used, the degreaser is equipped with a solid fluid stream spray, rather than a fine, atomized or shower spray.
- c. Pursuant to 35 Ill. Adm. Code 218.182(c)(2)(B), no person shall operate a cold cleaning degreaser with a solvent vapor pressure which exceeds 1.0 mmHg (0.019 psi) measured at 20°C (68°F).
  - d. Pursuant to 35 Ill. Adm. Code 218.204(j)(2)(A), except as provided in 35 Ill. Adm. Code 218.205, 218.207, 218.208, 218.212, 218.215 and 218.216, no owner or operator of a coating line shall apply at any time

any coating in which the VOM content exceeds the following emission limitations for the specified coating. The following emission limitations are expressed in units of VOM per volume of coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied at each coating applicator, except where noted. Compounds which are specifically exempted from the definition of VOM should be treated as water for the purpose of calculating the "less water" part of the coating composition. Compliance with 35 Ill. Adm. Code 218 Subpart F must be demonstrated through the applicable coating analysis test methods and procedures specified in 35 Ill. Adm. Code 218.105(a) and the recordkeeping and reporting requirements specified in 35 Ill. Adm. Code 218.211(c) except where noted. The emission limitations are as follows:

<u>Miscellaneous Metal Parts and Products Coating</u>	<u>kg/l</u>	<u>lb/gal</u>
Extreme Performance Air Dried Coatings	0.42	3.5

- e. Pursuant to 35 Ill. Adm. Code 218.209, no owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.204 is required to meet the limitations of 35 Ill. Adm. Code 218 Subpart G (35 Ill. Adm. Code 218.301 or 218.302), after the date by which the coating line is required to meet 35 Ill. Adm. Code 218.204.
- f. Pursuant to 35 Ill. Adm. Code 218.301, no person shall cause or allow the discharge of more than 3.6 kg/hour (8 lbs/hour) of organic material into the atmosphere from any emission unit, except as provided in 35 Ill. Adm. Code 218.302, 218.303, or 218.304 and the following exception: If no odor nuisance exists the limitation of 35 Ill. Adm. Code 218 Subpart G shall only apply to photochemically reactive material.
- 6. In the event that the operation of this source results in an odor nuisance, the Permittee shall take appropriate and necessary actions to minimize odors, including but not limited to, changes in raw material or installation of controls, in order to eliminate the odor nuisance.
- 7. The boiler shall only be operated with natural gas as the fuel. The use of any other fuel in the boiler requires that the Permittee first obtain a construction permit from the Illinois EPA and then perform stack testing to verify compliance with all applicable requirements.
- 8a. Operation and VOM emissions from new paint booth PB11 and existing paint booths PB1 - PB7 shall not exceed the following limits:

<u>Paint Usage</u>		<u>VOM Emissions</u>	
<u>(Gallons/Month)</u>	<u>(Gallons/Year)</u>	<u>(Tons/Month)</u>	<u>(Tons/Year)</u>
2,500	20,000	1.75	14.00

These limits are based on maximum coating usage and a maximum VOM content of 1.4 lbs/gallon.

- b. This permit is issued based on negligible emissions of Particulate Matter (PM) from the paint booths. For this purpose, emissions from each emission unit shall not exceed nominal emission rates of 0.1 lbs/hour and 0.44 tons/year.
- c. Operation and VOM emissions from the wastewater evaporator shall not exceed the following limits:

Wastewater Throughput		VOM Emissions	
<u>(Pounds/Hour)</u>	<u>(Tons/Year)</u>	<u>(Tons/Month)</u>	<u>(Tons/Year)</u>
250	780	0.5	5.15

These limits are based on maximum throughput of wastewater multiplied by the VOM concentration of wastewater.

- d. Operation and emission of the natural gas fired combustion equipment shall not exceed the following limits:
  - i. Natural Gas Usage: 15 mmscf/month and 120 mmscf/year
  - ii. Emissions of nitrogen oxide (NO<sub>x</sub>), carbon monoxide (CO), particulate matter (PM), volatile organic material (VOM), and sulfur dioxide (SO<sub>2</sub>):

<u>Pollutant</u>	Emission	Emissions	
	<u>Factor</u> <u>(Lbs/mmscf)</u>	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
Nitrogen Oxides (NO <sub>x</sub> )	100	0.75	6.00
Carbon Monoxide (CO)	84	0.63	5.04
Particulate Matter (PM)	7.6	0.06	0.46
Volatile Organic Material (VOM)	5.5	0.04	0.33
Sulfur Dioxide (SO <sub>2</sub> )	0.6	0.01	0.04

These are the emission factors for uncontrolled natural gas combustion in small boilers with less than 100 mmBtu/hour of heat input, (Tables 1.4-1 and 1.4-2, AP-42, Fifth Edition, Volume I, Supplement D, March 1998).

- e. This permit is issued based on negligible emissions of VOM from each cold cleaning degreaser. For this purpose, VOM emissions from each cold cleaning degreaser shall not exceed nominal emission rates of 0.44 tons/year.
9. The emissions of Hazardous Air Pollutants (HAPs) as listed in Section 112(b) of the Clean Air Act shall not exceed 0.9 tons/month and 9.0 tons/year of any single HAP and 2.25 tons/month and 22.5 tons/year of any combination of such HAPs. As a result of this condition, this permit is issued based on the emissions of any HAP from this source not

triggering the requirement to obtain a CAAPP permit from the Illinois EPA.

10. Compliance with the annual limits of this permit shall be determined on a monthly basis from the sum of the data for the current month plus the preceding 11 months (running 12 month total).
- 11a. Pursuant to 35 Ill. Adm. Code 212.282, every emission source or air pollution control equipment shall be subject to the following testing requirements for the purpose of determining the nature and quantities of specified air contaminant emissions and for the purpose of determining ground level and ambient air concentrations of such air contaminants:
  - i. Testing by Owner or Operator. The Illinois EPA may require the owner or operator of the emission source or air pollution control equipment to conduct such tests in accordance with procedures adopted by the Illinois EPA, at such reasonable times as may be specified by the Illinois EPA and at the expense of the owner or operator of the emission source or air pollution control equipment. The Illinois EPA may adopt procedures detailing methods of testing and formats for reporting results of testing. Such procedures and revisions thereto, shall not become effective until filed with the Secretary of State, as required by the APA Act. All such tests shall be made by or under the direction of a person qualified by training and/or experience in the field of air pollution testing. The Illinois EPA shall have the right to observe all aspects of such tests.
  - ii. Testing by the Illinois EPA. The Illinois EPA shall have the right to conduct such tests at any time at its own expense. Upon request of the Illinois EPA, the owner or operator of the emission source or air pollution control equipment shall provide, without charge to the Illinois EPA, necessary holes in stacks or ducts and other safe and proper testing facilities, including scaffolding, but excluding instruments and sensing devices, as may be necessary.
- b. Testing required by Condition 12 shall be performed upon a written request from the Illinois EPA by a qualified independent testing service.
- 12a. Pursuant to 35 Ill. Adm. Code 212.107, for both fugitive and nonfugitive particulate matter emissions, a determination as to the presence or absence of visible emissions from emission units shall be conducted in accordance with Method 22, 40 CFR part 60, Appendix A, incorporated by reference in 35 Ill. Adm. Code 212.113, except that the length of the observing period shall be at the discretion of the observer, but not less than one minute. This Condition shall not apply to 35 Ill. Adm. Code 212.301, pursuant to 35 Ill. Adm. Code 212.107.

- b. Pursuant to 35 Ill. Adm. Code 212.109, except as otherwise provided in 35 Ill. Adm. Code Part 212, and except for the methods of data reduction when applied to 35 Ill. Adm. Code 212.122 and 212.123, measurements of opacity shall be conducted in accordance with Method 9, 40 CFR Part 60, Appendix A, and the procedures in 40 CFR 60.675(c) and (d), if applicable, incorporated by reference in 35 Ill. Adm. Code 212.113, except that for roadways and parking areas the number of readings required for each vehicle pass will be three taken at 5-second intervals. The first reading shall be at the point of maximum opacity and second and third readings shall be made at the same point, the observer standing at right angles to the plume at least 15 feet away from the plume and observing 4 feet above the surface of the roadway or parking area. After four vehicles have passed, the 12 readings will be averaged, pursuant to 35 Ill. Adm. Code 212.109.
  - c. Pursuant to 35 Ill. Adm. Code 212.110(a), measurement of particulate matter emissions from stationary emission units subject to 35 Ill. Adm. Code Part 212 shall be conducted in accordance with 40 CFR part 60, Appendix A, Methods 5, 5A, 5D, or 5E, pursuant to 35 Ill. Adm. Code 212.110(a).
  - d. Pursuant to 35 Ill. Adm. Code 212.110(b), the volumetric flow rate and gas velocity shall be determined in accordance with 40 CFR part 60, Appendix A, Methods 1, 1A, 2, 2A, 2C, 2D, 3, and 4, pursuant to 35 Ill. Adm. Code 212.110(b).
  - e. Pursuant to 35 Ill. Adm. Code 212.110(c), upon a written notification by the Illinois EPA, the owner or operator of a particulate matter emission unit subject to 35 Ill. Adm. Code Part 212 shall conduct the applicable testing for particulate matter emissions, opacity, or visible emissions at such person's own expense, to demonstrate compliance. Such test results shall be submitted to the Illinois EPA within thirty (30) days after conducting the test unless an alternative time for submittal is agreed to by the Illinois EPA, pursuant to 35 Ill. Adm. Code 212.110(c).
13. Pursuant to 35 Ill. Adm. Code 218.211(a), the VOM content of each coating and the efficiency of each capture system and control device shall be determined by the applicable test methods and procedures specified in 35 Ill. Adm. Code 218.105 to establish the records required under 35 Ill. Adm. Code 218.211.
14. Pursuant to 40 CFR 63.10(b)(3), if an owner or operator determines that his or her stationary source that emits (or has the potential to emit, without considering controls) one or more hazardous air pollutants regulated by any standard established pursuant to section 112(d) or (f) of the Clean Air Act, and that stationary source is in the source category regulated by the relevant standard, but that source is not subject to the relevant standard (or other requirement established under 40 CFR Part 63) because of limitations on the source's potential to emit or an exclusion, the owner or operator must keep a record of the applicability determination on site at the source for a period of 5

years after the determination, or until the source changes its operations to become an affected source, whichever comes first. The record of the applicability determination must be signed by the person making the determination and include an analysis (or other information) that demonstrates why the owner or operator believes the source is unaffected (e.g., because the source is an area source). The analysis (or other information) must be sufficiently detailed to allow the USEPA and/or Illinois EPA to make a finding about the source's applicability status with regard to the relevant standard or other requirement. If relevant, the analysis must be performed in accordance with requirements established in relevant subparts of 40 CFR Part 63 for this purpose for particular categories of stationary sources. If relevant, the analysis should be performed in accordance with USEPA guidance materials published to assist sources in making applicability determinations under Section 112 of the Clean Air Act, if any. The requirements to determine applicability of a standard under 40 CFR 63.1(b)(3) and to record the results of that determination under 40 CFR 63.10(b)(3) shall not by themselves create an obligation for the owner or operator to obtain a Title V permit.

15. Pursuant to 35 Ill. Adm. Code 212.110(e), the owner or operator of an emission unit subject to 35 Ill. Adm. Code Part 212 shall retain records of all tests which are performed. These records shall be retained for at least three (3) years after the date a test is performed.
- 16a. Pursuant to 35 Ill. Adm. Code 218.182(d)(2), all persons subject to the requirements of 35 Ill. Adm. Code 218.182(c)(1)(B) and (c)(2)(B) must maintain records which include for each purchase:
  - i. The name and address of the solvent supplier;
  - ii. The date of purchase;
  - iii. The type of solvent; and
  - iv. The vapor pressure of the solvent measured in mmHg at 20° C (68° F).
- b. Pursuant to 35 Ill. Adm. Code 218.182(e), all records required by 35 Ill. Adm. Code 218.182(d) shall be retained for three years and shall be made available to the Illinois EPA upon request.
- c. Pursuant to 35 Ill. Adm. Code 218.211(c)(2), any owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.204 other than 35 Ill. Adm. Code 218.204(a)(2) or (a)(3) and complying by means of 35 Ill. Adm. Code 218.204 shall collect and record all of the following information for each coating line and maintain the information at the source for a period of three years:
  - i. The name and identification number of each coating as applied on each coating line.

- ii. The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.
- 17a. The Permittee shall maintain records of the following items so as to demonstrate compliance with the Conditions of this permit:
- i. Coating usage (gallons/month and gallons/year);
  - ii. Solvent usage (gallons/month and gallons/year);
  - iii. VOM and HAP contents of materials used (percent by weight);
  - iv. The densities of materials used (lbs/gallon);
  - v. Natural gas usage (mmscf/month and mmscf/year); and
  - vi. Monthly and annual emissions of CO, NO<sub>x</sub>, PM, SO<sub>2</sub>, VOM and HAPs (individual and combined) with supporting calculations (tons/month and tons/year).
- b. All records and logs required by this permit shall be retained at a readily accessible location at the source for at least five (5) years from the date of entry and shall be made available for inspection and copying by the Illinois EPA or USEPA upon request. Any records retained in an electronic format (e.g., computer) shall be capable of being retrieved and printed on paper during normal source office hours so as to be able to respond to an Illinois EPA or USEPA request for records during the course of a source inspection.
- 18a. Pursuant to 35 Ill. Adm. Code 212.110(d), a person planning to conduct testing for particulate matter emissions to demonstrate compliance shall give written notice to the Illinois EPA of that intent. Such notification shall be given at least thirty (30) days prior to the initiation of the test unless a shorter period is agreed to by the Illinois EPA. Such notification shall state the specific test methods from 35 Ill. Adm. Code 212.110 that will be used.
- b. Pursuant to 35 Ill. Adm. Code 218.211(c)(3), any owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.204 of and complying by means of 35 Ill. Adm. 218.204 shall notify the Illinois EPA in the following instances:
- i. Any record showing violation of 35 Ill. Adm. Code 218.204 shall be reported by sending a copy of such record to the Illinois EPA within 30 days following the occurrence of the violation.
  - ii. At least 30 calendar days before changing the method of compliance from 35 Ill. Adm. Code 218.204 to 35 Ill Adm. Code 218.205 or 35 Ill. Adm. Code 218.207, the owner or operator shall

comply with all requirements of 35 Ill Adm. Code 218.211(d)(1) or (e)(1), respectively. Upon changing the method of compliance from 35 Ill. Adm. Code 218.204 to 35 Ill. Adm. Code 218.205 or 35 Ill. Adm. Code 218.207, the owner or operator shall comply with all requirements of 35 Ill. Adm. Code 218.211(d) or (e), respectively.

19. If there is an exceedance of or deviation from the requirements of this permit as determined by the records required by this permit, the Permittee shall submit a report to the Illinois EPA's Compliance Section in Springfield, Illinois within 30 days after the exceedance/deviation. The report shall include the emissions released in accordance with the recordkeeping requirements, a copy of the relevant records, and a description of the exceedance or deviation and efforts to reduce emissions and future occurrences.
20. Two (2) copies of required reports and notifications shall be sent to:

Illinois Environmental Protection Agency  
Division of Air Pollution Control  
Compliance Section (#40)  
P.O. Box 19276  
Springfield, Illinois 62794-9276

and one (1) copy shall be sent to the Illinois EPA's regional office at the following address unless otherwise indicated:

Illinois Environmental Protection Agency  
Division of Air Pollution Control  
9511 West Harrison  
Des Plaines, Illinois 60016

If you have any questions on this, please call David Hulskotter at 217/782-2113.

Edwin C. Bakowski, P.E.  
Acting Manager, Permit Section  
Division of Air Pollution Control

Date Signed: \_\_\_\_\_

ECB:DWH:jws

cc: Illinois EPA, FOS Region 1  
Lotus Notes

Attachment A - Emission Summary

This attachment provides a summary of the maximum emissions from the pump manufacturing plant operating in compliance with the requirements of this federally enforceable permit. In preparing this summary, the Illinois EPA used the annual operating scenario which results in maximum emissions from such a plant. The resulting maximum emissions are below the levels, (e.g., 100 tons per year of VOM, 10 tons per year for a single HAP, and 25 tons per year for totaled HAPs) at which this source would be considered a major source for purposes of the Clean Air Act Permit Program. Actual emissions from this source will be less than predicted in this summary to the extent that less material is handled, and control measures are more effective than required in this permit.

<u>Emission Unit</u>	E M I S S I O N S (Tons/Year)						
	<u>VOM</u>	<u>NO<sub>x</sub></u>	<u>CO</u>	<u>PM</u>	<u>SO<sub>2</sub></u>	Single <u>HAP</u>	Total <u>HAPs</u>
8 Paint Spray Booths Natural Gas-Fired	14.00	----	----	3.52	----	----	----
Combustion Equipment	0.33	6.00	5.04	0.46	0.04	----	----
Wastewater Evaporator	5.15	----	----	----	----	----	----
2 Cold Cleaning Degreasers	<u>0.88</u>	----	----	----	----	----	----
Totals	20.36	<u>6.00</u>	<u>5.04</u>	<u>3.98</u>	<u>0.04</u>	<u>9.0</u>	<u>22.5</u>

DWH:jws