

217/782-2113

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT - RENEWAL

PERMITTEE

Rowe Construction Company
Attn: Scott Ketcham
1523 North Cottage Avenue
Bloomington, Illinois 61701

Application No.: 72100874

I.D. No.: 113825AAD

Applicant's Designation: ROWE090494

Date Received: April 6, 2004

Subject: Asphalt Batch Plant

Date Issued:

Expiration Date:

Location: Rural Route 1, Heyworth, McLean County

This permit is hereby granted to the above-designated Permittee to OPERATE emission source(s) and/or air pollution control equipment consisting of

- One (1) Batch Mix Asphalt Plant with a Distillate Oil-Fired Rotary Dryer
Controlled by Cyclone and Baghouse
- One (1) Distillate Oil-Fired Asphalt Storage tank Heater
- One (1) Asphalt Storage Tank

as described in the above-referenced application. This Permit is subject to standard conditions attached hereto and the following special condition(s):

- 1a. This federally enforceable state operating permit is issued to limit the emissions from the asphalt plant to less than major source thresholds (i.e., less than 100 tons/year for Carbon Monoxide (CO)). As a result, the source is excluded from requirements to obtain a Clean Air Act Permit Program (CAAPP) permit. The maximum emissions of this source, as limited by the conditions of this permit are described in Attachment A.
- b. Prior to issuance, a draft of this permit has undergone a public notice and comment period.
- c. This permit supersedes all operating permits issued for this location.
- 2a. No person shall cause or allow the emission of smoke or other particulate matter, with an opacity greater than 30 percent, into the atmosphere from any emission unit other than those emission units subject to the requirements of 35 Ill. Adm. Code 212.122, pursuant to 35 Ill. Adm. Code 212.123(a), except as allowed by 35 Ill. Adm. Code 212.123(b) and 212.124.
- b. Pursuant to 35 Ill. Adm. Code 212.206, no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period to exceed 0.15 kg of particulate matter per MW-hour of actual heat input from any fuel combustion emission unit using liquid fuel exclusively (0.10 lbs/mmBtu).

- c. Pursuant to 35 Ill. Adm. Code 212.301, no person shall cause or allow the emission of fugitive particulate matter from any process, including any material handling or storage activity, that is visible by an observer looking generally toward the zenith at a point beyond the property line of the source.
- d. Pursuant to 35 Ill. Adm. Code 212.321(a), no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period from any new process emission unit which, either alone or in combination with the emission of particulate matter from all other similar process emission units for which construction or modification commenced on or after April 14, 1972, at a source or premises, exceeds the allowable emission rates specified in 35 Ill. Adm. Code 212.321(c).
- 3a. Pursuant to 35 Ill. Adm. Code 214.122(b)(2), no person shall cause or allow the emission of sulfur dioxide into the atmosphere in any one hour period from any new fuel combustion source with actual heat input smaller than, or equal to, 73.2 MW (250 mmBtu/hour), burning liquid fuel exclusively to exceed 0.46 kg of sulfur dioxide per MW-hour of actual heat input when distillate fuel oil is burned (0.3 lbs/mmBtu).
- b. Pursuant to 35 Ill. Adm. Code 214.301, no person shall cause or allow the emission of sulfur dioxide into the atmosphere from any process emission source to excess 2000 ppm.
- 4a. Pursuant to 35 Ill. Adm. Code 215.122(b), no person shall cause or allow the loading of any organic material into any stationary tank having a storage capacity of greater than 946 l (250 gallons), unless such tank is equipped with a permanent submerged loading pipe, submerged fill, or an equivalent device approved by the Illinois EPA according to the provisions of 35 Ill. Adm. Code 201 or unless such tank is a pressure tank as described in 35 Ill. Adm. Code 215.121(a) or is fitted with a recovery system as described in 35 Ill. Adm. Code 215.121(b)(2).
- b. Pursuant to 35 Ill. Adm. Code 215.301, no person shall cause or allow the discharge of more than 3.6 kg/hr (8.0 lbs/hr) of organic material into the atmosphere from any emission source, except as provided in 35 Ill. Adm. Code 215.302, 215.303, 215.304 and the following exception: If no odor nuisance exists the limitation of 35 Ill. Adm. Code 215 Subpart K shall only apply to photochemically reactive material.
- 5. Pursuant to 35 Ill. Adm. Code 212.314, 35 Ill. Adm. Code 212.301 shall not apply and spraying pursuant to 35 Ill. Adm. Code 212.304 through 212.310 and 35 Ill. Adm. Code 212.312 shall not be required when the wind speed is greater than 40.2 km/hour (25 mph). Determination of wind speed for the purposes of this rule shall be by a one-hour average or hourly recorded value at the nearest official station of the U.S. Weather Bureau or by wind speed instruments operated on the site. In cases where the duration of

operations subject to this rule is less than one hour, wind speed may be averaged over the duration of the operations on the basis of on-site wind speed instrument measurements.

6. Pursuant to 35 Ill. Adm. Code 215.122(c), if no odor nuisance exists the limitations of 35 Ill. Adm. Code 215.122 shall only apply to the loading of volatile organic liquid with a vapor pressure of 17.24 kPa (2.5 psia) or greater at 294.3°K (70°F).
- 7a. The cyclone and baghouse shall be in operation at all times when the associated rotary dryer is in operation and emitting air contaminants.
- b. The Permittee shall, in accordance with the manufacturer(s) and/or vendor(s) recommendations, perform periodic maintenance on the cyclone and baghouse such that the cyclone and baghouse are kept in proper working condition and not cause a violation of the Illinois Environmental Protection Act or regulations promulgated therein.
- c. The drum dryer, boilers, and tank heater associated with the asphalt plant shall only be operated with distillate fuel oil as the fuel. The use of any other fuel in the drum dryer, boilers, and tank heaters requires that the Permittee first obtain a construction permit from the Illinois EPA and then perform stack testing to verify compliance with all applicable requirements.
- d. The Permittee shall not keep, store or utilize distillate fuel oil (Grades No. 1 and 2) at this source with a sulfur content greater than the larger of the following two values:
 - i. 0.28 weight percent, or
 - ii. The wt. percent given by the formula: Maximum wt. percent sulfur = $(0.00015) \times (\text{Gross heating value of oil, Btu/lbs})$.
- e. Organic liquid by-products or waste materials shall not be used in any emission unit at this source without written approval from the Illinois EPA.
- f. The Illinois EPA shall be allowed to sample all fuels stored at the above location.
- g. In the event that the operation of this source results in an odor nuisance, the Permittee shall take appropriate and necessary actions to minimize odors, including but not limited to, changes in raw material or installation of controls, in order to eliminate the nuisance.
- 8a. Emissions and operation of batch mix asphalt plant shall not exceed the following limits:
 - i. Asphalt Production Limits:

<u>(Tons/Hour)</u>	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
205	13,000	75,000

ii. Emissions from Batch Mixer/Dryer:

<u>Pollutant</u>	Emission Factor <u>(lb/Ton)</u>	Emissions	
		<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
CO	0.40	2.60	15.00
NO _x	0.12	0.80	4.50
PM	0.042	0.27	1.60
PM ₁₀	0.027	0.18	1.01
SO ₂	0.088	0.57	3.30
VOM	0.0082	0.05	0.30

iii. Emissions from Asphalt Silo Loading and Truck Loadout:

<u>Pollutant</u>	Emission Factor <u>(lb/Ton)</u>	Emissions	
		<u>(lb/Mo)</u>	<u>(Tons/Yr)</u>
CO	0.0007	9.10	0.03
PM	0.0007	9.10	0.03
PM ₁₀	0.0007	9.10	0.03
VOM	0.0048	62.40	0.18

iv. These limits are based on maximum asphalt production and standard AP-42 emission factors (Tables 11.1-1, 11.1-5, 11.1-6, and 11.1-14 AP-42, Volume I, Fifth Edition, Update 2001, December 2000).

iv. These limits are based on maximum asphalt production and standard AP-42 emission factors (Tables 11.1-1, 11.1-5, 11.1-6, and 11.1-14 AP-42, Volume I, Fifth Edition, Update 2001, December 2000).

b. Operation and combustion emissions of the asphalt tank heater shall not exceed the following limits:

<u>Pollutant</u>	Emission Factor <u>(lbs/10³ Gal)</u>	Emissions	
		<u>(lb/hr)</u>	<u>(Tons/Yr)</u>
Carbon Monoxide (CO)	5.00	0.08	0.33
Nitrogen Oxides (NO _x)	20.00	0.30	1.32
Particulate Matter (PM)	2.00	0.03	0.13
Sulfur Dioxide (SO ₂)	39.76	0.61	2.63
Volatile Organic Material (VOM)	0.20	0.01	0.01

These limits are based on maximum firing rate (2.115 mmBtu/hr), a heat content of 140,000 Btu/gallon for distillate fuel oil, 8,760 hours per year of operation, a sulfur content of 0.28% by weight,

and standard emission factors (Tables 1.3-1 and 1.3-3, AP-42, Fifth Edition, Volume I, Supplement E, September 1998).

- c. This permit is issued based on negligible emissions of volatile organic material (VOM) from the storage tank. For this purpose emissions from each emission source shall not exceed nominal emission rates of 0.1 lb/hour and 0.44 tons/year.
 - d. Compliance with annual limits shall be determined on a monthly basis from the sum of the data for the current month plus the preceding 11 months (running 12 month total).
- 9a. Pursuant to 35 Ill. Adm. Code 201.282, every emission source or air pollution control equipment shall be subject to the following testing requirements for the purpose of determining the nature and quantities of specified air contaminant emissions and for the purpose of determining ground level and ambient air concentrations of such air contaminants:
- i. Testing by Owner or Operator. The Illinois EPA may require the owner or operator of the emission source or air pollution control equipment to conduct such tests in accordance with procedures adopted by the Illinois EPA, at such reasonable times as may be specified by the Illinois EPA and at the expense of the owner or operator of the emission source or air pollution control equipment. The Illinois EPA may adopt procedures detailing methods of testing and formats for reporting results of testing. Such procedures and revisions thereto, shall not become effective until filed with the Secretary of State, as required by the APA Act. All such tests shall be made by or under the direction of a person qualified by training and/or experience in the field of air pollution testing. The Illinois EPA shall have the right to observe all aspects of such tests.
 - ii. Testing by the Illinois EPA. The Illinois EPA shall have the right to conduct such tests at any time at its own expense. Upon request of the Illinois EPA, the owner or operator of the emission source or air pollution control equipment shall provide, without charge to the Illinois EPA, necessary holes in stacks or ducts and other safe and proper testing facilities, including scaffolding, but excluding instruments and sensing devices, as may be necessary.
- b. Testing required by Condition 10 shall be performed upon a written request from the Illinois EPA by a qualified independent testing service.
- 10a. Pursuant to 35 Ill. Adm. Code 212.107, for both fugitive and nonfugitive particulate matter emissions, a determination as to the presence or absence of visible emissions from emission units shall be conducted in accordance with Method 22, 40 CFR part 60, Appendix A, except that the length of the observing period shall be at the

discretion of the observer, but not less than one minute. 35 Ill. Adm. Code 212 Subpart A shall not apply to 35 Ill. Adm. Code 212.301.

- b. Pursuant to 35 Ill. Adm. Code 212.109, except as otherwise provided in 35 Ill. Adm. Code Part 212, and except for the methods of data reduction when applied to 35 Ill. Adm. Code 212.122 and 212.123, measurements of opacity shall be conducted in accordance with Method 9, 40 CFR Part 60, Appendix A, and the procedures in 40 CFR 60.675(c) and (d), if applicable, except that for roadways and parking areas the number of readings required for each vehicle pass will be three taken at 5-second intervals. The first reading shall be at the point of maximum opacity and second and third readings shall be made at the same point, the observer standing at right angles to the plume at least 15 feet away from the plume and observing 4 feet above the surface of the roadway or parking area. After four vehicles have passed, the 12 readings will be averaged.
 - c. Pursuant to 35 Ill. Adm. Code 212.110(a), measurement of particulate matter emissions from stationary emission units subject to 35 Ill. Adm. Code Part 212 shall be conducted in accordance with 40 CFR part 60, Appendix A, Methods 5, 5A, 5D, or 5E.
 - d. Pursuant to 35 Ill. Adm. Code 212.110(b), the volumetric flow rate and gas velocity shall be determined in accordance with 40 CFR part 60, Appendix A, Methods 1, 1A, 2, 2A, 2C, 2D, 3, and 4.
 - e. Pursuant to 35 Ill. Adm. Code 212.110(c), upon a written notification by the Illinois EPA, the owner or operator of a particulate matter emission unit subject to 35 Ill. Adm. Code Part 212 shall conduct the applicable testing for particulate matter emissions, opacity, or visible emissions at such person's own expense, to demonstrate compliance. Such test results shall be submitted to the Illinois EPA within thirty (30) days after conducting the test unless an alternative time for submittal is agreed to by the Illinois EPA.
11. Inspections of the asphalt plants and control systems equipment and operations shall be performed as necessary but at least once per week when the affected asphalt plants are in operation to confirm compliance with the requirements of this permit.
12. Pursuant to 35 Ill. Adm. Code 212.110(e), the owner or operator of an emission unit subject to 35 Ill. Adm. Code Part 212 shall retain records of all tests which are performed. These records shall be retained for at least three (3) years after the date a test is performed.
- 13a. The Permittee shall maintain records of the following items so as to demonstrate compliance with the conditions of this permit:
- i. Records addressing use of good operating practices for the cyclone and baghouse:

- A. Operating logs for the asphalt plant dryer cyclone and baghouse, including operating data (pressure drop or stack condition), daily upon startup;
 - B. Records for periodic inspection of the cyclone and baghouse with date, individual performing the inspection, and nature of inspection; and
 - C. Records for prompt repair of defects, with identification and description of defect, effect on emissions, date identified, date repaired, and nature of repair.
- iii. Asphalt production (tons/month and tons/year);
 - iv. Total distillate fuel oil usage (gallons/month and gallons/year);
 - v. Sulfur content of distillate fuel oil (percent by weight) provided by the supplier of the fuel oil; and
 - vi. Monthly and Annual CO, NO_x, PM, SO₂, and VOM emissions, with supporting calculations (tons/month and tons/year).
- b. All records and logs required by this permit shall be retained at a readily accessible location at the source for at least five (5) years from the date of entry and shall be made available for inspection and copying by the Illinois EPA or USEPA upon request. Any records retained in an electronic format (e.g., computer storage device) shall be capable of being retrieved and printed on paper during normal source office hours so as to be able to respond to the Illinois EPA or USEPA request for records during the course of a source inspection.
14. Pursuant to 35 Ill. Adm. Code 212.110(d), a person planning to conduct testing for particulate matter emissions to demonstrate compliance shall give written notice to the Illinois EPA of that intent. Such notification shall be given at least thirty (30) days prior to the initiation of the test unless a shorter period is agreed to by the Illinois EPA. Such notification shall state the specific test methods from 35 Ill. Adm. Code 212.110 that will be used.
15. If there is an exceedance of or a deviation from the requirements of this permit as determined by the records required by this permit, the Permittee shall submit a report to the Illinois EPA's Compliance Section in Springfield, Illinois within 30 days after the exceedance or deviation. The report shall include the emissions released in accordance with the record keeping requirements, a copy of the relevant records, and a description of the exceedance or deviation and efforts to reduce emissions and future occurrences.

16. Two (2) copies of required reports and notifications shall be sent to:

Illinois Environmental Protection Agency
Division of Air Pollution Control
Compliance Section (#40)
P.O. Box 19276
Springfield, Illinois 62794-9276

and one (1) copy shall be sent to the Illinois EPA's regional office at the following address unless otherwise indicated:

Illinois Environmental Protection Agency
Division of Air Pollution Control
2009 Mall Street
Collinsville, Illinois 62234

17. The assembly of any these plants at a new location will require a construction permit for the new location. This permit must be obtained prior to commencing construction at the new location.

If you have any questions on this, please call Robert Bernoteit at 217/782-2113.

Edwin C. Bakowski, P.E.
Acting Manager, Permit Section
Division of Air Pollution Control

Date Signed: _____

ECB:RWB:jws

cc: Illinois EPA, FOS Region 3
Lotus Notes

Attachment A - Emission Summary

This attachment provides a summary of the maximum emissions from the asphalt plant operating in compliance with the requirements of this federally enforceable permit. In preparing this summary, the Illinois EPA used the annual operating scenario which results in maximum emissions from such a plant. The resulting maximum emissions are below the levels, (e.g., 100 tons per year of carbon monoxide) at which this source would be considered a major source for purposes of the Clean Air Act Permit Program. Actual emissions from this source will be less than predicted in this summary to the extent that less material is handled and control measures are more effective than required in this permit.

<u>Emissions Unit</u>	EMISSIONS (Tons/Year)				<u>VOM</u>
	<u>CO</u>	<u>NO_x</u>	<u>PM</u>	<u>SO₂</u>	
Oil-Fired Batch-Mix Asphalt	15.00	4.50	1.60	3.30	0.30
Asphalt Silo Loading & Truck Loadout	0.03	--	0.03	--	0.18
Tank Heater	0.33	1.32	0.13	2.63	0.01
Storage Tank	-----	-----	-----	-----	<u>0.44</u>
Totals:	<u>15.36</u>	<u>5.82</u>	<u>1.76</u>	<u>5.93</u>	<u>0.93</u>

RWB:jws