

217/782-2113

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT -- RENEWAL

PERMITTEE

T/CCI Manufacturing, L.L.C.
Attn: Monte Lange
2120 North 22nd Street
Decatur, Illinois 62526

<u>Application No.:</u> 99030033	<u>I.D. No.:</u> 115015AJV
<u>Applicant's Designation:</u>	<u>Date Received:</u> August 8, 2011
<u>Subject:</u> Air Conditioner Compressor Manufacturing Plant	
<u>Date Issued:</u>	<u>Expiration Date:</u>
<u>Location:</u> 2120 North 22nd Street, Decatur, Macon County	

This permit is hereby granted to the above-designated Permittee to OPERATE emission source(s) and/or air pollution control equipment consisting of sixteen (16) cold degreasers, one (1) compressor leak-testing tank, one (1) paint booth controlled by water curtain, and phenolic resin molding press pursuant to the above-referenced application. This Permit is subject to standard conditions attached hereto and the following special condition(s):

- 1a. This federally enforceable state operating permit is issued:
 - i. To limit the emissions of air pollutants from the source to less than major source thresholds (i.e., 100 tons/year for Volatile Organic Material (VOM), 10 tons/year for any single Hazardous Air Pollutant (HAP) and 25 tons/year for combination of such HAPs). As a result, the source is excluded from the requirement to obtain a Clean Air Act Permit Program (CAAPP) permit. The maximum emissions of this source, as limited by the conditions of this permit are described in Attachment A.
 - ii. To establish federally enforceable production and operating limitations, which restrict the potential to emit to less than 10 tons/year for any individual Hazardous Air Pollutant (HAP) and 25 tons/year of any combination of such HAPs so that the source is not subject to the requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Surface Coating of Miscellaneous Metal Parts and Products, 40 CFR 63 Subpart Mmmm.
- b. Prior to issuance, a draft of this permit has undergone a public notice and comment period.
- c. This permit supersedes all operating permit(s) issued for this location.

- 2a. Pursuant to 35 Ill. Adm. Code 212.123(a), no person shall cause or allow the emission of smoke or other particulate matter, with an opacity greater than 30 percent, into the atmosphere from any emission unit other than those emission units subject to 35 Ill. Adm. Code 212.122.
 - b. Pursuant to 35 Ill. Adm. Code 212.123(b), the emission of smoke or other particulate matter from any such emission unit may have an opacity greater than 30 percent but not greater than 60 percent for a period or periods aggregating 8 minutes in any 60 minute period provided that such opaque emissions permitted during any 60 minute period shall occur from only one such emission unit located within a 305 m (1000 ft) radius from the center point of any other such emission unit owned or operated by such person, and provided further that such opaque emissions permitted from each such emission unit shall be limited to 3 times in any 24 hour period.
 - c. Pursuant to 35 Ill. Adm. Code 212.301, no person shall cause or allow the emission of fugitive particulate matter from any process, including any material handling or storage activity, that is visible by an observer looking generally toward the zenith at a point beyond the property line of the emission source.
 - d. Pursuant to 35 Ill. Adm. Code 212.321(a), no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period from any new process emission unit which, either alone or in combination with the emission of particulate matter from all other similar process emission units for which construction or modification commenced on or after April 14, 1972, at a source or premises, exceeds the allowable emission rates specified in 35 Ill. Adm. Code 212.321(c).
3. Pursuant to 35 Ill. Adm. Code 215.301, no person shall cause or allow the discharge of more than 3.6 kg/hour (8 lbs/hour) of organic material into the atmosphere from any emission source, except as provided in 35 Ill. Adm. Code 215.302, 215.303, 215.304 and the following exception: If no odor nuisance exists the limitation of 35 Ill. Adm. Code 215 Subpart K shall apply only to photochemically reactive material.
- 4a. This permit is issued based on the sixteen (16) cold degreasers not being subject to the requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Halogenated Solvent Cleaning, 40 CFR 63 Subpart T because the cold degreasers do not use any solvent containing methylene chloride (CAS No. 75-09-2), perchloroethylene (CAS No. 127-18-4), trichloroethylene (CAS No. 79-01-6), 1,1,1-trichloroethane (CAS No. 71-55-6), carbon tetrachloride (CAS No. 56-23-5) or chloroform (CAS No. 67-66-3), or any combination of these halogenated HAP solvents, in a total concentration greater than 5 percent by weight, as a cleaning and/or drying agent.
 - b. This permit is issued based on the source not being subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for Surface Coating of Miscellaneous Metal Parts and Products, 40 CFR 63 Subpart MMMM because the source is not a major source of HAP emissions.

This is a result of the federally enforceable production and operating limitations, which restrict the potential to emit to less than 10 tons/year for any individual Hazardous Air Pollutant (HAP) and 25 tons/year of any combination of such HAPs.

- c. This permit is issued based on the coating operations at this source not being subject to the National Emission Standards for Hazardous Air Pollutants (NESAHP) for Paint Stripping And Miscellaneous Surface Coating at Area Sources, 40 CFR Part 63 Subpart HHHHHH. Pursuant to 40 CFR 63.11170(a)(3), you are subject to 40 CFR 63 Subpart HHHHHH if you operate an area source of HAP as defined in 40 CFR 63.11170(b), including sources that are part of a tribal, local, State, or Federal facility and you perform spray application of coatings that contain the target HAP, as defined in 40 CFR 63.11180, to a plastic and/or metal substrate on a part or product, except spray coating applications that meet the definition of facility maintenance or space vehicle in 40 CFR 63.11180.
5. Pursuant to 35 Ill. Adm. Code 212.314, 35 Ill. Adm. Code 212.301 shall not apply and spraying pursuant to 35 Ill. Adm. Code 212.304 through 212.310 and 35 Ill. Adm. Code 212.312 shall not be required when the wind speed is greater than 40.2 km/hr (25 mph). Determination of wind speed for the purposes of this rule shall be by a one-hour average or hourly recorded value at the nearest official station of the U.S. Weather Bureau or by wind speed instruments operated on the site. In cases where the duration of operations subject to this rule is less than one hour, wind speed may be averaged over the duration of the operations on the basis of on-site wind speed instrument measurements.
6. Pursuant to 35 Ill. Adm. Code 215.206(a)(2), the limitations of 35 Ill. Adm. Code 215 Subpart F shall not apply to coating plants in which the total coating usage does not exceed 9,463 l/yr (2,500 gal/yr).
- 7a. Pursuant to 35 Ill. Adm. Code 212.306, all normal traffic pattern access areas surrounding storage piles specified in 35 Ill. Adm. Code 212.304 and all normal traffic pattern roads and parking facilities which are located on mining or manufacturing property shall be paved or treated with water, oils or chemical dust suppressants. All paved areas shall be cleaned on a regular basis. All areas treated with water, oils or chemical dust suppressants shall have the treatment applied on a regular basis, as needed, in accordance with the operating program required by 35 Ill. Adm. Code 212.309, 212.310 and 212.312.
- b. Pursuant to 35 Ill. Adm. Code 212.309(a), the emission units described in 35 Ill. Adm. Code 212.304 through 212.308 and 35 Ill. Adm. Code 212.316 shall be operated under the provisions of an operating program, consistent with the requirements set forth in 35 Ill. Adm. Code 212.310 and 212.312, and prepared by the owner or operator and submitted to the Illinois EPA for its review. Such operating program shall be designed to significantly reduce fugitive particulate matter emissions.
- c. Pursuant to 35 Ill. Adm. Code 212.310, as a minimum the operating program shall include the following:

- i. The name and address of the source;
 - ii. The name and address of the owner or operator responsible for execution of the operating program;
 - iii. A map or diagram of the source showing approximate locations of storage piles, conveyor loading operations, normal traffic pattern access areas surrounding storage piles and all normal traffic patterns within the source;
 - iv. Location of unloading and transporting operations with pollution control equipment;
 - v. A detailed description of the best management practices utilized to achieve compliance with 35 Ill. Adm. Code 212 Subpart K, including an engineering specification of particulate collection equipment, application systems for water, oil, chemicals and dust suppressants utilized and equivalent methods utilized;
 - vi. Estimated frequency of application of dust suppressants by location of materials; and
 - vii. Such other information as may be necessary to facilitate the Illinois EPA's review of the operating program.
- d. Pursuant to 35 Ill. Adm. Code 212.312, the operating program shall be amended from time to time by the owner or operator so that the operating program is current. Such amendments shall be consistent with 35 Ill. Adm. Code 212 Subpart K and shall be submitted to the Illinois EPA for its review.
- 8a. Pursuant to 35 Ill. Adm. Code 215.182(a), no person shall operate a cold cleaning degreaser unless:
- i. Waste solvent shall be stored in covered containers only and not disposed of in such a manner that more than 20 percent of the waste solvent (by weight) is allowed to evaporate into the atmosphere;
 - ii. The cover of the degreaser is closed when parts are not being handled; and
 - iii. Parts are drained until dripping ceases.
- b. Pursuant to 35 Ill. Adm. Code 215.182(b), no person shall operate a cold cleaning degreaser unless:
- i. The degreaser is equipped with a cover which is closed whenever parts are not being handled in the cleaner. The cover shall be designed to be easily operated with one hand or with the mechanical assistance of springs, counterweights, or a powered system if:

- A. The solvent vapor pressure is greater than 2 kPa (15 mmHg or 0.3 psi) measured at 38°C (100°F);
 - B. The solvent is agitated; or
 - C. The solvent is heated above ambient room temperature.
- ii. The degreaser is equipped with a facility for draining cleaned parts. The drainage facility shall be constructed so that parts are enclosed under the cover while draining unless:
- A. The solvent vapor pressure is less than 4.3 kPa (32 mmHg or 0.6 psi) measured at 38°C (100°F); or
 - B. An internal drainage facility cannot be fitted into the cleaning system, in which case the drainage facility may be external.
- iii. The degreaser is equipped with one of the following control devices if the vapor pressure of the solvent is greater than 4.3 kPa (32 mmHg or 0.6 psi) measured at 38°C (100 1/4°F) or if the solvent is heated above 50°C (120°F) or its boiling point:
- A. A freeboard height of 7/10 of the inside width of the tank or 91 cm (36 in), whichever is less; or
 - B. Any other equipment or system of equivalent emission control as approved by the Illinois EPA. Such a system may include a water cover, refrigerated chiller or carbon adsorber.
- iv. A permanent conspicuous label summarizing the operating procedure is affixed to the degreaser; and
- v. If a solvent spray is used, the degreaser is equipped with a solid fluid stream spray, rather than a fine, atomized or shower spray.
- 9a. In the event that the operation of this source results in an odor nuisance, the Permittee shall take appropriate and necessary actions to minimize odors, including but not limited to, changes in raw material or installation of controls, in order to eliminate the nuisance.
- b. The Permittee shall, in accordance with the manufacturer(s) and/or vendor(s) recommendations, perform periodic maintenance on the water curtain such that the water curtain is kept in proper working condition and not cause a violation of the Illinois Environmental Protection Act or regulations promulgated therein.
- 10a. Emissions and operation of the paint booth and degreaser shall not exceed the following limits:

- i. VOM usage and emission from the paint booth and degreaser shall not exceed the following limits:

<u>Process</u>	<u>VOM Usage</u>		<u>VOM Emission</u>	
	<u>(tons/mo)</u>	<u>(tons/yr)</u>	<u>(tons/mo)</u>	<u>(tons/yr)</u>
Coating	1.05	10.42	1.05	10.42
Degreasing/testing	7.00	67.20	7.00	67.20

These limits are based on the maximum production rate and material balance calculations. The VOM/HAP emissions shall be determined from the following equation:

$$E = \Sigma(M_i \times V_i \times d_i)/2,000 - \Sigma(W_j \times V_j), \text{ where:}$$

E = VOM/HAP emissions (tons);

M_i = VOM/HAP-containing material usage (gallons);

V_i = VOM/HAP content of material (% by weight);

d_i = density of materials (lbs/gallon);

W_j = certified amount of waste shipped-off (tons); and

V_j = certified VOM/HAP content of the waste (fraction).

- ii. The emission of particulate matter (PM) from paint booth shall not exceed 0.20 tons/month and 2.00 tons/year. These limits are based on the maximum production rate, coatings properties and control equipment manufacturer's guaranteed efficiency. PM emission shall be calculated using the following equation:

$$E = [P_i \times S_i] \times OS \times (1 - CE)/2,000, \text{ where:}$$

E = PM emission (tons);

P_i = Coating usage (gallons);

S_i = Solids content of coating used (lbs/gallon);

OS = Overspray (assumed 60%); and

CE = Control Efficiency (assumed 90%)

- b. This permit is issued based on negligible emission of Volatile Organic Materials from the phenolic resin molding press. For this purpose, emissions shall not exceed nominal emission rates of 0.1 lb/hour and 0.44 tons/year.
- c. The emissions of hazardous air pollutants (HAP) as listed in Section 112(b) of the Clean Air Act from this source shall not exceed 0.9 tons/month and 9.0 tons/year of any single HAP and 2.25 tons/month and

22.5 tons/year of any combination of such HAPs. As a result of this condition, this permit is issued based on the emissions of any HAP from this source not triggering the requirement to obtain a CAAPP permit from the Illinois EPA and the NESHAP for Surface Coating of Miscellaneous Metal Parts and Products, 40 CFR 63 Subpart Mmmm.

- d. Compliance with annual limits shall be determined on a monthly basis from the sum of the data for the current month plus the preceding 11 months (12 month total).
- 11a. Pursuant to 35 Ill. Adm. Code 201.282, every emission source or air pollution control equipment shall be subject to the following testing requirements for the purpose of determining the nature and quantities of specified air contaminant emissions and for the purpose of determining ground level and ambient air concentrations of such air contaminants:
- i. Testing by Owner or Operator. The Illinois EPA may require the owner or operator of the emission source or air pollution control equipment to conduct such tests in accordance with procedures adopted by the Illinois EPA, at such reasonable times as may be specified by the Illinois EPA and at the expense of the owner or operator of the emission source or air pollution control equipment. The Illinois EPA may adopt procedures detailing methods of testing and formats for reporting results of testing. Such procedures and revisions thereto, shall not become effective until filed with the Secretary of State, as required by the APA Act. All such tests shall be made by or under the direction of a person qualified by training and/or experience in the field of air pollution testing. The Illinois EPA shall have the right to observe all aspects of such tests.
 - ii. Testing by the Illinois EPA. The Illinois EPA shall have the right to conduct such tests at any time at its own expense. Upon request of the Illinois EPA, the owner or operator of the emission source or air pollution control equipment shall provide, without charge to the Illinois EPA, necessary holes in stacks or ducts and other safe and proper testing facilities, including scaffolding, but excluding instruments and sensing devices, as may be necessary.
- b. Testing required by Conditions 12 and 13 shall be performed upon a written request from the Illinois EPA by a qualified independent testing service.
12. Pursuant to 35 Ill. Adm. Code 212.110(c), upon a written notification by the Illinois EPA, the owner or operator of a particulate matter emission unit subject to 35 Ill. Adm. Code Part 212 shall conduct the applicable testing for particulate matter emissions, opacity, or visible emissions at such person's own expense, to demonstrate compliance. Such test results shall be submitted to the Illinois EPA within thirty (30) days after conducting the test unless an alternative time for submittal is agreed to by the Illinois EPA.

- 13a. Pursuant to 35 Ill. Adm. Code 215.208(a), the VOM content of coatings shall be determined by Method 24, 40 CFR Part 60, Appendix A, except for glues and adhesive coatings, two component reactive coatings forming volatile reaction products, coatings requiring energy other than heat to initiate curing, and coatings requiring high temperature catalysis for curing, providing the person proposing testing of the material submits to the Illinois EPA proof that the Method 24 results would not be representative and proof that a proposed alternative test method gives representative, accurate test results. For printing inks, the volatile organic material content shall be determined by Method 24A, 40 CFR Part 60, Appendix A. Any alternate test method must be approved by the Illinois EPA which shall consider data comparing the performance of the proposed alternative to the performance of the approved test method(s). If the Illinois EPA determines that such data demonstrates that the proposed alternative will achieve results equivalent to the approved test method(s), the Illinois EPA shall approve the proposed alternative.
- b. Pursuant to 35 Ill. Adm. Code 215.208(b), transfer efficiency shall be determined by a method, procedure or standard approved by the USEPA, under the applicable new source performance standard or until such time as USEPA has approved and published such a method, procedure or standard, by any appropriate method, procedure or standard approved by the Illinois EPA.
14. Pursuant to 40 CFR 63.10(b)(3), if an owner or operator determines that his or her stationary source that emits (or has the potential to emit, without considering controls) one or more hazardous air pollutants regulated by any standard established pursuant to section 112(d) or (f) of the Clean Air Act, and that stationary source is in the source category regulated by the relevant standard, but that source is not subject to the relevant standard (or other requirement established under 40 CFR Part 63) because of limitations on the source's potential to emit or an exclusion, the owner or operator must keep a record of the applicability determination on site at the source for a period of 5 years after the determination, or until the source changes its operations to become an unaffected source, whichever comes first. The record of the applicability determination must be signed by the person making the determination and include an analysis (or other information) that demonstrates why the owner or operator believes the source is unaffected (e.g., because the source is an area source). The analysis (or other information) must be sufficiently detailed to allow the USEPA and/or Illinois EPA to make a finding about the source's applicability status with regard to the relevant standard or other requirement. If relevant, the analysis must be performed in accordance with requirements established in relevant subparts of 40 CFR Part 63 for this purpose for particular categories of stationary sources. If relevant, the analysis should be performed in accordance with USEPA guidance materials published to assist sources in making applicability determinations under Section 112 of the Clean Air Act, if any. The requirements to determine applicability of a standard under 40 CFR 63.1(b)(3) and to record the results of that determination under 40 CFR

- 63.10(b) (3) shall not by themselves create an obligation for the owner or operator to obtain a Title V permit.
15. Pursuant to 35 Ill. Adm. Code 212.110(e), the owner or operator of an emission unit subject to 35 Ill. Adm. Code Part 212 shall retain records of all tests which are performed. These records shall be retained for at least three (3) years after the date a test is performed.
- 16a. The Permittee shall maintain records of the following items so as to demonstrate compliance with the conditions of this permit:
- i. Coating and solvent usage (gallons/month, gallons/year);
 - ii. Coating and solvent VOM and HAP content (% by weight);
 - iii. Density of coating and solvent (lbs/gallon);
 - iv. Certified records of waste solvent shipped-off (gal/mo, gal/yr) and its VOM content;
 - v. Monthly and annual PM, VOM, and HAP emissions from the source with supporting calculations (tons/month and tons/year).
- b. All records and logs required by this permit shall be retained at a readily accessible location at the source for at least five (5) years from the date of entry and shall be made available for inspection and copying by the Illinois EPA or USEPA upon request. Any records retained in an electronic format (e.g., computer storage device) shall be capable of being retrieved and printed on paper during normal source office hours so as to be able to respond to an Illinois EPA or USEPA request for records during the course of a source inspection.
17. Pursuant to 35 Ill. Adm. Code 212.110(d), a person planning to conduct testing for particulate matter emissions to demonstrate compliance shall give written notice to the Illinois EPA of that intent. Such notification shall be given at least thirty (30) days prior to the initiation of the test unless a shorter period is agreed to by the Illinois EPA. Such notification shall state the specific test methods from 35 Ill. Adm. Code 212.110 that will be used.
18. Pursuant to 35 Ill. Adm. Code 215.206(c), the owner or operator of a coating line or a group of coating lines using touch-up and repair coatings that are exempted from the limitations of 35 Ill. Adm. Code 215.204(b), (d), (f), (g), (i), and (j) because of the provisions of 35 Ill. Adm. Code 215.206(b) shall notify the Illinois EPA in writing if the use of touch-up and repair coatings at the source ever exceeds a volume of 0.95 l (1 quart) per eight-hour period or exceeds 209 l/year (55 gallons/year) for any rolling twelve-month period within 30 days after any such exceedence. Such notification shall include a copy of any records of such exceedence.

19a. If there is an exceedance of or a deviation from the requirements of this permit as determined by the records required by this permit, the Permittee shall submit a report to the Agency's Compliance and Enforcement Section in Springfield, Illinois within 30 days after the exceedance. The report shall include the emissions released in accordance with the recordkeeping requirements, a copy of the relevant records, and a description of the exceedances or deviation and efforts to reduce emissions and future occurrences.

b. Two (2) copies of required reports and notifications shall be sent to:

Illinois Environmental Protection Agency
Division of Air Pollution Control
Compliance and Enforcement Section (#40)
P.O. Box 19276
Springfield, Illinois 62794-9276

and one (1) copy shall be sent to the Illinois EPA's regional office at the following address unless otherwise indicated:

Illinois Environmental Protection Agency
Division of Air Pollution Control
2009 Mall Street
Collinsville, Illinois 62234

If you have any questions on this permit, please call Valeriy Brodsky at 217/782-2113.

Edwin C. Bakowski, P. E.
Manager, Permit Section
Division of Air Pollution Control

Date Signed: _____

ECB:VJB:

cc: IEPA, FOS Region 3
Lotus Notes

Attachment A-Emissions Summary

This attachment provides a summary of the maximum emission from the Air Conditioner Compressor Manufacturing Plant, operating in compliance with the requirements of this federally enforceable permit. In preparing this summary, the Illinois EPA used the annual operating scenario which results in maximum emissions from such a plant. The resulting maximum emissions are below the levels (i.e., 100 tons/year for VOM, 10 tons/year for any single HAP and 25 tons/year for any combination of such HAPs) at which this source would be considered a major source for purposes of the Clean Air Act Permit Program. Actual emissions from this source will be less than predicted in this summary to the extent that material is handled, coatings used and control measures are more effective than in this permit.

<u>Emission Units</u>	E M I S S I O N S			
	<u>PM</u>	<u>VOM</u>	Single <u>HAP</u>	Combined <u>HAPs</u>
Coating Booth	2.00	10.42		
Degreasing and Testing Operations		67.20		
Phenolic Resin Molding Press	<u>--</u>	<u>0.44</u>	<u>--</u>	<u>--</u>
Plant-Wide Total	2.00	<u>78.06</u>	9.0	<u>22.5</u>

ECB:VJB: