

Dioxide (SO₂)). As a result, the source is excluded from requirements to obtain a Clean Air Act Permit Program (CAAPP) permit. The maximum emissions of this source, as limited by the conditions of this permit are described in Attachment A.

- b. Prior to issuance, a draft of this permit has undergone a public notice and comment period.
 - c. This permit supersedes the current permit(s) issued for this location.
- 2a. Both the batch mix and the drum mix asphalt plants are subject to the New Source Performance Standards (NSPS) for Hot Mix Asphalt Facilities, 40 CFR 60, Subparts A and I. The Illinois EPA is administering the NSPS in Illinois on behalf of the United States EPA under a delegation agreement.
- b. Pursuant to 40 CFR 60.92(a), on and after the date on which the performance test required to be conducted by 40 CFR 60.8 is completed, no owner or operator subject to the provisions of 40 CFR 60 Subpart I shall discharge or cause the discharge into the atmosphere from any affected facility any gases which:
 - i. Contain particulate matter in excess of 90 mg/dscm (0.04 gr/dscf).
 - ii. Exhibit 20 percent opacity or greater.
- 3a. The crushing plant is subject to the New Source Performance Standards (NSPS) for Nonmetallic Mineral Processing Plants, 40 CFR 60, Subparts A and 000. The Illinois EPA is administering these standards in Illinois on behalf of the United States EPA under a delegation agreement.
- b. Pursuant to 40 CFR 60.670(b), an affected facility that is subject to the provisions of 40 CFR 60 Subpart F or I or that follows in the plant process any facility subject to the provisions of 40 CFR 60 Subparts F or I is not subject to the provisions of 40 CFR 60 Subpart 000.
 - c. Pursuant to 40 CFR 60.672(b), on and after the sixtieth day after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup as required under 40 CFR 60.11, no owner or operator subject to the provisions of 40 CFR 60 Subpart 000 shall cause to be discharged into the atmosphere from any transfer point on belt conveyors or from any other affected facility any fugitive emissions which exhibit greater than 10 percent opacity, except as provided in 40 CFR 60.672(c), (d), and (e).
 - d. Pursuant to 40 CFR 60.672(c), on and after the sixtieth day after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup as required under 40 CFR 60.11, no owner or operator shall cause to be discharged into the atmosphere from any crusher, at which a capture system is not used, fugitive emissions which exhibit greater than 15 percent opacity.
 - e. Pursuant to 40 CFR 60.672(d), truck dumping of nonmetallic minerals into any screening operation, feed hopper, or crusher is exempt from the requirements of 40 CFR 60.672.
- 4a. Pursuant to 35 Ill. Adm. Code 212.123(a), no person shall cause or allow the emission of smoke or other particulate matter, with an opacity greater than 30

percent, into the atmosphere from any emission unit other than those emission units subject to 35 Ill. Adm. Code 212.122.

- b. Pursuant to 35 Ill. Adm. Code 212.123(b), the emission of smoke or other particulate matter from any such emission unit may have an opacity greater than 30 percent but not greater than 60 percent for a period or periods aggregating 8 minutes in any 60 minute period provided that such opaque emissions permitted during any 60 minute period shall occur from only one such emission unit located within a 305 m (1000 ft) radius from the center point of any other such emission unit owned or operated by such person, and provided further that such opaque emissions permitted from each such emission unit shall be limited to 3 times in any 24 hour period.
- c. Pursuant to 35 Ill. Adm. Code 212.206, no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period to exceed 0.15 kg of particulate matter per MW-hr of actual heat input from any fuel combustion emission unit (e.g., asphalt tank heaters and boilers associated with these asphalt plants) using liquid fuel exclusively (0.10 lbs/mmBtu).
- d. Pursuant to 35 Ill. Adm. Code 212.301, no person shall cause or allow the emission of fugitive particulate matter from any process, including any material handling or storage activity, that is visible by an observer looking generally toward the zenith at a point beyond the property line of the source.
- e. Pursuant to 35 Ill. Adm. Code 212.321(a), no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period from any new process emission unit which, either alone or in combination with the emission of particulate matter from all other similar process emission units for which construction or modification commenced on or after April 14, 1972, at a source or premises, exceeds the allowable emission rates specified in 35 Ill. Adm. Code 212.321(c).
- 5a. Pursuant to 35 Ill. Adm. Code 214.122(b)(2), no person shall cause or allow the emission of sulfur dioxide into the atmosphere in any one hour period from any new fuel combustion source (e.g., asphalt tank heaters and boilers associated with these asphalt plants) with actual heat input smaller than, or equal to, 73.2 MW (250 mmBtu/hour), burning liquid fuel exclusively To exceed 0.46 kg of sulfur dioxide per MW-hr of actual heat input when distillate fuel oil is burned (0.3 lbs/mmBtu).
- b. Pursuant to 35 Ill. Adm. Code 214.301, no person shall cause or allow the emission of sulfur dioxide into the atmosphere from any process emission unit to excess 2000 ppm.
- 6a. Pursuant to 35 Ill. Adm. Code 215.122(b), no person shall cause or allow the loading of any organic material into any stationary tank having a storage capacity of greater than 946 l (250 gallons), unless such tank is equipped with a permanent submerged loading pipe, submerged fill, or an equivalent device approved by the Agency according to the provisions of 35 Ill. Adm. Code 201 or unless such tank is a pressure tank as described in 35 Ill. Adm. Code 215.121(a) or is fitted with a recovery system as described in 35 Ill. Adm. Code 215.121(b)(2).
- b. Pursuant to 35 Ill. Adm. Code 215.301, no person shall cause or allow the discharge of more than 3.6 kg/hour (8 lbs/hour) of organic material into the

atmosphere from any emission source, except as provided in 35 Ill. Adm. Code 215.302, 215.303, 215.304 and the following exception: If no odor nuisance exists the limitation of 35 Ill. Adm. Code 215 Subpart K shall only apply to photochemically reactive material.

7. Pursuant to 35 Ill. Adm. Code 212.314, 35 Ill. Adm. Code 212.301 shall not apply and spraying pursuant to 35 Ill. Adm. Code 212.304 through 212.310 and 35 Ill. Adm. Code 212.312 shall not be required when the wind speed is greater than 40.2 km/hour (25 mph). Determination of wind speed for the purposes of this rule shall be by a one-hour average or hourly recorded value at the nearest official station of the U.S. Weather Bureau or by wind speed instruments operated on the site. In cases where the duration of operations subject to this rule is less than one hour, wind speed may be averaged over the duration of the operations on the basis of on-site wind speed instrument measurements.
8. Pursuant to 35 Ill. Adm. Code 215.122(c), if no odor nuisance exists the limitations of this 35 Ill. Adm. Code 215.122 shall only apply to the loading of volatile organic liquid with a vapor pressure of 17.24 kPa (2.5 psia) or greater at 294.3°K (70°F).
9. Pursuant to 40 CFR 60.11(d), at all times, including periods of startup, shutdown, and malfunction, owners and operators shall to the extent practicable, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Illinois EPA or USEPA which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source.
- 10a. The baghouse shall be in operation at all times when the associated mixer/dryer is in operation and emitting air contaminants.
 - b. The Permittee shall, in accordance with the manufacturer(s) and/or vendor(s) recommendations, perform periodic maintenance on the baghouse such that the pollution control equipment is kept in proper working condition and not to cause a violation of the Illinois Environmental Protection Act or regulations promulgated therein.
 - c. The drum mixer and dryer shall only be operated with fuel oil grades No. 2 as the fuel. The use of any other fuel in the drum mixer and drum dryer requires that the Permittee first obtain a construction permit from the Illinois EPA and then perform stack testing to verify compliance with all applicable requirements.
 - d. The batch mixer and dryer shall only be operated with natural gas as the fuel. The use of any other fuel in the batch mixer and dryer requires that the Permittee first obtain a construction permit from the Illinois EPA and then perform stack testing to verify compliance with all applicable requirements.
 - e. The Permittee shall not keep, store, or use distillate fuel oil (Grades No. 1 and 2) at this source with a sulfur content greater than the larger of the following two values:
 - i. 0.28 weight percent, or

ii. The wt. percent given by the formula: Maximum wt. percent sulfur = (0.000015) x (Gross heating value of oil, Btu/lb).

f. Organic liquid by-products or waste materials shall not be used in any emission unit at this source without written approval from the Illinois EPA.

g. The Illinois EPA shall be allowed to sample all fuels stored at the above location.

h. In the event that the operation of this source results in an odor nuisance, the Permittee shall take appropriate and necessary actions to minimize odors, including but not limited to, changes in raw material or installation of controls, in order to eliminate the nuisance.

i. The surface moisture content of the aggregate to be processed in the crushing plant associated with the affected drum-mix asphalt plant shall be at least 1.5% by weight. The Permittee shall show compliance with this requirement as follows:

i. Water sprays shall be used on the emission units associated with the crushing plant (e.g., crushers, conveyors, and stockpiles, etc.) as necessary, except when weather conditions are below or expected to fall below freezing temperatures, to produce a moisture content of 1.5% by weight or higher to reduce particulate matter emissions; or

ii. Demonstrate compliance with Condition 10(i) by following the testing requirements of Condition 18(a).

11a. Emissions and operation of the drum mix asphalt plant shall not exceed the following limit:

i. Asphalt production limits:

	Asphalt Concrete Production		
	<u>(Tons/Hour)</u>	<u>(Tons/Month)</u>	<u>(Tons/Year)</u>
	320	50,000	300,000

ii. Emissions from drum mixer/dryer:

<u>Pollutant</u>	Emission Factor <u>(lbs/Ton)</u>	Emissions	
		<u>(Tons/Month)</u>	<u>(Tons/Year)</u>
CO	0.13	3.30	19.50
NO _x	0.055	1.40	8.30
PM	0.033	0.90	5.00
PM ₁₀	0.023	0.60	3.50
SO ₂	0.011	0.30	1.70
VOM	0.032	0.80	4.80

These limits are based on the maximum asphalt production and standard emission factors (Tables 11.1-3, 11.1-7, 11.1-8, and 11.1-14, AP-42, Volume I, Fifth Edition, Update 2001, December 2000).

b. Emissions and operation of the batch mix asphalt plant shall not exceed the following limit:

i. Asphalt production limits:

Asphalt Concrete Production		
<u>(Tons/Hr)</u>	<u>(Tons/Month)</u>	<u>(Tons/Year)</u>
250	33,000	200,000

ii. Emissions from batch mixer/dryer:

<u>Pollutant</u>	Emission Factor	Emissions	
	<u>(lbs/Ton)</u>	<u>(Tons/Month)</u>	<u>(Tons/Year)</u>
CO	0.400	6.60	40.0
NO _x	0.025	0.70	2.50
PM	0.042	0.70	4.20
PM ₁₀	0.027	0.50	2.70
SO ₂	0.0046	0.10	0.10
VOM	0.0082	0.20	0.90

These limits are based on the maximum asphalt production and standard emission factors (Tables 11.1-3, 11.1-7, 11.1-8, and 11.1-14, AP-42, Volume I, Fifth Edition, Update 2001, December 2000).

c. Emissions from asphalt silo loading and truck loadout:

<u>Pollutant</u>	Emission Factor	Emissions	
	<u>(lb/Ton)</u>	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
CO	0.00253	0.11	0.63
PM	0.00111	0.05	0.28
PM ₁₀	0.00111	0.05	0.28
VOM	0.01635	0.68	4.09

These limits are based on maximum asphalt production and standard AP-42 emission factors (Tables 11.1-1, 11.1-3, 11.1-5, 11.1-6, 11.1-7, 11.1-8, and 11.1-14 AP-42, Volume I, Fifth Edition, Update 2001, December 2000).

d. Emissions and operation of the crushing plant shall not exceed the following limits:

i. Total reclaimed asphalt pavement (RAP) and recycled concrete throughput:

<u>Equipment</u>	Aggregate Throughput	
	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
1 - Primer Crusher	90,000	900,000
1 - Secondary Crusher	10,000	100,000
1 - Tertiary Crusher	35,000	350,000
4 - Screens	165,000	1,650,000
39 - Conveyor	650,000	6,500,000
6 - Storage Bins	40,000	400,000
North Wash Plant Bin	16,000	160,000
South Wash Plant Bin	6,000	60,000

ii. Particulate matter emissions from the crushing plant:

<u>Equipment</u>	Emission Factor		Emissions			
	<u>PM</u>	<u>PM₁₀</u>	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
1 - Primer Crusher	0.0054	0.0024	0.24	2.43	0.11	1.08

1 - Secondary Crusher	0.0054	0.0024	0.03	0.27	0.01	0.12
1 - Tertiary Crusher	0.0054	0.0024	0.10	0.95	0.04	0.42
4 - Screens	0.0022	0.00074	0.18	1.82	0.06	0.61
39 - Conveyor	0.003	0.0011	0.98	9.76	0.36	3.58
6 - Storage Bins	0.003	0.0011	0.06	0.61	0.02	0.22
North Wash Plant Bin	0.003	0.0011	0.03	0.25	0.01	0.09
South Wash Plant Bin	0.003	0.0011	0.01	<u>0.10</u>	0.01	<u>0.03</u>
			Totals:	16.19		<u>6.15</u>

These limits are based on the maximum processing throughput of 900,000 tons/year and standard emission factors for conveying, and screening (controlled) (Table 11.19.2-2, AP-42, Fifth Edition, Volume I, Update 2004, August 2004).

e. Emissions and operation of the central mix concrete batch plant shall not exceed the following limits:

i. Operation of the central mix concrete batch plant shall not exceed the following limits:

<u>Equipment</u>	<u>Aggregate Throughput</u>	
	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
Total Concrete Production	96,000	960,000
Aggregate Transfer	44,760	447,600
Sand Transfer	34,272	342,720
Cement Silo Loading*	11,784	117,840
Cement Supplement Loading*	1,752	17,520
Weigh Hopper Loading	79,032	790,320
Mixer Loading**,*	13,536	135,360

ii. Particulate matter emissions from the concrete batch plant:

<u>Operation</u>	<u>Emission Factor</u> (lb/Ton)		<u>Emissions</u>			
	<u>PM</u>	<u>PM₁₀</u>	<u>PM</u>		<u>PM₁₀</u>	
			<u>(Ton/Mo)</u>	<u>(Tons/yr)</u>	<u>(Ton/Mo)</u>	<u>(Tons/yr)</u>
Aggregate Transfer	0.0069	0.0033	0.15	1.54	0.07	0.74
Sand Transfer	0.0021	0.00099	0.04	0.36	0.02	0.17
Cement Silo Loading*	0.00099	0.00034	0.01	0.06	0.01	0.02
Cement Supplement Loading*	0.0089	0.0049	0.01	0.08	0.01	0.04
Weigh Hopper Loading	0.0051	0.0024	0.20	2.02	0.10	0.95
Mixer Loading**,*	0.0173	0.0048	0.18	<u>1.17</u>	0.03	<u>0.32</u>
			Totals:	<u>5.23</u>		<u>2.24</u>

* Particulate matter control due to dust collector.

** Based on cement and cement supplement only.

These emissions are based on a maximum concrete throughput 960,000 tons (480,000 cubic yards) per year and standard emission factors (Table 11.12-2, AP-42, Fifth Edition, Volume I, June 2006).

f. This permit is issued based on negligible emissions of VOM from the four asphalt storage tanks. For this purpose, emissions from all such sources shall not exceed nominal emission rates of 0.1 lb/hour and 0.44 tons/year total.

g. Compliance with annual limits shall be determined on a monthly basis from the sum of the data for the current month plus the preceding 11 months (running 12

month total).

- 12a. Pursuant to 40 CFR 60.8(a), at such other times as may be required by the Illinois EPA or USEPA under section 114 of the Clean Air Act, the owner or operator of such facility shall conduct performance test(s) and furnish the Illinois EPA or USEPA a written report of the results of such performance test(s).
- b. Pursuant to 40 CFR 60.8(b), performance tests shall be conducted and data reduced in accordance with the test methods and procedures contained in each applicable subpart of 40 CFR Part 60 unless the Illinois EPA or USEPA:
 - i. Specifies or approves, in specific cases, the use of a reference method with minor changes in methodology;
 - ii. Approves the use of an equivalent method;
 - iii. Approves the use of an alternative method the results of which he has determined to be adequate for indicating whether a specific source is in compliance;
 - iv. Waives the requirement for performance tests because the owner or operator of a source has demonstrated by other means to the Illinois EPA's or USEPA's satisfaction that the affected facility is in compliance with the standard; or
 - v. Approves shorter sampling times and smaller sample volumes when necessitated by process variables or other factors. Nothing in this paragraph shall be construed to abrogate the Illinois EPA's or USEPA's authority to require testing under section 114 of the Clean Air Act.
- c. Pursuant to 40 CFR 60.8(c), performance tests shall be conducted under such conditions as the Illinois EPA or USEPA shall specify to the plant operator based on representative performance of the affected facility. The owner or operator shall make available to the Illinois EPA or USEPA such records as may be necessary to determine the conditions of the performance tests. Operations during periods of startup, shutdown, and malfunction shall not constitute representative conditions for the purpose of a performance test nor shall emissions in excess of the level of the applicable emission limit during periods of startup, shutdown, and malfunction be considered a violation of the applicable emission limit unless otherwise specified in the applicable standard.
- d. Pursuant to 40 CFR 60.8(d), the owner or operator of an affected facility shall provide the Illinois EPA or USEPA at least 30 days prior notice of any performance test, except as specified under other subparts, to afford the Illinois EPA or USEPA the opportunity to have an observer present. If after 30 days notice for an initially scheduled performance test, there is a delay (due to operational problems, etc.) in conducting the scheduled performance test, the owner or operator of an affected facility shall notify the Illinois EPA or USEPA as soon as possible of any delay in the original test date, either by providing at least 7 days prior notice of the rescheduled date of the performance test, or by arranging a rescheduled date with the Illinois EPA or USEPA by mutual agreement.

- e. Pursuant to 40 CFR 60.8(e), the owner or operator of an affected facility shall provide, or cause to be provided, performance testing facilities as follows:
 - i. Sampling ports adequate for test methods applicable to such facility. This includes:
 - A. Constructing the air pollution control system such that volumetric flow rates and pollutant emission rates can be accurately determined by applicable test 1 methods and procedures; and
 - B. Providing a stack or duct free of cyclonic flow during performance tests, as demonstrated by applicable test methods and procedures.
 - ii. Safe sampling platform(s).
 - iii. Safe access to sampling platform(s).
 - iv. Utilities for sampling and testing equipment.
- f. Pursuant to 40 CFR 60.8(f), unless otherwise specified in the applicable subpart of 40 CFR Part 60, each performance test shall consist of three separate runs using the applicable test method. Each run shall be conducted for the time and under the conditions specified in the applicable standard under 40 CFR Part 60. For the purpose of determining compliance with an applicable standard under 40 CFR Part 60, the arithmetic means of results of the three runs shall apply. In the event that a sample is accidentally lost or conditions occur in which one of the three runs must be discontinued because of forced shutdown, failure of an irreplaceable portion of the sample train, extreme meteorological conditions, or other circumstances, beyond the owner or operator's control, compliance may, upon the Illinois EPA's or USEPA's approval, be determined using the arithmetic mean of the results of the two other runs.
- 13a. Pursuant to 40 CFR 60.93(a), in conducting the performance tests required in 40 CFR 60.8, the owner or operator shall use as reference methods and procedures the test methods in appendix A of 40 CFR Part 60 or other methods and procedures as specified in this section, except as provided in 40 CFR 60.8(b).
- b. Pursuant to 40 CFR 60.93(b), the owner or operator shall determine compliance with the particulate matter standards in 40 CFR 60.92 as follows:
 - i. Method 5 shall be used to determine the particulate matter concentration. The sampling time and sample volume for each run shall be at least 60 minutes and 0.90 dscm (31.8 dscf).
 - ii. Method 9 and the procedures in 40 CFR 60.11 shall be used to determine opacity.
- 14a. Pursuant to 40 CFR 60.675(a), in conducting the performance tests required in 40 CFR 60.8, the owner or operator shall use as reference methods and procedures the test methods in appendix A of 40 CFR Part 60 or other methods and procedures as specified in this section, except as provided in 40 CFR 60.8(b). Acceptable alternative methods and procedures are given in 40 CFR 60.675(e).

- b. i. Pursuant to 40 CFR 60.675(c)(1), in determining compliance with the particulate matter standards in 40 CFR 60.672(b) and (c), the owner or operator shall use Method 9 and the procedures in 40 CFR 60.11, with the following additions:
 - A. The minimum distance between the observer and the emission source shall be 4.57 meters (15 feet).
 - B. The observer shall, when possible, select a position that minimizes interference from other fugitive emission sources (e.g., road dust). The required observer position relative to the sun (Method 9, Section 2.1) must be followed.
 - C. For affected facilities using wet dust suppression for particulate matter control, a visible mist is sometimes generated by the spray. The water mist must not be confused with particulate matter emissions and is not to be considered a visible emission. When a water mist of this nature is present, the observation of emissions is to be made at a point in the plume where the mist is no longer visible.
- ii. Pursuant to 40 CFR 60.675(c)(2), When determining compliance with the fugitive emissions standard for any affected facility described under 60.672(b), the duration of the Method 9 observations may be reduced from 3 hours (thirty 6-minute averages) to 1 hour (ten 6-minute averages) only if the following conditions apply:
 - A. There are no individual readings greater than 10 percent opacity; and
 - B. There are no more than 3 readings of 10 percent for the 1-hour period.
- iii. Pursuant to 40 CFR 60.675(c)(3), When determining compliance with the fugitive emissions standard for any crusher at which a capture system is not used as described under 40 CFR 60.672(c), the duration of the Method 9 observations may be reduced from 3 hours (thirty 6-minute averages) to 1 hour (ten 6-minute averages) only if the following conditions apply:
 - A. There are no individual readings greater than 15 percent opacity; and
 - B. There are no more than 3 readings of 15 percent for the 1-hour period.
- c. Pursuant to 40 CFR 60.675(e)(1), the owner or operator may use the following as alternatives, for the method and procedure of 40 CFR 60.675(c), if emissions from two or more facilities continuously interfere so that the opacity of fugitive emissions from an individual affected facility cannot be read, either of the following procedures may be used:
 - i. Use for the combined emission stream the highest fugitive opacity standard applicable to any of the individual affected facilities contributing to the emissions stream.

- ii. Separate the emissions so that the opacity of emissions from each affected facility can be read.
- d. Pursuant to 40 CFR 60.675(g), if, after 30 days notice for an initially scheduled performance test, there is a delay (due to operational problems, etc.) in conducting any rescheduled performance test required in this section, the owner or operator of an affected facility shall submit a notice to the Illinois EPA or USEPA at least 7 days prior to any rescheduled performance test.
- e. Pursuant to 40 CFR 60.675(h), initial Method 9 performance tests under 40 CFR 60.11 and 40 CFR 60.675 are not required for:
 - i. Wet screening operations and subsequent screening operations, bucket elevators, and belt conveyors that process saturated material in the production line up to, but not including the next crusher, grinding mill or storage bin.
 - ii. Screening operations, bucket elevators, and belt conveyors in the production line downstream of wet mining operations, that process saturated materials up to the first crusher, grinding mill, or storage bin in the production line.
- 15a. Pursuant to 35 Ill. Adm. Code 201.282, every emission source or air pollution control equipment shall be subject to the following testing requirements for the purpose of determining the nature and quantities of specified air contaminant emissions and for the purpose of determining ground level and ambient air concentrations of such air contaminants:
 - i. Testing by Owner or Operator. The Illinois EPA may require the owner or operator of the emission source or air pollution control equipment to conduct such tests in accordance with procedures adopted by the Illinois EPA, at such reasonable times as may be specified by the Illinois EPA and at the expense of the owner or operator of the emission source or air pollution control equipment. The Illinois EPA may adopt procedures detailing methods of testing and formats for reporting results of testing. Such procedures and revisions thereto, shall not become effective until filed with the Secretary of State, as required by the APA Act. All such tests shall be made by or under the direction of a person qualified by training and/or experience in the field of air pollution testing. The Illinois EPA shall have the right to observe all aspects of such tests.
 - ii. Testing by the Illinois EPA. The Illinois EPA shall have the right to conduct such tests at any time at its own expense. Upon request of the Illinois EPA, the owner or operator of the emission source or air pollution control equipment shall provide, without charge to the Illinois EPA, necessary holes in stacks or ducts and other safe and proper testing facilities, including scaffolding, but excluding instruments and sensing devices, as may be necessary.
- b. Testing required by Condition 16 shall be performed upon a written request from the Illinois EPA by a qualified independent testing service.
- 16. Pursuant to 35 Ill. Adm. Code 212.110(c), upon a written notification by the Illinois EPA, the owner or operator of a particulate matter emission unit

subject to 35 Ill. Adm. Code Part 212 shall conduct the applicable testing for particulate matter emissions, opacity, or visible emissions at such person's own expense, to demonstrate compliance. Such test results shall be submitted to the Illinois EPA within thirty (30) days after conducting the test unless an alternative time for submittal is agreed to by the Illinois EPA.

17. Inspections of the affected asphalt plants and control systems equipment and operations shall be performed as necessary but at least once per week when the affected drum-mix asphalt plant is in operation to confirm compliance with the requirements of this permit.
- 18a. The moisture content of a representative sample of the aggregate processed in the crushing plant associated with the affected drum-mix asphalt plant shall be measured at least one per week using ASTM Procedures (C566-67) for total moisture content of material.
 - b. Inspections of the affected drum-mix asphalt plant and control systems equipment and operations shall be performed as necessary but at least once per week when the affected drum-mix asphalt plant is in operation to confirm compliance with the requirements of this permit.
 - c.
 - i. The water supply to the spray equipment shall be equipped with a metering device used to determine water usage for the control of particulate matter emissions.
 - ii. Inspections of water spray equipment and operation (such as leaking, maintaining adequate flow, clogging of flow lines, etc.) shall be performed at least once per week when the crushing plant associated with the affected drum-mix asphalt plant is in operation.
- 19a. Pursuant to 40 CFR 60.7(b), any owner or operator subject to the provisions of 40 CFR Part 60 shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of an affected facility; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative.
 - b. Pursuant to 40 CFR 60.7(f), any owner or operator subject to the provisions of 40 CFR Part 60 shall maintain a file of all measurements, including continuous monitoring system, monitoring device, and performance testing measurements; all continuous monitoring system performance evaluations; all continuous monitoring system or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; and all other information required by 40 CFR Part 60 recorded in a permanent form suitable for inspection. The file shall be retained for at least two years following the date of such measurements, maintenance, reports, and records.
20. Pursuant to 35 Ill. Adm. Code 212.110(e), the owner or operator of an emission unit subject to 35 Ill. Adm. Code Part 212 shall retain records of all tests which are performed. These records shall be retained for at least three (3) years after the date a test is performed.
- 21a. The Permittee shall maintain records of the following items so as to demonstrate compliance with the conditions of this permit:
 - i. Records addressing use of good operating practices for the baghouses associated with the batch-mix and drum mix asphalt plants:

- A. Operating logs for each baghouse, including operating data (pressure drop or stack condition), daily upon startup;
 - B. Records for periodic inspection of the baghouses with the batch-mix and drum mix asphalt plants with date, individual performing the inspection, and nature of inspection; and
 - C. Records for prompt repair of defects, with identification and description of defect, effect on emissions, date identified, date repaired, and nature of repair.
- ii. Records addressing use of good operating practices for the crushing plant:
- A. If the Permittee is relying on the requirements of Condition 16 to demonstrate compliance with Condition 8(j), the Permittee shall maintain records of all moisture content tests performed including date, time, individual performing test, and location of sample (e.g., prior to crushing, stockpiles, etc.);
 - B. If the Permittee is relying on Condition 18(c) to demonstrate compliance with Condition 10(i), the Permittee shall maintain operating logs for the water spray equipment, including dates and times of usage, malfunctions (type, date, and measures taken to correct), water pressure, and dates when there was at least 0.25" of rainfall during the preceding 24 hours and the water spray equipment was not operated; and
 - C. The Permittee shall maintain weekly records of water consumption in the spray equipment, as determined by the meter required by Condition 18(c)(i) and the amount of precipitation specified in Condition 21(a)(ii)(B).
- iii. Asphalt concrete production in each asphalt plant (tons/month and tons/year);
- iv. Natural gas usage (mmscf/month and mmscf/year);
- v. Distillate fuel oil usage (gallons/month and gallons/year);
- vi. The sulfur content of the fuel oil used in the drum-mix asphalt plants (% weight), this shall be recorded for each shipment of oil delivered to the source.
- vii. Monthly and Annual CO, NO_x, PM, PM₁₀, SO₂, and VOM with supporting calculations (tons/month and tons/year).
- b. All records and logs required by this permit shall be retained at a readily accessible location at the source for at least five (5) years from the date of entry and shall be made available for inspection and copying by the Illinois EPA or USEPA upon request. Any records retained in an electronic format (e.g., computer) shall be capable of being retrieved and printed on paper during normal source office hours so as to be able to respond to an Illinois EPA or USEPA request for records during the course of a source inspection.

22. Pursuant to 35 Ill. Adm. Code 212.110(d), a person planning to conduct testing for particulate matter emissions to demonstrate compliance shall give written notice to the Illinois EPA of that intent. Such notification shall be given at least thirty (30) days prior to the initiation of the test unless a shorter period is agreed to by the Illinois EPA. Such notification shall state the specific test methods from 35 Ill. Adm. Code 212.110 that will be used.

23a. If there is an exceedance of or a deviation from the requirements of this permit as determined by the record required by this permit, the Permittee shall submit a report to the Illinois EPA's Compliance Section in Springfield, Illinois within 30 days after the exceedance or deviation. The report shall include the emissions released in accordance with the recordkeeping requirements, a copy of the relevant records, and a description of the exceedances or deviation and efforts to reduce emissions and future occurrences.

b. Two (2) copies of required reports and notifications shall be sent to:

Illinois Environmental Protection Agency
Division of Air Pollution Control
Compliance Section (#40)
P.O. Box 19276
Springfield, Illinois 62794-9276

and one (1) copy shall be sent to the Illinois EPA's regional office at the following address unless otherwise indicated:

Illinois Environmental Protection Agency
Division of Air Pollution Control
5415 North University
Peoria, Illinois 61614

23. The assembly of this plant at a new location will require a construction permit for the new location. This permit must be obtained prior to commencing construction at the new location.

If you have any questions on this, please call German Barria at 217/782-2113.

Edwin C. Bakowski, P.E.
Manager, Permit Section
Division of Air Pollution Control

Date Signed: _____

ECB:GB:jws

cc: Illinois EPA, FOS Region 2
Lotus Notes

Attachment A - Emissions Summary

This attachment provides a summary of the maximum emissions from the asphalt plant operating in compliance with the requirements of this federally enforceable permit. In preparing this summary, the Illinois EPA used the annual operating scenario which results in maximum emissions from such a plant. The resulting maximum emissions are well below the levels, (e.g., 100 tons per year of CO, NO_x, PM₁₀ and SO₂) at which this source would be considered a major source for purposes of the Clean Air Act Permit Program. Actual emissions from this source will be less than predicted in this summary to the extent that less material is handled and control measures are more effective than required in this permit.

<u>Item of Equipment</u>	<u>Annual Emissions (Tons/year)</u>				
	<u>CO</u>	<u>NO_x</u>	<u>PM</u>	<u>SO₂</u>	<u>VOM</u>
Batch Mixer/Dryer	40.00	2.50	4.20	2.70	0.10
Drum Mixer/Dryer	19.50	8.30	5.00	3.50	1.70
Asphalt Silos and Truck Loadout	0.63		0.28	0.28	----
4 Asphalt Oil Tanks	----	----	----	----	----
Central Mix Concrete Batch Plant	----	----	5.23	2.24	----
Stone Crushing Plant	----	----	<u>16.19</u>	<u>6.15</u>	----
Total	<u>60.13</u>	<u>10.80</u>	<u>30.90</u>	<u>14.87</u>	<u>1.80</u>

ECB:GB:jws