

217/782-2113

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT

PERMITTEE

Intermatic Incorporated
Attn: Ralph Tassone, Dir. OSHA/EPA Compliance
7777 Winn Road
Spring Grove, Illinois 60081

<u>Application No.:</u> 96030122	<u>I.D. No.:</u> 111080AAC
<u>Applicant's Designation:</u>	<u>Date Received:</u> December 4, 2007
<u>Subject:</u> Miscellaneous Manufacturing	
<u>Date Issued:</u>	<u>Expiration Date:</u>
<u>Location:</u> 7777 Winn Road, Spring Grove, McHenry County	

This permit is hereby granted to the above-designated Permittee to OPERATE emission unit(s) and/or air pollution control equipment consisting of five (5) sheet-fed non-heatset offset lithographic printing presses, one (1) degreaser, two (2) natural gas-fired boilers, solder operations, punch presses and screw machines pursuant to the above-referenced application. This Permit is subject to standard conditions attached hereto and the following special condition(s):

- 1a. This federally enforceable state operating permit is issued:
 - i. This federally enforceable state operating permit (FESOP) is issued to limit the emissions of air pollutants from the source to less than major source thresholds (i.e., 100 tons/year for Volatile Organic Material (VOM)). As a result, the source is excluded from the requirements to obtain a Clean Air Act Permit Program (CAAPP) permit. The maximum emissions of this source, as limited by the conditions of this permit are described in Attachment A.
 - ii. To limit the potential emissions of VOM from the source to less than 25 tons/year. As a result, the source is excluded from the requirement of 35 Ill. Adm. Code Part 205, Emission Reduction Market System. The maximum emissions of this source, as limited by the conditions of this permit, are described in Attachment A.
- b. Prior to issuance, a draft of this permit has undergone a public notice and comment period.
- c. This permit supersedes all operating permits issued for this location.
- 2a. No person shall cause or allow the emission of smoke or other particulate matter, with an opacity greater than 30 percent, into the atmosphere from any emission unit other than those emission units subject to the requirements of 35 Ill. Adm. Code 212.122, pursuant to 35 Ill. Adm. Code 212.123(a), except as allowed by 35 Ill. Adm. Code 212.123(b) and 212.124.

- b. No person shall cause or allow any visible emissions of fugitive particulate matter from any process, including any material handling or storage activity beyond the property line of the emission source unless the wind speed is greater than 40.2 kilometers per hour (25 miles per hour), pursuant to 35 Ill. Adm. Code 212.301 and 212.314.
- c. Pursuant to 35 Ill. Adm. Code 212.321(a), no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period from any new process emission unit which, either alone or in combination with the emission of particulate matter from all other similar process emission units for which construction or modification commenced on or after April 14, 1972, at a source or premises, exceeds the allowable emission rates specified in subsection (c) of 35 Ill. Adm. Code 212.321.
- d. Pursuant to 35 Ill. Adm. Code 214.301, no person shall cause or allow the emission of sulfur dioxide into the atmosphere from any process emission source to exceed 2000 ppm.
- 3. Pursuant to 35 Ill. Adm. Code 216.121, no person shall cause or allow the emission of carbon monoxide (CO) into the atmosphere from any fuel combustion emission source with actual heat input greater than 2.9 MW (10 mmBtu/hour) to exceed 200 ppm, corrected to 50 percent excess air.
- 4a. Pursuant to 35 Ill. Adm. Code 218.182(a), no person shall operate a cold cleaning degreaser unless:
 - i. Waste solvent is stored in covered containers only and not disposed of in such a manner that more than 20% of the waste solvent (by weight) is allowed to evaporate into the atmosphere;
 - ii. The cover of the degreaser is closed when parts are not being handled; and
 - iii. Parts are drained until dripping ceases.
- b. Pursuant to 35 Ill. Adm. Code 218.182(b), no person shall operate a cold cleaning degreaser unless:
 - i. The degreaser is equipped with a cover which is closed whenever parts are not being handled in the cleaner. The cover shall be designed to be easily operated with one hand or with the mechanical assistance of springs, counter-weights or a powered system if:
 - A. The solvent vapor pressure is greater than 2 kPa (15 mmHg or 0.3 psi) measured at 38°C (100°F);
 - B. The solvent is agitated; or
 - C. The solvent is heated above ambient room temperature.

- ii. The degreaser is equipped with a device for draining cleaned parts. The drainage device shall be constructed so that parts are enclosed under the cover while draining unless:
 - A. The solvent vapor pressure is less than 4.3 kPa (32 mmHg or 0.6 psi) measured at 38°C (100°F); or
 - B. An internal drainage device cannot be fitted into the cleaning system, in which case the drainage device may be external.
 - iii. The degreaser is equipped with one of the following control devices if the vapor pressure of the solvent is greater than 4.3 kPa (32 mmHg or 0.6 psi) measured at 38°C (100°F) or if the solvent is heated above 50°C (120°F) or its boiling point:
 - A. A freeboard height of 7/10 of the inside width of the tank or 91 cm (36 in), whichever is less; or
 - B. Any other equipment or system of equivalent emission control as approved by the Illinois EPA and further processed consistent with 35 Ill. Adm. Code 218.108. Such a system may include a water cover, refrigerated chiller or carbon adsorber.
 - iv. A permanent conspicuous label summarizing the operating procedure is affixed to the degreaser; and
 - v. If a solvent spray is used, the degreaser is equipped with a solid fluid stream spray, rather than a fine, atomized or shower spray.
- c. Pursuant to 35 Ill. Adm. Code 218.182(c)(3)(B), on and after May 30, 2007 no person shall operate a cold cleaning degreaser with a solvent vapor pressure which exceeds 1.0 mmHg (0.019 psi) measured at 20°C (68°F) , unless the person is in compliance with the control requirements of 35 Ill. Adm. Code 218.182(c)(4) or is exempt under 35 Ill. Adm. Code 218.182(f) or (g).
- d. Pursuant to 35 Ill. Adm. Code 218.204(j), except as provided in 35 Ill. Adm. Code 218.205, 218.207, 218.208, 218.212, 218.215 and 218.216, no owner or operator of a coating line shall apply at any time any coating in which the VOM content exceeds the following emission limitations for Miscellaneous Metal Parts and Products Coating. The following emission limitations are expressed in units of VOM per volume of coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied at each coating applicator, except where noted. Compounds which are specifically exempted from the definition of VOM should be treated as water for the purpose of calculating the "less water" part of the coating composition. Compliance with 35 Ill. Adm. Code 218 Subpart F must be demonstrated through the applicable coating analysis test methods and procedures specified in 35 Ill. Adm. Code 218.105(a) and the recordkeeping and reporting requirements

specified in 35 Ill. Adm. Code 218.211(c) except where noted. (Note: The equation presented in 35 Ill. Adm. Code 218.206 shall be used to calculate emission limitations for determining compliance by add on controls, credits for transfer efficiency, emissions trades and cross line averaging.) The emission limitations are as follows:

	<u>kg/l</u>	<u>lb/gal</u>
i. Extreme Performance Coating (Baked)	0.28	(2.3)
ii. All Other Coatings (Baked)	0.34	(2.8)

- e. Pursuant to 35 Ill. Adm. Code 218.301, no person shall cause or allow the discharge of more than 3.6 kg/hour (8 lbs/hour) of organic material into the atmosphere from any emission unit, except as provided in 35 Ill. Adm. Code 218.302, 218.303, or 218.304 and the following exception: If no odor nuisance exists the limitation of 35 Ill. Adm. Code 218 Subpart G shall only apply to photochemically reactive material.
5. This permit is issued based on the degreaser at this source not being subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Halogenated Solvent Cleaning, 40 CFR 63 Subpart T. The degreaser does not any solvent containing methylene chloride (CAS No. 75-09-2), perchloroethylene (CAS No. 127-18-4), trichloroethylene (CAS No. 79-01-6), 1,1,1-trichloroethane (CAS No. 71-55-6), carbon tetrachloride (CAS No. 56-23-5) or chloroform (CAS No. 67-66-3), or any combination of these halogenated HAP solvents, in a total concentration greater than 5 percent by weight, as a cleaning and/or drying agent.
- 6a. Pursuant to 35 Ill. Adm. Code 218.405(d)(2), on and after March 15, 1996, 35 Ill. Adm. Code Part 218.407 through 218.410 shall apply to all owners or operators of heatset web offset, non-heatset web offset, or sheet-fed offset lithographic printing line(s), unless the combined emissions of VOM from all lithographic printing line(s) at the source (including solvents used for cleanup operations associated with the lithographic printing line(s)) never exceed 45.5 kg/day (100 lbs/day), as determined in accordance with 35 Ill. Adm. Code 218.411(a)(1)(B), before the application of capture systems and control devices.
- b. Pursuant to 35 Ill. Adm. Code 218.408(b), no owner or operator of a lithographic printing line which is exempt from the limitations of 35 Ill. Adm. Code 218.407 because of the criteria in 35 Ill. Adm. Code 218.405(d), shall operate said printing line on or after March 15, 1996, unless the owner or operator has complied with, and continues to comply with, 35 Ill. Adm. Code 218.405(d) and 218.411(a).
- 7a. In the event that the operation of this source results in an odor nuisance, the Permittee shall take appropriate and necessary actions to minimize odors, including but not limited to, changes in raw material or installation of controls, in order to eliminate the odor nuisance.
- b. This degreaser shall not use any solvent containing methylene chloride, perchloroethylene, trichloroethylene, carbon tetrachloride, 1,1,1-trichloroethane or chloroform, or any combination of these halogenated

HAP solvents, in a total concentration greater than 5% by weight, as a cleaning and/or drying agent.

- c. The boilers shall only be operated with natural gas as the fuel. The use of any other fuel in the boilers requires that the Permittee first obtain a construction permit from the Illinois EPA and then perform stack testing to verify compliance with all applicable requirements.

- 8a. Emissions and operation of all sheetfed non-heatset offset lithographic printing presses at this source shall not exceed the following limits:

<u>Material</u>	<u>VOM Content % by Weight</u>	<u>Material Usage</u>		<u>VOM Emissions</u>	
		<u>(lbs/Mo)</u>	<u>(Tons/Yr)</u>	<u>(lbs/Mo)</u>	<u>(Tons/Yr)</u>
Ink	40	8,500	50.0	170	1.0
Solvent & Fountain Solution	100	2,500	15.0	<u>2,500</u>	<u>15.0</u>
Totals				<u>2,670</u>	<u>16.0</u>

These limits are based on the maximum material usage, the maximum VOM content of these materials and the equations below.

$$\text{VOM emissions} = (\text{non-heatset ink usage} \times \text{VOM content} \times 0.05) + (\text{cleaning solution usage} \times \text{VOM content}) + (\text{other material usage} \times \text{VOM content})$$

- b. Emissions and operation of the Degreaser shall not exceed 0.6 tons/month and 3.60 tons/year. These limits are based on the maximum material usage and VOM and HAP emissions from the degreaser being calculated based on the following:

$$E = \sum S_i \times V_i$$

Where:

E = VOM/HAP emissions (tons);

S_i = Solvent consumption (tons); and

V_i = VOM/HAP content of the solvent (weight fraction).

- c. Emissions and operation of the boilers and other fuel combustion units shall not exceed the following limits:

- i. The consumption of natural gas shall not exceed:

$$\frac{\text{Natural Gas Usage (mmscf/Month)}}{9} \leq \frac{\text{Natural Gas Usage (mmscf*/Year)}}{87}$$

* 1 mmscf = 10,200 therms

- ii. Emissions from the combustion of natural gas shall not exceed:

<u>Pollutant</u>	<u>Emission</u>	<u>Emissions</u>	
	<u>Factor</u>	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
Carbon Monoxide (CO)	84	0.4	3.7
Nitrogen Oxide (NO _x)	100	0.5	4.4
Particulate Matter (PM)	7.6	0.1	0.4
Sulfur Dioxide (SO ₂)	0.06	0.01	0.03
Volatile Organic Material (VOM)	5.5	0.1	0.3

These limits are based on the maximum equipment operations and standard emission factors (Tables 1.4-1 and 1.4-2, AP-42, Fifth Edition, Volume I, Supplement D, July 1998).

- d. This permit is issued based on negligible emissions of VOM and PM from the solder operations. For this purpose, emissions of each pollutant from the solder operations shall not exceed nominal emission rates of 0.44 tons/year.
 - e. This permit is issued based on negligible emissions of VOM from the punch presses and screw machines. For this purpose, emissions from each emission unit shall not exceed nominal emission rates of 0.44 tons/year.
 - f. Compliance with the annual limits of this permit shall be determined on a monthly basis from the sum of the data for the current month plus the preceding 11 months (running 12 month total).
9. This permit is issued based on the Potential to Emit (PTE) for Hazardous Air Pollutants (HAP) as listed in Section 112(b) of the Clean Air Act from the source being less than 10 tons/year of any single HAP and 25 tons/year of any combination of such HAPs. As a result, this permit is issued based on the emissions of all HAPs from this source not triggering the requirements to obtain a Clean Air Act Permit Program (CAAPP) Permit.
- 10a. Pursuant to 35 Ill. Adm. Code 212.282, every emission source or air pollution control equipment shall be subject to the following testing requirements for the purpose of determining the nature and quantities of specified air contaminant emissions and for the purpose of determining ground level and ambient air concentrations of such air contaminants:
- i. Testing by Owner or Operator. The Illinois EPA may require the owner or operator of the emission source or air pollution control equipment to conduct such tests in accordance with procedures adopted by the Illinois EPA, at such reasonable times as may be specified by the Illinois EPA and at the expense of the owner or operator of the emission source or air pollution control equipment. The Illinois EPA may adopt procedures detailing methods of testing and formats for reporting results of testing. Such procedures and revisions thereto, shall not become effective until filed with the Secretary of State, as required by the APA Act. All such tests shall be made by or under the direction of a

person qualified by training and/or experience in the field of air pollution testing. The Illinois EPA shall have the right to observe all aspects of such tests.

- ii. Testing by the Illinois EPA. The Illinois EPA shall have the right to conduct such tests at any time at its own expense. Upon request of the Illinois EPA, the owner or operator of the emission source or air pollution control equipment shall provide, without charge to the Illinois EPA, necessary holes in stacks or ducts and other safe and proper testing facilities, including scaffolding, but excluding instruments and sensing devices, as may be necessary.
 - b. Testing required by Conditions 11 and 12 shall be performed upon a written request from the Illinois EPA by a qualified independent testing service.
11. Pursuant to 35 Ill. Adm. Code 212.110(c), upon a written notification by the Illinois EPA, the owner or operator of a particulate matter emission unit subject to 35 Ill. Adm. Code Part 212 shall conduct the applicable testing for particulate matter emissions, opacity, or visible emissions at such person's own expense, to demonstrate compliance. Such test results shall be submitted to the Illinois EPA within thirty (30) days after conducting the test unless an alternative time for submittal is agreed to by the Illinois EPA, pursuant to 35 Ill. Adm. Code 212.110(c).
 12. Pursuant to 35 Ill. Adm. Code 218.211(a), the VOM content of each coating and the efficiency of each capture system and control device shall be determined by the applicable test methods and procedures specified in 35 Ill. Adm. Code 218.105 to establish the records required under 35 Ill. Adm. Code 218.211.
 13. Pursuant to 40 CFR 63.10(b)(3), if an owner or operator determines that his or her stationary source that emits (or has the potential to emit, without considering controls) one or more hazardous air pollutants regulated by any standard established pursuant to section 112(d) or (f) of the Clean Air Act, and that stationary source is in the source category regulated by the relevant standard, but that source is not subject to the relevant standard (or other requirement established under 40 CFR Part 63) because of limitations on the source's potential to emit or an exclusion, the owner or operator must keep a record of the applicability determination on site at the source for a period of 5 years after the determination, or until the source changes its operations to become an affected source, whichever comes first. The record of the applicability determination must be signed by the person making the determination and include an analysis (or other information) that demonstrates why the owner or operator believes the source is unaffected (e.g., because the source is an area source). The analysis (or other information) must be sufficiently detailed to allow the USEPA and/or Illinois EPA to make a finding about the source's applicability status with regard to the relevant standard or other requirement. If relevant, the analysis must be performed in accordance with

requirements established in relevant subparts of 40 CFR Part 63 for this purpose for particular categories of stationary sources. If relevant, the analysis should be performed in accordance with USEPA guidance materials published to assist sources in making applicability determinations under Section 112 of the Clean Air Act, if any. The requirements to determine applicability of a standard under 40 CFR 63.1(b)(3) and to record the results of that determination under 40 CFR 63.10(b)(3) shall not by themselves create an obligation for the owner or operator to obtain a Title V permit.

14. Pursuant to 35 Ill. Adm. Code 212.110(e), the owner or operator of an emission unit subject to 35 Ill. Adm. Code Part 212 shall retain records of all tests which are performed. These records shall be retained for at least three (3) years after the date a test is performed.
- 15a. Pursuant to 35 Ill. Adm. Code 218.182(d)(2), on and after March 15, 1999 all persons subject to the requirements of 35 Ill. Adm. Code 218.182(c)(1)(B), (c)(2)(B), and (c)(3)(B) must maintain records which include for each purchase:
 - i. The name and address of the solvent supplier;
 - ii. The date of purchase;
 - iii. The type of solvent; and
 - iv. The vapor pressure of the solvent measured in mmHg at 20°C (68°F); and
 - v. For any mixture of solvents, the vapor pressure of the mixture, as used, measured in mmHg at 20° C (68° F).
- b. Pursuant to 35 Ill. Adm. Code 218.182(e), all records required by 35 Ill. Adm. Code 218.182(d) shall be retained for three years and shall be made available to the Illinois EPA upon request.
- c. Pursuant to 35 Ill. Adm. Code 218.211(c)(2), any owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.204 other than 35 Ill. Adm. Code 218.204(a)(2) or (a)(3) and complying by means of 35 Ill. Adm. Code 218.204 shall collect and record all of the following information for each coating line and maintain the information at the source for a period of three years:
 - i. The name and identification number of each coating as applied on each coating line.
 - ii. The weight of VOM per volume and the volume of each coating (minus water and any compounds which are specifically exempted from the definition of VOM) as applied each day on each coating line.

- d. Pursuant to 35 Ill. Adm. Code 218.411(a)(2), an owner or operator of lithographic printing line(s) exempt from the limitations of 35 Ill. Adm. Code 218.407 because of the criteria in 35 Ill. Adm. Code 218.405(d) shall collect and record either the information specified in 35 Ill. Adm. Code 218.411(a)(2)(A) or (a)(2)(B) for all lithographic printing lines at the source:
 - i. Standard recordkeeping, including the following:
 - A. The name and identification of each fountain solution additive, lithographic ink, and cleaning solvent used on any lithographic printing line, recorded each month;
 - B. A daily record which shows whether a lithographic printing line at the source was in operation on that day;
 - C. The VOM content and the volume of each fountain solution additive, lithographic ink, and cleaning solvent used on any lithographic printing line, recorded each month;
 - D. The total VOM emissions at the source each month, determined as the sum of the product of usage and VOM content for each fountain solution additive, cleaning solvent, and lithographic ink (with the applicable ink VOM emission adjustment) used at the source, calculated each month; and
 - E. The VOM emissions in lbs/day for the month, calculated in accordance with 35 Ill. Adm. Code 218.411(a)(1)(B).
 - ii. Purchase and inventory recordkeeping, including the following:
 - A. The name, identification, and VOM content of each fountain solution additive, lithographic ink, and cleaning solvent used on any lithographic printing line, recorded each month;
 - B. Inventory records from the beginning and end of each month indicating the total volume of each fountain solution additive, lithographic ink, and cleaning solvent to be used on any lithographic printing line at the source;
 - C. Monthly purchase records for each fountain solution additive, lithographic ink, and cleaning solvent used on any lithographic printing line at the source;
 - D. A daily record which shows whether a lithographic printing line at the source was in operation on that day;
 - E. The total VOM emissions at the source each month, determined as the sum of the product of usage and VOM content for each fountain solution additive, cleaning solvent, and lithographic ink (with the applicable ink VOM

emission adjustment) used at the source calculated each month based on the monthly inventory and purchase records required to be maintained pursuant to 35 Ill. Adm. Code 218.411(a)(2)(B)(i), (a)(2)(B)(ii) and (a)(2)(B)(iii); and

F. The VOM emissions in lbs/day for the month, calculated in accordance with 35 Ill. Adm. Code 218.411(a)(1)(B).

16a. The Permittee shall maintain records of the following items so as to demonstrate compliance with the Conditions of this permit:

- i. Coating usage (tons/month and tons/year);
- ii. Solvent usage (lbs/month and tons/year);
- iii. Natural gas usage (mmscf/month and mmscf/year);
- iv. VOM and HAP contents of materials used; and
- v. Monthly and annual emissions of CO, NO_x, PM, SO₂, VOM and HAPs, (individual and combined) with supporting calculations (tons/month and tons/year).

b. All records and logs required by this permit shall be retained at a readily accessible location at the source for at least five (5) years from the date of entry and shall be made available for inspection and copying by the Illinois EPA or USEPA upon request. Any records retained in an electronic format (e.g., computer) shall be capable of being retrieved and printed on paper during normal source office hours so as to be able to respond to an Illinois EPA or USEPA request for records during the course of a source inspection.

17. Pursuant to 35 Ill. Adm. Code 212.110(d), a person planning to conduct testing for particulate matter emissions to demonstrate compliance shall give written notice to the Illinois EPA of that intent. Such notification shall be given at least thirty (30) days prior to the initiation of the test unless a shorter period is agreed to by the Illinois EPA. Such notification shall state the specific test methods from 35 Ill. Adm. Code 212.110 that will be used.

18a. Pursuant to 35 Ill. Adm. Code 218.182(d)(6), on and after March 15, 1999, all persons subject to the requirements of 35 Ill. Adm. Code 218.182(b) or (c) shall notify the Illinois EPA of any violation of 35 Ill. Adm. Code 218.182(b) or (c) by sending a description of the violation and copies of records documenting such violations to the Illinois EPA within 30 days following the occurrence of the violation.

b. Pursuant to 35 Ill. Adm. Code 218.211(c)(3), any owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.204 of and complying by means of 35 Ill. Adm. Code 218.204 shall notify the Illinois EPA in the following instances:

- i. Any record showing violation of 35 Ill. Adm. Code 218.204 shall be reported by sending a copy of such record to the Illinois EPA within 30 days following the occurrence of the violation.
 - ii. At least 30 calendar days before changing the method of compliance from 35 Ill. Adm. Code 218.204 to 35 Ill. Adm. Code 218.205 or 35 Ill. Adm. Code 218.207, the owner or operator shall comply with all requirements of 35 Ill. Adm. Code 218.211(d)(1) or (e)(1), respectively. Upon changing the method of compliance from 35 Ill. Adm. Code 218.204 to 35 Ill. Adm. Code 218.205 or 35 Ill. Adm. Code 218.207, the owner or operator shall comply with all requirements of 35 Ill. Adm. Code 218.211(d) or (e), respectively.
 - c. Pursuant to 35 Ill. Adm. Code 218.211(e)(3), any owner or operator of a coating line subject to the limitations of 35 Ill. Adm. Code 218.207 and complying by means of 35 Ill. Adm. Code 218.207(c), (d), (e), (f), (g) or (h) shall notify the Illinois EPA in the following instances:
 - i. Any record showing violation of 35 Ill. Adm. Code 218.207 shall be reported by sending a copy of such record to the Illinois EPA within 30 days following the occurrence of the violation.
 - ii. At least 30 calendar days before changing the method of compliance with 35 Ill. Adm. Code 218 Subpart F from 35 Ill. Adm. Code 218.207 to 35 Ill. Adm. Code 218.204 or 35 Ill. Adm. Code 218.205, the owner or operator shall comply with all requirements of 35 Ill. Adm. Code 218.207(c)(1) or (d)(1), respectively. Upon changing the method of compliance with 35 Ill. Adm. Code 218 Subpart F from 35 Ill. Adm. Code 218.207 to 35 Ill. Adm. Code 218.204 or 35 Ill. Adm. Code 218.205, the owner or operator shall comply with all requirements of 35 Ill. Adm. Code 218.207(c) or (d), respectively.
 - d. Pursuant to 35 Ill. Adm. Code 218.411(a)(3), an owner or operator of lithographic printing line(s) exempt from the limitations of 35 Ill. Adm. Code 218.407 because of the criteria in 35 Ill. Adm. Code 218.405(d) shall notify the Illinois EPA in writing if the combined emissions of VOM from all lithographic printing lines (including inks, fountain solutions, and solvents used for cleanup operations associated with the lithographic printing lines) at the source ever exceed 45.5 kg/day (100 lbs/day), before the use of capture systems and control devices, within 30 days after the event occurs. Such notification shall include a copy of all records of such event.
- 19a. If there is an exceedance of or a deviation from the requirements of this permit as determined by the records required by this permit, the Permittee shall submit a report to the Illinois EPA's Compliance Section in Springfield, Illinois within 30 days after the exceedance or deviation. The report shall include the emissions released in accordance with the recordkeeping requirements, a copy of the relevant records, and a description of the exceedance or deviation and efforts to reduce emissions and future occurrences.

b. Two (2) copies of required reports and notifications shall be sent to:

Illinois Environmental Protection Agency
Division of Air Pollution Control
Compliance Section (#40)
P.O. Box 19276
Springfield, Illinois 62794-9276

and one (1) copy shall be sent to the Illinois EPA's regional office at the following address unless otherwise indicated:

Illinois Environmental Protection Agency
Division of Air Pollution Control
9511 West Harrison
Des Plaines, Illinois 60016

If you have any questions on this, please call David Hulskotter at 217/782-2113.

Edwin C. Bakowski, P.E.
Manager, Permit Section
Division of Air Pollution Control

Date Signed: _____

ECB:DWH:jws

cc: Illinois EPA, FOS Region 1
Lotus Notes

Attachment A - Emission Summary

This attachment provides a summary of the maximum emissions from the manufacturing plant operating in compliance with the requirements of this federally enforceable permit. In preparing this summary, the Illinois EPA used the annual operating scenario which results in maximum emissions from such a plant. The resulting maximum emissions are below the levels, (e.g., 100 tons per year of VOM) at which this source would be considered a major source for purposes of the Clean Air Act Permit Program. Actual emissions from this source will be less than predicted in this summary to the extent that less material is handled, and control measures are more effective than required in this permit.

<u>Emission Unit</u>	E M I S S I O N S (Tons/Year)				
	<u>CO</u>	<u>NO_x</u>	<u>PM</u>	<u>SO₂</u>	<u>VOM</u>
Non-Heatset Offset					
Printing Presses					16.00
Durr Degreaser	---	---	---	---	3.60
Solder Operations	---	---	0.44	---	0.44
Punch Presses	---	---	---	---	0.44
Screw Machines	---	---	---	---	0.44
Fuel Combustion	<u>3.70</u>	<u>4.40</u>	<u>0.40</u>	<u>0.03</u>	<u>0.30</u>
Totals	3.70	4.40	0.84	0.03	21.22

DWH:jws