

217/785-1705

FEDERALLY ENFORCABLE STATE OPERATING PERMIT -- NSPS SOURCE

PERMITTEE

Henry County Highway Dept.
Attn: Steven Brandau
100 North East Road
Cambridge, Illinois 61238

Application No.: 10020033

I.D. No.: 073030AAN

Applicant's Designation:

Date Received: February 16, 2010

Subject: Hot Mix Asphalt Plant

Date Issued: November 21, 2014

Expiration Date: November 21, 2024

Location: 100 North East Road, Cambridge, Henry County

This permit is hereby granted to the above-designated Permittee to CONSTRUCT emission source(s) and/or air pollution control equipment consisting of

One (1) 250 tons/hour Natural Gas-fired drum-mix asphalt plant with baghouse;
One (1) 3.084 mmBtu/hour Natural Gas-fired asphalt tank heater;
Two (2) 20,000 gallon liquid asphalt storage tanks; and
Two (2) 100 ton asphalt storage silos;

as described in the above-referenced application. This Permit is subject to standard conditions attached hereto and the following special condition(s):

- 1a. This federally enforceable state operating permit (FESOP) is issued, to limit the emissions of air pollutants from the source to less than major source thresholds (i.e., 100 tons/year for Carbon Monoxide (CO)). As a result, the source is excluded from the requirements to obtain a Clean Air Act Permit Program (CAAPP) permit. The maximum emissions of this source, as limited by the conditions of this permit are described in Attachment A.
- b. Prior to issuance, a draft of this permit has undergone a public notice and comment period.
- c. This permit supersedes all operating permit(s) for this location.
- 2a. The Drum Mix Asphalt Plant is subject to the New Source Performance Standards (NSPS) for Hot Mix Asphalt Plants, 40 CFR 60, Subparts A and I. The Illinois EPA is administering the NSPS in Illinois on behalf of the United States EPA under a delegation agreement. Pursuant to 40 CFR 60.90(a), the affected facility to which the provisions of 40 CFR 60 Subpart I apply is each hot mix asphalt facility. For the purpose of 40 CFR 60 Subpart I, a hot mix asphalt facility is comprised only of any combination of the following: dryers; systems for screening, handling, storing, and weighing hot aggregate; systems for loading, transferring, and storing mineral filler, systems for mixing hot mix asphalt; and the loading, transfer, and storage systems associated with emission control systems.

- b. Pursuant to 40 CFR 60.90(b), any facility under 40 CFR 60.90(a) that commences construction or modification after June 11, 1973, is subject to the requirements of 40 CFR 60 Subpart I.
- c. Pursuant to 40 CFR 60.92(a), On and after the date on which the performance test required to be conducted by 40 CFR 60.8 is completed, no owner or operator subject to the provisions of 40 CFR 60 Subpart I shall discharge or cause the discharge into the atmosphere from any affected facility any gases which:
 - i. Contain particulate matter in excess of 90 mg/dscm (0.04 gr/dscf).
 - ii. Exhibit 20 percent opacity or greater.
- 3a. Pursuant to 35 Ill. Adm. Code 212.123(a), no person shall cause or allow the emission of smoke or other particulate matter, with an opacity greater than 30 percent, into the atmosphere from any emission unit other than those emission units subject to 35 Ill. Adm. Code 212.122.
- b. Pursuant to 35 Ill. Adm. Code 212.123(b), the emission of smoke or other particulate matter from any such emission unit may have an opacity greater than 30 percent but not greater than 60 percent for a period or periods aggregating 8 minutes in any 60 minute period provided that such opaque emissions permitted during any 60 minute period shall occur from only one such emission unit located within a 305 m (1000 ft) radius from the center point of any other such emission unit owned or operated by such person, and provided further that such opaque emissions permitted from each such emission unit shall be limited to 3 times in any 24 hour period.
- c. Pursuant to 35 Ill. Adm. Code 212.301, no person shall cause or allow the emission of fugitive particulate matter from any process, including any material handling or storage activity, that is visible by an observer looking generally toward the zenith at a point beyond the property line of the source.
- d. Pursuant to 35 Ill. Adm. Code 212.321(a), except as further provided in 35 Ill. Adm. Code Part 212, no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period from any new process emission unit which, either alone or in combination with the emission of particulate matter from all other similar process emission units for which construction or modification commenced on or after April 14, 1972, at a source or premises, exceeds the allowable emission rates specified in 35 Ill. Adm. Code 212.321(c).
- 4. Pursuant to 35 Ill. Adm. Code 214.301, except as further provided by 35 Ill. Adm. Code Part 214, no person shall cause or allow the emission of sulfur dioxide into the atmosphere from any process emission unit to exceed 2000 ppm.

- 5a. Pursuant to 35 Ill. Adm. Code 215.122(b), no person shall cause or allow the loading of any organic material into any stationary tank having a storage capacity of greater than 946 l (250 gal), unless such tank is equipped with a permanent submerged loading pipe, submerged fill, or an equivalent device approved by the Illinois EPA according to the provisions of 35 Ill. Adm. Code Part 201 or unless such tank is a pressure tank as described in 35 Ill. Adm. Code 215.121(a) or is fitted with a recovery system as described in 35 Ill. Adm. Code 215.121(b)(2).
- b. Pursuant to 35 Ill. Adm. Code 215.301, no person shall cause or allow the discharge of more than 3.6 kg/hr (8.0 lbs/hr) of organic material into the atmosphere from any emission unit, except as provided in 35 Ill. Adm. Code 215.302, 215.303, 215.304 and the following exception: If no odor nuisance exists the limitation of 35 Ill. Adm. Code Part 215 Subpart K (Use of Organic Material) shall only apply to photochemically reactive material.
6. Pursuant to 35 Ill. Adm. Code 212.314, 35 Ill. Adm. Code 212.301 shall not apply and spraying pursuant to 35 Ill. Adm. Code 212.304 through 212.310 and 35 Ill. Adm. Code 212.312 shall not be required when the wind speed is greater than 40.2 km/hr (25 mph). Determination of wind speed for the purposes of this rule shall be by a one-hour average or hourly recorded value at the nearest official station of the U.S. Weather Bureau or by wind speed instruments operated on the site. In cases where the duration of operations subject to this rule is less than one hour, wind speed may be averaged over the duration of the operations on the basis of on-site wind speed instrument measurements.
 - b. Pursuant to 35 Ill. Adm. Code 212.314, 35 Ill. Adm. Code 212.301 shall not apply and spraying pursuant to 35 Ill. Adm. Code 212.304 through 212.310 and 35 Ill. Adm. Code 212.312 shall not be required when the wind speed is greater than 40.2 km/hr (25 mph). Determination of wind speed for the purposes of this rule shall be by a one-hour average or hourly recorded value at the nearest official station of the U.S. Weather Bureau or by wind speed instruments operated on the site. In cases where the duration of operations subject to this rule is less than one hour, wind speed may be averaged over the duration of the operations on the basis of on-site wind speed instrument measurements.
7. Pursuant to 35 Ill. Adm. Code 215.122(c), if no odor nuisance exists the limitations of 35 Ill. Adm. Code 215.122 shall only apply to the loading of volatile organic liquid with a vapor pressure of 17.24 kPa (2.5 psia) or greater at 294.3°K (70°F).
- 8a. Pursuant to 40 CFR 60.11(b), compliance with opacity standards in 40 CFR Part 60 shall be determined by conducting observations in accordance with Method 9 in Appendix A of 40 CFR Part 60, any alternative method that is approved by the Illinois EPA or USEPA, or as provided in 40 CFR 60.11(e)(5). For purposes of determining initial compliance, the minimum total time of observations shall be 3 hours (30 6-minute averages) for the performance test or other set of

observations (meaning those fugitive-type emission sources subject only to an opacity standard)

- b. Pursuant to 40 CFR 60.11(c), the opacity standards set forth in 40 CFR Part 60 shall apply at all times except during periods of startup, shutdown, malfunction, and as otherwise provided in the applicable standard.
 - c. Pursuant to 40 CFR 60.11(d), at all times, including periods of startup, shutdown, and malfunction, owners and operators shall, to the extent practicable, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Illinois EPA or USEPA which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source.
- 9a. In the event that the operation of this source results in an odor nuisance, the Permittee shall take appropriate and necessary actions to minimize odors, including but not limited to, changes in raw material or installation of controls, in order to eliminate the nuisance.
- b. The baghouse shall be in operation at all times when the associated drum dryer is in operation and emitting air contaminants.
 - c. The Permittee shall, in accordance with the manufacturer(s) and/or vendor(s) recommendations, perform periodic maintenance on the baghouse such that the baghouse is kept in proper working condition and not cause a violation of the Illinois Environmental Protection Act or regulations promulgated therein.
 - d. The drum mixer, drum dryer, and asphalt tank heaters shall only be operated with natural gas as the fuel. The use of any other fuel in the drum mixer, drum dryer, or asphalt tank heaters requires that the Permittee first obtain a construction permit from the Illinois EPA and then perform stack testing to verify compliance with all applicable requirements.
- 10a. Emissions and operation of the asphalt plant shall not exceed the following limits:

i. Asphalt Production Limits:

Asphalt Concrete Production Rate		
<u>(Tons/Hour)</u>	<u>(Tons/Month)</u>	<u>(Tons/Year)</u>
250	20,000	120,000

ii. Emissions from Drum Mixer/Dryer:

<u>Pollutant</u>	<u>Emission Rate</u>	<u>Emissions</u>	
	<u>(lbs/Ton)</u>	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
Carbon Monoxide (CO)	0.13	1.30	7.80
Nitrogen Oxides (NO _x)	0.026	0.26	1.56
Particulate Matter (PM)	0.033	0.33	1.98
Sulfur Dioxide (SO ₂)	0.0034	0.05	0.20
Volatile Organic Material (VOM)	0.032	0.32	1.92

iii. Emissions from Asphalt Silo Filling:

<u>Pollutant</u>	<u>Emission Rate</u>	<u>Emissions</u>	
	<u>(lbs/Ton)</u>	<u>(lbs/Mo)</u>	<u>(Tons/Yr)</u>
Carbon Monoxide (CO)	0.00118	24	0.07
Particulate Matter (PM)	0.000586	12	0.04
Volatile Organic Material (VOM)	0.0122	244	0.73

iv. Emissions from Truck Load-out:

<u>Pollutant</u>	<u>Emission Rate</u>	<u>Emissions</u>	
	<u>(lb/Ton)</u>	<u>(lb/Mo)</u>	<u>(Tons/Yr)</u>
Carbon Monoxide (CO)	0.00135	27	0.08
Particulate Matter (PM)	0.000522	10	0.03
Volatile Organic Material (VOM)	0.00416	83	0.25

v. These limits are based on the maximum asphalt production and standard emission factors (Tables 11.1-3, 11.1-7, 11.1-8, and 11.1-14, AP-42, Fifth Edition, Volume I, Update 2004, April 2004).

b. Operation and emissions of the asphalt tank heater shall not exceed the following limits:

<u>Pollutant</u>	<u>Emission Factor</u>	<u>Emissions</u>	
	<u>(lbs/mmscf)</u>	<u>(Tons/Mo)</u>	<u>(Tons/Yr)</u>
Carbon Monoxides (CO)	84.0	0.11	1.13
Nitrogen Oxides (NO _x)	100.0	0.14	1.35
Particle Matter (PM)	7.6	0.01	0.10
Sulfur Dioxide (SO ₂)	0.6	0.01	0.01
Volatile Organic Material (VOM)	5.5	0.01	0.07

These limits are based on the maximum fuel consumption of the asphalt tank heater at the maximum firing rate (3.084 mmBtu/hour), a maximum of 8,760 hours/year of operation, and standard emission factors (Tables 1.4-1 and 1.4-2, AP-42, Fifth Edition, Volume I, Supplement D, July 1998).

c. This permit is issued based on negligible emissions of VOM from the two liquid asphalt storage tanks. For this purpose, emissions from each tank shall not exceed nominal emission rates of 0.1 lb/hour and 0.44 tons/year total.

- d. Compliance with the annual limits of this permit shall be determined on a monthly basis from the sum of the data for the current month plus the preceding 11 months (running 12 month total).
- 11a. Pursuant to 40 CFR 60.8(a), at such other times as may be required by the Illinois EPA or USEPA under section 114 of the Clean Air Act, the owner or operator of such facility shall conduct performance test(s) and furnish the Illinois EPA or USEPA a written report of the results of such performance test(s).
- b. Pursuant to 40 CFR 60.8(b), performance tests shall be conducted and data reduced in accordance with the test methods and procedures contained in each applicable subpart of 40 CFR Part 60 unless the Illinois EPA or USEPA:
 - i. Specifies or approves, in specific cases, the use of a reference method with minor changes in methodology;
 - ii. Approves the use of an equivalent method;
 - iii. Approves the use of an alternative method the results of which he has determined to be adequate for indicating whether a specific source is in compliance;
 - iv. Waives the requirement for performance tests because the owner or operator of a source has demonstrated by other means to the Illinois EPA's or USEPA's satisfaction that the affected facility is in compliance with the standard; or
 - v. Approves shorter sampling times and smaller sample volumes when necessitated by process variables or other factors. Nothing in this paragraph shall be construed to abrogate the Illinois EPA's or USEPA's authority to require testing under section 114 of the Clean Air Act.
- c. Pursuant to 40 CFR 60.8(c), performance tests shall be conducted under such conditions as the Illinois EPA or USEPA shall specify to the plant operator based on representative performance of the affected facility. The owner or operator shall make available to the Illinois EPA or USEPA such records as may be necessary to determine the conditions of the performance tests. Operations during periods of startup, shutdown, and malfunction shall not constitute representative conditions for the purpose of a performance test nor shall emissions in excess of the level of the applicable emission limit during periods of startup, shutdown, and malfunction be considered a violation of the applicable emission limit unless otherwise specified in the applicable standard.
- d. Pursuant to 40 CFR 60.8(d), the owner or operator of an affected facility shall provide the Illinois EPA or USEPA at least 30 days prior notice of any performance test, except as specified under other subparts, to afford the Illinois EPA or USEPA the opportunity to have an observer present. If after 30 days' notice for an initially

scheduled performance test, there is a delay (due to operational problems, etc.) in conducting the scheduled performance test, the owner or operator of an affected facility shall notify the Illinois EPA or USEPA as soon as possible of any delay in the original test date, either by providing at least 7 days prior notice of the rescheduled date of the performance test, or by arranging a rescheduled date with the Illinois EPA or USEPA by mutual agreement.

- e. Pursuant to 40 CFR 60.8(e), the owner or operator of an affected facility shall provide, or cause to be provided, performance testing facilities as follows:
 - i. Sampling ports adequate for test methods applicable to such facility. This includes:
 - A. Constructing the air pollution control system such that volumetric flow rates and pollutant emission rates can be accurately determined by applicable test 1 methods and procedures; and
 - B. Providing a stack or duct free of cyclonic flow during performance tests, as demonstrated by applicable test methods and procedures.
 - ii. Safe sampling platform(s).
 - iii. Safe access to sampling platform(s).
 - iv. Utilities for sampling and testing equipment.
- f. Pursuant to 40 CFR 60.8(f), unless otherwise specified in the applicable subpart of 40 CFR Part 60, each performance test shall consist of three separate runs using the applicable test method. Each run shall be conducted for the time and under the conditions specified in the applicable standard under 40 CFR Part 60. For the purpose of determining compliance with an applicable standard under 40 CFR Part 60, the arithmetic means of results of the three runs shall apply. In the event that a sample is accidentally lost or conditions occur in which one of the three runs must be discontinued because of forced shutdown, failure of an irreplaceable portion of the sample train, extreme meteorological conditions, or other circumstances, beyond the owner or operator's control, compliance may, upon the Illinois EPA's or USEPA's approval, be determined using the arithmetic mean of the results of the two other runs.
- g. Pursuant to 40 CFR 60.11(b), compliance with opacity standards in 40 CFR Part 60 shall be determined by conducting observations in accordance with Method 9 in appendix A of 40 CFR Part 60, any alternative method that is approved by the Illinois EPA or USEPA, or as provided in 40 CFR 60.11(e)(5). For purposes of determining initial compliance, the minimum total time of observations shall be 3 hours (30 6-minute averages) for the performance test or other set of

observations (meaning those fugitive-type emission sources subject only to an opacity standard).

- h. Pursuant to 40 CFR 60.11(e)(2), except as provided in 40 CFR 60.11(e)(3), the owner or operator of an affected facility to which an opacity standard in 40 CFR Part 60 applies shall conduct opacity observations in accordance with 40 CFR 60.11(b), shall record the opacity of emissions, and shall report to the Illinois EPA or USEPA the opacity results along with the results of the initial performance test required under 40 CFR 60.8. The inability of an owner or operator to secure a visible emissions observer shall not be considered a reason for not conducting the opacity observations concurrent with the initial performance test.
- 12a. Pursuant to 40 CFR 60.93(a), in conducting the performance tests required in 40 CFR 60.8, the owner or operator shall use as reference methods and procedures the test methods in appendix A of 40 CFR Part 60 or other methods and procedures as specified in 40 CFR 60.93, except as provided in 40 CFR 60.8(b).
- b. Pursuant to 40 CFR 60.93(b), the owner or operator shall determine compliance with the particulate matter standards in 40 CFR 60.92 as follows:
 - i. Method 5 shall be used to determine the particulate matter concentration. The sampling time and sample volume for each run shall be at least 60 minutes and 0.90 dscm (31.8 dscf).
 - ii. Method 9 and the procedures in 40 CFR 60.11 shall be used to determine opacity.
- 13a. Pursuant to 35 Ill. Adm. Code 201.282, every emission source or air pollution control equipment shall be subject to the following testing requirements for the purpose of determining the nature and quantities of specified air contaminant emissions and for the purpose of determining ground level and ambient air concentrations of such air contaminants:
 - i. Testing by Owner or Operator. The Illinois EPA may require the owner or operator of the emission source or air pollution control equipment to conduct such tests in accordance with procedures adopted by the Illinois EPA, at such reasonable times as may be specified by the Illinois EPA and at the expense of the owner or operator of the emission source or air pollution control equipment. The Illinois EPA may adopt procedures detailing methods of testing and formats for reporting results of testing. Such procedures and revisions thereto, shall not become effective until filed with the Secretary of State, as required by the APA Act. All such tests shall be made by or under the direction of a person qualified by training and/or experience in the field of air pollution testing. The Illinois EPA shall have the right to observe all aspects of such tests.

- ii. Testing by the Illinois EPA. The Illinois EPA shall have the right to conduct such tests at any time at its own expense. Upon request of the Illinois EPA, the owner or operator of the emission source or air pollution control equipment shall provide, without charge to the Illinois EPA, necessary holes in stacks or ducts and other safe and proper testing facilities, including scaffolding, but excluding instruments and sensing devices, as may be necessary.
 - b. Testing required by Condition 14 shall be performed upon a written request from the Illinois EPA by a qualified independent testing service.
14. Pursuant to 35 Ill. Adm. Code 212.110(c), upon a written notification by the Illinois EPA, the owner or operator of a particulate matter emission unit subject to 35 Ill. Adm. Code Part 212 shall conduct the applicable testing for particulate matter emissions, opacity, or visible emissions at such person's own expense, to demonstrate compliance. Such test results shall be submitted to the Illinois EPA within thirty (30) days after conducting the test unless an alternative time for submittal is agreed to by the Illinois EPA.
15. Inspections of the affected drum-mix asphalt plant and control systems equipment and operations shall be performed as necessary but at least once per week when the affected drum-mix asphalt plant is in operation to confirm compliance with the requirements of this permit.
- 16a. Pursuant to 40 CFR 60.7(b), any owner or operator subject to the provisions of 40 CFR Part 60 shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of an affected facility; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative.
- b. Pursuant to 40 CFR 60.7(f), any owner or operator subject to the provisions of 40 CFR Part 60 shall maintain a file of all measurements, including continuous monitoring system, monitoring device, and performance testing measurements; all continuous monitoring system performance evaluations; all continuous monitoring system or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; and all other information required by 40 CFR Part 60 recorded in a permanent form suitable for inspection. The file shall be retained for at least two years following the date of such measurements, maintenance, reports, and records.
17. Pursuant to 35 Ill. Adm. Code 212.110(e), the owner or operator of an emission unit subject to 35 Ill. Adm. Code Part 212 shall retain records of all tests which are performed. These records shall be retained for at least three (3) years after the date a test is performed.

- 18a. The Permittee shall maintain records of the following items so as to demonstrate compliance with the conditions of this permit:
- i. Records addressing use of good operating practices for the baghouse:
 - A. Operating logs for the drum-mix asphalt plant baghouse, including operating data (pressure drop or stack condition), daily upon startup;
 - B. Records for periodic inspection of the baghouse with date, individual performing the inspection, and nature of inspection; and
 - C. Records for prompt repair of defects, with identification and description of defect, effect on emissions, date identified, date repaired, and nature of repair.
 - ii. Asphalt concrete production (tons/month and tons/year);
 - iii. Natural gas usage (scf/month and scf/year); and
 - iv. Monthly and annual CO, NO_x, PM, SO₂, and VOM emissions from the source, with supporting calculations (tons/month and tons/year).
- b. All records and logs required by this permit shall be retained at a readily accessible location at the source for at least five (5) years from the date of entry and shall be made available for inspection and copying by the Illinois EPA or USEPA upon request. Any records retained in an electronic format (e.g., computer storage device) shall be capable of being retrieved and printed on paper during normal source office hours so as to be able to respond to the Illinois EPA or USEPA request for records during the course of a source inspection.
19. Pursuant to 40 CFR 60.7(a)(4), any owner or operator subject to the provisions of 40 CFR Part 60 shall furnish the Illinois EPA or USEPA written notification or, if acceptable to both the Illinois EPA and USEPA and the owner or operator of a source, electronic notification, as follows: A notification of any physical or operational change to an existing facility which may increase the emission rate of any air pollutant to which a standard applies, unless that change is specifically exempted under an applicable subpart or in 40 CFR 60.14(e). This notice shall be postmarked 60 days or as soon as practicable before the change is commenced and shall include information describing the precise nature of the change, present and proposed emission control systems, productive capacity of the facility before and after the change, and the expected completion date of the change. The Illinois EPA or USEPA may request additional relevant information subsequent to this notice.
20. Pursuant to 35 Ill. Adm. Code 212.110(d), a person planning to conduct testing for particulate matter emissions to demonstrate compliance

shall give written notice to the Illinois EPA of that intent. Such notification shall be given at least thirty (30) days prior to the initiation of the test unless a shorter period is agreed to by the Illinois EPA. Such notification shall state the specific test methods from 35 Ill. Adm. Code 212.110 that will be used.

21a. If there is an exceedance of or a deviation from the requirements of this permit as determined by the record required by this permit, the Permittee shall submit a report to the Illinois EPA's Compliance Section in Springfield, Illinois within thirty (30) days after the exceedance or deviation. The report shall include the emissions released in accordance with the recordkeeping requirements, a copy of the relevant records, and a description of the exceedance or deviation and efforts to reduce emissions and future occurrences.

b. Two (2) copies of required reports and notifications shall be sent to:

Illinois Environmental Protection Agency
Division of Air Pollution Control
Compliance Section (#40)
P.O. Box 19276
Springfield, Illinois 62794-9276

and one (1) copy shall be sent to the Illinois EPA's regional office at the following address unless otherwise indicated:

Illinois Environmental Protection Agency
Division of Air Pollution Control
Regional Field Office
412 SW Washington, Suite D
Peoria, Illinois 61602

Telephone: 309/671-3022 Fax: 309/671-3024

22. The assembly of this plant at a new location will require a construction permit for the new location. This permit must be obtained prior to commencing construction at the new location.

If you have any questions on this, please call German Barria at 217/785-1705.

Raymond E. Pilapil
Acting Manager, Permit Section
Division of Air Pollution Control

Date Signed: _____

REB:GB:jws

cc: Illinois EPA, FOS Region 2
Lotus Notes

Attachment A - Emissions Summary

This attachment provides a summary of the maximum emission of an affected drum-mix asphalt plant operating in compliance with the requirements of this federally enforceable permit. In preparing this summary, the Illinois EPA used the annual operating scenario, which results in maximum emissions from such a plant. The resulting maximum emissions are below the levels (e.g., 100 tons/year for CO) at which a plant would be considered a major source for purposes of the Clean Air Act Permit Program. Actual emissions from an affected drum-mix asphalt plant will be less than predicted in this summary to the extent that less material will be handled by the plant, gaseous fuel is used, and control measures are more effective than required by this permit.

<u>Item of Equipment</u>	E M I S S I O N S (Tons/year)				
	<u>CO</u>	<u>NO_x</u>	<u>PM</u>	<u>SO₂</u>	<u>VOM</u>
Drum Mixer/Dryer	7.80	1.56	1.98	0.20	1.92
Asphalt Silo Filling	0.07		0.04		0.73
Truck Loadout	0.08		0.03		0.25
Asphalt Tank Heater	1.13	1.35	0.10	0.01	0.07
2 Liquid Asphalt Storage Tanks	--	--	--	--	0.88
Total	9.08	2.91	2.15	0.21	3.85