

Ross county emission limits.

- (A) No owner or operator of any coal-fired steam generating unit, unless otherwise specified in this rule, shall cause or permit the emission of sulfur dioxide from any source to exceed a maximum of 3.6 pounds of sulfur dioxide per MM Btu actual heat input.
- (B) The "Chillicothe Paper Inc." (OEPA premise number 0671010028) or any subsequent owner or operator of the "Chillicothe Paper Inc." facility located on South Paint street, Chillicothe, Ohio shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated:
- (1) Boiler numbers 5, 7, and 8 (OEPA source numbers B001 through B003); a maximum of 9.9 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
 - (2) Chilpaco package boiler (OEPA source number B010); a maximum of 0.5 pounds of sulfur dioxide per MM Btu actual heat input.
 - (3) Recovery furnaces (OEPA source numbers B004 and B005); a maximum of 4.9 pounds of sulfur dioxide per ton of solids input.
- (C) The "Chillicothe Correctional Institute" (OEPA premise number 0671010104) or any subsequent owner or operator of the "Chillicothe Correctional Institute" facility located in Chillicothe, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 1 through 4 (OEPA source numbers B001 through B004) to exceed a maximum of 5.6 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.

Effective: 02/17/2011

R.C. 119.032 review dates: 11/30/2010 and 11/30/2015

CERTIFIED ELECTRONICALLY
Certification

02/07/2011
Date

Promulgated Under: 119.03
Statutory Authority: 3704.03(E)
Rule Amplifies: 3704.03(A), 3704.03(E)
Prior Effective Dates: 12/28/79, 1/23/06