

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY**

**AIR QUALITY DIVISION**

**PART 1. GENERAL PROVISIONS**

**R 336.1108 Definitions; H.**

Rule 108. As used in these rules:

(a) "Hardboard" means a panel manufactured primarily from interfelted ligno-cellulosic fibers which are consolidated under heat and pressure in a hot press.

(b) "Hardwood plywood" means plywood whose surface layer is a veneer of hardwood.

(c) "Heavy liquid" means a liquid which is less than 10% evaporated at 150 degrees Centigrade as determined by ASTM method d-86. ASTM d-86 is herein adopted by reference in these rules. A copy may be inspected at the Lansing office of the air quality division of the department of environmental quality. A copy may be obtained from the Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, at a cost of \$40.00. A copy may also be obtained from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, Pennsylvania 19428, at a cost of \$40.00.

(d) "High bake coating" means a coating which is designed to cure only at temperatures of more than 90 degrees Celsius (194 degrees Fahrenheit).

(e) "High-speed dispersion mill" means a mixer that has 1 or more blades which rotate at high speed to disperse coating solids.

History: 1979 ACS 7, Eff. Aug. 22, 1981; 1989 MR 4, Eff. Apr. 19, 1989; 2002 MR 10, Eff. May 28, 2002.