

3745-18-66

Muskingum county emission limits.

- (A) No owner or operator of any coal-fired steam generating unit, unless otherwise specified below, shall cause or permit the emission of sulfur dioxide from any source to exceed a maximum of 4.5 pounds of sulfur dioxide per MM Btu actual heat input.
- (B) The "Ohio Power Company, Philo Plant" (OEPA premise number 0660000001) or any subsequent owner or operator of the "Ohio Power Company, Philo Plant," Philo, Ohio shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated:
- (1) Boiler numbers 41 and 42 (OEPA source numbers B001 and B002); a maximum of 1.4 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
 - (2) Boiler numbers 51 and 52 (OEPA source numbers B003 and B004); a maximum of 1.4 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
 - (3) Boiler number 6 (OEPA source number B005); a maximum of 1.4 pounds of sulfur dioxide per MM Btu actual heat input.
- (C) The "~~Armedo Steel~~ AK Steel Corporation" (OEPA premise number 0660010006) or any subsequent owner or operator of the "~~Armedo Steel~~ AK Steel Corporation, 1724 Linden Avenue, Zanesville, Ohio" shall not cause or permit the emission of sulfur dioxide from boiler numbers 2 and 3 (OEPA source numbers B002 and B003) to exceed 6.1 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (D) "Columbia Cement" (OEPA premise number 0660000010) or any subsequent owner or operator of "Columbia Cement, Route 22, East Fultonham, Ohio" shall not cause or permit the emission of sulfur dioxide from the cement kilns (OEPA source number P001) to exceed a maximum of 20.4 pounds of sulfur dioxide per ton of cement produced.
- (E) The "Owens Brockway Glass Company" (OEPA premise number 0660010007) or any subsequent owner or operator of the "Owens Brockway Glass Company, 1700 State Street, Zanesville, Ohio" shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated:
- (1) Tank number 15 (OEPA source number P001); a maximum of 3.5 pounds of sulfur dioxide per ton of glass produced.

- (2) Tank number 16 (OEPA source number P002); a maximum of 13.0 pounds of sulfur dioxide per ton of glass produced.

Effective: 01/23/2006
R.C. 119.032 review dates: 10/28/2005 and 01/23/2011

CERTIFIED ELECTRONICALLY

Certification

01/13/2006

Date

Promulgated Under: 119.03
Statutory Authority: 3704.03(E)
Rule Amplifies: 3704.03(A) and 3704.03(E)
Prior Effective Dates: 12/28/79, 5/11/87