

3745-18-38

Hancock County emission limits.

- (A) No owner or operator of any coal-fired steam generating unit, unless otherwise specified below, shall cause or permit the emission of sulfur dioxide from any source to exceed a maximum of 2.6 pounds of sulfur dioxide per MM Btu actual heat input.
- (B) The "Ashland Oil Company" (OEPA premise number 0332010020) or any subsequent owner or operator of the "Ashland Oil Company" facility located on Glessner Avenue, Findlay, Ohio shall not cause or permit the emission of sulfur Dioxide from the following sources to exceed the amounts indicated:
- (1) Crude heater numbers 7-1-B-1, vacuum heater number 7-5-B-1 (OEPA source numbers B001 and B002); a maximum of 5.3 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
 - (2) Boiler numbers 8 and 9 (OEPA source numbers B003 and B004); a maximum of 5.3 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (C) The "Northern Ohio Sugar Company (OEPA premise number 0332010013) or any subsequent owner or operator of the "Northern Ohio Sugar Company" facility located in Findlay, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 2 and 3. (OEPA source numbers B002 and B003) to exceed a maximum of 2.5 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (D) The "Cooper Tire and Rubber Company" (OEPA premise number 0332010003) or any subsequent owner or operator of the "Cooper Tire and Rubber Company" facility located at Lima and Western Avenues, Findlay, Ohio shall not cause or permit the emission of sulfur dioxide from boiler number 1 (OEPA source number B004) to exceed a maximum of 5.3 pounds of sulfur dioxide per MM Btu actual heat input.
- (E) The "Archer Daniels Midland Company" (OEPA premise number 0332020187) or any subsequent owner or operator of the Archer Daniels Midland Company facility located on state route 12, Fostoria, Ohio shall not cause or permit the emission of sulfur dioxide from boiler number 1 (OEPA source number B001) to exceed a maximum of 1.2 pounds of sulfur dioxide per MM Btu actual heat input.

Effective: 01/23/2006

R.C. 119.032 review dates: 10/28/2005 and 01/23/2011

CERTIFIED ELECTRONICALLY

Certification

01/13/2006

Date

Promulgated Under: 119.03
Statutory Authority: 3704.03(E)
Rule Amplifies: 3704.03(A) and 3704.03(E)
Prior Effective Dates: 12/28/79