

3745-18-29

Fairfield County emission limits.

- (A) No owner or operator of any coal-fired steam generating unit, unless otherwise specified below, shall cause or permit the emission of sulfur dioxide from any source to exceed a maximum of 4.5 pounds of sulfur dioxide per MM Btu actual heat input.
- (B) The "~~Crown-Zellerbach~~Ohio Paperboard Corporation" (OEPA premise number 0123000005) or any subsequent owner or operator of the "~~Crown-Zellerbach~~Ohio Paperboard Corporation" facility located at 210 Water Street, Baltimore, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 2 and 3 (OEPA source numbers B001 and B002) to exceed a maximum of 7.0 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (C) The "Diamond Power Specialty Corporation" (OEPA premise number 0123010022) or any subsequent owner or operator of the "Diamond Power Specialty Corporation" facility located at 2600 East Main Street, Lancaster, Ohio shall not cause or permit the emission of sulfur dioxide from north boiler and south boiler (OEPA source numbers B001 and B003) to exceed a maximum of 6.9 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (D) The "~~Fairfield School for Boys~~Southeastern Correctional Institution" (OEPA premise number 0123010109) or any subsequent owner or operator of the "~~Fairfield School for Boys~~Southeastern Correctional Institution" facility located in Lancaster, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 1 and 2 (OEPA source numbers B001 and B002) to exceed a maximum of 4.1 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (E) The "~~Loroco Industries, Incorporated~~Sunoco Products Company" (OEPA premise number 0123010150) or any subsequent owner or operator of the "~~Loroco Industries, Incorporated~~Sunoco Products Company" facility located at South Columbus Street, Lancaster, Ohio shall not cause or permit the emission of sulfur dioxide from the Brothers boiler (OEPA source number B001) to exceed a maximum of 4.8 pounds of sulfur dioxide per MM Btu actual heat input.

Effective: 01/23/2006
R.C. 119.032 review dates: 10/28/2005 and 01/23/2011

CERTIFIED ELECTRONICALLY

Certification

01/13/2006

Date

Promulgated Under: 119.03
Statutory Authority: 3704.03(E)
Rule Amplifies: 3704.03(A) and 3704.03(E)
Prior Effective Dates: 12/28/79