

3745-18-28

Erie County emission limits.

- (A) No owner or operator of any coal-fired steam generating unit, unless otherwise specified below, shall cause or permit the emission of sulfur dioxide from any source to exceed a maximum of 2.6 pounds of sulfur dioxide per MM Btu actual heat input.
- (B) The "Charles J. Otto Greenhouse, Incorporated" (OEPA premise number 0322000173) or any subsequent owner or operator of the "Charles J. Otto Greenhouse, Incorporated" facility located at Route Number 1, Berlin Township, Ohio shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated and shall limit the operation of said sources such that the indicated average operating rates are not exceeded for any calendar day:
- (1) Coal boiler (OEPA source number B001); a maximum of 5.5 pounds of sulfur dioxide per MM Btu actual heat input and average operating rates as follows: first quarter, 10 MM Btu per hour; second quarter, 10 MM Btu per hour; third quarter, 8 MM Btu per hour; fourth quarter, 10 MM Btu per hour.
 - (2) Oil boiler (OEPA source number B002); a maximum of 2.0 pounds of sulfur dioxide per MM Btu actual heat input and averaging operating rates as follows: first quarter, 13 MM Btu per hour; second quarter, 13 MM Btu per hour; third quarter, 5 MM Btu per hour; fourth quarter, 13 MM Btu per hour.
- (C) The "Jacob H. Otto Greenhouse" (OEPA premise number 0322010174) or any subsequent owner or operator of the "Jacob H. Otto Greenhouse" facility located on Route Number 1, Huron, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 131083 and 91993 (OEPA source numbers B001 and B002) to exceed a maximum of 5.5 pounds of sulfur dioxide per MM Btu actual heat input from each boiler and shall operate said boilers such that the following combined average operating rates are not exceeded for any calendar day: first quarter, 15 MM Btu per hour; second quarter, 15 MM Btu per hour; third quarter, 10 MM Btu per hour; fourth quarter, 15 MM Btu per hour.
- (D) The "~~Ford Motor Company~~ Visteon Corp." (OEPA premise number 0322020042) or any subsequent owner or operator of the "~~Ford Motor Company~~ Visteon Corp." facility located at 3020 Tiffin Avenue, Sandusky, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 1 through 3 (OEPA source numbers B001 through B003) to exceed a maximum of 1.6 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (E) The "New Departure-Hyatt" (OEPA premise number 0322020045) or any subsequent owner or operator of the "New Departure-Hyatt" facility located at 2509 Hayes

Avenue, Sandusky, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 1 through 3 (OEPA source numbers B001 through B003) to exceed a maximum of 1.6 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.

- (F) The "Huron Lime Company" (OEPA premise number 0322010062) or any subsequent owner or operator of the "Huron Lime Company" facility located at 100 Meeker Street, Huron, Ohio shall not cause or permit the emission of sulfur dioxide from lime kiln numbers 1, 2, 3 (OEPA source numbers P001 through P003) to exceed a maximum of 4.0 pounds of sulfur dioxide per ton of product.
- (G) The "American Crayon Company" (OEPA premise number 0322020005) or any subsequent owner or operator of the "American Crayon Company" facility located at 1706 Hayes Avenue, Sandusky, Ohio shall not cause or permit the emission of sulfur dioxide from boiler number 1 (OEPA source number B001) to exceed a maximum of 6.0 pounds of sulfur dioxide per MM Btu actual heat input and shall operate said boiler such that the following average operating rates are not exceeded for any calendar day: first quarter, 15 MM Btu per hour; second quarter, 15 MM Btu per hour; third quarter, 10 MM Btu per hour; fourth quarter, 10 MM Btu per hour.
- (H) The "Ohio Soldiers and Sailors Home" (OEPA premise number 0322020095) or any subsequent owner or operator of the "Ohio Soldiers and Sailors" Home facility located on Columbus Avenue, Sandusky, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 2 and 3 (OEPA source numbers B002 and B003) to exceed a maximum of 1.6 pounds of sulfur dioxide per MM Btu actual heat input from each boiler and shall operate said boilers such that the following combined average operating rates are not exceeded for any calendar day: first quarter 32 MM Btu per hour; second quarter, 32 MM Btu per hour third quarter, 18 MM Btu per hour; fourth quarter, 18 MM Btu per hour.

Effective: 01/23/2006

R.C. 119.032 review dates: 10/28/2005 and 01/23/2011

CERTIFIED ELECTRONICALLY

Certification

01/13/2006

Date

Promulgated Under: 119.03
Statutory Authority: 3704.03(E)
Rule Amplifies: 3704.03(A) and 3704.03(E)
Prior Effective Dates: 12/28/79