

3745-18-78

**Sandusky county emission limits.**

- (A) No owner or operator of any coal-fired steam generating unit, unless otherwise specified below, shall cause or permit the emission of sulfur dioxide from any source to exceed a maximum of 2.6 pounds of sulfur dioxide per MM Btu actual heat input.
- (B) The "~~J.E. Baker Company, Millersville Plant~~Carmeuse Lime, Inc." (OEPA premise number 0372000081) or any subsequent owner or operator of the "~~J.E. Baker Company, Millersville Plant~~Carmeuse Lime, Inc., 3964 County Road Number 41, Millersville, Ohio" shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated:
- (1) Rotary kiln number 2160 (OEPA source number P005); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
  - (2) Rotary kiln number 2166 (OEPA source number P006); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
- (C) The "~~Ohio Lime Company~~Carmeuse Lime, Inc." (OEPA premise number 0372000104) or any subsequent owner or operator of the "~~Ohio Lime Company~~Carmeuse Lime, Inc., ~~3964 County Road Number 32, Millersville~~659 Anderson Road, Woodville, Ohio" shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated:
- (1) Rotary lime kiln (OEPA source number P012); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
  - (2) Number 1 rotary kiln (OEPA source number P015); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
  - (3) Number 2 rotary kiln (OEPA source number P016); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
  - (4) Number 3 rotary kiln (OEPA source number P017); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
  - (5) Number 4 rotary kiln (OEPA source number P018); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
- (D) "Pfizer, Incorporated" (OEPA premise number 0372000109); or any subsequent owner or operator of "Pfizer, Incorporated, Cedar Street, Gibsonburg, Ohio" shall not cause or permit the emission of sulfur dioxide from the following sources to

exceed the amounts indicated:

- (1) Number 6 rotary kiln (OEPA source number P009); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
  - (2) Number 7 rotary kiln (OEPA source number P010); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
  - (3) Number 5 rotary kiln (OEPA source number P008); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
- (E) "Martin Marietta Chemicals Magnesia Specialties, Inc." (OEPA premise number 0372000127) or any subsequent owner or operator of "Martin Marietta Chemicals Magnesia Specialties, Inc., 755 Lime Road, Woodville, Ohio" shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated:
- (1) Rotary lime kilns numbers 5 and 4 (OEPA source numbers P010 and P013); a maximum of twenty-five pounds of sulfur dioxide per ton of product.
  - (2) Number 6 rotary refractory kiln (OEPA source number P014); a maximum of twenty-five pounds of sulfur dioxide per ton of product.
  - (3) Rotary lime kiln numbers 1 and 2 (OEPA source numbers P015 and P019); a maximum of 25.0 pounds of sulfur dioxide per ton of product.
- ~~(F) The "Woodville Lime and Chemical Company" (OEPA premise number 0372000147) or any subsequent owner or operator of the "Woodville Lime and Chemical Company, 643 Lime Road, Woodville, Ohio" shall not cause or permit the emission of sulfur dioxide from rotary lime kiln numbers 1 and 2 (OEPA source numbers P001 and P005) to exceed a maximum of 25.0 pounds of sulfur dioxide per ton of product.~~
- ~~(G)~~(F) The "Northern Ohio Michigan Sugar Company" (OEPA premise number 0372030103) or any subsequent owner or operator of the "Northern Ohio Michigan Sugar Company, 1101 North Front Street, Fremont, Ohio" shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated:
- (1) Boiler number 3 (OEPA source number B004); a maximum of 0.5 pounds of sulfur dioxide per MM Btu actual heat input.

- (2) Main boiler numbers 1 and 2 (OEPA source numbers B005 and B006); a maximum of 5.9 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.

Effective: 01/23/2006

R.C. 119.032 review dates: 10/28/2005 and 01/23/2011

CERTIFIED ELECTRONICALLY

---

Certification

01/13/2006

---

Date

Promulgated Under: 119.03  
Statutory Authority: 3704.03(E)  
Rule Amplifies: 3704.03(A) and 3704.03(E)  
Prior Effective Dates: 12/28/79, 5/11/87