

Licking county emission limits.

- (A) No owner or operator of any coal-fired steam generating unit, unless otherwise specified in this rule, shall cause or permit the emission of sulfur dioxide from any source to exceed a maximum of 4.5 pounds of sulfur dioxide per MM Btu actual heat input.
- (B) The "Kaiser Aluminum and Chemical Corporation" (OEPA premise number 0145010093) or any subsequent owner or operator of the "Kaiser Aluminum and Chemical Corporation" facility located on State Route Number 79, South Heath, Ohio shall not cause or permit the emission of sulfur dioxide from boiler numbers 1 and 2 (OEPA source numbers B001 and B002) to exceed a maximum of 4.3 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (C) The "Denison University" (OEPA premise number 0145000018) or any subsequent owner or operator of the "Denison University" facility located on South Main street, Granville, Ohio shall not cause or permit the emission of sulfur dioxide from the central heating plant FJ-18 number 48 (OEPA source number B001) to exceed a maximum of 6.2 pounds of sulfur dioxide per MM Btu actual heat input from each boiler.
- (D) The "Owens-Corning Fiberglas" (OEPA premise number 0145020185) or any subsequent owner or operator of the "Owens-Corning Fiberglas" facility located on Case avenue, Newark, Ohio shall not cause or permit the emission of sulfur dioxide from the following sources to exceed the amounts indicated:
 - (1) D-5 furnace (OEPA source number P006); a maximum of 1.4 pounds of sulfur dioxide per ton of process weight.
 - (2) D-6 furnace (OEPA source number P007); a maximum of 1.4 pounds of sulfur dioxide per ton of process weight.
 - (3) F-5 furnace (OEPA source number P008); a maximum of 3.7 pounds of sulfur dioxide per ton of process weight.
- (E) The "Newark Gardens Greenhouse" (OEPA premise number unassigned) or any subsequent owner or operator of the "Newark Gardens Greenhouse" facility located in Newark, Ohio shall not cause or permit the emission of sulfur dioxide from boiler number 1 (OEPA source number unassigned) to exceed a maximum of 6.0 pounds of sulfur dioxide per MM Btu actual heat input.

Effective: 02/17/2011

R.C. 119.032 review dates: 11/30/2010 and 11/30/2015

CERTIFIED ELECTRONICALLY
Certification

02/07/2011
Date

Promulgated Under: 119.03
Statutory Authority: 3704.03(E)
Rule Amplifies: 3704.03(A), 3704.03(E)
Prior Effective Dates: 12/28/79