San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

MAR 31 2015

Jerry Frost
California Resources Production Corp
9600 Ming Ave, Suite 300
Bakersfield, CA 93311

RE: Final – Authority to Construct/Certificate of Conformity (Minor Mod)
Facility Number: S-1326
Project Number: S-1143924

Dear Mr. Frost:

The Air Pollution Control Officer has issued the Authority to Construct permits to California Resources Production Corp for authorizing combustion of Thermally Enhanced Oil Recovery (TEOR) and tank vapor control system (TVR) gas in steam generators S-1326-405, '-406, '-407, '-417 and '-418. Also, TEOR operation permits S-1326-26, '-27, '-28, and '-35 and TVR permit '-263 will be revised to list S-1326-405, '-406, '-407, '-417 and '-418 as authorized disposal devices., at CRP's Heavy Oil Central Stationary Source.

Enclosed are the Authority to Construct permits and invoice for the engineering evaluation fees pursuant to District Rule 3010. The District's analysis of the proposal was sent to US EPA Region IX on March 9, 2015. No comments were received following the District's preliminary decision on this project.

Prior to operating with modifications authorized by the Authority to Construct, you must submit an application to modify the Title V permit as an administrative amendment in accordance with District Rule 2520, Section 11.5.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Leonard Scandura at (661) 392-5500.

Sincerely,

for Arnaud Marjollet
Director of Permit Services

AM:RCR

Enclosures
cc: Gerardo C. Rios, EPA (w/enclosure) via email

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-26-24 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

SECTION: NE23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
MODIFICATION THERMALLY ENHANCED OIL RECOVERY OPERATION WITH WELL VENT VAPOR CONTROL SYSTEM SERVING 120 STEAM ENHANCED WELLS, INCLUDING SULFA-TREAT SYSTEM, GAS TRAPS, COLLECTION PIPING, VAPOR COMPRESSOR WITH ELECTRIC MOTOR, AND PIPING TO FIELD FUEL GAS SYSTEM, APPROVED COMBUSTION DEVICES, DOGGR DISPOSAL WELL, AND FLARE (FANO): DESIGNATE S-1326-405, '-406, '-407, '-417 AND '-418 AS AUTHORIZED DISPOSAL DEVICES.

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. TEOR operation shall include sulfatreat system, gas traps, collection piping, vapor compressor with electric motor, piping to field fuel gas system, piping to steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, '-405, '-406, '-407, '-417 and '-418 and '-419 through '-425, DOGGR disposal well and flare (Fano). [District Rule 2201] Federally Enforceable Through Title V Permit
4. Wells may be operated with closed casing vents or be vented to vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services
S-1326-26-24 : Mar 31 2015 8:44AM -- RINALDIR : Joint Inspection Required with RINALDIR

5. Fluids produced from wells with closed vents shall be introduced only to production equipment served by vapor control system listed on tank S-1326-46 which is 99% efficient. [District Rule 2201] Federally Enforceable Through Title V Permit

6. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit

7. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

8. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

9. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

10. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

11. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

12. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

14. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

15. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit

16. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit

17. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

18. The permittee shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.3.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit

19. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 108.1. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

20. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

21. The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

22. Permittee shall maintain with the permit a current listing of all steam enhanced wells connected to the casing vent control system and shall make such listing readily available for District inspection upon request. [District Rule 4401] Federally Enforceable Through Title V Permit

23. Sulfur content of scrubbed TEOR gas and flare pilot gas shall not exceed 1 gr/100scf. [District Rule 2201] Federally Enforceable Through Title V Permit

24. The well vent vapors and tank vapors from vapor collection systems #S-1326-46 shall vent only to existing otherwise permit exempt combustion equipment, DOGGR approved injection wells, 2.9 MMBtu/hr waste gas flare, or steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, '-405, '-406, '-407, '-417, '-418 and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit

25. Flare shall be used exclusively for incineration of vapors from this TEOR control system and tank vapor control systems #S-1326-46. [District Rule 2201] Federally Enforceable Through Title V Permit

26. Collected liquids shall be piped only to vapor controlled tanks. [District Rule 2201] Federally Enforceable Through Title V Permit

27. VOC content of well vent vapor gas shall not exceed 10% by weight. If the VOC content of the well vent vapor gas is less than 10% by weight for 8 consecutive quarterly samplings per District approved plan, sampling frequency shall only be required annually. Representative samples shall be collected during periods of normal operation and not be within 48 hours after routine maintenance or repair. Records of test shall be maintained for a period of five years and be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

28. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

29. Emissions rates shall not exceed any of the following: VOC: 0.063 lb/MMBtu; NOx: 0.068 lb/MMBtu; PM10: 0.008 lb/MMBtu; and CO: 0.37 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

30. The higher heating value of the flared gas shall be monitored at least quarterly. Measured higher heating value and quantity of gas flared shall be used to determine compliance with heat input limits. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

31. Permittee shall test annually the sulfur content of casing gas combusted in permit exempt equipment using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

32. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

33. If this flare requires a pilot flame, then the flare shall be operated with a flame present at all times, and kept in operation when emissions may be vented to it. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

34. Permittee shall maintain daily records of pilot gas and TEOR gas flared and shall make such records readily available for District inspection for a period of five years. [District Rule 2520, 9.4.2 and District Rule 1070] Federally Enforceable Through Title V Permit

35. This flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA Method 9 test shall be conducted within 72 hours. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

36. This flare shall not be used as a leak control device as described in Rule 4403, 5.3.1, nor as a control device for any permit unit subject to NSPS, without modification of permit requirements to address 40 CFR 60.18. [District Rule 2520, 9.3.3] Federally Enforceable Through Title V Permit

37. Sulfa Treat equipment shall be purged with natural gas, inert gas, or air prior to opening any vessel, filter, pipeline or connection to prevent sulfur compound emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-27-21 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

SECTION: 02 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
MODIFICATION OF THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION WITH WELL VENT VAPOR CONTROL SYSTEM SERVING UP TO 100 STEAM ENHANCED WELLS INCLUDING: GAS LIQUID SEPERATORS, COMPRESSOR, CONDENSATE HANDLING AND 2.9 MMBTU/HR AIR ASSISTED FLARE (SECTION 2 EAST CVR): DESIGNATE S-1326-405, '-406, '-407, '-417 AND '-418 AS AUTHORIZED DISPOSAL DEVICES.

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Wells may be operated with closed casing vents or be vented to vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit
4. TEOR operation (Section 2 East CVR) shall include gas liquid separator, compressor, condensate handling equipment, 2.9 MMBtu/hr McGill, #1011-2, flare equipped with 2 in. dia. burner tip, 1/2 hp air assist blower, and K/O drum at flare base and vapor piping from TEOR system S-1326-28 . [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services
S-1326-27-21 : Mar 31 2015 8:44AM -- RINALDIR : Joint Inspection Required with RINALDIR

5. The well vent vapors shall vent only to 2.9 MMBtu/hr waste gas flare or steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, '-405, '-406, '-407, '-417, '-418 and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit

6. Fluids produced from wells with closed vents shall be introduced only to production equipment served by vapor control system listed on tank S-1326-201 which is 99% efficient. [District Rule 2201] Federally Enforceable Through Title V Permit

7. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit

8. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

9. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

10. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

11. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

12. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

13. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

14. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

15. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

16. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit

17. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

18. The control efficiency, measured and calculated as carbon ,of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

19. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.3.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit

20. Permittee shall maintain with the permit a current listing of all steam enhanced wells connected to the casing vent control system and shall make such listing readily available for District inspection upon request. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit

21. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 108.1. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

22. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

23. The requirements of District Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit because it is not an in situ combustion well vent. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

24. Flare Visible emissions shall not exceed 1/4 Ringelmann. [District Rule 2201] Federally Enforceable Through Title V Permit

25. Sulfur content of scrubbed TEOR gas and flare pilot gas shall not exceed 1 gr/100scf. [District Rule 2201] Federally Enforceable Through Title V Permit

26. All well vent gas shall be scrubbed prior to incineration in 2.9 MMBtu/hr waste gas flare or steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, '-405, '-406, '-407, '-417, '-418 and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit

27. Emission rates for flare shall not exceed any of the following limits: 0.008 lb-PM10/MMBtu, 0.068 lb-NOx/MMBtu (as NO2) , 0.063 lb-VOC/MMBtu, or 0.37 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit

28. The higher heating value of the flared gas shall be monitored at least quarterly. Measured higher heating value and quantity of gas flared shall be used to determine compliance with heat input limits. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

29. VOC content of well vent vapor gas shall not exceed 10% by weight. If the VOC content of the well vent vapor gas is less than 10% by weight for 8 consecutive quarterly samplings per District approved plan, sampling frequency shall only be required annually. Representative samples shall be collected during periods of normal operation and not be within 48 hours after routine maintenance or repair. Records of test shall be maintained for a period of five years and be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

30. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

31. Permittee shall test annually the sulfur content of scrubbed casing gas using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

32. Permittee shall maintain a current well roster and shall make such roster, component count and resulting emissions readily available for District inspection upon request. [District Rule 1070]

33. Condensed liquids from condensate handling system shall be piped in closed systems to the WASP disposal well. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Emergency condensate overflow pit shall be empty except during breakdown conditions pursuant to Rule 1100. [District Rule 2201] Federally Enforceable Through Title V Permit

35. All wells served by this vapor control system shall be shut-in and shall not vent to the atmosphere in the event of failure of the non-condensible VOC disposal system. [District Rule 2201] Federally Enforceable Through Title V Permit

36. Permittee shall at least monthly, measure and record sulfur content and BTU content of TEOR gas exiting the desulfurizer using ASTM method D1072, D3031, D4084, D3246 or a gas detector tube, and shall make all records and analyses readily available for District inspection. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

37. Permittee shall maintain daily records of pilot gas and TEOR gas flared and shall make such records readily available for District inspection for a period of five years. [District Rule 2520, 9.4.2 and District Rule 1070] Federally Enforceable Through Title V Permit

38. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

39. If this flare requires a pilot flame, then the flare shall be operated with a flame present at all times, and kept in operation when emissions may be vented to it. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

40. This flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA Method 9 test shall be conducted within 72 hours. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

41. This flare shall not be used as a leak control device as described in Rule 4403, 5.3.1, nor as a control device for any permit unit subject to NSPS, without modification of permit requirements to address 40 CFR 60.18. [District Rule 2520, 9.3.3] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-28-20 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

SECTION: 2 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
MODIFICATION OF THERMALLY ENHANCED OIL RECOVERY OPERATION INCLUDING DEEP EMERGENCY OVERFLOW PIT WITH MESH COVER, HORIZONTAL GAS LIQUID SEPARATOR, AIR-COOLED HEAT EXCHANGER, HORIZONTAL CONDENSATE COLLECTION VESSEL WITH LIQUID TRANSFER PUMPS, 30 HP COMPRESSOR (K-101), 2.9 MMBTU/HR MCGILL STANDBY FLARE (#1011-2) EQUIPPED WITH 2 IN DIA BURNER TIP, AIR ASSIST BLOWER, KO DRUM SHARED WITH PERMIT UNIT S-1326-27, AND WELL VENT VAPOR CONTROL SYSTEM SERVING 150 STEAM DRIVE WELLS: DESIGNATE S-1326-405, '-406, '-407, '-417 AND '-418 AS AUTHORIZED DISPOSAL DEVICES.

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. TEOR operation shall include deep emergency overflow pit with mesh cover, horizontal gas-liquid separator, air-cooled heat exchanger,horizontal condensate collection vessel with liquid transfer pumps for the pumping of condensate to heavy oil tank battery, 30 hp compressor (K-101) with compressed vapors sent to common field fuel gas line, and production well vent casing line to TEOR system S-1326-27 and steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, '-405, '-406, '-407, '-417, '-418 and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services

S-1326-28-20 : Mar 31 2015 8:44AM -- RINALDIR : Joint Inspection Required with RINALDIR

4. Wells may be operated with closed casing vents or be vented to vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit

5. Fluids produced from wells with closed vents shall be introduced only to production equipment served by vapor control system listed on tank S-1326-201 which is 99% efficient. [District Rule 2201] Federally Enforceable Through Title V Permit

6. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit

7. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit

8. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit

9. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

10. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

11. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

12. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

13. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

14. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit

15. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit

16. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

17. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit

18. The permittee shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.3.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit

19. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 108.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

20. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

21. The requirements of District Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit because it is not an in situ combustion well vent. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

22. Components shall be maintained and leaks shall be repaired as specified in Rule 4401. [District Rule 2201] Federally Enforceable Through Title V Permit

23. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit

24. Permittee shall maintain with the permit a current listing of all steam enhanced wells connected to the casing vent control system and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

25. Well vent vapor control system shall include vapor piping connected to tank vapor control system listed on permit #S-1326-201. [District Rule 2201] Federally Enforceable Through Title V Permit

26. Sulfur content of scrubbed TEOR gas shall not exceed 1 gr/100scf. [District Rule 2201] Federally Enforceable Through Title V Permit

27. Sulfur scrubber shall be operated to maintain continued compliance with fuel gas sulfur content limit of 1 grain-S/100 scf of fuel gas. [District Rule 2201] Federally Enforceable Through Title V Permit

28. Only PUC quality natural gas or comparable quality lease gas with sulfur content of 1 grain-S/100 scf or less shall be utilized as make-up gas for the horizontal condensate collection vessel and utilized as pilot fuel for standby flare. [District Rule 2201] Federally Enforceable Through Title V Permit

29. Sulfur scrubber shall be monitored monthly for H2S content of gas after treatment to determine when recharging is required. [District Rule 2201] Federally Enforceable Through Title V Permit

30. Permittee shall maintain a written record of H2S content and recharging dates and such records shall be made readily available for District inspection upon request. [District NSR Rule and District Rule 1070] Federally Enforceable Through Title V Permit

31. Permittee shall test annually the sulfur content of scrubbed casing gas using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

32. VOC content of well vent vapor gas shall not exceed 10% by weight. If the VOC content of the well vent vapor gas is less than 10% by weight for 8 consecutive quarterly samplings per District approved plan, sampling frequency shall only be required annually. Representative samples shall be collected during periods of normal operation and not be within 48 hours after routine maintenance or repair. Records of test shall be maintained for a period of five years and be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

33. The emergency condensate overflow pit shall be empty except during breakdown conditions pursuant to Rule 1100. [District Rule 2201] Federally Enforceable Through Title V Permit

34. Well head casing vent gas collection system shall be shut-in and shall not vent to the atmosphere in the event of failure of the non-condensible VOC disposal system. [District Rule 2201] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-35-17 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

SECTION: 14 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
MODIFICATION OF THERMALLY ENHANCED OIL RECOVERY OPERATION WITH WELL VENT VAPOR CONTROL SYSTEM SERVING 250 STEAM ENHANCED WELLS, INCLUDING 50 HP COMPRESSOR, ONE AIR-COOLED VAPOR CONDENSER, AND PIPING TO FIELD FUEL GAS SYSTEM, DOGGR DISPOSAL WELL, AND/OR 3.6 MMBTU/HR KALDAIR FLARE INCLUDING TWO 8000 LB SULFATREAT CANISTERS (ONE AS BACKUP) (SECTION 14 YOUNG): DESIGNATE UNITS AS APPROVED COMBUSTION DEVICES FOR S-1326-405, '-406, '-407, '-417 AND '-418

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Fluids produced from wells with closed vents shall be introduced only to production equipment served by vapor control system listed on tank S-1326-201 which is 99% efficient. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Well vent vapors shall vent to the field fuel gas system, DOGGR approved injection wells, flare listed on this permit, or steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, '-405, '-406, '-407, '-417 and '-418 and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services
S-1326-35-17 : Mar 31 2015 8:44AM -- RINALDIR : Joint Inspection Required with RINALDIR

5. Well head casing vent collection piping network shall be limited to 250 steam enhanced wells. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Sulfur scrubber shall be monitored monthly for H2S content of gas after treatment to determine when recharging is required. [District NSR Rule and District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. Sulfur content of gas combusted in flare shall not exceed 1 gr/100 scf. [District NSR Rule, District Rule 4801, and Kern County Rule 407] Federally Enforceable Through Title V Permit
8. Permittee shall test annually the sulfur content of gas combusted in flare using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. Flare shall operate with no visible emission in excess of 5% opacity. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Maximum amount of gas (pilot and waste gas) combusted by flare shall not exceed 150.0 MMBtu/day. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emissions from the flare shall not exceed any of the following limits (based on total gas combusted): NOx (as NO2): 0.068 lb/MMBtu; PM10: 0.008 lb/MMBtu; CO: 0.37 lb/MMBtu; or VOC: 0.063 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The higher heating value of the flared gas shall be monitored at least quarterly. Measured higher heating value and quantity of gas flared shall be used to determine compliance with heat input limit. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
13. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. If this flare requires a pilot flame, then the flare shall be operated with a flame present at all times, and kept in operation when emissions may be vented to it. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. This flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA Method 9 test shall be conducted within 72 hours. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. This flare shall not be used as a leak control device as described in Rule 4403, 5.3.1, nor as a control device for any permit unit subject to NSPS, without modification of permit requirements to address 40 CFR 60.18. [District Rule 2520, 9.3.3] Federally Enforceable Through Title V Permit
17. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401] Federally Enforceable Through Title V Permit
18. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401] Federally Enforceable Through Title V Permit
19. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. The following conditions shall be used to determination of a violation: 1) Existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere; 2) Existence of a component with a major liquid leak; 3) Existence of a component with a gas leak greater than 50,000 ppmv; or 4) Existence of a component leak consisting of a minor liquid or gas leak, or a gas leak greater than 10,000 ppmv up to 50,000 ppmv, in excess of the allowable number of leaks specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

21. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended December 14, 2006) at any one time. [District Rule 4401] Federally Enforceable Through Title V Permit

22. Operator shall affix a readily visible tag bearing the date and time of leak detection, the date and time of leak measurement, the leak concentration of gaseous leaks (in ppmv), for liquid leaks whether it is a major liquid leak or a minor liquid leak, and whether the component is an essential component, an unsafe-to monitor component, or a critical component leak. [District Rule 4401] Federally Enforceable Through Title V Permit

23. The tag shall remain in place until the leaking component is repaired, re-inspected, using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401] Federally Enforceable Through Title V Permit

24. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401] Federally Enforceable Through Title V Permit

25. Except for leaking critical components or leaking essential components, the operator shall repair each leak within time specified in Table 3, of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

26. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401] Federally Enforceable Through Title V Permit

27. The operator shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401] Federally Enforceable Through Title V Permit

28. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401] Federally Enforceable Through Title V Permit

29. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year [District Rule 4401] Federally Enforceable Through Title V Permit

30. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of this rule. [District Rule 4401] Federally Enforceable Through Title V Permit

31. An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. [District Rule 4401] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

32. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of this rule. [District Rule 4401] Federally Enforceable Through Title V Permit

33. An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401] Federally Enforceable Through Title V Permit

34. An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. [District Rule 4401] Federally Enforceable Through Title V Permit

35. An operator shall inspect a component, except for a PRD that releases to the atmosphere, that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401] Federally Enforceable Through Title V Permit

36. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401] Federally Enforceable Through Title V Permit

37. The operator shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one centimeter or less from the surface of the component interface. [District Rule 4401] Federally Enforceable Through Title V Permit

38. VOC content of well vent vapor gas shall not exceed 10% by weight. If the VOC content of the well vent vapor gas is less than 10% by weight for 8 consecutive quarterly samplings per District approved plan, sampling frequency shall only be required annually. Representative samples shall be collected during periods of normal operation and not be within 48 hours after routine maintenance or repair. Records of test shall be maintained for a period of five years and be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

39. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401] Federally Enforceable Through Title V Permit

40. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401] Federally Enforceable Through Title V Permit

41. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components; and the efficiency of destruction devices determined by USEPA Method 25, 25a, or 25b as applicable. [District Rule 4401] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

42. Permittee shall maintain an inspection log which includes the following information: 1) the total number of components inspected and the total number and percentage of leaking components found by component type, 2) the location, type, and name or description of each leaking component and description of any unit where the leaking component is found, 3) the date and method of leak detection, 4) the size of the leak (in ppmv for gaseous leaks, and major or minor for liquid leaks), 5) the date the leaking component is repaired, replaced, or removed from service, 6) the identity and location of essential or critical components found leaking that cannot be repaired until the next regular process unit turnaround or not later than one year after leak detection, whichever comes later, 7) the methods used to minimize the leak from essential or critical components, 8) the date of re-inspection and the leak concentration (in ppmv) after the component is repaired or replaced, 9) the inspector's name, mailing address, and business telephone number, and 10) the date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401] Federally Enforceable Through Title V Permit

43. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4401] Federally Enforceable Through Title V Permit

44. The operator shall shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system. [District Rule 4401] Federally Enforceable Through Title V Permit

45. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. Permittee shall maintain at the facility the copies of the training records of the training program. [District Rule 4401] Federally Enforceable Through Title V Permit

46. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule4401] Federally Enforceable Through Title V Permit

47. Permittee shall maintain a copy of the latest APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB, and US EPA upon request. [District Rule 4401] Federally Enforceable Through Title V Permit

48. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit

49. The permittee shall keep accurate records of the amount of gas (pilot and waste gas) flared, H2S content and recharging dates, for a period of five years, and shall make such records available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

50. Permittee shall maintain a current well roster of all wells served by collection system, and such roster shall be made readily available for District inspection upon request. [District Rule 2520, 9.3.2 and District Rule 1070] Federally Enforceable Through Title V Permit

51. All records required by this permit shall be maintained and retained on-site for a minimum of five (5) years and made available for District, ARB, and EPA inspection upon request. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-263-25 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

SECTION: SW23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
MODIFICATION OF 3,000 BBL FIXED ROOF WASH TANK SERVED BY TANK VAPOR CONTROL SYSTEM SHARED WITH CASING VENT RECOVERY (CVR) SYSTEM LISTED ON S-1326-287 AND CRUDE OIL STORAGE TANKS S-1326-263, -279, -280, -281, -283, -285, AND '-315 (SECTION 23 FACILITY): DESIGNATE S-1326-405, '-406, '-407, '-417 AND '-418 AS AUTHORIZED DISPOSAL DEVICES.

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. Collected TVR vapors shall be disposed of in a Department of Oil, Gas and Geothermal Resources (DOGGR) approved vapor disposal well, injected into the field fuel gas system and used in permit exempt equipment, or combusted in steam generators S-1326-9, '-294, '-314, '-337, '-338, '385, '-390, '-391, '-392, '-400, '-401. '-405, '-406, '-407, '-417 and '-418 [District Rules 2020 and 2201] Federally Enforceable Through Title V Permit
4. VOC content of tank vapor space and vapor control system piping and components shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services

S-1326-263-25 : Mar 31 2015 8:45AM -- RINALDIR : Joint Inspection Required with RINALDIR

5. Prior to injecting collected TVR (and S-1326-287 CVR) vapors into field fuel gas system, the collected vapors shall be treated by a hydrogen sulfide removal system which reduces the hydrogen sulfide concentration in the collected vapors by at least 95%. The sulfur content of the treated vapors may not exceed 1.0 grains S/ 100 scf gas. The treated TVR (and CVR) vapors injected into the field fuel gas line shall not be greater than five percent by weight hydrocarbons heavier than butane as determined by test method ASTM D-1945 or equivalent test method with prior District approval. [District Rules 2020 and 2201] Federally Enforceable Through Title V Permit

6. Operator shall ensure the vapor control system is functional and operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

7. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

8. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rules 4623, 4.4 and 2201] Federally Enforceable Through Title V Permit

9. Connections between this TVR system and the wellhead casing vent recovery (CVR) system listed on S-1326-287 shall be made upstream of the hydrogen sulfide removal system included in this permit. [District Rule 2201] Federally Enforceable Through Title V Permit

10. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit

11. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

12. Prior to opening the tank to allow tank cleaning, one of the following procedures must be followed: 1) Prior to venting the tank to the atmosphere, operate the tank vapor recovery system/vapor control device for at least 24 hours such that it collects the tank vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil tank by restricting the outflow of water, such that 90% of the tank volume is displaced; or 3) Vent the tank to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3\ V/Q$, where t = time, V = tank volume (cubic feet), and Q= flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit

13. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit

14. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

15. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit

16. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit

17. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

18. Operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit

19. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit

20. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit

21. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit

22. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

23. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

24. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit

25. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit

26. The permittee shall keep accurate records of VOC content of vapors, liquids stored and true vapor pressure of such liquids for a period of 5 years and shall make such records available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

27. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-405-2 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
MODIFICATION OF 85.0 MMBTU/HR NATURAL GAS -FIRED STEAM GENERATOR WITH NORTH AMERICAN 4231-85-GLE/X8701 GLE BURNER S/N SD857413-01 AND A FLUE GAS RECIRCULATION SYSTEM: AUTHORIZE COMBUSTION OF TEOR AND TVR GAS

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
4. Steam generator shall be equipped with variable frequency drive electrical motors driving the blower and water pump and a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr of maximum rated heat input (verified by manufacturer) or a manufacturer's overall thermal efficiency rating of 88%. [Public Resources Code 21000-21177: California Environmental Quality Act and District Rule 2410] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

S-1326-405-2 : Mar 31 2015 8:45AM -- RINALDIR : Joint Inspection Required with RINALDIR

6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit

7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit

8. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201, 4320 and 4801] Federally Enforceable Through Title V Permit

9. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

11. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 10 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

12. A source test to demonstrate compliance with NOx and CO emission limits shall be performed within 60 days of initial startup of this unit. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

13. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

14. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit

19. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

22. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

25. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

27. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-406-2 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
MODIFICATION OF 85.0 MMBTU/HR NATURAL GAS -FIRED STEAM GENERATOR WITH NORTH AMERICAN 4231-85-GLE/X8701 GLE BURNER AND A FLUE GAS RECIRCULATION SYSTEM: AUTHORIZE COMBUSTION OF TEOR AND TVR GAS

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
4. Steam generator shall be equipped with variable frequency drive electrical motors driving the blower and water pump and a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr of maximum rated heat input (verified by manufacturer) or a manufacturer's overall thermal efficiency rating of 88%. [Public Resources Code 21000-21177: California Environmental Quality Act and District Rule 2410] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services

Southern Regional Office • 34946 Flyover Court • Bakersfield, CA 93308 • (661) 392-5500 • Fax (661) 392-5585

6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit

7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit

8. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201 4801, and 4320] Federally Enforceable Through Title V Permit

9. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

11. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 10 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

12. A source test to demonstrate compliance with NOx and CO emission limits shall be performed within 60 days of initial startup of this unit. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

13. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

14. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit

19. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

22. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

25. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

27. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-407-2 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:
MODIFICATION OF 85.0 MMBTU/HR NATURAL GAS -FIRED STEAM GENERATOR WITH NORTH AMERICAN 4231-85-GLE/X8701 GLE BURNER S/N SD89244-04 AND A FLUE GAS RECIRCULATION SYSTEM: AUTHORIZE COMBUSTION OF TEOR AND TVR GAS

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
4. Steam generator shall be equipped with variable frequency drive electrical motors driving the blower and water pump and a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr of maximum rated heat input (verified by manufacturer) or a manufacturer's overall thermal efficiency rating of 88%. [Public Resources Code 21000-21177: California Environmental Quality Act and District Rule 2410] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services

Southern Regional Office • 34946 Flyover Court • Bakersfield, CA 93308 • (661) 392-5500 • Fax (661) 392-5585

6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit

7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit

8. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201 4801, and 4320] Federally Enforceable Through Title V Permit

9. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

11. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 10 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

12. A source test to demonstrate compliance with NOx and CO emission limits shall be performed within 60 days of initial startup of this unit. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

13. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

14. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit

19. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

22. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

25. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

27. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-417-2 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:
MODIFICATION OF 85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR WITH NORTH AMERICAN 4231-85 GLE BURNER AND A FLUE GAS RECIRCULATION SYSTEM: AUTHORIZE COMBUSTION OF TEOR AND TVR GAS

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
4. Steam generator shall be equipped with variable frequency drive electrical motors driving the blower and water pump and a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr of maximum rated heat input (verified by manufacturer) or a manufacturer's overall thermal efficiency rating of 88%. [Public Resources Code 21000-21177: California Environmental Quality Act and District Rule 2410] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services
S-1326-417-2 : Mar 31 2015 8:45AM -- RINALDIR : Joint Inspection Required with RINALDIR

7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit

8. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201 4801, and 4320] Federally Enforceable Through Title V Permit

9. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

11. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

12. A source test to demonstrate compliance with NOx and CO emission limits shall be performed within 60 days of initial startup of this unit. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

13. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

14. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit

19. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

22. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

25. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

27. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: S-1326-418-2 **ISSUANCE DATE:** 03/31/2015

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP
MAILING ADDRESS: 9600 MING AVENUE, SUITE 300
BAKERSFIELD, CA 93311

LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:
MODIFICATION OF 85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR WITH COEN QLN-II ULTRA LOW NOX BURNER AND A FLUE GAS RECIRCULATION SYSTEM: AUTHORIZE COMBUSTION OF TEOR AND TVR GAS

CONDITIONS

1. This Authority to Construct serves as a written certificate of conformity with the procedural requirements of 40 CFR 70.7 and 70.8 and with the compliance requirements of 40 CFR 70.6(c). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Prior to operating with modifications authorized by this Authority to Construct, the facility shall submit an application to modify the Title V permit with an administrative amendment in accordance with District Rule 2520 Section 5.3.4. [District Rule 2520, 5.3.4] Federally Enforceable Through Title V Permit
3. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
4. Steam generator shall be equipped with variable frequency drive electrical motors driving the blower and water pump and a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr of maximum rated heat input (verified by manufacturer) or a manufacturer's overall thermal efficiency rating of 88%. [Public Resources Code 21000-21177: California Environmental Quality Act and District Rule 2410] Federally Enforceable Through Title V Permit
5. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
6. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (661) 392-5500 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services
S-1326-418-2 : Mar 31 2015 8:45AM -- RINALDIR : Joint Inspection Required with RINALDIR

7. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit

8. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201 4801, and 4320] Federally Enforceable Through Title V Permit

9. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit

10. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

11. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

12. A source test to demonstrate compliance with NOx and CO emission limits shall be performed within 60 days of initial startup of this unit. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

13. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

14. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

16. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit

19. The following test methods shall be used: NOX (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit

20. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

21. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

22. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

23. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

24. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

25. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit

26. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit

27. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit

28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit